

webMethods Error Message Reference

Version 9.6

April 2014

This document applies to webMethods Product Suite Version 9.6.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 2013-2014 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors..

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA, Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://documentation.softwareag.com/legal/>.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <http://documentation.softwareag.com/legal/> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices and license terms, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". This document is part of the product documentation, located at <http://documentation.softwareag.com/legal/> and/or in the root installation directory of the licensed product(s).

Document ID: XSU-MESSAGES2-96-20140218

Table of Contents

1 ActiveTransfer Messages	1
2 Application Designer Messages	9
3 Broker Messages	11
4 Business Rules Messages	217
5 CentraSite Messages	257
6 CloudStreams Messages	503
7 Command Central Messages	585
8 Common Monitoring Provider Messages	613
9 Database Component Configurator Messages	635
10 Deployer Messages	637
11 Designer Common Plugin Pool Messages	723
12 Designer Service Development Messages	725
13 Event-Driven Architecture Tools Messages	727
14 Installer Messages	745
15 Integration Server Messages	749
16 Mediator Messages	1227
17 My webMethods Server Messages	1271
18 OSGi Messages	1415
19 Platform Manager Messages	1431
20 Process Engine Messages	1499
21 Realtime Monitoring Messages	1559
22 Security Messages	1685
23 System Management Hub Messages	1691
24 Tamino Messages	1711
25 Tamino Adapter Messages	2183
26 Tamino Tools Messages	2187
27 Trading Network Messages	2209
28 Universal Messaging Messages	2451
29 Web Services Stack Messages	2457
30 webMethods Events Messages	2487

1 ActiveTransfer Messages

- 1002 **An ActiveTransfer Server instance is already running. All the servers in the ActiveTransfer application have been started.**
- 1003 **Error while initializing ActiveTransfer database connection. The original error message was: {0}**
- 1004 **The ActiveTransfer application instance is not running.**
- 1005 **Active Transfer: License is invalid. Exception is - {0}**
- 1007 **Property 'mft.gatewayServer.port' is not provided, defaulting it to 8500.**
- 2001 **Invalid or unsupported RDBMS vendor: {0}.**
- 2002 **The database connection pool associated with ActiveTransfer should allow at least 2 connections. Your ActiveTransfer pool is currently configured with a maximum of {0} connections. Aborting TN startup. Please increase your ActiveTransfer database pool maximum and restart the server.**

- 2003 There was an error while reading the dbops.sql file. The original error message was: {0}
- 2004 There was an error while reading the dblimits.cnf file. The original error message was: {0}
- 2005 A connection was returned to the connection pool with autoCommit = false. This may indicate some changes to the database were not committed properly. The changes will be rolled back. Stack trace {0}
- 2006 ActiveTransfer database pool is not configured. Please configure a database pool for functional alias "ActiveTransfer".
- 2007 There was an error while connecting to ActiveTransfer connection pool. The original error message was: {0}
- 2008 ActiveTransfer database pool is not configured properly. Make sure that a valid database pool is assigned for functional alias "ActiveTransfer".
- 2009 Error while reading the database configuration. The exception message is : {0}
- 2011 ActiveTransfer could not retrieve data from your database. Go to the JDBC Pools page in the Integration Server Administrator and make sure your database URL, user name, and password are set correctly. Also make sure you created the ActiveTransfer database tables as described in the Product Installation Guide.
- 3001 A scheduled action with this name already exists.
- 3004 Unable to save scheduled archive service "{0}".
- 3009 Interval is required.

3010	Interval is not a valid integer.
3011	Interval must be greater than zero.
3012	The scheduled {0} is invalid. Format must be YYYY/MM/DD.
3013	The scheduled {0} is invalid. Format must be hh:mm:ss.
3020	The scheduled delivery date/time is in the past.
3021	If an end time is supplied, an end date must also be supplied.
3022	End date/time is in the past.
3023	End date/time is before start date/time.
3024	Could not construct a valid timestamp from this schedule. Dates must be in YYYY/MM/DD format and times must be in hh:mm:ss format.
3025	Delivery schedule dates must be in the format "YYYY/MM/DD" and times must be in the format "hh:mm:ss".
3031	A post process event with this name already exists.
3032E	The action name "{0}" repeats for multiple actions in this event. Retry with unique action names.
Explanation	Each action defined in an ActiveTransfer event must have a unique name.
Action	Specify a unique name for each action in an ActiveTransfer event.

3033	The action name cannot be null.
3034E	Scheduled event "{0}" does not exist. Retry with an existing scheduled event.
Explanation	The scheduleName parameter provided for the wm.mft.schedule:executeEvent service is not a valid scheduled event in ActiveTransfer.
Action	Ensure that the scheduled event name specified by the scheduleName parameter is defined in ActiveTransfer.
4003E	Update of asset failed.
Explanation	ActiveTransfer Server could not update the asset.
Action	Check the ActiveTransfer error logs for details.
4005E	Insertion of asset failed.
Explanation	ActiveTransfer could not insert the asset on the target server.
Action	Check the ActiveTransfer error logs for details.
4006E	The export file name cannot be null.
Explanation	The exportData service could not execute because no export file was specified.
Action	In the exportFileName parameter, specify the path and name of the XML file in which to save the exported assets.
4007E	The import file name cannot be null.
Explanation	The importData service could not execute because no import file was specified.
Action	In the importDataFileName parameter, specify the path and name of the XML file containing the assets to import.
4008E	The import file {0} does not exist.
Explanation	The specified file containing the assets to import does not exist.
Action	In the importDataFileName parameter, specify a valid path and name of the XML file containing the assets to import.

4009E	The import file {0} cannot be read.
Explanation	ActiveTransfer Server could not read the specified import file.
Action	In the importDataFileName parameter, specify a file name that ActiveTransfer Server can access.
4010E	Specify values for input parameter importData or set input parameter all to true.
Explanation	The "all" input parameter for the importData service is set to "false," but no assets are specified to import.
Action	Either set the "all" input parameter to "true" or specify the assets to import in the "importData" parameter.
4011E	The value of input parameter assetType of importData[{0}] is null. Specify a value for the asset type.
Explanation	ActiveTransfer Server could not import the asset for the indicated importData document because no asset type was specified.
Action	Specify a value in the assetType variable for each asset type you want to import.
4012E	No assets to import.
Explanation	The export file is blank or the assets selected for import are not in the export file.
4013E	The version information in the import file cannot be null.
Explanation	The version information in the import file is null. ActiveTransfer supports import of assets into ActiveTransfer 9.5 or later. The server could not find version information in the file the importData service is attempting to import.
4014E	Only the data exported from version {0} can be imported.
Explanation	ActiveTransfer supports the export of assets from version 9.5 or later. This export file was created from an earlier version of ActiveTransfer
4015E	A reference is not available on the target server. Reference details- type:{0}, name:{1}, and ID:{2}.
Explanation	A reference to a server instance is not available on the target server.

- 4016 **assetType element not found in XML.**

- 7001 **A server with the same protocol and 'host + port' combination already exists.**

- 7002 **A server tunnel with the same name already exists.**

- 7003 **Error while updating the server. Check the logs.**

- 7004 **A proxy instance with the same host and port combination already exists.**

- 7005 **A proxy instance with the same name already exists.**

- 8001 **An invalid template has been specified for the user. Template ID:{0}**

- 8002 **A user template with the same name already exists.**

- 8003 **A user with the specified id does not exist. User ID:{0}**

- 8004 **The user does not have an associated template. User ID:{0}**

- 8005 **The user "{0}" already exists.**

- 8006 **No default user template is defined in ActiveTransfer. Please create a default user template before creating a user.**

- 8007 **Default template cannot be deleted.**

- 8101 **A Virtual Folder with the same name already exists.**

8102 **A Virtual Folder with the ID does not exist.**

9999 **An internal error has occurred while executing the service. Contact your System Administrator.**

2 Application Designer Messages

INMBAE0001	Login failed. The reason could be an incorrect username and/or password, or a database access error.
Explanation	The system could not log you on. An error occurred during authentication.
Action	Specify correct user name (possibly including domain name) and password. Note that letters in passwords must be typed using the correct case. You may also want to check whether the CentraSite server is started.
INMBAE0002	Please enter an appropriate value.
Explanation	Please enter an appropriate value.
Action	Please enter an appropriate value.
INMBAE0003	Cannot uninstall plug-in with id {0}, is required e.g. by plug-in with id {1}.
Explanation	The plug-in you wish to uninstall cannot be uninstalled because another plug-in depends on it.
Action	Check whether to uninstall the dependent plug-in as well.
INMBAE0005	Failed to delete {0}.
Explanation	The given file or directory could not be deleted.
Action	Check whether in use by another program.

INMBAE0006	Unable to load JAAS Configuration. The jaas.config file may have syntax errors.
Explanation	JAAS Configuration seems to be invalid and hence cannot be loaded. The jaas.config file may have syntax errors
Action	Ensure the syntax correctness of jaas.config file. Fix any additional issues as pointed out in the error message
INMBAE0009	Subject does not supply credentials. The subject instance is {0}.
Explanation	Authenticated subject does not have credentials after authentication.
Action	This is most probably due to a CentraSite security misconfiguration.
INMBAE0010	Connection handler {0} failed to establish connection.
Explanation	Connection handler {0} failed to establish connection.
Action	Check logs.
INMBAE0011	Plug-in {0} has been disabled.
Explanation	Plug-in {0} has been disabled.
Action	Check logs for reason.
INMBAE0012	Database access error. Can't connect to server CentraSite.
Explanation	CentraSite Server is not running.
Action	Start CentraSite Server.
INMBAW0004	Forced uninstall of plug-in with id {0} will cause disabling of dependent plug-in with id {1}.
Explanation	When the plug-in is uninstalled, the dependent plug-in will no longer be usable.
Action	The dependent plug-in will be re-enabled when the required plug-in is available again.

3 Broker Messages

BAC.11.1096E	Unable to connect to Broker Server: {0}. Reason:{1}
Explanation	The reason for the Broker Server connection failure is specified in the error message.
Action	Check the detailed error message and take appropriate action.
BAC.11.1097E	Error: Cannot get the version number of Broker Server "{0}".
Explanation	Unable to get the version of the specified Broker Server.
Action	Check the detailed error message and take appropriate action.
BRC.001.1002S	Could not start Windows sockets: %1
Explanation	The Broker Server failed to start Windows sockets.
Action	Examine the system error messages to determine the problem.
BRC.001.1003S	Wrong version of Windows sockets.
Explanation	The Windows sockets version used is incorrect.
Action	Make sure that the correct version of Windows sockets is used.
BRC.001.1004E	Could not get local host name: %1 -- Check the network configuration.
Explanation	The Broker Server failed to obtain the current host's name.
Action	Check the network configuration.

- BRC.001.1005** **Cannot open guaranteed data store: %1 [EXITING]**
- BRC.001.1006** **Cannot open persistent data store: %1 [EXITING]**
- BRC.001.1007** **Cannot allocate guaranteed storage: %1 [EXITING]**
- BRC.001.1008S** **Data store version is wrong. [EXITING]**
Explanation The Broker Server version and the data store version are incompatible.
Action Make sure that the Broker Server version is appropriate for the current data files.
- BRC.001.1009** **Restarted adapter process %1 %2 times, giving up**
- BRC.001.1010** **Starting adapter process %1 - cannot create pipe: %2**
- BRC.001.1011** **Starting adapter process %1 - cannot open pipe: %2**
- BRC.001.1012** **Starting adapter process %1 - cannot create IO port: %2**
- BRC.001.1013** **Starting adapter process %1 - cannot find executable %1: %2**
- BRC.001.1014** **Starting adapter process %1 - %2 is not executable**
- BRC.001.1015** **Starting adapter process %1 - cannot find directory %2: %3**
- BRC.001.1016** **Starting adapter process %1 - %2 is not a directory**
- BRC.001.1017** **Starting adapter process %1 - cannot create process: %2**

BRC.001.1018	Starting adapter process %1 %2 - cannot create socket: %3
BRC.001.1019	Starting adapter process %1 %2 - host not found
BRC.001.1020	Starting adapter process %1 %2 - cannot connect: %3
BRC.001.1021	Cannot accept connections: %1
BRC.001.1022	Cannot create main socket for network connections: %1 -- [EXITING]
BRC.001.1023	Cannot bind main socket to port %1: %2 -- Another Broker Server/Monitor may be running already. -- [EXITING]
BRC.001.1024	Cannot create thread: %1 -- [EXITING]
BRC.001.1026	Broker Server Monitor exiting, Process ID %1
BRC.001.1027	Cannot open config file %1: %2 -- The Broker Server Monitor must be started in the main install directory.
BRC.001.1028	Incomplete config file %1
BRC.001.1029	Restarted Broker Server in directory %1 %2 times, giving up
BRC.001.1030	Broker Server Monitor starting Broker Server in directory %1 - cannot create process: %2
BRC.001.1031	Stopping Broker Server %1 Process ID %2 - cannot terminate process: %3

- BRC.001.1032** **Stopping Broker Server %1 Process ID %2 - cannot get exit code: %3**

- BRC.001.1033** **Unexpected stop of Broker Server in directory %1 Process ID %2 - exit code %3**

- BRC.001.1034** **Unexpected stop of Broker Server in directory %1 Process ID %2 - Signal %3 %4**

- BRC.001.1035** **Broker Server %1 Process ID %2 - Suspended on signal %3**

- BRC.001.1036** **Broker Server %1 Process ID %2 - Continued**

- BRC.001.1037** **Wait on synchronization object failed: %1**

- BRC.001.1038** **Broker Server Monitor starting Broker Server executable %1 in directory %2**

- BRC.001.1039** **Stopping Broker Server executable %1 in directory %2 Process ID %3**

- BRC.001.1040** **Cannot get address for local host %1: %2**

- BRC.001.1041** **Cannot create socket for SNMP: %1 -- SNMP traps will not be sent.**

- BRC.001.1042** **Cannot bind SNMP socket to port: %1 -- SNMP traps will not be sent.**

- BRC.001.1043** **Starting Broker Server in directory %1 - could not find executable %2: %3**

- BRC.001.1044** **Starting Broker Server in directory %1 - cannot create pipe: %2**

- BRC.001.1045** **Starting Broker Server in directory %1 - %2 is not executable**

BRC.001.1046	Starting Broker Server - cannot find directory: %1
BRC.001.1047	Starting Broker Server - %1 is not a directory
BRC.001.1048	Parsing filter '%1' - %2
BRC.001.1049I	Broker cannot get IP address for itself (%1): %2
Explanation	Informational message listing the Broker Servers found on the local host while checking for a port conflict.
Action	None.
BRC.001.1050	Multiple attempts to open data store.
BRC.001.1051	Insufficient memory resources for operation. -- [EXITING]
BRC.001.1052	Cannot open data store %1: %2
BRC.001.1053	Cannot open data store %1: File is too short.
BRC.001.1054	Cannot open data store %1: File type is wrong.
BRC.001.1055	Cannot open data store %1: Map address mismatch -- %2, %3
BRC.001.1056	Cannot open data store %1: File too big (file size %2, available %3)
BRC.001.1057	Cannot open data store %1: mprotect failed - %2
BRC.001.1058	Cannot initialize data store %1: %2

- BRC.001.1059** **Cannot read data store header %1: %2**

- BRC.001.1060** **Cannot open data store %1: map failed - %2**

- BRC.001.1061** **Cannot open transaction log %1: %2**

- BRC.001.1062** **Cannot open transaction log %1: File is too short**

- BRC.001.1063** **Cannot open transaction log %1: File is wrong type**

- BRC.001.1064** **Cannot open transaction log %1: Wrong page size -- %2, %3**

- BRC.001.1065** **Cannot create transaction log %1: %2**

- BRC.001.1066** **Cannot initialize transaction log %1: %2**

- BRC.001.1067** **Cannot create data store %1: %2**

- BRC.001.1068** **End transaction without matching begin. -- [CRASHING]**

- BRC.001.1070** **Lost transaction identity. -- [CRASHING]**

- BRC.001.1071** **Cannot write transaction log index: %1 -- [CRASHING]**

- BRC.001.1072** **Cannot write transaction log header: %1 -- [CRASHING]**

- BRC.001.1073** **Cannot commit transaction: %1 -- [CRASHING]**

BRC.001.1074	Cannot read transaction page: %1 -- [CRASHING]
BRC.001.1075	Cannot write transaction page to data file: %1 -- [CRASHING]
BRC.001.1076	Cannot write transaction page: %1 -- [CRASHING]
BRC.001.1077	No more space in data store %1
BRC.001.1078	Cannot increase size of data store %1: %2
BRC.001.1079	Cannot increase size of data store %1: mprotect failed - %2
BRC.001.1080	Caught access beyond data store %1 -- %2 -- [CRASHING]
BRC.001.1081	Cannot access data directory: %1 -- [EXITING]
BRC.001.1082	Low disk space for data store -- %1K bytes free, %2K bytes total
BRC.001.1083	CRITICALLY LOW DISK SPACE for data store -- %1K bytes free, %2K bytes total
BRC.001.1084	Resolved low disk space condition for data store -- %1K bytes free, %2K bytes total
BRC.001.1087	Cannot start service dispatcher: %1
BRC.001.1088	Object system error: %1
BRC.001.1089	Cannot register service %1: %2

BRC.001.1090	Cannot access registry key %1: %2
BRC.001.1091	Cannot access directory %1: %2
BRC.001.1092	Cannot set environment variable %1: %2
BRC.001.1093	Cannot set service status: %1
BRC.001.1094	Attempted to start Broker Server before starting Broker Server Monitor.
BRC.001.1095	Attempted to stop Broker Server before starting Broker Server Monitor.
BRC.001.1096	Cannot open service control manager: %1
BRC.001.1097	Cannot create service %1: %2
BRC.001.1098	Cannot open service %1: %2
BRC.001.1099	Cannot delete service %1: %2
BRC.001.1100	Cannot start service %1: %2
BRC.001.1101	Cannot stop service %1: %2
BRC.001.1102	The webMethods Broker license file is missing. webMethods Broker will not run without a license file. -- [EXITING]
BRC.001.1103	The license file %1 is invalid. webMethods Broker will not run without a valid license file. Internal error message: %2 -- [EXITING]

BRC.001.1104	The license has expired for webMethods Broker. The Broker will not accept any documents until the license is renewed.
BRC.001.1105	Broker Server or Broker Monitor initialization failed, network manager did not start -- [EXITING]
BRC.001.1106	Broker Server or Broker Monitor initialization failed, network listener did not start -- [EXITING]
BRC.001.1107	Internal error -- %1
BRC.001.1108	Broker initialization failed, cannot create IO port -- %1 [EXITING]
BRC.001.1109	Client connection failed, cannot use IO port -- %1 [EXITING]
BRC.001.1110	Persistent data file %1 is missing, resetting Brokers and client queues.
BRC.001.1111	Found persistent storage file, but no guaranteed storage file. Expected to find file %1 [EXITING]
BRC.001.1112	Reached operating system connection limit. No more connections can be made to the Broker Server until existing connections are closed.
BRC.001.1113	Network I/O operation %1 failed -- %2
BRC.001.1114	Wrong password for SSL key file "%1". SSL disabled.
BRC.001.1115	Could not find SSL keystore file "%1". SSL disabled.
BRC.001.1116	Error in SSL key file "%1", error code %2. SSL disabled.

- BRC.001.1117** **Error in SSL library %1. Could not find symbols %2 -- SSL disabled.**
- BRC.001.1118** **Could not create SSL socket, unknown error code %1 (%2). SSL disabled.**
- BRC.001.1119** **Could not accept SSL connection, error code %1 (%2)**
- BRC.001.1120** **Could not accept SSL connection, bad handshake from %1: %2**
- BRC.001.1121S** **Fatal error, SSL disabled: %1 %2**
Explanation The Broker Server encountered an internal error.
Action Contact Software AG Global Support.
- BRC.001.1122** **Could not find DN <%1> in key file "%2". SSL disabled.**
- BRC.001.1123** **SSL connection using expired certificate DN = <%1> begin-date = "%2" end-date = "%3"**
- BRC.001.1124** **Broker SSL certificate has expired. Clients using SSL may refuse to connect to Broker until the certificate is renewed. DN = <%1> begin-date = "%2" end-date = "%3"**
- BRC.001.1125** **No certificate for DN <%1> in key file "%2". SSL disabled.**
- BRC.001.1126** **Incomplete configuration, the webMethods Enterprise Broker cannot be started. This is usually caused by an error during installation.**
- BRC.001.1127E** **Broker Server in directory %1 failed on first start, giving up**
Explanation The Broker Server failed to start up.
Action Examine the Broker Server log file to determine the problem.

BRC.001.1128	Out of memory while sending data to IP network address %1, connection has been broken
BRC.001.1129	Persistent data file %1 is corrupted, attempting recovery.
BRC.001.1130	Persistent data file %1 is corrupted (quickcheck), attempting recovery.
BRC.001.1131	Persistent data file %1 is corrupted (slowcheck), attempting recovery.
BRC.001.1132	Persistent data file %1 is out of date, attempting recovery.
BRC.001.1133	Persistent data file %1 is out of date, performing a partial reset of Brokers and client queues.
BRC.001.1134	The persistent data file %1 is corrupted and has been removed. All statistics have been reset and all persistent documents have been lost.
BRC.001.1135	The statistics for Broker "%1" have been reset.
BRC.001.1136	The incoming queue for Broker "%1" has been reset, all unprocessed persistent documents have been lost.
BRC.001.1137	The statistics for document type "%2" on Broker "%1" have been reset.
BRC.001.1138	The statistics for client group "%2" on Broker "%1" have been reset.
BRC.001.1139	The statistics for client "%2" on Broker "%1" have been reset.
BRC.001.1140	The queue for client "%2" on Broker "%1" has been reset, all unfetched persistent documents have been lost.

- BRC.001.1141** **Could not determine Fully Qualify Name for computer, using "%1". Some clients or Brokers may not be able to contact this Broker.**
- BRC.001.1142** **Close to maximum storage limit on data store %1 -- %2K bytes available, %3K bytes maximum**
- BRC.001.1143** **Maximum storage limit reached for data store %1 -- %2K bytes available, %3K bytes maximum**
- BRC.001.1144** **Resolved low storage space for data store %1 -- %2K bytes available, %3K bytes maximum**
- BRC.001.1145** **The statistics for remote Broker "%1" on Broker "%2" have been reset.**
- BRC.001.1146** **The forward queue for remote Broker "%1" on Broker "%2" has been reset, all unprocessed persistent documents have been lost.**
- BRC.001.1147W** **Warning: could not write to the Broker Server configuration file.**
Explanation The Broker Server could not write to its configuration file.
Action On the Broker Server, make sure that the configuration file exists, is not corrupt, and is writable.
- BRC.001.1148** **Could not read the Broker Server configuration file %1 from directory %2: %3 [EXITING]**
- BRC.001.1149** **Incomplete Broker Server configuration file %1 from directory %2 [EXITING]**
- BRC.001.1150** **Could not read new Broker Server configuration file in directory %1: %2**
- BRC.001.1151** **Could not read Broker Server configuration file in directory %1: %2**

BRC.001.1152	Could not query Broker Server as service "%1": %2
BRC.001.1153I	Broker Server Monitor found new Broker Server with data directory in "%1"
Explanation	The Broker Server Monitor found a new Broker Server with the specified data directory.
Action	None.
BRC.001.1154I	Broker Server Monitor found Broker Server with data directory in "%1", already known.
Explanation	A Broker Server with the specified data directory is already present in the known Broker Servers list.
Action	None.
BRC.001.1155I	Broker Server Monitor reading configuration from file "%1"
Explanation	The Broker Server Monitor is reading the configuration from the specified file.
Action	None.
BRC.001.1156	Broker "%1": Received an error label reply from access label adapter process "%2": Error: "%3" Detail: "%4" Client DN: "%5" Client Issuer DN: "%6"
BRC.001.1157	Broker "%1": Received a label reply for an unknown client from access label adapter process "%2": Client DN: "%3" Client Issuer DN: "%4"
BRC.001.1158	Broker "%1": Error: Could not find access label adapter process client. Access label lookup not available.
BRC.001.1159	Broker "%1": Received reply containing an illegal label from access label adapter process "%2"
BRC.001.1160	Broker "%1": Error: Could not allocate memory to send lookup to access label adapter process. Access label lookup not available.

- BRC.001.1161** **Broker "%1": Error: Could not prepare lookup document to send to access label adapter process. Access label lookup not available.**
- BRC.001.1162** **Error: Could not create SSL socket: SSL not initialized. SSL disabled.**
- BRC.001.1163** **Error: Could not create SSL socket for port %1: could not open socket (%2). SSL disabled.**
- BRC.001.1164** **Error: Could not create SSL socket for port %1: no memory. SSL disabled.**
- BRC.001.1165** **Error: Could not create SSL socket: bind to port %1 failed (%2). SSL disabled.**
- BRC.001.1166** **Error: Could not create SSL socket: listen on port %1 failed (%2). SSL disabled.**
- BRC.001.1167** **Warning: Could not resolve specified Broker hostname "%1" to an IP address. Connections from remote Brokers may fail.**
- BRC.001.1168** **SSL key file "%1" seems to be corrupted. SSL disabled.**
- BRC.001.1169I** **Error: Cannot setuid to "%1" (uid %2): %3.**
Explanation Informational message listing the Broker Servers found on the local host while checking for a port conflict.
Action None.
- BRC.001.1170** **Error: Cannot lookup user "%1" or group "%2".**
- BRC.001.1171** **Error: Cannot make secure Broker connections: SSL is disabled or not configured.**
- BRC.001.1172** **Broker "%1": Cannot connect to Broker Server "%2", error in resolving hostname to IP address: %3.**

BRC.001.1173	Broker "%1": Cannot connect to Broker Server "%2": %3.
BRC.001.1174	Broker "%1": Connection to "%2"@%3 was rejected by the remote Broker. Reason: The remote Broker is not licensed for territories.
BRC.001.1175	Broker "%1": Connection to "%2"@%3 was rejected by the remote Broker. Reason: The remote Broker Server is incompatible with this Broker Server.
BRC.001.1176	Broker "%1": Connection to "%2"@%3 was rejected by the remote Broker. Reason: The remote broker does not have a territory set.
BRC.001.1177	Broker "%1": Connection to "%2"@%3 was rejected by the remote Broker. Reason: The remote broker is not part of territory "%4".
BRC.001.1178	Broker "%1": Connection to "%2"@%3 was rejected by the remote Broker. Reason: Permission denied.
BRC.001.1179	Broker "%1": Connection to "%2"@%3 was rejected by the remote Broker. Reason: A gateway to territory "%4" already exists on the remote Broker.
BRC.001.1180	Broker "%1": Connection to "%2"@%3 was rejected by the remote Broker. Reason: An internal error occurred (error code %4).
BRC.001.1181	Broker "%1": Cannot connect to "%2"@%3: Received a malformed reply from remote Broker.
BRC.001.1182	Broker "%1": Incorrect Broker connection made to "%2"@%3: configurations are not consistent.
BRC.001.1183	Broker "%1": Cannot connect to "%2"@%3: The logical clock is not consistent with the local copy.

- BRC.001.1184** **Broker "%1": Initial synchronization failed for Broker connection to "%2"@"%3.**

- BRC.001.1185** **Broker "%1": A Broker connection from "%2"@"%3 was denied access.**

- BRC.001.1186** **Broker "%1": A gateway connection from "%2"@"%3 was denied access.**

- BRC.001.1187** **Broker "%1": A Broker connection to "%2"@"%3 was successfully established.**

- BRC.001.1188** **Cannot lock data file "%1": %2**

- BRC.001.1189** **The persistent data file "%1" is corrupted beyond repair and automatic recovery is disabled. [EXITING]**

- BRC.001.1190** **Error: Cannot open the internal log file "%1": %2 Internal logging is disabled.**

- BRC.001.1191** **Thread creation failed: %1**

- BRC.001.1192** **Multiple servers (%1) not supported on this platform. Only starting the first configured server.**

- BRC.001.1193** **Maximum transaction size exceeded. [EXITING]**

- BRC.001.1194** **Could not accept SSL connection, handshake from %1: %2 timed out after %3 ms.**

- BRC.001.1195** **System defined. Deliver to client '/' to determine if the Broker is active.**

- BRC.001.1196** **System defined. Used by clients to acknowledge completion of a request.**

- BRC.001.1197** **System defined. Used by adapter processes to report information on themselves.**

BRC.001.1198	System defined. Used by clients to announce the start of a transaction.
BRC.001.1199	System defined. Used by clients to announce the end of a transaction.
BRC.001.1200	System defined. Used by clients to report an error processing a request
BRC.001.1201	System defined. Used by clients to report an error.
BRC.001.1202	System defined. Used by tools to discover which adapter processes are running.
BRC.001.1203	System defined. Used by tools to inform version 2.x adapter processes of changes to document types and client groups.
BRC.001.1204	System defined. Published by the Broker when a document is dropped.
BRC.001.1205	System defined. Published by the Broker when a document is queued for a client.
BRC.001.1206	System defined. Published by the Broker when a document is queued for a remote Broker.
BRC.001.1207	System defined. Published by the Broker when a document is published by a client.
BRC.001.1208	System defined. Published by the Broker when a document is received from a remote Broker.
BRC.001.1209	System defined. Published by the Broker when a document is received by a client.
BRC.001.1210	System defined. Published by the Broker when a document is received by a remote Broker.

- BRC.001.1211** **System defined. Published by the Broker when the state of a client changes.**
- BRC.001.1212** **System defined. Published by the Broker when a client group changes.**
- BRC.001.1213** **System defined. Published by the Broker when a document type changes.**
- BRC.001.1214** **System defined. Published by the Broker when the Broker's territory changes.**
- BRC.001.1215** **System defined. Delivered by the ALA when an error occurred during Access Label lookup.**
- BRC.001.1216** **System defined. Delivered by the ALA when an Access Label is returned.**
- BRC.001.1217** **System defined. Delivered by the Broker to the ALA when an Access Label is looked up.**
- BRC.001.1218** **System defined. Delivered by the ALA when the Access Label for a client changes.**
- BRC.001.1222** **Check sum failed replaying the Guaranteed storage log. Broker server cannot continue. [CRASHING]**
- BRC.001.1223S** **Check sum failed processing a document (%1). Broker Server cannot continue. [CRASHING]**
- Explanation** The Broker Server encountered a fatal error. The storage file is corrupt.
- Action** Contact Software AG Global Support.
- BRC.001.1224** **System defined. Published by the Broker when a document is dropped by a remote Broker.**
- BRC.001.1225** **System defined. Published by the Broker when a document is inserted administratively into a target client queue.**

BRC.001.1226	System defined. Published by the Broker when a document is deleted administratively from a target client queue.
BRC.001.1227	System defined. Published by the Broker when a document is peeked administratively from a target client queue.
BRC.001.1228S	Error: The Server has no sessions configured. [EXITING]
Explanation	The Broker Server has no sessions configured.
Action	On the Broker Server, examine the configuration file to make sure that a valid session is specified.
BRC.001.1229	Error: The Server cannot initialize config session with URL "%1". Error code %2. [EXITING]
BRC.001.1230	Error: The Server cannot initialize data session with URL "%1". Error code %2. [EXITING]
BRC.001.1231	Error: The Server cannot access its configuration from the config session: %1 [EXITING]
BRC.001.1232	Error: The Server cannot access its configuration from the data session: %1 [EXITING]
BRC.001.1233	Error: The Server cannot read its configuration from the config session: %1 [EXITING]
BRC.001.1234S	Error: The Server cannot store its initial configuration to the config session: %1 [EXITING]
Explanation	The Broker Server could not update its initial configuration.
Action	On the Broker Server, examine the configuration files to make sure they exist and are not corrupt.

- BRC.001.1235** **Warning: Broker "%1": Event dropped from forward queue to remote Broker "%2" because it was larger than the receiving Broker's limit (%3 bytes).**
- BRC.001.1236** **Broker Server in directory %1 Process ID %2 exited with exit code %3.**
- BRC.001.1237** **Usage: %1 { start | stop }**
- BRC.001.1238** **Start webMethods Enterprise Broker subsystem.**
- BRC.001.1239** **Stop webMethods Enterprise Broker subsystem.**
- BRC.001.1240W** **Warning: The locale "%1" is not supported on this platform for filter collation. Reverting to "C" locale.**
- Explanation** An unsupported locale was specified as the filter collation locale.
- Action** Make sure that a supported locale is specified.
- BRC.001.1241** **Broker ran out of memory. Failing memory allocation request of %1 bytes.**
- BRC.001.1242** **Warning: Broker "%1": The Transaction Manager rolled back the server, error %2 occurred. [RESTARTING]**
- BRC.001.1243** **Error: Could not create configuration storage for Broker "%1", error %2 occurred.**
- BRC.001.1244** **Error: Could not retrieve configuration storage for Broker "%1", error %2 occurred. [RESTARTING]**
- BRC.001.1245** **Error: Could not create queuing storage for Broker "%1", error %2 occurred.**
- BRC.001.1246** **Error: Could not retrieve queuing storage for Broker "%1", error %2 occurred. [RESTARTING]**

BRC.001.1247W	Warning: Queuing storage for Broker "%1" missing, attempting to recreate all client queues and queues to other Brokers.
Explanation	The Broker run-time storage files "BrokerData.qs.*" (for example, BrokerData.qs.log and BrokerData.qs.stor) have been removed or are not found when recreating client queues and forward queues.
Action	Broker automatically recreates these files during startup. No action is required.
BRC.001.1248	Error: Could not recover queuing storage for Broker "%1", error %2 occurred. [RESTARTING]
BRC.001.1249I	Recreated queuing storage for Broker "%1" successfully.
Explanation	The Broker run-time storage files "BrokerData.qs.*" (for example, BrokerData.qs.log and BrokerData.qs.stor) have been removed or are not found when recreating client queues and forward queues. Broker successfully recreated the storage required files.
Action	No action required.
BRC.001.1250	Error: Broker "%1": Could not create configuration storage for Client Group "%2", error %3 occurred.
BRC.001.1251	Error: Broker "%1": Could not create configuration storage for Event Type "%2", error %3 occurred.
BRC.001.1252	Error: Broker "%1": Could not create configuration storage for Client "%2", error %3 occurred.
BRC.001.1253	Error: Broker "%1": Could not create queuing storage for Client "%2", error %3 occurred.
BRC.001.1254	Error: Broker "%1": Could not create configuration storage for remote Broker "%2", error %3 occurred.
BRC.001.1255	Error: Broker "%1": Could not create queuing storage for remote Broker "%2", error %3 occurred.

- BRC.001.1256** **Warning: Broker "%1": Client Group "%2" purged non-existent eventtype index %3 from the %4 list.**
- BRC.001.1257** **Warning: Broker "%1": Event Type "%2" subscription SRR refcount fixed (from %3 to %4).**
- BRC.001.1258** **Warning: Broker "%1": Event Type "%2" subscription refcount check finds error "%3".**
- BRC.001.1259** **Warning: Broker "%1": Remote Broker "%2" times out on getting events (%3 secs), disconnecting now, retry pending.**
- BRC.001.1260** **Broker Server configured with version "%1", but executable is version "%2".**
- BRC.001.1261** **Warning: Meta-data update activity has cancelled the currently running backup. Backup was started from session %1 at %2.**
- BRC.001.1262** **System defined. Published by the Broker when a document is modified administratively on a target client queue.**
- BRC.001.1263** **System defined. Published by the Broker when a client subscription changes.**
- BRC.001.1264** **System defined. Published by the Broker when a remote Broker subscription changes.**
- BRC.001.1265** **Error: Broker Monitor cannot open the internal log file "%1": %2 Internal logging is disabled.**
- BRC.001.1266** **Error: Broker "%1": Out of storage occurred while processing update from Remote Broker "%2". [RESTARTING]**

BRC.001.1267	Error: Broker "%1": Out of memory occurred while processing update from Remote Broker "%2". [RESTARTING]
BRC.001.1268W	Warning: Disconnecting connection ID %1 for client at ipaddress:port %2 having connection FD %3 because the client is not responding to the keep alive requests. Client details: %4
Explanation	Broker is disconnecting a client session because the expected response was not received for a keep-alive request. This is probably because the client is disconnected or there are network issues.
Action	Make sure that the network is stable and the client is not disconnected. Otherwise, consider using "auto-reconnect" option to reconnect automatically.
BRC.001.1269E	Broker ran out of memory. Broker will exit.
Explanation	Broker ran out of memory. Most likely the Broker has reached the operating system's imposed per-process memory usage limit and cannot successfully allocate memory.
Action	Add more memory to the box and increase the per-process memory usage limit to a higher number.
BRC.001.1270	Broker "%1": Invalid or corrupt event received from remote Broker "%2" from "%3").
BRC.001.1271	Invalid value for max-memory: %1. The value is ignored.
BRC.001.1272	Warning: The server is running low in memory %1M bytes used, %2M bytes max
BRC.001.1273	WARNING: The server is CRITICALLY LOW in memory %1M bytes used, %2M bytes max
BRC.001.1274	Memory usage is back to normal level %1M bytes used, %2M bytes max
BRC.001.1275	Warning: Suspending event forwarding from Broker %1 to %2 because there is not enough memory to process events

- BRC.001.1276** **Warning: Broker "%1": Refusing a forwarded creation of "%4" from "%2"@"%3. If applicable, "%4" must be created manually.**
- BRC.001.1277** **Warning: Broker "%1": Refusing a forwarded update of "%4" from "%2"@"%3. This may cause event flow from "%2"@"%3 to stop. The differences in "%4" must be resolved manually.**
- BRC.001.1278** **Warning: Broker "%1": Refusing a forwarded deletion of "%4" from "%2"@"%3. If applicable, "%4" must be deleted manually.**
- BRC.001.1279** **Warning: Broker "%1": Event flow from "%2"@"%3 is stopping completely! An event of type "%4" was received from "%2"@"%3, but "%4" is out of sync due to "%1" refusing updates from "%2"@"%3. Differences in "%4" must be resolved manually before event flow can be resumed!**
- BRC.001.1280** **Broker "%1": Event flow from "%2"@"%3 is being resumed (it was stopped earlier due to "%4" not being synchronized).**
- BRC.001.1281** **Broker Server Monitor listening on %1**
- BRC.001.1282** **Failed to stop Broker Server on "%1". Server is unresponsive. Terminating server process %2.**
- BRC.001.1283** **The Broker Server was configured for SSL using the prior SSL configuration data. Due to changes in the way SSL is configured, the Broker Server will be started without SSL enabled and the old configuration data is removed from the Broker Server storage files. The prior configuration was: Certificate filename: %1 DN: %2 Issuer DN: %3**
- BRC.001.1284** **SSL is not enabled. The Broker Server is unable to initialize the pseudo-random number generator. Make sure that the operating system has been properly configured.**

BRC.001.1287	Failed to create audit log file. Audit logging will be disabled.
BRC.001.1288	Failed to open audit log file. Audit logging will be disabled.
BRC.001.1289	Failed to create audit log directory. Audit logging will be disabled.
BRC.001.1290	Failed to write audit record. Audit logging will be disabled.
BRC.001.1291	SSL is not enabled. The Broker Server is unable to initialize OpenSSL.
BRC.001.1292	Could not access SSL keystore file "%1": access denied. SSL disabled.
BRC.001.1293	Could not access SSL keystore file "%1": operating system error. SSL disabled.
BRC.001.1294	The SSL keystore file "%1" is not a regular file. SSL disabled.
BRC.001.1295	Unable to open the SSL keystore file "%1". SSL disabled.
BRC.001.1296	Unable to interpret SSL keystore file "%1". Verify that the correct keystore type and password were supplied. SSL disabled.
BRC.001.1297	Unable to parse SSL keystore file "%1". Verify that the correct password was supplied. SSL disabled.
BRC.001.1298	Unable to access SSL truststore file "%1": not found. SSL disabled.
BRC.001.1299	Could not access SSL truststore file "%1": access denied. SSL disabled.
BRC.001.1300	Could not access SSL truststore file "%1": operating system error. SSL disabled.

- BRC.001.1301** **The SSL truststore file "%1" is not a regular file and the truststore type is PEM. SSL disabled.**

- BRC.001.1302** **The SSL truststore file "%1" is not a directory and the truststore type is DIR. SSL disabled.**

- BRC.001.1303** **Unable to load certificates from SSL truststore "%1". SSL disabled.**

- BRC.001.1304** **Unable to use certificates from SSL keystore "%1". SSL disabled.**

- BRC.001.1305** **Unable to setup certificate chain from SSL keystore "%1" and truststore "%2". SSL disabled.**

- BRC.001.1306** **Unable to use private key from SSL keystore "%1". SSL disabled.**

- BRC.001.1307** **SSL is configured but no keystore is specified. SSL disabled.**

- BRC.001.1308** **SSL is configured but no truststore is specified. SSL disabled.**

- BRC.001.1309** **SSL keystore type "%1" is invalid. SSL disabled.**

- BRC.001.1310** **SSL truststore type "%1" is invalid. SSL disabled.**

- BRC.001.1311** **SSL cipher suite specification "%1" is invalid. SSL disabled.**

- BRC.001.1312** **Synchronizing Gateway Shared Eventtype [%1] failed in Remote Broker [%2]: syncresult received by Local Broker [%3]**

- BRC.001.1320** **Unable to open CRL File.**

BRC.001.1321	FIPS mode enabled with OpenSSL version ("%1").
BRC.001.1323	FIPS mode is not supported.
BRC.001.1324	FIPS mode initialization failed.
BRC.001.1345E	Cannot resolve the hostname to the Internet address: %1. [EXITING]
Explanation	The host name provided is incorrect.
Action	Provide the correct host name.
BRC.011. 1013E	Deploying assets failed. Reason:{0}
Explanation	The assets could not be deployed to the target runtime.
Action	Check the detailed error message and take appropriate action.
BRC.011. 1074E	Error while getting the list of clients from Broker Server {0}. Reason {1}
Explanation	Unable to get the list of clients from Broker Server.
Action	Check the detailed error message and take appropriate action.
BRC.011.1000E	Could not create the Broker dependency list due to an IOException:{0}.
Explanation	Could not read the ACDL file.
Action	Verify that the ACDL file path and the format are correct.
BRC.011.1001E	Could not create the Broker dependency list due to an Exception:{0}.
Explanation	The exception message describes the cause.
Action	Contact Software AG Global Support for further assistance and provide the exact steps to reproduce this issue.
BRC.011.1002E	Error creating the Broker ACDL for file {0}. Exception message is {1}.
Explanation	The exception message describes the cause.
Action	Contact Software AG Global Support for further assistance and provide the exact steps to reproduce this issue.

BRC.011.1005E	Error writing Broker client information. Exception message is {0}.
Explanation	Error occurred while writing client information to the XML file.
Action	Contact Software AG Global Support for further assistance and provide the exact steps to reproduce this issue.
BRC.011.1008E	Deploying Broker:{0} failed. Reason:{1}
Explanation	Could not create a Broker.
Action	Verify if the Broker Server can be connected using ping.
BRC.011.1010E	Deploying Client Group:{0} failed. Reason:{1}
Explanation	Unable to create a client group on the target Broker.
Action	Retry deploying the ClientGroup.
BRC.011.1012E	Deploying Document Type:{0} failed. Reason:{1}
Explanation	Unable to create a document type on the target Broker.
Action	Retry deploying the document type.
BRC.011.1014E	Deploying asset {0} failed. Reason:{1}
Explanation	The specified asset could not be deployed to the target runtime.
Action	Check the detailed error message and take appropriate action.
BRC.011.1015E	Keystore is provided, but the password is not specified.
Explanation	The keystore password is not provided.
Action	Please provide the password for the keystore.
BRC.011.1016E	Keystore is provided, but the truststore is not specified.
Explanation	The truststore is not provided.
Action	Please provide the truststore.
BRC.011.1017E	Invalid asset encountered: {0}
Explanation	The asset type is not among the valid types. The valid types are Client, Client Group, Document Type, and JMS Destination.
Action	Please provide a valid asset type.

BRC.011.1018E	Cannot export the JMS destinations into multiple JNDI contexts. Export the JMS destinations into one JNDI context at a time for partial export.
Explanation	Creation of partial composite with the selected JMS assets is possible for only one context at a time.
Action	Make sure that the selected assets are from a single context.
BRC.011.1021E	Cannot create file at location: {0}
Explanation	The file could not be created at the specified location.
Action	Check the detailed error message and take appropriate action.
BRC.011.1024E	Deploying JMS Destination:{0} failed. Reason:{1}
Explanation	JMS destination deployment failed.
Action	Check the detailed error message and take appropriate action.
BRC.011.1025E	Exception occurred while trying to connect to JNDI Context:{0}. Reason:{1}
Explanation	Unable to create the Context:
Action	Check the detailed error message and take appropriate action.
BRC.011.1026E	Unable to create a folder at the location: {0}
Explanation	Failed to create a folder at the specified location to store the ADLs and other related files exported from the Broker.
Action	Check the exception details and take appropriate action.
BRC.011.1027E	File does not exist at the location: {0}.
Explanation	The source (binary) file of the exported assets does not exist at the specified location.
Action	Check the exception details and take appropriate action.
BRC.011.1028E	Output location is not provided.
Explanation	The location for storing the exported assets is not specified.
Action	Provide the location for storing the exported assets.

BRC.011.1029E	URL provided is not following a valid syntax: {0}
Explanation	JNDI context creation failed because of syntax error.
Action	Check the exception details and take appropriate action.
BRC.011.1030E	Some unexpected exception occurred.
Explanation	The exception message describes the cause.
Action	Check the exception details and take appropriate action.
BRC.011.1031E	Exception occurred at the Broker: {0}
Explanation	Exception occurred at the Broker while getting details of the deployable resources.
Action	Check the exception details and take appropriate action.
BRC.011.1032E	Exception occurred with the file mapping : {0}
Explanation	Failed to map the asset details.
Action	Check the exception details and take appropriate action.
BRC.011.1033E	File mapping utility is already closed.
Explanation	The exception message describes the cause.
Action	Check the exception details and take appropriate action.
BRC.011.1034E	Unexpected Exception occurred in file mapping.
Explanation	An unexpected error occurred during file mapping.
Action	Check the exception details and take appropriate action.
BRC.011.1035E	Corresponding ADL file is missing.
Explanation	The ADL file into which the asset was exported is missing.
Action	Contact Software AG Global Support for further assistance and provide the exact steps to reproduce this issue.
BRC.011.1036E	Unable to connect to Broker: {0}. Reason:{1}
Explanation	The exception message describes the cause.
Action	Check the exception details and take appropriate action.

BRC.011.1037E	Cannot create partial binaries at the folder '{0}' specified, as it is already populated with some contents.
Explanation	The binary zip file is being unzipped into an already populated folder.
Action	If the issue is not resolved even after you retry using the correct procedure, contact Software AG Global Support for further assistance.
BRC.011.1038E	Partial binary file is not created.
Explanation	The assets specified for partial export do not exist in the full binary.
Action	Make sure the assets specified for partial export exist in the full binary.
BRC.011.1039E	Skipping creation of partial ACDL as the partial binary itself is not created.
Explanation	The creation of the partial export file requires creation of partial Broker binary.
Action	Make sure the partial Broker binary is generated before attempting to create the partial export file.
BRC.011.1040E	Persistence Manager is not set.
Explanation	This is an unexpected error.
Action	Contact Software AG Global Support for further assistance and provide the exact steps to reproduce this issue.
BRC.011.1041E	Persistence Manager threw an exception: {0}
Explanation	The exception message describes the cause.
Action	Check the exception details and take appropriate action. Contact Software AG Global Support for further assistance.
BRC.011.1042E	Broker Name is required.
Explanation	The name of the Broker to which the connection needs to be created, is not provided.
Action	Provide the Broker name through the API or the relevant UI.
BRC.011.1043E	Host is required.
Explanation	The name of the Broker Server to which the connection needs to be created, is not provided.
Action	Provide the Broker Server name through the API or the relevant UI.

BRC.011.1044E	Port is required.
Explanation	The Broker Server port, to which the connection needs to be created, is not provided.
Action	Provide the Broker Server port through the API or the relevant UI.
BRC.011.1045E	Authentication properties are required.
Explanation	The connection information such as the Broker name and port required to create an Admin client is not provided to the API.
Action	Provide the connection information through the API or the relevant UI.
BRC.011.1046E	Exporting the asset {0} failed. Reason:{1}
Explanation	The exception message describes the cause.
Action	Check the exception details and take appropriate action. Contact Software AG Global Support for further assistance.
BRC.011.1047E	Error while getting the client information. Exception text:{0}
Explanation	The exception message describes the cause.
Action	Check the exception details and take appropriate action. Contact Software AG Global Support for further assistance.
BRC.011.1048E	Error while getting the client group information. Exception text:(0)
Explanation	The exception message describes the cause.
Action	Check the exception details and take appropriate action. Contact Software AG Global Support for further assistance.
BRC.011.1049E	Error while getting the event type information. Exception text:{0}
Explanation	The exception message describes the cause.
Action	Check the exception details and take appropriate action. Contact Software AG Global Support for further assistance.
BRC.011.1052E	The asset {0} could not be activated.Reason {1}
Explanation	The exception message describes the cause.
Action	Check the exception details and take appropriate action. Contact Software AG Global Support for further assistance.

BRC.011.1054E	This version of server {0} does not support this functionality.
Explanation	The requested functionality is not supported on the server.
Action	The use case might not be applicable for the Broker version.
BRC.011.1055E	The JNDI creation at the provider URL {0} failed, with the following exception: {1}
Explanation	The exception message describes the cause.
Action	Check the exception details and take appropriate action. Contact Software AG Global Support for further assistance.
BRC.011.1060E	The list containing the assets to be delivered is empty
Explanation	The Delivered Artifacts list is empty.
Action	Populate the list of delivered artifacts.
BRC.011.1061E	Exception occurred while delivering assets. Reason:{0}
Explanation	The exception message contains the reason why the exception occurred while delivering the assets.
Action	Check the detailed error message and take appropriate action.
BRC.011.1062E	Deploying Client:{0} failed. Reason:{1}
Explanation	The exception message contains the reason why the exception occurred while trying to deploy the client.
Action	Check the detailed error message and take appropriate action.
BRC.011.1063E	Dependency check failed for asset {0}
Explanation	The dependent assets are missing in the Accl file.
Action	Export the assets with dependency and re-build the Accl file.
BRC.011.1067E	The asset {0} could not be modified.
Explanation	The specified asset was not updated because of the reason specified in the error message.
Action	Check the detailed error message and take appropriate action.

BRC.011.1068E	Invalid asset type {0} encountered.
Explanation	The asset type is not valid.
Action	Provide a valid asset type. Valid asset types are ClientGroup, Client, DocumentType, JMSDestination, and JndiContext.
BRC.011.1069E	Invalid composite type {0} encountered.
Explanation	The Composite type is not valid.
Action	Provide the correct composite type. Valid composite types are Broker and JNDIProvider.
BRC.011.1070E	Exception occurred while trying to get the server version.
Explanation	Error occurred while trying to get the version of the server.
Action	Check the detailed error message and take appropriate action.
BRC.011.1071E	Exception occurred while trying to create the connection descriptor.
Explanation	Error occurred while trying to create the connection descriptor that holds the connection parameters required for connecting to the server.
Action	Check the detailed error message and take appropriate action.
BRC.011.1072E	Invalid Product Namespace {0} entered.
Explanation	The Product Namespace entered is invalid.
Action	Enter the correct value. The Product Namespace should be Broker.
BRC.011.1073E	The list containing the assets to be verified is empty.
Explanation	The list of assets for verification is empty.
Action	Provide the list of assets that require verification.
BRC.011.1075E	Error while getting the list of client groups from Broker Server {0}.Reason {1}
Explanation	Unable to get the list of clients groups from Broker Server.
Action	Check the detailed error message and take appropriate action.

BRC.011.1084E	Error: Failed to make a connection with the JNDI provider.Reason {0}
Explanation	Broker is unable to connect with the JNDI Provider.
Action	Check the detailed error message and take appropriate action.
BRC.011.1092E	Error while listing the assets from the JNDI Provider. Reason {0}
Explanation	Unable to list the assets from the JNDI Provider.
Action	Check the detailed error message and take corrective action.
BRC.011.1094E	Asset simulation failed. Reason: {0}
Explanation	Asset simulation failed because of the reason specified in the error message.
Action	Check the detailed error message and take corrective action.
BRC.200.1011E	Error: Unknown subcommand "%1"
Explanation	The subcommand is unknown.
Action	Refer to the documentation for this command and specify the required subcommands.
BRC.200.1013E	Error: No data directory supplied.
Explanation	The Broker Server data directory is not specified.
Action	Make sure to specify a valid data directory.
BRC.200.1014E	Error: Datadir "%1" is a relative path; a complete path must be supplied.
Explanation	The specified path for the data directory is a relative path. It must be an absolute path.
Action	Make sure to specify an absolute path for the data directory.
BRC.200.1015W	Warning: Extra license key "%1" specified but not needed.
Explanation	An extra license key was specified.
Action	Make sure to specify a single license key in the arguments list.
BRC.200.1016E	Error: No license key specified. Please specify a valid license key.
Explanation	The Broker Server license key is not specified.
Action	Make sure to specify a valid license key.

BRC.200.1017W	Warning: Extra port number "%1" specified but not needed.
Explanation	An extra port number was specified.
Action	Make sure to specify a single port number in the arguments list.
BRC.200.1018W	Warning: Bad port number value "%1" specified, ignoring.
Explanation	A bad port number was specified and will be ignored.
Action	Make sure to specify a valid port number.
BRC.200.1019W	Warning: Extra description "%1" specified but not needed.
Explanation	An extra description string was specified.
Action	Make sure to specify a single description string.
BRC.200.1020E	Error: No description specified.
Explanation	The description is not specified.
Action	Make sure to specify a valid description string.
BRC.200.1021E	Error: The description "%1" contains non-ISO Latin characters, which is not supported by this tool. Please use webMethods Broker Administrator to set the description.
Explanation	The description contains unsupported characters.
Action	Refer to the Broker administration guide for details on supported characters.
BRC.200.1022W	Warning: Extra Broker Server executable "%1" specified but not needed.
Explanation	An extra Broker Server executable file was specified.
Action	Make sure to specify a single Broker Server executable file.
BRC.200.1023E	Error: No Broker Server executable specified.
Explanation	The Broker Server executable file is not specified.
Action	Make sure to specify a valid Broker Server executable.
BRC.200.1024W	Warning: Extra awbroker.cfg filename "%1" specified but not needed.
Explanation	An extra awbroker.cfg file name was specified.
Action	Make sure to specify the awbroker.cfg file name only once.

BRC.200.1025E	Error: No Broker Server configuration file specified.
Explanation	The Broker Server configuration file is not specified.
Action	Make sure to specify a valid Broker Server configuration file in the arguments.
BRC.200.1026	Warning: Extra storage size number "%1" specified but not needed.
BRC.200.1027	Warning: Bad storage size value "%1" specified, ignoring.
BRC.200.1028W	Warning: Extra option -test specified but not needed.
Explanation	An extra option "-test" was specified.
Action	Make sure to specify the "-test" option only once.
BRC.200.1029W	Warning: Extra option -nostart specified but not needed.
Explanation	An extra option "-nostart" was specified.
Action	Make sure to specify the "-nostart" option only once.
BRC.200.1030W	Warning: Extra hostname "%1" specified but not needed.
Explanation	An extra hostname parameter was specified.
Action	Make sure to specify the hostname parameter only once.
BRC.200.1031E	Error: No hostname specified.
Explanation	The Broker Server host name is not specified.
Action	Refer to the command usage and specify all the required parameters.
BRC.200.1032W	Warning: Port number specified in hostname "%1" is invalid, ignoring.
Explanation	The specified port number is invalid and will be ignored.
Action	Make sure to specify a valid port number.
BRC.200.1033W	Warning: Extra option -f for forcing deletion specified but not needed.
Explanation	An extra option "-f" (for forcing deletion) was specified.
Action	Refer to the documentation for this command and specify only the required parameters.

BRC.200.1034E	Error: "%1" unknown switch.
Explanation	The option specified in the command line is unknown.
Action	Refer to the documentation for this command and specify only the required parameters.
BRC.200.1035E	Error: Unexpected arg "%1".
Explanation	The argument is not valid.
Action	Refer to the documentation for this command and specify only the required parameters.
BRC.200.1036E	Error: Value for session flag "%1" is missing.
Explanation	The value for the specified session flag is missing.
Action	Make sure to specify values for the session flags.
BRC.200.1037E	Error: Missing storage session specification Use -session_config or -session_data to specify.
Explanation	The storage session specification is missing.
Action	Make sure to specify a valid storage session specification.
BRC.200.1038E	Error: "%1" is specified but not required.
Explanation	Extra storage parameters are specified but not required.
Action	Refer to the documentation for this command and specify only the required parameters.
BRC.200.1039E	Error: Filename for "%1" is missing.
Explanation	The file name for the storage or log file is missing.
Action	Make sure to specify a valid file name for storage or log files.
BRC.200.1040E	Error: "%1" is specified more than once.
Explanation	More than one log file is specified in the argument list.
Action	Make sure to specify the log file only once.
BRC.200.1041E	Error: File size for "%1" is missing.
Explanation	The file size for the QS storage file is missing.
Action	Make sure to specify valid file size parameters.

BRC.200.1042E	Error: QS logfile "%1" must be an absolute path.
Explanation	The QS log file must have an absolute path.
Action	Make sure that the log file has an absolute path.
BRC.200.1043E	Error: QS storagefile "%1" must be an absolute path.
Explanation	The QS storage file must have an absolute path.
Action	Make sure that the storage file has an absolute path.
BRC.200.1044E	Error: QS logfile "%1" already exists, will not overwrite.
Explanation	The QS log file already exists and cannot be overwritten.
Action	QS log files cannot be overwritten.
BRC.200.1045E	Error: Resizing the configured QS logfile "%1" is not supported. A different logfile must be configured instead.
Explanation	The QS log file cannot be resized.
Action	Instead of attempting to resize the current log file, a different log file must be configured.
BRC.200.1046	Error: QS logfile size %1 Kb must be higher or equal to %2 Kb.
BRC.200.1047	Error: QS storagefile "%1" size %2 Kb must be higher or equal to %3 Kb.
BRC.200.1048	Error: QS storagefile "%1" reserved size %2 Kb must be less than or equal to %3 Kb, and also larger than %4 Kb.
BRC.200.1049E	Error: QS storage "%1" already exists, will not overwrite.
Explanation	The QS log file already exists and cannot be overwritten.
Action	Make sure that the QS storage file does not already exist.
BRC.200.1050E	Error: Shrinking QS storage "%1" (from %2 Kb to %3 Kb) is not supported.
Explanation	The Broker Server failed to shrink the QS storage file.
Action	On the Broker Server, make sure that the specified storage file size is not less than the current size of QS storage.

- BRC.200.1051** **Error: Cannot reserve less from QS storage "%1" (currently %2 Kb, specified %3 Kb).**
- BRC.200.1052E** **Error: Cannot determine parent dir for "%1".**
Explanation The Broker Server failed to determine the parent directory of the data directory.
Action Make sure that the path string of the data directory is valid and the parent directory exists on the Broker Server.
- BRC.200.1053** **Error: Directory "%1" for file "%2" is not writable.**
- BRC.200.1054E** **Error: Incorrect or insufficient arguments supplied to program.**
Explanation Incorrect or insufficient arguments were supplied to this program.
Action Refer to the documentation for this command and specify all the required parameters.
- BRC.200.1055E** **Error: The webMethods Broker license has expired. Contact your license key administrator for a valid license file. Internal error message: %1**
Explanation The Broker Server license has expired.
Action Make sure you specify a license file containing a valid license.
- BRC.200.1056E** **Error: The webMethods Broker license file could not be found or is invalid. Internal error message: %1**
Explanation Either the license file is not found or it is corrupt.
Action Specify a valid license file path. Make sure you specify the absolute path to the license file and not a relative path. Recommended - /tmp/saglic/broker_license_unix.xml, C:\temp\SAGLIC\broker_license_win32.xml etc. Not recommended - ../saglic/broker_license_unix.xml, ..\SAGLIC\broker_license_win32.xml etc.
- BRC.200.1057** **Error: Specified data directory "%1" not accessible: %2**
- BRC.200.1058E** **Error: Cannot determine parent dir for "%1".**
Explanation The Broker Server failed to determine the parent directory of the data directory.
Action Make sure that the path string of the data directory is valid and the parent directory exists on the Broker Server.

BRC.200.1059	Error: Parent directory "%1" not accessible: %2
BRC.200.1060	Error: Parent directory "%1" not writable: %2
BRC.200.1061	Error: Parent directory "%1" not readable: %2
BRC.200.1062	Error: Data directory "%1" not writable: %2
BRC.200.1063	Error: Data directory "%1" not readable: %2
BRC.200.1064	Warning: Cannot get file system type of parent directory "%1": %2
BRC.200.1065	Warning: Parent directory "%1" is not a local file system.
BRC.200.1066	Error: Parent directory "%1" is not a local file system. The Broker cannot access network drives when running on Windows as a Windows Service.
BRC.200.1067	Warning: Cannot determine the file system type of parent directory "%1": %2. Do you still want to continue? %0
BRC.200.1068	Warning: You are about to create the broker storage files on a non-local file system. Do you still want to continue? %0
BRC.200.1069	Error: Not enough space free (%1 bytes minimum) on file system for "%2"
BRC.200.1070	Error: The Broker Server configuration file "%1" is not accessible: %2
BRC.200.1071	Error: The Broker Server configuration file "%1" is not readable: %2

- BRC.200.1072** **Error: The Broker Server configuration file "%1" is not writable: %2**
- BRC.200.1073** **Error: Port number choice %1 which reserves ports %2 and %3 as well, is conflicting with the Broker Server in "%4", which is reserving ports %5, %6 and %7.**
- BRC.200.1074** **Error: Port number choice %1 conflicts with reserved port %2.**
- BRC.200.1075E** **Error: Cannot bind to port number choice %1: port not available for use.**
Explanation The specified port conflicts with other applications.
Action Make sure to specify a different port that is available.
- BRC.200.1076E** **Please specify a different port number.**
Explanation The specified port conflicts with other applications.
Action Make sure to specify a different port that is available.
- BRC.200.1077** **Warning: Cannot bind to port number choice %1: %2 Port may not be available for use.**
- BRC.200.1078** **Error: awbrokermon configuration file "%1" not readable: %2**
- BRC.200.1079** **Error: awbrokermon configuration file "%1" not present and cannot create: %2**
- BRC.200.1080** **Error: awbrokermon configuration file "%1" not writable: %2**
- BRC.200.1081E** **Error: Could not get directory for the Broker Server Monitor configuration file.**
Explanation The Broker Server failed to locate the directory for the Broker Server Monitor configuration file.
Action Make sure that the directory exists.
- BRC.200.1082** **Error: Could not create Broker Server Monitor configuration dir "%1": %2**

BRC.200.1083	Error: Could not create connection to Service Control Manager: %1
BRC.200.1084E	Error: Could not access Service Control Manager with required permissions: %1
Explanation	The Broker Server failed to access the service control manager with the required permissions.
Action	On the Broker Server, make sure that the service control manager is accessible with the required permissions.
BRC.200.1085	Error: Could not create new service "%1" from Service Control Manager: %2
BRC.200.1086	Error: Could not delete service "%1" from Service Control Manager: %2
BRC.200.1087I	Warning: Cannot switch to uid=%1 (%2): %3
Explanation	Informational message listing the Broker Servers found on the local host while checking for a port conflict.
Action	None.
BRC.200.1088E	Error: Configuration session type "%1" not supported.
Explanation	The specified configuration session type is not supported.
Action	Make sure that the specified configuration session type is "qs".
BRC.200.1089E	Error: Data session type "%1" not supported.
Explanation	The specified data session type is not supported.
Action	Make sure that the specified data session type is "qs".
BRC.200.1090	Error: Broker Server executable "%1" not accessible: %2
BRC.200.1091E	Error: Specified Broker Server executable "%1" not an executable file.
Explanation	The Broker Server executable file is not valid.
Action	On the Broker Server, make sure that the executable file is executable and that the appropriate permissions are set.

- BRC.200.1092** **Error: Specified Broker Server config "%1" not accessible: %2**
- BRC.200.1093E** **Error: Specified Broker Server config "%1" is not a regular file.**
Explanation The Broker Server configuration file is not a standard file.
Action On the Broker Server, examine the configuration file to make sure that it is a standard file.
- BRC.200.1094** **Error: Specified Broker Server config "%1" not readable: %2**
- BRC.200.1095** **Error: Could not read the configuration from "%1": %2**
- BRC.200.1096** **Error: Could not create Broker Server data directory "%1": %2**
- BRC.200.1097W** **Warning: Could not get installation bin directory, using "%1".**
Explanation The Broker Configuration tool failed to obtain the installation \bin directory from the environment settings.
Action Make sure to specify an executable file for the Broker Server. In addition, make sure that the environment settings are valid. (In Windows, check the registry; in UNIX, check the environment variable.)
- BRC.200.1098W** **Warning: Could not signal Broker Server Monitor to reread configuration.**
Explanation The Broker Configuration tool failed to signal the Broker Server Monitor to reread the configuration.
Action Make sure that the Broker Server Monitor is running. Examine the error message for details on the problem.
- BRC.200.1099** **Error: Could not write to the Broker Server configuration file "%1": %2**
- BRC.200.1100E** **Error: Broker Server configuration file "%1" already exists.**
Explanation The Broker Server configuration file was not created because it already exists.
Action Remove or backup the current configuration file and execute the request again.

BRC.200.1101E	Warning: No license key specified for Broker Server. The Broker Server will not be able to start.
Explanation	The Broker Server license key is not specified.
Action	Make sure to specify a valid license key.
BRC.200.1102W	Warning: No executable specified for Broker Server. Broker Server Monitor will not be able to start the Broker Server.
Explanation	No executable file was specified for the Broker Server while adding/creating the Broker Server.
Action	Make sure to specify the name and location of the Broker Server executable file.
BRC.200.1103E	Error: The Broker Server associated with "%1" is still running. Please stop Broker Server first.
Explanation	The remove or delete operation failed because the Broker Server is currently running.
Action	Stop the Broker Server, and then issue the delete or remove request.
BRC.200.1104	The Broker Server on port %1, associated with data directory "%2" is still running. Attempting to stop Broker Server.
BRC.200.1105	Warning: Could not stop Broker Server on port %1, associated with data directory "%2". Continuing deletion anyway.
BRC.200.1106I	Successfully stopped Broker Server on port %1.
Explanation	The Broker Server on the specified port has successfully stopped.
Action	None.
BRC.200.1107E	Error: Could not read the configuration file in "%1", aborting.
Explanation	The Broker Server configuration file could not be read.
Action	Make sure that the configuration file exists and that the user has privileges to read it.
BRC.200.1108	Error: Could not read Broker Server Monitor configuration file "%1": %2

- BRC.200.1109** **Error: Could not write Broker Server Monitor configuration file "%1": %2**
- BRC.200.1110** **Error: File "%1" in data directory "%2" is not a regular file, will not remove.**
- BRC.200.1111** **Error: Could not remove file "%1" in data directory "%2": %3**
- BRC.200.1112** **Error: Could not remove data directory "%1": %2**
- BRC.200.1113E** **Error: Could not find data directory "%1" in the Broker Server Monitor configuration.**
Explanation The Broker Server Monitor configuration does not have the data directory specified.
Action Examine the Broker Server Monitor's configuration file to make sure that the Broker Server is specified correctly.
- BRC.200.1114** **Removed Broker Server in "%1", but errors and/or warnings occurred.**
- BRC.200.1115** **Error: Could not write the Broker Server configuration to "%1": %2**
- BRC.200.1116E** **Error: The Broker Server on port %1 is currently running; cannot change port number. Please stop Broker Server first.**
Explanation The port number of the Broker Server was not changed because the Server is currently running.
Action Stop the Broker Server, and then change the port number.
- BRC.200.1117E** **Error: Could not remove the Broker Servers service definition as part of changing the port number.**
Explanation The service was not removed because the system call to delete an NT service failed.
Action Make sure that the service exists and that the user has privileges to remove services.
- BRC.200.1118E** **Error: Could not create the new service definition for the Broker Server as part of changing the port number.**
Explanation The service was not created because the system call to create an NT service failed.
Action Make sure that the service does not already exist and that the user has privileges to create services.

BRC.200.1119W	Warning: Could not contact Broker Server Monitor for list of Broker Servers. Listing local configuration:
Explanation	The Broker Configuration tool failed to obtain a list of active Broker Servers from the Broker Server Monitor.
Action	Make sure that the Broker Server Monitor is running. Examine the error message for details on the problem.
BRC.200.1120	Error: The Broker Server in data directory "%1" is currently running; cannot grow storage. Please stop Broker Server first.
BRC.200.1121	Error: Cannot open guaranteed storage file "%1": %2
BRC.200.1122	Error: Cannot read signature of file "%1": %2
BRC.200.1123	Error: Cannot read signature of file "%1": file too short.
BRC.200.1124	Error: File "%1" is the wrong file type.
BRC.200.1125	Error: Cannot get size of file "%1": %2
BRC.200.1126	Error: Cannot decrease the size of guaranteed storage. Current size %1 MB (%2 bytes), requested size %3 MB (%4 bytes).
BRC.200.1127	Error: Cannot get free disk space on drive "%1": %2
BRC.200.1128	Error: Insufficient disk space on drive %1 for request. %2 MB (%3 bytes) needed, %4 MB (%5 bytes) available.
BRC.200.1129	Error: Cannot get free space on partition for directory "%1": %2

BRC.200.1130	Error: Insufficient free space on partition for directory "%1" for request. %2 MB (%3 bytes) needed, %4 MB (%5 bytes) available.
BRC.200.1131	Error: Cannot set guaranteed storage size: %1
BRC.200.1132	%1. Datadir: %2 Executable: %3 Port: %4 Version: %5 License-key: "%6" Description: "%7"
BRC.200.1133I	List of configured servers running on "%1":
Explanation	Informational message listing the Broker Servers running on the specified host.
Action	None.
BRC.200.1134	%1. Datadir: %2 Runstatus: %3 Executable: %4 Port: %5 Version: %6 License-key: "%7" Description: "%8"
BRC.200.1135	%1. Datadir: %2 Runstatus: %3 Executable: %4 Port: %5 Description: "%6"
BRC.200.1136	Creating new Broker Server: Datadir: %1 Executable: %2 Port: %3 License-key: "%4" Description: "%5"
BRC.200.1137I	Successfully created Broker Server in "%1".
Explanation	Informational message indicating that the Broker Server was successfully created.
Action	None.
BRC.200.1138	Broker Server: Datadir: %1 Executable: %2 Port: %3 License-key: "%4" Description: "%5" Do you want to delete this Broker Server (y or Y for yes, no otherwise)? %0
BRC.200.1143I	Successfully removed Broker Server in "%1" from the Broker Server Monitor configuration file.
Explanation	The Broker Server was successfully removed from the Broker Server Monitor's configuration file.
Action	None.

BRC.200.1144I	Successfully removed Broker Server data directory "%1".
Explanation	The Broker Server's data directory was successfully removed.
Action	None.
BRC.200.1145I	Successfully read configuration from "%1".
Explanation	The Broker Server successfully read the configuration file.
Action	None.
BRC.200.1146I	Successfully wrote updated configuration to "%1".
Explanation	The Broker Server's configuration file was successfully updated.
Action	None.
BRC.200.1147I	Triggered Broker Server Monitor to reread configuration.
Explanation	Informational message indicating that the Broker Server Monitor was triggered to reread its configuration.
Action	None.
BRC.200.1148I	Triggered Broker Server Monitor to start Broker Server.
Explanation	Informational message indicating that the Broker Server Monitor was triggered to start the Broker Server.
Action	None.
BRC.200.1149I	Broker Server on port %1 is now running.
Explanation	Informational message indicating that the Broker Server on the specified port is now running.
Action	None.
BRC.200.1156	Changing guaranteed data store in "%1".
BRC.200.1157	Current size of guaranteed storage is the same as the requested size. No changes made.

- BRC.200.1158** **Increasing size to %1 MB by adding %2 MB (%3 bytes).**
- BRC.200.1159** **Size of guaranteed storage is now %1 MB (%2 bytes).**
- BRC.200.1160W** **Warning: Cannot make a connection to the local Broker Server Monitor: %1**
Explanation The Broker Configuration tool failed to establish a connection to the Broker Server Monitor.
Action Make sure that the Broker Server Monitor is running. Examine the error message for details on the problem.
- BRC.200.1161** **Warning: Cannot make a connection to the Broker Server Monitor on "%1": %2**
- BRC.200.1162W** **Warning: Cannot close connection to the local Broker Server Monitor: %1**
Explanation The Broker Configuration tool failed to close the connection to the Broker Server Monitor.
Action Make sure that the Broker Server Monitor is running. Examine the error message for details on the problem.
- BRC.200.1163W** **Warning: Cannot signal Broker Server Monitor to reload its configuration: %1**
Explanation The Broker Configuration tool failed to signal the Broker Server Monitor to reload its configuration.
Action Make sure that the Broker Server Monitor is running. Examine the error message for details on the problem.
- BRC.200.1164** **Warning: Cannot signal Broker Server Monitor to reload the configuration for the Broker Server in data directory "%1": %2**
- BRC.200.1165** **Warning: Cannot signal Broker Server Monitor to start the Broker Server in data directory "%1": %2**
- BRC.200.1166W** **Warning: Cannot get list of active Broker Servers from Broker Server Monitor: %1**
Explanation The Broker Configuration tool failed to obtain a list of active Broker Servers from the Broker Server Monitor.
Action Make sure that the Broker Server Monitor is running. Examine the error message for details on the problem.

BRC.200.1167	Warning: Cannot get current run status of the Broker Server in data directory "%1": %2
BRC.200.1168	Warning: Broker Server on port %1 not (yet) running, status is: %2
BRC.200.1169E	Error: Cannot open connection to the Service Control Manager: %1
Explanation	The Broker Server failed to open a connection to Windows NT's service control manager.
Action	Make sure that the user has privileges to connect to the service control manager.
BRC.200.1170	Error: Cannot create new Broker Server as NT service "%1": %2
BRC.200.1171	Error: Cannot open Broker Server as NT service "%1": %2
BRC.200.1172	Error: Cannot delete Broker Server as NT service "%1": %2
BRC.200.1173	Error: Cannot connect to Broker Server on port %1: %2
BRC.200.1174	Error: Cannot stop the Broker Server on port %1
BRC.200.1175	Error: Cannot start Broker Server on port %1
BRC.200.1176	Error: Cannot close connection to Broker Server on port %1
BRC.200.1177E	Removed Broker Server in "%1" from configuration, but errors and/or warnings occurred.
Explanation	The Broker Server was removed, but errors occurred.
Action	In the log files, examine the errors and/or warnings to determine the problem.
BRC.200.1178	Broker Server: Datadir: %1 Executable: %2 Port: %3 License-key: "%4" Description: "%5" Note that Broker Server Data files will not be removed. Do you want to remove this Broker Server from the Broker Server Monitors server configuration (y or Y for yes, no otherwise)? %0

BRC.200.1180I	Removing Broker Server from configuration.
Explanation	The Broker Server is being removed from the configuration.
Action	None.
BRC.200.1181I	Successfully removed Broker Server data directory "%1" from configuration.
Explanation	The Broker Server's data directory was successfully removed.
Action	None.
BRC.200.1182	Error: Cannot open QS configuration file "%1": %2
BRC.200.1183E	Error: Cannot open QS storage: %1
Explanation	The Broker Server failed to open QS storage.
Action	On the Broker Server, make sure that the QS storage file exists and has the appropriate permissions set.
BRC.200.1184E	Error: Cannot replay QS logs: %1
Explanation	The Broker Server failed to replay the QS log file.
Action	Examine the error message to determine the problem.
BRC.200.1185E	Error: Cannot clear QS logs: %1
Explanation	The Broker Server failed to clear the QS log file.
Action	Examine the QS error message to determine the problem.
BRC.200.1186	Error: Cannot add QS log file "%1": %2
BRC.200.1187I	Adding QS files (this may take a few moments):
Explanation	Informational message listing the Broker Servers found on the local host while checking for a port conflict.
Action	None.

BRC.200.1188	Since no log file and no storage file were specified, the Broker Server will create a default log and storage file at startup.
BRC.200.1189	Added QS log file "%1" size %2 Kb successfully.
BRC.200.1190	Error: Cannot add QS storage file "%1": %2
BRC.200.1191	Added QS storage file "%1" size %2 Kb (%3 kb reserved) successfully.
BRC.200.1192	Error: Cannot grow QS storage file "%1" to "%2" bytes: %3
BRC.200.1193	Grew QS storage file "%1" to size %2 Kb (%3 kb reserved) successfully.
BRC.200.1194E	Error: Cannot start QS logs: %1
Explanation	The Broker Server failed to start the QS logs.
Action	Examine the QS error message to determine the problem.
BRC.200.1195	Error: Cannot activate QS log "%1": %2
BRC.200.1196I	Starting Broker Server (this may take a few moments).
Explanation	Informational message indicating that the Broker Server is being started.
Action	None.
BRC.200.1197	The Broker Server at "%1" is currently running. Would you like to stop it (y or Y for yes, no otherwise)? %0
BRC.200.1198	Warning: Attempted to stop the Broker Server at "%1", but it still seems to be running.
BRC.200.1199	Successfully stopped the Broker Server at "%1".

BRC.200.1200	The Broker Server at "%1" is not currently running.
BRC.200.1201	The Broker Server at "%1" is not currently running. Attempting to start it.
BRC.200.1202	Warning: The Broker Server at "%1" did not seem to start.
BRC.200.1203	Successfully started the Broker Server at "%1".
BRC.200.1204	The Broker Server at "%1" is already running.
BRC.200.1205	Error: Could not read the configuration from "%1": %2
BRC.200.1206E	Error: The Broker Server associated with "%1" is still running. Please stop Broker Server first.
Explanation	The remove or delete operation failed because the Broker Server is currently running.
Action	Stop the Broker Server, and then issue the delete or remove request.
BRC.200.1207W	Warning: Extra argument -list specified but not needed.
Explanation	An extra argument "-list" was specified.
Action	Reissue the command without the "-list" argument.
BRC.200.1208I	Successfully configured Broker Server storage.
Explanation	Informational message indicating that storage was successfully added.
Action	None.
BRC.200.1209I	QS Configuration for Broker Server in "%1":
Explanation	Informational message describing the QS configuration.
Action	None.
BRC.200.1210	Log file: "%1", size %2 Kb,

BRC.200.1211	Storage file: "%1", max size %2 Kb, reserved %3 Kb.
BRC.200.12121	The Broker Server configuration tool "broker_config" was renamed to "server_config". Please use "server_config" to configure your Broker Servers.
Explanation	The "broker_config" tool was renamed to "server_config".
Action	Use "server_config" to configure the Broker Servers.
BRC.200.1213	Warning: Parent directory "%1" for "%2" is not on a local file system.
BRC.200.1214	Error: Not enough space free (%1 Kb requested, %2 Kb present) on file system for "%3"
BRC.200.1215	Error: Parent dir "%1" for file "%2" is not present, and must be created first.
BRC.200.1216	Since no log file and no storage file were specified for config data, the Broker Server will create a default log and storage file for config data at startup.
BRC.200.1217	Since no log file and no storage file were specified for queue data, the Broker Server will create a default log and storage file for queue data at startup.
BRC.200.1218	Error: The %1 option cannot be specified without specifying a QS session type using either -session_config or -session_data.
BRC.200.1219	Error: Specifying -session_data when using combined storage is not allowed.
BRC.200.1220	Error: Specifying combined storage is only allowed on the create command.
BRC.200.1221	Error: Config session log file was specified but a storage file was not specified. Storage file must be specified if the log file is specified.

- BRC.200.1222** **Error: A config session storage file was specified but log file was not specified. Log file must be specified if a storage file is specified.**
- BRC.200.1223** **Error: Data session log file was specified but a storage file was not specified. Storage file must be specified if the log file is specified.**
- BRC.200.1224** **Error: A data session storage file was specified but log file was not specified. Log file must be specified if a storage file is specified.**
- BRC.200.1225** **Warning: Bad Broker Monitor port number value "%1" specified, ignoring.**
- BRC.200.1226** **Error: Cannot stop Broker Monitor on host %1 port %2**
- BRC.200.1227** **Using Monitor configuration from "%1".**
- BRC.200.1228** **Error: Broker storage at "%1" is not owned by this installation.**
- BRC.200.1233** **Error: Values for the "%1" storage mapping option are missing.**
Explanation Values for the qs_map_file option are not provided while executing the server_config relocate command.
Action Provide the absolute paths to the old and the new Broker storage files that are not present in the data directory.
- BRC.200.1234** **Warning: Extra queue storage path mapping, "%1" specified, but not needed.**
Explanation QS file mappings are required only for the relocate subcommand of server_config.
Action Provide the QS file mappings only for the server_config relocate command.
- BRC.200.1235** **Error: Cannot relocate the QS storage files.**
Explanation The server_config relocate command failed to relocate the config or data storage files to the new location. Either the QS storage files could not be opened or the files were not provided.
Action Recheck the locations, mappings, and the permissions of the QS files.

BRC.200.1236	Error: Cannot update QS configuration file "%1": %2
Explanation	Cannot update the QS configuration file because of one of these reasons:- Unable to open the BrokerConfig.qs or BrokerData.qs files.- Unable to open the log or stor files.- File mappings are not provided for the stor files that are outside the data directory.
Action	Recheck the locations and permissions of the QS, config/data log, and stor files. Check the mappings of the QS files. Provide separate mapping for each storage file that is located outside the new data directory.
BRC.200.1238	Warning: Extra basic authentication configuration filename, "%1" specified, but not needed.
Explanation	The basic authentication configuration file is required only for the relocate subcommand of server_config.
Action	Check the command description in the webMethods Broker documentation.
BRC.200.1239	Error: No basic authentication configuration file specified for the Broker Server.
Explanation	The basic authentication configuration file is not provided for the server_config relocate command.
Action	Provide the absolute path to the basic authentication configuration file.
BRC.200.1240	Error: Could not read the configuration from "%1".
Explanation	Broker Server's configuration file, awbroker.cfg, is not readable.
Action	Make sure the awbroker.cfg file is present in data directory and has read permissions.
BRC.200.1241	Error: Could not write to the Broker Server configuration file "%1".
Explanation	Broker Server's configuration file, awbroker.cfg, does not have write permission.
Action	Make sure the awbroker.cfg file is present in data directory and has read/write permissions.
BRC.JAVAAPI.100.1010E	A failure occurred on the Broker. The error code is \${code} and the message is '\${fail_string}'.
Explanation	The response from the Broker could not be read properly.
Action	One of the parameters in the error message <failString> contains additional information about the failure. Review the error message to determine the appropriate action. Contact Technical Services for further assistance.

BRC.JAVAAPI.100.1011E – A failure occurred on the Broker. An uninterpretable reply was sent back.

Explanation The response from the Broker could not be read properly.

Action Unknown error. Check the Broker log files for relevant entries in this timeframe.

BRC.JAVAAPI.100.1012E – The operation failed because the Broker is running out of memory. Alert your administrator.

Explanation The Broker could not allocate enough memory to complete the operation.

Action Ensure that enough memory is available on the Broker Server host machine and for the Broker process.

BRC.JAVAAPI.100.1013E – The document was too large for the Broker to process successfully.

Explanation The Queue Manipulation operation failed because the document was too large to add to the queue.

Action Ensure that the document to be inserted into the queue is of a valid BrokerEvent size.

BRC.JAVAAPI.100.1014E – The operation failed because the Broker is having storage problems. Alert your administrator.

Explanation A default Broker could not be created because of storage corruption or invalid storage files.

Action Ensure that the storage files are created and present in the data directory.

BRC.JAVAAPI.100.1015 – The operation failed because the Broker's license has expired. Alert your administrator.

Explanation Broker license has expired.

Action Use a valid Broker license file.

BRC.JAVAAPI.100.1016E – The Broker was unable to join the territory. The error code is '{fail_string}'.

Explanation The Broker could not join the territory because the connection between the Broker and the Broker territory was interrupted or disconnected.

Action Check the network connection between the two Broker hosts. Ensure that the connection is established and then retry the join operation.

BRC.JAVAAPI.100.1017 – The Broker was unable to join the territory, because the territory Broker is processing another territory operation. This is usually a temporary failure, so try again. If the failure persists, check to make sure you are not trying to join the Broker to itself.

Explanation The territory Broker might be busy processing another operation.

Action Try again after some time.

BRC.JAVAAPI.100.1018E – An error occurred in the Broker while looking up the client's access label.

Explanation The request to the access label adapter has timed out or the access label adapter has stopped responding.

Action Check the access label adapter status to see if it is running. Restart the access label adapter if necessary.

BRC.JAVAAPI.100.1019E – The access label adapter process reported an error in looking up the client's access label.

Explanation The access label adapter process could not look up the client's access label. The access label adapter may not be running.

Action Check the access label adapter status to see if it is running. Restart the access label adapter if necessary.

BRC.JAVAAPI.100.1025 – Unable to log audit record.

Explanation This issue might occur when the audit log file creation operation fails.

Action Enable audit logging for error action by setting the auditlog-errorAction=1 in the Broker Server configuration file (awbroker.cfg).

BRC.JAVAAPI.100.1937 – The Broker was unable to join the cluster. The error code is '{fail_string}'.

Explanation The cluster Broker might be busy processing another operation.

Action Try again after some time.

BRC.JAVAAPI.100.1938 – The Broker was unable to join the cluster, because the cluster Broker is processing another cluster operation. This is usually a temporary failure, so try again. If the failure persists, check to make sure you are not trying to join the Broker to itself.

Explanation The cluster Broker might be busy processing another operation.

Action Try again after some time.

BRC.JAVAAPI.100.1940 – The Broker was unable to join the cluster. The cluster Broker is using an incompatible software version.

Explanation The version of the Broker attempting to join the cluster is not compatible with the version of the Broker in the cluster.

Action Make sure the version of the Broker joining the cluster and the version of the Broker in the cluster are compatible. Only webMethods Broker 8.0 and later versions support the Broker cluster functionality.

BRC.JAVAAPI.100.1943 – The Broker was unable to complete the operation, because it is busy processing another cluster operation. This is usually a temporary failure, so try again.

Explanation The cluster Broker might be busy processing another operation.

Action Try again after some time.

BRC.JAVAAPI.100.1948 – The Broker was unable to create the gateway, because the cluster Broker is busy processing another cluster operation. This is usually a temporary failure, so try again. If the failure persists, check to make sure you are not opening a gateway back to the Broker itself.

Explanation Unable to create the gateway because the cluster Broker might be busy processing another operation.

Action Try again after some time.

BRC.JAVAAPI.100.2010E – The gateway operation failed. The error code is '{fail_string}'.

Explanation The gateway operation did not complete because a request to create a gateway or update the shared document types on the gateway failed.

Action One of the parameters in the error message <fail_string> contains additional information about the failure. Review the error message to determine the appropriate action.

BRC.JAVAAPI.100.2011 – The Broker was unable to create the gateway, because the territory Broker is busy processing another territory operation. This is usually a temporary failure, so try again. If the failure persists, check to make sure you are not opening a gateway back to the Broker itself.

Explanation Unable to create the gateway because the territory Broker might be busy processing another operation.

Action Try again after some time.

BRC.JAVAAPI.100.2012 – The gateway could not be created because the Brokers are of incompatible versions.

Explanation The version of the Broker selected for creating the gateway is not compatible with the version of the other gateway Broker.

Action Make sure the versions of the Brokers forming the gateway are compatible.

BRC.JAVAAPI.100.2013E – The Broker was unable to complete the operation, because it is busy processing another territory operation. This is usually a temporary failure, so try again.

Explanation The Broker is busy processing another territory operation.

Action Wait for the territory operation to complete and then reissue the request.

BRC.JAVAAPI.100.2014 – The Broker was unable to join the territory. The other Broker is using an incompatible software version.

Explanation The version of the Broker attempting to join the territory is not compatible with the version of the Broker in the territory.

Action Make sure the version of the Broker joining the territory and the version of the Broker in the territory are compatible.

BRC.JAVAAPI.100.2015E – The operation failed because the Broker does not have enough storage to process the request. Alert your administrator.

Explanation The Broker Server does not have enough storage space available to complete the operation.

Action Contact your system administrator.

BRC.JAVAAPI.100.2016E – The operation failed because the Broker does not have permission to write to the server configuration file.

Explanation The Broker does not have permission to write to the Broker Server's configuration file.

Action Verify the permissions on the Server configuration files. Ensure that the permissions are set properly and then reissue the operation.

BRC.JAVAAPI.100.2017E – The operation failed because the Broker does not have enough disk space to write to the server configuration file.

Explanation The Broker does not have enough disk space to update the Broker Server's configuration file.

Action Increase the storage space. Use the Broker command line utilities to add storage files or to make room on the existing store.

BRC.JAVAAPI.100.2018E – The operation failed because the Broker was unable to write to the server configuration file.

Explanation The Broker does not have permission to write to the Broker Server's configuration file.

Action Verify the permissions on the Server configuration files. Make sure that the permissions are set properly and then reissue the operation.

BRC.JAVAAPI.100.2019 – The operation failed because the Broker was attempted to contact another Broker at the same time that Broker was attempting to contact it. Please retry your operation.

Explanation Brokers try to connect to each other as part of territory join operation at same time.

Action Try again after some time.

BRC.JAVAAPI.100.2020E – The operation failed because the name of the locale does not conform to POSIX locale naming standards.

Explanation The specified local name does not conform to POSIX standards.

Action Check the POSIX compliance of the locale name and then reissue the operation.

BRC.JAVAAPI.100.2021E – The operation failed because the specified character set is not supported on the Broker.

Explanation The specified character set is not supported on the Broker.

Action Install and add support for the character set on the Broker.

BRC.JAVAAPI.100.2022E – The operation failed because the requested locale is not installed on the Broker's host.

Explanation The Broker Server host does not support the specified locale.

Action Install OS support for the specified locale on the Broker Server host machine.

BRC.JAVAAPI.101.1020 – The host '{host}' was found, but no Broker Server is running on port {port} of that host.

Explanation Broker Server is not running on the specified port and host.

Action Make sure that the host and port provided are correct, and Broker is running on the host machine.

BRC.JAVAAPI.101.1021 – The host '{host}' was found, but no Broker Server is running with secure sockets support on port {port} of that host.

Explanation Broker Server is not running with secured sockets on the specified port and host.

Action Check if the host and port provided are correct. Check if the Broker is running on the host machine. Check if SSL is configured properly in the Broker Server.

BRC.JAVAAPI.101.1022 – The host '{host}' was found, but no Broker monitor is running on port {port} of that host.

Explanation Broker Monitor is not running on the specified port and host.

Action Make sure that the host and port provided are correct, and Broker Monitor is running on the host machine.

BRC.JAVAAPI.101.1023E – The gateway operation could not be completed, because the Broker in the other territory is not running or could not be successfully connected to.

Explanation The connection attempt between the gateway Brokers failed. Either the connection between the gateway Brokers has closed or the remote Broker is not running.

Action Ensure that the remote Brokers across the gateway are connected and running.

BRC.JAVAAPI.101.1966 – The gateway operation could not be completed, because the Broker in the other cluster is not running or could not be successfully connected to.

Explanation The gateway operation failed because the Broker in the other cluster is not available.

Action Make sure the Broker in the other cluster is available for the gateway operation.

BRC.JAVAAPI.102.1050E – Failed to create client session with the Broker on host '{host}' and port {port}. Perhaps this port does not have a Broker installed on it, or the Broker is overloaded and cannot accept the connection.

Explanation The client session could not be created on the Broker because a connection to the Broker could not be established. Either the Broker is not running or it is too busy to accept a new client connection.

Action Ensure that the Broker is running. If it is running, then wait for the Broker to become available and try again.

BRC.JAVAAPI.102.1055E – Unable to connect to host '{host}'. It is not currently on the network.

Explanation The Broker Server host <hostName> is not currently on the network.

Action Check that the Broker Server host exists on the current node and can be accessed on the network.

BRC.JAVAAPI.102.1056 – Unable to open connection to host '{host}' due to a lack of network resources. Perhaps too many connections are already open.

Explanation The client could not initialize the connection with Broker Server due to lack of network resources. There might be too many open connections.

Action Close the unwanted connections or increase the limit on the system (try ulimit on Linux).

BRC.JAVAAPI.102.2050 – Unable to open connection to host '{host}'. Error '{errstring}' was reported by the socket call.

Explanation The Java socket open operation failed.

Action Recheck if Broker Server is running on the given host and is reachable.

BRC.JAVAAPI.102.2051 – Unable to send to Broker. Error '{errstring}' was reported by the send call.

Explanation The Java socket write operation failed.

Action Recheck if Broker Server is running on the given host and is reachable.

BRC.JAVAAPI.103.1070E – The connection is closed. {conn_string}

Explanation The connection to the Broker is closed. The Broker or the Broker host may not be responding or the Broker has terminated the connection to this Broker client.

Action Ensure that the Broker and Broker Server host are responding and check the network connection.

BRC.JAVAAPI.104.1080E – The document field data has been corrupted.

Explanation The document field data has been corrupted.

Action Ensure that the document is valid.

BRC.JAVAAPI.104.1081E – The type definition data has been corrupted.

Explanation The type definition data has been corrupted.

Action Recreate the document type by importing any saved ADL files.

BRC.JAVAAPI.105.1190E – Unable to find host '{host}' on the network.

Explanation The <host> host could not be found on the network.

Action Ensure that the host exists on the network and is reachable from the current node.

BRC.JAVAAPI.105.1192E – Territory join failed. Unable to find host '{host}' on the network.

Explanation The territory join request failed because the Broker was unable to find the <host> host on the network.

Action Ensure that the host exists on the network and is reachable.

BRC.JAVAAPI.105.1193 – Gateway creation failed. Unable to find host '{host}' on the network.

Explanation Gateway creation failed as the given host was not on the network.

Action Recheck if Broker host is running and is reachable.

BRC.JAVAAPI.105.1936 – Cluster join failed. Unable to find host '{host}' on the network.

Explanation Failed to add the specified Broker to cluster as the host is not on the network.

Action Recheck if the Broker host is running and is reachable.

BRC.JAVAAPI.106.1200 – The Broker is from webMethods Broker version 3.0 or earlier and is not compatible with the client library version.

Explanation The Broker client session could not be established as the Broker version is 3.0 or earlier.

Action Upgrade the Broker to a version that is compatible with the client library version.

BRC.JAVAAPI.106.1201E – The Broker is not compatible with the client library version. The Broker version is newer.

Explanation The Broker is not compatible with this version of the client library. The Broker is running a newer version of webMethods Broker.

Action Upgrade to a newer version of webMethods Broker where this feature is supported.

BRC.JAVAAPI.106.1202 – The Broker Server is from webMethods Broker version 3.0 or earlier and is not compatible with the client library version.

Explanation The Broker Server client session could not be established as the Broker Server version is 3.0 or earlier.

Action Upgrade the Broker Server to a version that is compatible with the client library version.

BRC.JAVAAPI.106.1203E – The Broker Server is not compatible with the client library version. The Broker Server version is newer.

Explanation The Broker Server client session could not be established as the Broker Server version is newer.

Action Use a Broker Server that is compatible with the client library or upgrade the client library to a version that is compatible with the Broker Server.

BRC.JAVAAPI.106.1204 – The Broker monitor is from webMethods Broker version 3.1.2 or earlier and is not compatible with the client library version.

Explanation The Broker Monitor client session could not be established because the Broker Monitor version is 3.1.2 or earlier.

Action Upgrade the Broker Monitor to a latest version that is compatible with the client library version.

BRC.JAVAAPI.106.1205E – The Broker monitor is not compatible with the client library version. The Broker Monitor version is newer.

Explanation The Broker Monitor client session could not be established because the Broker Monitor version is newer.

Action Use a Broker Monitor that is compatible with the client library or upgrade the client library to a version that is compatible with the Broker Monitor.

BRC.JAVAAPI.106.1206E – The Broker does not support subscription filters for territory gateways.

Explanation Filters for territory gateways are not supported on Broker versions prior to 4.0.

Action Upgrade the Broker Server to a compatible latest version to avail support for territory gateway filters.

BRC.JAVAAPI.106.1207E – The Broker Server does not support access to a server log.

Explanation This version of webMethods Broker does not support access to a server log.

Action Upgrade to a newer version of webMethods Broker where this feature is supported.

BRC.JAVAAPI.106.1208E – The Broker does not support changelocks.

Explanation This version of the Broker does not support the change locks feature.

Action Upgrade to a newer version of webMethods Broker where this feature is supported.

BRC.JAVAAPI.106.1811 – Client Queue Browser is supported only on Brokers of version 6.5 or higher.

BRC.JAVAAPI.106.1907 – The Broker Server does not support old form of SSL configuration.

BRC.JAVAAPI.106.1908 – The Broker Server does not support OpenSSL configuration.

BRC.JAVAAPI.106.1912 – The Broker Server does not support BrokerSSLIdentity lookup.

BRC.JAVAAPI.106.1955 – Cluster gateway keep alive is not supported on this version of the Broker.

BRC.JAVAAPI.106.1956 – Cluster gateway pause is not supported on this version of the Broker.

BRC.JAVAAPI.106.1957 – The Broker does not support setting subscription filters for cluster gateways.

BRC.JAVAAPI.106.2023E – The Broker Server does not support setting the filter collation locale.

Explanation This version of webMethods Broker does not support setting filter collation locale.

Action Upgrade to a newer version of webMethods Broker where this feature is supported.

BRC.JAVAAPI.106.2024E – Redelivery counting is not supported on this version of the Broker.

Explanation Redelivery counting is not supported on the version of Broker that the client is currently connected to.

Action Ensure that the Broker is version 6.1 or higher.

BRC.JAVAAPI.106.2025E – Territory gateway keep alive is not supported on this version of the Broker.

Explanation Territory gateway keep-alive is not supported on the version of Broker that the client is currently connected to.

Action Ensure that the Broker is version 6.1 or higher.

BRC.JAVAAPI.106.2026E – Territory gateway pause is not supported on this version of the Broker.

Explanation Territory gateway pause is not supported on the version of Broker that the client is currently connected to.

Action Ensure that the Broker is version 6.1 or higher.

BRC.JAVAAPI.106.2029M – Check for Events is not supported on this version of the Broker.

Explanation The check for events feature is not supported on pre-6.1 versions of Broker.

Action To use the check for events feature, ensure that you are using webMethods Broker 6.1 or higher.

BRC.JAVAAPI.106.2030M – Client keep alive is not supported on this version of the Broker.

Explanation The client keep alive feature is not supported on pre-6.1 versions of Broker.
Action To use the client keep alive feature, ensure that you are using webMethods Broker 6.1 or higher.

BRC.JAVAAPI.106.2031M – Transaction administration is not supported on this version of the Broker.

Explanation Transaction administration is not supported on webMethods Broker version 6.1.
Action To use the transaction administration feature, ensure that you are using webMethods Broker 6.1 or higher.

BRC.JAVAAPI.106.2032M – Synchronous get event(s) is not supported on this version of the Broker.

Explanation This version of the Broker does not support synchronous receive operation.
Action Ensure that the Broker Server is version 6.5 or higher.

BRC.JAVAAPI.106.2033M – Static gateway subscription is not supported on this version of the Broker.

Explanation This version of the Broker does not support static gateway forwarding feature.
Action Ensure that the Broker Server is version 6.1 SP3 or higher.

BRC.JAVAAPI.106.2034M – The Broker Server does not support meta data backup.

Explanation This version of the Broker does not support meta data backup.
Action Ensure that the Broker Server is version 6.5 or higher.

BRC.JAVAAPI.107.1210E – The operation was interrupted by request.

Explanation The operation was interrupted by a user request.
Action None.

BRC.JAVAAPI.109.1370E – Cannot create or reconnect to client on Broker '{broker}' on host '{host}:{port}'. Permission is denied.

Explanation A client application was denied permission to create or reconnect to the client on Broker <brokerName> on host <hostName>:<portNum>.
Action Verify that the ACL is set up correctly and the access label adapter is running.

BRC.JAVAAPI.109.1371E – Cannot create or reconnect to client on the default Broker on host '\${host}:\${port}'. Permission is denied.

Explanation	A request to create or reconnect to a client on the default Broker on host <hostName>:<portNum> was denied because no default Broker exists on the Broker Server.
Action	Ensure that a default broker exists on the Broker Server.

BRC.JAVAAPI.109.1372E – Cannot deliver the document. Permission is denied. Check the 'can publish' permissions in the client's client group.

Explanation	The Broker client tried to deliver a document but was unable to because the client does not have the correct permissions.
Action	Check the "can publish" permissions in the client's client group. Ensure that the client's client group has the appropriate publish permission set.

BRC.JAVAAPI.109.1373E – Cannot access information about document type '\${etype}'. Must have either 'can publish' or 'can subscribe' permission in the client's client group.

Explanation	The Broker client cannot access information about the document type <docType>. The Broker client must have either "can publish" or "can subscribe" permissions set in the client's client group.
Action	Check the permissions in the client's client group. Make sure that the current client's client group has either publish or subscribe permission on the document type <docType>.

BRC.JAVAAPI.109.1374E – Cannot publish the document. Permission is denied. Check the 'can publish' permissions in the client's client group.

Explanation	The Broker Client could not publish the document because the client does not have the required publish permissions.
Action	Ensure that the client's client group has the appropriate publish permission set.

BRC.JAVAAPI.109.1375E – The field '\${field_name}' is read only.

Explanation	A client application tried to set the fieldname <fieldName>, but this field is read only and cannot be set or modified.
Action	Ensure that the fieldName is user settable before setting or modifying it.

BRC.JAVAAPI.109.1376E – Cannot set the state share limit on an unshared client.

Explanation A client application was unable to set the share state limit because the Broker Client used is not enabled for state sharing.

Action Enable state sharing on the client and then set the state share limit.

BRC.JAVAAPI.109.1377E – Cannot subscribe to document type '{etype}'. Permission is denied. Check the 'can subscribe' permissions in the client's client group.

Explanation The Broker Client tried to subscribe to a document of the specified type and failed because the client does not have the required permissions.

Action Check the client's client group subscribe permissions. Ensure that the appropriate subscribe permissions are set.

BRC.JAVAAPI.109.1378E – Client connection failed because this client requires an additional license.

Explanation The client connection failed because the Broker's current license does not support SSL connections.

Action Check the Broker's license. Ensure that it is valid and supports SSL.

BRC.JAVAAPI.109.1379E – Operation failed. Permission denied.

Explanation The requested operation failed because the client does not have administrative permissions.

Action Ensure that the client issuing the request has appropriate permissions to complete the operation.

BRC.JAVAAPI.109.1380E – Cannot change the value of platform key '{key}'.

Explanation The Broker denied a request to edit the platform key because the key is not user settable.

Action Ensure that the keys are user settable. For further assistance, see the webMethods Broker API documentation for the Java client.

BRC.JAVAAPI.109.1381 – The password for keystore file '{cert_file}' is missing or incorrect.

BRC.JAVAAPI.109.1382E – Operation failed because permission is denied. This operation requires administrative permissions.

Explanation A client application tried to perform an operation, but the operation could not complete because the Broker Client did not have administrative permissions.

Action Use an administrative client to complete the operation.

BRC.JAVAAPI.109.1383E – Cannot create a host client connection to host '{host}'. Permission is denied.

Explanation The Broker Monitor Client could not connect to the Broker Monitor on the specified host because it does not have the required permission.

Action Ensure that the Broker monitor is running and the license is valid.

BRC.JAVAAPI.109.1384E – The certificate file '{cert_file}' was found, but it cannot be read. Permission is denied.

Explanation A client application tried to execute an SSL related operation and failed because it could not read the certificate file specified in the function call. A possible cause is that the client application does not have read permission for the file.

Action Check the read permissions for the certificate file. Ensure that the appropriate read permissions are set.

BRC.JAVAAPI.109.1385E – This operation cannot be completed because it is attempting to modify or delete a system-defined value.

Explanation An operation tried to modify or delete a system-defined value, but this is not allowed.

Action Ensure that the system-defined client groups and event types are not modified or deleted.

BRC.JAVAAPI.109.1386E – Operation failed. The Broker is not licensed for Broker interconnection.

Explanation The Broker cannot complete the multi-Broker operation because the Broker is not licensed for interconnection.

Action Obtain a new multi-broker Broker license.

BRC.JAVAAPI.109.1387E – Cannot publish or deliver the document. Permission is denied. The document can only be published by the Broker.

Explanation The Broker Client could not publish or deliver the document because the client does not have the required publish permissions. Only the Broker can publish the document.

Action Check the publish permissions in the client's client group. Ensure that the client group does not specify documents that are only publishable by the Broker.

BRC.JAVAAPI.109.1388E – The client has no access label because the client does not have an owner.

Explanation A client application tried to get or set an access label and failed because the client does not have an owner and as a result does not have an access label.

Action Verify that the client has an owner. If the client does not have an owner, it cannot have an access label.

BRC.JAVAAPI.109.1389 – The file '{cert_file}' is not a valid certificate file.

BRC.JAVAAPI.109.2370E – Cannot connect to the specified client group because that client group requires an encryption level higher than you are using.

Explanation The specified client group's encryption level does not match that of the issuing client. The specified client group requires a higher level of encryption than the one the issuing client uses.

Action Check the encryption levels. Ensure the encryption levels match.

BRC.JAVAAPI.109.2371E – Cannot publish or deliver a document with a control label value that exceeds your client's access label.

Explanation The client cannot publish or deliver a document. The document's control label value may exceed the client's access label.

Action Check the control label value for the document. Ensure that the correct value is specified.

BRC.JAVAAPI.109.2372E – An access label cannot be required on the accessLabelAdapter client group.

Explanation A client application tried to set EnforcedAccessLabel on an ALA client group, but this is not allowed because it may cause connection issues on the ALA client group.

Action Ensure that the accessLabelAdapter client group's settings have not been modified.

BRC.JAVAAPI.109.2373 – The class '{class_name}' cannot be instantiated because it is not a public class. Note that inner classes may be declared as public using the 'public static' class modifier.

BRC.JAVAAPI.109.2374 – The class '{class_name}' cannot be instantiated either because it is not a public class, or because it is an abstract class or an interface. Note that inner classes may be declared as public using the 'public static' class modifier.

BRC.JAVAAPI.110.1390E – The requested operation is not implemented in this release.

Explanation The client application requested an operation that is not available in this release.

Action Upgrade to a newer version of webMethods Broker where this feature is supported.

BRC.JAVAAPI.111.1430E – Client creation failed due to missing platform information.

Explanation The client could not be created because of missing information on the client platform.

Action Contact Software AG Global Support.

BRC.JAVAAPI.111.1431E – The operation failed due to missing arguments in the protocol.

Explanation	Missing arguments in the protocol request caused the operation to fail. A communication problem could have caused the protocol commands to fragment.
Action	Contact Software AG Global Support.

BRC.JAVAAPI.111.1433E – A protocol failure occurred.

Explanation	An unknown error in the protocol request caused the operation to fail.
Action	Contact Software AG Global Support.

BRC.JAVAAPI.111.1434 – The operation failed due to an unknown command in the protocol.**BRC.JAVAAPI.111.1435 – The operation failed due to incorrect arguments in the protocol.****BRC.JAVAAPI.112.1450E – The request timed out.**

Explanation	An operation that is expecting a reply from the Broker timed out.
Action	Ensure that the Broker Server is running on the specified host:port and that connectivity between the server host and the client host is stable. Reissue any request that can be reissued on timeout conditions.

BRC.JAVAAPI.112.1451E – The Broker Server monitor reports that the server was not started within its timeout period. It may or may not have been started.

Explanation	The Broker Server start operation failed to return the server status within the default timeout period of 30 seconds.
Action	Check the Broker Server. If it was not started, reissue a start request. Note that the Broker Server can start successfully even after the timeout condition.

BRC.JAVAAPI.112.1452E – Initializing a connection to host '`{host}:{port}`' timed out.

Explanation	A request to create a Broker client timed out while waiting for the connection to the Broker server to initialize. A network delay or an engaged Broker may be the cause.
Action	Ensure that the Broker Server is running on the specified host:port and that connectivity between the server host and the client host is stable.

BRC.JAVAAPI.113.1127 – Secure socket truststore file '{cert_file}' was not found.

BRC.JAVAAPI.113.1128 – Secure socket keystore file '{cert_file}' was not found.

BRC.JAVAAPI.113.1129E – Secure socket certificate file '{cert_file}' was not found on the Broker host.

Explanation The secure socket certificate file <certFile> was not found on the Broker Server host.
Action Check that the secure socket certificate file exists in the location specified during SSL configuration.

BRC.JAVAAPI.114.1435E – The specified certificate is not valid. It has expired.

Explanation The specified certificate is not valid. It has expired.
Action Check the certificate. Ensure that the certificate is valid and has not expired.

BRC.JAVAAPI.114.1436E – The distinguished name was not in the proper format.

Explanation The distinguished name was not in the proper format.
Action Check the distinguished names. Ensure that they are in the proper format. Contact Software AG Global Support for further assistance.

BRC.JAVAAPI.114.1437E – The distinguished name exists, but its certificate is not certified.

Explanation The certificate is not certified, although the distinguished name exists.
Action Ensure that all the certificates in the certificate file are properly certified.

BRC.JAVAAPI.114.1439E – The connection to host '{host}' could not be opened because the secure socket handshake failed. The Broker's certificate is not valid because it has expired.

Explanation At attempt to connect to the Broker host failed because the Broker's SSL certificate has expired.
Action Check the SSL certificate and make sure it is still valid.

BRC.JAVAAPI.114.1441 – The connection to host '{host}' could not be opened because the secure socket handshake failed. This can happen if the server's certificate is not trusted by your truststore, or the server rejects a client certificate when making the connection.

BRC.JAVAAPI.114.1442 – Secure sockets are not supported with this version of the classes.

BRC.JAVAAPI.114.1443E – Secure sockets are not supported or are not enabled on the Broker.

Explanation Secure sockets are not supported or are not enabled on the Broker.

Action Ensure that the SSL is installed and enabled on the Broker. Also, make sure that the native SSL libraries are available at the shared library path.

BRC.JAVAAPI.114.1444E – There is no default certificate in the specified certificate file. Only certificate files with one certificate in them may use this option.

Explanation The specified certificate file does not contain a default certificate. Only certificate files that contain one certificate may use this option.

Action Check the certificate. Ensure that the certificate is specified explicitly when using a certificate file with more than one certificate.

BRC.JAVAAPI.114.1445E – Secure sockets are not supported or are not enabled on the Broker trying to join the territory, and the territory requires secure connections.

Explanation A Broker attempted to join a territory that requires SSL connections, but SSL is not supported or is not enabled on the Broker.

Action Check the Brokers in the territory. Ensure that all of them either have SSL enabled or disabled.

BRC.JAVAAPI.114.1446 – Invalid SSL protocol level specified.

BRC.JAVAAPI.114.1447 – Invalid SSL cipher suite specified.

BRC.JAVAAPI.114.1944 – Secure sockets are not supported or are not enabled on the Broker trying to join the cluster, and the cluster requires secure connections.

BRC.JAVAAPI.115.1024 – The publish operation could not be completed, because the Broker publication processing was paused by the administrator.

BRC.JAVAAPI.200.1000E – Cannot register callback for a sub ID before registering a general callback

Explanation The Broker could not execute the callback for the requested tag or sub-id because the client did not register a general callback first. To use a specific callback, a client must register a general callback first.

Action Register a general callback first, then register specific callbacks for a BrokerClient.

BRC.JAVAAPI.200.1001E – Cannot register callback for a tag before registering a general callback

Explanation The Broker could not execute the callback for the requested tag or sub-id because the client did not register a general callback first. To use a specific callback, a client must register a general callback first.

Action Register a general callback before registering a specific callback for a BrokerClient.

BRC.JAVAAPI.200.1002 – This operation cannot be called from within a callback method.

BRC.JAVAAPI.200.1003 – There currently are no connected clients.

BRC.JAVAAPI.200.1004 – Cannot use request-and-wait operations without registering a general callback first.

BRC.JAVAAPI.200.1005E – Cannot get the Broker's distinguished name because the client is not connected using secure sockets.

Explanation The Broker client attempted to access SSL information on a non-SSL client connection.

Action Ensure that the client is enabled for SSL before issuing any SSL-specific API calls.

BRC.JAVAAPI.200.1006E – Cannot get the access label because the access label feature is not enabled. No access label adapter process is connected to the Broker.

Explanation An access label adapter is not running to support the access label feature.

Action To use the access label feature, enable and start an access label adapter on the Broker.

BRC.JAVAAPI.200.1007 – Could not release Broker change lock. The Broker change lock is not currently held by any client.

BRC.JAVAAPI.200.1008E – Could not release Broker change lock. The Broker change lock is currently held by client '{client_id}', session '{session_id}', and was locked at '{lock_time}'.

Explanation The Broker administrative client could not acquire or release the change lock because the lock is held by a different client. The change lock is held by <clientID>.

Action Acquire or release the Broker change lock on <clientID> as appropriate, and reissue the change lock request.

BRC.JAVAAPI.200.1953 – Cluster gateway is already paused.

BRC.JAVAAPI.200.1954 – Cluster gateway is already resumed.

BRC.JAVAAPI.200.2027E – Territory gateway is already paused.

Explanation A client attempted to pause a territory gateway that is already paused.

Action Ensure that the gateway is not already paused before attempting a pause operation.

BRC.JAVAAPI.200.2028E – Territory gateway is already resumed.

Explanation A client attempted to resume a territory gateway that was not paused.

Action Ensure that the gateway is paused before attempting a resume operation.

BRC.JAVAAPI.201.1030E – Cannot reconnect client '{client_id}'. Another process is already connected to the Broker and is using this client.

Explanation The Broker client is in use by another client.

Action Verify that the client ID used by the Broker client is unique and is not used by another client connection.

BRC.JAVAAPI.201.1031E – Cannot reconnect client '{client_id}'. The maximum number of reconnections for this shared state client has been exceeded.

Explanation The Broker client's shared state limit has been exceeded. A new session cannot be created for the specified Broker client.

Action Increase the client's shared limit and try again.

BRC.JAVAAPI.201.1032 – Cannot reconnect client '{client_id}'. Cannot change shared state property while reconnecting to an existing client.

BRC.JAVAAPI.201.1033 – Cannot reconnect client '{client_id}'. Cannot change access label hint while reconnecting to an existing client.

BRC.JAVAAPI.201.1034 – Cannot reconnect client '{client_id}'. Cannot change shared document ordering property while reconnecting to an existing client.

BRC.JAVAAPI.201.1035 – Cannot reconnect client '{client_id}'. Cannot change redelivery count mode while reconnecting to an existing client.

BRC.JAVAAPI.201.1036 – Cannot reconnect client '{client_id}'. Cannot change volatile acknowledgement setting while reconnecting to an existing client.

BRC.JAVAAPI.201.1037 – Cannot reconnect client '{client_id}'. Cannot change forced reconnect property while reconnecting to an existing client.

BRC.JAVAAPI.201.1038 – Cannot reconnect client '{client_id}'. Cannot change client life cycle property while reconnecting to an existing client.

BRC.JAVAAPI.201.1039 – Cannot reconnect client '{client_id}'. Cannot change client storage property while reconnecting to an existing client.

BRC.JAVAAPI.201.6670 – Cannot reconnect client '{client_id}'. Cannot change priority ordering property while reconnecting to an existing client.

BRC.JAVAAPI.202.1040E – Cannot create client '{client_id}'. The client has already been created.

Explanation A Broker client named <clientID>already exists on the Broker.

Action Use a unique name for the client ID.

BRC.JAVAAPI.203.1090E – The field '{field_name}' could not be found in the document.

Explanation The field <fieldName> could not be found in the document.

Action Ensure that the specified field name exists in the document.

BRC.JAVAAPI.203.1091E – The field '{field_name}' is not defined in the document type definition.

Explanation [DELETED] The field <fieldName> is not defined in the document type definition.

Action Ensure that the specified field name is defined in the document type definition.

BRC.JAVAAPI.203.1092 – The field '{field_name}' is not accessible because it is a member of a non-public class.

BRC.JAVAAPI.203.1093 – The field '{field_name}' is defined in the storage class but is not defined in the document type definition.

BRC.JAVAAPI.203.1094 – The indicator field '{field_name}' does not correspond to any field defined in the storage class.

BRC.JAVAAPI.204.1110E – Field type mismatch when looking up '{field_name}'. A field of a non-sequence type is being accessed as if it were a sequence.

Explanation The field type does not match the <fieldName> field. A sequence type operation can only be performed on a sequence type field.

Action Ensure that only sequence type operations are performed on sequence type fields.

BRC.JAVAAPI.204.1111E – Field type mismatch when looking up '{field_name}'. A field of a non-structured type is being accessed as if it were a struct.

Explanation There is a mismatch in the field type of the specified field. The operation requires structured data.

Action Make sure valid operations are applied based on the field type.

BRC.JAVAAPI.204.1112E – Field type mismatch when looking up '{field_name}'. A field of a basic type is being accessed as if it were a struct or sequence.

Explanation The field type does not match the <fieldName> field. A basic type field is being accessed when a structured or sequence type is expected.

Action Ensure that operations that are valid for structured or sequence data types are applied on structured or sequence fields.

BRC.JAVAAPI.204.1113E – Field '{field_name}' cannot be cleared because it is not a valid field.

Explanation Field <fieldName> is not a valid field and cannot be cleared.

Action Ensure that the field specified by <fieldName> is a valid field.

BRC.JAVAAPI.204.1114 – Field '{field_name}' in the document is not of type {type} as defined in the type definition.

BRC.JAVAAPI.204.1115E – Field '{field_name}' in the document is not a sequence of type {type} as defined in the type definition.

Explanation Field <fieldName> in the document does not match the stored type definition for a sequence type <fieldType>.

Action Ensure that the fields in the document match the type definition.

BRC.JAVAAPI.204.1116E – The field '{field_name}' must be a sequence for this operation.

Explanation The field <fieldName> is not a sequence. The field must be a sequence for this operation.

Action Ensure that the field is a sequence data type.

BRC.JAVAAPI.204.1117E – The field '{field_name}' must be a struct for this operation.

Explanation The field <fieldName> is not structured. The field must be structured for this operation.

Action Ensure the field is a structured data type.

BRC.JAVAAPI.204.1118E – Field '{field_name}' is not of type {type}.

Explanation The Field <fieldName> does not match the requested field type.

Action Ensure that the field types match.

BRC.JAVAAPI.204.1119E – Field '{field_name}' is not a sequence of type {type}.

Explanation The field <fieldName> is not a sequence type field. The field must be a sequence type field for this operation.

Action Ensure that the field is a sequence type.

BRC.JAVAAPI.204.1120E – Field '{field_name}' has a sequence being accessed with a field name. Sequence types only have a '[' field.

Explanation Field <fieldName> has a sequence being accessed with a field name. Sequence types only have a "[" field.

Action Ensure that the sequence field is accessed with a "[" field and not with field names.

BRC.JAVAAPI.204.1121E – Cannot convert document to string. The document does not match its type definition.

Explanation The Broker Client cannot convert the document to a string because the document does not match its type definition.

Action Ensure that a valid document is used.

BRC.JAVAAPI.204.1122E – Validation failed. The document does not match its type definition.

Explanation Validation failed. The document does not match its type definition.

Action Ensure that a valid document is used.

BRC.JAVAAPI.204.1123E – Sequence field '{field_name}' cannot be resized because its type is not known.

Explanation Sequence field <fieldName> cannot be resized because its type is not known.

Action Check the sequence type and make sure it is one of the know data types.

BRC.JAVAAPI.204.1124 – Field '{field_name}' is a sequence, but it is not a sequence of type {type}.

BRC.JAVAAPI.204.1125 – Indicator field '{field_name}' has type {type}, but it needs to be a boolean.

BRC.JAVAAPI.204.2110 – Value parameter must be the proper type for the specified field_type.

BRC.JAVAAPI.204.2111 – The field '{field_name}' has a different type in the storage class than in the type definition.

BRC.JAVAAPI.205.1130E – A syntax error was encountered while parsing the filter. {parse_msg}

Explanation A syntax error was encountered while parsing the filter.

Action Ensure that the filter string is valid and syntactically correct.

BRC.JAVAAPI.205.1131E – Parser stack underflow. {parse_msg}

Explanation An operation encountered a stack underflow error while parsing the filter string.
Check the error message <parseMsg> for more details.

Action Verify that the filter string is valid and syntactically correct.

BRC.JAVAAPI.205.1132E – The filter contains an invalid character constant. {parse_msg}

Explanation The filter contains an invalid character constant.

Action Ensure that the filter is valid and the syntax in the filter is correct.

**BRC.JAVAAPI.205.1133E – The filter contains a string that is missing its closing quotation mark.
{parse_msg}**

Explanation The filter contains a string that is missing a closing quotation mark.

Action Check the syntax for the filter strings. Ensure that the quotation symbols are used correctly.

BRC.JAVAAPI.205.1134E – The field '{field}' does not exist. {parse_msg}

Explanation The field <fieldName> is not found in the document type definition.
Action Verify that the field names specified in the filter are valid and present in the document type definition.

BRC.JAVAAPI.205.1135E – The function '{func}' does not exist. {parse_msg}

Explanation The function <function> does not exist. The specified function is not valid or not supported by the filter compiler.
Action Verify that the filter string is valid and only supported functions are used. For the list of supported functions, see the webMethods Broker API documentation for the Java client.

BRC.JAVAAPI.205.1136E – The filter contains an invalid number. {parse_msg}

Explanation The filter contains an invalid number.
Action Verify that the filter string is valid and that the correct parameters are used.

BRC.JAVAAPI.205.1137E – An unexpected character was encountered while parsing the filter. {parse_msg}

Explanation An unexpected character was encountered while parsing the filter.
Action Ensure that the filter string is valid and syntactically correct.

BRC.JAVAAPI.205.1138E – The type '{type}' was found where a boolean type was expected. {parse_msg}

Explanation The type <fieldType> was found where a Boolean type was expected.
Action Verify that the filter string is valid and uses the correct parameters.

BRC.JAVAAPI.205.1139E – The type '{type}' was found where a string, date or numeric type was expected. {parse_msg}

Explanation The type <fieldType> was found where a string, date, or numeric type was expected. Or, a sequence or structured type was found where a basic type was expected.
Action Verify that the filter string is valid and uses the correct parameters.

BRC.JAVAAPI.205.1140E – The type '{type}' was found where a numeric type was expected. {parse_msg}

Explanation A numeric type was expected while evaluating a numeric expression in the filter, but a non-numeric type was found.
Action Verify that the filter string is valid and the correct parameter types are passed.

BRC.JAVAAPI.205.1141E – The type ' $\{type\}$ ' was found where an integral type was expected. $\{parse_msg\}$

Explanation The type $\langle type \rangle$ was found where an integral type was expected. An integral type is needed for certain operations, such as bit-wise operations.

Action Verify that the filter string is valid and correct parameters are passed.

BRC.JAVAAPI.205.1142E – The types ' $\{type1\}$ ' and ' $\{type2\}$ ' are incompatible for comparison. $\{parse_msg\}$

Explanation The types $\langle type1 \rangle$ and $\langle type2 \rangle$ are incompatible for comparison.

Action Verify that the filter string is valid and correct.

BRC.JAVAAPI.205.1143E – The function ' $\{func\}$ ' does not have enough parameters. $\{parse_msg\}$

Explanation The function $\langle function \rangle$ does not have enough parameters.

Action Verify that the correct number of parameters are passed to the functions in the filter.

BRC.JAVAAPI.205.1144E – The function ' $\{func\}$ ' has too many parameters. $\{parse_msg\}$

Explanation The function $\langle function \rangle$ has too many parameters. Too many arguments are being passed to a filter function.

Action Ensure that the correct number of parameters are passed to the functions used in the filter.

BRC.JAVAAPI.205.1145E – One of the parameters to the function ' $\{func\}$ ' is the wrong type. $\{parse_msg\}$

Explanation One of the function parameters $\langle function \rangle$ is of the wrong type.

Action Verify that the functions specified in the filter are passed with parameters of expected types.

BRC.JAVAAPI.205.1146E – An internal error was encountered while parsing the filter. $\{parse_msg\}$

Explanation The filter may contain an invalid unary operation.

Action Verify that the filter string is valid and that the operations specified in the filter are valid.

BRC.JAVAAPI.205.1147E – The filter contains an invalid escape character. $\{parse_msg\}$

Explanation The filter contains an invalid escape character.

Action Make sure that the filter is valid and the syntax in the filter is correct.

BRC.JAVAAPI.205.1148E – The function '{func}' has the wrong number of parameters. {parse_msg}

Explanation The wrong number of parameters were passed to the <function> function.
Action Ensure that the filter string is valid and that the parameters passed to the functions used in the filter are correct.

BRC.JAVAAPI.205.1149E – Incomplete hint field. {parse_msg}

Explanation The filter string specified an incomplete hint field.
Action Verify that the filter string is valid and complete.

BRC.JAVAAPI.206.1160E – The filter operation resulted in a division by zero.

Explanation The filter operation could not complete. The evaluation of the filter expression at run time resulted in a division by zero.
Action Ensure that the filter string is valid and does not result in a division by zero condition while evaluating operands.

BRC.JAVAAPI.206.1161 – The operands are not of the same type and they cannot be promoted to be of the same type.

BRC.JAVAAPI.206.1162E – The document type does not match.

Explanation The document type of the passed document and the document type specified in the filter do not match.
Action Ensure that the passed document is of the same type as the one specified in the filter.

BRC.JAVAAPI.206.1163E – The value passed to '{func}' is not valid.

Explanation The value passed to <function> is not valid.
Action Ensure that the filter string is valid and passed with correct values for the parameters.

BRC.JAVAAPI.206.1164E – The filter result is not a boolean.

Explanation The filter string returned an error because the filter result is not a Boolean.
Action Ensure that the filter string evaluates to a Boolean value.

BRC.JAVAAPI.206.1165U – After completion, the filter had remaining stack entries.

Explanation The filter string syntax may be incorrect or the string itself may be invalid.

Action Ensure that the filter string is valid and syntactically correct.

BRC.JAVAAPI.206.1166E – The regular expression error '{regexp_error}' occurred while applying the filter.

Explanation The regular expression error <regExpError> occurred while applying the filter. The specified regular expression might be invalid or incorrect.

Action Ensure that the filter string is valid and that all specified regular expressions are correct.

BRC.JAVAAPI.206.1167E – A filter stack overflow has occurred.

Explanation The filter string might be invalid.

Action Ensure that the filter string is valid.

BRC.JAVAAPI.206.1168E – A filter stack underflow has occurred.

Explanation The filter string might be invalid.

Action Ensure that the filter string is valid.

BRC.JAVAAPI.206.1169E – An unexpected function was encountered while applying the filter.

Explanation The filter string might be invalid or might contain unsupported functions.

Action Ensure that the filter string is valid and contains only supported functions. For more information about supported functions, see the webMethods Broker API documentation for the Java client.

BRC.JAVAAPI.206.1170E – An unexpected operation was encountered while applying the filter.

Explanation The filter string might be invalid or might contain unsupported operations.

Action Ensure that the filter string is valid and contains only supported operations. For more information about supported functions, see the webMethods Broker API documentation for the Java client.

BRC.JAVAAPI.206.1171E – An unexpected type was encountered while applying the filter.

Explanation The specified filter may not be valid. An unexpected type was encountered while applying the filter.

Action Ensure that the specified filter is valid.

BRC.JAVAAPI.206.1172M – Invalid filter version was encountered.

Explanation A runtime error occurred due to a mismatch between filter compiler versions (internal to the filter engine) while parsing the specified filter.

Action Check that the specified filter string is valid. If the filter string is valid, contact Software AG Global Support for further assistance.

BRC.JAVAAPI.206.1173M – Invalid filter length was encountered

Explanation A runtime error occurred due to a mismatch between filter length on the compiled filter code (internal to the filter engine) while parsing the specified filter.

Action Check that the specified filter string is valid. If the filter string valid, contact Software AG Global Support for further assistance.

BRC.JAVAAPI.207.1180E – Error in parsing document bin string body header.

Explanation The bin string might be invalid.

Action Ensure that the bin string is valid and obtained from a valid BrokerEvent.

BRC.JAVAAPI.207.1181E – Error in parsing document bin string data.

Explanation The bin string may be invalid or might have been obtained from an invalid BrokerEvent.

Action Ensure that the bin string is valid and was obtained from a valid BrokerEvent.

BRC.JAVAAPI.207.1182E – Error in parsing document bin string envelope header.

Explanation The bin string may be invalid or might have been obtained from an invalid BrokerEvent.

Action Ensure that the bin string is valid and was obtained from a valid BrokerEvent.

BRC.JAVAAPI.207.1183E – Error parsing numeric value.

Explanation A numeric value was expected in the string representation.

Action Ensure that a proper number value is passed in the string.

BRC.JAVAAPI.207.1185E – The type definition typecode contained a format error.

Explanation The type definition typecode contained a format error.

Action Ensure that the type definition of the document is valid and syntactically correct.

BRC.JAVAAPI.207.1186 – The license string contains a format error.

BRC.JAVAAPI.208.1220E – Cannot acknowledge the requested document because the sequence number is out of order with respect to other unacknowledged documents.

Explanation The requested document cannot be acknowledged because the sequence number is out of order with other unacknowledged documents.

Action Acknowledge documents in order with other unacknowledged documents.

BRC.JAVAAPI.209.1230 – The client object has already been disconnected or destroyed.

BRC.JAVAAPI.209.1231E – The client is no longer valid because it has been destroyed by the Broker.

Explanation The client is no longer valid because it has been destroyed by the Broker.

Action Cannot complete the specified operation because the client is not valid and does not exist on the Broker.

BRC.JAVAAPI.210.1240 – Could not create or reconnect client. The client id '{client_id}' is not valid. Client IDs cannot contain unprintable characters, a colon, '@', '/', or '\ and can only begin with '#' when created by the Broker. They must be between 1 and 255 ANSI characters or 1 and 42 Unicode characters in length.

BRC.JAVAAPI.212.1261E – The document was not received from the Broker and has no publisher ID.

Explanation The document was not received from the Broker and does not have a publisher ID.

Action Ensure that the document originated from a valid source, for example, a Broker Client or from another Broker.

BRC.JAVAAPI.212.1263E – Document is not a properly formed document of its type. One or more fields do not match the document definition in the Broker.

Explanation The document is not in the expected format. One or more fields do not match the document definition in the Broker.

Action Ensure that the document is valid and matches the definition on the Broker.

BRC.JAVAAPI.213.1270E – The document name '{event_name}' contains an invalid character. Only alphanumeric characters, underscores, and characters above unicode 009F are allowed in parts of a document type name, and ':' can be used to separate parts.

Explanation The document name <docName> contains an invalid character. Only alphanumeric characters, underscores, and characters above Unicode 009F are allowed in parts of a document type name. ":" can be used to separate parts.

Action Ensure that the document name is valid and contains only supported characters.

BRC.JAVAAPI.213.1271E – The document name '{event_name}' contains an illegal character sequence. Names may contain ':' but not '.' or '::'

Explanation The document name <docname> contains an illegal character sequence. Names may contain ":" but not "." or "::"

Action Ensure that the document name is valid and properly formatted.

BRC.JAVAAPI.213.1272E – The document name '{event_name}' contains an invalid character at the start of a document name. A field name cannot start with a numeric character or an underscore.

Explanation The document name <docName> contains an invalid character at the start of a document name. A field name cannot start with a numeric character or an underscore.

Action Ensure that the document name is valid.

BRC.JAVAAPI.213.1273 – The document name '{event_name}' has an invalid length. Document names must be between 1 and 255 ANSI characters or 1 and 42 Unicode characters in length.

BRC.JAVAAPI.213.1274E – The document name '{event_name}' uses a reserved word.

Explanation The document name <docName> uses a reserved word.

Action Check the document name. Make sure it does not contain a reserved word.

BRC.JAVAAPI.213.1275E – The document name '{event_name}' has a part which is less than 1 character in length.

Explanation The document name <docName> contains a part that is of length 0 or 1. Parts must be at least 2 characters long.

Action Specify a valid document name.

BRC.JAVAAPI.213.1276E – The infoset name '{event_name}' contains an invalid character. Only alphanumeric characters, underscores, and characters above unicode 009F are allowed in an infoset name. Colons are not allowed.

Explanation The infoset name <eventName> contains an invalid character. Only alphanumeric characters, underscores, and characters above Unicode 009F are allowed in an infoset name. A colon is not a valid character.

Action Check the infoset name. Make sure it contains only supported characters.

BRC.JAVAAPI.214.1280E – The field name '{field_name}' contains a sequence index which was not closed with a ']' as expected.

Explanation The field name <fieldName> contains a sequence index that was not properly closed with a "]".

Action Check the field name. Make sure it is closed with a "]".

BRC.JAVAAPI.214.1281E – The field name '{field_name}' contains a sequence index with no numeric value in it at all.

Explanation The field name <fieldName> contains a sequence index that does not contain a numeric value.

Action Check the field name. Make sure it contains a numeric value.

BRC.JAVAAPI.214.1282E – The field name '{field_name}' contains an invalid character in the sequence index. The index must be a numeric value of zero or greater.

Explanation The field name <fieldName> contains an invalid character in the sequence index. The index must be a numeric value of zero or greater.

Action Check the field name. Make sure it contains a numeric value of zero or greater.

BRC.JAVAAPI.214.1283 – The field name '{field_name}' contains an invalid character. Only alphanumeric characters, underscores, '\$' and characters above unicode 009F are allowed in a field name.

BRC.JAVAAPI.214.1284E – Must specify a field name. A zero length string was provided.

Explanation A call to set the type definition of a field failed because no field name was specified or a zero length string was provided.

Action Check the field name. Make sure it is valid.

BRC.JAVAAPI.214.1285 – The field name '{field_name}' contains an invalid character at the start of a field name.

BRC.JAVAAPI.214.1286 – The field name '{field_name}' has an invalid length. Field names must be between 1 and 255 ANSI characters or 1 and 42 Unicode characters in length.

BRC.JAVAAPI.214.1287E – The field name '{field_name}' uses a reserved word.

Explanation The field name <fieldName> uses a reserved word.

Action Check the field name. Make sure it does not contain a reserved word.

BRC.JAVAAPI.214.1288 – The field '{field_name}' is not a valid envelope field.

BRC.JAVAAPI.214.1289E – The field '{field_name}' already exists, so you cannot rename a field to its name.

Explanation The field name <fieldName> already exists.

Action Choose a field name that does not already exist.

BRC.JAVAAPI.214.1722M – The field '{field_name}' already exists, so you cannot set a property with this name.

Explanation A field with the specified name already exists in the document. Field names in a document should be unique.

Action While setting properties, make sure to specify a field name that is not present in the document type.

BRC.JAVAAPI.216.1310E – The filter '{filter}' contains a parse error.

Explanation The specified filter contains a parse error.

Action Check the filter string. Ensure that it is valid.

BRC.JAVAAPI.216.1311E – The subscription is invalid. Perhaps the event_type_name is null.

Explanation The subscription is invalid. The event_type_name might be NULL.

Action Check the event_type_name. Make sure that it corresponds to a valid event type on the Broker and is not NULL.

BRC.JAVAAPI.216.1312 – Subscription IDs cannot be less than 0.

BRC.JAVAAPI.216.1313E – Cannot cancel the requested subscription because it does not exist.

Explanation The subscription does not exist on the Broker.

Action Check the subscriptions on the Broker. Ensure that the specified subscriptions are valid and exist on the Broker.

BRC.JAVAAPI.216.1314E – Failed to cancel {count} subscriptions because they do not exist.

Explanation The <count> subscriptions do not exist on the Broker.

Action Check the subscriptions on the Broker. Ensure that the specified subscriptions are valid and exist on the Broker.

BRC.JAVAAPI.216.1315E – The subscription is invalid. The character at position `{char_pos}` in the filter is not valid inside a hint.

Explanation The subscription is invalid. The character at position `<charPosition>` in the filter is not valid inside a hint.

Action Check the syntax of the hint. Make sure to follow the syntax for creating subscriptions.

BRC.JAVAAPI.216.1316E – The subscription is invalid. The subscription hint `{hint_value}` is not valid.

Explanation The subscription is invalid. The subscription hint `<hintValue>` is not valid.

Action Verify that the specified hint value is valid.

BRC.JAVAAPI.216.1317E – The subscription is invalid. The hint at position `{char_pos}` is missing its value.

Explanation The subscription is invalid. The hint at position `<charPosition>` is missing its value.

Action Check the syntax of the hint. Verify that the correct syntax is used for creating subscriptions.

BRC.JAVAAPI.216.1318E – The subscription is invalid. The subscription hint value `{hint_value}` is not valid for the hint at position `{char_pos}`.

Explanation The subscription is invalid. The subscription hint value `<hintValue>` is not valid for the hint at position `<charPosition>`.

Action Check the syntax of the hint. Verify that the correct syntax is used for creating subscriptions.

BRC.JAVAAPI.216.1319E – The subscription is invalid. The hint at position `{char_pos}` is missing its closing brace.

Explanation The subscription is invalid. The hint at position `<charPosition>` is missing its closing brace.

Action Check the syntax of the hint. Verify that the correct syntax is used for creating subscriptions.

BRC.JAVAAPI.216.2310E – The subscription is invalid. The hint at position `{char_pos}` is missing its `'hint:'` prefix.

Explanation The subscription is invalid. The hint at position `<charPosition>` is missing its `"hint"` prefix.

Action Check the syntax of the hint. Verify that the correct syntax is used for creating subscriptions.

BRC.JAVAAPI.216.2311 – The subscription is invalid. The hint at position `{char_pos}` is missing a comma delimiter.

BRC.JAVAAPI.217.1321E – Cannot get a field of type sequence using a basic get function. Use a sequence get function.

Explanation The client application attempted to use a basic get function to get a sequence type field, but only a sequence get function can be used for this purpose.

Action Use a sequence get function to get sequence fields from a BrokerEvent.

BRC.JAVAAPI.217.1322E – Cannot get a field of type sequence of sequence.

Explanation The client application attempted to get a "sequence of sequence" field as a simple sequence field type, which is not permitted.

Action Use a sequence get function to get "sequence of sequence" fields from a BrokerEvent.

BRC.JAVAAPI.217.1323E – Cannot set a field of type sequence using a basic set function. Use a sequence set function.

Explanation The client application tried to use a basic set function to assign a value to a sequence type field, but only a sequence set function can be used for this purpose.

Action Use the correct function for the field type. If you want to assign a value to a non-sequence field, use a basic set function. If you want to assign a value to a sequence field, use a sequence set function.

BRC.JAVAAPI.217.1324E – Cannot set a field of type sequence of sequence.

Explanation A client application tried to assign a value to a "sequence of sequence" field. A "sequence of sequence" is equivalent to an "array of arrays" or multi-dimensional array. You cannot assign a value to a "sequence of sequence" field using basic sequence set functions.

Action Use the correct function for the field type. If you want to assign a value to a basic sequence field, use a basic sequence set function. If you want to assign a value to a "sequence of sequence" field, use set sequence functions of appropriate type on individual members of the base sequence. For more information, see the webMethods Broker API documentation.

BRC.JAVAAPI.217.1325E – Cannot set a field to type sequence using the type setting functions.

Explanation The client application tried to use a basic set function (basic set <Field> API) to change a sequence type field to another type, but you must use setSeq<Type>Field API to do this.

Action Use the setSeq<Type>Field API instead.

BRC.JAVAAPI.217.1326E – The document contains data of an unsupported type.

Explanation The event contains data of an unsupported type.
Action Verify that the event is valid and contains supported data types.

BRC.JAVAAPI.217.1328E – The formatter encountered an unsupported data type. The field type is '{type}'. Perhaps a structure or sequence field is being used where it should not be.

Explanation One of the internal helper functions encountered an unsupported data type. The field type is <type>. Perhaps a structure or sequence field is being used where it should not be.
Action Ensure that the event is valid and contains supported data types.

BRC.JAVAAPI.217.1329E – An unsupported type was specified.

Explanation The Broker Client could not complete the requested operation because the specified field type is unknown or unsupported in the Broker Event.
Action Ensure that the specified type is supported.

BRC.JAVAAPI.217.1330E – Cannot get field names from an unstructured field.

Explanation A client application cannot get field names from an unstructured field.
Action To get field names, verify that the field specified by the "field_name" parameter is of type "struct" or "BrokerEvent".

BRC.JAVAAPI.217.1331E – The type definition code contains an unsupported type.

Explanation The type definition code contains an unsupported type.
Action Ensure that the type code is valid.

BRC.JAVAAPI.217.1332E – The type definition contains data of an unsupported type.

Explanation The type definition contains data of an unsupported type.
Action Ensure that the type definition is valid and contains supported types.

BRC.JAVAAPI.217.2300E – Only struct and document types are valid for this operation.

Explanation A client application tried to perform an operation on a field that is not of type "struct" or "document", but the requested operation can only work on those types of fields.
Action Specify a struct or BrokerEvent field name when creating a new document type, ordering the fields in a document type, or changing the name of a document.

BRC.JAVAAPI.217.2301E – Only document types are valid for this operation.

Explanation A client application tried to perform an operation that is supported only on a Broker Event. Only fields of type "Event" are supported for this type of operation.

Action Ensure that a typedef of "document" is specified when performing these operations.

BRC.JAVAAPI.217.2302E – Cannot rename the contents of sequence field, such as 'x[]', where the last part of the field name is a set of sequence brackets.

Explanation The client application tried to rename the contents of a sequence field, such as "x[]", where the last part of the field name is a set of sequence brackets. You cannot rename the contents of a sequence field.

Action Ensure that the rename request is not issued on the contents of a sequence field.

BRC.JAVAAPI.217.2303E – Cannot rename a field to become the contents of a sequence field, such as 'x[]', where the last part of the field name is a set of sequence brackets.

Explanation The client application tried to rename a field to become the contents of a sequence field, such as "x[]", where the last part of the field name is a set of sequence brackets. You cannot perform a rename to convert a non-sequence field to a sequence field.

Action Ensure that the rename request is not issued to convert a non-sequence field to a sequence field.

BRC.JAVAAPI.218.1340E – The type cache pointer is null or is not a type cache. Perhaps the variable is uninitialized or the client has been disconnected.

Explanation The type cache pointer is NULL or is not a type cache. Possible causes are that the variable is uninitialized or the client has been disconnected.

Action Ensure that the passed parameter of type "TypeDefCache" is valid, properly initialized, and not NULL.

BRC.JAVAAPI.219.1351E – The document was not created with a client and therefore has no type definition.

Explanation A client application tried to get the type definition from the document, but could not because the document was not created with a Broker Client and does not have a type definition.

Action Recreate the document as a typed document and associate it with a Broker Client.

BRC.JAVAAPI.219.1353E – Type definition top-level entry was not named.

Explanation A type definition top-level entry was not named.
Action Specify a top level type name when creating new type definitions.

BRC.JAVAAPI.219.1354E – Cannot look up definition for an unnamed type.

Explanation The Broker cannot look up a definition for an unnamed type.
Action Specify a valid type name for the look up operation.

BRC.JAVAAPI.219.1356E – The type `{type_name}` is not in the type cache.

Explanation The specified type is not found in the cache.
Action Ensure that the type exists on the Broker.

BRC.JAVAAPI.219.1357E – The document type `{type_name}` cannot be synchronized with the other territory because it does not exist in the other territory.

Explanation The Broker could not synchronize one of its document types (`<typeName>`) with the document type in another territory because the document type does not exist in the other territory.
Action Ensure that the document type is present on both territories before synchronizing them.

BRC.JAVAAPI.219.1358E – The document type `{type_name}` cannot be synchronized with the other territory because the document type's definition contains different fields.

Explanation The Broker could not synchronize one of its document types (`<typeName>`) with the document type in another territory because the definitions in the two territories are not the same.
Action Ensure that the type definition of document types present on both territories are the same.

BRC.JAVAAPI.219.1359 – The document type `{type_name}` cannot be synchronized with the other territory because the document type's storage type is different.**BRC.JAVAAPI.219.1959 – The document type `{type_name}` cannot be synchronized with the other cluster because it does not exist in the other cluster.**

BRC.JAVAAPI.219.1960 – The document type `$(type_name)` cannot be synchronized with the other cluster because the document type's definition contains different fields.

BRC.JAVAAPI.219.1961 – The document type `$(type_name)` cannot be synchronized with the other cluster because the document type's storage type is different.

BRC.JAVAAPI.219.1962 – The document type `$(type_name)` cannot be synchronized with the other cluster because the document type's validation is different.

BRC.JAVAAPI.219.1963 – The document type `$(type_name)` cannot be synchronized with the other cluster because the document type's time-to-live is different.

BRC.JAVAAPI.219.1964 – The document type `$(type_name)` cannot be synchronized with the other cluster because the document type's description is different.

BRC.JAVAAPI.219.1965 – The document type `$(type_name)` cannot be synchronized with the other cluster because the document type's infosets are different.

BRC.JAVAAPI.219.2350 – The document type `$(type_name)` cannot be synchronized with the other territory because the document type's time-to-live is different.

BRC.JAVAAPI.219.2351 – The document type `$(type_name)` cannot be synchronized with the other territory because the document type's description is different.

BRC.JAVAAPI.219.2352 – The document type `$(type_name)` cannot be synchronized with the other territory because the document type's infosets are different.

BRC.JAVAAPI.219.2353E – The document type `$(type_name)` cannot be stored in the Broker because its type definition is not valid.

Explanation Client Application tried to store a document on the Broker, but the document's type `<typeName>` does not have valid type definition.

Action Ensure that the type code specified is valid. For further assistance on creating document types, see the webMethods Broker API documentation.

BRC.JAVAAPI.219.2354 – The document type `{type_name}` cannot be converted because the reflect document is not type checked.

BRC.JAVAAPI.219.2355 – The document type `{type_name}` does not match the type def used by the reflect document.

BRC.JAVAAPI.219.2356E – The document type `{type_name}` cannot be synchronized with the other territory because the document type's validation is different.

Explanation The Broker could not synchronize one of its document types (<typeName>) with the document type in another territory because the document type's validation is not the same in the two territories.

Action Ensure that the document type <typeName> validation is present on both territories before synchronizing.

BRC.JAVAAPI.220.1400E – The input parameter '`{param}`' is null.

Explanation The input parameter <parameter> was null, but this operation requires input.

Action Ensure that the input parameters are allocated and initialized properly.

BRC.JAVAAPI.220.1402 – The value of instance member '`{param}`' is null.

BRC.JAVAAPI.221.1400M – The input parameter '`{field_name}`' is out of range.

Explanation An incorrect value was supplied when setting Territory Gateway permissions.

Action Supply the correct permission value(s).

BRC.JAVAAPI.221.1410E – Cannot set client share limit to a value of zero or less than -1.

Explanation The Broker client denied a request to set the shared state limit to zero or a negative value.

Action Specify a positive value as the shared state limit.

BRC.JAVAAPI.221.1411 – Cannot set forced reconnect option on a shared state client.

BRC.JAVAAPI.221.1412E – The value of 'flag' is not a legal value.

Explanation The Broker encountered a serious internal error.

Action Contact Software AG Global Support.

BRC.JAVAAPI.221.1413E – The value of 'max_n' must not be less than -1.

Explanation The specified "max_n" value is less than -1. A valid range is -1 to any +ve number.
Action Specify a valid value for "max_n" (≥ -1).

BRC.JAVAAPI.221.1414E – The value of 'msecs' must not be less than -1.

Explanation The specified "msecs" value for timeout is less than -1. A valid range is -1 to any +ve number.
Action Specify a valid value for "msecs" (≥ -1).

BRC.JAVAAPI.221.1415E – Cannot use a sequence number less than zero.

Explanation The specified sequence number is -ve. It cannot be less than 0.
Action Specify a valid sequence number (≥ 0).

BRC.JAVAAPI.221.1416E – Cannot set a sequence size to a value less than zero.

Explanation The specified sequence size is -ve. It cannot be less than 0.
Action Specify a valid sequence size (≥ 0).

BRC.JAVAAPI.221.1417E – The value of 'nc' must not be less than -1.

Explanation The specified input parameter "nc" contains an invalid value. It should not be < -1 .
Action Specify a valid value for "n".

BRC.JAVAAPI.221.1419E – A sequence index in field name '\${field_name}' is out of bounds.

Explanation The specified sequence index on a sequence field name is out of bounds (either < 0 or $>$ the actual length of the sequence)
Action Check the index in the field name. Ensure that it is within the bounds of the actual sequence length.

BRC.JAVAAPI.221.1420E – Offset must be between 0 and the actual length of the sequence.

Explanation The specified offset range is invalid. It should be between 0 and the actual length of the sequence.
Action Check the offset range. Ensure that it is valid.

BRC.JAVAAPI.221.1421E – Offset must be between 0 and the actual length of the string.

Explanation The specified range for the substring is invalid for a setStringField operation. The value must be ≥ 0 and $< \text{length}(\text{string})$.

Action Specify a valid range for the substring.

BRC.JAVAAPI.221.1422E – Subscription IDs cannot be less than 0.

Explanation A client tried to pass a negative number for the subscription ID.

Action Specify a positive value for the subscription ID.

BRC.JAVAAPI.221.1423E – Cannot use a sequence number less than -1.

Explanation A client tried to pass a negative number for the sequence number of an acknowledge operation.

Action Specify a positive value for the sequence number.

BRC.JAVAAPI.221.1425E – Time to live cannot be a negative number.

Explanation The time to live value cannot be negative.

Action Specify a positive value for time to live.

BRC.JAVAAPI.221.1426E – The storage type specified is not a valid value.

Explanation The specified value for storage type is not valid.

Action Specify a valid storage type while creating client groups and event types, for example, AW_STORAGE_VOLATILE and AW_STORAGE_GUARANTEED.

BRC.JAVAAPI.221.1427E – The lifecycle specified is not a valid value.

Explanation During a request to create a client, an invalid lifecycle was encountered. It should be within the range of the AW_LIFECYCLE_MIN and AW_LIFECYCLE_MAX values.

Action Specify a valid lifecycle value.

BRC.JAVAAPI.221.1428E – The lifecycle and storage type values specified is not a valid combination of values.

Explanation An attempt to create a client group failed because a storage type of Volatile or Guaranteed was not specified.

Action Specify either Volatile or Guaranteed as the storage type while creating client groups.

BRC.JAVAAPI.221.1429E – The input parameter '{field_name}' is less than zero.

Explanation A negative value was passed to the specified input parameter. This is not a valid value.

Action For a list of expected parameter values, see the webMethods Broker API documentation.

BRC.JAVAAPI.221.1430 – The specified priority is not valid. Valid priority values range from 0 to 9.

BRC.JAVAAPI.221.1726 – The index parameter is out of range.

BRC.JAVAAPI.221.1730 – The specified number of events to be peeked, are not in the queue.

BRC.JAVAAPI.221.1731 – The specified number of max_events is out of range.

BRC.JAVAAPI.221.1732 – The specified max_time is out of range.

BRC.JAVAAPI.221.1733 – The specified lock_id is out of range.

BRC.JAVAAPI.221.1781M – Territory gateway keep alive cannot be a negative number.

Explanation The supplied keep-alive parameters are out of range.

Action Supply the correct keep-alive parameters.

BRC.JAVAAPI.221.1783 – Invalid client keep alive setting.

BRC.JAVAAPI.221.1942 – Cannot join this Broker to the cluster because the cluster already has a Broker with the same name as this Broker.

BRC.JAVAAPI.221.1946 – Cannot remove the current Broker from the cluster with this operation.

BRC.JAVAAPI.221.1949 – Cannot create the gateway because a gateway already exists to the specified cluster.

BRC.JAVAAPI.221.1950 – Cannot create a gateway to the current cluster or to a cluster with the same name as the current cluster.

BRC.JAVAAPI.221.1952 – Cluster gateway keep alive cannot be a negative number.

BRC.JAVAAPI.221.1958 – The document type `$(type_name)` cannot be synchronized with the other cluster because it is a local-only document type.

BRC.JAVAAPI.221.1967 – Cannot create the primary cluster gateway because another primary gateway already exists to the specified cluster.

BRC.JAVAAPI.221.2420 – Index for insert must be between 0 and size-1 for existing fields.

BRC.JAVAAPI.221.2421E – Index for insert must be between 0 and size for new fields.

Explanation The specified index for the insert field operation is out of range. It should be between 0 and the number of fields.

Action Specify a valid index for the insert operation.

BRC.JAVAAPI.221.2422E – The specified log output value is not in the log configuration.

Explanation The specified log topic value is invalid. It should be one of the following:
AW_LOG_OUTPUT_UNIX_SYSLOG or AW_LOG_OUTPUT_NT_EVENT_LOG or
AW_LOG_OUTPUT_SNMP_TRAP.

Action Specify a valid topic value.

BRC.JAVAAPI.221.2423E – The specified log topic value is not in the log configuration.

Explanation The specified log topic value is invalid. It should be one of the following:
AW_LOG_TOPIC_ALERT or AW_LOG_TOPIC_WARNING or
AW_LOG_TOPIC_INFO.

Action Specify a valid topic value.

BRC.JAVAAPI.221.2424E – Cannot create client. The specified client group must have explicit destroy life cycle.

Explanation An attempt to create a Broker client failed because the client group does not have an explicit destroy life cycle.

Action Specify a client group that has an explicit destroy life cycle for clients that require redelivery count feature.

BRC.JAVAAPI.221.2425E – An invalid encryption level was specified.

- Explanation** The specified encryption level is invalid. It should be within the range of the AW_ENCRYPT_MIN and AW_ENCRYPT_MAX values.
- Action** Specify a valid encryption level while setting up security for the client group, territory, etc.

BRC.JAVAAPI.221.2426E – Cannot join this Broker to the territory because the territory already has a Broker with the same name as this Broker.

- Explanation** A request to join a Broker to a territory failed because a Broker with the same name already exists in the territory. Each Broker in a territory must have a unique name.
- Action** Ensure that the Broker has a unique name before joining the territory.

BRC.JAVAAPI.221.2427E – Cannot create the gateway because a gateway already exists to the specified territory.

- Explanation** A request to create a gateway failed because a gateway already exists between the specified territories.
- Action** Ensure that a gateway does not already exist between the two territories before issuing a create request. Only one gateway is allowed between two territories.

BRC.JAVAAPI.221.2428E – Cannot create a gateway to the current territory or to a territory with the same name as the current territory.

- Explanation** A client application tried to create a gateway specifying two territories with the same name.
- Action** Specify two different territories to create the gateway.

BRC.JAVAAPI.221.2429 – The document type `$(type_name)` cannot be synchronized with the other territory because it is a local-only document type.

BRC.JAVAAPI.221.3420 – Date cannot be represented in a Java date object.

BRC.JAVAAPI.221.3421 – The value of 'n' must not be less than -1.

BRC.JAVAAPI.221.3422 – Date cannot be represented in a Java calendar object.

BRC.JAVAAPI.221.3423E – An invalid transaction mode was specified.

Explanation	During a call to end a transaction, an invalid transaction mode was encountered. It should be within the range of the AW_TRANSACTION_MODE_MIN and AW_TRANSACTION_MODE_MAX values.
Action	Specify a valid transaction mode value.

BRC.JAVAAPI.221.3424E – Destination offset must be between -1 and the actual length of the sequence.

Explanation	The destination offset, which is used when packing a sequence in a BrokerEvent, is invalid. It should be between -1 and the actual length of the sequence.
Action	Ensure that the offset range is valid.

BRC.JAVAAPI.221.3425 – Cannot set the same document type twice in one operation.**BRC.JAVAAPI.221.3426 – Cannot set the same client group twice in one operation.****BRC.JAVAAPI.221.3427E – Cannot remove the current Broker from the territory with this operation.**

Explanation	The Broker tried to remove itself from the Territory.
Action	Issue the remove request from a different Broker.

BRC.JAVAAPI.221.3429E – The shared document ordering value in the client's descriptor is not a valid value for this Broker.

Explanation	The specified value for shared document ordering is invalid.
Action	Specify a valid shared document ordering value in the client creation calls, for example, "None" or "Publisher".

BRC.JAVAAPI.221.3430E – The shared document ordering value must not contain spaces or unprintable characters.

Explanation	The ordering value for the specified document contains spaces or unprintable characters.
Action	Specify a valid value for the document ordering specification.

BRC.JAVAAPI.221.3431E – An invalid authentication type was specified.

Explanation	While setting up territory/gateway security, the client application specified an invalid authentication type. It should be within the range of the AW_AUTH_TYPE_MIN and AW_AUTH_TYPE_MAX values.
Action	Specify a valid authentication type when setting up security.

BRC.JAVAAPI.221.3432E – An access control list for a gateway cannot consist of more than one user name or more than one authenticator name.

Explanation An attempt was made to specify more than one user name or authenticator name in the ACL list for a gateway.

Action Specify only one user name and authenticator name in the access control list.

BRC.JAVAAPI.221.3433 – A shared document type for a gateway does not have accept_subscribe set to true, but has a non-empty filter set.

BRC.JAVAAPI.221.3434 – Duplicate sequence number was specified.

BRC.JAVAAPI.221.3435 – Invalid sequence number was passed in.

BRC.JAVAAPI.221.3436 – Invalid validation type specified.

BRC.JAVAAPI.221.3437M – The specified prepare timeout is out of range.

Explanation An incorrect timeout value for the transaction was specified when setting the transaction default.

Action Supply the correct timeout value: -1, 0 or a positive number.

BRC.JAVAAPI.221.3438M – The specified prepare timeout action is not valid.

Explanation An incorrect timeout action for the transaction was specified when setting the transaction default.

Action Supply the correct transaction timeout action (commit or rollback).

BRC.JAVAAPI.221.3439M – The specified transaction type is invalid.

Explanation An invalid parameter was supplied to the Broker when attempting to list the current transactions.

Action Supply the correct operation parameters.

BRC.JAVAAPI.221.3440M – The specified transaction operation is invalid.

Explanation An invalid operation was specified when attempting to forcefully end a transaction from an administrative tool.

Action Supply the correct operation parameters.

BRC.JAVAAPI.222.1440 – A subscription with the same document type name and filter already exists.

BRC.JAVAAPI.223.1460E – No Broker by the name '{broker}' was found on host '{host}:{port}'.

Explanation Broker could not complete the operation because the specified Broker is not found on the host <hostName>:<portNum>.

Action Ensure that the specified Broker exists on the Broker Server.

BRC.JAVAAPI.223.1461E – No default Broker was found on host '{host}:{port}'.

Explanation The Broker could not create the client because a default Broker is not defined on the Broker Server.

Action Assign a default Broker to the Broker Server and use the Broker name explicitly while creating clients.

BRC.JAVAAPI.223.1462E – Territory join failed. No Broker by the name '{broker}' was found on host '{host}:{port}'.

Explanation An attempt to join a Broker to a territory failed because the specified Broker does not exist on the Broker Server.

Action Ensure that a Broker with the specified name exists on the Broker Server and reissue the territory join request.

BRC.JAVAAPI.223.1463E – There is no Broker in the territory by the name '{broker}' on host '{host}:{port}'.

Explanation Broker could not complete the operation because Broker <brokerName> does not exist in the territory.

Action Ensure that a Broker with the specified name exists in the territory.

BRC.JAVAAPI.223.1464E – Territory join failed. Must specify a specific Broker to join to. You cannot join to the default Broker.

Explanation The join operation could not be completed because the target Broker was not specified.

Action Specify the target Broker for the join operation. Ensure that the target Broker is already a member of the territory.

BRC.JAVAAPI.223.1465M – No Territory or Gateway Broker was found with the specified name.

Explanation An invalid or non-existent remote broker name was specified for the check and restart forwarding operation.

Action Ensure that the specified remote Broker name corresponds to one of the territory Brokers.

BRC.JAVAAPI.223.1935 – Cluster join failed. No Broker by the name '{broker}' was found on host '{host}:{port}'.

BRC.JAVAAPI.223.1945 – There is no Broker in the cluster by the name '{broker}' on host '{host}:{port}'.

BRC.JAVAAPI.224.1470E – Could not create client. Client group '{group}' was not found on the Broker.

Explanation Client Application could not complete the create operation because the specified client group does not exist on the Broker.

Action Ensure that the specified client group exists on the Broker.

BRC.JAVAAPI.224.1471E – Could not complete operation. Client group '{group}' was not found on the Broker.

Explanation Client Application could not complete the operation because the specified client group does not exist on the Broker.

Action Ensure that the specified client group exists on the Broker.

BRC.JAVAAPI.225.1480E – Could not reconnect client. Client '{client_id}' does not exist.

Explanation The Broker could not reconnect the client because the specified client ID cannot be found on the Broker.

Action Ensure that the client is valid and a client with the specified name exists on the Broker. Reissue the reconnect request.

BRC.JAVAAPI.225.1481E – Could not complete operation. Client '{client_id}' does not exist.

Explanation The Broker could not complete the operation because the client with the specified client ID does not exist on the Broker.

Action Ensure that the client with the specified client ID exists on the Broker.

BRC.JAVAAPI.226.1490E – Document type '{etype}' is not defined in the Broker.

Explanation The Broker could not complete the operation because the specified document type does not exist on the Broker.

Action Ensure that the specified document type is defined on the Broker.

BRC.JAVAAPI.226.1491 – There is no document type folder named '{scope_name}' defined in the Broker.

BRC.JAVAAPI.227.1500E – There is no infoset named '{infoset_name}' defined on document type '{etype}' in the Broker.

Explanation The Broker could not complete the infoset operation because the specified infoset name could not be found on the Broker.

Action Ensure that the specified infoset exists on the Broker and re-issue the infoset related API calls.

BRC.JAVAAPI.227.1501 – One or more of the infosets specified on the event type '{etype}' were not found in the Broker.

BRC.JAVAAPI.228.1510E – There is no platform key named '{key}' defined.

Explanation Platform information could not be obtained for the specified platform key because the key is not present in the platform information.

Action Check the platform key. Ensure that the key is valid before requesting the platform information.

BRC.JAVAAPI.229.1520E – A certificate for the provided distinguished name is not available in the certificate file '{cert_file}'.

Explanation A client application could not set SSL on the Broker Server because the specified distinguished name does not exist in the certificate file.

Action Ensure that the specified distinguished name is valid and present in the certificate file.

BRC.JAVAAPI.230.1530 – Cannot create Broker. The Broker '{broker}' already exists.

BRC.JAVAAPI.231.1540E – Cannot create client group. The client group '{group}' already exists on the Broker.

Explanation A client group named <clientgroupName>already exists on the Broker.

Action Use a unique name for the client group.

BRC.JAVAAPI.232.1550 – Operation failed because of a dependency.

BRC.JAVAAPI.232.1551E – Client group destroy failed. The client group has existing clients which should be destroyed first.

Explanation The destroy client group operation failed. The Broker client group has existing clients that must be destroyed first.

Action Remove the clients from the client group and then reissue the client group destroy request.

BRC.JAVAAPI.232.1552E – Document type destroy failed. The document type has client groups which can publish or can subscribe to the type. These permissions should be removed first.

Explanation The destroy document type operation failed. There is at least one client group that has "can publish" or "can subscribe" permissions assigned to this document type.

Action Remove all the "can publish" or "can subscribe" permissions for this document type and then reissue the document type destroy request.

BRC.JAVAAPI.233.1560 – `{parse_msg}`, line `{line_number}` column `{column_number}`.

BRC.JAVAAPI.234.1570E – The Broker cannot join a territory because it is already in a territory.

Explanation The Broker cannot join a territory because it already belongs to a territory.

Action Verify that the current Broker does not already exist as part of a territory.

BRC.JAVAAPI.234.1571E – The Broker cannot be destroyed while it is in a territory with other Brokers. It must leave the territory first.

Explanation A request to destroy the Broker failed because it is still in a territory with other Brokers.

Action You cannot destroy a Broker while it exists in a territory with other Brokers. Remove it from the territory, then retry this operation.

BRC.JAVAAPI.234.1933 – The Broker cannot join a cluster because it is already in a cluster.

BRC.JAVAAPI.234.1934 – The Broker cannot be destroyed while it is in a cluster with other Brokers. It must leave the cluster first.

BRC.JAVAAPI.235.1580E – The DN access list contained invalid values.

Explanation The distinguished names access list contained invalid values.

Action Ensure that the distinguished names access list contains valid values that are properly formatted.

BRC.JAVAAPI.236.1590E – The Broker name '{broker}' is not valid. Broker names cannot contain unprintable characters, a colon, '@', '/', or \ and they cannot start with a '#' symbol. They must be between 1 and 255 ANSI characters or 1 and 42 Unicode characters in length.

Explanation The Broker name <brokerName> is not valid. Broker names cannot contain unprintable characters (":", "@", "/", or "\"), and they cannot start with the "#" symbol. They must be between 1 and 255 ANSI characters or 1 and 42 Unicode characters in length.

Action Ensure that the Broker name is valid and contains only supported characters.

BRC.JAVAAPI.237.1600E – The client group name '{group}' is not valid. Client group names cannot contain unprintable characters, a colon, '@', '/', or \ and they cannot start with a '#' symbol. They must be between 1 and 255 ANSI characters or 1 and 42 Unicode characters in length.

Explanation The client group name <group> is not valid. Client group names cannot contain unprintable characters (":", "@", "/", or "\"), and they cannot start with the "#" symbol. They have to be between 1 and 255 ANSI characters or 1 and 42 Unicode characters in length.

Action Ensure that the client group name is valid and contains only supported characters.

BRC.JAVAAPI.238.1610 – The license string specified is not valid.

BRC.JAVAAPI.238.1611 – The license file specified is not valid.

BRC.JAVAAPI.239.1620E – Could not set one or more log configurations. The following configuration names are not recognized by the Broker: {name}.

Explanation The Broker did not recognize the configuration names specified in <brokerName>.

Action Check the configuration name. Ensure that it is valid and supported by the Broker.

BRC.JAVAAPI.240.1630E – Could not create or reconnect client. The application name '{name}' is not valid.

Explanation The specified application name is not valid. It may contain one or more non-printable characters.

Action Check the application name. Ensure that it contains valid characters.

BRC.JAVAAPI.240.1631E – Could not set log entry. The name '{name}' is not a valid log entry code. It cannot contain spaces or unprintable characters.

Explanation The Broker Server Client could not set a log entry. The name <name> is not a valid log entry code. It contains spaces or unprintable characters.

Action Verify that the log entry code contains only valid characters.

BRC.JAVAAPI.241.1640 – The permissions contained an invalid setting.

BRC.JAVAAPI.242.1650E – Could not set the platform info. The key '{key}' is not valid.

Explanation The platform information key could not be set on the Broker Client. The key may contain invalid or restricted characters.

Action Specify a valid platform information key.

BRC.JAVAAPI.243.1660E – The port {port} is not a valid port on the host.

Explanation Port <portNum> is not a valid port on the Broker host.

Action Specify a valid port number.

BRC.JAVAAPI.243.1661E – The port '{port}' is not a valid port on the host because it contains invalid characters.

Explanation Port <portNum> is not a valid port number because it contains invalid or restricted characters.

Action Specify a valid port number.

BRC.JAVAAPI.244.1670E – The territory name '{territory}' is not valid. Territory names cannot contain unprintable characters, a colon, '@', '/', or '\ and they cannot start with a '#' symbol. They must be between 1 and 255 ANSI characters or 1 and 42 Unicode characters in length.

Explanation The specified territory name contains invalid or unsupported characters.

Action Verify that the specified territory name is valid and follows the rules outlined in the webMethods Broker API documentation.

BRC.JAVAAPI.244.1930 – The cluster name '{cluster}' is not valid. Cluster names cannot contain unprintable characters, a colon, '@', '/', or '\ and they cannot start with a '#' symbol. They must be between 1 and 255 ANSI characters or 1 and 42 Unicode characters in length.

BRC.JAVAAPI.245.1680E – Could not complete the operation. The Broker is not a member of a territory.

Explanation The requested territory operation could not complete because the Broker does not belong to a territory.

Action Ensure that the current Broker is a member of a territory before attempting this territory operation.

BRC.JAVAAPI.245.1681E – Territory join failed. The remote Broker is not a member of a territory.

Explanation The territory join request failed because the remote Broker is not a member of a territory.

Action Retry the territory join operation after making the remote Broker a member of a territory.

BRC.JAVAAPI.245.1931 – Could not complete the operation. The Broker is not a member of a cluster.

BRC.JAVAAPI.245.1932 – Cluster join failed. The remote Broker is not a member of a cluster.

BRC.JAVAAPI.247.1700E – Could not complete the operation. No server is configured on port \${port}.

Explanation The Broker Server operation could not complete because there is no Broker Server configured on the specified port. The monitor process may be running on the host, but a Broker Server is not configured.

Action Ensure that the Broker Server on the specified host:port is started before issuing any Broker Server operations.

BRC.JAVAAPI.248.1710E – Could not complete the operation. The session \${session_id} does not exist for client \${client_id}.

Explanation The disconnect operation could not complete because the specified session ID does not exist on the Broker client. The session may already be closed or it may not exist.

Action Ensure that a session with the specified session-ID exists on the Broker client before issuing a disconnect request.

BRC.JAVAAPI.249.1720E – Could not create the gateway. The specified Broker is not a member of territory '\${terr_name}'.

Explanation The gateway could not be created because the specified territory does not exist on the Broker or the specified Broker is not a member of the territory.

Action Ensure that the Broker and the territory exist and the Broker is a member of the territory.

BRC.JAVAAPI.249.1721E – There is no gateway defined on the current Broker that connects to territory '\${terr_name}'.

Explanation The requested gateway operation could not complete because the gateway on the specified territory does not exist on the Broker.

Action Ensure that the gateway in the specified territory exists on the current Broker.

BRC.JAVAAPI.249.1947 – Could not create the gateway. The specified Broker is not a member of cluster `'${cluster_name}'`.

BRC.JAVAAPI.249.1951 – There is no gateway defined on the current Broker that connects to cluster `'${cluster_name}'`.

BRC.JAVAAPI.250.1723 – The specified client queue is already locked.

BRC.JAVAAPI.250.1724 – The specified client queue's lock is held by another client.

BRC.JAVAAPI.250.1725 – The specified client queue's state is bad.

BRC.JAVAAPI.250.1727 – The specified `lock_id` is invalid.

BRC.JAVAAPI.250.1728 – The specified client's queue is not locked.

BRC.JAVAAPI.250.1729 – The specified filter string is invalid.

BRC.JAVAAPI.250.1734 – The specified client queue is locked.

BRC.JAVAAPI.250.1735 – Cannot insert one or more documents. Permission is denied. Check the 'can subscribe' permissions in the target client's client group.

BRC.JAVAAPI.250.1736 – Duplicate client id was specified.

BRC.JAVAAPI.250.1737 – Duplicate `lock_id` was specified.

BRC.JAVAAPI.251.1640M – You do not have permission to do the current operation on the specified transaction.

Explanation You do not have permission to end or finalize the transaction.

Action You must end the transaction from the correct client.

BRC.JAVAAPI.251.1740M – The specified transaction is already prepared.

Explanation The specified transaction was already prepared.

Action No action required because the specified transaction is already in the desired state.

BRC.JAVAAPI.251.1741 – The specified transaction is unknown.

BRC.JAVAAPI.251.1742 – The specified transaction is closed.

BRC.JAVAAPI.251.1743 – There is client mismatch in the current transaction.

BRC.JAVAAPI.251.1744 – The specified transaction is not open.

BRC.JAVAAPI.251.1745M – The transaction is not in the appropriate state for the requested operation.

Explanation The specified transaction is not in a state where the attempted operation is allowed.

Action Apply the correct operation to the current state, for example, a prepared transaction cannot be reopened, but it can be committed or rolled back.

BRC.JAVAAPI.251.1746M – The transaction has been heuristically committed.

Explanation The transaction can not be completed because the Broker's transaction manager heuristically completed it already.

Action Examine the Broker's transaction manager's list of heuristically (lost) transactions and possibly purge this transaction from the list. Also, consult the Transaction Coordinator to commit this transaction.

BRC.JAVAAPI.251.1747M – The transaction has been heuristically rolled back.

Explanation The transaction can not be completed because the Broker's transaction manager heuristically rolled it back already.

Action Examine the Broker's transaction manager's list of heuristically (lost) transactions and possibly purge this transaction from the list. Also, consult the Transaction Coordinator to roll back this transaction.

BRC.JAVAAPI.251.1748M – The specified transaction cannot be reopened.

Explanation The transaction is not in a state where it can be reopened.

Action The transaction could have been created by a different client, or it could have been prepared. Apply the correct operation to the transaction.

BRC.JAVAAPI.251.1749M – There is an invalid value in the current transaction.

Explanation An invalid value was supplied when trying to end, prepare, commit, or rollback a transaction.

Action Supply the correct value for the API call.

BRC.JAVAAPI.251.1750M – The specified transaction id is not valid.

Explanation The supplied transaction identifier is not recognized by the Broker's transaction manager.

Action Supply the correct transaction identifier.

BRC.JAVAAPI.251.1762M – The transaction time out value specified is invalid.

Explanation An incorrect timeout value for the transaction was specified when creating a new transaction.

Action Supply the correct timeout value: -1, 0 or a positive number.

BRC.JAVAAPI.251.1763M – The specified transaction already exists.

Explanation A transaction with the specified external identifier already exists in the Broker's transaction manager.

Action Choose a different external identifier for your transaction.

BRC.JAVAAPI.251.1764 – The specified transaction already exists heuristically.

BRC.JAVAAPI.252.1751 – No valid Brokers available on the territory for the cluster operation.

BRC.JAVAAPI.252.1752 – Broker \${broker} is not found in the cluster publisher's Broker client pool.

BRC.JAVAAPI.252.1753 – Broker \${broker} is already found in the cluster publisher's Broker client pool.

BRC.JAVAAPI.252.1754 – BrokerClusterPublisher is not supported on this version of Broker.

BRC.JAVAAPI.252.1755 – publish/deliver request and wait operation failed.

BRC.JAVAAPI.252.1756 – Cannot include Broker `{broker}`. It was not previously excluded from the cluster operations.

BRC.JAVAAPI.252.1757 – Cannot exclude the last single client from the cluster publisher's Broker client pool.

BRC.JAVAAPI.274.1760E – A manual increment of a redelivery count was attempted for a client that has automatic increments enabled.

Explanation A client application attempted to manually increment the redelivery count when the redelivery count mode is automatic.

Action Ensure that the redelivery count mode is set to manual before attempting changes on the redelivery count.

BRC.JAVAAPI.274.1761M – Could not complete operation. A request to check or get events already exists.

Explanation A request to check for events cannot be issued as there already exists a pending get events request on the Broker from this client session.

Action Reissue the request after the get events request is served by the Broker.

BRC.JAVAAPI.274.1809 – Could not complete operation. An active queue browser is open on this client session.

BRC.JAVAAPI.277.1770 – Cannot increment the redelivery count of the requested document because the sequence number `{seqn}` does not correspond to any unacknowledged document.

BRC.JAVAAPI.277.1771E – Cannot negatively acknowledge requested document because the sequence number or numbers do not correspond to any unacknowledged document.

Explanation A client attempted to negatively acknowledge an event that was not returned from the Broker or the document was already acknowledged

Action Ensure that the event is valid and not yet acknowledged on the Broker before attempting a negative acknowledgement.

BRC.JAVAAPI.277.1772 – Cannot negatively acknowledge requested document because the a duplicate sequence number or numbers was provided.

BRC.JAVAAPI.277.1773 – Invalid sequence number was passed in.

BRC.JAVAAPI.278.1780E – Cannot increment redelivery counts for a client that does not have redelivery counting enabled.

Explanation A client attempted to update the redelivery count when this feature was not enabled on the Broker.

Action Ensure that the redelivery count mode is enabled before attempting changes on the redelivery count.

BRC.JAVAAPI.279.1782M – One or more of the operations are not valid poll operations.

Explanation An invalid Broker client poll operation was specified.

Action Supply the correct Broker client poll operation. The only valid Broker client poll operation is BrokerClientPoll.GET_EVENTS.

BRC.JAVAAPI.280.2035M – Backup is in progress on another session.

Explanation Backup is in progress on another session. Only one active backup session is supported.

Action Ensure that there is no other session performing metadata backup and reissue the backup request.

BRC.JAVAAPI.280.2036 – Backup is only supported on Broker servers with split meta-data and runtime data.

BRC.JAVAAPI.281.1801 – Queue browser has been already closed or invalid.

BRC.JAVAAPI.281.1802M – The client queue/ forward queue has been already locked by this client.

Explanation An attempt was made to reacquire the queue lock of a client that is already locked by this client session.

Action Ensure that the client queue is unlocked before opening a locked queue browser.

BRC.JAVAAPI.281.1803 – The client queue/ forward queue is already locked.

BRC.JAVAAPI.281.1804M – The queue already has an open queue browser session from this client.

Explanation An attempt was made to open a queue browser on a client for which a queue browser already exists on the current client session.

Action Ensure that there is no queue browser open on the desired target client queue before issuing an open queue browser request.

BRC.JAVAAPI.281.1806 – The queue is exhausted, no more events to return.

BRC.JAVAAPI.281.1807 – Attempt to replace a queued event of sequence number '{seqn}' with an event of different storage type. Events of different storage type cannot be replaced.

BRC.JAVAAPI.281.1808M – The operation failed because the queue is busy. Please retry your operation.

Explanation Could not complete the operation because the client queue is busy (serving an asynchronous request or clearing the queue).

Action Retry the operation after a few seconds.

BRC.JAVAAPI.281.1810 – Attempt to replace an unacked event of sequence number '{seqn}'. Unacked events cannot be modified.

BRC.JAVAAPI.281.1812M – The operation failed because the event at the cursor position was removed. Please retry after setting the cursor to a valid queue position.

Explanation A request to browse the client queue was rejected because the last set queue position on the browser got invalidated as the event in that position got removed from the queue.

Action Set the queue position to a valid position and retry the browse operation.

BRC.JAVAAPI.281.1813 – The target Client/Remote Broker is no longer valid because it has been destroyed by the Broker.

BRC.JAVAAPI.281.3434 – Duplicate sequence number '{seqn}'.

BRC.JAVAAPI.281.3435 – Invalid sequence number '{seqn}'.

BRC.JAVAAPI.282.1310 – The filter '{filter}' contains a parse error.

BRC.JAVAAPI.282.1315M – The filter is invalid. The character at position {char_pos} in the filter is not valid inside a hint.

Explanation Specified filter is invalid because an invalid character was specified in a hint.

Action Ensure that the filter hint contains valid characters.

BRC.JAVAAPI.282.1316M – The filter is invalid. The hint '{hint_value}' is not valid.

Explanation Specified filter is invalid because it contains an invalid hint.
Action Ensure that the filter hint is valid.

BRC.JAVAAPI.282.1317M – The filter is invalid. The hint at position \${char_pos} is missing its value.

Explanation Specified filter is invalid because the hint is missing its value.
Action Ensure that the filter hint is valid.

BRC.JAVAAPI.282.1318M – The filter is invalid. The hint value '{hint_value}' is not valid for the hint at position \${char_pos}.

Explanation The specified filter is invalid because the value specified for the hint is invalid.
Action Ensure that the filter hint value is valid.

BRC.JAVAAPI.282.1319M – The filter is invalid. The hint at position \${char_pos} is missing its closing brace.

Explanation Specified filter is invalid because of the invalid syntax of the hint.
Action Ensure that the filter hint is valid.

BRC.JAVAAPI.282.2310 – The filter is invalid. The hint at position \${char_pos} is missing its 'hint:' prefix.

BRC.JAVAAPI.282.2311M – The filter is invalid. The hint at position \${char_pos} is missing a comma delimiter.

Explanation Specified filter is invalid because of the invalid syntax of the hint.
Action Ensure that the filter hint is valid.

BRC.JAVAAPI.291.1901 – Invalid keystore type '{value}'. The keystore type must be PKCS12, PEM or null.

BRC.JAVAAPI.291.1902 – Invalid truststore type '{value}'. The truststore type must be PEM, DIR or null.

BRC.JAVAAPI.291.1903 – Invalid SSL protocol type '{value}'. The SSL protocol must be ALL, SSLv3 or TLSv1.

BRC.JAVAAPI.291.1904 – Invalid verify depth '{value}'. The verify depth must be ≥ 0 .

BRC.JAVAAPI.291.1905 – The keystore is null.

BRC.JAVAAPI.291.1906 – The truststore is null.

BRC.JAVAAPI.291.1909 – Unable to read keystore '{value}' due to file format problems.

BRC.JAVAAPI.291.1910 – Unable to read truststore '{value}' due to file format problems.

BRC.JAVAAPI.291.1911 – SSL is not initialized on the server.

BRC.JAVAAPI.291.1913 – The truststore '{value}' is not a regular file and truststore type is PEM.

BRC.JAVAAPI.291.1914 – The truststore '{value}' is not a directory and truststore type is DIR.

BRC.JAVAAPI.291.1915 – Unable to access the truststore '{value}' due to an OS error on the server.

BRC.JAVAAPI.291.1916 – Unable to load a certificate from the keystore: '{value}'.

BRC.JAVAAPI.291.1917 – The keystore '{value}' is not a regular file.

BRC.JAVAAPI.291.1918 – Unable to access the keystore '{value}' due to an OS error on the server.

BRC.JAVAAPI.291.1919 – Unable to load certificates from the truststore '{value}'.

BRC.JAVAAPI.291.1920 – Unable to use certificate from the keystore '{value}'.

BRC.JAVAAPI.291.1921 – Unable to setup certificate chain from the keystore '{value}'.

BRC.JAVAAPI.291.1922 – Unable to use private key from the keystore '{value}'.

BRC.JAVAAPI.291.1923 – Unable to load certificate from the keystore '{value}'.

BRC.JAVAAPI.291.1924 – Unable to open keystore file '{value}'.

BRC.JAVAAPI.291.1925 – Unable to interpret keystore file '{value}'. Verify that the correct keystore type and password were supplied.

BRC.JAVAAPI.291.1926 – Unable to parse keystore file '{value}'. Verify that the correct password was supplied.

BRC.JAVAAPI.291.1927 – File format problem. Cannot read the Certificate Revocation List file '{value}'.

BRC.JAVAAPI.291.1928 – Invalid file path. Cannot load the Certificate Revocation List file '{value}'.

BRC.JAVAAPI.291.1929 – Invalid Certificate Revocation List (CRL) type '{value}'. The CRL type must be PEM or DER.

BRC.JAVAAPI.292.2200 – Unable to access keystore: '{keystore}'. Error: {nestedException}

BRC.JAVAAPI.292.2201 – Keystore returns no such algorithm when accessing: '{keystore}'. Error: {nestedException}

BRC.JAVAAPI.292.2202 – I/O error while accessing: '{keystore}'. Error: {nestedException}

BRC.JAVAAPI.292.2203 – Certificate error while accessing: '{keystore}'. Error: {nestedException}

BRC.JAVAAPI.293.2400 – The attempt to join the territory at host '{host}:{port}' encountered an SSL handshake failure. Check the certificates and truststores for both Broker servers.

BRC.JAVAAPI.293.2401 – The attempt to join the cluster at host '{host}:{port}' encountered an SSL handshake failure. Check the certificates and truststores for both broker servers.

BRC.JAVAAPI.294.2500 – The attempt to create a gateway with host '{host}:{port}' encountered an SSL handshake failure. Check the certificates and truststores for both Broker servers.

BRJ.100.1001 Unable to bind "{0}". JMS Exception: {1}
Explanation A JMS exception occurred while trying to bind the specified object.
Action Check the details in the exception message and take appropriate action.

BRJ.100.1002 Unable to bind "{0}". JNDI Exception: {1}
Explanation A JNDI exception occurred while trying to bind the specified object.
Action Check the details in the exception message and take appropriate action.

BRJ.100.1003 Unable to bind "{0}". Broker Exception: {1}
Explanation An exception occurred in Broker while trying to bind the specified object.
Action Check the details in the exception message and take appropriate action.

BRJ.100.1005 Unable to bind "{0}". "{1}" was not found.
Explanation The required parameter is not found while trying to bind the specified object.
Action Check the details in the exception message and provide the required parameter.

BRJ.100.1006 Unable to bind "{0}". It is already bound into the name server.
Explanation The specified object is already bound.
Action Check the details in the exception message and take appropriate action.

BRJ.100.1007	Unable to bind "{0}". "{1}" is not a Context.
Explanation	The specified Context is not correct.
Action	Check the details in the exception message and provide the correct Context.
BRJ.100.1008	Unable to bind "{0}". Missing required TopicName property.
Explanation	TopicName property value is not provided.
Action	Provide the TopicName property value.
BRJ.100.1009	Unable to bind "{0}". Missing required QueueName property.
Explanation	QueueName property value is not provided.
Action	Provide the QueueName property value.
BRJ.100.1016	Unable to modify "{0}". The current object is not a webMethods Topic object or is an incompatible version of a Topic. Object class is "{1}"
Explanation	Cannot modify a non-webMethods Topic object or a Topic belonging to an incompatible version.
Action	Specify the correct Topic.
BRJ.100.1018	Unable to modify "{0}". The current object is not a webMethods TopicConnectionFactory object or is an incompatible version of a TopicConnectionFactory. Object class is "{1}"
Explanation	Cannot modify a non-webMethods TopicConnectionFactory object or a TopicConnectionFactory belonging to an incompatible version.
Action	Specify the correct TopicConnectionFactory.
BRJ.100.1020	Unable to modify "{0}". The current object is not a webMethods Queue object or is an incompatible version of a Queue. Object class is "{1}"
Explanation	Cannot modify a non-webMethods Queue object or a Queue belonging to an incompatible version.
Action	Specify the correct Queue.
BRJ.100.1022	Unable to modify "{0}". The current object is not a webMethods QueueConnectionFactory object or is an incompatible version of a QueueConnectionFactory. Object class is "{1}"
Explanation	Cannot modify a non-webMethods QueueConnectionFactory object or a QueueConnectionFactory belonging to an incompatible version.
Action	Specify the correct QueueConnectionFactory.

BRJ.100.1044	Not connected to a JNDI provider; the Bind command is not allowed.
Explanation	There is no connection to a JNDI provider.
Action	Make sure that the connection to the JNDI provider is available before executing the Bind command.
BRJ.100.1066	Unable to bind "{0}". Queue name cannot be an empty string.
Explanation	The Queue name cannot be an empty string.
Action	Provide a correct Queue name.
BRJ.100.1067	Unable to bind "{0}". Topic name cannot be an empty string.
Explanation	The Topic name cannot be an empty string.
Action	Provide a correct Topic name.
BRJ.100.1068	Unable to modify "{0}". The current object is not a webMethods ConnectionFactory object or is an incompatible version of a ConnectionFactory. Object class is "{1}"
Explanation	Cannot modify a non-webMethods ConnectionFactory object or a ConnectionFactory belonging to an incompatible version.
Action	Specify the correct ConnectionFactory.
BRJ.101.1002	Unable to change context to "{0}". JNDI Exception: {1}
Explanation	A JNDI exception occurred while trying to change context.
Action	Check the details in the exception message and take appropriate action.
BRJ.101.1007	Unable to change context to "{0}". "{1}" is not a Context.
Explanation	The specified object is not a Context.
Action	Check the details in the exception message and take appropriate action.
BRJ.101.1044	Not connected to a JNDI provider; the Change Context (cd) command is not allowed.
Explanation	There is no connection to the JNDI provider.
Action	Make sure the connection to the JNDI provider is available before trying to execute the Change Context command.

BRJ.102.1058	Unable to connect to Broker "{1}" on server "{0}". {2}
Explanation	There was an error while connecting to Broker.
Action	Check the details in the exception message and take appropriate action.
BRJ.106.1001E	Unable to create Durable Subscriber "{0}". JMS Exception: {1}
Explanation	A JMS exception occurred while trying to create the durable subscriber.
Action	Check the details in the exception message and take appropriate action.
BRJ.106.1003	Unable to create Durable Subscriber "{0}". Broker Exception: {2}
Explanation	A Broker exception occurred while trying to create the durable subscriber.
Action	Check the details in the exception message and take appropriate action.
BRJ.106.1015E	Unable to create Durable Subscriber "{0}". Topic "{1}" was not found.
Explanation	The topic to which the durable subscriber is being created does not exist.
Action	Make sure that the topic exists before creating the durable subscriber to the topic.
BRJ.106.1016E	Unable to create Durable Subscriber "{0}". "{1}" is not bound to a webMethods Topic. Class is "{2}"
Explanation	The topic to which the durable subscriber is being created is not a webMethods topic.
Action	Check if the destination to which the durable subscriber is being created is a topic created on webMethods Broker. Durable subscriber creation is allowed only for a webMethods topic.
BRJ.106.1017E	Unable to create Durable Subscriber "{0}". Connection Factory "{2}" was not found.
Explanation	The connection factory specified for durable subscriber creation is not present.
Action	Provide the correct connection factory name.
BRJ.106.1018E	Unable to create Durable Subscriber "{0}". "{2}" is not bound to a webMethods created Connection Factory. Class is "{3}"
Explanation	The connection factory for durable subscriber creation must be a webMethods connection factory; it should not be a QueueConnectionFactory instance.
Action	Specify a webMethods TopicConnectionFactory or a generic webMethods ConnectionFactory instance.

BRJ.106.1023E	Unable to create Durable Subscriber "{0}". Broker connection required.
Explanation	The connection to Broker is not established.
Action	Provide all the parameters required to establish connection to Broker.
BRJ.106.1044E	Not connected to a JNDI name service; create durable subscriber cannot access JNDI names.
Explanation	The connection to the JNDI provider is not established.
Action	Please check if all the relevant parameters have been passed to establish the connection to the JNDI provider.
BRJ.106.1051E	Unable to create Durable Subscriber "{0}". Client "{1}##{0}" already exists in the Broker.
Explanation	The durable subscriber already exists on Broker.
Action	Provide the correct durable subscriber name.
BRJ.106.1052E	Unable to create Durable Subscriber. Subscriber name is required.
Explanation	The durable subscriber name is required for durable subscriber creation.
Action	Provide the durable subscriber name.
BRJ.106.1053E	Unable to create Durable Subscriber "{0}". ClientID is required.
Explanation	ClientID is required for durable subscriber creation.
Action	Provide the ClientID.
BRJ.106.1069E	Unable to create Durable Subscriber "{0}" using "{2}". The Broker specified in the ConnectionFactory ("{8}@{6};{7}") is not the same as the currently connected Broker ("{5}@{3};{4}").
Explanation	The Broker specified in the connection factory is not the Broker on which the durable subscriber creation is being attempted.
Action	Specify the correct connection factory name.
BRJ.107.1002E	Unable to create group(s) "{0}". JNDI Exception: {1}
Explanation	A JNDI exception occurred while trying to create the groups.
Action	Check the details in the exception message and take appropriate action.

BRJ.107.1003E	Unable to create group(s) "{0}". Broker Exception: {1}
Explanation	A Broker exception occurred while trying to create the groups.
Action	Check the details in the exception message and take appropriate action.
BRJ.107.1023E	Unable to create group(s) "{0}". Broker connection required.
Explanation	Connection to the Broker is not established.
Action	Provide the properties required for establishing the Broker connection.
BRJ.108.1001E	Unable to create Queue "{0}" using "{1}". JMS Exception: {2}
Explanation	A JMS exception occurred while trying to create the queue.
Action	Check the details in the exception message and take appropriate action.
BRJ.108.1002E	Unable to create Queue "{0}". JNDI Exception: {1}
Explanation	A JNDI exception occurred while trying to create the queue.
Action	Check the details in the exception message and take appropriate action.
BRJ.108.1003E	Unable to create Queue "{0}". Broker Exception: {2}
Explanation	Broker exception occurred while trying to create the queue.
Action	Check the details in the exception message and take appropriate action.
BRJ.108.1005E	Unable to create Queue "{0}". Queue "{0}" was not found.
Explanation	The destination object for creating the queue on Broker not found.
Action	Provide the correct queue name.
BRJ.108.1020E	Unable to create Queue "{0}". "{0}" is not a webMethods created Queue.
Explanation	The destination object specified for creating the queue is not an instance of webMethods queue.
Action	Specify an instance of webMethods queue.
BRJ.108.1021E	Unable to create Queue "{0}". QCF "{1}" was not found.
Explanation	The Queue was not created because the Queue Connection Factory was not found.
Action	Create the Queue Connection Factory for the context.

BRJ.108.1022E	Unable to create Queue "{0}". "{1}" is not a webMethods QCF.
Explanation	Could not create the Queue because the Queue Connection Factory is not a webMethods implementation.
Action	Create a webMethods Queue Connection Factory before creating the Queue.
BRJ.108.1023E	Unable to create Queue "{0}". Broker connection required.
Explanation	Could not create the Queue because a Broker connection could not be obtained.
Action	Use the command line utilities to check if the Broker is running.
BRJ.108.1044E	Not connected to a JNDI name service; create queue cannot access JNDI names.
Explanation	Could not create the Queue because the connection to the JNDI could not be made.
Action	Check if the JNDI provider is running. Also, check the entries in the jndi.properties file.
BRJ.108.1048E	Unable to create Queue "{0}". {1}
Explanation	The Queue could not be created.
Action	Check the detailed error message and take corrective action.
BRJ.108.1055E	Queues created: {0}. Queues not processed: {1}
Explanation	The queue was created successfully. However, the queue may not have the permissions to subscribe/publish the documents in its client group.
Action	Connect to the Broker using the SSL/Basic Identity.
BRJ.108.1057E	Queues not processed: {0}.
Explanation	Queue may not have the permissions to subscribe/publish the documents in its client group.
Action	Connect to the Broker using the SSL/Basic Identity.
BRJ.108.1069E	Unable to create Queue "{0}" using "{1}". The Broker specified in the ConnectionFactory ("{7}@{5};{6}") is not the same as the currently connected Broker ("{4}@{2};{3}").
Explanation	Queue could not be created. Broker specified in the Connection Factory is not the Broker you are connected to.
Action	Connect to the Broker specified in the Connection Factory before you attempt to create the Queue.

BRJ.109.1002E	Unable to create Topic "{0}". JNDI Exception: {1}
Explanation	The Topic could not be created.
Action	Check the detailed error message and take corrective action.
BRJ.109.1003E	Unable to create Topic "{0}". Broker Exception: {1}
Explanation	The Topic could not be created.
Action	Check the detailed error message and take corrective action.
BRJ.109.1005E	Unable to create Topic "{0}". Topic "{0}" was not found.
Explanation	The Topic could not be created.
Action	Create the Topic on the JNDI.
BRJ.109.1016E	Unable to create Topic "{0}". "{0}" is not a webMethods created Topic.
Explanation	The Topic could not be created. The Topic on the JNDI is not a webMethods implementation.
Action	Create a webMethods Topic on the JNDI.
BRJ.109.1023E	Unable to create Topic "{0}". Broker connection required.
Explanation	The Topic could not be created because there is no connection to the Broker.
Action	Connect to the Broker before creating the Topic.
BRJ.109.1043E	Unable to create Topic "{0}". The Broker Document "{1}" used for the Topic already exists.
Explanation	The Topic could not be created. The event type of the Topic exists on the Broker.
Action	Delete the event type and reissue the command.
BRJ.109.1044E	Not connected to a JNDI name service; create topic cannot access JNDI names.
Explanation	You are not connected to the JNDI service.
Action	Check if the JNDI service is running.
BRJ.109.1048E	Unable to create Topic "{0}". {1}
Explanation	The Topic could not be created.
Action	Check the detailed message and take corrective action.

BRJ.109.1055E	Topics created: {0}. Topics not processed: {1}
Explanation	Successfully created the Topic. However, the Topic may not have the permissions to subscribe/publish the documents in its client group.
Action	Connect to the Broker using the SSL/Basic Identity.
BRJ.109.1057E	Topics not processed: {0}.
Explanation	May not have the permission to subscribe/publish the documents to the Topic client group.
Action	Connect to the Broker using the SSL/Basic Identity.
BRJ.110.1003E	Unable to delete Broker "{0}" on "{1}". Broker Exception: {2}
Explanation	Permission to delete Broker is not available or there could be a connection issue.
Action	Check the error details and take appropriate action.
BRJ.111.1002E	Unable to delete Context "{0}". JNDI Exception: {1}
Explanation	JNDI connection is not available.
Action	Check the error details and take appropriate action.
BRJ.111.1005E	Unable to delete Context "{0}". "{1}" was not found.
Explanation	The specified context is not found in the JNDI.
Action	Specify a valid and existing context.
BRJ.111.1034E	Unable to delete Context "{0}". "{0}" contains Subcontexts; specify (recursive) to delete them as well.
Explanation	Cannot delete a context that contains subcontexts.
Action	Specify "Recursive" to delete the subcontexts as well.
BRJ.111.1044E	Not connected to a JNDI provider; the Delete Context command is not allowed.
Explanation	A connection to the JNDI provider is required to execute the Delete Context command.
Action	Connect to the JNDI provider before attempting to delete a context.

BRJ.112.1001E	Unable to delete Durable Subscriber "{0}". JMS Exception: {1}
Explanation	Permission to delete the durable subscriber is not available or there is a Broker connection error.
Action	Take appropriate action after checking the permissions and the error details.
BRJ.112.1017E	Unable to delete Durable Subscriber "{0}". Connection Factory "{1}" was not found.
Explanation	The specified connection factory is not available to delete the durable subscriber.
Action	Check the error description and take appropriate action.
BRJ.112.1018E	Unable to delete Durable Subscriber "{0}". Connection Factory "{1}" is not a webMethods created Connection Factory.
Explanation	The connection factory is not created using webMethods implementation.
Action	Check the error description and take corrective action.
BRJ.112.1023E	Unable to delete Durable Subscriber "{0}". Broker connection required.
Explanation	Connection to Broker is required to delete a durable subscriber.
Action	Make sure Broker is connected before attempting to delete a durable subscriber.
BRJ.112.1044E	Not connected to a JNDI name service; delete durable subscriber cannot access JNDI names.
Explanation	There is no connection to the JNDI provider.
Action	Connect to the JNDI provider before attempting to delete a durable subscriber.
BRJ.112.1046	Unable to delete Durable Subscriber "{0}". Client "{1}##{0}" does not exist in the Broker.
Explanation	The specified client does not exist in Broker.
Action	Check the exception description and take appropriate action.
BRJ.112.1052E	Unable to delete Durable Subscriber. Subscriber name is required.
Explanation	The subscriber name is required to delete the durable subscriber.
Action	Provide the durable subscriber name.

BRJ.112.1053E	Unable to delete Durable Subscriber "{0}". ClientId is required.
Explanation	Client ID is required to delete the durable subscriber.
Action	Provide the Client ID.
BRJ.113.1003E	Unable to delete group(s) "{0}". Broker Exception: {1}
Explanation	Permission to delete groups is not available or there is no connection to Broker.
Action	Check the exception details and take appropriate action.
BRJ.113.1023	Unable to delete group(s) "{0}". Broker connection required.
Explanation	Broker connection is not available to delete the group(s).
Action	Make sure Broker connection is available before attempting to delete group(s).
BRJ.113.1048E	Unable to delete group "{0}". {1}
Explanation	Permission to delete the group is not available or there is no connection to Broker.
Action	Check the exception details and take appropriate action.
BRJ.114.1001	Unable to delete Queue "{0}" using "{1}". JMS Exception: {2}
Explanation	JMS exception thrown while trying to delete the queue.
Action	Check the corresponding exception description and take appropriate action.
BRJ.114.1002E	Unable to delete Queue "{0}". JNDI Exception: {1}
Explanation	A JNDI exception is thrown while trying to delete a queue.
Action	Please check the corresponding JNDI exception description and take appropriate action.
BRJ.114.1003E	Unable to delete Queue "{0}". Broker Exception: {1}
Explanation	Broker has thrown an exception while trying to delete a queue.
Action	Check the corresponding Broker exception description and take appropriate action.
BRJ.114.1005E	Unable to delete Queue "{0}". Queue "{0}" was not found.
Explanation	This error can occur while trying to delete a queue that does not exist in the JNDI context.
Action	Make sure that the queue name is correct and it exists in the JNDI context.

BRJ.114.1019E	Unable to delete Queue "{0}". Queue does not exist.
Explanation	The queue specified for deletion does not exist on the Broker.
Action	Make sure that the queue name is correct, and it exists on the Broker.
BRJ.114.1020E	Unable to delete Queue "{0}". "{0}" is not a webMethods created Queue.
Explanation	The queue specified in the delete command is not a webMethods JNDI queue.
Action	Make sure the queue specified for deletion is a webMethods JNDI queue type.
BRJ.114.1023E	Unable to delete Queue "{0}". Broker connection required.
Explanation	There is no connection to the Broker.
Action	Make sure that the JMSAdmin session is connected to the Broker. Please check the documentation for details on how to connect to a Broker.
BRJ.114.1044E	Not connected to a JNDI name service; delete queue cannot access JNDI names.
Explanation	The current JMSAdmin session is not connected to a JNDI provider.
Action	Make sure that the JMSAdmin session is connected to a JNDI provider, and it is initialized.
BRJ.114.1048E	Unable to delete Queue "{0}". {1}
Explanation	Exception encountered while trying to delete the queue.
Action	Check the exception details and take appropriate action or contact Software AG support.
BRJ.114.1055E	Queues deleted: {0}. Queues not processed: {1}
Explanation	Some delete operations failed while deleting multiple queues.
Action	Make sure you use the command correctly. See documentation for details or contact Software AG Global Support.
BRJ.114.1057E	Queues not processed: {0}.
Explanation	All the delete operations failed while deleting multiple queues.
Action	Make sure you use the command correctly. See the documentation for details or contact Software AG Global Support.

BRJ.115.1002E	Unable to delete Topic "{0}". JNDI Exception: {1}
Explanation	A JNDI exception is thrown while trying to delete a topic.
Action	Check the corresponding JNDI exception description and take appropriate action.
BRJ.115.1003E	Unable to delete Topic "{0}". Broker Exception: {1}
Explanation	Broker has thrown an exception while trying to delete a topic.
Action	Check the corresponding Broker exception description and take appropriate action.
BRJ.115.1005E	Unable to delete Topic "{0}". Topic "{0}" was not found.
Explanation	This would happen while trying to delete a topic, which does not exist in the JNDI context.
Action	Make sure that the topic name is correct, and the topic exists in the JNDI context.
BRJ.115.1016E	Unable to delete Topic "{0}". "{0}" is not a webMethods created Topic.
Explanation	The topic specified in the delete command is not a webMethods JNDI topic.
Action	Make sure the topic specified in the delete command is a webMethods JNDI topic type.
BRJ.115.1023E	Unable to delete Topic "{0}". Broker connection required.
Explanation	There is no connection to the Broker.
Action	Make sure that the JMSAdmin session is connected to the Broker. Please check the documentation for details on how to connect to a Broker.
BRJ.115.1044E	Not connected to a JNDI name service; delete topic cannot access JNDI names.
Explanation	The current JMSAdmin session is not connected to a JNDI provider.
Action	Make sure that the JMSAdmin session is connected to a JNDI provider, and it is initialized.
BRJ.115.1048E	Unable to delete Topic "{0}". {1}
Explanation	Exception encountered while trying to delete the topic.
Action	Check the exception details and take appropriate action or contact Software AG Global Support.

BRJ.115.1055E	Topics deleted: {0}. Topics not processed: {1}
Explanation	Some delete operations failed while deleting multiple topics.
Action	Make sure you use the command correctly. See the documentation for details or contact Software AG Global Support.
BRJ.115.1057E	Topics not processed: {0}.
Explanation	All the delete operations failed while deleting multiple topics.
Action	Make sure you use the command correctly. See the documentation for details or contact Software AG Global Support.
BRJ.116.1003E	Unable to revoke permissions. Broker Exception: "{0}"
Explanation	Broker has thrown an exception while trying to revoke the permissions.
Action	Check the corresponding Broker exception description and take appropriate action.
BRJ.116.1017E	Unable to revoke permissions. TCF "{0}" was not found.
Explanation	The specified Topic Connection Factory was not found in the JNDI context.
Action	Check if the Topic Connection Factory exists on the connected JNDI context.
BRJ.116.1018E	Unable to revoke permissions. TCF "{0}" is not a webMethods created TCF.
Explanation	This error might have occurred while trying to revoke the permissions from a Topic Connection Factory that is not created by webMethods JNDI library.
Action	Make sure that the specified Topic Connection Factory is created by webMethods JNDI.
BRJ.116.1019E	Unable to revoke permissions. Queue "{0}" has not been created on this Broker.
Explanation	This error may occur while trying to revoke the permissions from a Queue that does not exist on the Broker connected to the current JMSAdmin session.
Action	Make sure that the Queue exists on the Broker to which JMSAdmin is connected.
BRJ.116.1023E	Unable to revoke permissions. Broker connection required.
Explanation	There is no connection to the Broker.
Action	Make sure that the JMSAdmin session is connected to the Broker. Please check the documentation for details on how to connect to a Broker.

BRJ.116.1029E	Unable to revoke permission to use "{0}". Topic "{0}" has not been created on this Broker.
Explanation	Topic does not exist on the Broker connected to the JMSAdmin session.
Action	Make sure that the Topic exists on the Broker connected to the JMSAdmin session.
BRJ.116.1048E	Unable to revoke permission to use "{0}". "{1}"
Explanation	Exception encountered while trying to revoke the permissions.
Action	Check the exception details and take appropriate action or contact Software AG Global Support.
BRJ.116.1055E	Permissions revoked for: {0}. Not processed: {1}
Explanation	Some operations failed while revoking the permissions from multiple JNDI objects.
Action	Make sure you use the command correctly. See webMethods Broker documentation for details or contact Software AG Global Support.
BRJ.117.1003E	Unable to disconnect from Broker. Broker Exception: "{0}"
Explanation	Broker throws an exception while the JMSAdmin session is trying to disconnect from Broker.
Action	Check the exception details and take appropriate action or contact Software AG Global Support.
BRJ.117.1048E	Unable to disconnect from Broker. "{0}"
Explanation	An error occurred while JMSAdmin attempted to disconnect from Broker.
Action	Check if the connection is closed or contact Software AG Global Support.
BRJ.121.1026E	Unable to import file "{0}": "{1}".
Explanation	The file does not exist or the file is not accessible by JMSAdmin.
Action	Make sure that the file path is correct. Check if the file exists and it is accessible by JMSAdmin.
BRJ.121.1054E	Unable to import file "{0}": "{1}" is not a valid encoding.
Explanation	File encoding format is incorrect.
Action	Make sure that the file has the default system encoding or set the correct encoding format on JMSAdmin. See webMethods Broker documentation for details on the supported encoding formats.

BRJ.122.1003E	Unable to initialize Broker. Broker Exception: {0}
Explanation	Broker throws an exception during initialization.
Action	Check the exception details and take appropriate action. Contact Software AG Global Support.
BRJ.122.1023E	Unable to initialize Broker. Broker connection required.
Explanation	Initialize command was called without a valid connection to the Broker.
Action	Make sure that the JMSAdmin session is connected the Broker before executing the initialize command. See the webMethods Broker documentation for details on how to connect to a Broker.
BRJ.122.1048E	Unable to initialize Broker. {0}
Explanation	Broker throws exception during initialization.
Action	Check the exception message and take appropriate action. Contact Software AG Global Support.
BRJ.123.1002E	Unable to list context "{0}". JNDI Exception: {1}
Explanation	There is a NamingException while trying to list the JNDI objects .
Action	Check the error details and take appropriate action, or contact Software AG Global Support.
BRJ.123.1007E	Unable to list context "{0}". "{0}" is not a Context.
Explanation	While listing JNDI objects, the specified name is not a Context.
Action	Check the JNDI URL, and verify if the Context name is correct and it exists.
BRJ.123.1044E	Not connected to a JNDI provider; the List Context (ls) command is not allowed.
Explanation	The current JMSAdmin session is not connected to a JNDI provider.
Action	Make sure that the JMSAdmin session is connected to a JNDI provider and it is initialized.
BRJ.124.1002E	Unable to move "{0}" to "{1}". JNDI Exception: {2}
Explanation	A JNDI exception is thrown while moving the JNDI object.
Action	Check the corresponding JNDI exception description and take appropriate action.

BRJ.124.1006E	Unable to move "{0}" to "{1}". The name "{1}" is already in use.
Explanation	Unable to move the JNDI object as the JNDI name is already bound.
Action	Make sure that the target JNDI name is not in use.
BRJ.124.1010E	Unable to move "{0}" to "{1}". Destination path element not found: "{2}".
Explanation	Unable to move the JNDI object as the destination path is not found.
Action	Provide the correct destination path.
BRJ.124.1044E	Not connected to a JNDI provider; the Move command is not allowed.
Explanation	Move command is not allowed because there is no connection available to a JNDI provider.
Action	Connect to a JNDI provider, and then execute the Move command.
BRJ.125.1001E	Unable to grant permissions. JMS Exception: "{0}"
Explanation	A JMS exception is thrown while trying to grant permission.
Action	Check the corresponding JMS exception description and take appropriate action.
BRJ.125.1003E	Unable to grant permissions. Broker Exception: "{0}"
Explanation	Broker has thrown an exception while trying to grant permission.
Action	Check the corresponding Broker exception description and take appropriate action.
BRJ.125.1017E	Unable to grant permissions. TCF "{0}" was not found.
Explanation	The specified Topic Connection Factory was not found in the JNDI context.
Action	Check if the Topic Connection Factory exists on the connected JNDI context.
BRJ.125.1018E	Unable to grant permissions. TCF "{0}" is not a webMethods created TCF.
Explanation	This error might have occurred while trying to grant the permissions from a Topic Connection Factory that is not created by webMethods JNDI library.
Action	Make sure that the specified Topic Connection Factory is created by webMethods JNDI.

BRJ.125.1019E	Unable to grant permissions. Queue "{0}" has not been created on this Broker.
Explanation	This error may occur while trying to grant the permissions from a Queue that does not exist on the Broker connected to the current JMSAdmin session.
Action	Make sure that the Queue exists on the Broker to which JMSAdmin is connected.
BRJ.125.1023E	Unable to grant permissions. Broker connection required.
Explanation	There is no connection to the Broker.
Action	Make sure that the JMSAdmin session is connected to the Broker. See the webMethods Broker documentation for details on how to connect to a Broker.
BRJ.125.1029E	Unable to grant permission to use "{0}". Topic "{0}" has not been created on this Broker.
Explanation	Topic does not exist on the Broker connected to the JMSAdmin session.
Action	Make sure that the Topic exists on the Broker connected to the JMSAdmin session.
BRJ.125.1048E	Unable to grant permission to use "{0}". "{1}"
Explanation	Exception encountered while trying to grant the permissions.
Action	Check the exception details and take appropriate action or contact Software AG Global Support.
BRJ.125.1055E	Permissions granted for: {0}. Not processed: {1}
Explanation	Some operations failed while granting permissions from multiple JNDI objects.
Action	Make sure you use the command correctly. See the webMethods Broker documentation for details or contact Software AG Global Support.
BRJ.126.1028E	Unable to set "{0}". "{0}" is a read-only system variable.
Explanation	You cannot change the read-only properties on Broker.
Action	Specify the correct operation.
BRJ.126.1036E	"{0}" is not a known variable.
Explanation	You are attempting to change the value of a property that does not exist on Broker.
Action	Specify the correct property name.

BRJ.127.1001E	Unable to show "{0}". JMS Exception: {1}
Explanation	A JMS exception occurred.
Action	Check the details in the exception message and take appropriate action.
BRJ.127.1002E	Unable to show "{0}". JNDI Exception: {1}
Explanation	A JNDI exception occurred.
Action	Check the details in the exception message and take appropriate action.
BRJ.127.1005E	Unable to show "{0}". "{1}" was not found.
Explanation	The specified object does not exist in JNDI.
Action	Specify the correct name.
BRJ.127.1007E	Unable to show "{0}". "{1}" is not a Context.
Explanation	You have specified a wrong context name.
Action	Specify the correct name.
BRJ.127.1044E	Not connected to a JNDI provider; the Show command is not allowed.
Explanation	Not connected to the JNDI provider.
Action	Specify the correct properties required for connecting to the JNDI provider.
BRJ.128.1002E	Unable to unbind "{0}". JNDI Exception: {1}
Explanation	An exception occurred while trying to unbind the specified object.
Action	Check the details in the exception message and take appropriate action.
BRJ.128.1005E	Unable to unbind "{0}". "{1}" was not found.
Explanation	An exception occurred while trying to unbind the object.
Action	Check the details in the exception message and take appropriate action.
BRJ.128.1037E	Unable to unbind "{0}". "{0}" is a Context. Use delete context to destroy it.
Explanation	You cannot unbind a Context.
Action	Use the delete command to delete a Context.

BRJ.128.1044E	Not connected to a JNDI provider; the Unbind command is not allowed.
Explanation	The connection to the JNDI provider is not available.
Action	Establish the connection to the JNDI provider and run the unbind command.
BRJ.129.1004E	Unable to process commands. IOException: {0}.
Explanation	An IOException occurred while processing the commands.
Action	Check the details in the exception message and take appropriate action.
BRJ.129.1026E	Unable to process commands from: {0}.
Explanation	An exception occurred while processing the commands.
Action	Check the details in the exception message and take appropriate action.
BRJ.129.1030E	Unable to process commands. Exception: {0}.
Explanation	An exception occurred while processing the commands.
Action	Check the details in the exception message and take appropriate action.
BRJ.129.1032E	Unable to process commands. EOF occurred while reading command.
Explanation	An exception occurred while processing the commands.
Action	Check the details in the exception message and take appropriate action.
BRJ.129.1054E	Unable to process commands: "{0}" is not a valid encoding.
Explanation	An exception occurred while processing the commands because the encoding format is not valid.
Action	Check the details in the exception message. Provide the correct encoding format.
BRJ.130.1031E	"Encountered: "{0}". Expected: "+System.getProperty("line.separator")+ "{1}"
Explanation	Error in the command syntax.
Action	Check the details in the exception message and provide the correct command.
BRJ.131.1002E	Unable to get InitialContext. Naming system exception: {0}
Explanation	An exception occurred while trying to get the initial context.
Action	Specify the valid JMS naming context factory class name: java.naming.factory.initial.

BRJ.131.1004E	Unable to read properties. IOException: {0}.
Explanation	An exception occurred while trying to read the properties.
Action	Check the details in the exception message and take appropriate action.
BRJ.131.1005E	Unable to get InitialContext. Name not found exception. Provider URL: "{0}".
Explanation	An exception occurred while trying to get the initial context.
Action	Make sure the JNDI server corresponding to the specified provider URL is running.
BRJ.131.1026E	Unable to read properties from: {0}.
Explanation	An exception occurred while trying to read the properties.
Action	Check the details in the exception message and take appropriate action.
BRJ.132.1001E	Unable to export "{0}". JMS Exception: {1}
Explanation	A JMS exception occurred while trying to export the specified object.
Action	Check the details in the exception message and take appropriate action.
BRJ.132.1002E	Unable to export "{0}". JNDI Exception: {1}
Explanation	A JNDI exception occurred while trying to export the specified object.
Action	Check the details in the exception message and take appropriate action.
BRJ.132.1005E	Unable to export "{0}". Object "{1}" was not found.
Explanation	The object specified for export is not found.
Action	Specify the correct object for export.
BRJ.132.1026E	Unable to export "{0}". "{2}".
Explanation	An exception occurred while trying to export the specified object.
Action	Check the details in the exception message and take appropriate action.
BRJ.132.1033E	Unable to export "{0}". File "{1}" already exists.
Explanation	The file specified for storing the exported object already exists.
Action	Specify a new file.

BRJ.132.1044E	Not connected to a JNDI provider; the Export command is not allowed.
Explanation	JNDI provider connection is required.
Action	Make sure the JNDI provider connection is available before requesting for export.
BRJ.133.1001E	Unable to create groups for "{0}". JMS Exception: {1}
Explanation	A JMS exception occurred while trying to create groups.
Action	Check the details in the exception message and take appropriate action.
BRJ.133.1002E	Unable to create groups for "{0}". JNDI Exception: {1}
Explanation	A JNDI exception occurred while trying to create groups.
Action	Check the details in the exception message and take appropriate action.
BRJ.133.1003E	Unable to create groups for "{0}". Broker Exception: {1}
Explanation	A Broker exception occurred while trying to create groups.
Action	Check the details in the exception message and take appropriate action.
BRJ.133.1005E	Unable to create groups for "{0}". Name not found: "{1}"
Explanation	An exception occurred while trying to create groups. The specified name is not found.
Action	Check the details in the exception message and specify the correct name.
BRJ.133.1007E	Unable to create groups for "{0}". "{0}" is not a Context.
Explanation	An exception occurred while trying to create groups. The specified object is not a Context.
Action	Check the details in the exception message and specify the correct Context.
BRJ.133.1023E	Unable to create groups for "{0}". Broker connection required.
Explanation	An exception occurred while trying to create groups. Broker connection is required.
Action	Make sure the Broker connection is available before creating the groups.
BRJ.133.1024E	Unable to create groups for "{0}". "{0}" is not a webMethods TCF, QCF or Queue.
Explanation	The specified object is not a webMethods Topic Connection Factory, Queue Connection Factory, or Queue.
Action	Specify a webMethods Topic Connection Factory, Queue Connection Factory, or Queue.

BRJ.134.1003E	Unable to set "{0}" as the default Broker on server "{1}". Broker Exception: {2}
Explanation	A Broker exception occurred while trying to set the default Broker.
Action	Check the details in the exception message and take appropriate action.
BRJ.135.1003E	Unable to display Brokers on server "{0}". Broker Exception: {1}
Explanation	A Broker exception occurred while trying to list the available Brokers on the Broker Server.
Action	Check the details in the exception message and take appropriate action.
BRJ.136.1003E	Unable to display group "{0}". Broker Exception: {1}
Explanation	A Broker exception occurred while trying to display the groups.
Action	Check the details in the exception message and take appropriate action.
BRJ.136.1023E	Unable to display group "{0}". Broker connection required.
Explanation	Admin client not connected to Broker.
Action	Check the details in the exception message and take appropriate action.
BRJ.136.1048E	Unable to display group "{0}". {1}
Explanation	A JMS Admin exception occurred while trying to display the client groups.
Action	Check the details in the exception message and take appropriate action.
BRJ.137.1003E	Unable to display groups. Broker Exception: {0}
Explanation	A Broker exception occurred while trying to display the client groups.
Action	Check the details in the exception message and take appropriate action.
BRJ.137.1023E	Unable to display groups. Broker connection required.
Explanation	Admin client not connected to Broker.
Action	Check the details in the exception message and take appropriate action.
BRJ.137.1050E	No groups are currently defined on this Broker.
Explanation	The operation requires groups to be configured on Broker.
Action	Configure the groups on Broker and try again.

BRJ.138.1003E	Unable to display queue "{0}". Broker Exception: {1}
Explanation	A Broker exception occurred while trying to display the queue.
Action	Check the details in the exception message and take appropriate action.
BRJ.138.1023E	Unable to display queue "{0}". Broker connection required.
Explanation	There is no connection to Broker.
Action	Make sure the connection to Broker is available and try again.
BRJ.138.1046E	Unable to display queue "{0}". The queue is not currently defined on this Broker.
Explanation	The specified queue is not defined on Broker.
Action	Specify the correct queue.
BRJ.138.1048E	Unable to display queue "{0}". {1}
Explanation	An exception occurred while trying to display the queue.
Action	Check the details in the exception message and take appropriate action.
BRJ.139.1003E	Unable to display queues. Broker Exception: {0}
Explanation	A Broker exception occurred while trying to display the queues.
Action	Check the details in the exception message and take appropriate action.
BRJ.139.1023E	Unable to display queues. Broker connection required.
Explanation	Broker connection is required to display the queues.
Action	Make sure that the Broker connection is available.
BRJ.139.1045E	No queues are currently defined on this Broker.
Explanation	The queues must be defined for the Broker.
Action	Create the queues.
BRJ.139.1048E	Unable to display queues. {0}
Explanation	An exception occurred while trying to display queues.
Action	Check the details in the exception message and take appropriate action.

BRJ.140.1003E	Unable to display durable subscriber "{0}". Broker Exception: {1}
Explanation	A Broker exception occurred while trying to display durable subscriber.
Action	Check the details in the exception message and take appropriate action.
BRJ.140.1023E	Unable to display durable subscriber "{0}". Broker connection required.
Explanation	Connection to Broker is required to display the durable subscriber.
Action	Re-try the operation after establishing the Broker connection.
BRJ.140.1046E	Unable to display durable subscriber "{0}". The durable subscriber is not currently defined on this Broker.
Explanation	The specified durable subscriber is not defined on Broker.
Action	Retry the operation after creating the durable subscriber on Broker.
BRJ.140.1048E	Unable to display durable subscriber "{0}". {1}
Explanation	An exception occurred while trying to display the durable subscriber.
Action	Check the details in the exception message and take appropriate action.
BRJ.141.1003E	Unable to display durable subscribers. Broker Exception: {0}
Explanation	A Broker exception occurred while trying to display the durable subscribers.
Action	Check the details in the exception message and take appropriate action.
BRJ.141.1023E	Unable to display durable subscribers. Broker connection required.
Explanation	Connection to Broker is required to display the durable subscribers.
Action	Re-try the operation after establishing the Broker connection.
BRJ.141.1045E	No durable subscribers are currently defined on this Broker.
Explanation	There are no durable subscribers defined on Broker.
Action	Retry the operation after creating the durable subscribers on Broker.
BRJ.141.1048E	Unable to display durable subscribers. {0}
Explanation	An exception occurred while trying to display the durable subscribers.
Action	Check the details in the exception message and take appropriate action.

BRJ.142.1003E	Unable to display subscriber "{0}". Broker Exception: {1}
Explanation	A Broker exception occurred while trying to display the specified durable subscriber.
Action	Check the details in the exception message and take appropriate action.
BRJ.142.1023E	Unable to display subscriber "{0}". Broker connection required.
Explanation	Connection to Broker is required to display the specified durable subscriber.
Action	Retry the operation after establishing the Broker connection.
BRJ.142.1046E	Unable to display subscriber "{0}". The subscriber is not currently defined on this Broker.
Explanation	The specified durable subscriber is not defined on Broker.
Action	Retry the operation after defining the durable subscriber on Broker.
BRJ.142.1048E	Unable to display subscriber "{0}". {1}
Explanation	An exception occurred while trying to display the subscriber.
Action	Check the details in the exception message and take appropriate action.
BRJ.143.1003E	Unable to display subscribers. Broker Exception: {1}
Explanation	A Broker exception occurred while trying to display the subscribers.
Action	Check the details in the exception message and take appropriate action.
BRJ.143.1023E	Unable to display subscribers. Broker connection required.
Explanation	Connection to Broker is required to display the durable subscribers.
Action	Re-try the operation after establishing the Broker connection.
BRJ.143.1045E	No subscribers are currently defined on this Broker.
Explanation	An exception occurred while trying to display the subscribers because there are no subscribers defined on this Broker.
Action	Add at least one subscriber and try again.
BRJ.143.1048E	Unable to display subscribers. {1}
Explanation	An exception occurred while trying to display the subscribers.
Action	Make sure at least one subscriber is defined.

BRJ.144.1003E	Unable to display topic "{0}". Broker Exception: {1}
Explanation	An exception occurred while trying to display the specified topic.
Action	Check the details in the exception message and take appropriate action.
BRJ.144.1023E	Unable to display topic "{0}". Broker connection required.
Explanation	Broker connection is required to display the specified topic.
Action	Check the details in the exception message and make sure the Broker connection is available.
BRJ.144.1047E	Unable to display topic "{0}". The topic is not currently defined on this Broker.
Explanation	An exception occurred while trying to display the topic because the specified topic is not defined on the Broker.
Action	Check the details in the exception message and define the topic.
BRJ.144.1048E	Unable to display topic "{0}". {1}
Explanation	An exception occurred while trying to display the specified topic.
Action	Check the details in the exception message and take appropriate action.
BRJ.145.1003E	Unable to display topics. Broker Exception: {0}
Explanation	An exception occurred while trying to display the topics.
Action	Check the details in the exception message and take appropriate action.
BRJ.145.1023E	Unable to display topics. Broker connection required.
Explanation	Broker connection is required to display the topics.
Action	Check the details in the exception message and make sure the Broker connection is available.
BRJ.145.1048E	Unable to display topics. {0}
Explanation	An exception occurred while trying to display the topics.
Action	Check the details in the exception message and take appropriate action.

BRJ.145.1049E	No topics are currently defined on this Broker.
Explanation	An exception occurred because no topics are defined on the Broker.
Action	Define the topics on the Broker.
BRJ.146.1054E	Unable to change the encoding: "{0}" is not a valid encoding.
Explanation	An exception occurred while trying to use encoding.
Action	Check the details in the exception message and specify the correct encoding format.
BRJ.147.1060E	Group "{0}" does not have publish permission on "{1}"
Explanation	An exception occurred because the specified group does not have the publish permission for the object.
Action	Check the details in the exception message and specify the correct group that has the required publish permission.
BRJ.147.1061E	Group "{0}" does not have subscribe permission on "{1}"
Explanation	An exception occurred because the specified group does not have the subscribe permission for the object.
Action	Check the details in the exception message and specify the correct group that has the required subscribe permission.
BRJ.148.1062E	Group "{0}" already has publish permission on "{1}"
Explanation	An exception occurred while trying to set the publish permission for the group. The group already has the publish permission for the specified event type.
Action	Check the details in the exception message and specify the correct group and event type.
BRJ.148.1063E	Group "{0}" already has subscribe permission on "{1}"
Explanation	An exception occurred while trying to set the subscribe permission for a group. The group already has the subscribe permission for the specified event type.
Action	Check the details in the exception message and specify the correct group and the event type.

BRJ.149.1064E	Skipping group "{0}" -- it already exists.
Explanation	Unable to create the client group. A client group with the specified name exists.
Action	Provide a different client group name.
BRJ.149.90001E	Group types on create have been deprecated. Ignoring "{0}"
Explanation	Unable to the create client group using the specified client group type. The specified client group type is deprecated.
Action	Do not specify a deprecated client group type while creating client groups. You can create a client group without specifying the client group type.
BRJ.150.1065E	Skipping group "{0}" -- it does not exist.
Explanation	Unable to delete the client group. The specified client group does not exist.
Action	Specify the correct client group for deletion.
BRJ.151.90002W	Property "{1}" for "{0}" has been deprecated - value ignored.
Explanation	This a warning while trying to bind the JMSAdmin objects to the context. The value of the deprecated property will be ignored.
Action	No action required.
BRJ.151.90003W	Property "{1}" for "{0}" has been deprecated. Using the value for the "{2}" property.
Explanation	This a warning while binding the JMSAdmin objects to the context. The value specified for the deprecated property is assigned to the replacement property.
Action	No action required.
BRJ.152.1001E	Set RecoverMode failed. JMS Exception: {1}
Explanation	Unable to set the recover mode of the Broker. You might not have the required permissions.
Action	Check the details in the exception message and take appropriate action.
BRJ.152.1023E	Set RecoverMode requires a Broker connection.
Explanation	Unable to set the recover mode of the Broker. A connection to the Broker is required.
Action	Make sure the Broker connection is available.

BRJ.153.1074E	Cannot bind connection factory. Missing clusterName property value when includeAllBrokers property is set to true.
Explanation	Cannot bind a connection factory without the cluster name.
Action	Provide the cluster name.
BRJ.153.1075E	Cannot bind connection factory. Invalid clusterPolicy property value. Valid values: {}.
Explanation	Unable to bind the connection factory because the cluster policy is invalid.
Action	Check the details in the exception message and specify a valid cluster policy.
BRJ.153.1076E	Cannot bind connection factory. Missing weights property value.
Explanation	Unable to bind the connection factory because the value for Weights is not set.
Action	Specify the Weights for a Weighted Round Robin policy.
BRJ.153.1077E	Cannot bind connection factory. Missing multiSendCount property value.
Explanation	Unable to bind the connection factory because the MultiSendCount is not set.
Action	Specify the MultiSendCount.
BRJ.153.1078E	Cannot bind connection factory. Missing clusterBrokers property value.
Explanation	Unable to bind the connection factory because the cluster Brokers are missing.
Action	Specify the list of Brokers in the cluster.
BRJ.153.1079E	Cannot bind connection factory. The clusterRefreshInterval property value must be an integer greater than 0.
Explanation	Unable to bind the connection factory because the specified cluster refresh interval is invalid.
Action	Specify a value greater than 0 (zero) for cluster refresh interval.
BRJ.153.1080E	Cannot bind connection factory. Set clusterPolicy property value when you specify a cluster policy parameter.
Explanation	Unable to bind the connection factory because the cluster policy is not specified, but some of the cluster policy parameters are specified.
Action	Specify the cluster policy when you specify the cluster policy parameters.

BRJ.153.1081E	Cannot bind connection factory. Missing clusterConnectionFactories property value.
Explanation	Unable to bind the connection factory because a cluster connection factory is not specified.
Action	Specify at least one cluster connection factory and try again.
BRJ.153.1082E	Cannot bind connection factory. The multiSendCount property value must be greater than 0 and less than the number of Brokers in the cluster.
Explanation	The multiSendCount property value must be greater than 0 and less than the number of Brokers in the cluster.
Action	Provide a valid value for the multiSendCount property.
BRJ.153.1083E	Cannot bind connection factory. The weights property value must be greater than 0.
Explanation	The weights property value must be greater than 0.
Action	Provide a value greater than 0 for the weights property.
BRJ.153.1084E	Cannot bind connection factory. MULTISEND_GUARANTEED cluster policy is applicable only to XA connection factories.
Explanation	The MULTISEND_GUARANTEED cluster policy is supported only for XA Cluster connection factories.
Action	Select the correct cluster policy. For more information about the supported cluster policies, see the webMethods Broker documentation.
BRJ.153.1085E	Cannot bind connection factory. The specified connection factory is not a valid cluster connection factory.
Explanation	The specified connection factory is not a valid cluster connection factory.
Action	Make sure you specify a valid cluster connection factory.
BRJ.153.1086E	Cannot bind connection factory. The specified connection factory is not a valid composite cluster connection factory.
Explanation	The specified connection factory is not a valid composite cluster connection factory.
Action	Specify a valid composite cluster connection factory.

BRJ.153.1087E	Cannot bind connection factory. A property value is NULL. Ensure the variable is set.
Explanation	Cluster connection factory property value is not set.
Action	Check the cluster connection factory property details and set the variable.
BRM.010.1002E	Unable to convert property "{0}" to {1}.
Explanation	The client attempted to get a property in a message using the wrong method. For example, a client calling the Message.getIntProperty method for a property that is of type boolean can cause this error.
Action	Use the appropriate method either to get the correct property type or to correctly convert the property to the requested type.
BRM.010.1003E	Invalid webMethods specific property: "{0}".
Explanation	The client attempted to set a non-existent provider-specific property in a message. JMS defines provider-specific property names as "JMS_<vendor>". webMethods provider-specific property names begin with "JMS_WM".
Action	Specify a valid webMethods provider-specific property name.
BRM.010.1004E	Null is not a valid value for envelope field: "{0}".
Explanation	The client attempted to set a webMethods envelope field to null.
Action	Do not set an envelope field value to null.
BRM.010.1005E	Invalid object type for Message field: "{0}".
Explanation	The client attempted to set an object property with an invalid type.
Action	The type must be an object corresponding to a native type (Boolean, Byte, Short, Integer, Long, Float, Double) or a String.
BRM.010.1007E	Version field is missing in serialized message.
Explanation	The serialized Message object does not contain the required version field.
Action	Verify that the client mentions the required version field.
BRM.010.1008E	Incorrect message version. Expected {0}, received {1}.
Explanation	The serialized Message object is of an incompatible version.
Action	Verify that the client does not attempt to deserialize an incompatible Message object.

BRM.010.1009E	Message data field is missing in serialized message.
Explanation	The serialized message object does not contain the required data field.
Action	Verify that the client does not attempt to deserialize an incompatible Message object.
BRM.010.1010E	Property name cannot be null.
Explanation	The client attempted to set or get a property in a message using a null property name.
Action	Make sure that the value passed for property name is not null.
BRM.010.1011E	Property name cannot be an empty string.
Explanation	The client attempted to set or get a property in a message using a property name that is an empty string.
Action	Verify that an empty string is not passed as a property name.
BRM.010.1012E	{1} property "{0}" was not found in the message.
Explanation	The client attempted to get a JMS-defined property using an invalid type.
Action	Verify that a method corresponding to the correct type is used to get a JMS-defined property from a message.
BRM.010.1014E	Invalid delivery mode specified: "{0}". Use either DeliveryMode.NON_PERSISTENT (1) or DeliveryMode.PERSISTENT (2).
Explanation	An invalid delivery mode value was provided to the setJMSDeliveryMode method.
Action	Verify that the delivery mode value is either DeliveryMode.NON_PERSISTENT or DeliveryMode.PERSISTENT.
BRM.010.1015E	Attempt to set or get a JMS message standard header field "{0}" as a property failed. To get and set the message property "{1}" use the get{2}() or set{3}() methods.
Explanation	The client attempted to use a property name that began with "JMS" but is not defined in the JMS standard.
Action	Do not use property names starting with "JMS" unless defined in the JMS standard.
BRM.010.1016E	Invalid property name "{0}"; must start with Java identifier start character.
Explanation	The client attempted to use a property name that began with an invalid character.
Action	Verify that the property name is a valid Java identifier.

BRM.010.1017E	Invalid property name "{0}"; must contain only Java identifier part characters.
Explanation	The client attempted to use an invalid character in the property name.
Action	Verify that the property name is a valid Java identifier.
BRM.010.1018E	Invalid property name "{0}"; must not be a JMS keyword.
Explanation	The client attempted to use a property name that is a JMS keyword.
Action	Verify that the property name is not a JMS keyword: NULL, TRUE, FALSE, NOT, AND, OR, BETWEEN, LIKE, IN, IS, or ESCAPE.
BRM.010.1019E	Attempt to set read-only envelope field "{0}".
Explanation	The client attempted to set a read-only envelope field.
Action	Do not attempt to set a read-only envelope field.
BRM.010.1020E	Attempt to access unknown envelope field "{0}" of type "{1}".
Explanation	The client attempted to set an unknown envelope field.
Action	Verify that a correct envelope field name is provided.
BRM.010.1021E	Unable to access envelope field "{0}" of type "{1}".
Explanation	The client attempted to get an envelope field using the incorrect type.
Action	Use the correct type to access an envelope field.
BRM.010.1022E	Attempt to set envelope field "{0}" of type "{1}" with a value of type "{2}".
Explanation	The client attempted to set an envelope field using the incorrect type.
Action	Verify that the correct type is used to set an envelope field.
BRM.010.1050E	BytesMessage.writeUTF cannot take a null value parameter.
Explanation	The value passed to BytesMessage.writeUTF was null.
Action	Supply a value other than null.
BRM.010.1051E	BytesMessage.writeBytes cannot take a null value parameter.
Explanation	The value passed to BytesMessage.writeBytes was null.
Action	Supply a non-null value.

BRM.010.1052E	BytesMessage.writeObject cannot take a null value parameter.
Explanation	The value passed to BytesMessage.writeObject was null.
Action	Supply a non-null value.
BRM.010.1053E	BytesMessage.writeObject Objects of class "{0}" are not allowed.
Explanation	An unsupported object type was passed to the method.
Action	The object type must correspond to a native type (Boolean, Byte, Short, Integer, Long, Float, Double) or a String.
BRM.010.1054E	Unexpected end of stream when reading message.
Explanation	The end of the bytes stream reached while reading the message.
Action	Verify the contents of BytesMessage.
BRM.010.1060E	Unable to convert Map Message field "{0}" to {1}.
Explanation	The client attempted to get a field using the incorrect type.
Action	Retrieve the field using the correct or compatible type.
BRM.010.1061E	Map Message field "{0}" cannot have type "{1}".
Explanation	An unsupported object type was passed to the method.
Action	The type must be an object corresponding to a native type (Boolean, Byte, Short, Integer, Long, Float, Double) or a String.
BRM.010.1062E	Map Message field name cannot be null.
Explanation	The field name passed was null.
Action	Supply a non-null value.
BRM.010.1063E	Map Message field name cannot be an empty string.
Explanation	The field name passed was an empty string.
Action	Supply a non-empty string.
BRM.010.1064E	MapMessage.setBytes for field "{0}": offset + length exceeds value size.
Explanation	The number of bytes passed to the operation are less than the total expected size (offset + length).
Action	Please make sure that the byte array is of correct size.

BRM.010.1070E	Exception occurred while setting object in Object Message: "{0}"
Explanation	An error occurred while serializing the object.
Action	Verify that the object can be serialized properly.
BRM.010.1071E	Exception occurred while getting object from Object Message: "{0}"
Explanation	An error occurred while deserializing the object.
Action	Verify that the object can be deserialized properly.
BRM.010.1080E	Unable to convert Stream Message field at position {0} to {1}.
Explanation	The client attempted to read a field using an incorrect type.
Action	Retrieve the field using the correct or a compatible type.
BRM.010.1081E	Stream Message field at position {0} cannot have type "{1}".
Explanation	An unsupported object type was passed to the method.
Action	The type must be an object corresponding to a native type (Boolean, Byte, Short, Integer, Long, Float, Double) or a String.
BRM.010.1082E	Read called while bytes still remain in bytes field.
Explanation	The client attempted to read the next field of a StreamMessage while there were bytes remaining in the previous field.
Action	Make sure all the bytes of a field are read before attempting to read the content of the next field.
BRM.010.1083E	Unexpected end of stream when reading message at position {0}.
Explanation	The end of the stream has been reached.
Action	Verify the contents of StreamMessage.
BRM.010.1090E	WmFileMessage.saveFile can only be called on a received message.
Explanation	This could happen if the WmFileMessage.saveFile method is called before the Consumer is set for the message.
Action	Please make sure that the Consumer is set for the message before calling the WmFileMessage.saveFile method.

BRM.010.1100E	Selector syntax error: {0}
Explanation	The message selector contains a syntax error.
Action	Correct the syntax of the message selector.
BRM.010.1101E	Selector contains unknown webMethods property name: {0}
Explanation	The message selector contains an unknown provider-specific property name.
Action	webMethods-specific property names begin with "JMS_WM". Correct the property name.
BRM.010.1102E	Selector contains invalid property name: {0}
Explanation	The message selector contains an invalid property name.
Action	Property names must be valid Java identifiers.
BRM.010.1103E	Selector contains unknown operator: {0}
Explanation	The message selector contains an unknown operator.
Action	Correct the operator in the message selector.
BRM.010.1104E	Selector contains invalid ESCAPE character: <{0}>. Must be a single character.
Explanation	The message selector contains an invalid escape character.
Action	Correct the escape character in the message selector.
BRM.010.1105E	Selector contains invalid LIKE ESCAPE pattern: escape character at end of selector.
Explanation	The message selector contains an escape character at the end of the pattern.
Action	Correct the pattern in the message selector.
BRM.010.1106E	Selector contains invalid value for JMSDeliveryMode: {0}. Must be 'PERSISTENT' or 'NON_PERSISTENT'.
Explanation	The message selector contains an invalid value for the JMSDeliveryMode property.
Action	The delivery mode value must be either NON_PERSISTENT or PERSISTENT.
BRM.010.1200E	Cannot call commit or rollback on an XASession.
Explanation	An XASession's commit or rollback method was called.
Action	It is illegal to call an XASession's commit or rollback method.

BRM.010.1201E	Subscription name is null.
Explanation	A null subscription name was passed when creating a durable subscriber.
Action	A non-null subscription name must be used when creating a durable subscriber.
BRM.010.1202E	Client ID is not set.
Explanation	The connection's client ID is not set.
Action	In order to create a durable subscription, the connection's client ID must be set.
BRM.010.1203E	Client ID is already set.
Explanation	The client attempted to set the connection's client ID when the client ID was already set.
Action	Verify that the connection's client ID is set only once.
BRM.010.1204E	Connection is closed.
Explanation	General error thrown when the connection is closed. This could occur if the Broker is down or there is an operation on the connection after it has been closed.
Action	Please make sure the connection is open and the Broker is running. Also, the method which threw this error should not be called after the connection is closed.
BRM.010.1206E	Session is not transacted.
Explanation	The client attempted to call commit or rollback on a session that is not transacted.
Action	Create a transacted session.
BRM.010.1208E	Illegal method call from message listener: {0}
Explanation	The stop or close method was called within a message listener.
Action	The stop or close method must not be called by a message listener.
BRM.010.1209E	Session conflict between message consumer and listener.
Explanation	The client attempted to create a message consumer when the session already has a message listener, or attempted to add a message listener to the session when the session already has a message consumer.
Action	A session may not have both message listener and message consumer.

BRM.010.1210E	Message producer is closed.
Explanation	The client attempted to invoke a method on a closed message producer.
Action	Make sure that the message producer is closed only after it is no longer needed.
BRM.010.1211E	Message consumer is closed.
Explanation	The client attempted to invoke a method on a closed message consumer.
Action	Verify the program logic so that the message consumer is closed only after it is no longer needed.
BRM.010.1212E	Message consumer is receiving messages asynchronously.
Explanation	The client attempted to call receive on a message consumer that has a message listener.
Action	A message consumer may only receive messages asynchronously through a message listener or synchronously by invoking the receive method.
BRM.010.1213E	Queue browser is closed.
Explanation	The client attempted to invoke a method on a closed queue browser.
Action	Verify the program logic so that the queue browser is closed only after it is no longer required.
BRM.010.1214E	Invalid method in domain: {0}
Explanation	The client attempted to invoke a domain inappropriate method. It is an error to invoke a domain inappropriate method such as TopicSession.createQueue.
Action	Make sure that the correct methods are invoked.
BRM.010.1215E	Temporary destination "{0}" has been deleted.
Explanation	The client attempted to use a deleted temporary destination.
Action	Verify the program logic so that the temporary destination is deleted only after it is no longer needed.
BRM.010.1216E	Temporary destination "{0}" does not belong to this connection.
Explanation	The client attempted to create a message consumer with a temporary destination that does not belong to the connection.
Action	A temporary destination can only be consumed by the connection that created it.

BRM.010.1217E	Temporary destination "{0}" is in use.
Explanation	The client attempted to delete a temporary destination that is in use.
Action	Verify that the temporary destination is no longer in use before deleting it.
BRM.010.1218W	Session has no message listener.
Explanation	The application server failed to register a message listener for a session in the server session pool.
Action	No action required.
BRM.010.1219E	Invalid acknowledge mode: {0}
Explanation	The client attempted to create a non-transacted session using an invalid acknowledge mode value.
Action	The only allowed acknowledge mode values are Session.AUTO_ACKNOWLEDGE, Session.CLIENT_ACKNOWLEDGE, and Session.DUPS_OK_ACKNOWLEDGE.
BRM.010.1220E	Invalid delivery mode value: {0}
Explanation	The client attempted to send a message with an invalid delivery mode value.
Action	The only allowed delivery mode values are DeliveryMode.PERSISTENT and DeliveryMode.NON_PERSISTENT.
BRM.010.1221E	Invalid priority: {0}. Valid priority values range from 0 to 9.
Explanation	The client attempted to send a message with an invalid priority value.
Action	The valid range for message priority value is 0 to 9.
BRM.010.1222E	Destination is read-only.
Explanation	Attempted to edit a property of a Destination, which is read-only.
Action	Before making any changes to a Destination, make sure that the Destination is not read-only.
BRM.010.1223E	Connection factory is read-only.
Explanation	The client attempted to modify the administered object, which is in read-only mode.
Action	The client must not attempt to modify an administered object that is in the read-only mode.

BRM.010.1224W	Transaction rolled back due to lost connection.
Explanation	The client reconnected to the Broker resulting in open transactions being aborted.
Action	No action required.
BRM.010.1225W	Asynchronous message listener has thrown an exception.
Explanation	The client's message listener code has thrown a RuntimeException.
Action	Verify the message listener's code.
BRM.010.1226E	Client ID cannot be set because the connection is already in use.
Explanation	The client invoked the Connection.setClientID method after the connection has been in use.
Action	It is illegal to invoke the Connection.setClientID method after the connection is in use.
BRM.010.1227E	Unable to instantiate marshalling class: {0}. Incorrect type.
Explanation	This would happen if the Marshalling class is not assignable to the Marshalling interface.
Action	Please make sure that the Marshalling class can be assigned to the Marshalling interface.
BRM.010.1228E	Unable to instantiate marshalling class: {0}. Class not found.
Explanation	This would happen when the Marshalling class is not present in the classpath of the application or that class cannot be loaded.
Action	Please make sure the Marshalling class can be loaded during runtime.
BRM.010.1229E	Unable to instantiate marshalling class: {0}. InstantiationException.
Explanation	This would happen if the class used for Marshalling is not instantiable.
Action	Please make sure that the class used for Marshalling can be initialized using reflection.
BRM.010.1230E	Unable to instantiate marshalling class: {0}. IllegalAccessException.
Explanation	This would happen if the instantiation of class used for Marshalling throws an IllegalAccessException.
Action	Please make sure that the class used for Marshalling can be initialized using reflection without any exceptions.

BRM.010.1231E	Unable to set marshalling classname: "{0}" is not a valid Java Class name.
Explanation	This would happen when Marshalling class name is not valid.
Action	Please make sure that the Marshalling class name is a valid Java class name.
BRM.010.1233E	The operation failed because the client queue is busy. Please retry your operation.
Explanation	This error is thrown when Broker is busy finishing up the previous operation, usually related to territory synchronization. For example, consider a Broker is asked to leave a territory and then join another territory. The territory join operation may fail with this error if the leave territory operation is still going on asynchronously in the background.
Action	Retry the operation after some time.
BRM.010.1236E	Exception while retrieving the QueueBrowser messages.
Explanation	Could not browse the queue for messages.
Action	Contact Software AG Global Support.
BRM.010.2000E	Client ID is null.
Explanation	The client called the Connection.setClientID method with a null client identifier.
Action	The client identifier must be non-null.
BRM.010.2001E	Client ID is invalid: "{0}"
Explanation	The client called the Connection.setClientID method with an invalid client identifier.
Action	The client identifier must be valid.
BRM.010.2002E	Client ID "{0}" is already in use.
Explanation	This error can occur on clients without shared state enabled. The client called the Connection.setClientID method with a client identifier that is already in use.
Action	Make sure your application does not create multiple clients with same client ID for queues that do not have shared state enabled.
BRM.010.2003E	Client ID "{0}" shared state connection limit has been exceeded.
Explanation	The number of allowed shared connections for the client identifier has exceeded the limit.
Action	Increase the client's session limit on the Broker or limit the number of connections that are sharing the same client identifier.

BRM.010.2004W	Client ID "{0}" does not exist.
Explanation	The client attempted to reconnect to a client identifier that does not exist.
Action	The client ID must be existing and valid for reconnection.
BRM.010.2005E	Client ID "{0}" already exists with {1}={2}.
Explanation	The client attempted to reconnect to a client identifier with property values that differ from the existing client on the Broker.
Action	Use a different client identifier.
BRM.010.2100E	Invalid shared state ordering value: {0}
Explanation	The client specified an invalid shared state ordering value.
Action	The shared state ordering value must be either WmDestination.SHARED_STATE_ORDERING_NONE or WmDestination.SHARED_STATE_ORDERING_PUBLISHER.
BRM.010.2101E	Invalid storage value: {0}
Explanation	The administration client specified an invalid storage type value.
Action	The storage type value must be either WmJMSAdmin.STORAGE_GUARANTEED or WmJMSAdmin.STORAGE_VOLATILE.
BRM.010.2102E	Invalid lifecycle value: {0}
Explanation	The administration client specified an invalid lifecycle value.
Action	The lifecycle value must be either WmJMSAdmin.LIFECYCLE_DESTROY_ON_DISCONNECT or WmJMSAdmin.LIFECYCLE_EXPLICIT_DESTROY.
BRM.010.2103E	Invalid validation value: {0}
Explanation	The administration client specified an invalid validation value.
Action	The validation type value must be either WmJMSAdmin.VALIDATION_NONE, WmJMSAdmin.VALIDATION_OPEN, or WmJMSAdmin.VALIDATION_FULL.
BRM.010.2104E	Invalid TTL value: {0}. Must be greater than zero, or zero to disable TTL.
Explanation	The client specified an invalid Time to Live (TTL) value.
Action	The Time to Live (TTL) value must be greater than or equal to zero.

BRM.010.2105E	Invalid recover mode: {0}. Must be either 0 (restricted) or 1 (global).
Explanation	The administration client specified an invalid value for transaction recover mode.
Action	The transaction recover mode must be either WmJMSAdmin.RECOVER_GLOBAL or WmJMSAdmin.RECOVER_RESTRICTED.
BRM.010.2106E	Invalid timeout action: {0}. Must be either 1 (commit) or 2 (rollback).
Explanation	The administration client specified an invalid transaction timeout action.
Action	The transaction timeout action must be either WmJMSAdmin.TRANSACTION_COMMIT or WmJMSAdmin.TRANSACTION_ROLLBACK.
BRM.010.2107E	Invalid timeout: {0}
Explanation	An invalid value is used for setting the timeout.
Action	Please refer to webMethods Broker documentation for providing the valid values for timeout.
BRM.010.2108E	Invalid event type name: {0}
Explanation	The administration client specified an invalid event type name.
Action	Specify a valid event type name when creating an event.
BRM.010.2109E	Invalid Broker name: "{0}"
Explanation	The administration client specified an invalid Broker name.
Action	Specify a valid Broker name when creating a Broker.
BRM.010.2110E	Invalid territory name: "{0}"
Explanation	The administration client specified an invalid territory name.
Action	Specify a valid territory name when creating a territory.
BRM.010.2111E	Invalid client group name: "{0}"
Explanation	The administration client specified an invalid client group name.
Action	Specify a valid client group name when creating a client group.

BRM.010.2112E	Invalid client name: "{0}"
Explanation	The administration client specified an invalid client name.
Action	Specify a valid client name when creating a client.
BRM.010.2113E	Client "{0}" already exists.
Explanation	The administration client attempted to create a client that already exists.
Action	Before creating the client, verify that the client does not already exist.
BRM.010.2114E	Client "{0}" does not exist.
Explanation	The administration client attempted to destroy a client that does not exist.
Action	Before attempting to destroy a client, verify that the client exists.
BRM.010.2115E	Client group "{0}" already exists.
Explanation	The administration client attempted to create a client group that already exists.
Action	Before creating a client group, verify that the client group does not already exist.
BRM.010.2116E	Event type "{0}" already exists.
Explanation	The administration client attempted to create an event type that already exists.
Action	Before attempting to create an event type, make sure that the event type does not already exist.
BRM.010.2117E	Broker "{0}" already exists.
Explanation	The administration client attempted to create a Broker that already exists.
Action	Before trying to create a Broker, verify that Broker does not already exist.
BRM.010.2118E	Broker "{0}" does not exist.
Explanation	The administration client attempted to destroy a Broker that does not exist.
Action	Before attempting to destroy a Broker, verify that the Broker exists.
BRM.010.2119E	Broker is not in a territory.
Explanation	The administration client is connected to a Broker that does not belong to a territory.
Action	Verify that the Broker belongs to a territory before invoking a method applicable to a territory.

BRM.010.2120E	Broker is already in a territory.
Explanation	The administration client is connected to a Broker that already belongs to a territory.
Action	Before attempting to add a Broker to a territory, verify that the Broker does not belong to a territory.
BRM.010.2121E	The filter "{0}" contains a parse error.
Explanation	The administration client passed an invalid Broker filter to a client subscription.
Action	Provide the correct Broker filter.
BRM.010.2122E	Administration client is closed.
Explanation	A method was invoked on a closed administration client.
Action	Correct the code to make sure that the administration client is closed only after all the required operations are performed.
BRM.010.2123E	Conflicting event types and/or client groups with territory to be joined.
Explanation	The administration client attempted to join a Broker to a territory that has event type or client group conflicts.
Action	Fix the conflicts before attempting to join the Broker to the territory.
BRM.010.2125E	The client group "{0}" has existing clients which should be destroyed first.
Explanation	The administration client attempted to destroy a client group that is being used by existing clients.
Action	Before attempting to destroy a client group, destroy the clients that are using that client group.
BRM.010.2126E	The event type "{0}" has client groups which has "can publish" or "can subscribe" permission. These permissions should be removed first.
Explanation	The administration client attempted to destroy an event type that has "can publish" or "can subscribe" permissions on a client group.
Action	Remove the client group permissions before attempting to destroy the event type.
BRM.010.2127E	Cannot destroy a Broker while it is in a territory.
Explanation	The administration client attempted to destroy a Broker belonging to a territory.
Action	Remove the Broker from its territory before attempting to destroy the Broker.

BRM.010.2200E	Event type "{0}" does not exist.
Explanation	The client attempted to use an event type that does not exist.
Action	Create the event type on Broker before attempting to use that event type.
BRM.010.2201E	Queue "{0}" does not exist.
Explanation	The client attempted to access a queue that does not exist on the Broker.
Action	Create the queue on the Broker before using the queue.
BRM.010.2202E	Queue "{0}" already exists.
Explanation	The client attempted to create a queue that already exists on the Broker.
Action	Verify that the queue does not exist before attempting to create the queue.
BRM.010.2203E	Queue "{0}" is in use.
Explanation	The client attempted to access a queue that is already in use by another client.
Action	For multiple access to a queue, the destination's shared state property must be set.
BRM.010.2204E	Queue "{0}" has reached its maximum share limit.
Explanation	The client attempted to consume messages from a shared state queue that has reached its share limit.
Action	Increase the queue's session limit on the Broker or limit the number of consumers that are sharing the same queue.
BRM.010.2205E	Cannot connect to queue "{0}" with {1}={2}. It already exists with a conflicting value.
Explanation	The client attempted to use a queue whose properties differ from the properties of the queue on the Broker.
Action	Verify that the queue's properties are identical to the properties of the queue on the Broker.
BRM.010.2206E	Queue name is invalid: "{0}"
Explanation	The client specified an invalid queue name.
Action	The client must use a valid queue name. Check the queue naming specification in the webMethods Broker documentation.

BRM.010.2207E	Durable subscription "{0}" does not exist.
Explanation	The client attempted to reconnect to a durable subscription that does not exist.
Action	Create the durable subscription on the Broker before attempting to reconnect to it.
BRM.010.2208E	Durable subscription "{0}" already exists.
Explanation	The client attempted to create a durable subscription that already exists on the Broker.
Action	For multiple access to a durable subscription, you must set the destination's shared state property.
BRM.010.2209E	Durable subscription "{0}" is in use.
Explanation	The client attempted to unsubscribe a durable subscription that is in use.
Action	Verify that the durable subscription is no longer in use before attempting to unsubscribe.
BRM.010.2210E	Durable subscription "{0}" has reached its maximum share limit.
Explanation	The client attempted to consume messages from a shared state durable subscription that has reached its share limit.
Action	Increase the durable subscription's session limit on the Broker or limit the number of consumers that are sharing the same durable subscription.
BRM.010.2211E	Cannot connect to durable subscription "{0}" with {1}={2}. It already exists with a conflicting value.
Explanation	The client attempted to use a durable subscription whose properties differ from the properties of the durable subscription on the Broker.
Action	Verify that the durable subscription properties are identical to the properties of the durable subscription on the Broker.
BRM.010.2212E	Durable subscription name is invalid: "{0}"
Explanation	The client specified an invalid subscription name.
Action	The client must use a valid subscription name.
BRM.010.2213E	Destination name is null.
Explanation	The client attempted to use a null destination.
Action	Verify that the destination is not null.

BRM.010.2214E	Invalid destination class: "{0}"
Explanation	The client attempted to use a foreign destination.
Action	Verify that the destination is a webMethods destination.
BRM.010.2215E	Invalid destination: "{0}". Wildcard not allowed.
Explanation	The client attempted to publish to a destination specified by a wildcard.
Action	Make sure that the destination for client publish is not specified by a wildcard.
BRM.010.2216E	Invalid destination: "{0}"
Explanation	The Destination Name provided is invalid.
Action	Please refer to webMethods Broker documentation and provide a valid Destination Name.
BRM.010.2217E	Invalid queue "{0}"; client not connected to territory "{1}".
Explanation	The client attempted to create a message consumer for a queue in a different territory.
Action	Verify that the client has access to the fully qualified queue name.
BRM.010.2218E	Invalid queue "{0}"; client not currently connected to Broker "{1}".
Explanation	The client attempted to create a message consumer for a queue on a different Broker.
Action	Verify that the client has access to the fully qualified queue name.
BRM.010.2219E	Client group "{0}" does not exist.
Explanation	The client attempted to use a client group that does not exist on the Broker.
Action	Create the client group on the Broker.
BRM.010.2220E	Connection factory is null.
Explanation	The administration client passed null to a method that requires a connection factory.
Action	Make sure a non-null connection factory value is passed to the method.
BRM.010.2221E	Destination is null.
Explanation	The Destination Name passed to an operation is null.
Action	Please make sure the Destination Name is not null before passing it to an operation.

BRM.010.2223E	Magic number not found.
Explanation	This is an internal error.
Action	Please contact Software AG Global Support. You may try to work around this error by reconnecting the clients or restarting the Broker.
BRM.010.2224E	File name is null.
Explanation	This would happen when the File Name passed to "WmFileMessage.setFileName" is null.
Action	Please make sure that the File Name is not null.
BRM.010.2225E	Corrupt Event: {0}.
Explanation	The reason for event corruption is mentioned in the exception message.
Action	Check the exception message and take appropriate action.
BRM.010.2227E	Infoset "{0}" does not exist.
Explanation	This could happen when there is call made to <code>com.webmethods.jms.protocol.AdminProtocolHandler.getClientInfoset(int, String)</code> or <code>com.webmethods.jms.protocol.AdminProtocolHandler.getEventTypeInfoset(int, String, String)</code> and the requested EventType or Client does not exist.
Action	Please make sure that the EventType or Client exists.
BRM.010.4000E	Bad Broker reply: "{0}"
Explanation	Broker connection could be down, or there is a socket exception.
Action	Check if Broker is active, then retry the operation. Otherwise, contact Software AG Global Support.
BRM.010.4001E	No response from Broker "{0}".
Explanation	The client failed to receive a response from the Broker within the Broker timeout value because the Broker stopped running, there was a network outage, or the Broker was too busy to respond.
Action	Verify that the Broker is running and there is network connectivity. You can increase the Broker timeout value by setting the <code>com.webmethods.jms.brokerTimeout</code> System property.

BRM.010.4002E	License expired.
Explanation	License provided has expired.
Action	Provide a valid license key.
BRM.010.4003W	Protocol is missing arguments.
Explanation	An internal error indicating that the Broker failed to return all the protocol arguments.
Action	No action required.
BRM.010.4005E	Incompatible Broker version. Supported versions are {0}.
Explanation	The version of Broker connected to client is not supported.
Action	Only the Broker versions listed are supported.
BRM.010.4006E	No default Broker at {0}.
Explanation	The client attempted to connect to the default Broker, but no Broker has been designated as the default Broker.
Action	Define a default Broker on the Broker Server, or have the client provide a Broker name.
BRM.010.4007E	Unknown Broker "{0}".
Explanation	Cannot connect to the Broker specified in the JMS connection factory.
Action	Specify a valid Broker name in the JMS connection factory.
BRM.010.4008E	Lost connection to Broker "{0}".
Explanation	The client lost connection to the Broker. The Broker closed the socket connection to the client.
Action	Check if that Broker is still running.
BRM.010.4009E	Unable to connect to Broker at "{0}": host not found
Explanation	The client attempted to connect to a Broker on a host that could not be found.
Action	Verify that the host exists.

BRM.010.4010E	Unable to connect to Broker at "{0}": out of resources
Explanation	The client failed to connect to the Broker because the Broker ran out of resources.
Action	Increase the number of allowed connections on the machine that the Broker is running on.
BRM.010.4011E	Unable to connect to Broker at "{0}": {1}
Explanation	The exception message explains why the client failed to connect to the Broker.
Action	Check the exception message and take appropriate action.
BRM.010.4012E	Invalid port number: {0}
Explanation	The client attempted to connect to a Broker using an invalid port number.
Action	The client must use a valid port number.
BRM.010.4013E	Unable to connect to Brokers at "{0}".
Explanation	The client failed to connect to any of the Brokers in the client's Broker list.
Action	If the Broker is not running, start the Broker. Otherwise, check the exception details and take appropriate action.
BRM.010.4028E	Invalid license.
Explanation	License provided is invalid.
Action	Provide a valid license key.
BRM.010.4031W	Client has been deleted.
Explanation	The client has been administratively deleted.
Action	No action required.
BRM.010.4032W	Queue cursor is out of bounds.
Explanation	This is an internal error indicating that the Broker queue's cursor is out of bounds.
Action	No action required.
BRM.010.4033W	Acknowledgement is out of order.
Explanation	An internal error indicating that message acknowledgement arrived out of order.
Action	No action required.

BRM.010.4034E	Duplicate sequence number.
Explanation	The sequence number passed by the JMS API for acknowledging the message is a duplicate one.
Action	Contact Software AG Global Support.
BRM.010.4035E	Bad sequence number.
Explanation	The sequence number passed by the JMS API for acknowledging the message is wrong.
Action	Contact Software AG Global Support.
BRM.010.4036W	Client has been destroyed.
Explanation	The client has been administratively destroyed.
Action	No action required.
BRM.010.4037W	Broker has run out of storage.
Explanation	The Broker to which the client is connected has run out of storage.
Action	No action required.
BRM.010.4038W	Protocol is missing arguments.
Explanation	An internal error indicating that the command sent to Broker is incorrect.
Action	Check the webMethods Broker documentation for the correct usage of commands.
BRM.010.4039W	Broker storage is corrupt.
Explanation	The Broker's storage has become corrupted.
Action	Run the server_qsck utility and check if the storage is recoverable. Another option is to restore the storage from a recent backup. This may require manual intervention for documents that have been processed since the last backup. Otherwise, contact Software AG Global Support.
BRM.010.4042W	Broker protocol error: {0}
Explanation	An internal error indicating a Broker protocol error.
Action	No action required.

BRM.010.4045W	Broker is out of memory.
Explanation	The Broker that the client is connected to has run out of memory.
Action	No action required.
BRM.010.4046W	Connection to Broker "{0}" has been reconnected.
Explanation	The current operation failed because of reconnection to the Broker.
Action	No action required.
BRM.010.4047E	Incompatible Broker version. Cannot connect to Broker server.
Explanation	The JMS connection could not be established because the Broker Server version is incompatible. The JMS API tried to connect to an unsupported version.
Action	Use a Broker Server version supported by this JMS API. Contact Software AG Global Support.
BRM.010.4048E	The publish operation could not be completed, because the Broker publication processing was paused by the administrator.
Explanation	The publish operation could not complete because the Broker is shutting down.
Action	Restart Broker, if you have manually shut down. If Broker has shut down automatically, wait until Broker restarts.
BRM.010.4100I	Reconnecting to "{0}" in {1} seconds.
Explanation	The client has lost its connection to the Broker and will be reconnecting.
Action	No action required.
BRM.010.4101I	Reconnected successfully to "{0}".
Explanation	The client has successfully reconnected to the Broker.
Action	No action required.
BRM.010.4241W	Transaction cannot be reopened.
Explanation	An internal error indicating that a closed transaction was attempted to be reopened.
Action	No action required.

BRM.010.4244E	Transaction has been heuristically rolled-back.
Explanation	The client attempted to use a transaction that has been heuristically rolled-back.
Action	The client must provide a new transaction.
BRM.010.4245E	Transaction has been heuristically committed.
Explanation	The client attempted to use a transaction that has been heuristically committed.
Action	The client must provide a new transaction.
BRM.010.5000E	No permissions for current operation.
Explanation	The administration client does not have sufficient permissions for the current operation.
Action	Make sure that the administration client is using the "admin" client group.
BRM.010.5001E	No send permissions for event type "{0}" in client group "{1}"
Explanation	The client group used by the client does not have the send permissions for the destination's event type.
Action	Update the client group permissions to include the "can publish" permissions for the event type.
BRM.010.5002E	No receive permissions for event type "{0}" in client group "{1}"
Explanation	The client group being used by the client does not have the permissions to receive the destination's event type.
Action	Update the client group permissions to include the "can subscribe" permissions for the event type.
BRM.010.5003E	Client group "{0}" requires encryption
Explanation	The client group being used by the client requires SSL encryption.
Action	Configure the client to use SSL encryption.
BRM.010.5057E	SSL handshake failed with Broker at "{0}"
Explanation	The client was unable to connect with SSL to the Broker Server.
Action	Verify that SSL has been configured correctly on both the Broker Server and the client.

BRM.010.5058E	Cannot establish a secure socket connection on "{0}". However, Broker Server is running.
Explanation	The Broker Server is not configured for SSL.
Action	Configure the Broker Server for SSL.
BRM.010.5059E	SSL is not available: {0}
Explanation	The SSL library could not be loaded for the indicated reason.
Action	Check the exception message and take appropriate action.
BRM.010.5060E	SSL keystore "{0}": not found
Explanation	A certificate for the distinguished name was not found in the client's keystore.
Action	The client's keystore must contain a certificate for the distinguished name.
BRM.010.5061E	SSL certificate "{0}": bad certificate.
Explanation	The client's certificate is bad.
Action	Make sure the client uses a valid certificate.
BRM.010.5062E	SSL certificate is not found.
Explanation	The client provided a null keystore name.
Action	The client must specify a non-null keystore name.
BRM.010.5063E	SSL certificate "{0}": invalid password
Explanation	The client provided an incorrect password for the keystore.
Action	Provide a correct password for the keystore.
BRM.010.5064E	SSL context create failed: {0}
Explanation	The client was unable to create an SSL context.
Action	Check the exception message and take appropriate action.
BRM.010.5065E	SSL client certificate is expired.
Explanation	The client's certificate is expired.
Action	Make sure the client uses a new certificate.

BRM.010.5066E	SSL certificate for distinguished name "{0}" not found.
Explanation	The client's keystore does not contain a certificate for the specified distinguished name.
Action	Verify that the client's keystore contains a certificate for its distinguished name.
BRM.010.5067E	SSL certificate file contains multiple valid certificates.
Explanation	The client's keystore contains multiple certificates for the same distinguished name.
Action	The client's keystore should contain only one certificate for its distinguished name.
BRM.010.5068E	SSL distinguished name "{0}" is malformed.
Explanation	The client provided an incorrect format for the distinguished name.
Action	Fix the format of the distinguished name.
BRM.010.5070E	SSL certificate is not certified.
Explanation	The Broker Server's certificate is not trusted.
Action	Verify that the client's keystore contains the correct trusted certificates in order to certify the Broker Server's certificate.
BRM.010.5071E	SSL server certificate is expired.
Explanation	The Broker Server's certificate has expired.
Action	Configure the Broker Server with a new certificate.
BRM.010.5072E	SSL truststore "{0}": not found
Explanation	Could not create the SSL connection because the SSL truststore is missing.
Action	Provide the SSL truststore in the connection factory settings.
BRM.010.5073S	The host was found, but no Broker Server is running with secure sockets support on that host: {0}
Explanation	Broker Server is not running on the SSL port because it is not SSL enabled or SSL port is blocked.
Action	Make sure the Broker Server is SSL enabled and the SSL port (main port -2) is not blocked.

BRM.010.5076E	Basic Authentication failed for username: {0}
Explanation	The basic authentication user name provided is not valid.
Action	Provide a valid basic authentication user name.
BRM.010.5077E	Cannot make an Basic Authentication connection to Broker: username is missing.
Explanation	User name is not provided for basic authentication.
Action	Provide the user name for configuring basic authentication.
BRM.010.5078E	Cannot make an Basic Authentication connection to Broker: password is missing.
Explanation	Password is not provided for basic authentication.
Action	Provide the basic authentication password.
BRM.010.5100E	Cannot make SSL connection to Broker: keystore is missing.
Explanation	The administration client attempted to create an SSL connection to the Broker without specifying a keystore.
Action	Specify a keystore.
BRM.010.5101E	Cannot make an authenticated connection to Broker: username is missing.
Explanation	The administration client attempted to create an SSL connection to the Broker without specifying a distinguished name.
Action	Specify a distinguished name.
BRM.010.5102E	Cannot make an authenticated connection to Broker: password is missing.
Explanation	The administration client attempted to create an SSL connection to the Broker without specifying a password.
Action	Specify the keystore's password.
BRM.010.5103E	Cannot make SSL connection to Broker: truststore is missing.
Explanation	The truststore was not provided while creating a SSL connection to the Broker.
Action	The truststore should be provided in the connection factory settings while creating a SSL connection to the Broker.

BRM.010.6048E	Exception occurred while processing marshalled event: "{0}"
Explanation	This would happen when there is an error while marshalling the event.
Action	Please check the implementation of WmMarshalOut for errors.
BRM.010.6049E	Runtime exception in marshalling method: "{0}"
Explanation	There is an exception in the "mapMessageToEvent" method of "WmMarshalOut" implementation.
Action	Please check for errors in the implementation of "WmMarshalOut".
BRM.010.6050E	Marshalling method returned an event that does not have an event type name.
Explanation	This would happen if the "mapMessageToEvent" method of the implementation of "WmMarshalOut" is not setting the event type name.
Action	Please make sure that the implementation of "WmMarshalOut" is setting the event type name.
BRM.010.6052E	Exception occurred creating event from wire format: "{0}"
Explanation	This would happen when the data bytes in the message cannot be read into an object Marshalling class.
Action	Please make sure the data can be read into the specified Marshalling class.
BRM.010.6053E	Exception occurred while marshalling event to message: "{0}"
Explanation	This exception is thrown from "mapMessageFromEvent" method of the class implementing "WmMarshalIn".
Action	Please check the implementation of the Marshalling class.
BRM.010.6054E	Runtime error occurred while marshalling event to message: "{0}"
Explanation	This is a runtime exception thrown from "mapMessageFromEvent" method of the class implementing "WmMarshalIn".
Action	Please check the implementation of the Marshalling class.
BRM.010.6059E	Access label cannot be set to negative value(s).
Explanation	Access label cannot be set to a negative value.
Action	Please provide a positive value for the Access label.

BRM.010.8001E	Compression failed.
Explanation	This could happen when compression is enabled for a message and there is a failure in data compression.
Action	Make sure that the Compression Level is correctly used. Also, this signifies general IOException in the java.io.DataOutputStream.
BRM.010.8002E	Decompression failed.
Explanation	This could happen when compression is enabled for a message and there is a failure in data decompression.
Action	Make sure that the Compression Level is correctly used. Also, this signifies general IOException in the java.io.DataOutputStream.
BRM.010.9001E	Specified load balancing policy is not valid. Please provide a valid load balancing policy
Explanation	The specified load balancing policy is not valid.
Action	Please provide a valid load balancing policy. The valid policy names are "MULTISEND_GUARANTEED", "RANDOM", "ROUND_ROBIN", "STICKY", "WEIGHTED_ROUND_ROBIN" and "MULTISEND_BEST_EFFORT".
BRM.010.9003E	Unable to connect to any Brokers in the cluster: {0}
Explanation	The Brokers in the cluster are down and not reachable. So the JMS API could not connect to any Broker in the cluster.
Action	Ensure that all Brokers in the cluster are active and responding. Retry the connect operation after the Brokers are available.
BRM.010.9004e	Local Transactions are not supported for Multi Send Best Effort policy.
Explanation	Multi Send Best effort policy is not supported in JMS local transactions.
Action	Do not use local transactions when using the Multi Send Best effort policy.
BRM.010.9005E	Failed to set Message Listener: {0} for Broker:{1}. Exception Message is: {2}.
Explanation	This could happen if the JMS Connection is closed or the said Broker is down, or there are Consumers created with a previously set Listener.
Action	Please make sure that the JMS Connection is open, Broker is running, and Consumers have not already been created with another Listener.

BRM.010.9006E	Failed to set Message Listener: {0} for the Cluster.
Explanation	The JMS API could not set the asynchronous message listener for the cluster.
Action	Contact Software AG Global Support.
BRM.010.9013	Application Server Facilities is not supported in JMS Clustering.
Explanation	We do not support Application Server Facilities (ASF) in JMS Clustering.
Action	Do not use Application Server Facilities (ASF) APIs with JMS Clustering.
BRM.010.9015E	Could not publish message: {0} as no Brokers are available to publish
Explanation	The Brokers in the cluster are down and not reachable. So the JMS API could not publish the message to any Broker in the cluster.
Action	Ensure that all Brokers in the cluster are active and responding. Retry the publish operation after the Brokers are available.
BRM.010.9016E	Cluster Multi-Send Best Effort publish failed for message: {0}
Explanation	Could not publish to the minimum number of Brokers in the cluster.
Action	Contact Software AG Global Support.
BRM.010.9017E	Could not publish message {0} as an XA session is not available to publish.
Explanation	This could happen if the API cannot allocate an XA Session for the publish operation. Also, if the Cluster Policy Override is used and the defined Broker is not able to have an XA Session for this publish.
Action	Make sure that the Brokers in the Cluster allow XA Session. If the Cluster Policy Override is in use, the selected Broker must be running.
BRM.010.9018E	Cluster Multi Send Broker count should be greater than or equal to one.
Explanation	The cluster Multi Send Broker count specified is not greater than zero.
Action	Make sure the cluster Multi Send Broker count is greater than zero.
BRM.010.9019E	Composite Cluster: Could not publish message {0} as an XA session is not available to publish.
Explanation	This could happen if the required XA Session(s) cannot be allocated. Also, if the Cluster Policy Override is used and the defined Broker is not able to give an XA Session for this publish.
Action	Make sure that the Brokers in the cluster(s) of the composite allow XA Session. If the Cluster Policy Override is in use, the selected Broker(s) must be running.

BRM.010.9020E	Specified Cluster Policy {0} is invalid.
Explanation	The specified Cluster Policy in the connection factory is not valid.
Action	Please specify a valid cluster policy.
BRM.010.9021E	Specified Cluster Brokers is null. Please specify valid Brokers for the cluster.
Explanation	Specified Cluster Brokers is null.
Action	Please specify valid Brokers for the cluster.
BRM.010.9022E	Specified Cluster name is null. Please specify a valid name for the cluster.
Explanation	Specified Cluster name is null.
Action	Please specify a valid name for the cluster.
BRM.010.9023E	Specified Cluster Policy name is null. Please specify a valid name for the cluster policy.
Explanation	The specified cluster policy name is null.
Action	Please specify a valid name for the cluster policy.
BRM.010.9024E	Could not create the cluster connection. Specified Broker: {0} not a part of Cluster {1}
Explanation	Could not create the cluster connection as the specified Broker is not a not a part of Cluster.
Action	Add the Broker to the cluster and then create the cluster connection.
BRM.010.9025E	Not able to recieve messages. Cluster Brokers not available.
Explanation	The Brokers in the cluster are down and not reachable. So the JMS API could not get any messages from the cluster.
Action	Ensure that all Brokers in the cluster are active and responding. Retry the receive operation after the Brokers are available.
BRM.010.9028E	Please check the type of composite child factories set .It is inconsistent with the Composite Cluster Factory.
Explanation	This error can occur when a Cluster Connection Factory of a different type is added to a Composite Cluster Connection Factory.
Action	Make sure all the Cluster Connection Factories are of the same type as that of the Composite Cluster Connection Factory to which they are being added to.

BRM.010.9029E	Could not unsubscribe {0} on Broker {1} . Exception message is: {2}
Explanation	This could happen if the JMS Connection is closed, or the Broker is down, or the Destination name is null, or the Destination is already unsubscribed from the Brokers and unsubscribe is not forced.
Action	Make sure that the JMS Connection is open, the Brokers are running, the Destination name is not null, and the Destination is not already unsubscribed from the Brokers or unsubscribe is forced.
BRM.010.9030	Could not unsubscribe {0} on the Cluster . Exception message is: {1}
Explanation	This could happen if the JMS Connection is closed, or all the Brokers in the cluster are down, or the Destination name is null, or the Destination is already unsubscribed from all the Brokers in the Cluster and unsubscribe is not forced.
Action	Make sure that the JMS Connection is open, all the Brokers in the cluster are running, the Destination name is not null, and the Destination is not already unsubscribed from all the Brokers in the Cluster or unsubscribe is forced.
BRM.010.9031E	Could not acknowledge: {0}
Explanation	The JMS API failed to acknowledge the message to a specific Broker in the cluster. The reason is provided in the exception message.
Action	Ensure that the Broker in the cluster is active and responding. Contact Software AG Global Support.
BRM.010.9032E	Could not acknowledge on the Cluster: Exception message is: {0}
Explanation	The JMS API failed to acknowledge the message in the cluster. The reason is provided in the exception message.
Action	Ensure that all Brokers in the cluster are active and responding. Contact Software AG Global Support.
BRM.010.9033E	Request events failed on all Brokers of the cluster
Explanation	The JMS API could not get the messages from any of the Brokers in the cluster.
Action	Contact Software AG Global Support.
BRM.010.9035E	Unable to connect to any Brokers in the composite cluster: {0}
Explanation	This would happen when creating a connection to a Composite Cluster Connection Factory, and if all the Brokers of all the Cluster Connection Factories that are a part of the Composite Cluster Connection Factory are down.
Action	Make sure that the Brokers in the Composite Cluster Connection Factory are running.

BRM.010.9036E	Specified Cluster Policy {0} is not supported for Composite Cluster Connection Factory.
Explanation	The specified cluster policy is not supported for Composite Cluster Connection Factory.
Action	Check the webMethods Broker documentation and specify a valid cluster policy for the Composite Cluster Connection Factory.
BRM.010.9037E	Specified Cluster Policy {0} is not supported for Child Composite Cluster Connection Factory.
Explanation	The cluster policy of the cluster connection factory added to a composite cluster connection factory is not supported.
Action	Make sure that the cluster policies of all the children of composite cluster connection factory are supported. webMethods Broker documentation contains information about the policies supported.
BRM.010.9038E	Request for XA resources is only supported for Multi-Send Guaranteed policy.
Explanation	This would happen when a call is made to <code>com.webmethods.broker.connection.composite.WmCompositeClusterXASessionImpl.getMultiXAResources(String)</code> and the Cluster Policy is not Multi-send Guaranteed.
Action	Please make sure that the call to <code>getMultiXAResources</code> is made only on Composite Cluster Connection Factories with Cluster Policy set to Multi-send Guaranteed.
BRM.010.9039E	Adequate XA resources not available for Multi-Send Guaranteed policy.
Explanation	The multi send count set for the Multi-Send Guaranteed policy is greater than the number of active Brokers available.
Action	Set the multi send count to a value lesser than or equal to the number of active Brokers available.
BRM.010.9045E	Multisend count for Cluster connection should be greater than zero.
Explanation	Multisend count for Cluster connection cannot be zero or less than zero.
Action	Set the multisend count to a value greater than zero.
BRM.010.9046E	An error occurred while obfuscating the password in the "{0}" property file. {1}
Explanation	The error may occur if the API is unable to obfuscate the password.
Action	Make sure that "enttoolkit.jar" is present in the classpath, or contact Software AG Global Support.

BRM.010.9047E	An error occurred while obfuscating the password in the "{0}" property file. The 'enttoolkit.jar' file is missing in the classpath.
Explanation	The password obfuscation requires "enttoolkit.jar" in the classpath of the application.
Action	Make sure that "enttoolkit.jar" is present in the classpath.
BRN.100.1002	Name {0} not found.
Explanation	An object with the given lookup name is not found in the JNDI.
Action	Make sure the lookup name is correct.
BRN.100.1003	Name {0} is not a context. Remaining part of name is {1}
Explanation	A context is required to proceed with the operation, but the resolved object is not a context.
Action	Make sure the lookup name is correct.
BRN.100.1004	Unable to get the object instance for name: {0}. Object class: {1}. Exception: {2}
Explanation	Unable to get the object instance for the specified lookup name.
Action	Make sure the lookup name is correct.
BRN.100.1005	{0} is not a BrokerNamingContext. Object is: {1}
Explanation	The object is not a context.
Action	Make sure the lookup name is correct.
BRN.100.1006	Cannot bind an empty name.
Explanation	The name provided is empty or null.
Action	Provide a name that is not empty or null.
BRN.100.1007	Cannot bind {0}: An object is already bound to that name.
Explanation	The name is already bound to another object.
Action	Provide another name.
BRN.100.1009	Cannot bind a null value.
Explanation	The value provided is empty or null.
Action	Provide the correct value.

BRN.100.1010	Name: {0} has more components than the BrokerNamingContext can handle.
Explanation	The specified name does not conform to the syntax of a naming system.
Action	Provide the correct name.
BRN.101.1001	Lookup failed: Context has been closed or destroyed.
Explanation	The connection to the JNDI is destroyed or closed.
Action	Check the connection to the JNDI.
BRN.101.1002	Lookup failed: Name {0} not found.
Explanation	An object with the given lookup name is not found in the JNDI.
Action	Make sure the lookup name is correct.
BRN.101.1003	Lookup failed: Name {0} is not a context. Remaining part of name is {1}
Explanation	A context is required to proceed with the operation, but the resolved object is not a context.
Action	Make sure the lookup name is correct.
BRN.101.1004	Lookup failed: Unable to get the object instance for name: {0}. Object class: {1}. Exception: {2}
Explanation	Unable to get the object instance for the specified lookup name.
Action	Make sure the lookup name is correct.
BRN.102.1001	Bind failed: Context has been closed or destroyed.
Explanation	The connection to the JNDI is destroyed or closed.
Action	Check the connection to the JNDI.
BRN.102.1006	Bind failed: Cannot bind an empty name.
Explanation	The name provided is empty or null.
Action	Provide a name that is not empty or null.
BRN.102.1007	Bind failed: An object is already bound to the name {0}.
Explanation	The name is already bound to another object.
Action	Provide another name.

BRN.103.1001	Rebind failed: Context has been closed or destroyed.
Explanation	The connection to the JNDI is destroyed or closed.
Action	Check the connection to the JNDI.
BRN.103.1006	Rebind failed: Cannot rebind an empty name.
Explanation	The name provided is empty or null.
Action	Provide a name that is not empty or null.
BRN.104.1001	Unbind failed: Context has been closed or destroyed.
Explanation	The connection to the JNDI is destroyed or closed.
Action	Check the connection to the JNDI.
BRN.104.1002	Unbind failed: Name {0} not found.
Explanation	An object with the given lookup name is not found in the JNDI.
Action	Make sure the lookup name is correct.
BRN.104.1006	Unbind failed: Cannot unbind an empty name.
Explanation	The name provided is empty or null.
Action	Provide a name that is not empty or null.
BRN.105.1001	Rename failed: Context has been closed or destroyed.
Explanation	The connection to the JNDI is destroyed or closed.
Action	Check the connection to the JNDI.
BRN.105.1006	Rename failed: Cannot bind an empty name.
Explanation	The name provided for rename is empty or null.
Action	Provide a name that is not empty or null.
BRN.106.1001	List failed: Context has been closed or destroyed.
Explanation	The connection to the JNDI is destroyed or closed.
Action	Check the connection to the JNDI.

BRN.107.1001	List bindings failed: Context has been closed or destroyed.
Explanation	The connection to the JNDI is destroyed or closed.
Action	Check the connection to the JNDI.
BRN.107.1004	List bindings failed: Unable to get the object instance for name: {0}. Object class: {1}. Exception: {2}
Explanation	Unable to get the object instance for the specified lookup name.
Action	Make sure the lookup name is correct.
BRN.108.1001	Destroy subcontext failed: Context has been closed or destroyed.
Explanation	The connection to the JNDI is destroyed or closed.
Action	Check the connection to the JNDI.
BRN.108.1006	Destroy subcontext failed: Cannot destroy a subcontext without a name.
Explanation	The name provided for destroying the subcontext is empty or null.
Action	Make sure that the sub-context name is not empty or null.
BRN.108.1011	Destroy subcontext failed: Cannot destroy a non-empty subcontext. Subcontext has {0} entries.
Explanation	Cannot destroy a sub-context if it contains any entries.
Action	Make sure the sub-context is empty before attempting to delete it.
BRN.109.1001	Create subcontext failed: Context has been closed or destroyed.
Explanation	The connection to the JNDI is destroyed or closed.
Action	Check the connection to the JNDI.
BRN.109.1006	Create subcontext failed: Cannot destroy a subcontext without a name.
BRN.109.1007	Create subcontext failed: An object is already bound with the name {0}.
Explanation	The name is already bound to another object.
Action	Provide another name.

BRN.110.1008	Lookup link failed: Operation is not supported.
Explanation	The context does not support the operation invoked.
Action	Do not use this operation. This operation is not supported.
BRN.111.1001	GetNameParser failed: Context has been closed or destroyed.
Explanation	The connection to the JNDI is destroyed or closed.
Action	Check the connection to the JNDI.
BRN.112.1001	ComposeName failed: Context has been closed or destroyed.
Explanation	The connection to the JNDI is destroyed or closed.
Action	Check the connection to the JNDI.
BRN.112.1006	ComposeName failed: Cannot compose an empty name.
Explanation	The name provided is empty or null.
Action	Make sure that the name is not empty or null.
BRN.113.1001	AddToEnvironment failed: Context has been closed or destroyed.
Explanation	The connection to the JNDI is destroyed or closed.
Action	Check the connection to the JNDI.
BRN.113.1006	AddToEnvironment failed: Cannot add property without a name.
Explanation	The property name provided is empty or null.
Action	Make sure that the property name is not empty or null.
BRN.113.1009	AddToEnvironment failed: Cannot add property {0} without a value.
Explanation	The value provided for the property is empty or null.
Action	Provide the correct value for the property.
BRN.114.1001	RemoveFromEnvironment failed: Context has been closed or destroyed.
Explanation	The connection to the JNDI is destroyed or closed.
Action	Check the connection to the JNDI.

BRN.114.1006	RemoveFromEnvironment failed: Cannot remove property without a name.
Explanation	The property name provided for removal is empty or null.
Action	Make sure that the property name is not empty or null.
BRN.115.1001	GetEnvironment failed: Context has been closed or destroyed.
Explanation	The connection to the JNDI is destroyed or closed.
Action	Check the connection to the JNDI.
BRN.116.1001	GetNameInNamespace failed: Context has been closed or destroyed.
Explanation	The connection to the JNDI is destroyed or closed.
Action	Check the connection to the JNDI.
BRN.117.1013	Format is not recognized.
Explanation	The format of the URL provided is incorrect.
Action	Provide the correct URL format.
BRN.118.1018	Unable to reconstruct Context from {0} in {1}: Invalid Subcontext name: {2}.
Explanation	The sub-context provided is incorrect.
Action	Provide the correct sub-context.
BRN.118.1019	Unable to reconstruct ConnectionFactory {2} from {0} in {1}: JMS Exception: {3}
Explanation	An internal error occurred while loading the connection factory.
Action	Contact Software AG Global Support for further assistance and provide the exact steps to reproduce this issue.
BRN.118.1020	Unable to reconstruct Topic: {2} from {0} in {1}. JMS Exception: {3}
Explanation	An internal error occurred while loading the topic.
Action	Contact Software AG Global Support for further assistance and provide the exact steps to reproduce this issue.
BRN.118.1021	Unable to reconstruct Queue: {2} from {0} in {1}. JMS Exception: {3}

BRN.118.1022	Unable to load context {0} from: {1}. Broker Exception: {2}
BRN.118.1023	Unable to load context {0} from: {1}. I/O Exception: {2}
BRN.118.1024	Unable to load context {0} from: {1}. ClassNotFoundException: {2}
BRN.118.1028	Unable to load context {0} from: {1}. Context store name "{0}" is not a valid Broker Document name.
BRN.119.1019	Unable to serialize ConnectionFactory {2} from {0} in {1}: JMS Exception: {3}
Explanation	An internal error occurred while storing the connection factory.
Action	Contact Software AG Global Support for further assistance and provide the exact steps to reproduce this issue.
BRN.119.1020	Unable to serialize Topic: {2} from {0} in {1}. JMS Exception: {3}
Explanation	An internal error occurred while storing the topic.
Action	Contact Software AG Global Support for further assistance and provide the exact steps to reproduce this issue
BRN.119.1021	Unable to serialize Queue: {2} from {0} in {1}. JMS Exception: {3}
Explanation	An internal JMS error occurred while storing a queue.
Action	Contact Software AG Global Support for further assistance and provide the exact steps to reproduce this issue.
BRN.119.1022	Unable to store context {0} in: {1}. Broker Exception: {2}
Explanation	An internal Broker error occurred while storing data.
Action	Contact Software AG Global Support for further assistance and provide the exact steps to reproduce this issue.
BRN.119.1023	Unable to store context {0} in: {1}. I/O Exception: {2}
Explanation	An internal IO error occurred while storing data.
Action	Contact Software AG Global Support for further assistance and provide the exact steps to reproduce this issue.

- BRN.119.1025** **Unable to store context {0} in: {1}. Read-only access.**
Explanation No permission to destroy context because the client group has only read-only permissions.
Action Use "admin" client group.
- BRN.119.1026** **Unable to store context {0} in: {1}. Another process has changed the backing store.**
Explanation Concurrent data changes causes error while storing the data.
Action Try again after some time.
- BRN.120.1022** **Unable to destroy context {0} stored in: {1}. Broker Exception: {2}**
Explanation Internal Broker error occurred while destroying the context.
Action Contact Software AG Global Support for further assistance and provide the exact steps to reproduce this issue.
- BRN.120.1025** **Unable to destroy context {0} stored in: {1}. Read-only access.**
Explanation No permission to destroy context because the client group has only read-only permissions.
Action Use "admin" client group.
- BRN.121.1027** **Property {0} is not of type java.lang.String.**
Explanation One of the properties specified is not a String.
Action Make sure all the property values are of type String.
- BRN.121.1029** **Unable to set child cluster connection factories for Composite Factory {0} .Exception {1}**
Explanation Could not load the child cluster connection factories while loading the composite connection factory.
Action Contact Software AG Global Support for further assistance and provide the exact steps to reproduce this issue.
- BROKER_SERVER_STOPPINGE – Publish operation failed as the Broker is shutting down.**
Explanation When Broker is shutting down, the publish operation cannot be performed.
Action Restart Broker, if you have manually shut down. If Broker is shut down automatically, wait until Broker restarts.

COULD_NOT_IMPORT_ASSETSE – Deploying assets failed. Reason is:{0}

Explanation Asset deployment failed because of an error.
Action Please check the exception message and take necessary action.

ERRNAME_295 Blank Parameter**ERR_100_2023E The operation failed because the Broker Server is stopping.**

Explanation The operation failed because the Broker Server is stopping.
Action Resubmit the request after the Broker Server starts.

ERR_102_1022E Broker Monitor connection error. Broker Monitor is not running on the specified host: '{host}' and port: '{port}'.

Explanation Broker Monitor is not running at the specified host and port.
Action Specify the correct host and port. If the input is correct, contact the system administrator to start Broker Monitor.

ERR_109_2375 The document type {type_name} cannot be synchronized with the other territory because this document is not in the territory gateway shared event types list**ERR_118_1030 Unable to reconstruct ConnectionFactory {0} due to an invalid property value. Exception {1}****ERR_281_1814E The operation failed because the forward queue browsing is not supported on the Broker.**

Explanation Forward queue browsing is supported only on Broker version 8.2 or higher.
Action Upgrade to the latest version of Broker if you want to use the forward queue browsing feature.

ERR_281_1815E Could not complete operation. Remote Broker '{target_queue_id}' does not exist.

Explanation Specified remote Broker does not exist. The current Broker and the remote Broker should be present in the same territory or cluster, or at the two ends of the gateway.
Action Specify a valid remote Broker. Specify another Broker in the same territory or cluster, or a Broker at the other end of the gateway.

ERR_281_1816E **Invalid input arguments. The array length of sequence number and the array length of events must be equal.**

Explanation Array length of sequence number and events must be the same for the input to be valid.

Action Supply the correct arguments.

ERR_295_1403 **The input parameter '{param}' is blank.**

ERR_296_2501E **Basic Authentication failed for user: {auth_username}**

Explanation Either the user credentials provided are wrong or basic authentication is not enabled on Broker Server.

Action Make sure basic authentication is enabled on Broker Server. Provide the correct user credentials for authentication.

ERR_296_2502E **Basic Authentication password is not specified for user: {auth_username}**

Explanation A null password is specified.

Action Specify a non-null password.

ERR_297_1947E **Could not create the gateway. The specified Broker is not a member of cluster '{cluster_name}'.**

Explanation Cannot create a gateway because the Broker is not part of the specified cluster.

Action Make sure to provide a valid cluster name. Ensure that the specified Broker is part of that cluster.

ERR_297_1951E **There is no gateway defined on the current Broker that connects to cluster '{cluster_name}'.**

Explanation Current Broker does not have any remote Brokers belonging to the specified cluster.

Action Check if the specified cluster name is valid, or create a gateway from the current Broker to a remote Broker in the specified cluster.

ERR_298_1931E **Could not complete the operation. The Broker is not a member of a cluster.**

Explanation Broker must be a member of a cluster for the requested operation to succeed.

Action Ensure that Broker is a member of a cluster before making the call.

ERR_298_1932E	Cluster join failed. The remote Broker is not a member of a cluster.
Explanation	Current Broker could not join the cluster because the specified Broker is not a member of a cluster.
Action	Specify a Broker that is a member of a cluster.
ERR_299_1933E	The Broker cannot join a cluster because it is already in a cluster.
Explanation	The current Broker is already a member of a cluster. Broker should leave the current cluster before joining another cluster.
Action	Ensure that the Broker leaves the cluster before requesting to join another cluster.
ERR_299_1934E	The Broker cannot be destroyed while it is in a cluster with other Brokers. It must leave the cluster first.
Explanation	The Broker cannot be destroyed when it is part of a cluster along with the other Brokers. It must leave the cluster first.
Action	Make the Broker leave the cluster.
ERR_300_1930E	The cluster name '<code>{cluster}</code>' is not valid. Cluster names cannot contain unprintable characters, a colon, '@', '/', or '\ and they cannot start with a '#' symbol. They must be between 1 and 255 ANSI characters or 1 and 42 Unicode characters in length.
Explanation	Cluster names cannot contain unprintable characters such as a colon, '@', '/', or '\\'. Cluster names cannot start with a '#' symbol. The cluster name length must be between 1 and 255 ANSI characters or 1 and 42 Unicode characters.
Action	Provide a valid name.
ERR_301_2401E	The attempt to join the cluster at host '<code>{host}:{port}</code>' encountered an SSL handshake failure. Check the certificates and truststores for both Broker servers.
Explanation	SSL connection between Brokers failed. This problem usually happens when the SSL keystore of one of the Broker Server is not trusted by the other Broker Server.
Action	Check if Brokers are using compatible SSL keystores and truststores.
FAIL_GET_REFERENCEE – ObjectFactory.getReference() caught an exception.	
Explanation	This could happen if there is an error in creating a reference to the object passed to the method.
Action	Please make sure the class path contains the classes for which the reference has been created.

FILE_NOT_CREATEDE Cannot create file at location: {0}

- Explanation** The specified file path may not be valid, or there is no permission to create the file in the specified file path.
- Action** Check if the file path is valid. Make sure the permissions to create the file in the specified file path are available.

INVALID_ASSET_ENCOUNTEREDE – Invalid asset encountered: {0}

- Explanation** Either the specified asset in the Broker .acdl file does not belong to Broker, or the Broker .acdl file is corrupted.
- Action** Regenerate the .acdl file if it is corrupted. If the issue persists even after using the regenerated .acdl file, contact Software AG support with details of the exception stack trace.

Invalid_NameE Error: Invalid {0} name(s).

- Explanation** The names you have entered is not valid.
- Action** Enter valid names based on the detailed error message.

KEYSTORE_PROVIDED_PASSWORD_NOT_PROVIDEDE – Keystore is provided, but the password is not specified.

- Explanation** The SSL Keystore is provided, but the password is not specified.
- Action** Please provide the password.

KEYSTORE_PROVIDED_TRUSTSTORE_NOT_PROVIDEDE – Keystore is provided, but the trustore is not specified.

- Explanation** The SSL Keystore is provided but the trustore is not specified.
- Action** Please provide the location of the truststore file.

MessageId=3799_SymbolicName=AW_MINOR_BASIC_AUTH_FAILED – Basic Authentication failed for user: '{username}'.

- Explanation** Server rejected the basic authentication credentials (user name and password) supplied. Either the user does not exist in any of the aliases, or the password is wrong.
- Action** Provide a valid user name and password.

MessageId=3800_SymbolicName=AW_MINOR_BASIC_AUTH_INVALID_PASSWORDE – Basic Authentication password is not specified for user: '{username}'.

Explanation Password is null. A non-null password must be specified. Otherwise, the connection request is rejected.

Action Specify a non-null password.

MessageId=3801_SymbolicName=AW_MINOR_BASIC_AUTH_NOT_SUPPORTED – The Broker Server does not support Basic Authentication.

Explanation Client has requested authentication by providing the user name and password, but the Broker Server does not support basic authentication.

Action Ask your administrator to enable basic authentication on the Broker Server.

MessageId=3802_SymbolicName=AW_MINOR_SERVER_STOPPING – The operation failed because the Broker Server is stopping.

Explanation The operation failed because the Broker Server is stopping.

Action Wait for the Broker Server to restart, and then resubmit the request.

MessageId=_SymbolicName=BROKERCFG_ERROR_NO_LICENSEFILE – Error: No license file specified. Please specify a valid license file.

MessageId=_SymbolicName=BROKERCFG_HELP_MOVE – move : Modifies the QS configuration file and the awbroker.cfg file in the new data directory to configure the path of the storage files. move datadir [-k license-file-path] [-b basic-auth-cfg] [-qs_map_file <old-path> <new-path>]* datadir : Full path of the new data directory. -k license-file-path : Full path of the new Broker Server license file. -b basic-auth-cfg : Full path of the new basic authentication configuration file (basicauth.cfg). [-qs_map_file <old-path> <new-path>]* : Full path of the old storage file and the new storage file, if the storage is not present in the new data directory. Provide separate mapping for each storage file. Notes: Provide the license file path, basic authentication configuration file path, and storage file mapping only if these files reside outside the new data directory. By default, the storage files are picked up from the new data directory.

MessageId=_SymbolicName=BROKERCFG_HELP_UPGRADE – upgrade : upgrades the existing broker server to a newer version. <TBD>

MessageId=_SymbolicName=BROKERCFG_INFO_BROKER_FAILED – Failed

Explanation Broker restart failed.
Action Contact Software AG Global Support.

MessageId=_SymbolicName=BROKERCFG_WARNING_ADDCREATE_MISSING_LICENSEFILE – Warning: No license file specified for Broker Server. The Broker Server will not be able to start.

MessageId=_SymbolicName=BROKERCFG_WARNING_BASIC_AUTH_CFG_ALREADY_EXISTSW – Warning: Basic authentication configuration file "%1" already exists. Basic authentication configuration is not done. Manually configure basic authentication.

Explanation The basic authentication configuration file is not overwritten by the template file because a configuration file already exists.
Action Administrator should manually configure the basic authentication to enable basic authentication. Refer to the Broker administration guide for more details.

MessageId=_SymbolicName=BROKERCFG_WARNING_BASIC_AUTH_CFG_TEMPLATE_NOT_ACCESSIBLEW – Warning: Basic authentication configuration template file "%1" is not accessible (Reason: %2). Basic authentication configuration is not done. Manually configure basic authentication.

Explanation The specified source file could not be read. Either the file is not present, or the file is created by another user and is not readable. Since the file is not readable, the application did not perform the default basic authentication configuration step.
Action Administrator should manually configure the basic authentication to enable basic authentication. Refer to the Broker administration guide for more details.

MessageId=_SymbolicName=BROKERCFG_WARNING_EXTRA_LICENSEFILE – Warning: Extra license file "%1" specified but not needed.

MessageId=_SymbolicName=M_BASICAUTH_ALIAS_DISABLED – Unresponsive Alias "%1" is disabled for "%2" seconds.

MessageId=_SymbolicName=M_BASICAUTH_ALIAS_ENABLED – Alias "%1" is enabled.

MessageId=_SymbolicName=M_BASICAUTH_CANNOT_INIT_AUTHENTICATION_MODULEE – Unable to initialize basic authentication module. Verify the contents of basic authentication config file.

Explanation Initialization of the basic authentication module fails because the basic authentication configuration file contains invalid entries.
Action Verify the contents of the basic authentication configuration file. Refer to the Broker administration guide for more details.

MessageId=_SymbolicName=M_BASICAUTH_CANNOT_LOAD_AUTHENTICATION_LIBRARYE – Unable to load basic authentication library "%1".

Explanation Broker Server was unable to load the dynamic library required to enable basic authentication. Basic authentication will be disabled.

Action Check the access permission for the dynamic library.

MessageId=_SymbolicName=M_BASICAUTH_CANNOT_READ_AUTHCFG_FILEE – Unable to access or interpret the basic authentication configuration file "%1". Verify that the correct file was supplied.

Explanation Broker Server failed to read the specified basic authentication configuration file. Either the configuration file is not accessible, or the contents in the file are corrupt.

Action Make sure the basic-auth-cfg-file parameter in the awbroker.cfg file points to a valid basic authentication configuration file. Also, make sure that the basic authentication configuration file contains all the required parameters.

MessageId=_SymbolicName=M_BROKERMONITORSTOP – Broker Monitor got a request to stop itself. Process ID: %1.

MessageId=_SymbolicName=M_BROKERMONITORSTOPALLSERVER – Broker Monitor got a request to stop all the Broker Servers.

MessageId=_SymbolicName=M_BROKERMONITORSTOPSERVER – Broker Monitor got a request to stop the Broker Server running at port %1.

MessageId=_SymbolicName=M_BROKERSERVER_LOADED_POTENTIALLY_UNSAFE_WIN_LIB – Cannot load the library "%1" from default Windows system folders.

MessageId=_SymbolicName=M_BROKERSERVER_STORAGE_PLATFORM_MISMATCH – Error: Platform mismatch. The platform of the Broker Server and the platform of the Broker storage in the data directory do not match. Storage platform is %1. [EXITING]

Explanation The platform of the Broker Server and the platform of the Broker storage in the data directory do not match. If the OS, processor, or the byte order does not match, Broker will not be available.

Action Make sure the platform of the Broker Server and the Broker storage is same.

MessageId=_SymbolicName=M_BROKER_DIR_PATH_EXCEEDS_MAXPATHLEN_LIMIT – Warning:
The length of the Broker data directory path [%1] exceeds the limit of [%2] characters.

MessageId=_SymbolicName=M_BROKER_RBROKER_NOT_ENOUGH_STORAGE – Broker %1 could not forward documents from %2 due to insufficient memory or storage. The forwarding between these 2 Brokers will not continue until this is corrected. Please make sure that there is sufficient memory or storage (both log and/or storage files) to accommodate %3 bytes of data.

MessageId=_SymbolicName=M_BROKER_RBROKER_UNKNOWN_ERROR – Broker %1 could not forward documents from %2 due to an unknown error (%d). Please check if the documents are still being forwarded between these two Brokers.

MessageId=_SymbolicName=M_CANNOTSTOPBROKERSERVERSERVICE – Failed to stop Broker Server on "%1". Server is unresponsive. Stopping the service %2.

MessageId=_SymbolicName=M_CYCLIC_GATEWAY_ENABLED – Cyclic Gateway feature is enabled, be careful while defining can-forward/can-receive permissions across gateways.

MessageId=_SymbolicName=M_LICENSEEXPIRINGSOONW – The license will be expiring in %1 days for webMethods Broker. The Broker will not accept any documents after the license expires.

Explanation webMethods Broker license will be expiring soon.

Action Use the new webMethods Broker license.

MessageId=_SymbolicName=M_RBROKER_PARALLELCHANNEL_DISABLED – Remote Broker Parallel channel disabled.

MessageId=_SymbolicName=M_RBROKER_PARALLELCHANNEL_ENABLED – Remote Broker Parallel channel enabled.

MessageId=_SymbolicName=M_SSL_ENABLED – SSL enabled with version ("%1").

MessageId=_SymbolicName=M_STREAMING_DISABLED – Streaming is disabled.

MessageId=_SymbolicName=M_STREAMING_ENABLED – Streaming is enabled.

PARTIAL_EXPORT_INVALID_MULTIPLE_JNDI_CONTEXTSE – Cannot export JMS destinations into multiple JNDI contexts. Export JMS destinations into one JNDI context at a time for partial export

Explanation Partial deployment of JMS destinations into multiple JNDI contexts is not supported.

Action Select only one JNDI destination while partially exporting the JNDI assets.

PIFSPME0001E Unexpected exception encountered: {0}

Explanation An unexpected exception occurred.

Action Check the detailed error message and take appropriate action. Contact Software AG Global Support for further assistance.

PIFSPME0002E Broker installation folder '{0}' is missing.

Explanation Broker installation is incorrect.

Action Contact your webMethods product administrator and re-install webMethods Broker.

PIFSPME0003E The passed runtime component instance is not a Broker Server process. Object passed is an instance of {0}.

Explanation The passed runtime component ID is wrong.

Action Pass the correct runtime component ID.

PIFSPME0005E Invalid configuration object. {0} expected.

Explanation Format of the port configuration is wrong.

Action Contact your webMethods product administrator and re-configure the port settings.

PIFSPME0006E Invalid configuration instance. {0} entered.

Explanation Format of port configuration is wrong.

Action Contact your webMethods product administrator and re-configure the port settings.

PIFSPME0007E Broker Server is not running.

Explanation Broker Server is not running.

Action Start the Broker Server.

PIFSPME0009E **Broker Server port cannot be non-primary.**
Explanation The primary parameter is set to false in the port configuration.
Action Set the primary parameter to true in the port configuration.

PIFSPME0010E **Broker Server port cannot be disabled.**
Explanation The Enabled parameter is set to false in the port configuration.
Action Set the Enabled parameter to true in the port configuration.

PIFSPME0011E **Broker Server port type must be Custom.**
Explanation Broker Server port type is not CUSTOM.
Action Set the Broker Server port type as CUSTOM.

PIFSPME0012E **The custom type of Broker Server port must be MIXED.**
Explanation The custom type of Broker Server port is not MIXED.
Action Set the custom type of Broker Server port to MIXED.

PIFSPME0013E **At least one port must be specified.**
Explanation Port configuration is not specified in the PortSettings input.
Action Add the port configuration to the PortSettings input.

PIFSPME0014E **Broker Server protocol must be TCP.**
Explanation Broker Server protocol is not set to TCP.
Action Set TCP as the Broker Server protocol.

PIFSPME0015E **Error occurred while saving the SSL settings.**
Explanation Unable to save the SSL settings.
Action Verify the SSL settings and retry.

PIFSPME0016 **Only one set of port settings is allowed.**
Explanation More than one set of port settings are passed in the input.
Action Configure only one port setting per Broker Server.

PIFSPME0017	Broker Server port number must not be changed.
Explanation	Attempted to change the Broker Server port number.
Action	Do not modify the Broker Server port number.
PIFSPME0018	Do not set the BindAddress.
Explanation	Attempted to set the BindAddress.
Action	Do not set the BindAddress in the input.
PIFSPME0019	Broker Server does not support deletion of Bind address.
Explanation	Attempted to modify the Bind address.
Action	Do not modify or delete the Bind address.
PIFSPME0020	Broker Server does not support backlog configuration.
Explanation	Attempted to set the backlog.
Action	Do not set the backlog in the input.
PIFSPME0021	Error occurred while saving the port configurations.
Explanation	Unable to save the port configurations.
Action	See the detailed error message and verify the cause of failure.
PIFSPME0022	ClientAuth must be NONE.
Explanation	ClientAuth in the port configuration input is not set as NONE.
Action	Set the ClientAuth as NONE.
PIFSPME0023	Keystore definition must not be null.
Explanation	Keystore definition for SSL in the port configuration input is set to Null.
Action	Set a valid value for the keystore definition.
PIFSPME0024	Truststore definition must not be null.
Explanation	Truststore definition for SSL in the port configuration input is set to Null.
Action	Set a valid value for the truststore definition.

PIFSPME0025	Broker Server allows only default alias for keystore, truststore, and key.
Explanation	Keystore definition alias, truststore definition alias, and key alias are not set to default.
Action	Set the keystore definition alias, truststore definition alias, and key alias to default.
PIFSPME0026	ExtendedProperties is not supported by Broker Server.
Explanation	ExtendedProperties is set.
Action	Do not set the ExtendedProperties.
PIFSPME0027	IPAccess is not supported by Broker Server.
Explanation	IPAccess is set.
Action	Do not set the IPAccess.
PIFSPME0028	KeepAliveTimeout is not supported by Broker Server.
Explanation	KeepAliveTimeout is set.
Action	Do not set the KeepAliveTimeout.
PIFSPME0029	ThreadPool is not supported by Broker Server.
Explanation	ThreadPool is set.
Action	Do not set the ThreadPool.
PIFSPME0030	URLAccess is not supported by Broker Server.
Explanation	URLAccess is set.
Action	Do not set the URLAccess.
PIFSPME0036	Configuration value for BROKER-MWSADMIN can only be a String.
Explanation	The value provided for the BROKER-MWSADMIN parameter is not of type String.
Action	Provide a value of type String.
PIFSPME0039	Keystore cannot be null if trustore is present.
Explanation	If you enter the trustore value, the keystore value is also required.
Action	Specify the keystore location.

PIFSPME0040	Operation not supported for current Broker security configuration.
Explanation	Command Central does not currently support management of a Broker Server, which is protected with SSL or basic authentication.
Action	Disable SSL and basic authentication to make this Broker Server manageable from Command Central.
PIFSPMI0037	Unable to create the BrokerMWSNodes properties file.
Explanation	An error occurred while creating the BrokerMWSNodes properties file.
Action	Please contact the administrator.
PIFSPMI0038	BROKER_MWSADMIN is supported only for Broker Server instances.
Explanation	BROKER_MWSADMIN specifies the link to the Messaging user interface in My webMethods. This is a Broker Server specific configuration parameter.
Action	Configure parameters specific to the product. For information about configuration parameters, see Command Central Help.
POP.012.0037E	Error: Failed to submit the client changes.
Explanation	Unable to add/remove clients from the Export/Import summary.
Action	Check the detailed error message and take appropriate action.
POP.012.0038E	Error: Failed to submit the client group changes.
Explanation	Unable to add/remove client groups from the Export/Import summary .
Action	Check the detailed error message and take appropriate action.
POP.012.0039E	Error: Failed to submit the document type changes.
Explanation	Unable to add/remove document types from the Export/Import summary.
Action	Check the detailed error message and take appropriate action.
POP.012.0040E	Error: Failed to initialize the export descriptor.
Explanation	Unable to initialize the export descriptor.
Action	Check the detailed error message and take appropriate action.

POP.012.0041E	Error: Failed to get the assets from Broker.
Explanation	Unable to connect to Broker to fetch the assets.
Action	Check if Broker is running.
POP.012.0042E	Error: File does not exist or it is empty.
Explanation	ADL file upload operation failed.
Action	Check if the file exists and it is not empty.
POP.012.0043E	Error: Import ADL caused the following exception: {0}
Explanation	ADL file upload operation failed.
Action	Check the detailed error message and take appropriate action.
POP.012.0044E	Error: Import ADL caused the following IO-exception: {0}
Explanation	ADL file upload operation failed.
Action	Check the detailed error message and take appropriate action.
POP.012.0045E	Error: Import ADL caused the following parse-exception: {0}
Explanation	ADL file upload operation failed.
Action	Check the detailed error message and take appropriate action.

TX_HEURISTIC_ROLLBACK_TIMEOUT – Transaction timed out and has been heuristically rolled-back.

4 Business Rules Messages

0005.0500	Unable to find the setter method: "{0}" for the class: "{1}"
Explanation	An error occurred while trying to set a value in a data model.
Action	Please contact your administrator and provide the log file.
0005.0920	An exception was thrown when creating the JAXB context for contextPath: "{0}"
Explanation	An error occurred while reading/writing a data model XML file.
Action	Please contact your administrator and provide the log file.
0005.0925	An error occurred while trying to generate the Java sources for DataModel "{1}" in project: "{0}"
Explanation	An error occurred while creating the Java source/class file for the data model.
Action	Please contact your administrator and provide the log file and the data model file.
0005.0930	An error occurred while reading the content of a rule project file: {0}
Explanation	An error occurred while reading the content of the rule project file.
Action	Please contact your administrator and provide the log file and the rule project.
0005.0934	An error occurred while retrieving all decision tables: {0}.
Explanation	An error occurred while retrieving the decision tables from a rule project.
Action	Please contact your administrator and provide the log file and the rule project.

0005.0935	An error occurred while retrieving all event rules: {0}.
Explanation	An error occurred while retrieving the event rules from a rule project.
Action	Please contact your administrator and provide the log file and the rule project.
0005.0936	An error occurred while retrieving all external event rules: {0}.
Explanation	An error occurred while retrieving the external event rules from a rule project.
Action	Please contact your administrator and provide the log file and the rule project.
0005.0937	An error occurred while retrieving a rule set source: {0}.
Explanation	An error occurred while retrieving the rule sets from a rule project.
Action	Please contact your administrator and provide the log file and the rule project.
0005.0950	An error occurred while transforming the rule project "{0}" to version {1}.
Explanation	An error occurred while transforming/migrating the rule project to the given version.
Action	Please contact your administrator and provide the log file and the rule project.
0005.0951	An error occurred while transforming the rule project "{0}" to version {1}: transforming asset "{2}" failed.
Explanation	An error occurred while transforming/migrating a specific asset of the rule project to the given version.
Action	Please contact your administrator and provide the log file and the rule project.
0005.0952	An error occurred while transforming the rule project "{0}" to version {1}: adding new file "{2}" failed.
Explanation	An error occurred while transforming/migrating the rule project to the given version: adding a new file failed.
Action	Please contact your administrator and provide the log file and the rule project.
0005.0953	An error occurred while transforming the rule project "{0}" to version {1}: adding new directory "{2}" failed.
Explanation	An error occurred while transforming/migrating the rule project to the given version: adding a new directory failed.
Action	Please contact your administrator and provide the log file and the rule project.

0005.0954	An error occurred while transforming the rule project "{0}" to version {1}: deleting directory "{2}" failed.
Explanation	An error occurred while transforming/migrating the rule project to the given version: deleting a directory failed.
Action	Please contact your administrator and provide the log file and the rule project.
0005.0955	An error occurred while flushing the changes of the transformations in the rule project "{0}" to version {1}.
Explanation	An error occurred while persisting the changes of the transformation/migration of the rule project to the given version.
Action	Please contact your administrator and provide the log file and the rule project.
0005.0956	An error occurred while executing the transformation processor [{3}] in the rule project "{0}" to version {1}.
Explanation	An error occurred in the specific transformation processor while transforming/migrating the rule project to the given version.
Action	Please contact your administrator and provide the log file and the rule project.
0005.0959	The transformation XML file is corrupt.
Explanation	The standard transformation XML file is not valid.
Action	Please contact your administrator and provide the log file. Probably you need to reinstall the Rules feature.
0005.0960	Some rule project content can not be retrieved.
Explanation	An error occurred while trying to read the rule project.
Action	Please contact your administrator and provide the log file and the rule project.
0005.0961	An error occurred while trying to retrieve the project version file.
Explanation	An error occurred while trying to read the project version file from the rule project.
Action	Please contact your administrator and provide the log file and the rule project.
0005.0962	No migration information found: startVersion {4}, targetVersion {1}.
Explanation	No transformation/migration information was found to transform the rule project from the start version to the target version.
Action	Please contact your administrator and provide the log file and the rule project.

0005.0970	An error occurred while trying to build the rule project assets for project: "{0}".
Explanation	An error occurred while trying to build the rule project assets for project: "{0}".
Action	Please contact your administrator and provide the log file and the rule project.
0005.0971	An error occurred while trying to compile the Java classes project: "{0}"; compiler errors: [{1}]
Explanation	Compiling of project sources was not successful.
Action	Please see the provided error information and/or look for additional error message in the log.
0005.1002	An error occurred while moving rule set entries: {0}.
Explanation	While attempting to move one or more entries within the rule set, a problem occurred.
Action	Try again. If the problem persists, please contact your administrator and provide the log file and the rule project.
0005.1004	An error occurred while loading the rule set: {0}.
Explanation	A problem was encountered while attempting to load the rule set file.
Action	Try again. If the problem persists, please contact your administrator and provide the log file and the rule project.
0005.1006	An error occurred while persisting the rule set: {0}.
Explanation	A problem was encountered while attempting to save the rule set file.
Action	Try again. If the problem persists, please contact your administrator and provide the log file and the rule project.
0010.0100	RESFacade initialized with basePath: [{0}] and logger: [{1}]
Explanation	The RuleEngineServer (RES) was successfully initialized.
Action	n/a
0010.0202	[[SessionId: {0}]] An unexpected exception was thrown in the shutdown process that should not have happened: [{1}]
Explanation	An unexpected exception was thrown in the shutdown process of the WmBusinessRules package. Probably an error occurred in the startup process of the package.
Action	Check the IS server log when the WmBusinessRules package is started. Probably, a license problem is reported.

0010.0203	[[SessionId: {0}]] An unexpected exception was thrown in the shutdown process
Explanation	An error occurred while collecting the deployed rule projects. Due to this, the shutdown process may not have been completed successfully.
Action	Please contact your software support center and provide the IS server log file.
0010.0300	License is expired. Locking RESFacade...
Explanation	The license for the WmBusinessRules package has expired. As a result no functionality from this package is available.
Action	Please contact your software support center and install a new valid Business Rules license.
0010.0502	[[SessionId: {0}]] Unexpected end to get data model class with name [{1}] from rule project [{2}].
Explanation	An unexpected execution path was found. This might cause subsequent problems.
Action	Please contact your software support center and provide the IS server log file.
0010.0605	[[SessionId: {0}]] Unexpected end of rule invocation => returning NULL. projectKey [{1}], ruleSetName [{2}].
Explanation	An unexpected execution path was found. This might cause subsequent problems.
Action	Please contact your software support center and provide the IS server log file.
0010.0723	[[SessionId: {0}]] Set pool minEvictableIdleTimeMillis to [{1}].
0010.0724	[[SessionId: {0}]] Set pool timeBetweenEvictionRunsMillis to [{1}].
0010.0902	[[SessionId: {0}]] Unexpected end of monitorPool for rule project [{1}].
Explanation	An unexpected execution path was found. This might cause subsequent problems.
Action	Please contact your software support center and provide the IS server log file.
0010.0925	[[SessionId: {0}]] Pool minEvictableIdleTimeMillis = [{1}].

0010.0926	[[SessionId: {0}]] Pool timeBetweenEvictionRunsMillis = [{1}].
0010.1105	[[SessionId: {0}]] Starting version validation for archive of rule project [{1}].
Explanation	Starting to determine the version of the rule project.
Action	n/a
0010.1106	[[SessionId: {0}]] Archive is older than current version: [{1}].
Explanation	The given rule project archive is outdated and needs to be upgraded.
Action	n/a
0010.1107	[[SessionId: {0}]] Starting migration of archive of rule project [{1}].
Explanation	Starting the upgrade of the given rule project archive.
Action	n/a
0010.1108	[[SessionId: {0}]] Start to create new rule archive of migrated rule project [{1}].
Explanation	The given rule archive is outdated and needs to be upgraded.
Action	n/a
0010.1305	[[SessionId: {0}]] ADCL file could not be deleted for project [{1}].
Explanation	The ACDL file for the given project could not be removed. Due to this, the rule project may not have been completely unstored.
Action	Please contact your software support center and provide the IS server log file.
0010.1402	[[SessionId: {0}]] Unexpected end of getDeployedProjects.
Explanation	An unexpected execution path was found. This might cause subsequent problems.
Action	Please contact your software support center and provide the IS server log file.
0010.1502...0	[[SessionId: {0}]] Unexpected end of getStoredProjects.
Explanation	An unexpected execution path was found. This might cause subsequent problems.
Action	Please contact your software support center and provide the IS server log file.

0010.1505	[[SessionId: {0}]] The following projects are stored: [{1}].
Explanation	The given list of rule projects are stored in the WmBusinessRules project.
Action	n/a
0010.2510	[[SessionId: {0}]] Start to store project [{1}] with unique jar name [{2}].
Explanation	The project with the given name and jar file will be stored.
Action	n/a
0010.2511	[[SessionId: {0}]] Calling RuleProjectArchiveFacade.storeAcdlFile: project [{1}], unique jar name [{2}].
Explanation	The internal component to store the ACDL file is called.
Action	n/a
0010.2512	[[SessionId: {0}]] ACDL file stored.
Explanation	The ACDL file is successfully stored, i.e. saved on the local disc.
Action	n/a
0010.2800	[[SessionId: {0}]] Calling EDAEventReceiver.notifyObservers(): validate=[{1}]
Explanation	The rules component received an event that is now forwarded to all registered listeners.
Action	n/a
0010.2801	[[SessionId: {0}]] Trying to validate the incoming XML Document based on the available schema located at [{1}]
Explanation	The incoming event XML is validated against its schema. Error messages are logged.
Action	n/a
0010.2802	[[SessionId: {0}]] Found the BODY element!
Explanation	The body element of the payload was found in the XML of the incoming event.
Action	n/a
0010.2803	[[SessionId: {0}]] No BODY element found!
Explanation	The body element of the payload was NOT found in the XML of the incoming event. Therefore the event can not be forwarded to any listener.
Action	You need to contact the "owner" of the event to make sure the event XML contains a valid body according to the schema (envelope.xsd).

0010.2804	[[SessionId: {0}]] Starting to notify registered list of listeners for eventTypeName {{1}}
Explanation	The eventTypeName (i.e. Topic) of the incoming event was found and the event is now forwarded to the registered listeners.
Action	n/a
0010.2805	[[SessionId: {0}]] Notifying one registered listener for eventTypeName {{1}}
Explanation	The rules compent forwards this event to one specific listener.
Action	n/a
0010.2820	[[SessionId: {0}]] Adding listener for eventTypeName {{1}}
Explanation	One listener to the given topic is added.
Action	n/a
0010.2821	[[SessionId: {0}]] Removing listener for eventTypeName {{1}}
Explanation	One listener to the given topic is removed.
Action	n/a
0010.2897	[[SessionId: {1}]] Error while notifying the listener: {{0}}
Explanation	An unexpected error happened while notifying the listeners.
Action	See the error log (on IS) for more details and contact your system administrator.
0010.2898	[[SessionId: {1}]] Error while reading the payload XML: {{0}}
Explanation	An unexpected error happened while reading the payload XML to get the body.
Action	See the error log (on IS) for more details and contact your system administrator.
0010.2899	[[SessionId: {1}]] Validation error: {{0}}
Explanation	An error was found while validating the XML with the given xsd schema.
Action	See the error log (on IS) for more details and contact the "owner" of the incoming event to make sure the event is valid.

0010.2900	[[SessionId: {0}]] Calling RuleProjectManager.unregisterEDAEventListener()
Explanation	One listener for a given topic is removed.
Action	n/a
0010.2901	[[SessionId: {0}]] EDAEventHandler unregistered for event type [{1}].
Explanation	One listener for a given topic is removed.
Action	n/a
0010.3000	[[SessionId: {0}]] Calling RuleProjectManager.registerEDAEventListener()
Explanation	One listener for a given topic is added.
Action	n/a
0010.3001	[[SessionId: {0}]] EDAEventHandler created.
Explanation	An event handler is created to handle the future events for this topic.
Action	n/a
0010.3002	[[SessionId: {0}]] EDAEventHandler registered for event type [{1}].
Explanation	One listener for a given topic is added.
Action	n/a
0010.3102	[[SessionId: {0}]] No className found for parameterName [{1}] for rule set [{2}] from rule project [{3}].
Explanation	No classname was found for the given parameter. This might cause problems in the rule project archive. The given parameter may not be defined in the rule project.
Action	Please check, if the parameter exists in the rule set. If so, please contact your software support center and provide the IS server log file and the rule project archive.
0010.3103	[[SessionId: {0}]] Unexpected end of getDataModelClassName for parameterName [{1}] for rule set [{2}] from rule project [{3}].
Explanation	An unexpected execution path was found. This might cause subsequent problems.
Action	Please contact your software support center and provide the IS server log file.

0010.3103...0	[[SessionId: {0}]] Unexpected end of getDataModelClassName for parameterName {{1}} for rule set {{2}} from rule project {{3}}.
Explanation	An unexpected execution path was found. This might cause subsequent problems.
Action	Please contact your software support center and provide the IS server log file.
0010.3203	[[SessionId: {0}]] Unexpected end of getParameterNames for rule set {{1}} from rule project {{2}}.
Explanation	An unexpected execution path was found. This might cause subsequent problems.
Action	Please contact your software support center and provide the Integration Server log file.
0010.4000	Constructing an EventPublisher ...
0010.4001	Message creator OSGi service is retrieved
0010.4002	EventPublisher is constructed.
0010.4003	-> emit
0010.4004	-- emit event {0}
0010.4005	<- emit
0010.4006	Event: {0}
0010.4900	-- emit of {0} failed: {1}
0010.4901	Cannot marshal an event: {0}
0010.4902	Could not construct or emit the message {0}

0010.4903	Could not get Event Emitter object or Message Creator object from NERV: {0}
0010.4904	Event headers cannot be created: {0}
0010.9900	[[SessionId: {0}]] An exception had been thrown in Runtime Core: [{1}]
Explanation	An unexpected error occurred.
Action	Please contact your software support center and provide the IS server log file.
0010.9901	[[SessionId: {0}]] Error while deploying project project [{1}] on startup: [{2}]
Explanation	An error occurred during startup while deploying an existing project.
Action	Please contact your software support center and provide the IS server log file.
0010.9902	[[SessionId: {0}]] Cannot read archive while startup initialization of stored projects: [{1}]
Explanation	An error occurred during startup while reading the stored projects.
Action	Please contact your software support center and provide the IS server log file.
0010.9903	[[SessionId: {0}]] Error while initial setup of stored projects. storedProject: [{1}]
Explanation	An error occurred during startup while reading the stored projects.
Action	Please contact your software support center and provide the IS server log file.
0010.9904	[[SessionId: {0}]] Error while closing rule project archive classLoader in deployment exception case.
Explanation	An error occurred during the deployment of an archive.
Action	Please contact your software support center and provide the IS server log file.
0010.9905	[[SessionId: {0}]] Error while closing archive/acdlFile FileOutputStream. fileNameAndPath: [{1}]
Explanation	A file system error occurred while writing the content of the archive file or ACDL file to the disk.
Action	Please contact your software support center and provide the IS server log file.

0010.9906	[[SessionId: {0}]] Error while trying to internally deploy project [{1}] on startup: [{2}]
Explanation	An error occurred during startup while deploying an existing project.
Action	Please contact your software support center and provide the IS server log file.
0010.9907	[[SessionId: {0}]] Unknown error while trying to internally deploy project [{1}] on startup: [{2}]
Explanation	An error occurred during startup while deploying an existing project.
Action	Please contact your software support center and provide the IS server log file.
0010.9908	[[SessionId: {0}]] Unknown error: cannot read archive while startup initialization of stored projects: [{1}]
Explanation	An error occurred during startup while reading the stored projects.
Action	Please contact your software support center and provide the IS server log file.
0010.9910	[[SessionId: {0}]] Error while creating missing parameter instance: parameterName[{1}], className[{2}].
Explanation	An error occurred during execution of the rules archive.
Action	Please contact your software support center and provide the IS server log file.
0010.9911	[[SessionId: {0}]] No valid license exists for the RES: {1}
Explanation	No valid license was found for the WmBusinessRules package.
Action	Please contact your software support center and provide the IS server log file.
0010.9912	[[SessionId: {0}]] Can't generate current time in event.
0010.9913	[[SessionId: {0}]] Can't resolve current host name.
0010.9914	[[SessionId: {0}]] Can't set project creator application.
0010.9990	Error while launching.
Explanation	A license error occurred during startup of the WmBusinessRules package.
Action	Please check, if you supplied a valid license for the WmBusinessRules package. See the IS server log file for more details about the license checking.

0010.9991	Error occurred while trying to handle ProjectDeployed event: projectName: {0}, projectVersion: {1}, dateTimeOfActivity: {2}, hostAndPort: {3}, userId: {4}, correlationId: {5}, prjectCreatorApp: {6}, deployedWith: {7}, invocationSessionId: {8}, displayName: {9}, attributes: {10}
0030.0100	initializing the RESFacade via class [{0}]
Explanation	The RuleEngineServer (RES) is being initialized.
Action	n/a
0030.0101	initializing the RESFacade: basePath: "{0}", wrapperLoggerClassName: "{1}", commonLoggerClassName: "{2}"
Explanation	The RESFacade is being initialized using the configured basePath and logger.
Action	n/a
0030.0102	successfully initialized the RESFacade.
Explanation	The RESFacade was successfully initialized and is now ready for use.
Action	n/a
0030.0103	querying for initialization status. RESFacade is initialized: {0}
Explanation	A client queries the initialization status that is displayed.
Action	n/a
0030.0600	[[SessionId: {0}]] Calling invoke with Integration Server sessionId [{1}].
Explanation	The method "invoke" was called.
Action	n/a
0030.0601	[[SessionId: {0}]] starting getResultFilterParameterNames
Explanation	Starting to get the parameter names for the result filter.
Action	n/a
0030.0602	[[SessionId: {0}]] ResultFilterParameterNames: [{1}]
Explanation	Got the parameter names for the result filter.
Action	n/a

0030.0603	[[SessionId: {0}]] starting getResultFilterClassNames
Explanation	Starting to get the class names for the result filter.
Action	n/a
0030.0604	[[SessionId: {0}]] ResultFilterClassNames: [{1}]
Explanation	Got class names for the result filter.
Action	n/a
0030.0605	[[SessionId: {0}]] starting mapEngineResultsToIData
Explanation	Starting to map the results of the core rules engine to the result IData.
Action	n/a
0030.0606	[[SessionId: {0}]] mapEngineResultsToIData: [{1}]
Explanation	Mapped the results of the core rule engine to the result IData.
Action	n/a
0030.0607	[[SessionId: {0}]] starting invokeEngine: resultFilterParameterNames [{1}], resultFilterClassNames: [{2}]
Explanation	Starting to invoke the core rules engine.
Action	n/a
0030.0608	[[SessionId: {0}]] returning results after invocation: projectInformation [{1}], ruleSetName [{2}], facts [{3}], result [{4}]
Explanation	Got results from the core rule engine.
Action	n/a
0030.0609	[[SessionId: {0}]] starting getFacts ({2}) for project [{1}]
Explanation	Starting to extract input facts from the incoming IData pipeline.
Action	n/a
0030.0610	[[SessionId: {0}]] facts for project [{1}]: [{2}]
Explanation	Extracted all input facts from the incoming IData pipeline.
Action	n/a

0030.0680	The feature [{0}] is not licensed and therefore all requests are answered with an exception.
Explanation	The requested feature is not part of the used Rules license. Therefore all requests to this feature are denied.
Action	If you want to use this feature, you need to buy and install the appropriate Rules license.
0030.0700	calling configPool
Explanation	The method "configPool" was called.
Action	n/a
0030.0900	calling monitorPool
Explanation	The method "monitorPool" was called.
Action	n/a
0030.1000	calling storeArchive
Explanation	The method "storeArchive" was called.
Action	n/a
0030.1200	calling undeployArchive
Explanation	The method "undeployArchive" was called.
Action	n/a
0030.1300	calling unstoreArchive
Explanation	The method "unstoreArchive" was called.
Action	n/a
0030.1400	calling getDeployedProjects
Explanation	The method "getDeployedProject" was called.
Action	n/a

0030.1500	calling getStoredProjects
Explanation	The method "getStoredProject" was called.
Action	n/a
0030.2000	Calling getAllActiveInvokeSession
Explanation	The method "getAllActiveInvokeSessions" was called.
Action	n/a
0030.2100	Calling haltEngine
Explanation	The method "haltEngine" was called.
Action	n/a
0030.2200	calling deployWithACDL
Explanation	The "deployObjectWithACDL" method was called.
Action	n/a
0030.2201	simulation not yet supported
Explanation	The Business Rules component does not (yet) support the simulate feature.
Action	n/a
0030.2202	deployment successful
Explanation	The deployment of the Rules artifact was successful.
Action	n/a
0030.2203	deployment failed: {0}
Explanation	The deployment failed for some reason.
Action	See the error log (in IS) for details.
0030.2204	deployWithACDL was called with simulate=[true], nothing will be done in the RES; an appropriate message will be send to the caller
Explanation	A simulation of "deployObjectWithACDL" was requested, but this is not (yet) supported by the Rules component.
Action	n/a

0030.2400	[[SessionId: {0}]] Calling convertEventSourceToShadowFact: parameterName: "{1}", className: "{2}"
Explanation	Trying to convert the event source to a shadow fact to be used by the rules engine.
Action	n/a
0030.2401	[[SessionId: {0}]] Conversion service inputs created.
Explanation	The input values for the conversion of the event source to the shadow fact are being created.
Action	n/a
0030.2402	[[SessionId: {0}]] Conversion service has returned results.
Explanation	The conversion service has returned the result, i.e. a shadow fact to be used by the rules engine
Action	n/a
0030.2403	[[SessionId: {0}]] Event IData extracted: [{1}]
Explanation	The IData representation of the event is being extracted.
Action	n/a
0030.2404	[[SessionId: {0}]] Ready to return result: [{1}]
Explanation	The converter is now ready to return the result, i.e. the shadow fact.
Action	n/a
0030.2500	receiving event
Explanation	The Rules component received an event.
Action	n/a
0030.2501	receiving event, jmsMessage: "{0}"
Explanation	The Rules component received an event. The jmsMessage representing this event is displayed.
Action	n/a

0030.2502	receiving event, body: "{0}"
Explanation	The Rules component received an event. The body of the jmsMessage representing this event is displayed.
Action	n/a
0030.2503	receiving event, it is sent via NERV, so we need to add the body tags
Explanation	The Rules component received an event. The payload of jmsMessage (i.e. the event XML) representing this event is displayed.
Action	n/a
0030.9900	An exception has been thrown in the Runtime Wrapper: {0}
Explanation	An unexpected error occurred in the IS Wrapper of the RuleEngineServer.
Action	See the error log (on IS) for more details and contact your system administrator.
0030.9901	An internal exception occurred. {0}
Explanation	An unexpected internal exception occurred.
Action	See the error log (on IS) for more details and contact your system administrator.
0030.9902	A business rules exception occurred. {0}
Explanation	An unexpected business exception occurred in the Rules component.
Action	See the error log (on IS) for more details and contact your system administrator.
0030.9903	An unexpected exception occurred. {0}
Explanation	An unexpected exception occurred in the Rules component.
Action	See the error log (on IS) for more details and contact your system administrator.
0030.9904	No valid license exists for the RES. {0}
Explanation	During initialization the license for the Business Rules component is checked and there is no valid license found.
Action	This might have several reasons: no license file found, license expired, the license is not valid for the Rules component. See the error log (on IS) for details. Ask your system administrator to install a valid license.

0050.0250	The license file does not exist in the specified location: {0}
Explanation	The mandatory license file for the rules engine does not exist.
Action	Please consult your local system administrator and install a new license file for the rules engine.
0050.0251	Error while reading the content of the license file: {0}
Explanation	A general/undefined error occurred while reading the license file for the rules runtime.
Action	Please see the log file for more details and consult your local system administrator.
0050.0252	The license file did not pass the signature check: {0}
Explanation	The license file for the rules runtime is not valid as the signature/checksum is invalid.
Action	Please consult your local system administrator and install a valid license.
0050.0253	Error while checking if the expiration date is unlimited: {0}
Explanation	An internal error occurred while checking the unlimited expiration date in the license file for the rules runtime.
Action	Please see the logs for more details. Consult your local system administrator and install a new license file.
0050.0254	The license grace period [{0} days] is expired, engine is shutting down...
Explanation	The license for the rules runtime is expired.
Action	Please consult your local system administrator and install a new license.
0050.0255	The license [{2}, {3}] is not valid for the product code(s) {0} and/or version [{1}]
Explanation	The license is invalid for the rules runtime.
Action	Consult your local system administrator and install a valid license file for the rules runtime.
0050.0258	Error while reading the parameters: {0}
Explanation	An internal error occurred while reading the parameters for product code and version.
Action	Please see the error log for more details.

- 0050.0259** **License expired [{0}] days ago! You need to update the license file to use Business Rules.**
- Explanation** The expiration date of the license was reached and therefore the Rules Engine will not start.
- Action** Consult your local system administrator and install a valid license file for the rules runtime.
-
- 0050.0260** **An unexpected exception occurred during check of the license file: {0}**
- Explanation** An unexpected error occurred while the license file was checked.
- Action** Please see the log for more details.
-
- 0050.0261** **An unexpected exception occurred during daily check of the license file: {0}**
- Explanation** An unexpected error occurred while the daily license check was executed.
- Action** Please see the log for more details.
-
- 0050.0307** **can not register server with id: {0}**
- Explanation** Due to a database problem, the server can not be registered in the BusinessRulesDatabase.
- Action** Please check the configuration of the JDBC Pool for the "ProcessAudit" function. Please verify that the tables for the BusinessRulesDatabase are properly created using the database component configurator. If everything is set up properly and the error still occurs, please contact your software support center and provide the IS server log file.
-
- 0050.0308** **can not unregister server with id: {0}**
- Explanation** Due to a database problem, the server cannot be unregistered in the BusinessRulesDatabase.
- Action** Please check the configuration of the JDBC Pool for the "ProcessAudit" function. Please verify that the tables for the BusinessRulesDatabase are properly created using the database component configurator. If everything is set up properly and the error still occurs, please contact your software support center and provide the IS server log file.
-
- 0050.0309** **error while deleting current RES instance: serverId: {0}**
- Explanation** Due to a database problem, the server cannot be removed from the BusinessRulesDatabase.
- Action** Please check the configuration of the JDBC Pool for the "ProcessAudit" function. Please verify that the tables for the BusinessRulesDatabase are properly created using the database component configurator. If everything is set up properly and the error still

occures, please contact your software support center and provide the IS server log file.

0050.0310	could not set the online status for current server: {0}; online: {1}
Explanation	Due to a database problem, the online status of the server cannot be set in the BusinessRulesDatabase.
Action	Please check the configuration of the JDBC Pool for the "ProcessAudit" function. Please verify that the tables for the BusinessRulesDatabase are properly created using the database component configurator. If everything is set up properly and the error still occurs, please contact your software support center and provide the IS server log file.
0050.0311	could not set the blacklisted status for current server: {0}; blacklisted: {1}
Explanation	Due to a database problem, the blacklisted status of the server cannot be set in the BusinessRulesDatabase.
Action	Please check the configuration of the JDBC Pool for the "ProcessAudit" function. Please verify that the tables for the BusinessRulesDatabase are properly created using the database component configurator. If everything is set up properly and the error still occurs, please contact your software support center and provide the IS server log file.
0050.0353	could not save log for deployment on server: serverId: {0}; project name: {1}; project version: {2}; user name: {3}; timestamp: {4}
Explanation	Due to a database problem, the deployment log cannot be written to the BusinessRulesDatabase.
Action	Please check the configuration of the JDBC Pool for the "ProcessAudit" function. Please verify that the tables for the BusinessRulesDatabase are properly created using the database component configurator. If everything is set up properly and the error still occurs, please contact your software support center and provide the IS server log file.
0050.0354	could not save log for undeployment on server: serverId: {0}; project name: {1}; project version: {2}; user name: {3}; timestamp: {4}
Explanation	Due to a database problem, the undeployment log cannot be written to the BusinessRulesDatabase.
Action	Please check the configuration of the JDBC Pool for the "ProcessAudit" function. Please verify that the tables for the BusinessRulesDatabase are properly created using the database component configurator. If everything is set up properly and the error still occurs, please contact your software support center and provide the IS server log file.

0050.0423 **trying to store rule project deployed event: projectName: {0}, projectVersion: {1}, dateTimeOfActivity: {2}, hostAndPort: {3}, userId: {4}, correlationId: {5}, projectCreatorApp: {6}, deployedWith: {7}, invocationSessionId: {8}, displayName: {9}, attributes: {10}**

0050.0424 **tried to store rule project deployed event: projectName: {0}, projectVersion: {1}, dateTimeOfActivity: {2}, hostAndPort: {3}, userId: {4}, correlationId: {5}, projectCreatorApp: {6}, deployedWith: {7}, invocationSessionId: {8}, displayName: {9}, attributes: {10}; success: {11}**

0050.0425 **project deployed event have been stored successfully: projectName: {0}, projectVersion: {1}, dateTimeOfActivity: {2}, hostAndPort: {3}, userId: {4}, correlationId: {5}, projectCreatorApp: {6}, deployedWith: {7}, invocationSessionId: {8}, displayName: {9}, attributes: {10}**

0050.0426 **project deployed event could not be stored: projectName: {0}, projectVersion: {1}, dateTimeOfActivity: {2}, hostAndPort: {3}, userId: {4}, correlationId: {5}, projectCreatorApp: {6}, deployedWith: {7}, invocationSessionId: {8}, displayName: {9}, attributes: {10}**

0050.0499 **an exception occurred while accessing the BusinessRules database: {0}**

Explanation

Problems occurred when accessing the database.

Action

Please read the appended original message part and see if you can solve the problem. Otherwise consult your software support center and provide this message.

0050.0500 **SQL Exception while trying to add log: serverId: {0}, projectName: {1}, projectVersion: {2}, userName: {3}, timestamp: {4}, type: {5}**

Explanation

Due to a database problem, the log cannot be written to the BusinessRulesDatabase.

Action

Please check the configuration of the JDBC Pool for the "ProcessAudit" function. Please verify that the tables for the BusinessRulesDatabase are properly created using the database component configurator. If everything is set up properly and the error still occurs, please contact your software support center and provide the IS server log file.

0050.0501 **Database Exception: no connection available**

Explanation

The SQL connection to the database is not available.

Action

Please check the configuration of the JDBC Pool for the "ProcessAudit" function. Please verify that the tables for the BusinessRulesDatabase are properly created using the database component configurator. If everything is set up properly and the error still occurs, please contact your software support center and provide the IS server log file.

0050.0502	Database Exception: error in releasing connections
Explanation	The SQL connection to the database cannot be released.
Action	Please check the configuration of the JDBC Pool for the "ProcessAudit" function. Please verify that the tables for the BusinessRulesDatabase are properly created using the database component configurator. If everything is set up properly and the error still occurs, please contact your software support center and provide the IS server log file.
0050.0503	Database Exception: error while rolling back from deleting all target runtimes
Explanation	After an error occurred, the transaction in the database is rolled back. During rollback another error occurred.
Action	Please check the configuration of the JDBC Pool for the "ProcessAudit" function. Please verify that the tables for the BusinessRulesDatabase are properly created using the database component configurator. If everything is set up properly and the error still occurs, please contact your software support center and provide the IS server log file.
0050.0504	Database Exception: error while rolling back from updating the online status of a target runtime: serverId: {0}, timestamp: {1}, isOnline: {2}
Explanation	After an error occurred, the transaction in the database is rolled back. During rollback another error occurred.
Action	Please check the configuration of the JDBC Pool for the "ProcessAudit" function. Please verify that the tables for the BusinessRulesDatabase are properly created using the database component configurator. If everything is set up properly and the error still occurs, please contact your software support center and provide the IS server log file.
0050.0505	Database Exception: error while rolling back from updating the blacklisted status of a target runtime: serverId: {0}, timestamp: {1}, isBlacklisted: {2}
Explanation	After an error occurred, the transaction in the database is rolled back. During rollback another error occurred.
Action	Please check the configuration of the JDBC Pool for the "ProcessAudit" function. Please verify that the tables for the BusinessRulesDatabase are properly created using the database component configurator. If everything is set up properly and the error still occurs, please contact your software support center and provide the IS server log file.

0050.0550	an exception occurred while shutting down the RESFacade
Explanation	An error occurred during shutdown of the WmBusinessRules package.
Action	Please contact your software support center and provide the IS server log file.
0050.1020	An exception occurred while saving rule auditing event to the DB: {0}
0050.1021	exception of previous error: {0}
0050.1023	trying to store rule auditing event: {0}
0050.1024	rule auditing event has been stored successfully: {0}
0050.1025	the server name can not be resolved: {0}
0050.1026	server name unknown (localhost)
0050.1027	port was not retrieved using service: pub.flow:getTransportInfo: {0}
0050.4905	the server name can not be resolved: {0}
0050.4906	server name unknown (localhost)
0050.9901	An unexpected exception occurred while loading the messages resources for facility [{1}] in component [{2}]: {0}
Explanation	An unexpected exception occurred while creating the IS logger.
Action	Please contact your software support center and provide the complete text of this message.
AbstractMainPage_projectOutdatedError – The project is outdated. Please upgrade to the current version.	
Explanation	The version of the rule project to be exported is outdated.
Action	Right-click the rule project in the Rules Explorer view and select Upgrade project.

AbstractMainPage_serverVersionOutdated – The server version is outdated. Please upgrade the server to the current version.

Explanation	The version of the rules environment on the server is older than the version of the rule project to be exported.
Action	Upgrade the server.

ActionSelectionWizardPage_InputOrOutputDataModelsMissing – The selected action is invalid, because one of its data models is missing.

Explanation	An action can have multiple data models. The data model files are referenced in the xml of the action. If one or more of the data models are missing, this error occurs. Action data models are not shown in the Rules Explorer view.
Action	Clean all projects in Software AG Designer. If that did not help and the data models are not shown in the Navigator view, the action might be corrupted. Try to create an action that uses the same type of data models. If this should fail, please contact your system administrator.

Common_ErrorNotConnectedToServer – No connection to the selected Integration Server available.

Explanation	The selected Integration Server is not reachable.
Action	Check, if the Integration Server is running. If so, investigate why it is not reachable through the network.

DataTypeComparisonHelper.assignmentNotPossible – Data types differ and can not be assigned.

Explanation	This is related to validating actions in decision entities. The data type of the action output may have changed and its reference in a cell may now be incorrect.
Action	Edit the referenced action and change the output type. Or remove reference to action from decision entity.

DataTypeComparisonHelper.dataTypeNotRecognized – Data type is not recognized (

Explanation	Related to validating action references in decision entities. The output type of an action or the data type of a cell is not recognized (i.e. was not known at design time).
Action	Change action output type or remove action reference and contact your software support center.

DataTypeComparisonHelper.toByte – to Byte could result in loss of data

Explanation	The user tries to assign a data type that has a greater value than the data type "byte".
Action	Remove action reference, change action output type or change data type of cell (or column).

DataTypeComparisonHelper.toCharacter – to Character could result in loss of data

- Explanation** The user tries to assign a data type that has a greater value than the data type "character".
- Action** Remove action reference, change action output type or change type of cell (or column).

DataTypeComparisonHelper.toDouble – to Double could result in loss of data

- Explanation** The user tries to assign a data type that has a greater value than the data type "double".
- Action** Remove action reference, change action output type or change type of cell (or column).

DataTypeComparisonHelper.toFloat – to Float could result in loss of data

- Explanation** The user tries to assign a data type that has a greater value than the data type "float".
- Action** Remove action reference, change action output type or change type of cell (or column).

DataTypeComparisonHelper.toInteger – to Integer could result in loss of data

- Explanation** The user tries to assign a data type that has a greater value than the data type "integer".
- Action** Remove action reference, change action output type or change type of cell (or column).

DataTypeComparisonHelper.toShort – to Short could result in loss of data

- Explanation** The user tries to assign a data type with a greater value than the data type "short".
- Action** Remove action reference, change action output type or change type of cell (or column).

EditorProjectToNewComposite_ErrorDescription – Could not open the editor:

- Explanation** There is an asset in the specified rule project that has a version newer than the version of the installed Rules Development plugin.
- Action** Update the Rules Development plugin of Software AG Designer.

EditorProjectToNewComposite_ErrorMessage – The rule project "{0}" was created with a newer version of Software AG Designer ({1}). Please upgrade the Rules Development feature.

- Explanation** There is an asset in the specified rule project that has a version newer than the version of the installed Rules Development plugin.
- Action** Update the Rules Development plugin of Software AG Designer.

EditorUpgradeComposite_ErrorMessage – The rule project "{0}" is outdated.

Explanation	The rule project "{0}" is outdated. It needs to be updated first.
Action	Right-click the rule project in the Rules Explorer view and select "Update".

EditorUtility_file_must_not_be_null – File must not be null

Explanation	An error occurred while opening the editor for the file.
Action	Try to refresh your rule project. See error log for additional information.

EditorUtility_no_active_WorkbenchPage – No active workbench page

Explanation	No active workbench could be obtained for opening the file.
Action	Try to restart Software AG Designer. See log for additional errors.

EditorUtility_no_editorInput – Could not get an editor input for the given element

Explanation	No editor input could be created for the file.
Action	Check, if the file is corrupt. See log for detailed information about the error.

EventModelSourceSelectionPage_FileNotFound – There is no file at the specified location.

Explanation	In the textbox on page two of the New Event Model wizard, the given location for the schema file is invalid.
Action	Use the browse button on the same page to search for an existing schema file, or enter a valid location for a schema file.

EventModelSourceSelectionPage_File_Not_Parsed – Error while importing Event Type. File could not be parsed.

Explanation	Problem while trying to parse an NSRecord from the chosen XSD.
Action	Make sure the chosen file is an event type (payload), or select a different file.

EventModelSourceSelectionPage_Stream_Null – Error while retrieving contents of Event Type.

Explanation	NSRecords could not be created from the given schema file.
Action	Make sure the selected schema file is a valid event type (payload), or select a different file.

ExportWizard_ExportFailedMessage – Export failed

Explanation Export failed.

Action Please consult the log file for further information.

ExportWizard_ExportFailedReason – Could not export project. Make sure you have selected the right server and that it is configured correctly. See documentation, the Eclipse Error Log and check the IS Server log for more detailed information about the error.

Explanation The rule project could not be exported.

Action Make sure that you have selected the right server and that it is configured correctly. For more information, consult the product documentation and the Eclipse Error Log.

IDataModelConstants_DataTypeNotAllowed_Error – You may not select a data element of type "{0}". Please make another selection.

Explanation The user tries to assign a data model (element) of a data type that is not allowed.

Action Select another data type.

ISExporter_ServerNotFound – Couldn't find server: "{0}"

Explanation The specified Integration Server could not be found.

Action In Software AG Designer preferences, check if the selected Integration Server is available and configured properly.

JCRImporter_ImportFolderCreationError – Folder could not be created.

Explanation When an outdated rule project is imported from the My webMethods Server repository to the Rules Development feature of Software AG Designer, it is stored in a temporary location and upgraded there. Empty folders are not received from the My webMethods Server repository, but are needed for structural integrity. Those folders are created manually by the import code. In this case, the empty folder could not be created.

Action See the log file (stack trace) for further information on the error.

JcrImportWizard_ErrorUpgradeLocalProject – Could not upgrade local project.

Explanation As the rule project from the My webMethods Server repository was outdated, it was imported to a temporary location. An error occurred, while it was upgraded in the temporary space.

Action See the log file for further information on the error.

MainIsExportPage_pingServiceNotExisting – Unable to contact the Rule engine server.

Explanation An error occurred while invoking the ping service on the Integration Server.

Action Try again. Check the versions of Software AG Designer and the Integration Server.
Check connection.

MainJcrImportPage_CantRetrieveLocalProjectInfo – Problem retrieving local project version

Explanation An error occurred while retrieving the version of the local rule project (the one that will be overwritten by the imported one).

Action See the log file for further information on the error.

MainJcrImportPage_NoConnectionToJCR0 – Can't connect to server. Check the connection!

Explanation No connection to the selected My webMethods Server repository available.

Action Verify the connection details in the Preferences page and check, if the connection actually works (is the server running, is it accessible through the network, etc.).

MainJcrImportPage_ProjectToNewErrorMessage – The remote rule project "{0}" was created with a newer version of Software AG Designer ({1}). Please upgrade the Rules Development feature.

Explanation Cannot import a rule project that was created with a newer version of the Rules Development feature.

Action Upgrade the Software AG Designer plugins.

MainJcrImportPage_WillUpgradeImportedProjectInfo – Outdated rule projects will be automatically upgraded to the current version of the Rules Development feature.

Explanation The rule project in the My webMethods Server repository is outdated. It will be updated in a temporary location before it is copied into the workspace.

Action n/a

MainJcrImportPage_WillUpgradeLocalProjectInfo – After the import, you will have an up-to-date rule project in the workspace.

Explanation The outdated rule project in your local workspace will be upgraded to the current version.

Action n/a

MetaphorActionValidator_ActionDoesNotExist – Action definition file does not exist in the specified location:

- Explanation** Related to validating actions in decision entities. The file "#ActionName#.action" is missing.
- Action** Search on the filesystem for the file (ProjectFolder/Actions/#ActionName#.action). If it exists, refresh the files in Software AG Designer and clean all projects. if it does not exist, remove the reference to the action.

MetaphorActionValidator_CouldNotGetReturnTypeOfAction – Couldn't get return type of Action.

- Explanation** Error while trying to retrieve output type of action. Action definition file (RuleProject/Actions/#ActionName#.action) may be corrupted, or file does not exist.
- Action** Clean all projects, or remove reference to action.

MetaphorActionValidator_CouldNotLoadDT – Could not load Decision Table File:

- Explanation** Decision table file (see message for detailed information) could not be parsed/loaded. Could be corrupt or missing.
- Action** Clean all projects, or remove corrupt decision table from rule project.

MetaphorActionValidator_CouldNotLoadER – Could not load Event Rule File:

- Explanation** Event rule file (for detailed information see message) could not be parsed/loaded. Could be corrupt or missing.
- Action** Clean all projects, or remove corrupt event rule from rule project.

MetaphorActionValidator_NoAccessToReturnType – Could not gain access to return type of Column with fieldId

- Explanation** Problem getting data model for column data type.
- Action** Clean all projects, or change column data type, or remove column.

MetaphorActionValidator_NoGoodAction – ActionCall does not reference an Action which is correct/complete.

- Explanation** Validation of action could not be completed as the action seems to be corrupted.
- Action** Check for other error messages, or remove action and reference to action.

MetaphorActionValidator_NoReturnValue – Action has no return value which does not work in column of type

Explanation	Action has no output value, but output type is needed in the column.
Action	Edit the action (in the Rules Explorer view, right click the action and select "Edit" from the context menu) and specify an output value on the last wizard page. Or remove the reference to the action.

MetaphorActionValidator_ReturnTypeDoesNotMatch – Return type of Action ({0}) does not match to Column Data Type ({1})

Explanation	Data type of an action output value does not match data type of the column.
Action	Change data type of the column, or change data type of the action output value.

MetaphorCorrectionProcessor_error_quickassist_message – An error occurred while computing quick assists. Check log for details.

Explanation	An error occurred while computing quick assists.
Action	Check log for details.

MetaphorCorrectionProcessor_error_quickfix_message – An error occurred while computing quick fixes. Check log for details.

Explanation	An error occurred while computing quick fixes.
Action	Check log for details.

MetaphorCorrectionProcessor_error_status – Exception while processing quick fixes or quick assists

Explanation	An error occurred while computing quick fixes or quick assists.
Action	Check log for details.

MetaphorSuppressWarningsProposal_Error_Msg – An exception occurred while applying the quick fix

Explanation	An error occurred while applying the quick fix.
Action	Please see the dialog and/or error log for additional information on the error.

MissingDataModelValidator_DataModel – The data model for a parameter is missing: {0}.

Explanation	A parameter references a data model that is missing. The data model may have been deleted.
Action	Either recreate the data model, or remove the parameter from the decision entity and all data elements that belonged to it.

MissingDataModelValidator_EventModel – The event model for a parameter is missing: {0}.

Explanation A parameter references an event model that is missing. The event model may have been deleted.

Action Either recreate the event model, or remove the parameter from the decision entity and all data elements that belonged to it.

MissingSlotKeyValidator_ErrorLoadingDataModel – error loading data model: "{0}"

Explanation An error occurred while attempting to load a data model.

Action Refresh the rule project and try again. If that does not fix the problem, contact your administrator and provide the log file and the rule project.

MissingSlotKeyValidator_ParameterDoesNotContainField – Parameter "{0}" does not contain field "{1}" of type "{2}".

Explanation This problem may occur when synchronizing data models with document types or event models with event types. It means that a data element is being used within a decision entity that no longer exists within a data model or event model.

Action If the decision entity is a decision table, the column referencing the missing field should be deleted. If it is an event rule, then the row referencing the missing field should be deleted.

NewEventModelWizard_ErrorCreatingEventModel – Error creating event model

Explanation An error occurred while importing the event type .xsd-file. NSRecord (event model) files may have not been created.

Action Try again, or try another schema file. Refer to the logged exception.

ParameterSelectionComposite_SelectAtLeastOne_Error – Select at least one data model for a parameter.

Explanation No data model is selected as an input or output parameter.

Action On the current wizard page, select a data model and move it to the right to make it available as parameter.

Resources_OutOfSyncResources_Msg – Some resources are out of synch

Explanation One or more resources are out of synch with the file system. They need to be refreshed inside Software AG Designer.

Action Please refresh your rule project.

Resources_OutOfSync_Msg – Resource "{0}" is out of synch with the file system

Explanation One or more resources are out of synch with the file system. They need to be refreshed inside Software AG Designer.

Action Please refresh your rule project.

ResultCellValidator.DivisionByZero – Division by 0 is not allowed.

Explanation You may not divide a value by zero.

Action Correct the expression to avoid division by zero.

ResultCellValidator.LiteralValueMissing – The literal value in the result cell is missing.

Explanation The literal value in the result cell is missing.

Action Enter a literal value, parameter element, constant or action call.

ResultCellValidator.OperatorAndValueMissing – The result cell is empty.

Explanation Both the operator and value for a result cell are missing. This is a warning.

Action Either ignore the warning or enter an operator and value.

ResultCellValidator.OperatorMissing – The operator in the result cell is missing.

Explanation No operator has been specified for a condition cell.

Action Select an operator.

ResultCellValidator.OperatorUndefined – The operator in the result cell is undefined.

Explanation No operator has been specified for a result cell.

Action Select an operator.

ResultCellValidator.ParameterMissing – The parameter in the result cell is missing.

Explanation The parameter for a result cell is missing.

Action Enter a parameter element, literal value, constant or action call.

ResultCellValidator.ValueMissing – The value of the result cell is missing.

Explanation The result cell value is missing.

Action Enter a literal value or select a parameter element, constant or action call.

ResultCellValidator.ValueUndefined – The value of the result cell is not defined.

Explanation The result cell value is not defined.
Action Enter a literal value or select a parameter element, constant or action call.

RuleFile_ErrorParsingDTXMLForProcessingMode – Error parsing decision table XML for ProcessingModeType.

Explanation An error occurred while parsing one of the selected files.
Action Try to deselect the files and retry your selection.

RuleLocalLaunchRunner_ErrorUndeploying_Msg – An error occurred while undeploying the rule project [%s].

Explanation The execution of the launch was terminated abnormally, and an attempt was made to clean up the rule project. The attempt failed.
Action Start Software AG Designer with -clean option. If the problem persists, send the details of this exception to your technical support.

RuleProjectContentRetrievalException.msg.specific.extended – [{0}] can not be found. Cause: [{1}]

Explanation A resource that was requested could not be found.
Action See the error log for additional information about the error. If the error occurred in Software AG Designer, refresh your rule project.

RulesArchive.FutureVersionRuleProject – The version ("{1}") of the rule project "{0}" is too new for this builder ("{2}"). Please upgrade your build environment.

Explanation The provided rule project is built with a newer version of Business Rules compared to the version of the Asset Build Environment.
Action Please upgrade your Asset Build Environment to the latest version or contact your support.

ValidationMessage.project.contains.errors – The project "{0}" contains at least one error.

Explanation The evaluated rule project contains at least one validation error and cannot be exported and executed.
Action Check the Problems view or the log file for the error(s).

VersionValidator.asset.outdated – The "{0}" is outdated. Its version is {1}. The required version is {2}.

Explanation The user has attempted to open a decision entity that was created with an older version of the Rules Development feature or the Rules Management Console.

Action The user must upgrade the decision entity in order to be able to edit it.

VersionValidator.asset.too.new – The "{0}" was created with a newer version of rules. Its version is {1}. The required version is {2}.

Explanation The user has attempted to open a decision entity that was created with a newer version of the Rules Development feature or Rules Management Console.

Action The user must upgrade to the latest version in order to be able to edit the selected decision entity.

VersionValidator.project.outdated – The project "{0}" is outdated. Its version is {1}. The required version is {2}.

Explanation The user has attempted to open rule project that was created with an older version of the Rules Development feature or Rules Management Console.

Action The user must upgrade the rule project in order to be able to modify any of its rule assets.

VersionValidator.project.too.new – The project "{0}" was created with a newer version of rules. Its version is {1}. The required version is {2}.

Explanation The user has attempted to open a rule project that was created with a newer version of the Rules Development feature or Rules Management Console.

Action The user must upgrade the rule project to the latest version in order to modify any of its rule assets.

cancel.confirm.msg This will cancel all unsaved changes. Would you like to proceed?

Explanation The state of the configuration before editing was started will be restored. All added rows of the Master Integration Server configuration will be deleted and all removed rows will be restored.

Action n/a

error.comma.entered – Commas are not allowed for name, host and port fields.

Explanation In one of the input fields "logical name", "host" or "port" a comma was entered. This is not allowed.

Action Check for commas and remove them.

error.host.invalidCharacter – You have used an invalid character in the host name

Explanation The host name contains invalid characters.
Action Check host name for following characters: ':'

error.hostName.missing – You must specify a host name

Explanation The host input field must not be empty.
Action Specify the host.

error.logicalName.duplicate – Two servers in the list have identical names. Server names must be unique.

Explanation There are at least two rows in the list of Master Integration Server that share the same 'logical name'. This is not allowed.
Action Be sure to have a unique 'logical name' for each server.

error.logicalName.missing – You must specify a name for each server.

Explanation The input field 'logical name' must not be empty.
Action Specify a unique name.

error.port.missing You must specify a port for each host

Explanation The port input field must not be empty.
Action Specify a valid port.

error.port.portValidationErrorMsg – Please enter valid Port value.

Explanation The entered port value is not valid.
Action The port value has to be a numeric value between 0 and 65535.

exception.not.saved – Error! Decision Entity could not be saved.

Explanation An exception occurred while persisting the decision entity contents into the My webMethods Server repository.
Action Please contact your software support center. Also provide the following log file found in location MWS_SERVER_BASE_DIR/logs/_full_.log

hotDeployment.results.message.error_deploymentFailed – Deployment on target IS {0} failed. Exception message: {1}

Explanation The RMC has tried to deploy to Integration Server with host name {0}. There was an exception which has the message {1}.

Action Check whether wmBusinessRules package is up and running on the Integration Server.

hotDeployment.results.message.error_noMasterIsConnection – No connection to master IS [{0}] established. Exception message: {1}

Explanation The RMC has tried to connect to the Master Integration Server with host name {0} that manages a list of Deployment Target Integration Servers. An exception occurred that has the message {1}. No deployment for all its Target Integration Servers is possible.

Action Check network connection to Master Integration Server.

hotDeployment.results.message.error_noMasterIsList – The list of configured master IS cannot be retrieved. Exception message: {0}

Explanation An exception occurred with message {0} while trying to read the list of configured Master Integration Servers.

Action Please contact your software support center. Also provide the following log file found in location MWS_SERVER_BASE_DIR/logs/_full_.log.

hotDeployment.results.message.error_noTargetIsConnection – No connection to target IS [{0}] established. Exception message: {1}

Explanation The RMC has tried to connect to the Deployment Target Integration Server with host name {0}. An exception occurred that has the message {1}. No deployment on this Target Integration Server is possible.

Action Check network connection to Target Integration Server.

hotDeployment.results.message.error_noTargetIsList – Cannot retrieve deployment target IS servers from master IS [{0}]. Exception message: {1}

Explanation The RMC has tried to retrieve the list of Deployment Target Integration Servers from the Master Integration Server with host name {0}. An exception occurred that has the message {1}. No deployment for all its Target Integration Servers is possible.

Action Check whether package wmBusinessRules is up and running on Master Integration Server. If it is up and running, please contact your software support center. Also provide the following log file found in location MWS_Server_Base_Dir/logs/_full_.log and try to provide the Integration Server log file as well.

hotDeployment.results.message.error_projectArchiveCreationFailed – Error creating rule project archive for hot deployment: {0}

Explanation An exception occurred with the message {0} while creating the rule project archive file needed for the hot deployment step.

Action Please contact your software support center. Also provide the following log file found in location MWS_SERVER_BASE_DIR/logs/_full_.log.

hotDeployment.results.message.success_deploymentSuccessful – Deployment on target IS {0} successful.

Explanation Deployment was successfully finished on the Integration Server in location {0}.

Action n/a

label.hotDeployment.confirmation1 – This will require verification of the rule project "{0}" and will update it on all configured Integration Servers.

Explanation Confirmation message before hot deployment starts. The user should be aware to redeploy the rule project with name {0} on all Integration Servers that are indirectly configured through the Master Integration Server list.

Action n/a

label.hotDeployment.confirmation2 – Note that all decision entities that are part of this rule project will be overwritten on the Integration Server with the current version stored in the My webMethods Server repository.

Explanation Second message part of the confirmation before hot deployment starts. The user should be aware that the rule content for the deployment is taken from the My webMethods Server repository. All unsaved changes of the current RMC workspace are not part of the hot deployment.

Action n/a

label.hotDeployment.results.message.errors – Hot Deployment of rule project "{0}" completed with errors.

Explanation Errors occurred during hot deployment.

Action For error details, please click "See details".

label.hotDeployment.results.message.successfully – Hot Deployment of rule project "{0}" completed successfully.

Explanation The rule project was deployed on all indirectly configured Target Integration Servers.

Action To see the list of the Target Integration Servers, please click "See details".

lock.err.lock.exception – An error occurred while trying to lock the selected Decision Entity:

- Explanation** An exception occurred while trying to create the lock file for the decision entity in the My webMethods Server repository.
- Action** Please contact your software support center. Also provide the following log file found in location MWS_SERVER_BASE_DIR/logs/_full_.log

lock.err.unlock.exception – An error occurred while trying to unlock the selected Decision Entity:

- Explanation** An exception occurred while trying to delete the lock file for the decision entity in the My webMethods Server repository.
- Action** Please contact your software support center. Also provide the following log file found in location MWS_SERVER_BASE_DIR/logs/_full_.log

text.newer.version.dialog.to.newer.rule.project.version – The rule project "{0}" has a newer version "{1}" than the currently installed version "{2}".

- Explanation** The rule project has been created with a newer version of the Rules Development feature or Rules Management Console.
- Action** Please upgrade the Rules Management Console.

text.upgrade.displayed.only.upgraded – Only updated rule projects can be displayed.

- Explanation** The rule project is outdated. The update may have failed.
- Action** Try to update the rule project and see the log for details.

text.upgrade.warning.old.version – Only updated rule projects can be displayed.

- Explanation** The rule project is outdated. The update may have failed.
- Action** Try to update the rule project and see the log for details.

5

CentraSite Messages

E_assertionNotFound30000 – Signifies that a particular publisher assertion (consisting of two businessKey values, and a keyed reference with three components) cannot be identified in a save or delete operation.

Explanation The specified publisher assertion does not exist in the registry.

Action Please make sure the publisher assertion exists before deleting or updating it.

E_authTokenRequired10120AUTH – The authentication token value is missing in the authInfo argument of the UDDI request.

Explanation The authInfo element is not present in the UDDI request. CentraSite requires the authInfo element to be present in the request with a valid authToken.

Action Please make sure that authInfo is present in UDDI request.

E_authTokenRequired10120DEF – Signifies that an invalid authentication token was passed to an API call that requires authentication.

Explanation The authentication token passed is not valid.

Action Please fetch the authentication token using get_authToken API and use it in the API.

E_authTokenRequired10120INVAUTH – The authentication token value {0} passed in the authInfo argument of the UDDI request is not valid.

Explanation The authentication token passed is not valid.

Action Please fetch the authentication token again using get_authToken API and use it in the API.

E_fatalError10500 {0}

Explanation Fatal error occurred while processing the request.

Action Please retry and make sure the UDDI request is valid.

E_fatalError10500APPDOWN – UDDI application not properly initialized. Please try restarting the CentraSite server.

Explanation UDDI application received UDDI API calls before the UDDI web application initialized properly.

Action Restart the CentraSite server.

E_fatalError10500CUSTOWN – Custody and Ownership Transfer API calls are not supported when security policy is Deactivated

Explanation CentraSite needs a security policy to be activated for processing the Custody and Ownership Transfer API.

Action Please activate a security policy.

E_fatalError10500INFOSEL – Attribute infoSelection is not present in request.

Explanation The get_registeredInfo API requires the infoSelection attribute. If it is not present in the request then this error will occur.

Action Please make sure the infoSelection attribute is present in the get_registeredInfo request.

E_fatalError10500INVFINDGET – Invalid find_xx or get_xx api specified in the subscriptionFilter

Explanation The subscriptionFilter does not contain the valid UDDI v3 subscription filter.

Action Please make sure the subscription filter in the save_subscription request is valid.

E_fatalError10500KREFNATB – KeyedReference does not contain required attribute.

Explanation The KeyedReference should contain the keyValue attribute.

Action Please make sure the keyedReference in the request has attribute keyValue.

E_fatalError10500MISCFAT – Saving subscription failed due to internal registry error.

Explanation Internal registry error.

Action Please retry the request.

E_fatalError10500MSE – Search limit exceeded, maximum allowed is {0}. Contact node operator to increase the search limit.

Explanation Maximum search limit reached.

Action Please reduce the number of search keys in the inquiry request or increase the search limit via the System Management Hub.

E_fatalError10500PERF – Performance metrics with key {0} cannot be saved. Please make sure Performance Log is enabled in SMH.

Explanation The user is trying to save performance metrics, but the performance log is disabled in SMH. Performance metrics will be saved only if the performance log is enabled in SMH.

Action Please make sure the performance log is enabled in SMH.

E_fatalError10500SUBKEXP – The subscription with subscriptionKey {0} has expired. Please renew this subscription.

Explanation The subscription has expired as the specified expiration date has been reached.

Action Please renew the subscription by saving it with a new expiration date.

E_invalidCombination40500QUA – The combination of Qualifiers is not allowed

Explanation Invalid find qualifier combinations were found in the request.

Action Please make sure the combination of find qualifiers present in the inquiry request is valid. The invalid combinations are: andAllKeys, orAllKeys and orLikeKeys are mutually exclusive; sortByNameAsc and sortByNameDesc are mutually exclusive; sortByDateAsc and sortByDateDesc are mutually exclusive; combineCategoryBags, serviceSubset and bindingSubset are mutually exclusive; exactMatch and approximateMatch are mutually exclusive; exactMatch and caseInsensitiveMatch are mutually exclusive; binarySort and UTS-10 are mutually exclusive, as are all collation algorithm tModels with each other; diacriticSensitiveMatch and diacriticInsensitiveMatch are mutually exclusive; exactMatch and diacriticInsensitiveMatch are mutually exclusive; caseSensitiveSort and caseInsensitiveSort are mutually exclusive; caseSensitiveMatch and caseInsensitiveMatch are mutually exclusive.

E_invalidCompletionStatus30100 – {0} is not a valid completion status.

Explanation An invalid value was passed for completion status argument. Valid completion status are status:complete, status:fromKey_incomplete, status:toKey_incomplete and status:both_incomplete.

Action Please provide a proper completion status.

E_invalidKeyPassed10210 – No matching key found in the registry for {0}.

Explanation CentraSite does not contain any UDDI entity with the key specified in the UDDI request.

Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210BEBEK – Could not find the business entity corresponding to the business key.

Explanation CentraSite does not contain any business entity with the key specified in the UDDI request.

Action Please make sure the business key specified in the request is valid.

E_invalidKeyPassed10210BEBK – Could not find the business service corresponding to the binding key {0}.

Explanation CentraSite does not contain a business service corresponding to the service key specified in the binding template.

Action Please make sure the service key specified in the request is valid.

E_invalidKeyPassed10210BEMAT – No businessEntity in the UDDI registry matched the key {0}.

Explanation CentraSite does not contain any business entity with the key specified in the UDDI request.

Action Please make sure the business key specified in the request is valid.

E_invalidKeyPassed10210BKBE – Tried to get a businessEntity with key {0}, but key did not match with any existing businessEntities.

Explanation CentraSite does not contain any business entity with the business key specified in the UDDI request.

Action Please make sure the business entity with the specified business key exists in CentraSite.

E_invalidKeyPassed10210BKINV – BusinessKey invalid.

Explanation The BusinessKey specified in the request is invalid.

Action Please make sure the specified businessKey is valid.

E_invalidKeyPassed10210BKMAT – No bindingTemplate in the UDDI registry matched the key {0}.

Explanation CentraSite does not contain a binding template with the key specified in the UDDI request.

Action Please make sure the binding key specified in the request is valid.

E_invalidKeyPassed10210BSMAT – No businessService in the UDDI registry matched the key {0}.

Explanation CentraSite does not contain a business service with the key specified in the UDDI request.

Action Please make sure the service key specified in the request is valid.

E_invalidKeyPassed10210BSNE – A businessService with key {0} does not exist.

Explanation CentraSite does not contain a business service with the key specified in the UDDI request.

Action Please make sure the service key specified in the request is valid.

E_invalidKeyPassed10210BSNF – Could not find the businessService corresponding to the service key {0}

Explanation CentraSite does not contain a business service corresponding to the service key specified in the binding template.

Action Please make sure the service key specified in the request is valid.

E_invalidKeyPassed10210BT – The bindingKey of the bindingTemplate to save does not match any existing bindingTemplate in the UDDI registry.

Explanation CentraSite does not contain a binding template with the key specified in the UDDI request.

Action Please make sure the binding key specified in the request is valid.

E_invalidKeyPassed10210BTNF – Could not find the binding Template corresponding to the binding key {0}

Explanation CentraSite does not contain a binding template with the key specified in the UDDI request.

Action Please make sure the binding key specified in the request is valid.

E_invalidKeyPassed10210BTSK – The bindingTemplate to save does not contain a serviceKey.

Explanation The binding template to be saved does not contain the service key required for this binding template. The service key has to be specified when saving a binding template.

Action Please specify a valid service key in the UDDI request.

E_invalidKeyPassed10210CAT – Invalid tModelKey in categoryBag.

Explanation The category bag should contain keyedReference/KeyedReferenceGroups with valid values for tModelKey and KeyValue.

Action Please specify valid values for tModelKey/KeyValue in the category bag.

E_invalidKeyPassed10210DBE – Tried to delete a businessEntity with key {0}, but key did not match with any existing businessEntities.

Explanation CentraSite does not contain any business entity with the business key specified in the delete request.

Action Please make sure the business key specified in the request is valid.

E_invalidKeyPassed10210DEF – Signifies that the uuid_key value passed did not match with any known key values.

Explanation CentraSite does not contain any UDDI entity with the key specified in the UDDI request.

Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210DELSUB – Tried to delete a subscription with key {0}, but key did not match with any existing subscriptions.

Explanation CentraSite does not contain any subscription with the key specified in the delete request.

Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210EMTTMBAG – Tmodel bag is empty

Explanation TModelBag cannot be empty, but the UDDI request contains an empty tModelBag.

Action Please make sure tModelBag contains the required values.

E_invalidKeyPassed10210FRMK – No businessEntity in the UDDI registry matched the fromKey {0}

Explanation The fromKey specified in the add_publisherAssertion request is either invalid, or no business entity matched the fromKey.

Action Please make sure the fromKey specified in the request is valid.

E_invalidKeyPassed10210HIDTM – Tried to delete a tModel with key {0} which is not hidden.

Explanation Hidden Tmodels cannot be deleted.

Action Hidden tModels cannot be deleted. Please update the tModel and delete it.

E_invalidKeyPassed10210IBAG – Invalid tModelKey in identifierBag.

Explanation The identifier bag should contain keyedReference/KeyedReferenceGroups with valid values for tModelKey and KeyValue.

Action Please specify valid values for tModelKey/KeyValue in the identifier bag.

E_invalidKeyPassed10210INVKEY – The Key {0} is invalid.

Explanation The specified key is not valid.

Action Please make sure the key is valid according to the UDDI standard.

E_invalidKeyPassed10210INVTMK – Invalid tModelKey {0}.

Explanation CentraSite does not contain a TModel with the key specified in the UDDI request.

Action Please specify a valid tModelKey in the UDDI request.

E_invalidKeyPassed10210KBAGK – key {0} passed in the key bag does not match any businessEntity or tModel.

Explanation CentraSite does not contain a business entity or tModel with the key specified in key bag of the discard_transferToken request.

Action Please specify a valid business key or tModel key in the key bag.

E_invalidKeyPassed10210KREF – KeyedReference should be passed !

Explanation The publisher assertion should contain a keyedReference and it is missing in the UDDI request.

Action Please specify a KeyedReference for the publisher assertion.

E_invalidKeyPassed10210MITS – Multiple instances of the same {0} {1} were passed.

Explanation Keys should be unique for all UDDI entities. The UDDI request contains an existing UDDI entity key.

Action Please provide a unique key for the UDDI entity.

E_invalidKeyPassed10210MREF – The tModelKey cannot have multiple references to be deleted.

Explanation Multiple references of a tModelKey were specified in the UDDI request.

Action Please make sure that a single reference exists for a single tModelKey in the request.

E_invalidKeyPassed10210NBE – Tried to update a businessEntity with key {0}, but no businessEntity in the UDDI registry matched the key.

Explanation CentraSite does not contain any business entity with the business key specified in the save request.

Action Please make sure the business key specified in the request is valid.

E_invalidKeyPassed10210NULTM – Tried to delete a tModel with key, but the key did not match with any existing tModel or it is null.

Explanation CentraSite does not contain any TModel with the key specified in the delete request.

Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210OPINFMAT – No OperationalInfo in the UDDI registry matched the key {0}.

Explanation The operational info cannot be found for the given key.

Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210PAINV – The Publisher Assigned Key {0} is not a valid key.

Explanation The key provided for the UDDI entity by the publisher is not valid.

Action Please specify the key according to the UDDI standard

E_invalidKeyPassed10210PANAL – The Publisher Assigned Key is not allowed.

Explanation The user is not allowed to assign keys for the UDDI entity (CentraSite object).

Action Save the UDDI entity without assigning a key to it.

E_invalidKeyPassed10210SUBMAT – No subscription in the UDDI registry matched the key {0}.

Explanation CentraSite does not contain any subscription with the key specified in the delete request.

Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210SUBNE – The subscription having subscriptionKey as {0} does not exist.

Explanation CentraSite does not contain any subscription with the key specified in the delete request.

Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210TMIBK – Invalid tModelKey in tModelInstanceInfo for BindingKey {0}.

Explanation The specified binding template does not contain a valid tModelKey in tModelInstanceInfo.

Action Please make sure the tModelKey specified in tModelInstanceInfo of the binding template is valid.

E_invalidKeyPassed10210TMKN – TModelvalue should not be null !

Explanation The key value of KeyedReference does not contain a valid value.

Action Please specify a valid key value for the KeyedReference.

E_invalidKeyPassed10210TMKNF – No matching tmodelkey was found. Please check that the tModelKey is of relationship type.

Explanation CentraSite does not contain a tModel with the key specified in the UDDI request.

Action The tModelKey of the keyedReference in the publisher assertion must be the key of the uddi-org:relationships tModel.

E_invalidKeyPassed10210TMKREF – tModelKey not specified in one of the keyedReferenceGroup.

Explanation The tModel key has to be specified for all KeyedReferenceGroups.

Action Please specify a valid tModel key for all KeyedReferenceGroups.

E_invalidKeyPassed10210TMMAT – No tModel in the UDDI registry matched the key {0}.

Explanation CentraSite does not contain a tModel with the key specified in the UDDI request.

Action Please specify a valid tModel key in the UDDI request.

E_invalidKeyPassed10210TMNF – The specified tModelkey {0} cannot be found.

Explanation CentraSite does not contain a TModel with the key specified in the UDDI request.
Action Please specify a valid tModelKey in the UDDI request.

E_invalidKeyPassed10210TOK – No businessEntity in the UDDI registry matched the toKey {0}

Explanation The toKey specified in the add_publisherAssertion request is either invalid or no business entity matched the toKey.
Action Please make sure the toKey specified in the request is valid.

E_invalidKeyPassed10210USUBK – Tried to update a subscription with key {0}, but no subscription in the UDDI registry matched the key.

Explanation CentraSite does not contain any subscription with the key specified in the delete request.
Action Please make sure the key specified in the request is valid.

E_invalidKeyPassed10210UTM – Tried to update a TModel with key {0}, but no TModel in the UDDI registry matched the key.

Explanation CentraSite does not contain a TModel with the key specified in the UDDI request.
Action Please specify a valid tModelKey in the UDDI request.

E_invalidProjection20230 – No businessService with service key {0} exists in the UDDI registry.

Explanation CentraSite does not contain a business service with the key specified in the UDDI request.
Action Please make sure the service key specified in the request is valid.

E_invalidTime40030 Invalid time period specified or the date/time pair is invalid.

Explanation The date/time provided in the UDDI request is not valid.
Action Please provide the date/time in the format specified in UDDI specification.

E_invalidValue20200EXPAFTDAT – The specified expiresAfter date value is incorrect

Explanation The specified expiresAfter value for the subscription is not in the proper format.
Action Please provide expiresAfter in the proper format.

E_invalidValue20200EXPAFTVAL – expiresAfter has a value older than the current date/time.

Explanation The expiresAfter element of the subscription denotes when the subscription will expire. However, the value specified in the expiresAfter element is older than the current time.

Action Please provide a newer date/time value than the current time for the expiresAfter attribute.

E_invalidValue20200INV – {0} is not a valid value

Explanation The specified attribute does not contain a valid value in the UDDI request.

Action Please provide a valid value.

E_invalidValue20200INVVAL – Invalid Value: {0}

Explanation The key value of the relationship KeyedReference is invalid.

Action Please provide a valid key value.

E_invalidValue20200KNAMNUL – keyName and keyValue should be specified for {0} keyedReference

Explanation In UDDI, the keyedReference with tModelKey “uddi:uddi.org:categorization:general_keywords or uuid:A035A07C-F362-44dd-8F95-E2B134BF43B4” has different behavior. Unchecked value sets can be specified using this KeyedReference. Since this is unchecked, the value sets keyName and KeyValue are mandatory.

Action Please provide a value for KeyName and the KeyValue attribute of the uddi-org:general_keywords KeyedReference.

E_invalidValue20200KVALINV – The attribute keyValue {0} for keyedReference {1} failed validation.

Explanation Validation failed for the KeyedReference as it does not contain a proper key value.

Action Please provide valid key value.

E_invalidValue20200KVALNUL – The attribute keyValue should not be null for a keyedReference.

Explanation KeyValue is a mandatory attribute and it should contain a valid value.

Action Please provide a value for the KeyValue attribute of KeyedReference.

E_invalidValue20200MAXENT – maxEntities has a negative value.

Explanation The maxEntities attribute of the subscription should contain a positive number.
Action Please provide a positive value for the maxEntities attribute.

E_invalidValue20200NOVAL – For asynchronous subscription, both the bindingKey and notificationInterval values should be specified

Explanation To identify whether a subscription is asynchronous or synchronous, the elements bindingKey and notificationInterval are used. Element bindingKey is used to identify to which web service/email address the notification has to be sent. Element notificationInterval is used to identify how often the notification has to be sent. Both elements are required for asynchronous subscription.
Action Please provide values for the bindingKey and notificationInterval attributes for asynchronous subscription.

E_invalidValue20200NTFINT – {0} is not a valid value for notification interval.

Explanation The notificationInterval attribute has to be specified in xsd:duration format.
Action Please provide notificationInterval attribute in xsd:duration format.

E_tokenAlreadyExists40070 – Token Generated for key {0} has expired or the token is already occupied for the specified entities.

Explanation CentraSite already generated a transfer token for the specified entities.
Action Please re-generate the token or use the existing token for the specified entities.

E_transferNotAllowed40600DEF – Transfer Not Allowed!!

Explanation CentraSite does not allow this transfer. The specified transfer token is not present in CentraSite. It might be discarded.
Action Transfer of the entities are not allowed

E_transferNotAllowed40600DNE – TransferToken does not exist.

Explanation The specified transfer token does not exist in CentraSite. It might be invalid or discarded.
Action Please generate new transfer token.

E_transferNotAllowed40600INV – Transfer not allowed. Custody (Operator) or ownership are not same.

Explanation CentraSite does not allow the entities to be transferred if the owners or operator are not the same.

Action Operator and ownership must be the same to transfer entities.

E_transferNotAllowed40600TCBE – Transfer the custody of this businessEntity {0} to the node {1} on which it is modified.

Explanation CentraSite does not support transferring the node businessEntity.

Action The transfer is not allowed for this business entity.

E_transferNotAllowed40600TCBS – Transfer the custody of this businessService {0} to the node {1} on which it is modified.

Explanation The node of the businessService does not match the CentraSite node businessEntity.

Action Transfer is not allowed for this businessService.

E_transferNotAllowed40600TCBT – Transfer the custody of this bindingTemplate {0} to the node {1} on which it is modified.

Explanation The node of the bindingTemplate does not match the CentraSite node businessEntity.

Action Transfer is not allowed for this bindingTemplate.

E_transferNotAllowed40600TCTM – Transfer the custody of this tModel {0} to the node {1} on which it is modified.

Explanation The node of the tModel does not match the CentraSite node businessEntity.

Action Transfer is not allowed for this tModel.

E_transferNotAllowed40600TTNEX – This TransferToken does not exist.

Explanation CentraSite does not contain the specified transfer token.

Action Please fetch a new transfer token.

E_unknownUser10150ID – User ID {0} and password pair passed in a get_authToken API is unknown to the UDDI node or is not valid.

Explanation A user ID in the get_authToken request is mandatory, but the userId element in the get_authTokenRequest request is null.

Action Please provide a valid user ID and password in the get_authToken request.

E_unknownUser10150PASS – User ID and password {0} pair passed in a get_authToken API is unknown to the UDDI node or is not valid.

Explanation The cred element in the get_authToken request is mandatory, but the cred element in the get_authTokenRequest request is null.

Action Please provide a valid user ID and password in the get_authToken request.

E_unrecognizedVersion10040 – Namespace {0} is unsupported by the node being queried.

Explanation The request is not a valid UDDI request or the request cannot be processed by CentraSite.

Action Please provide a valid UDDI request as defined in the UDDI specification.

E_unsupported10050 Feature {0} is not supported.

Explanation The request is not a valid UDDI request or the request cannot be processed by CentraSite.

Action Please provide a valid UDDI request as defined in the UDDI specification.

E_unsupported10050AUTH – authInfo element present in get_assertionStatusReport element is required.

Explanation Authorization is required to process the get_assertionStatusReport call.

Action Please provide an authInfo element with a proper authToken in the get_assertionStatusReport call. Please fetch the authToken using a get_authToken call.

E_unsupported10050INVFINDGET – Invalid find_xx or get_xx api specified in the subscriptionFilter or some part of the subscription to be saved is invalid.

Explanation The subscription filter for the subscription is not valid.

Action Please provide the subscription filter for the subscription according to the UDDI specification.

E_unsupported10050INVFQ – {0} is not a valid find qualifier value in version {1}.

Explanation The provided find qualifier is not valid. The valid qualifiers can be found in UDDI specification.

Action Please provide find qualifiers compliant with the UDDI specification.

E_unsupported10050NINV – The notification interval specified is less than {0}. Please increase the notification interval.

Explanation UDDI configuration parameter UDDIMinimalNotificationInterval specified the minimal notification interval that the UDDI engine can handle. If the given value is less than the UDDIMinimalNotification interval then this error will occur.

Action Please increase the notification interval

E_unsupported10050QUA – This Qualifier is not allowed with FindBinding Inquiry API.

Explanation The find qualifiers binarySort, bindingSubset, caseInsensitiveSort, caseSensitiveSort, combineCategoryBags, sortByNameAsc, sortByNameDesc, serviceSubset and suppressProjectedServices are not supported in the find_binding call.

Action Please specify find qualifiers other than binarySort, bindingSubset, caseInsensitiveSort, caseSensitiveSort, combineCategoryBags, sortByNameAsc, sortByNameDesc, serviceSubset and suppressProjectedServices for the find_binding call.

E_unsupported10050QUARELB – This Qualifier is not allowed with FindRelatedBusinesses Inquiry API.

Explanation The find qualifiers andAllKeys, bindingSubset, combineCategoryBags, orAllKeys, orLikeKeys, serviceSubset and suppressProjectedServices are not supported in the find_relatedBusinesses call.

Action Please specify find qualifiers other than andAllKeys, bindingSubset, combineCategoryBags, orAllKeys, orLikeKeys, serviceSubset and suppressProjectedServices for the find_relatedBusinesses call.

E_unsupported10050QUARSER – This Qualifier is not allowed with FindService Inquiry API.

Explanation The serviceSubset find qualifier is not supported in the find_service call.

Action Please remove the serviceSubset find qualifier from the find_service request.

E_unsupported10050QUARTM – This Qualifier is not allowed with FindTModel Inquiry API.

Explanation The find qualifiers bindingSubset, combineCategoryBags, serviceSubset and suppressProjectedServices are not supported in the find_tModel call.

Action Please specify find qualifiers other than bindingSubset, combineCategoryBags, serviceSubset and suppressProjectedServices for the find_tModel call.

E_unvalidatable20220UNVALID – The referenced tModel has been marked unvalidatable.

Explanation CentraSite does not allow an unvalidatable KeyedReference to be present in the UDDI request.

Action The specified tModel cannot be used in the keyedReference.

E_userMismatch10140 – Signifies that an attempt was made to use the publishing API to change data that is controlled by another party.

Explanation An access violation exception occurred as the user tried to modify a UDDI entity owner by another user.

Action Please make sure proper permissions are assigned to the user to update the entity.

E_userMismatch10140DELSUBUSR – Tried to delete a subscription that is controlled by another individual.

Explanation An access violation exception occurred as the user tried to delete the subscription owned by another user.

Action Please provide the authToken of the user who owns the subscription.

E_userMismatch10140DIFSUB – The owner of the subscription is different.

Explanation The subscription is not owned by the specified user.

Action Please provide the authToken of the user who owns the subscription.

E_userMismatch10140FRMTOK – USER-MISMATCH for publisherAssertion fromKey {0} and toKey {1}.

Explanation The user should own the business specified in fromKey or toKey.

Action Please provide the business key owned by the user either in fromKey or in toKey.

E_userMismatch10140PBE – You are not authorized to publish a businessEntity.

Explanation The user does not have permission to create a business in CentraSite.

Action Please make sure the user has permission to create a business in CentraSite.

E_userMismatch10140TT – You are not authorized to get the TransferToken for the key {0} which is owned by another publisher.

Explanation The transfer token for an entity can be fetched by the user who owns the entity. Transfer token for the entities which the user does not own cannot be fetched.

Action Please provide the key of the owned UDDI entity.

E_userMismatch10140UEK – Tried to update the {0} {1} that is controlled by another individual.

Explanation The user does not own or does not have permission to update the UDDI entity.

Action Make sure the user has permission to update the UDDI entity, or make sure the user owns the UDDI entity.

E_userMismatch10140USUBUSR – Tried to update the subscription with key {0}, that is controlled by another individual.

Explanation The subscription is not owned by the specified user.

Action Please provide the authToken of the user who owns the subscription.

E_valueNotAllowed20210NODE – This checked category system is only permitted to be used by the node itself.

Explanation The node business cannot be updated by the user.

Action The node business cannot be updated by the user.

INMAFE0001 The registry object must not be null.

Explanation The constructor CSAppFixedRegistryObject() is trying to create a new instance so the registry object passed can't be null.

Action Pass valid registry object.

INMAFE0002 A fixed registry object's name cannot be changed.

Explanation This is a fixed Registry Object. It's name must not be changed.

Action Don't change a fixed registry object's name.

INMAFE0003 Different object with duplicate key already registered: {0}

Explanation Two different objects that have the same keys are being registered.

Action Check for any reasons why the duplicate keys exist or change one of the object's keys.

INMAFE0004 Different association type with duplicate name already registered {0}

Explanation Two different associations that have the same names are being registered.

Action Change one of the association's names.

INMAFE0005 **Different object type with duplicate name already registered {0}**
Explanation Object types have to have unique names.
Action Change the object type name to a unique one.

INMAFE0006 **Different child list already registered for parent path: {0}**
Explanation for this path there is already a defined child list.
Action Create another parent path to add the new child list.

INMAFE0007 **Unknown taxonomy: {0}**
Explanation The desired taxonomy does not exist.
Action Use an existing Taxonomy.

INMAFE0008 **Multiple taxonomies named {0} found.**
Explanation Taxonomies must have unique names.
Action Find a way to make the used taxonomies have a unique name.

INMAFE0010 **Different object with duplicate name already registered: {0}**
Explanation The objects are classification schemes, their names must be unique.
Action Find a way to change the object names to unique ones.

INMAFE0011 **No such concept: {0}**
Explanation This Concept does not exist in the database.
Action Create such a Concept or change to an existing one.

INMAFE0012 **No such classification scheme: {0}**
Explanation This classification scheme does not exist in the database.
Action Create a new one or change to an existing classification scheme.

INMAFE0013 **No such association type: {0}**
Explanation This association type does not exist in the database.
Action Create a new one or change to an existing association type.

INMAFE0014	No such object type: {0}
Explanation	This object type does not exist in the database.
Action	Create a new one or change to an existing object type.
INMAFE0015	Child list not available for parent {0}, did you set the cache strategy 'childs'?
Explanation	The cache strategy "childs" needs to be set in order to access child concepts.
Action	Set the cache strategy 'childs'.
INMAFE0017	Child list not available for taxonomy {0}, did you set the cache strategy 'childs'?
Explanation	The cache strategy "childs" needs to be set in order to access child concepts.
Action	Set the cache strategy 'childs'.
INMAFE0018	Child list not available for parent concept {0}, did you set the cache strategy 'childs'?
Explanation	The cache strategy "childs" needs to be set in order to access child concepts.
Action	Set the cache strategy childs.
INMAFE0019	No object with key {0} is known by the pool.
Explanation	No fixed RegistryObject was found in the bean pool.
Action	The fixed registry object must be added to the bean pool.
INMAFE0021	Invalid element {0}, expected either of {1}
Explanation	The specified element is not contained in the list of expected elements.
Action	Use or change the element to one of the expected types.
INMAFE0023	Missing attribute: {0}
Explanation	The searched attribute is mandatory and must be provided.
Action	Provide the missing attribute or change it so it is not mandatory any more.
INMAFE0024	Empty attribute: {0}
Explanation	The attribute is empty.
Action	Provide data for the attribute.

INMAFE0025 **Duplicate objectType name: {0}**
Explanation Object Types must have unique names.
Action Provide a unique name for the object type, delete or rename the existing one.

INMAFE0026 **Duplicate associationType name: {0}**
Explanation The assoiation type name must be unique.
Action Provide a unique association type name, delete or rename the existitng one.

INMAFE0027 **Duplicate taxonomy name: {0}**
Explanation Taxonomy name must be unique.
Action Provide unique name for the Taxonomy, rename or delete the existing one.

INMAFE0028 **Invalid value for {0}**
Explanation The specified value is invalid.
Action Provide valid value.

INMAFE0029 **Invalid element {0}, expected {1}**
Explanation The specified element does not match the expected element.
Action The element must be changed accordingly to the expected item.

INMAFE0031 **Duplicate concept value for taxonomy {0}**
Explanation Taxonomy must have a unique concept value.
Action Provide a unique concept value for the taxonomy.

INMAFE0032 **Duplicate concept value for concept {0}**
Explanation Concept must have a unique concept value.
Action Provide a unique concept value for the concept.

INMAFE0033 **Invalid argument: {0}**
Explanation The specified argument is invalid.
Action Provide a valid argument.

INMAFE0034	The class {0} has no annotation of type {1} or has an empty 'implementation' attribute.
Explanation	The given class does not have the expected annotation, or the annotation's "implementation" attribute is empty.
Action	Provide an annotation of the given type or fill in the 'implementation' attribute.
INMAFE0037	The object type's qualified name must not be null.
Explanation	One of the arguments has a null value.
Action	Provide arguments with a valid value.
INMAFE0038	A classification's scheme must not be null.
Explanation	The classification has a null value.
Action	Provide a valid value for classification.
INMAFE0039	A classification's value must not be null.
Explanation	The classification has a null value.
Action	Provide a valid value for classification.
INMAFE0040	The object type's qualified name must not be null.
Explanation	The object type's qualified name has null value.
Action	Provide a valid value for object type's qualified name.
INMAFE0041	The classification schemes must not be null.
Explanation	The classification schemes have a null value.
Action	Provida a valid value for the classification schemes.
INMAFE0042	This object is unmodifiable.
Explanation	The object cannot be modified.
Action	Do not try to modify the object.
INMAFE0043	Unknown property {0}
Explanation	The property has unknown value.
Action	Provide a valid value for the property.

INMAFE0044	The IOC annotation of the field {0} has no ID or an empty ID.
Explanation	Some annotation has an empty ID or no ID.
Action	Provide a valid ID for the annotation.
INMAFE0045	The object to initialize must not be null.
Explanation	The initializer has a null value.
Action	Provide a valid value for the initializer.
INMAFE0046	The document must not be null.
Explanation	The document is null.
Action	Provide a valid value for the document.
INMAFE0047	The QName {0} is invalid, because it contains no terminating '}' character.
Explanation	The value argument has no enclosing '}' character.
Action	Make sure the value argument has an enclosing '}' character.
INMAFE0049	Expected {0} element, got {1}
Explanation	The element is different than expected.
Action	Make sure the element type is as expected.
INMAFE0051	Missing attribute for {0}
Explanation	The attribute has a null value.
Action	Provide a valid value for the attribute.
INMAFE0052	Invalid attribute {0} for element {1}
Explanation	The attribute has an invalid value.
Action	Provide a valid value for the attribute.
INMAFE0054	The attribute {0} for element {1} is using an invalid prefix: {2}
Explanation	Some of the attributes have an invalid prefix.
Action	Make sure the attribute has a valid prefix.

INMAFE0056	Missing attribute: {0}
Explanation	Attribute is missing.
Action	Provide attribute.
INMAFE0057	Empty attribute: {0}
Explanation	Attribute is missing.
Action	Provide attribute.
INMAFE0058	The class {0} doesn't implement {1}
Explanation	Wrong class provided.
Action	Provide a valid class.
INMAFE0116	Missing @RegistryObject annotation on persistent class {0}
Explanation	The processed class has no @RegistryObject annotation. As long as there is no such annotation the persistent class cannot be considered a RegistryBean and cannot be processed.
Action	Add a @RegistryObject annotation to the persistent class interface or use different RegistryBean.
INMAFE0119	The given registry bean is managed by another pool: {0}
Explanation	A registry bean instance can be managed by one bean pool only. For example it is not allowed to read a bean with one bean pool instance and update it with another.
Action	Check for multiple beanPool instances managing your registry beans. For a single thread, make one bean pool instance to handle the registry beans.
INMAFE0121	The given registry bean is not managed by the pool: {0}
Explanation	The registry bean is being used by a bean pool it does not belong to.
Action	Find and use the bean pool instance that this registry bean belongs to. For example if a registry bean is read or created by one bean pool instance, this is the instance it belongs to and it cannot be managed by another one.
INMAFE0123	Missing information for attribute with name {0} of type {1}
Explanation	This attribute should have an attribute description but it does not. For example, attribute description is required for @Relationship , @DateAttribute and other attributes.
Action	When using @Relationship, @DateAttribute etc. an attributeName property must be specified, which corresponds to the name of an existing AttributeDescription. Either create new attribute description, or change the name of the attributeName property to an existing one.

INMAFE0128	The RegistryObject must be an association, but is a {0}
Explanation	The RegistryObject to be processed must be a javax.xml.registry.infomodel.Association. The method is trying to create a RegistryBean instance from a javax.xml.registry.infomodel.Association instance.
Action	Check the mapping of theRegistryBean that is being created for any inconsistencies.
INMAFE0129	AssociationTarget property of {0} is null. Association target cannot be null.
Explanation	While creating a javax.xml.registry.infomodel.Association instance from a registry bean Association instance. The target of the association must be present in order to create a javax.xml.registry.infomodel.Association.
Action	Set target for the association.
INMAFE0130	Unable to determine object type. Missing RegistryObject annotation for class {0}.
Explanation	Either the processed registry bean is not a registry bean at all, or it is missing its RegistryObject annotation. Without it the registry bean cannot be created and it is not considered a registry bean.
Action	Either use a different registry bean that has a RegistryObject annotation, or add the annotation in the used registry bean interface.
INMAFE0131	Missing concept with key {0}.
Explanation	The key that is specified is either wrong or does not belong to a concept instance.
Action	Use a different object type key for this annotation.
INMAFE0132	Missing concept with name {0}
Explanation	The name that is specified is either wrong or does not belong to a concept instance.
Action	Use a different object type name for this annotation.
INMAFE0133	The RegistryObject must be a classification.
Explanation	The registry object to be processed must be a javax.xml.registry.infomodel.Classification instance.
Action	Use a registry object that is an instance of javax.xml.registry.infomodel.Classification.

INMAFE0134	ClassificationConcept property of {0} is null. The concept for internal classification cannot be null.
Explanation	The classification's concept property is not specified.
Action	Specify a concept for this classification.
INMAFE0135	Missing {0} annotation. {1} must be classified instance.
Explanation	The ClassifiedInstances annotation is missing. It must be present in order to create a ClassifiedInstances property.
Action	Add the ClassifiedInstances annotation to the registry bean.
INMAFE0136	{0} is not specified as ClassifiedInstance
Explanation	None of the bean interfaces is a classified instance in the ClassifiedInstances annotation's instances.
Action	Specify a bean interface as ClassifiedInstance.
INMAFE0137	Cannot find the required classification on {0}
Explanation	There is no corresponding classification for the given registry object.
Action	Provide the classification.
INMAFE0138	BeanInfo {0} for {1} must be instance of {2}
Explanation	The BeanInfo instance is not of type BackedBeanInfo.
Action	Make the BeanInfo an instance of BackedBeanInfo.
INMAFE0139	No setter found for property {0} in class {1}
Explanation	The name of the setter is different and a corresponding setter cannot be found in the jaxr representation of this registry bean.
Action	Change the name of the setter in the registry bean interface.
INMAFE0140	Missing type information for {0}
Explanation	The BeanType for this jaxr registry object cannot be found in the registry object model. It is not supported by CSAF.
Action	Add BeanType for the required jaxr registry object type in the registry object model.

INMAFE0141	Getter returns unexpected value type: {0} . Expected: Collection. For property: {1} in class: {2}
Explanation	The value returned by the getter method does not match the return type specified in the bean interface.
Action	Change the return type to collection or change the annotation used for this property.
INMAFE0142	No instance of SlotHandler registered for the type {0}
Explanation	None of the existing slot handlers handles the given property type.
Action	Add a slot handler or change the property type.
INMAFE0143	Expected RegistryObject of type javax.xml.registry.infomodel.User or javax.xml.registry.infomodel.Organization {0}
Explanation	The javax.xml.registry.infomodel.TelephoneNumbers support type can only be found in a javax.xml.registry.infomodel.User or javax.xml.registry.infomodel.Organization instance.
Action	Use a javax.xml.registry.infomodel.User or javax.xml.registry.infomodel.Organization instance for operations with javax.xml.registry.infomodel.TelephoneNumbers.
INMAFE0144	A Collection is expected {0}
Explanation	TelephoneNumbers is always a collection. Single property is not allowed.
Action	Use a collection of TelephoneNumbers.
INMAFE0145	Expected RegistryObject of type User or Organization RegistryBeans {0}
Explanation	The CSAF support type TelephoneNumbers can only be found in a User or Organization RegistryBean instance.
Action	Use a User or Organization RegistryBean instance for operations with CSAF TelephoneNumbers.
INMAFE0146	Beans to restore must be of BackedBeanInfo instance
Explanation	Only BackedBeanInfo instances can provide access to the underlying RegistryObject.
Action	Use BackedBeanInfo to provide access to the RegistryObject that is standing behind the RegistryBean.

INMAFE0147	Invalid bean mode
Explanation	The bean mode of a configuration can be BACKED or SIMPLE (has been deprecated). Any other bean mode set to the configuration will result in this exception.
Action	Set the bean mode of the configuration to BACKED. The BACKED constant is located under com.softwareag.centrasite.appl.framework.persistence.BeanMode.java.
INMAFE0148	The object to be read must be a RegistryObject instance: {0}
Explanation	The object to be read must be an instance of javax.xml.registry.infomodel.RegistryObject but is not.
Action	Read a different object that is of javax.xml.registry.infomodel.RegistryObject instance.
INMAFE0149	Unsupported value type passed: {0}
Explanation	The value type passed is not supported by this method and cannot be processed.
Action	Change the value Type or change the method you are using to process this value. For example, the toJaxrValue() method expects one of the support types defined in CSAF (EmailAddress, TelephoneNumbers etc.) and processes it to a JAXR support type , while the toBeanValue method does the opposite.
INMAFE0150	Missing type information for {0}
Explanation	No BeanType found in the registry object model for the given registry object. It is not supported by CSAF.
Action	Create a BeanType and add it to the registry object model for the given registry object type.
INMAFE0151	The BulkResponse collection must currently be java.util.List {0}
Explanation	The result method of the Search class always has to return a java.util.List object.
Action	Change the Search's BulkResponse collection to java.util.List.
INMAFE0152	Missing type information for {0}
Explanation	No BeanType found in the registry object model for the given registry object. It is not supported by CSAF.
Action	Create a BeanType and add it to the registry object model for the given registry object type.

INMAFE0153	Property is null, this kind of predicate is not allowed
Explanation	A predicate has been created for a property that does not exist.
Action	Check the search criteria for wrong property names.
INMAFE0154	The given class: {0} is not supported
Explanation	No BeanType found for the given class in the registry object model.
Action	Add BeanType in the registry object model for the desired class.
INMAFE0159	Invalid attribute name. Attribute name must not contain a space or special characters.
Explanation	Creating a slot attribute with spaces or special characters in its name is not allowed.
Action	Use camel case (example: SlotAttribute) or '_' (example: Slot_Attribute) in the name instead of space, or change the name in a different way that it does not contain spaces.
INMAFE0160	Invalid slot attribute data type.
Explanation	The data type passed when creating slot attribute is not supported.
Action	Change the data type to one that is supported. Constants with supported data types can be found in AttributeDescription class.
INMAFE0161	Unknown Error
Explanation	The error that has been thrown has unknown reasons.
Action	Contact your software supplier.
INMAFE0162	The parent concept must not be null.
Explanation	The Concept must have a parent.
Action	Add parent to the concept.
INMAFE0163	Invalid namespace prefix: {0}
Explanation	The namespace prefix is invalid.
Action	Change the namespace to a valid one.
INMAFE0164	Don't know how to handle skipped entity: {0}
Explanation	The Parser has encountered a skipped entity. CSAF does not support skipped entities.
Action	Exclude the skipped entities from the entity list.

INMAFE0165	Expected empty stack.
Explanation	The Parser has reached the end of the file, and its stack should be empty.
Action	Check the file for any inconsistencies or errors.
INMAFE0166	No getter for property {0} found in class {1}
Explanation	In order to access a RegistryBean property it must have a getter method.
Action	Provide a getter method for this RegistryBean property. In some cases the getter methods are not provided for a purpose. These RegistryBeans should be documented.
INMAFE0167	The method {0} in class {1} must be public, and neither static, nor abstract.
Explanation	There is a restriction that must be followed.
Action	Change the method to public and remove any static or abstract modifiers.
INMAFE0168	Failed to parse getter name: {0}
Explanation	A getter method follows a rule when created. It must begin with either get or is. Any other case will result in this exception.
Action	Rename the getter method so it follows the described rule.
INMAFE0169	The setter {0} in class {1} has return type {2} , not void.
Explanation	A setter method must have a void return type.
Action	Change the setter return type to void.
INMAFE0170	The method {0} in class {1} must be public, and not static.
Explanation	There is a restriction to this method, namely it must be public and not static.
Action	Follow the restriction.
INMAFE0171	Failed to parse method name: {0}
Explanation	The method must start with either get, set, has or is. This is necessary in order to be recognized by the parser so a property name can be extracted.
Action	Change the method name accordingly.

INMAFE0172	Illegal access to default constructor of class {0} : {1}
Explanation	Nested exception is thrown here. The constructor has to be called with an empty expression list, or check {1} for more information.
Action	Change the constructor accordingly.
INMAFE0173	Failed to instantiate class {0} : {1}
Explanation	Nested exception is thrown here. More details are found in {1}
Action	Handle according to the nested exception message.
INMAFE0174	Illegal access to default constructor of class {0} : {1}
Explanation	Nested exception is thrown here. The constructor has to be called with an empty expression list, or check {1} for more information.
Action	Change the constructor accordingly.
INMAFE0175	Failed to instantiate class {0} : {1}
Explanation	Nested exception is thrown here. More details are found in {1}
Action	Handle according to the nested exception message.
INMAFE0176	Failed to invoke constructor of class {0} : {1}
Explanation	Nested Exception. See {1} for more information.
Action	Handle the case according to information in {1}.
INMAFE0177	No field named {0} found in class {1} or any of its superclasses.
Explanation	The desired field is not present in the class, nor in any of the superclasses.
Action	Provide the missing field, or change the field name being searched.
INMAFE0178	Illegal access to field {0} in class {1} : {2}
Explanation	Nested Exception thrown, see {2} for more details.
Action	Handle according to the information in {2}.
INMAFE0179	Failed to load the class named {0}.
Explanation	The class with the given name was not found.
Action	Provide the missing class.

INMAFE0180	Invalid property specification: {0}
Explanation	The property has opening bracket [but no closing bracket].
Action	Provide the closing bracket] .
INMAFE0181	Invalid property specification: {0}
Explanation	The property was not specified correctly.
Action	Make sure that the property follows all rules.
INMAFE0182	No list was returned for property specification {0}
Explanation	This property is expected to return a list.
Action	Check the property for any inconsistencies.
INMAFE0183	No add method found for property {0} in class {1}
Explanation	The property must correspond to an add method, but it doesn't.
Action	Provide an add method, change the property or check the property for inconsistencies.
INMAFE0184	No remove method found for property {0} in class {1}
Explanation	The property must correspond to a remove method, but it doesn't.
Action	Provide a remove method, change the property or check the property for inconsistencies.
INMAFE0185	A fixed registry object's description cannot be changed.
Explanation	This registry object description cannot be changed.
Action	Don't attempt to change a fixed registry object's description.
INMAFE0186	The interface {0} doesn't have its implementation attribute set in the {1} annotation.
Explanation	Each interface bean needs to specify its implementation class.
Action	Please use correct value for the annotation attribute.
INMAFE0187	The key must not be null.
Explanation	Each key must have a non-null id value.
Action	Provide non-empty, unique key value.

INMAFE0188	The concept key must point to a Concept: {0}
Explanation	Classifications can only be based on concepts.
Action	Make sure that the Classification's concept key is actually pointing to a Concept registry object.
INMAFE0189	The registry object type key must point to a Concept from the ObjectType taxonomy: {0}
Explanation	The required object needs to be a child of the "ObjectType" taxonomy.
Action	Make sure that object type key points to a Concept from the ObjectType taxonomy (Classification Scheme).
INMAFE0190	The association type key must point to a Concept from the AssociationType taxonomy: {0}
Explanation	The required object needs to be a child of the "AssociationType" taxonomy.
Action	Make sure that association type key points to a Concept from the AssociationType taxonomy (Classification Scheme).
INMAFE0191	The property is null.
Explanation	The getMapper() method requires a non-null property argument.
Action	Make sure the property is available.
INMAFE0192	No property mapper found for Property {0}
Explanation	The property mapper for the desired property does not exist.
Action	Make sure that a suitable property mapper is available for this property.
INMAFE0193	Wrong value type passed. Expected Collection<com.softwareag.centrasite.appl.framework.beans.standard.TelephoneNumber>
Explanation	The method requires an argument of type "Collection".
Action	Make sure the correct value type is used.
INMAFE0194	Cannot parse string to long(timestamp) {0}
Explanation	The given value does not match the syntax rules for long numeric values.
Action	Expected long numeric value.

INMAFE0195	Cannot parse date string {0}
Explanation	The given value does not match the syntax rules for dates.
Action	Make sure the string is in the proper date format.
INMAFE0196	Unsupported value passed: {0}. String value expected: either {namespace}localPart or localPart only.
Explanation	The method expects a vlue of type "String".
Action	Please provide the correct value.
INMAFE0197	Unsupported value type {0}
Explanation	The KeyPredicate value type must be one of "String", "Key", or "RegistryBean".
Action	Please provide a valid value.
INMAFE0198	Unable to create predicate for : {0}. Check the passed sequence and try again.
Explanation	The values specified for the predicate cannot be properly converted to a query criterion.
Action	Please provide a valid predicate.
INMAFE0199	The given object is not a RegistryObject.
Explanation	The method requires a RegistryObject parameter.
Action	Please provide the correct object.
INMAFE0200	Given object is not Classification: {0}
Explanation	The method requires a Classification object.
Action	Please provide a valid Classification object.
INMAFE0201	Unsupported collection. Should be java.util.List or java.util.Set.
Explanation	The method requires a parameter of type List or Set.
Action	Please provide a collection of valid type.
INMAFE0202	Only attributes of type Slot can be indexed.
Explanation	Index definitions are only possible for Slot attributes.
Action	Use an attribute of valid type.

INMAFE0203	Value and forward label must not be null.
Explanation	When creating a new association type it is mandatory to specify a value and a forward label.
Action	Correct the application program.
INMAFE0204	Object type to be generated not found: {0}
Explanation	The object type name specified when calling the RegistryBeanGenerator does not exist.
Action	Specify an existing type name.
INMAFE0205	Invalid object ({0}) passed to delete operation
Explanation	The delete operation only accepts RegistryBean instances. In particular, NULL pointers are rejected.
Action	Call the delete operation with correct RegistryBean instances.
INMAPE0001	The user {0} does not have the view permission; contact the asset owner or administrator for help.
Explanation	If the current user has no permission to view this object, then this error will be thrown.
Action	The user needs to be provided proper permission to view this object.
INMBUE0002	Invalid URI {0}.
Explanation	You have entered an invalid URI.
Action	Enter a valid URI.
INMBUE0003	Invalid phone number.
Explanation	You have entered an invalid phone number.
Action	Enter a valid phone number.
INMBUE0004	Search scope is empty.
Explanation	You have not entered a valid search scope in the recipe.
Action	Enter a valid search scope.

INMBUE0007	Saved search token is not valid.
Explanation	You have entered an invalid saved search token in the URL.
Action	Enter a valid saved search token.
INMBUE0009	Failed to initialize the Unwatch action on selected assets.
Explanation	Could not initialize the Unwatch action on selected assets; possibly because one or more of the selected assets are not already watched.
Action	Choose the assets that are already watched.
INMBUE0011	Enter a valid IP address
Explanation	Enter a valid IP address
Action	Enter a valid IP address
INMBUE0012	Duplicate values for {0}
Explanation	A user was selected as an administrator, but this user has already been selected.
Action	Avoid selecting a user as administrator that has already been chosen.
INMBUE0013	Invalid URL
Explanation	You have entered an invalid URL.
Action	Enter a valid URL.
INMBUE0014	Enter a valid Administrator
Explanation	You have entered an invalid administrator name.
Action	Enter a valid administrator name.
INMBUE0015	Group name is empty
Explanation	You have not entered a group name while creating a local group.
Action	Enter a group name.
INMBUE0016	Invalid URI.
Explanation	You have entered an invalid URI.
Action	Enter a valid URI.

INMBUE0017	Invalid numeric value in attribute.
Explanation	You have entered an invalid numeric value for this attribute.
Action	Enter a valid numeric value.
INMBUE0018	Invalid attribute value.
Explanation	You have entered an invalid attribute value for the chosen type.
Action	Enter a valid value for the chosen type.
INMBUE0019	Required attribute value is empty.
Explanation	You have entered a blank value for the required attribute.
Action	Enter a value for the required attribute.
INMBUE0020	Enter a valid string value for the attribute.
Explanation	You have entered an invalid value for this string attribute.
Action	Enter a valid string value.
INMBUE0021	Enter a valid IP address.
Explanation	You have entered an invalid IP address.
Action	Enter a valid IP address.
INMBUE0022	Enter a valid email address.
Explanation	You have entered an invalid email address. You must enter a valid email address (e.g. example@example).
Action	Enter a valid email address (e.g. example@example).
INMBUE0023	Invalid category name.
Explanation	You have entered an invalid category name for this classification attribute.
Action	Enter a valid category name for the defined taxonomy.
INMBUE0024	Refresh interval is empty.
Explanation	Number. Required. An input denoting the time interval for refreshing a portlet automatically is not specified.
Action	Enter a value (in seconds) for refresh interval.

INMBUE0025	Required attribute value is empty.
Explanation	You have entered a blank value for the required attribute.
Action	Enter a value for the required attribute.
INMBUE0026	Invalid search condition.
Explanation	An invalid search condition has occurred. A search condition consists of one or more predicates, each joined by a keyword (ALL or ANY). A predicate can be a comparison predicate, such as an Equals predicate, NotEquals predicate, StartsWith predicate, or a Contains predicate. This error occurs when none of the above search conditions are met.
Action	Correct the search condition.
INMBUE0028	Invalid combination of x and y axes; at least one of the axes must have a numeric attribute for the graph to render properly.
Explanation	One of the attribute in the x or y axis should have a numeric value.
Action	Choose a numeric attribute in one of the two axes.
INMBUE0029	Invalid search for charts; you must choose at least one numeric attribute.
Explanation	The chosen search does not have a numeric attribute to plot the chart. To plot a chart you must have a combination of non-numeric attribute and numeric attribute.
Action	Choose a search with at least one numeric attribute.
INMBUE0030	Organization name is empty
Explanation	The organization name field is empty, but the organization name must be provided when creating an organization.
Action	Enter the organization name.
INMBUE0031	Role name is empty
Explanation	The role name field is empty, but the role name must be provided when creating a role.
Action	Enter a role name.

INMBUE0032	Enter a valid consumer application name.
Explanation	The consumer application name specified is either invalid or empty.
Action	Enter a valid consumer application name.
INMBUE0035	Required Base URL value is empty.
Explanation	The Base URL value is a required attribute value and if at least one such URL value is not provided, then this error occurs to indicate that the base URL value is required and should not be empty.
Action	Enter at least one URL value for your API.
INMBUI0005	No document(s) available.
Explanation	Documents are not available to download.
Action	No action required.
INMBUI0006	Selected item(s) not applicable for Export
Explanation	The selected item(s) are not applicable for export.
Action	No action required.
INMBUI0008	No target found for deployment.
Explanation	No target found was for deployment
Action	Register a target for deployment before initiating the Publish action.
INMBUI0010	Error while instantiating the activity {0}.
Explanation	Could not instantiate the activity {0}. The failure is likely to be cause by incorrect configuration.
Action	Verify that the activity has been configured correctly.
INMBUI0027	Unable to view the profile information.
Explanation	You do not have sufficient access right to view the profile information.
Action	Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.

INMBUI0033 **Enter the base URL for your API.**
Explanation The base URL for the API you are trying to create should be specified in the Endpoint field.
Action Enter the Base URL value.

INMBUI0034 **Enter a namespace.**
Explanation A namespace for the instance is required to be entered in the input field.
Action Enter a valid namespace for the instance.

INMBUW0001 **Invalid search query.**
Explanation You have entered an invalid search query, possibly because the query is not available in the CentraSite repository.
Action The search query {0} is not available. Configure your portlet with a valid search query.

INMBU_LBL_USER_BEEPER_PHONE – Beeper

INMBU_LBL_USER_DOMAIN_NAME – Display Name

INMBXE0003 **Enter a valid username or password.**
Explanation You have entered an invalid username or password. To log in to CentraSite, you must enter a valid username and password.
Action Enter a valid username or password.

INMBXE0004 **Enter a valid username.**
Explanation You have entered an invalid username. To log in to CentraSite, you must enter a valid username.
Action Enter a valid username.

INMBXE0005 **Enter a valid email address (e.g. example@example)**
Explanation You have entered a wrong or blank email address. You must enter a valid email address (e.g. example@example).
Action Enter a valid email address (e.g. example@example).

INMBXE0009	Enter a valid password. This email address will be used when signing into CentraSite.
Explanation	To request an account in CentraSite, you must enter a password.
Action	Enter a valid password.
INMBXE0010	Enter your first name. Example: John.
Explanation	To request an account in CentraSite, you must enter your first name.
Action	Enter your first name.
INMBXE0011	Enter your last name. Example: Smith.
Explanation	To request an account in CentraSite, you must enter your last name.
Action	Enter your last name.
INMBXE0012	Enter a reason for requesting access to CentraSite.
Explanation	To register an account in CentraSite, you must provide a valid reason for requesting the account to CentraSite.
Action	Enter a valid reason for requesting access to CentraSite.
INMBXE0016	Password does not match
Explanation	The password for Confirm Password does not match the given password.
Action	Confirm the given password by entering the same password again.
INMBXI0001	CentraSite gives your organization a single place to store, find and reuse service and process assets. That speeds up development. Automatic policy enforcement helps you ensure new services and processes perform consistently and to the quality standards you've set.
Explanation	This message provides an introduction to CentraSite in the login page.
Action	Get an overview of the product.
INMBXI0002	Log in to Your Account
Explanation	Enter the user account credentials to log in to CentraSite.
Action	Log in to CentraSite.

INMBXI0006	Create Your Account
Explanation	Request for an account in CentraSite.
Action	Enter the user credentials and create an account in CentraSite.
INMBXI0008	Thank you for your registration in CentraSite.
Explanation	Thank you for your registration. We will contact you soon and inform you of the next steps. In the meantime you may visit CentraSite as a guest.
Action	Log in to CentraSite as a guest.
INMBXI0013	You will be contacted by a CentraSite administrator.
Explanation	The CentraSite administrator will process your registration request and contact you shortly.
Action	The CentraSite Administrator will process your request and contact you shortly.
INMBXI0014	Access CentraSite as a guest.
Explanation	You may access CentraSite as a guest.
Action	Access CentraSite as a guest.
INMBXW0015	JavaScript is not enabled in your web browser.
Explanation	If JavaScript is already installed but the application does not work, you may need to enable JavaScript in your web browser.
Action	Enable the JavaScript in your web browser.
INMBX_LBL_ERROR_PAGE – Enable your CentraSite license.	
Explanation	Members of the CentraSite Community Edition (CE) are not allowed to use the CentraSite Business UI. This is because the Community Edition is a free-of-charge version of CentraSite that does not include a CentraSite license. In order to use the CentraSite Business UI, you must have the CentraSite license installed.
Action	Install the CentraSite license. For further information contact your software supplier.
INMBX_LBL_IE8_COMPATIBILITY_TEXT – CentraSite Business UI is not designed to run in compatibility mode. Disable the compatibility mode to render the Business UI.	
Explanation	CentraSite Business UI is not designed to run in compatibility mode.
Action	Disable the compatibility mode to render the Business UI.

INMBX_LIC_ACCESS_ERROR – Error accessing license information. Check the error log for more information.

Explanation Error encountered while accessing the CentraSite license information.

Action If this error persists, contact your administrator.

INMCBE0009 You do not have sufficient access rights to modify this object.

Explanation You do not have sufficient access rights to modify this object.

Action Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.

INMCBE0012 Invalid password specified.

Explanation You have specified an invalid password.

Action Correct password and try again.

INMCBE0013 HTTP response {0} received while updating password.

Explanation While updating the password, the user received an http error with the given error code.

Action Analyse the reason for this error based on the http error code.

INMCBE0014 Error occurred when reading configuration file at {0}.

Explanation An error occurred when reading the user-specific configuration file at the given location.

Action Refer to the stack trace - you may need to delete the given file from the repository.

INMCBE0015 You have entered no file or folder name.

Explanation You have entered no file or folder name.

Action Enter a name.

INMCBE0016 The name you have entered is invalid. Web Folder names cannot include any of the following characters: :*\<>|\"

Explanation The name you have entered is invalid. Web folder names cannot include any of the following characters: :*\<>|\"

Action Specify another name.

INMCBE0017	The name you have entered exceeds the maximum allowed name length.
Explanation	The name you have entered exceeds the maximum allowed name length.
Action	Specify a shorter name.
INMCBE0018	No report definition is linked to given report object
Explanation	The report must have an external link referencing the report definition created via BIRT.
Action	Repeat the import of the report either via the "Import Report" command in the user interface or via the "Export to CentraSite" command in the BIRT plugin of Eclipse.
INMCBE0020	Failed to obtain value of parameter {0}
Explanation	Could not determine value for the parameter with given name.
Action	Contact your software supplier.
INMCBE0021	The domain of the specified user is invalid.
Explanation	The domain of the specified user is invalid. For non-windows platforms, only the domain LOCAL or LDAP is allowed.
Action	Enter a valid domain. For non-Windows platforms, only the domain LOCAL or LDAP is allowed.
INMCBE0022	Object no longer available
Explanation	The selected object does not exist, possibly because it has been implicitly discarded before or an import has failed.
Action	Check recent activities.
INMCBE0024	The passwords you typed do not match.
Explanation	The passwords you typed do not match.
Action	Enter the new password in both text boxes.
INMCBE0027	The specified user does not exist.
Explanation	The specified user is not present in CentraSite.
Action	Specify a valid user.

INMCBE0029	Error occurred when initializing CentraSite Control - disabling plug-in.
Explanation	An error occurred when initializing CentraSite Control.
Action	Check details of error message for further information.
INMCBE0030	Invalid change of data type for existing data.
Explanation	An attempt is being made to change the data type of a property that already has data present that is not of the type specified.
Action	Select a data type that matches the existing data.
INMCBE0032	Asset name must not be empty.
Explanation	No name is specified for the asset.
Action	Enter a valid asset name.
INMCBE0033	Asset type not valid.
Explanation	The selected asset type is not valid for this operation.
Action	Select a valid asset type.
INMCBE0035	The associated object of type Associated with could not be deleted
Explanation	User does not have permission to delete the associated object
Action	Grant delete permission to the user for the associated object
INMCBE0036	The associated object of type WS-Policy attachment could not be deleted
Explanation	The user does not have permission to delete the WS-Policy associated with the virtual service.
Action	Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.
INMCBE0037	The associated object of type External Link could not be deleted
Explanation	The user does not have permission to delete associated external links.
Action	Verify that you have the appropriate access rights. Contact your administrator and request access if necessary and then try again.

INMCBE0038	Asset with name {0} already exists of type {1}
Explanation	There is a duplicate asset name.
Action	Enter another name for the asset.
INMCBI0001	New ExternalLink has been copied to the internal clipboard. It can be added to arbitrary registry objects now.
Explanation	The newly created ExternalLink object has been copied to the internal clipboard. It can be used to add the ExternalLink to any registry object via the tab "External Links".
Action	No action required.
INMCBW0002	Resource cannot be deleted as it is the target of one or more ExternalLink objects.
Explanation	You cannot delete this resource as it is referenced by one or more external links.
Action	You may run the impact analysis in order to determine the registry objects that have an external link referencing this resource.
INMCBW0003	Folder cannot be deleted as it is the target of one or more ExternalLink objects.
Explanation	You cannot delete this folder as it is referenced by one or more External Links.
Action	You may run the impact analysis in order to determine the registry objects that have an external link depending on this folder.
INMCBW0004	Resource cannot be renamed as it is the target of one or more ExternalLink objects.
Explanation	You cannot rename this resource as it is referenced by one or more registry objects.
Action	You may run the impact analysis in order to determine the registry objects that have an external link depending on this resource.
INMCBW0007	No report is linked to type {0}.
Explanation	No report has been associated to the type via the 'Link Reports' command.
Action	You can associate a report via the command 'Link Reports' for the respective type.
INMCBW0010	No operation is defined for type {0}.
Explanation	The definition of the respective type does not contain any operations.
Action	You can add operations via the 'Modify Type' command for the respective type.

INMCBW0011	You are connected as a read-only user. This will lead to limited functionality being available.
Explanation	A read-only user does not have privileges to modify registry objects.
Action	Log in as another user if you want to modify registry objects.
INMCBW0019	No items have been exported
Explanation	No items have been exported - this may happen if items selected for export are embedded into other objects and thus cannot be exported without their parent objects.
Action	Select the parent object for export.
INMCBW0031	File cannot be deleted as it is the target of one or more Favorite objects of My CentraSite.
Explanation	You cannot delete this file as it is referenced by one or more External Links in My CentraSite.
Action	You may run the impact analysis in order to determine the Favorite Object in My CentraSite that has an external link referencing this resource.
INMCCE0001	Command {0} is not supported by CentraSite command line tool
Explanation	The specified command cannot be executed by the CentraSite command line tool. It is not in the list of supported commands.
Action	Please check the usage of CentraSiteCommand and make sure you specify the command which is listed in the usage.
INMCCE0002	Exception while fetching email properties
Explanation	CentraSiteCommand is not able to fetch the email properties from CentraSite.
Action	Please make sure all the parameters are valid and re-execute the command.
INMCCE0003	Exception while storing email properties
Explanation	CentraSiteCommand is not able to store the email properties into CentraSite.
Action	Please make sure all the parameters are valid and re-execute the command.
INMCCE0006	Parsing failed! Please make sure configuration file syntax and path are correct.
Explanation	Parsing the CentraSiteCommand option and/or configFile failed.
Action	Please make sure the CentraSiteCommand options are specified properly and configFile exists in the specified location.

INMCCE0007	Parsing failed! Please make sure configuration file syntax and path are correct.
Explanation	This error can occur because of two reasons. 1) The syntax of the configuration file is not valid. 2) The specified configuration file path is incorrect.
Action	Please refer to the documentation for information on creating a valid configuration file.
INMCCE0008	Failed to execute command {0}
Explanation	Error occurred while executing the command.
Action	Please check the error message for details.
INMCCE0009	Internal error occurred
Explanation	This error may occur because of problems in the system execution.
Action	Please contact the administrator.
INMCCE0010	{0} is an invalid log unit, possible values are {1}
Explanation	The provided log unit is invalid. This can occur when the user specifies a log unit other than the supported ones.
Action	Please refer to the error message for the possible values.
INMCCE0011	{0} is invalid log unit value, possible values are {1}
Explanation	The provided log unit value is invalid. This can occur when the user specifies a log unit value other than the supported ones.
Action	Please refer to the error message for the possible values.
INMCCE0012	Purger unavailable for {0}
Explanation	No purger was found for the given log unit. This error can occur if an appropriate purger is not found/available for the given log unit.
Action	Please ensure the correct log units are provided in the configuration file.
INMCCE0013	Purging stopped for {0} as there is no write permission for export location {1}
Explanation	This error will occur when the user does not have the required write permission for the export location.
Action	Please provide required permissions before purging.

INMCCE0014	Insufficient disk space in {0}. Required space {1}. Available space {2}.
Explanation	The specified export location does not contain enough space for the exported logs. Please refer to the error message for the available and required space.
Action	Please choose a different export location.
INMCCE0015	Purging Failed. Following error occurred {0}.
Explanation	Purging failed for the log unit mentioned in the error message. Some failures may happen because of network time out and similar problems.
Action	Please try again later or contact the administrator for assistance.
INMCCE0016	Unable to archive the export directory {0}
Explanation	The archiving of the exported logs failed. This may happen because of files being accessed by an other application.
Action	Please close the other application and try again.
INMCCE0017	Unable to create the export directory {0}
Explanation	This error can occur when the user does not have the required write permission for the export location or the export location is invalid.
Action	Please provide required permissions before purging or make sure the export location is valid.
INMCCE0018	Command {0} is not supported by CentraSite command line tool
Explanation	The displayed command is invalid. This can occur when the user specifies a command other than the supported ones. For example, to purge logs, you should specify -command purge_logs.
Action	Please refer to the documentation for the list of supported commands and their usage.
INMCCE0019	castUri option is mandatory for the command {1}
Explanation	The castUri option is required for the specified commands.
Action	Please specify the cast URI in the -castUri option.
INMCCE0020	CentraSite Application Server Object (CAST) already registered in CentraSite with the specified castUri {0}
Explanation	The CAST will be identified using the host present in castUri option, and CentraSite already contains a CAST registered with the specified host.
Action	Specify a different value in the castUri option or de-register the existing CAST and register it again. A CAST can be de-registered using the deregister_cast command.

INMCCE0021	{0} and {1} both present in configuration for log unit {2}
Explanation	The tags Until and OlderThan are both present in the configuration file.
Action	Please use only one of the given tags in the configuration file. For more information, please refer to the Administration guide.
INMCCE0022	Unable to obtain policy query manager. Cause: {0}
Explanation	It was not possible to obtain the policy query manager.
Action	Verify your installation or contact the administrator.
INMCCE0023	Exception occurred during restore operation. Cause: {0}.
Explanation	An exception occurred during the restore operation.
Action	Please check the exception message for more details.
INMCCE0024	Archive seal error. Invalid start/end date entries in the archive seal properties for the Archive file {0} located in {1}.
Explanation	An archive seal error occurred. There are invalid start/end date entries in the archive seal properties.
Action	Please verify the seal properties file for correctness.
INMCCE0025	Error creating archive seal file. Cause {0}.
Explanation	An error occurred while creating the archive seal file.
Action	Please check the error message for more details.
INMCCE0026	Command option {0} missing
Explanation	The specified command requires a command option.
Action	See the usage information for the correct command syntax.
INMCCE0028	Domain {0} not found
Explanation	The domain to be processed does not exist.
Action	Correct the specified domain name.

INMCCE0029	Domain {0} already exist
Explanation	A domain entry with the specified name is already present.
Action	Correct the specified domain name.
INMCCE0030	Error processing configuration file: {0}
Explanation	The configuration file does not contain a valid domain entry.
Action	Correct the domain entry in the configuration file.
INMCCE0031	Error deleting domain entry: {0}
Explanation	The specified domain entry could not be deleted.
Action	Contact your support center.
INMCCE0039	{0} is not a LDAP domain
Explanation	The validate command is only supported for LDAP domains.
Action	Specify an LDAP domain for validating an authentication configuration.
INMCCE0040	LDAP basic configuration validation error
Explanation	The basic LDAP configuration is invalid.
Action	Check the basic settings for the specified domain.
INMCCE0041	LDAP user login validation error
Explanation	The user could not log on with supplied user name and password.
Action	Check if the user name and password were specified correctly. Check the settings for the specified domain.
INMCCE0042	LDAP user properties validation error
Explanation	The user properties configuration is invalid.
Action	Check the user properties settings for the specified domain.
INMCCE0043	LDAP group resolution validation error
Explanation	The group resolution configuration is invalid.
Action	Check the group resolution settings for the specified domain.

INMCCE0046	CS Admin user {0} not created
Explanation	An error occurred while attempting to create a user with the CentraSite Administrator role.
Action	See the additional information provided to find the reason.
INMCCE0047	CS Admin user {0} ({1}) not created
Explanation	An error occurred while attempting to create a user with the CentraSite Administrator role.
Action	See the additional information provided to find the reason.
INMCCE0053	{0} No Users found!
Explanation	Searched users are not found
Action	user has to retry the search
INMCCE0054	{0} No group properties found!
Explanation	The group properties entered for the configuration are not correct.
Action	Correct the group properties.
INMCCE0055	Can't get group properties. {0}
Explanation	{0} --> error message from the LDAP
Action	re-configuration needs to be done
INMCCE0056	cannot read user property {0}
Explanation	{0} --> user property configured
Action	Re-configure the user properties
INMCCE0058	cannot read user property {0}
Explanation	{0} --> user property
Action	Re-configure the property
INMCCE0059	{0} No user properties found!
Explanation	{0} --> status warning message
Action	Re-configure the user properties

INMCCE0060	Cannot contact the server. {0}
Explanation	An attempt to connect to the server failed with the error message {0}.
Action	Re-configure the server properties.
INMCCE0066	Unable to connect to socket!
Explanation	There was a problem while connecting to the socket.
Action	Re-configure the connection.
INMCCE0067	The old file is not deleted
Explanation	An SSX trace file already exists and should be deleted.
Action	The SSX trace file needs to be deleted manually.
INMCCE0068	Unable to listen to port
Explanation	It was not possible to connect to the given port.
Action	Re-configure the port.
INMCCE0088	Cannot write to log4j.
Explanation	A message could not be written to the log4j log file.
Action	Check your log4j configuration.
INMCCE0089	Cannot write in the {0}
Explanation	A message could not be written to the SSX trace file {0}.
Action	Check your trace file configuration.
INMCCE0090	cannot connect to database - possibly password wrong?
Explanation	An error was detected while trying to connect to the database.
Action	Check that you entered the correct password.
INMCCE0091	Database 'CentraSite' not running
Explanation	The database 'CentraSite' is not running.
Action	Start the CentraSite database.

INMCCE0092	{0} User authentication for "{0}" failed!
Explanation	{0} --> State error {1} --> user name
Action	Re-enter the user authentication
INMCCE0093	The user repository cannot be created with parameters: {0}
Explanation	The user repository cannot be created with the given parameters.
Action	Re-configure the repository.
INMCCE0094	{0} open SSXRepository - {1}
Explanation	The SSX repository is not connected. The state error is {0} and the error message is {1}.
Action	Re-configure the connection to the repository.
INMCCE0096	Can't get users {0}
Explanation	The user mapping does not match any entry on the LDAP server.
Action	Provide a user mapping that matches an entry in LDAP.
INMCCE0100	Can't get member of group {0}
Explanation	An incorrect group ID was specified.
Action	Provide a correct group ID.
INMCCE0103	Can't get groups for user {0}
Explanation	No groups were found for the given user.
Action	Provide a proper group resolution.
INMCCE0105	db 'CentraSite' not running
Explanation	The database "CentraSite" is not currently active.
Action	Restart the "CentraSite" database.
INMCCE0111	Failed to obtain the user {0} folder from CentraSite
Explanation	Could not obtain the folder for the user with given name. The username is used to store a search definition in CentraSite.
Action	Make sure the user is registered in CentraSite.

INMCCE0112	Search definition {0} already exists in CentraSite
Explanation	An attempt was made to overwrite the existing report search definition.
Action	Make sure that you publish a new module or pass the argument -overwrite option_value.
INMCCE0113	File {0} not found
Explanation	The file {0} was not found in the folder.
Action	Check the availability of the file in the specified path.
INMCCE0114	Retrieving the namespace from {0} failed because the namespace is null.
Explanation	Cannot retrieve the namespace in the search definition since the namespace is null.
Action	Make sure a valid namespace is declared in the search definition.
INMCCE0115	Namespace does not match with the module
Explanation	The specified namespace does not match with the new module and search definition.
Action	Make sure that the namespace matches with the new module and search definition.
INMCCE0116	Error loading the module
Explanation	Failed to load the new module into CentraSite.
Action	Make sure the module format is correct.
INMCCE0117	The namespace {0} is already used by a module in CentraSite
Explanation	The specified namespace {0} was already used by a module. The module namespace should be unique in CentraSite.
Action	Define a new module namespace or use -overwrite TRUE to overwrite the existing module with this new namespace.
INMCCE0118	The user you specified does not exist
Explanation	The user you specified is not a known user.
Action	Specify the name of a known user.

INMCCE0119	The number of Arguments for the command SetAsymmetricBindingConfigurations is not sufficient
Explanation	The number of Arguments for the command SetAsymmetricBindingConfigurations is not sufficient
Action	Please provide proper number of Arguments
INMCCE0120	Additional arguments provided to the Command SetAsymmetricBindingConfiguration
Explanation	Additional arguments provided to the Command SetAsymmetricBindingConfiguration
Action	Please delete the unwanted arguments
INMCCE0121	Required parameters missing
Explanation	At least one of the parameters among InitiatorTokenInclusion, RecipientTokenInclusion, AlgorithmSuite and Layout required for the command.
Action	Please Add one of InitiatorTokenInclusion, RecipientTokenInclusion, AlgorithmSuite or Layout
INMCCE0122	Invalid values provided for InitiatorTokenInclusion
Explanation	InitiatorTokenInclusion value can only be one among Always, AlwaysToRecipient, AlwaysToInitiator, Once, Never
Action	Please provide one value among Always, AlwaysToRecipient, AlwaysToInitiator, Once, Never
INMCCE0123	Invalid values provided for RecipientTokenInclusion
Explanation	RecipientTokenInclusion value can be one among AlwaysToRecipient, Always, AlwaysToInitiator, Once, Never
Action	Please provide one among AlwaysToRecipient, Always, AlwaysToInitiator, Once, Never
INMCCE0124	Invalid values provided for AlgorithmSuite
Explanation	Invalid values provided for AlgorithmSuite
Action	Please provide a valid value

INMCCE0125	Invalid value provided for Layout
Explanation	Layout can have one value among Strict,Lax,LaxTsFirst,LaxTsLast
Action	Please provide one value among Strict,Lax,LaxTsFirst,LaxTsLast
INMCCE0126	Exception writing the values to the repository .Reason : {0}
Explanation	{0}
Action	{0}
INMCCE0127	Exception while reading from the repository .Reason : {0}
Explanation	{0}
Action	{0}
INMCCE0129	The target for federation cannot be configured in the file at {0}
Explanation	While trying to configure a target for federation, the file at location {0} will be modified to include the configuration. This error occurs if the "multicast" element cannot be found in the file.
Action	Check to ensure that the "multicast" element is available after "from" in the file {0}.
INMCCE0130	The mandatory parameter(s), {0} is/are not specified for the command
Explanation	The command requires some parameters for proper execution and they are not specified. Without these mandatory parameters, the execution cannot proceed.
Action	Provide the parameters needed for the command execution. If you don't know the command format, just provide the command name alone to get the usage for the command.
INMCCE0131	The provided configFile {0} is not configured with the {1} element.
Explanation	While parsing the XML configFile, {0}, the parser cannot obtain the {1} element which is needed for the command execution.
Action	Check the configFile {0} to see if the {1} element is configured. If it is not, provide the necessary details.
INMCCE0132	The given federation id {0} does not have any target associated with it.
Explanation	The provided ID {0} is not configured to have a federation target.
Action	Use show_uddi_federation to determine the list of configured federation targets and identifiers.

INMCCE0139	An Internal Error occurred
Explanation	An Internal Error occurred
Action	An Internal Error occurred
INMCCE0140	Invalid Credentials
Explanation	Invalid Credentials provided
Action	Please provide valid credentials
INMCCE0142	Invalid Virtual Service name
Explanation	The specified virtual service name is invalid.
Action	Enter a valid virtual service name.
INMCCE0144	Invalid Target name
Explanation	The target is not created or is invalid for virtual services to be deployed, undeployed or redeployed.
Action	Please provide a valid target name.
INMCCE0152	Command execution failed. Parameter value cannot be null or empty.
Explanation	A command parameter value was not entered.
Action	Before you execute a command, make sure that you set a value for every parameter in the command.
INMCCE0153	Command execution failed. Description of the path already exists.
Explanation	Description of the command path already exists.
Action	Before you execute a command, make sure that you set a valid command path.
INMCCE0154	Command execution failed. Combination of the path already exists.
Explanation	Combination of the command path already exists.
Action	Before you execute a command, make sure that you set a valid command combination.
INMCCE0155	Command execution failed. The name for command token is not valid.
Explanation	You have entered an invalid name for the command token.
Action	Enter a valid name for the command token.

INMCCE0156	Command execution failed. The input for command token is not valid.
Explanation	You have entered invalid input for the command token.
Action	Enter a valid input for the command token.
INMCCE0157	Command execution failed. Path already exists for the tokens: {0}
Explanation	The path already exists for the command tokens: {0}.
Action	Before you execute a command, make sure that you set a valid path for the tokens.
INMCCE0158	Command execution failed. Parameter value cannot be null or empty.
Explanation	A command parameter value was not entered.
Action	Before you execute a command, make sure that you set a value for every parameter in the command.
INMCCE0159	Command execution failed. Token or parameter value cannot be null or empty.
Explanation	A command token or parameter value was not entered.
Action	Before you execute a command, make sure that you set a value for every token and parameter in the command.
INMCCE0160	Command execution failed. Combination of the command tokens {} already exists.
Explanation	An attempt was made to specify the same token that is already present in the command.
Action	Before you execute a command, make sure that you set a valid token in the command.
INMCCE0161	Parameter {0} should not empty.
Explanation	The '{0}' parameter is mandatory.
Action	Enter a value for the {0} parameter.
INMCCE0162	Check the length of the command help.
Explanation	The command help text you have entered does not meet the minimum requirement of {0} characters.
Action	Correct the help text appropriately.

INMCCE0163	Command execution failed. Unable to join null or empty strings, or a single string.
Explanation	The combination of a null and empty string, or a null and single string is not valid.
Action	Before you execute a command, make sure that you set valid combination of strings in the command.
INMCCE0164	Configuration property {0} cannot be empty.
Explanation	The configuration property '{0}' was not specified.
Action	Specify the property {0}.
INMCCE0165	Command execution failed. Invalid value {0} for configuration parameter {1}.
Explanation	The value {0} for configuration parameter {1} is not valid.
Action	Before you execute a command, make sure that you set a valid value for parameter {1} in the command.
INMCCI0027	Domain {0} not found
Explanation	The domain to be processed does not exist.
Action	Correct the specified domain name.
INMCCI0032	Domain {0} successfully added
Explanation	The domain entry of the authentication configuration was created.
Action	No action required.
INMCCI0033	Domain {0} successfully removed
Explanation	The domain entry of the authentication configuration was removed.
Action	No action required.
INMCCI0034	Validating LDAP domain {0}
Explanation	The validate command has started.
Action	No action required.
INMCCI0035	LDAP basic configuration validated successfully
Explanation	The basic LDAP configuration is valid.
Action	No action required.

INMCCI0036	LDAP user login validated successfully
Explanation	The user could log on with supplied user name and password.
Action	No action required.
INMCCI0037	LDAP user properties validated successfully
Explanation	The user properties configuration is valid.
Action	No action required.
INMCCI0038	LDAP group resolution validated successfully
Explanation	The group resolution settings are valid.
Action	No action required.
INMCCI0044	Creating CS Admin user {0} for domain {1}
Explanation	The processing for creating a user with the CentraSite Administrator role has started.
Action	No action required.
INMCCI0045	CS Admin user {0} created
Explanation	A user with the CentraSite Administrator role has been successfully created.
Action	No action required.
INMCCI0048	Do you want to see the LDAP search trace? {0}:
Explanation	This prompt asks you whether or not you want to see the LDAP search results.
Action	Type Y (for yes) or N (for no) as appropriate, then press Enter. The default is N.
INMCCI0049	User elements found: {0}. Do you want to see them?
Explanation	The LDAP search found the given number of users.
Action	Type Y to see the results, otherwise N.
INMCCI0050	Do you want to see all the users? (Y/N) [N]:
Explanation	This prompt asks you whether or not to display all of the users.
Action	Type Y (for yes) or N (for no) as appropriate, then press Enter. The default is N.

INMCCI0051	User with filter: {0}
Explanation	User search filter
Action	search filter needs to be entered
INMCCI0052	{0} The following group was found:
Explanation	{0} --> ok
Action	No action
INMCCI0057	Can't get user properties. {0}
Explanation	{0} --> error message
Action	re-configure the user properties
INMCCI0061	{0} User authenticated successfully
Explanation	The user authentication was successful. The returned status is {0}.
Action	No action required.
INMCCI0062	Trying to ping the server now...
Explanation	An attempt is being made to connect to the server.
Action	No action required.
INMCCI0063	Is the connection to the server protected with SSL? (Y/N) [N]:
Explanation	This prompt asks you whether or not the LDAP connection to the server is protected with SSL.
Action	Type Y (for yes) or N (for no) as appropriate, then press Enter. The default is N.
INMCCI0064	Do you want use LDAP Technical User? (Y/N) [N]:
Explanation	The prompt asks whether or not you wish to use the LDAP Technical User.
Action	Type Y (for yes) or N (for no) as required. The default is N.
INMCCI0065	Provide the LDAP Technical User credentials file:
Explanation	The credentials file of the the LDAP Technical User needs to be given as input.
Action	Specify the credentials file.

INMCCI0069	Direct binding using the constructed DN was successful.
Explanation	A direct binding using the constructed DN was successful.
Action	No action required.
INMCCI0070	Do you want use LDAP Technical User Key file?
Explanation	User key file needs to be given or not
Action	File path will be given as input
INMCCI0071	Trying to connect to LDAP at: {0};{1}
Explanation	An attempt is being made to connect to LDAP at host {0} and port {1}.
Action	No action required.
INMCCI0072	To test the connection, please provide the credentials of a valid LDAP user.
Explanation	To test the connection, the credentials of a valid LDAP user are required.
Action	Provide the credentials of a valid LDAP user.
INMCCI0073	Do you want to keep this default mapping? {0}:
Explanation	The prompt asks you to specify whether or not you want to keep the default mapping.
Action	Reply Y (for yes) or N (for no). The default value is Y.
INMCCI0074	Do you want to save the configuration to CentraSite? (Y/N) [N]:
Explanation	The prompt asks you whether or not to save the modified configuration to CentraSite.
Action	Reply Y (for yes) or N (for no). The default value is N.
INMCCI0075	To store the connection, please provide the credentials of a user with role "CentraSite Administrator".
Explanation	The connection can only be stored by a user with the role "CentraSite Administrator".
Action	Provide the credentials of a user with the role "CentraSite Administrator".
INMCCI0076	Repeat configuration step {0}, Continue, or End? (R/C/E) [C]:
Explanation	You can either repeat the given configuration step, continue to the next step, or end the processing.
Action	Type R, C or E to select the required option. The default is C.

INMCCI0077	Repeat configuration step {0} or End? (R/E) [R]:
Explanation	You can repeat the given configuration step or end the processing.
Action	Type R or E to select the required option. The default is R.
INMCCI0078	Check 1: LDAP Host >> PLEASE WAIT...
Explanation	This message is shown when the configuration of the LDAP host is being checked.
Action	No action required.
INMCCI0079	Check 2: LDAP User >> PLEASE WAIT...
Explanation	This message is shown when the configuration of the LDAP user is being checked.
Action	No action required.
INMCCI0080	Check 3: LDAP User Authentication >> PLEASE WAIT...
Explanation	This message is shown when the configuration of the LDAP user authentication is being checked.
Action	No action required.
INMCCI0081	Check 3: LDAP User Properties >> PLEASE WAIT...
Explanation	This message is shown when the configuration of the LDAP user properties is being checked.
Action	No action required.
INMCCI0082	Check 4: LDAP User Search >> PLEASE WAIT...
Explanation	This message is shown when the configuration of the LDAP user search is being checked.
Action	No action required.
INMCCI0083	Check 5: LDAP Group >> PLEASE WAIT...
Explanation	This message is shown when the configuration of the LDAP group is being checked.
Action	No action required.

INMCCI0084	Check 6: LDAP Group Mapping >> PLEASE WAIT...
Explanation	This message is shown when the configuration of the LDAP group mapping is being checked.
Action	No action required.
INMCCI0085	Check 7: LDAP Group Search >> PLEASE WAIT...
Explanation	This message is shown when the configuration of the LDAP group search is being checked.
Action	No action required.
INMCCI0086	Check 8: LDAP Group Resolution Host >> PLEASE WAIT...
Explanation	This message is shown when the configuration of the LDAP group resolution host is being checked.
Action	No action required.
INMCCI0087	Check 9: Displaying and saving configuration in CentraSite >> PLEASE WAIT...
Explanation	This message is shown when the checked LDAP configuration is being saved in CentraSite.
Action	No action required.
INMCCI0095	Do you want to see the complete trace? {0} :
Explanation	The prompt asks you whether or not you want to see the complete trace.
Action	Type Y (yes) or N (no) as required. The default is N.
INMCCI0097	Group elements found: {0} . Do you want to see them?
Explanation	This is a confirmation message indicating that group elements have been found.
Action	Reply Yes if you want to see the group elements.
INMCCI0098	Do you want to see all groups? {0} :
Explanation	This prompt asks you if you want to see all groups.
Action	Reply Yes if you want to see the groups.

INMCCI0099	Groups with filter: {0}
Explanation	This is a confirmation message indicating that groups have been found with the filter.
Action	No action required.
INMCCI0101	Groups for user found: {0} Do you want to see them?
Explanation	Groups were found for the given user.
Action	Reply Yes if you want to see the groups that were found.
INMCCI0106	Please provide your custom mapping (press Enter if unmapped)
Explanation	This prompt asks you to provide your custom mapping.
Action	Provide your custom mapping.
INMCCI0107	Do you want to use the LDAP Technical User {0}:
Explanation	This prompt asks you whether you want to use the LDAP Technical User (LDAP Principal) to access the LDAP user repository. If you reply Y, all authentication requests sent to the LDAP server will be made using this user. If you reply N, the client has to send its own credentials to LDAP to access a user record.
Action	Type Y (for yes) or N (for no) as appropriate, then press Enter. The default is N.
INMCCI0108	Provide the LDAP Technical User credentials file.
Explanation	This prompt asks you to provide the LDAP Technical User credentials file.
Action	Provide the LDAP Technical User credentials file.
INMCCI0109	Provide the LDAP Technical User Key file
Explanation	This prompt asks you to provide the LDAP Technical User Key file.
Action	Provide the LDAP Technical User key file.
INMCCI0110	Trying to connect to LDAP at: {0}
Explanation	An attempt is being made to connect to the LDAP Server with the given host name and port.
Action	No action required.

INMCCI0133	The target identified by "{0}" has been removed from the configured federation targets.
Explanation	The target identified by "{0}" has been removed from the configured federation targets during the execution of the command.
Action	No action required.
INMCCI0134	A target is already associated with the given federation id "{0}".
Explanation	The provided federation identifier already has a target associated with it.
Action	To obtain more details about the target associated with ID "{0}", execute the command <code>show_uddi_federation</code> .
INMCCI0135	Do you want to update/overwrite the target at {0} ? {1} :
Explanation	While running the <code>add_uddi_federation</code> command with the ID {0}, it may be already configured with another target. Then you should choose whether you want to update the target or not.
Action	Enter either y (Yes) to update/overwrite the target, or n (No) to do no modification. The default is y (Yes).
INMCCI0136	Not overwriting the current configuration. Please provide another federation identifier
Explanation	While executing the <code>add_uddi_federation</code> command, if an already existing identifier is provided, and you choose not to overwrite the target, then this message is displayed.
Action	You can provide a new identifier which does not already exist. To obtain the list of configured federation identifiers, execute the command <code>show_uddi_federation</code> .
INMCCI0137	Overwriting/updating the target identified by "{0}"
Explanation	While executing the command <code>add_uddi_federation</code> , if the provided federation identifier already exists, and you choose to overwrite/update the target, then you get this message.
Action	No action required.
INMCCI0138	A target has been added/updated with the federation identifier {0}
Explanation	This message is displayed if a target for federation has been successfully configured with the provided federation ID.
Action	No action required.

INMCCI0143	Number of targets configured for federation : {0}
Explanation	This message displays the number of targets configured for federation. {0} - Number of targets
Action	No action required.
INMCCI0145	Deployment succeeded
Explanation	The deployment succeeded.
Action	No action required.
INMCCI0147	There are no Consumer Applications to deploy.
Explanation	There are no consumer applications created in CentraSite to deploy.
Action	Create consumer applications in CentraSite to deploy to Mediator.
INMCCI0148	The XML configuration of the Federation target "{0}":
Explanation	The XML configuration of the federation target identified by {0} will be displayed in the console.
Action	No action required.
INMCCI0149	The XML configuration of the Federation target "{0}" has been written to file "{1}"
Explanation	This message informs that the XML configuration of the federation target identified by {0} has been written to the file located at {1}.
Action	No action required.
INMCCI0150	The XML log configuration can be seen below:
Explanation	The XML log configuration will be displayed to the console.
Action	No action required.
INMCCI0151	The XML log configuration has been written to the file "{0}"
Explanation	This message informs that the XML log configuration has been written to the file located at {0}.
Action	No action required.

INMCCW0004	Default Organization is not present in CentraSite. Hence UDDI configurations cannot be saved.
Explanation	UDDI Configurations for CentraSite will be stored in "Default Organization". CentraSiteCommand is not able to find the "Default Organization" in CentraSite and hence cannot store the UDDI configurations.
Action	Make sure the user provided to execute the command has permission to update the "Default Organization".
INMCCW0005	No CentraSite Application Server Tier (CAST) found in CentraSite with specified cast URI {0}. Please specify fully qualified host name in -casturi option.
Explanation	UDDI configurations for a CAST will be stored in an Application Server object. The object will have the host and port details. This object is required to store the local configurations for the CAST. CentraSiteCommand is not able to find the ApplicationServer object with the host specified in the cast URI option.
Action	Please make sure the value specified for the option cast URI is valid. Please specify the host as a fully qualified domain name in the cast URI option.
INMCCW0104	unknown host
Explanation	The host name provided is not the name of a known host.
Action	Provide a proper host name.
INMCCW0128	An error occurred while trying to close a resource - {0}
Explanation	Occasionally an error might be encountered while trying to close open connections, streams, etc., This is just a warning that an error was encountered and can be ignored.
Action	Make sure that the resource in question is not opened and/or modified by another program/application.
INMCCW0146	Deployment failed
Explanation	The deployment failed.
Action	Check related messages to find the reason why the deployment failed.
INMCLE0013	Caught an exception while retrieving the configurator instance.
Explanation	This is an internal error. It is probably because of an invalid data in the configuration file.
Action	Verify that the data in configuration file are valid.

INMCLE0014	System is unable to retrieve value for {0}.
Explanation	This is an internal error. It is probably because of an invalid data in the configuration file.
Action	Verify that the data in configuration file are valid.
INMCLE0015	Invalid path {0}.
Explanation	You have entered an invalid path.
Action	Enter a valid path.
INMCLE0017	Failed to check whether or not property of {0} is read-only.
Explanation	Could not check whether or not the property of the given path {0} is read-only. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0018	Caught an exception while retrieving the configuration file of type {0}.
Explanation	This is an internal error. It is probably because of an invalid data in the configuration file.
Action	Verify that the data in configuration file are valid.
INMCLE0019	Caught an exception while trying to save the configuration file of type {0}.
Explanation	This is an internal error. It is probably because of an invalid data in the configuration file.
Action	Verify that the data in configuration file are valid.
INMCLE0020	Failed to remove {0}.
Explanation	This is an internal error. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0021	Caught an exception while trying to get the configuration file URL for type {0}.
Explanation	Could not get configuration file URL for type {0}, possibly because of an invalid data in the configuration file.
Action	Verify that the data in configuration file are valid.

INMCLE0022	Path or property value is empty.
Explanation	You have entered an empty path or property value.
Action	Enter a valid path or property value.
INMCLE0023	Failed to set configuration(s) for the path(s), {0}
Explanation	Unable to set configuration(s) for the path(s). This is probably because of the following reasons: 1) configuration file is modified 2) failed to save the configuration file.
Action	Check to make sure that the configuration in a higher level is not already protected. Else, check the stack trace for detailed information.
INMCLE0024	Failed to setProtectAll.
Explanation	Unable to set ProtectAll configuration. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0025	Failed to getAllItems.
Explanation	Unable to get one or more configuration items. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0026	Unable to construct ActivityMenuItem for id {0}.
Explanation	Could not construct ActivityMenuItem for the given id {0}, possibly because the XPath of the ActivityMenuItem is invalid.
Action	Verify that the XPath of the ActivityMenuItem is valid.
INMCLE0027	Unable to construct activity for id {0}.
Explanation	Could not construct activity for the given id {0}, possibly because the XPath of the activity is invalid.
Action	Verify that the XPath of the activity is valid.
INMCLE0028	Unable to construct ActivityMenuItem for activity {0}.
Explanation	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
Action	Check to make sure that the XPath of the ActivityMenuItem and Activity is correct and the corresponding Activity could be created.

INMCLE0029	Failed to instantiate class {0}.
Explanation	Could not instantiate the implementation class {0}, possibly because the class does not follow a valid syntax.
Action	Verify that the implementation class follows a valid syntax. Refer to the documentation reference for Activity Implementation class.
INMCLE0030	Unable to find activity entry for id {0}.
Explanation	Could not find an activity entry for the given id {0}, possibly because the id is invalid.
Action	Verify that the given activity id is correct.
INMCLE0031	Unable to construct an ActivityMenu using activities.
Explanation	Could not construct an ActivityMenu using the given activities. It is probably because, the activities do not exist.
Action	Verify that the activities exist. If the problem persists, contact the CentraSite administrator.
INMCLE0033	Failed to remove ActivityMenuItems.
Explanation	Could not remove the ActivityMenuItems from given configuration file. It is possibly because of the following reasons: 1) XPath to remove the ActivityMenuItem is invalid. 2) ActivityMenuItem does not exist.
Action	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
INMCLE0034	Failed to save ActivityMenuItems.
Explanation	Could not save the ActivityMenuItems from given configuration file. It is possibly because of the following reasons: 1) XPath to save the ActivityMenuItem is invalid. 2) ActivityMenuItem does not exist.
Action	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
INMCLE0035	User has not passed the CentraSite connection object. For a valid diagnostics configuration, CentraSite connection object is mandatory.
Explanation	User has not passed the CentraSite connection object, which is mandatory for a valid diagnostics configuration.
Action	Enter a valid CentraSite connection object.

INMCLE0036	Email address is empty,
Explanation	You have not entered the email address for diagnostics configuration. An email address is mandatory to send the diagnostic information.
Action	Enter a valid email address.
INMCLE0037	Email subject and template are empty.
Explanation	You have not entered the email subject and template for diagnostics configuration. An email template is mandatory to send the diagnostic information. Refer to the CentraSite online documentation's section "Message Handling and Diagnostics".
Action	Enter the email subject and a valid template.
INMCLE0038	Failed to get all activities.
Explanation	Could not get all the activities, possibly because the activity classes are not set in the classpath.
Action	Verify that the activity classes are set in the classpath. If the problem persists, contact the CentraSite administrator.
INMCLE0039	Failed to remove activity for given id {0}.
Explanation	Could not remove the activity for given id {0}, possibly because the activity id is invalid.
Action	Verify that the given activity id is valid.
INMCLE0040	Failed to show one or more activity menu items that are associated with activity menu.
Explanation	Could not display one or more activity menu items, possibly because the menu items are not associated with the activity menu.
Action	Verify that all the activity menu items are associated with activity menu.
INMCLE0041	Failed to populate diagnostic context.
Explanation	Could not populate the diagnostic context object, possibly because the CentraSite Connection object is incorrect.
Action	Verify that the CentraSite Connection object is correct.

INMCLE0042	Invalid CentraSite connection URL {0}.
Explanation	You have entered an invalid CentraSite Connection URL.
Action	Enter a valid CentraSite Connection URL.
INMCLE0043	User has not passed CLLEException object. For a valid diagnostics configuration, CLLEException object is mandatory.
Explanation	User has not passed the CLLEException object which is mandatory for the diagnostics configuration.
Action	Enter a valid CLLEException object.
INMCLE0044	Unable to fetch email template from repository {0}.
Explanation	Could not fetch the email template from given repository {0}, possibly because of the following reasons: 1) email template does not exists 2) repository URL is invalid.
Action	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
INMCLE0045	Error loading implementation class for ActivityManager.
Explanation	An unexpected error occurred while trying to load the implementation class for given ActivityManager. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0046	Error loading diagnosticHandler implementation class.
Explanation	An unexpected error occurred while trying to load the diagnosticHandler implementation class. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0048	Failed to instantiate class {0}.
Explanation	Could not instantiate the given class {0}, possibly because of the following reasons: 1) class file does not exist 2) classpath is incorrect.
Action	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.

INMCLE0049	Failed to initialize {0}.
Explanation	Could not initialize the given component {0}.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0050	Failed to get CentraSite registry object property {0}.
Explanation	Could not get the CentraSite registry object property. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0051	Failed to set registry object property {0}.
Explanation	Could not set the CentraSite registry object property. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0052	Failed to save CentraSite object {0}.
Explanation	An error occurred while trying to save CentraSite model object. Possible reasons: {1}
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0053	Failed to delete CentraSite object {0}.
Explanation	Could not delete the CentraSite object. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0054	Failed to get CentraSite object for id {0}.
Explanation	Could not get CentraSite object for the given id {0}, possibly because the object id is invalid.
Action	Verify that the object id is valid.
INMCLE0055	Failed to create CentraSite object {0}.
Explanation	You cannot create the CentraSite object {0}, possibly because of the following reasons: 1) insufficient privileges to create the object 2) object type is invalid.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.

INMCLE0056	Failed to delete CentraSite object.
Explanation	You cannot delete the CentraSite object {0}, possibly because you do not have the required permission to delete the object.
Action	Verify that you have the required permission to delete the CentraSite object. Contact your administrator and request permission if necessary and try again.
INMCLE0057	Unable to get list of CentraSite objects: {0}.
Explanation	You cannot retrieve the following list of CentraSite objects: {0}. It is possibly because you do not have the required permission to retrieve the objects.
Action	Verify that you have the required permission to retrieve the given objects. Contact your administrator and request permission if necessary and try again.
INMCLE0058	Unable to save list of CentraSite objects: {0}
Explanation	You cannot save the following list of CentraSite objects: {0}. It is possibly because you do not have the required permission to save the objects.{0}
Action	Verify that you have the required permission to save the given objects. Contact your administrator and request permission if necessary and try again.
INMCLE0059	Unable to delete list of CentraSite objects:
Explanation	You cannot delete the following list of CentraSite objects: {0}. It is possibly because you do not have the required permission to delete the objects.
Action	Verify that you have the required permission to delete the given objects. Contact your administrator and request permission if necessary and try again.
INMCLE0060	Caught an unexpected exception while converting concept to CentraSiteObjectType.
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0061	Failed to populate ObjectType for given name {0}.
Explanation	Could not populate the ObjectType for display name {0}, possibly because the given display name is incorrect.
Action	Verify that the display name is correct.

INMCLE0063	Unsupported attribute {0} for object type {1}.
Explanation	This is an internal error. Cannot find the attribute {0} of the specified object type {1}.
Action	Check to make sure that the attribute {0} is present in the object type {1}.
INMCLE0064	Failed to fetch attributes for {0}.
Explanation	Could not fetch attributes for {0}, possibly because the object type {1} is invalid.
Action	Verify that the object type {1} is valid.
INMCLE0065	Unable to obtain value for attribute {0}.
Explanation	Could not obtain the value for attribute {0}. The cause is not immediately known.
Action	Verify integrity of the object and try later.
INMCLE0066	Unsupported method for attribute {0} of object type {1}.
Explanation	This method is not applicable for attribute {0} of object type {1}.
Action	Do not use this method for attribute {0} of object type {1}.
INMCLE0067	Error while initializing CentraSiteConnector {0}.
Explanation	Could not initialize the CentraSiteConnector {0}. It is probably because of the following reasons: 1) invalid class as CentraSite Connection Factory 2) invalid system property (com.softwareag.centrasite.common.connection.impl) for initializing.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.
INMCLE0068	Failed to create an ActivityMenuItem for id {0}.
Explanation	Could not create the ActivityMenuItem for above id, possibly because of the invalid configurations.
Action	Verify that the activity id and class name are configured properly.
INMCLE0069	Error when closing connection {0}.
Explanation	Error occurred when trying to close the underlying connection.
Action	Initialize before opening a connection.

INMCLE0070	Failed to log in {0}.
Explanation	Could not log in {0}, possibly because the login credentials are invalid.
Action	Enter valid login credentials.
INMCLE0071	Cannot instantiate CentraSiteConnector class {0}.
Explanation	Could not instantiate the CentraSiteConnector implementation class, possibly because the implementation class is invalid.
Action	Check to make sure that the CentraSiteConnector class is valid.
INMCLE0072	Error loading email template {0} {1}.
Explanation	Error when loading the admin and/or user email templates, possibly because the email template path is invalid.
Action	Verify that the email template path is valid.
INMCLE0073	Email address is empty.
Explanation	You have not entered an email address.
Action	Enter a valid email address.
INMCLE0074	Invalid attribute {0} {1}.
Explanation	The attribute {1} is not a valid {0} attribute.
Action	Check to make sure that the {1} attribute is valid.
INMCLE0075	Usage of {0} operation in object {1} is not supported.
Explanation	This operation is not supported on the given object {1}.
Action	Refer to the usage document for further information on the supported APIs.
INMCLE0076	Unable to obtain relationship details of attribute {0} to object type {1}.
Explanation	Could not obtain the relationship details of attribute {0} associated to the above object type {1}.
Action	Make sure that the attribute {0} is a valid relationship attribute for the object type {1}.

INMCLE0077	Failed to execute query {0}.
Explanation	Could not execute the query {0}, possibly because the query syntax is incorrect.
Action	Correct the query syntax.
INMCLE0078	Failed to execute query {0}.
Explanation	Could not execute the query {0}, possibly because the query syntax is incorrect.
Action	Correct the query syntax.
INMCLE0079	Failed to get objectTypeValue from given ObjectType.
Explanation	Could not get the objectTypeValue from ObjectType, possibly because the given ObjectType is invalid.
Action	Check to make sure that the given ObjectType is valid.
INMCLE0080	Failed to construct search query.
Explanation	Could not construct the search query. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0081	Caught an exception while getting iterator from CSOSearchResult.
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0082	Failed to get search result count.
Explanation	Could not get the number of results displayed on the Search Results page. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0083	Unable to fetch next object for id {0}.
Explanation	An unexpected exception occurred while trying to fetch the next object for above id.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0084	The configuration file is invalid; attribute {0} is mandatory for multi-valued elements.
Explanation	The required attribute for multi-valued elements is not specified in the XML configuration file.
Action	Before you save the configuration file, check to make sure that all the required attributes are specified.

INMCLE0085	The configuration file is invalid; attribute {0} is mandatory for multi-valued elements.
Explanation	The required attribute for multi-valued elements is not specified in the XML configuration file.
Action	Before you save the configuration file, check to make sure that all the required attributes are specified.
INMCLE0086	Failed to fetch common attribute {0}.
Explanation	Could not fetch the common attribute {0}, possibly because the attribute does not exist.
Action	Verify that the common attribute {0} is valid.
INMCLE0087	Caught an exception while trying to set value for attribute {0}.
Explanation	Could not set a value for attribute {0}. It is probably because of the following reasons: 1) attribute does not exist 2) attribute is read-only.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.
INMCLE0088	Failed to retrieve attribute {0}.
Explanation	Could not retrieve attribute {0}, possibly because the attribute does not exist.
Action	Verify that the attribute is valid.
INMCLE0089	{0} based search has null or empty value.
Explanation	Could not execute {0} based search, possibly because of a null or empty value in the search criteria.
Action	Check to make sure that the search criteria is valid.
INMCLE0090	Data type {0} in search criteria is invalid.
Explanation	The specified data type {0} in search criteria is not supported.
Action	Specify a valid data type. Refer to the CentraSite online documentation's section "Attribute Data Types" for a list of the supported data types.

INMCLE0091	The number of values provided in the search criteria does not match with the mandatory number allowed for the operator {0}.
Explanation	Every operator will support only the specified number of values. This error occurs when the number of values entered is less than or greater than the specified number.
Action	Refer to the CentraSite online documentation's section "Searching the CentraSite Catalog".
INMCLE0092	Failed to serialize search {0}.
Explanation	Could not serialize the above search, possibly because of invalid parameters in the search criteria.
Action	Check to make sure that the mandatory parameters are specified in search criteria.
INMCLE0093	Failed to create folder in WebDav.
Explanation	Could not create folder in the WebDav, possibly because you do not have the necessary permission to create a folder or intermediate folder in WebDav.
Action	Verify that you have the required permission to create a folder or intermediate folder in WebDav.
INMCLE0094	Failed to retrieve file from given URI {0}.
Explanation	Could not retrieve file from the above URI. It is probably because of the following reasons: 1) file does not exist in the given URI 2) insufficient permissions to read the file.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.
INMCLE0095	Search cannot be executed with given URI {0}.
Explanation	Could not execute a search with URI {0}, possibly because the given URI is invalid.
Action	Verify that the specified URI is valid. If the problem persists, contact the CentraSite administrator.
INMCLE0096	Failed to parse persisted search output {0}.
Explanation	Could not parse the search output, possibly because of an invalid XML syntax.
Action	Verify that the XML syntax is correct.

INMCLE0097	Failed to convert input {0} to bytes.
Explanation	Could not convert the given input {0} to bytes. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0098	Failed to read output.
Explanation	Failed to read the output, possibly because the input or output stream is closed.
Action	Make sure that the input or output stream is open.
INMCLE0099	Failed to initialize parser.
Explanation	Error: could not initialize parser. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0100	Failed to get search data stored in folder {0}.
Explanation	Could not get search data files that were stored in the above folder, possibly because you do not have insufficient permission to access the files.
Action	Verify that you have required permissions to access the data files.
INMCLE0101	Cannot instantiate class{0}.
Explanation	Could not instantiate the above class, possibly because the class is incorrect.
Action	Check to make sure that the implementation class is correct and follows a specified syntax. Refer to the documentation reference for Action Implementation class.
INMCLE0102	Failed to load actions from system configurations.
Explanation	Could not load specific actions from the system configuration file because of the following reasons: 1) class name for action is incorrect 2) action is not configured.
Action	Check to make sure that the class name for actions is correct and is configured in your system.xml file.
INMCLE0103	Unable to retrieve actions for null parameter.
Explanation	Internal error. It is possibly because you are trying to pass parameter with null value.
Action	Check if the parameter contains a null value.

INMCLE0104	Failed to get configurator {0}
Explanation	Could not get the above configurator, possibly because you do not have the required permissions.
Action	Verify that you have the required permission to get configurator. Contact your administrator and request permission if necessary and try again.
INMCLE0105	Failed to get owner from connection.
Explanation	Could not get the owner from connection, possibly because you do not have the required permissions.
Action	Verify that you have the required permission to get owner from connection. Contact your administrator and request permission if necessary and try again.
INMCLE0106	Login failed.
Explanation	Failed to login to CentraSite. It is possibly because of the following reasons: 1) incorrect CentraSite URL 2) invalid authentication credentials.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.
INMCLE0107	{0} object is null.
Explanation	Error: given object is null.
Action	Check to make sure that the given object is not null.
INMCLE0108	Failed to get an instance of component {0}.
Explanation	Could not get an instance of the above component. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0111	Failed to remove file {0} from WebDaV.
Explanation	Could not create a folder in WebDav. It is probably because of the following reasons: 1) file does not exist in WebDav 2) insufficient permission to remove a file from WebDav.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.

INMCLE0112	Failed to create a file in {0}.
Explanation	Could not create a file in {0}, possibly because the parent directory does not exist in the given location.
Action	Verify that parent directory exists in the given location.
INMCLE0113	Could not instantiate AccessControlElement.
Explanation	Unable to instantiate the AccessControlElement. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0114	Failed to find resource exists for given URL {0}.
Explanation	Could not find the file for given URL. It is probably because the file does not exist in the given URL.
Action	Check to make sure that the file exists in given URL.
INMCLE0115	Failed to purge older versions of CentraSite object.
Explanation	Could not purge older versions of the CentraSite object. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0116	Unable to version CentraSite object.
Explanation	Could not create a new version of the CentraSite object. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0117	Unable to obtain base type for {0}.
Explanation	Could not obtain the base type for {0}. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0118	Failed to retrieve profiles for {0}.
Explanation	Could not retrieve profiles for {0} because of the following reasons: 1) failure in retrieving profiles from type 2) insufficient permission for accessing the profiles.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.

INMCLE0119	Failed to retrieve information for profile {0}.
Explanation	Could not retrieve the information for profile. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0120	Failed to choose assets for {0}.
Explanation	Could not choose the assets for executing above action, possibly because the action is not in the 'initial' state.
Action	Verify that the action is in 'initial' state.
INMCLE0122	Failed to retrieve immediate allowed states.
Explanation	This is an unexpected exception. It is probably because the current lifecycle state does not have at least one immediate state.
Action	Check to make sure that the current lifecycle state has at least one immediate state.
INMCLE0123	Failed to retrieve immediate preferred state
Explanation	This is an unexpected exception. It is probably because the current lifecycle state does not have at least one immediate state.
Action	Check to make sure that the current lifecycle state has at least one immediate state.
INMCLE0124	Failed to retrieve current state.
Explanation	This is an unexpected exception. It is probably because the object is not associated with any of the lifecycle model.
Action	Check to make sure that the object type is associated with at least one lifecycle model.
INMCLE0125	Failed to retrieve pending state.
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact your system administrator.
INMCLE0126	Failed to identify if state of object is pending or not.
Explanation	Could not identify if state of the object is in pending or not. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact your system administrator.

INMCLE0127	Failed to get lifecycle model assigned types.
Explanation	Could not get the lifecycle model assigned types. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact your system administrator.
INMCLE0128	Failed to identify initial state of lifecycle model.
Explanation	Could not identify initial state of the lifecycle model. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact your system administrator.
INMCLE0129	Failed to get applicable states of lifecycle model.
Explanation	Could not get applicable states of the lifecycle model. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact your system administrator.
INMCLE0130	Failed to identify if given lifecycle model is global or not.
Explanation	Could not identify if the given lifecycle model belongs to the global category. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact your system administrator.
INMCLE0131	Mandatory parameters to identify applicable lifecycle models are empty.
Explanation	An attempt is made to pass one or more of the mandatory parameters (CentraSiteObjectType or Organization) empty.
Action	Enter valid value for the mandatory parameters.
INMCLE0132	Mandatory parameters to identify applicable lifecycle models are empty.
Explanation	An attempt is made to pass one or more of the mandatory parameters (Keyword, CentraSiteObjectType or Organization) empty.
Action	Enter valid value for the mandatory parameters.

INMCLE0133	setParameter value for a CSOSearch is empty.
Explanation	An attempt is made to pass an empty list of values for the setParameter of CSOSearch.
Action	Enter a valid list of values for the CSOSearch.
INMCLE0134	Invalid authentication credentials.
Explanation	You have entered invalid authentication credentials.
Action	Enter valid authentication credentials.
INMCLE0135	Folder {0} does not exist.
Explanation	The specified folder does not exist in WebDav.
Action	Create the folder in WebDav and try again.
INMCLE0136	Choose the CentraSite Object(s) to perform this action.
Explanation	You have not chosen the CentraSite Object(s) for performing this action.
Action	Choose the CentraSite Object(s) to perform this action.
INMCLE0137	Failed to perform {0} on multiple CentraSite objects.
Explanation	You cannot perform {0} on multiple CentraSite objects at a time.
Action	Ensure you choose only one CentraSite object for performing {0}.
INMCLE0138	Failed to check if {0} is applicable or not.
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0139	Failed to perform {0} on specified CentraSite object(s).
Explanation	Could not perform {0} on the specified CentraSite object(s) due to one or more of the following reasons: (1) insufficient permission (2) CentraSite object is in 'Pending' state (3) CentraSite object is locked for editing by another user.
Action	Check for the above possible reasons and execute again. Else, contact the CentraSite administrator.

INMCLE0140	Failed to verify if current user has Edit permission on {0}.
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0141	You are trying to modify an outdated asset.
Explanation	You are trying to modify an asset which is outdated.
Action	Before you start to edit an asset, refresh the details page.
INMCLE0142	Failed to verify if user has Move permission on CentraSite object.
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0143	Failed to cancel {0}.
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0144	Error loading saved search with name {0}.
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	If the problem persists, contact our technical support.
INMCLE0145	{0} is required for CSOSearch.
Explanation	Mandatory property {0} for executing a CSOSearch is missing.
Action	Check to make sure that the mandatory property is specified.
INMCLE0146	Mismatch of attribute {0} specified in {1} with {2}.
Explanation	The attribute in {1} does not match with the given {2}.
Action	Remove the faulty {1} and execute again.
INMCLE0147	Caught an exception while getting profile id for {0}.
Explanation	Could not retrieve the profile id for {0}. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0148	{0} with name {1} used in {2} does not exist.
Explanation	{0} with name {1} used in {2} does not exist.
Action	Contact the CentraSite administrator.
INMCLE0149	Object {0} is null.
Explanation	Could not get the object {0}.
Action	The object should be initialized before executing this operation.
INMCLE0150	Caught an exception while trying to fetch pending approval requests.
Explanation	Could not fetch pending approval requests for the logged in user. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0151	Caught an exception while trying to verify if the logged in user has CentraSite Administrator role.
Explanation	Could not verify if the logged in user has CentraSite Administrator role. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0152	Wrong usage of {0} method.
Explanation	Wrong usage of {0} method. This method is allowed only in the following scenarios: (1) if the action is in {1} state (2) before triggering the finishAllSteps() execution.
Action	Make sure that the method is used in one of the above scenarios. If the problem persists, contact the CentraSite administrator.
INMCLE0153	{0} execution without comments is invalid.
Explanation	{0} execution without comments is invalid. The approver has not specified his/her comments for {0}.
Action	Enter the comments for {0} using {1} API.
INMCLE0154	Failed to execute {0}.
Explanation	Could not execute {0}. The cause is not immediately known.
Action	Check the stack trace for detailed information.

INMCLE0155	Failed to execute {0}
Explanation	Could not execute {0} due to one or more of the following reasons: (1) {0} is not allowed at the time of execution (2) assets for {0} are in 'Completed' state (3) for a Revert action, the you should have the CentraSite administrator role (4) you do not have a pending approval flow to proceed with {0}.
Action	Check for the above possible reasons and execute again. Else, contact the CentraSite administrator.
INMCLE0157	Invalid state transition from {0} by invoking {1} operation.
Explanation	The state transition from {0} by invoking the {1} operation is not valid.
Action	See the Action Java API documentation for more details.
INMCLE0158	One or more assets you have selected is not the most recent version of the asset.
Explanation	One or more selected assets is not the most recent version of the asset. The New Version action does not apply to assets with intermediate version.
Action	Check to make sure that the selected assets for versioning are in their most recent version.
INMCLE0159	Failed to create new version assets.
Explanation	Error occured when trying to create new version assets. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0160	Caught an exception while invoking {0} operation.
Explanation	An unexpected exception occurred while trying to execute the {0} operation.
Action	Check the stack trace for detailed information.
INMCLE0161	Could not exclude a CentraSite object in {0} state from export. The object should be in "Export Preview" state.
Explanation	CentraSite object in a state other than "Export Preview" cannot be excluded from export. The CentraSite object in "Export Preview" state will only have the option to preview and modify the export list.
Action	Verify that the CentraSite object is in "Export Preview" state. Read the usage instructions of Export action before use.

INMCLE0162 **Could not obtain export archive of a CentraSite object in {0} state. The object should be in "Completed" state.**

Explanation You cannot obtain an export archive of the CentraSite object, if the object is in a state other than "Completed".

Action Verify that the CentraSite object is in "Completed" state. Read the usage instructions of Export action before use.

INMCLE0163 **Failed to execute Consume action.**

Explanation Could not execute a Consume action, possibly because of one or more of the following reasons: 1) username is invalid 2) password is invalid 3) connection URL is incorrect.

Action Check for the above possible reasons and execute again. Else, contact the CentraSite administrator.

INMCLE0164 **An action in {0} state will not have Export List viewable. The action should be in "Export Preview" state.**

Explanation You cannot view an export list if the action is in a state other than "Export Preview".

Action Verify that the action is in "Export Preview" state. Read the usage instructions of Export action before use.

INMCLE0165 **Failed to execute Consume action.**

Explanation {0} execution can fail due to one or more of the following reasons: (1) consumers are not selected (2) consumer requests are not registered.

Action Check for the above possible reasons and execute again. Else, contact the CentraSite administrator.

INMCLE0166 **CentraSiteObject type list is empty.**

Explanation You have not entered a CentraSiteObject type list.

Action Enter a valid CentraSiteObject type list.

INMCLE0167 **Invalid object {1} for object type {2}.**

Explanation The specified CentraSite object {1} does not belong to CentraSiteObject type {2}.

Action Enter a valid CentraSite object of type {2}.

INMCLE0168	Caught an exception while trying to convert CentraSite objects.
Explanation	This is an unexpected exception. This is probably because an attempt is made to convert RegistryObjects to CentraSiteObjects, and vice versa.
Action	Check the stack trace for detailed information.
INMCLE0169	Invalid value set for {0}. Expected value : {1} Current value : {2}.
Explanation	The specified values for search condition does not match with the expected value.
Action	See the CentraSite online documentation's section "Searching the CentraSite Catalog" for details.
INMCLE0170	Failed to verify if user {0} is watching asset {0}.
Explanation	Could not verify if the user {0} is watching the given asset. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0171	Invalid operator set for {0}. Current operator: {1}. Supported operators for {2} type are {3}.
Explanation	The specified operator for search does not match with the attribute's applicable operators.
Action	See the CentraSite online documentation's section "Searching the CentraSite Catalog" for details.
INMCLE0172	Failed to get existing lists.
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0173	List {0} does not exist.
Explanation	An attempt is made to pass the list {0} that is not available for the current user.
Action	Check to make sure that the list you pass for setExistingList(..) is available for the current user.
INMCLE0174	Wrong usage of Add to List action API.
Explanation	Incorrect usage of the Add to List action API. This problem occurs, when the '{0}' method is triggered with action in a state other than 'Show Available Lists'.
Action	Before you execute the {0} method, verify that the Add to List action is in 'Show Available Lists' state.

INMCLE0175	List to add selected assets is not set.
Explanation	List to add the selected set of assets is not set. Use the {0} method to set this list.
Action	Make sure that you use the {0} method to set the list to add selected assets.
INMCLE0176	Failed to execute {0}.
Explanation	{0} execution can fail for a number of reasons: (1) action is not allowed (2) action is not applicable at the time of execution (3) action is in 'Completed' state.
Action	Check for the above possible reasons and execute again. Else, contact the CentraSite administrator.
INMCLE0177	Failed to create a new list {0}.
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0178	Failed to add selected assets to the list.
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0179	Choose a document to attach to asset.
Explanation	The document to attach to the asset is not specified.
Action	Call the setDocument method before invoking the execute method in Attach Document action.
INMCLE0180	Failed to create {0}
Explanation	Failed to create resources or asset. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.
INMCLE0182	Data of type {0} is ignored.
Explanation	Data of the above type defined for a CSOPparameter is not supported.
Action	Use the supported data types for CSOPparameter. See the CentraSite online documentation's section "Searching the CentraSite Catalog" for details.

INMCLE0183	Current CSOSearch has unresolved parameters: {0}.
Explanation	Current CSOSearch holds parameters that have a null value.
Action	Enter values for the unresolved parameters.
INMCLE0184	Number of parameters defined in CSOSearch differs from parameters defined for the XQuery module.
Explanation	Number of Parameters defined in the XQuery: {0} Number of Parameters defined in the CSOSearch: {1}.
Action	Validate your CSOSearch against the XQuery module.
INMCLE0185	Missing parameters
Explanation	The XQuery module used by the current CSOSearch requires {0} parameters.
Action	Validate the CSOSearch definition against the XQuery module that is being used.
INMCLE0186	Cannot find Xquery module {1} in namespace {0}.
Explanation	Could not find or load the XQuery module({0}:{1}) used by CSOSearch.
Action	Load the module / correct the CSOSearch definition.
INMCLE0187	No CentraSite object is available for Export action.
Explanation	You have not chosen the CentraSite objects for Export action.
Action	Choose the CentraSite objects for Export action.
INMCLE0188	Configuration base directory is not set.
Explanation	The configuration base directory specified by the path "com.softwareag.centrasite.api.configuration.basedir" is not set.
Action	Set the configuration base directory correctly. See the CentraSite online documentation for more details.
INMCLE0189	Type {0} not valid for Attach Document action.
Explanation	Could not perform the Attach Document action on selected type {0}.
Action	Enter a valid file. If the problem persists, contact the CentraSite administrator.

INMCLE0190	Failed to attach given document.
Explanation	Could not attach the given document, possibly because the document is invalid.
Action	Enter a valid document.
INMCLE0191	CentraSite object {0} does not belong to any of the given types {1}.
Explanation	The specified CentraSite object {0} does not belong to any of the given types {1}. Only objects that belong to the given types {1} are applicable for the Consume action.
Action	Choose a CentraSite object that belongs to one of the types {1}.
INMCLE0192	Could not choose consumer object in current state {0}.
Explanation	You cannot choose a consumer object in the current state {0}. The object should be in state {1}.
Action	Make sure that the consumer is in state {1}. Read the usage instructions of Consume action before use.
INMCLE0193	List of consumers is empty.
Explanation	An attempt is made to add an empty list of consumers for the Consume action.
Action	Choose a valid list of consumers. Read the usage instructions of Consume action before use.
INMCLE0194	Error: Timeout - The Document Processor Thread timed out waiting for the required inputs.
Explanation	You have not entered the required inputs within the time that the Document Processor was prepared to wait.
Action	Enter the required inputs as soon as prompted.
INMCLE0195	Failed to process missing resources, {0}.
Explanation	Could not process because the following resources are missing: {0}.
Action	Check to make sure that the required resources are specified.
INMCLE0196	Failed to initialize AttachDocumentProcessorThread.
Explanation	This is an internal error. The cause is not immediately known.
Action	Check to make sure that the mandatory inputs are specified.

INMCLE0198	Failed to attach given document(s), Reason : {0}.
Explanation	An exception occurred while trying to attach the document(s). This is probably because of the following reasons: 1) document is invalid 2) network failure.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.
INMCLE0199	Failed to get applicable reports for object {0}.
Explanation	An unexpected exception occurred while trying to get applicable reports for {0}. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0200	Wrong usage of the View Report action API {0}.
Explanation	Incorrect usage of the View Report action API. This problem occurs, when the '{0}' method is triggered with action in a state other than '{1}'.
Action	Before you execute the '{0}' method, verify that the action is in '{1}' state.
INMCLE0201	Could not get selected report.
Explanation	Failed to get the selected report, possibly because the report is not implicitly set for retrieval.
Action	Use the 'setSelectedReport(..)' to set a report for this action.
INMCLE0202	Could not get URL of selected report {0}.
Explanation	An unexpected exception occurred while trying to get URL of the selected report {0}. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0203	Failed to execute {0}.
Explanation	You do not have permission to perform this action.
Action	Before executing {0} make sure that you have the 'Use the Reports UI' permission. Contact your CentraSite administrator and if necessary request access and then try again.

INMCLE0204	Failed to close Centrasite ResourceAccessManager.
Explanation	Caught an exception while trying to close the ResourceAccessManager. This is a system error.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.
INMCLE0206	Failed to export {0}.
Explanation	Could not export the asset (s). This is probably because of the following reasons: 1) mandatory input is missing 2) prerequisite not satisfied.
Action	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
INMCLE0207	Exception in Export Processor Thread
Explanation	Export Processor Thread caught an unhandled exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0208	Specify mandatory {0}s for performing operation {1}.
Explanation	To perform this operation you should set the mandatory inputs.
Action	Check to make sure that the mandatory inputs are specified.
INMCLE0209	List to remove the selected assets is not set.
Explanation	The list to remove the selected assets is not set. Use the {0} method to set this list.
Action	Make sure that you use the {0} method to set the list to remove the selected assets.
INMCLE0210	Caught an unexpected exception when setting notification options for user {0}.
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0211	Invalid file; specify a valid path to external file {0}.
Explanation	You have entered an invalid file path.
Action	Enter a valid file path.

INMCLE0212	Exception occurred when setting the specified email addresses for user {0}.
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0213	Exception occurred when adding the specified telephone number for user {0}.
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0214	Exception occurred when setting the specified name for user {0}.
Explanation	An unexpected exception occurred when trying to set one of the specified name (First Name, Middle Name or Last Name) for the user {0}.
Action	Check the stack trace for detailed information.
INMCLE0215	Parameter passed for {0} is null.
Explanation	An attempt is made to specify the mandatory parameter {0} with a null value.
Action	Check to make sure that the {0} has a valid value.
INMCLE0216	Exception occurred when trying to store the given profile picture in WEBDAV for user {0}.
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.
INMCLE0217	Exception occurred when trying to check for pending consumer registrations for user {0}.
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.
INMCLE0218	Exception occurred when trying to get Approval Request Reason for {0}.
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.

INMCLE0219	Exception occurred when trying to get Approval Workflow Name for {0}.
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.
INMCLE0220	{0} is triggered for consumer registration approval / rejection process; accessing {1} is invalid.
Explanation	The {0} is triggered for consumer registration approval / rejection; accessing {1} is not valid.
Action	Accessing the {1} method for this kind of {0} is not valid. Ensure that you do not call this method here.
INMCLE0222	Exception occurred when trying to get Consumer Registration Requestor for {0}.
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.
INMCLE0223	Exception occurred when trying to get profile picture for user {0}.
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.
INMCLE0224	Exception occurred when getting the notification options for user {0}.
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.
INMCLE0225	Error loading predefined notification concepts
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the stack trace for detailed information. If the problem persists, contact the CentraSite administrator.

INMCLE0226	Invalid phone type {0}.
Explanation	You have entered an invalid phone type. The phone type should match one of the predefined types.
Action	Refer to CLL API documentation for details on predefined phone types.
INMCLE0228	Invalid name {0}.
Explanation	You have entered an invalid name.
Action	Enter a valid name without special characters.
INMCLE0230	Failed to create {0} for given URI {1}.
Explanation	Failed to create a {0} for the given URI {1}, possibly because the Save operation is applicable only for WebDav resources.
Action	Save is applicable only for WebDaV resources.
INMCLE0231	Failed to get content type for given URI {0}.
Explanation	Failed to get content type for given URI {0}, possibly because the content type could not find the external URI.
Action	Failed to get content type for given URI {0}, possibly because the content type could not find the external URI.
INMCLE0232	Unable to fetch folders from external URL {0}.
Explanation	Could not get folders from an external URL, because this operation is only supported for a WebDav URL.
Action	Enter a valid WebDav URL.
INMCLE0233	Unable to fetch files from external URL {0}.
Explanation	Could not fetch files from an external URL, because this operation is only supported for a WebDav URL.
Action	Enter a valid a WebDav URL.
INMCLE0234	Failed to read XQuery from file {0}.
Explanation	Could not read the XQuery from file, possibly because the file does not exist.
Action	Enter a valid file path.

INMCLE0235	Parameter passed to the method {0} is null.
Explanation	The parameter passed to the method {0} is null.
Action	Pass a valid parameter to the method {0}.
INMCLE0236	Invalid values for keyword condition
Explanation	Keyword condition takes only one string value as input. The value should be put in the collection and then set to keyword condition.
Action	Check to make sure that valid values are set as input to the keyword condition.
INMCLE0237	Failed to get TransformedContent {0}.
Explanation	Failed to get the TransformedContent, possibly because of a connection failure.
Action	Check the network connection. If the problem persists, contact CentraSite administrator.
INMCLE0240	{0} cannot be reset.
Explanation	An attempt is made to reset the {0} that already has a value specified and that is read-only.
Action	{0} is read-only.
INMCLE0241	Exception occurred while trying to get the webdav location of computed profile template.
Explanation	An unexpected exception occurred while trying to get the webdav location of computed profile template, possibly because the template does not exist.
Action	Check to make sure that the uploaded archive contains the computed profile template.
INMCLE0242	Exception occurred while loading the implementation class of computed profile.
Explanation	An unexpected exception occurred while loading the implementation class of computed profile, possibly because the class does not exist.
Action	Check to make sure that the uploaded archive contains the implementation class.
INMCLE0243	Database access is denied.
Explanation	Access to the database is denied.
Action	Login again.

INMCLE0244	Exception while trying to retrieve the computed profile data.
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Make sure that the getProfileDataAsJson() implementation is correct.
INMCLE0245	Exception while trying to compute the profile data.
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Make sure that the computeProfileData implementation is correct.
INMCLE0246	Required input is missing.
Explanation	The required input is missing.
Action	Enter a valid input.
INMCLE0247	Error loading profile data.
Explanation	An unexpected error occurred while trying to load the profile data, possibly because of the following reasons: {0}.
Action	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
INMCLE0248	Search cannot be saved.
Explanation	The current search contains validation errors.
Action	Correct the validation errors and try again.
INMCLE0249	Error establishing a database connection.
Explanation	Unable to connect the database, possibly because the database server is down.
Action	Start the database server.
INMCLE0250	Failed to convert the given duration {0} to date.
Explanation	Exception occurred while trying to convert the given duration to date; possibly because the duration string is invalid.
Action	Enter a valid duration.

INMCLE0251	Failed to covert the given string {0} to date.
Explanation	Exception occurred while trying to convert the given string to date; possibly because the string is invalid.
Action	Check to make sure that the string is valid and it supports the date format like "E MMM dd HH:mm:ss Z yyyy".
INMCLE0252	Failed to create a new {0}.
Explanation	The {0} could not be created; possibly because the inputs were invalid.
Action	Make sure the inputs are valid.
INMCLE0253	Failed to save an asset with the given permissions.
Explanation	Failed to save an asset with the given permissions; possibly because the asset is unlocked.
Action	Make sure the asset is locked and available for editing.
INMCLE0254	Exception fetching the asset's instace-level and profile-level permissions.
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Contact your system administrator if the problem persists.
INMCLE0255	Display Interval {0} is invalid.
Explanation	Specify the time interval how frequently you want to collect metrics for the service. The expected format is 3m 2d 6h; where m indicates the month, d indicates the day and h indicates the hour.
Action	Check to make sure that the time interval is specified in exactly the above format.
INMCLE0256	Exception {0} occurred while trying to fetch the list of targets.
Explanation	This exception is unexpected. The cause is not immediately known.
Action	Check the exception stack trace information.
INMCLE0257	Target {0} is not active.
Explanation	The target {0} is not active. The cause is not immediately known.
Action	Check the stack trace information for details.

INMCLE0258	Failed to deploy the asset {0} on target {1}.
Explanation	Could not deploy the asset {0} on given target {1}. Possible reason: {2}
Action	Check the stack trace information for details.
INMCLE0259	Unable to fetch policy with UUID '{0}'.
Explanation	Could not fetch policies with the given UUID '{0}'; possibly because of the following reasons: 1. A policy with a UUID '{0}' does not exist. 2. Logged in user does not have the required permission on policy.
Action	Ensure that at least one policy exists with the given UUID and the logged in user has the required permissions on the policy.
INMCLE0260	Unable to fetch policies with name pattern '{0}'.
Explanation	Could not fetch policies with the given name pattern '{0}'; possibly because of the following reasons: 1. A policy with a name pattern '{0}' does not exist. 2. Logged in user does not have the required permission on policy.
Action	Ensure that at least one policy exists with the given name pattern and the logged in user has the required permissions on the policy.
INMCLE0261	The policy action template is invalid.
Explanation	Invalid action template; possibly because one or more vital parameters are null or not available.
Action	Enter valid parameters for the action template.
INMCLE0262	Unable to fetch policy actions with UUID '{0}'.
Explanation	Could not fetch policy actions with the given UUID '{0}'; possibly because of the following reasons: 1. A policy action with a UUID '{0}' does not exist. 2. Logged in user does not have the required permission on action.
Action	Ensure that at least one policy action exists with the given UUID and the logged in user has the required permissions on the action.
INMCLE0263	Unable to fetch policy actions with name pattern '{0}'.
Explanation	Could not fetch policy actions with the given name pattern '{0}'; possibly because of the following reasons: 1. A policy action with a name pattern '{0}' does not exist. 2. Logged in user does not have the required permission on policy action.
Action	Ensure that at least one policy action exists with the given name pattern and the logged in user has the required permissions on the policy action.

INMCLE0264	Unable to fetch {0}.
Explanation	Could not fetch the {0}. The cause is not immediately known.
Action	Check the exception stack trace information.
INMCLE0266	Failed to identify the consumers for the asset {0}.
Explanation	Could not identify the consumers for the given asset {0}
Action	This is an internal error. If the problem persists, contact the system administrator.
INMCLE0267	Failed to identify the targets to which the asset {0} is deployed.
Explanation	Exception occurred when populating the targets to which the asset {0} is deployed.
Action	This is an internal error. If the problem persists, consult the system administrator.
INMCLE0268	Failed to identify the events for the given search filter.
Explanation	Exception occurred when populating events for the given search filter.
Action	This is an internal error. If the problem persists, consult the system administrator.
INMCLE0269	Failed to revoke profile permissions.
Explanation	Caught an exception when trying to revoke the profile permissions.
Action	This is an internal error. If the problem persists, consult the system administrator.
INMCLE0270	Failed to set profile permissions.
Explanation	Caught an exception when trying to set the profile permissions.
Action	This is an internal error. If the problem persists, consult the system administrator.
INMCLE0271	
INMCLE0272	Error obtaining the classifications for object {0}.
Explanation	Caught an unexpected exception occurred while trying to obtain the classifications of object {0} and which prevented the application from proceeding further.
Action	Check the stack trace information for details.

INMCLE0273	Missing attribute in virtualization.
Explanation	Mandatory attribute (Virtual Alias or Endpoint) is missing. Virtual Alias and Endpoint attributes are mandatory for virtualizing an API.
Action	Set the Virtual Alias and Endpoint attributes.
INMCLE0274	Invalid Display Interval {0}.
Explanation	The display interval specified is invalid.
Action	Specify a valid interval (ex. 1m 1d 1h) and try again.
INMCLE0275	Failed to configure the API Key.
Explanation	Could not configure the API Key for the given asset; possibly because of missing parameters.
Action	Check to make sure all the required parameters are set.
INMCLE0276	Failed to load approval groups from the CentraSite registry.
Explanation	One or more approval groups could not be loaded from the CentraSite registry.
Action	Make sure that an approval group exists and try again.
INMCLE0277	Error checking permissions or validity over objects.
Explanation	Could not check permissions or validity over the specified objects.
Action	Verify the user and asset type are valid in the CentraSite registry.
INMCLE0278	Failed to check if the current user has Manage Organizations permission.
Explanation	This is an unexpected exception. The cause is not immediately known.
Action	Check the stack trace for detailed information.
INMCLE0279	Unable to delete/remove the selected {0} {1}
Explanation	You cannot delete the {0} {1}, because you do not have the required permission to delete/remove the {0}.
Action	Verify that you have the required permission to delete/remove the {0}. Contact your administrator, request permission if necessary and try again.

INMCLE0280	Unable to delete the selected user {0}.
Explanation	{1}. A user cannot be deleted if the user owns/modifies object(s), or if the user has any pending actions or if the user is the sole administrator for an organization. Also, if the user modified some object, and the corresponding audit trail entry is still present, deletion is rejected.{0} - The user that was attempted to be deleted.
Action	Delete all of the objects owned by the user, complete all pending actions, ensure another user is appointed as administrator for the corresponding organization and after all modification audit trail entries are purged (if any), user deletion will be allowed.
INMCLE0281	Unable to delete the selected group {0}
Explanation	{1}. You cannot delete the selected group either because you do not have the required permission or the group is associated with another object which creates a dependency to the group.
Action	Verify that you have the required permission to delete the user. Ensure that the group does not have any associations to other objects and try deleting the associations (if any) before attempting to delete the group again.
INMCLE0282	Unable to delete the selected role {0}
Explanation	{1}. You cannot delete the selected role either because you do not have the required permission, or the role is a pre-defined system role which cannot be deleted, or the role is associated with another object which is dependent on it.
Action	Verify that you have the required permission to delete the role. Ensure that you are not attempting to delete a pre-defined role.
INMCLE0283	Unable to delete the selected Child Organization
Explanation	{0}. You cannot delete the selected Child Organization either because you do not have the required permission, or the organization has policies which are active, or other objects are associated with the organization.
Action	Verify that you have the required permission to delete the Child Organization. Ensure that organization dependencies are resolved before attempting to delete again.
INMCLE0284	Unable to delete/modify the selected group {0}
Explanation	You cannot modify the users of/delete pre-defined groups of CentraSite such as "Users" and "Members". Since the group {0} is a pre-defined object, the deletion/modification of the group has been rejected.
Action	Ensure that the group that you are trying to delete/modify is not a pre-defined object.

INMCLE0285	Unable to delete the selected role {0}
Explanation	You cannot delete the OrganizationAdministrator role of an organization. This is because this role indicates the Administrator(s) of an organization.
Action	Ensure that the role you are trying to delete is not that of the OrganizationAdministrator.
INMCLE0286	Caught an Exception while creating the VSProcessingStepsAdapter instance
Explanation	This is an internal error. It is probably because of an invalid connection.
Action	Verify that the user session is valid.
INMCLE0287	Invalid Native service.
Explanation	This is an internal error. It is probably because the native service Registry Object is null.
Action	Verify that the native service is valid.
INMCLE0288	Unable to virtualize the native service
Explanation	This is an internal error. It is probably because of an invalid MessageFlow.
Action	Verify that the MessageFlow is valid.
INMCLE0289	Cannot Construct MessageFlow from VirtualService.
Explanation	This is an internal error. It is probably because of an invalid VirtualService.
Action	Verify that the VirtualService is valid.
INMCLE0290	Invalid Virtual service.
Explanation	This is an internal error. It is probably because the virtual service Registry Object is null.
Action	Verify that the virtual service is valid.
INMCLE0291	Falied to edit the VirtualService .
Explanation	Cannot edit the VirtualService. It is probably because of an invalid MessageFlow.
Action	Verify the MessageFlow for the virtual service.

INMCLE0292	Caught an Exception while creating Default StraightThrough routing for the Virtual Service
Explanation	This is an internal error. It is probably because of an invalid route-to.
Action	Verify the endpoints for the virtualization
INMCLE0293	Caught an Exception while creating Default Routing Endpoints for the Virtual Service.
Explanation	This is an internal error. It is probably because of an invalid route-to.
Action	Verify the endpoint properties for the virtualization.
INMCLE0294	Cannot build Processing steps with Empty MessageFlow.
Explanation	This is an internal error. It is because the MessageFlow is empty.
Action	Verify the MessageFlow for the virtual service.
INMCLE0295	Caught an Exception while building Processing steps for the VirtualService.
Explanation	This is an internal error. It is probably because of an invalid MessageFlow.
Action	Verify that the MessageFlow is valid.
INMCLE0296	Cannot add the PolicyActionInstance with templateId {0} to Routing Step
Explanation	This probably occurs because the PolicyActionInstance does not belong to the routing step.
Action	Verify that the PolicyActionInstance is valid.
INMCLE0297	Cannot add empty Default StraightThrough routing and empty Default Routing Endpoints for a Virtual Service.
Explanation	Default routing and endpoint properties are mandatory for a virtual service and cannot be deleted.
Action	Verify that the default routing and endpoint properties are not deleted.
INMCLE0298	Cannot add the PolicyActionInstance with templateId {0} to Enforce Step.
Explanation	This probably occurs because the policy action instance does not belong to the enforce step.
Action	Verify that the policy action instance is valid.

INMCLE0299	Virtualization is not supported for type {0}
Explanation	The asset passed to the virtualization action is not supported for virtualization.
Action	Verify that the asset is suitable for virtualization.
INMCLE0300	Unable to delete the selected asset.
Explanation	{0}. You cannot delete the selected asset either because you do not have the required permission or the asset has dependencies/associations with other objects (Example: pending approval of assets).
Action	Verify that you have the required permission to delete the asset. Also delete all dependencies with the asset and then attempt the deletion again.
INMCLE0301	Unable to remove the selected role(s) for the user {0}
Explanation	{1} Removal of role(s) for the user may have failed if you are trying to delete role(s) inherited through group membership, or if there are dependencies/associations between the objects.
Action	Ensure that all dependencies are resolved, and do not attempt to delete roles inherited through group memberships.
INMCLE0302	Unable to remove the selected role(s) for the group {0}
Explanation	{1}. Removal of role(s) from the group may have failed if a role has dependencies/associations and hence the role removal for the group may fail.
Action	Ensure that the roles do not have any dependencies and then try again.
INMCLE0303	Unable to remove the group membership {0} for the user
Explanation	{1}. You may not be able to remove a user's group membership if the user has dependencies/associations with the group (example: due to an approval policy). In such cases, membership removal for a user will be rejected.
Action	Ensure that all dependencies are resolved between the user and the group, then try again.
INMCLE0304	Unable to retrieve {0} of a {1}
Explanation	{2}. The retrieval may have failed because you do not have required permission, or due to database access error.
Action	Verify that you have required permissions and also ensure that the database is running, then try again.

INMCLE0305	Failed to instantiate class {0}
Explanation	Could not instantiate the given class {0}, possibly because of the following reasons: 1) class file does not exist 2) classpath is incorrect.
Action	Check for the above possible reasons. If the problem persists, contact the CentraSite administrator.
INMCLE0306	Failed to check User {0} has Role {1}
Explanation	An exception occurred while checking the role {1} for the user {0}.
Action	This is an internal error. Please contact the system administrator.
INMCLE0307	Invalid Super User
Explanation	The given super user configuration in CentraSite web.xml is invalid.
Action	Please provide a valid super user ID for the com.softwareag.centrasite.service.privilege.user.id Init-Param property under CentraSite web.xml.
INMCLE0308	Invalid Super User Role
Explanation	The super user configured under CentraSite web.xml does not have the required role to perform the privileged service.
Action	Please assign the CentraSite Administrator role for the super user or provide a user ID that has the CentraSite Administrator role.
INMCLE0309	Invalid Calling User Role
Explanation	The calling user does not have the appropriate role to execute a privileged service.
Action	Please assign an appropriate role to the user in order to perform the privileged service.
INMCLE0310	API Key settings cannot be updated or deleted
Explanation	A policy related to API Key settings is in the pending state, hence the settings cannot be updated.
Action	Ask the approvers to process the pending approval request pertaining to this asset.
INMCLE0311	Cannot find a category for the policy.
Explanation	This is an internal error. The category type cannot be found.
Action	Please verify the message flow.

INMCLE0312	Caught an Exception while retrieving Default StraightThrough routing endpoint for the Virtual Service
Explanation	This is an internal error. It is probably because of an invalid route-to.
Action	Verify the endpoints for the virtualization
INMCLE0313	Caught an Exception while creating Default HTTP Authentication for the Virtual Service.
Explanation	This is an internal error. It is probably because of an invalid policy instance.
Action	Verify the policy instance.
INMCLE0314	Unable to create/edit the selected {0}.
Explanation	You cannot create the {0} {1}, because you do not have the required permission to create/edit the {0}.
Action	Verify that you have the required permission to create/edit the {0}. Contact your administrator, request permission if necessary and try again.
INMCLE0315	Unable to modify the selected group {0}
Explanation	Since the group you are trying to modify is associated with an external repository, you will not be able to modify the external group.
Action	Ensure that the group that you are trying to modify is not an external group.
INMCLE0316	Unable to remove the selected role
Explanation	The logged in user and the user for whom roles are attempted to be removed are the same. This is not allowed.
Action	Please make sure that you are not trying to remove roles assigned to you. It can only be done by the CentraSite Administrator or your Organization Administrator.
INMCLE0317	Failed to find the alias which exists with the given name {0}
Explanation	An exception occurred while trying to find the asset which already exists with the given name {0}.
Action	Please make sure the given asset name does not have any special characters.

INMCLE0319	Email address already registered in CentraSite
Explanation	This email address is already registered to a user in CentraSite.
Action	Enter a different email address.
INMCLE0320	Please wait while we process your registration.
Explanation	User registration with the given email address is being processed by the administrator.
Action	Please wait while we process your registration.
INMCLE0321	Configure parameters for the New Account Registration policy
Explanation	The parameters required for the New Account Registration Policy are missing.
Action	Configure parameters (such as, Approver Group, Approval Mode) for the New Account Registration policy.
INMCLE0322	Failed to publish the asset
Explanation	Unable to publish the asset; possibly because of an incorrect attribute.
Action	Check to make sure that the specified input parameters are correct.
INMCLE0323	Failed to get the publish progress
Explanation	An exception occurred while getting the publish progress information.
Action	Please make sure that the request end point, request and header parameters are correct.
INMCLE0324	Failed to get the publish failed targets
Explanation	An exception occurred while getting the deployment failed targets information.
Action	Please make sure that the request end point, request and header parameters are correct
INMCLE0325	Failed to cancel publish operation
Explanation	An exception occurred while canceling the publish operation.
Action	Please make sure that the request end point, request and header parameters are correct.
INMCLE0326	Privileged user credentials are not configured.
Explanation	The expected privileged user credentials are not configured in {0}.
Action	Check to make sure that the privilege user credentials are configured in {0}.

INMCLE0327	Required roles to perform the publish are missing
Explanation	One or more roles that are required to perform the publish are missing.
Action	Please contact the administrator to add roles required to perform the publish.
INMCLE0328	Aliases or Targets input is empty
Explanation	The publish request does not contains aliases or tagets information.
Action	Please make the you have provided the aliases and targets required to perform the publish operation.
INMCLE0329	You do not have sufficient permissions to execute {0}.
Explanation	You do not have sufficient permissions to execute {0}.
Action	Verify that you have the "Manage Organizations" permission. Contact your administrator and request permission if necessary and then try again.
INMCLE0330	Unauthorized: Access is denied.
Explanation	Access to the service is denied possibly because of insufficient permissions.
Action	Check to make sure that you have the required permissions for accessing the service.
INMCLE0331	Forbidden: Access is denied.
Explanation	Request is forbidden at the moment; possibly because the API key is pending for a renewal request.
Action	Kindly retry after sometime.
INMCLE0332	Required policies to execute the API key renewal and/or revocation are not found.
Explanation	Could not process the renewal and/or revocation requests for the API key; possibly because the requiried policies are not found.
Action	Check to make sure that the API key settings are configured for renewal and/or reovcation. If the problem persists, contact your system administrator.
INMCLE0333	The Message Flow stage {0} that includes the action {1} must include at least one of the following dependent actions: Require Signing, Require Encryption, Require SLL, Require WSS X.509 Token.
Explanation	This action {1} depends on the following actions: Require Signing, Require Encryption, Require SLL, Require WSS X.509 Token.
Action	Choose at least one of the dependent actions for {1}.

INMCLE0339	The Message Flow stage {0} that includes the action {1} must also include {2} of the following dependent action(s): {3}.
Explanation	This action {1} mandate that at least one of the dependent actions {3} be included in the message flow.
Action	Choose at least one of the dependent actions for {1}.
INMCLI0001	Parsing failed. Make sure the configuration file syntax (or) path is correct.
Explanation	This is probably because of the following reasons: 1) syntax of the configuration file is invalid 2) specified configuration file path is incorrect.
Action	Check for the above possible reasons and execute again. Refer to the CentraSite documentation for creating a valid configuration file.
INMCLI0002	Internal error.
Explanation	An unexpected error occurred due to failure in the system execution.
Action	Contact the CentraSite administrator.
INMCLI0003	Error while executing command \${0}.
Explanation	Unexpected error occurred while executing the command.
Action	Check the error message for details.
INMCLI0004	\${0} is an invalid log unit; possible values are \${1}.
Explanation	The specified log unit is not supported. Possible values are \${1}.
Action	Refer to the error message for a list of possible values.
INMCLI0006	Purger is unavailable for \${0}.
Explanation	Purger is not available for the specified log unit.
Action	Check to make sure that the log units specified in the XML configuration file are valid. Else, contact the CentraSite administrator.
INMCLI0007	Purging stopped for \${0} as there is no write permission for export location \${1}.
Explanation	Purging stopped for the log unit, possibly because you do not have the explicit permission to write to the export location.
Action	Verify if the user has required permissions for purging to the export location.

INMCLI0008	Insufficient disk space in \${0}. Required space \${1}. Available space \${2}.
Explanation	The specified export location does not contain enough space for the exported logs. Refer to error message for the available space and required space.
Action	Choose a different export location.
INMCLI0009	Purging Failed. Following error occurred \${0}.
Explanation	Purging failed for the log unit due to a network connection timeout.
Action	Try again later or contact CentraSite administrator.
INMCLI0010	Unable to archive export directory \${0}.
Explanation	An unexpected exception occurred while trying to archive the exported logs. This is probably because the files may be accessed by another application.
Action	Close the application and retry the operation.
INMCLI0011	Unable to create export directory \${0}.
Explanation	An unexpected exception occurred while trying to create the export directory. This is probably because of the following reasons: 1) you do not have the explicit permission to write to the export location 2) export location is invalid.
Action	Check for the above possible reasons and execute again. If the problem persists, contact the CentraSite administrator.
INMCLI0012	Command \${0} is invalid.
Explanation	The specified command is not supported. For example, to purge logs you must specify -command purge_logs.
Action	Refer to CentraSite documentation for a list of the supported commands and their usage.
INMCLI0016	Attribute {0} does not exist for specified path {1}.
Explanation	The given attribute does not exist for the specified path.
Action	Verify that the attribute and path values are configured properly.
INMCLI0121	Error: Invalid session.
Explanation	CentraSite session has expired (or) already closed.
Action	Close your browser and log in again.

INMCLI0156	Parameters for New Version action can only be set in "Show Params" state. Current state of action is {0}.
Explanation	Parameters for versioning an asset can only be set in "Show Params" state. Current state of the action is {0}.
Action	Refer to the CSOAction related java document.
INMCLI0181	Current search criteria is invalid.
Explanation	The current search criteria is invalid. Validate the search criteria before you run.
Action	Check to make sure that the current search criteria is valid.
INMCLI0239	No list available to perform {0}.
Explanation	List is not available to perform {0}.
Action	Make sure that at least one of the selected items is added to the logged in user's list already.
INMCLI0265	Failed to create the custom activity {0}.
Explanation	The custom activity syntax in the configuration file was invalid.
Action	Check the activity syntax in the configuration file.
INMCLI0334	This action cannot be added to the Message Flow more than {0} time(s).
Explanation	You cannot include this action more than the allowed number of time(s) in the Message Flow.
Action	Do not include this action more than the allowed number of time(s) in the Message Flow.
INMCLI0335	This action cannot co-exist with {0}.
Explanation	This action cannot co-exist with the existing {0} in the Message Flow. This is possibly because, the two actions are mutually exclusive.
Action	Check to make sure that there are no mutually exclusive actions in the Message Flow.
INMCLI0336	{0} of the dependent actions {1} should be configured in the Message Flow.
Explanation	This action mandates that at least one of the dependent actions {1} be included in the Message Flow.
Action	Choose at least one of the dependent actions for {1}.

INMCLI0337	This action cannot be added to the Message Flow more than once.
Explanation	You cannot include this action more than once in the Message Flow.
Action	Do not include this action more than once in the Message Flow.
INMCLI0338	This action is not applicable to the {0} Message Flow stage.
Explanation	You cannot include this action in the {0} Message Flow stage.
Action	Ensure that you include the action in the applicable Message Flow stage.
INMCLW0032	Activity {0} is not applicable for given user.
Explanation	Activity {0} is not applicable for the given user.
Action	Assign the activity to given user.
INMCLW0047	Failed to synchronize configurator items with other configurators.
Explanation	Could not synchronize or update the configurator item changes with other configurators.
Action	Reset the configurator items. If the problem persists, contact the CentraSite administrator.
INMCLW0109	Failed to retrieve guest locale. Instead, returns the default locale {0}.
Explanation	An unexpected exception occurred while trying to retrieve the locale for logged in user. The cause is not immediately known.
Action	If the problem persists, contact the CentraSite administrator.
INMCLW0110	Exception occurred when closing connection.
Explanation	An unexpected exception occurred when trying to close the underlying connection.
Action	Initialize before opening a connection.
INMCLW0197	Duplicate search condition.
Explanation	An attempt is made to specify a duplicate condition in the search recipe.
Action	Remove the duplicate condition from search recipe.

- INMCLW0227** **Search name '{0}' already exists.**
Explanation The same name is not allowed for two different searches. This error occurs when an attempt is made to save a search with a name that already exists.
Action Enter a different search name.
- INMCLW0238** **Enable at least one notification option in User Preferences.**
Explanation At least one notification options in the User Preferences page should be selected to allow the current user to receive notifications through email and/or Inbox.
Action Enable at least one notification option in the User Preferences page before subscribing to an asset.
- INMCLW0318** **Action {0} is not applicable for the message flow step {1}.**
Explanation The chosen action {0} is not applicable for the message flow step {1}.
Action Choose a valid action for the message flow.

INMCL_COMMON_ATTR_PENDING_APPROVALS – Pending Approvals

INMCL_COMMON_ATTR_PENDING_APPROVALS_DEC – Pending approvals for the asset

INMCL_USER_ATTR_AVATAR_URL_DESC – The WebDAV URL of the Avatar for the User

INMCL_USER_ATTR_AVATAR_URL_NAME – Avatar URL Location

INMCL_USER_ATTR_EMAIL_DESC – The email address for the user

INMCL_USER_ATTR_EMAIL_NAME – Email Address

INMCL_USER_ATTR_FIRSTNAME_DESC – The details of the user's first name

INMCL_USER_ATTR_FIRSTNAME_NAME – First Name

INMCL_USER_ATTR_LASTNAME_DESC – The details of the user's last name

INMCL_USER_ATTR_LASTNAME_NAME – Last Name

INMCL_USER_ATTR_PHONE_DESC – The user's telephone number details

INMCL_USER_ATTR_PHONE_NAME – Telephone Number

INMCSE0006 Select a taxonomy to delete

Explanation Attempting to execute the delete action without selecting a taxonomy.

Action Select a taxonomy to be deleted.

INMCSE0007 Select JPG, GIF or PNG image format

Explanation Adding files other than JPG, GIF or PNG formats into a taxonomy or concept object.

Action Add only files with JPG, GIF or PNG formats into a taxonomy or concept object.

INMCSE0008 The given URL is not a proper WebDAV URL.

Explanation Wrong WebDAV URL or resource added into the taxonomy.

Action Enter a correct WebDAV URL or resource.

INMCSE0011 Select at least one user

Explanation At least one user should be selected.

Action Select at least one user.

INMCSE0012 Select at least one permission

Explanation At least one permission should be selected.

Action Select at least one permission.

INMCSE0013 Select an organization to delete

Explanation An attempt was made to delete an organization without selecting an organization object.

Action Select an organization object to delete.

INMCSE0014	Select the property to delete
Explanation	An attempt was made to delete a property without selecting a property.
Action	Select the property to delete.
INMCSE0015	Select at least one administrator
Explanation	At least one administrator should be selected.
Action	Select at least one administrator.
INMCSE0018	Organization {0} already exists
Explanation	The same name is not allowed for two different organizations. This error occurs when an attempt is made to create an organization with a name that already exists.
Action	Enter a different organization name.
INMCSE0019	Select a user to delete
Explanation	An attempt was made to delete a user without selecting the user object.
Action	Select the user object to delete.
INMCSE0020	Enter a valid user
Explanation	A valid user is required.
Action	Enter a valid user.
INMCSE0033	Enter the mandatory fields
Explanation	Some mandatory fields were not entered.
Action	Enter the mandatory fields.
INMCSE0038	Enter a valid user
Explanation	A valid user has not been entered.
Action	Enter a valid user.
INMCSE0042	Select permission to remove
Explanation	At least one permission should be selected.
Action	Select at least one permission.

INMCSE0044	E-mail address is not valid
Explanation	An invalid E-mail address has been specified.
Action	Enter a valid E-mail address.
INMCSE0045	Check the length of the contact input
Explanation	The length of the contact input exceeds the limit.
Action	Check the length of the contact input.
INMCSE0046	Enter valid contact input
Explanation	A wrong value was entered in the contact input.
Action	Enter valid contact input.
INMCSE0047	First name should not be empty
Explanation	An empty first name was entered.
Action	Enter a value for the first name.
INMCSE0051	A request with status 'Pending' can't be deleted.
Explanation	It is not possible to perform an unregister if a selected request has 'InProgress' as its status.
Action	Ensure that none of the selected requests has the status 'InProgress'.
INMCSE0052	Enter valid IP values
Explanation	Valid IP values are required.
Action	Enter valid IP values.
INMCSE0062	{0} is the current logged in user
Explanation	An attempt was made to delete the logged in user.
Action	Ensure that selected user is not the current logged in user.
INMCSE0063	{0} is the primary contact of {1}
Explanation	The logged in user tried to delete the primary contact of an organization.
Action	Ensure that the selected user-{0} is not the primary contact of an organization-{1}.

INMCSE0064	{0} is the CentraSite Administrator
Explanation	The logged in user tried to delete the user who is the CentraSite Administrator.
Action	Ensure that the selected user to delete is not the CentraSite Administrator.
INMCSE0068	Group {0} already exists in this organization
Explanation	An attempt was made to create a group with the same name as an existing group in the same organization.
Action	Use a new group name which is not already in use in the organization.
INMCSE0074	At least one {0} should be present
Explanation	When there is only one user with the role CentraSite Administrator or Organization Administrator, and if that user is deleted, this error will be thrown.
Action	There should be at least one CentraSite Administrator or Organization Administrator user. Make sure that another user with the same role is available in CentraSite.
INMCSE0075	Database access error. Can't connect to server CentraSite.
Explanation	The CentraSite Server is not running.
Action	Start the CentraSite Server.
INMCSE0076	There are no results matching your search criteria
Explanation	No results were found that match the search criteria.
Action	No action required.
INMCSE0077	The WSDL file is unreachable. Make sure the input information is correct.
Explanation	The URL for the given WSDL is wrong.
Action	Verify the URL given for this WSDL file.
INMCSE0084	{0} still has child organization(s) and it cannot be deleted.
Explanation	An organization cannot be deleted if a child organization is associated with that organization.
Action	If the parent organization is not associated with any child organization then the parent organization can be deleted.

INMCSE0085	Select an attribute to move
Explanation	If a user tries to re-order the attribute without selecting anything, this error will be thrown. For this the user has to first select any attribute and then do the re-ordering.
Action	Select an attribute to move.
INMCSE0086	Reordering multiple attributes is not allowed
Explanation	While assigning attributes to the profile, a user can re-order the attributes. If the user tries to re-order multiple attributes simultaneously, this error will be thrown.
Action	Ensure that you do not select multiple attributes for reordering.
INMCSE0087	HTTP Methods cannot be empty
Explanation	HTTP methods for an XML / REST service cannot be empty during import.
Action	Please select any one of the HTTP methods for the XML / REST service.
INMCSE0090	User {0} not found in external user store
Explanation	The sychronization of users can be done only with users who belong to the current default external user store.
Action	Deselect the users who do not belong to the default external user store.
INMCSE0091	Users not found in external user store
Explanation	The sychronization of users can be done only with users who belong to the current default external user store.
Action	Deselect the users who do not belong to the default external user store.
INMCSE0092	No endpoint defined
Explanation	For the namespace to be defined, declare the endpoint of the service.
Action	Provide the endpoint information for the service before giving the namespace.
INMCSE0093	Only CentraSite Administrator can change the ownership
Explanation	Only a CentraSite Administrator can change the ownership or the organization.
Action	If you want to change the ownership or the organization, ensure that you are a CentraSite Administrator.

INMCSI0071 **It is not allowed to add multiple associations if Relationship attribute is not multi-value**

Explanation For any single value relationship attribute, multiple value is not possible.

Action Verify the given value for the single value relationship attribute.

INMCSW0053 **Define the primary contact**

Explanation A primary contact is required when creating the organization.

Action Define the primary contact.

INMCSW0060 **{0} cannot be deleted**

Explanation You can only delete an organization if you have the necessary permissions.

Action Ensure that you have the necessary permissions to delete an organization.

INMCSW0061 **Default organization cannot be deleted**

Explanation The default organization cannot be deleted by any user.

Action It is not possible to delete the default organization.

INMEUE0001 **A connection with the same name already exists.**

Explanation A CentraSite connection name should be unique.

Action Enter another connection name.

INMEUE0002 **Could not connect to host.**

Explanation The specified host could not be connected. But the connection can be saved in the workspace.

Action Enter a reachable host name.

INMEUE0003 **Could not resolve host address.**

Explanation The specified host could not be reached. But the connection can be saved in the workspace.

Action Enter a reachable host name.

INMEUE0004	Log on failed. Make sure your user name and password are correct.
Explanation	A logon failed due to invalid credentials.
Action	Make sure your user name and password are correct.
INMEUE0005	Connection Name should not be empty
Explanation	The required name for the connection is missing.
Action	Enter a name for the connection.
INMEUE0006	An error has occurred. See error log for more details.
Explanation	An internal error has been occurred. Refer to the log files for more details.
Action	Refer to the log files for more details.
INMEUE0007	Cannot connect to server. Verify the specified connection information!\nMaybe the application server or the registry is currently not available.
Explanation	Maybe the application server or the registry is currently not available.
Action	Check whether the application server and CentraSite are available and accessible.
INMEUE0008	Cannot initialize predicate editors.
Explanation	Due to non-compliance with the Eclipse UI, the UI rendering failed.
Action	Check your implementation and make sure it handles the predicate properly.
INMEUE0009	No editor found for predicate class {0}
Explanation	No editors are associated with the predicate.
Action	Check whether the implementation of IPredicateEditor is associated in your plugin description.
INMEUE0010	Profile already exists
Explanation	The specified profile already exists with the asset type.
Action	Create another profile if required.
INMEUE0011	Attribute already exists
Explanation	An attribute with the same name already exists.
Action	Enter another name for the attribute if required.

INMEUE0012	You cannot modify this predicate. Delete it and create a new one instead.
Explanation	Predefined profiles are not modifiable.
Action	Delete it and/or create a new one instead.
INMEUE0013	Could not save. Correct the input errors first!
Explanation	The input value is not compatible with the selected type.
Action	Enter an input value that is compatible with the selected type.
INMEUE0014	The object cannot be deleted because it still has incoming associations.
Explanation	An object with incoming/outgoing association cannot be deleted.
Action	If you want to delete this object, first delete the associations.
INMEUE0015	{0} cannot be renamed as it is the target of one or more ExternalLink objects.
Explanation	If this object is the target of any ExternalLink object, the name cannot be modified.
Action	No action required.
INMEUE0016	{0} cannot be deleted as it is the target of one or more ExternalLink objects.
Explanation	If this object is the target of any ExternalLink object, the object cannot be deleted.
Action	No action required.
INMEUI0001	You do not have the required authority.
Explanation	The permission required to do this operation has not been granted.
Action	Contact the CentraSite administrator to get sufficient permission to do this operation if required.
INMFEE0011	Error occurred while trying to publish UDDI object(s) : {0}
Explanation	While trying to publish UDDI object(s), if the program encounters any errors, it displays this message. {0} - The Disposition Report Fault Message exception.
Action	Ensure that the object in question is valid and any dependency required by the object is already federated to the target registry. For example, key generators specific to the source registry might not be recognized by the target.

INMFEE0012	Cannot find the taxonomy object : {0}, {1}
Explanation	The taxonomy processor is looking for the taxonomy object in the target registry and cannot find it. {0} - Object name {1} - Object key
Action	This error occurs very rarely. So make sure that a connection to the target registry can be obtained and re-execute the program.
INMFEE0013	Concept publish failed
Explanation	If you are using the taxonomy processor, then it will attempt to publish concepts and classification schemes to the target registry. If not all the concepts can be published, then this error occurs.
Action	Make sure that the concepts have valid values and try to re-execute the program.
INMFEE0014	The TModel for the key {0} is not available in the federated data.
Explanation	This message is displayed by the taxonomy processor. While trying to federate the data, if a particular TModel is identified as a taxonomy, then it looks for the TModel in the federated data. If the data is not available, then this error occurs. {0} - TModel key
Action	Provide the TModel name for federation in the configuration file and re-execute the program.
INMFEE0018	The given default Business Entity name "{0}" is not available in the target registry.
Explanation	In the configuration file, you will provide a default business entity name for the target, so that services can be associated with this business. If this business entity name does not have any businesses in the target registry, then this error occurs. {0} Business entity name.
Action	Provide the right business entity name after ensuring that it exists in the target registry.
INMFEE0022	The {0} registry details are not configured properly
Explanation	The federation takes the data specification from the provided configuration file. If the {0} registry details are not configured in the configuration file, you will get this error. {0} source / target.
Action	Make sure the {0} registry details are provided with the proper syntax in the configuration file. To get more details, please refer to the product documentation.

INMFEE0023	The provided configFile is not configured properly.
Explanation	The configuration file provided does not have the required elements eventTypeStoreLoc and nervAssetsLoc. These elements should be present in the configFile.
Action	Ensure that these two elements are provided in the configuration XML file. Also ensure that you provide a valid path.
INMFEE0026	Cannot obtain OSGi instance required for Federation
Explanation	Federation makes use of the OSGi runtime to emit events and this error message explains that one such instance required for Federation cannot be obtained. This could be because the OSGi container may not be initialized properly or it could be some internal error
Action	Try to restart your default container and give some time for the container initialization before starting the Federation execution.
INMFEI0001	No data available for federation. Terminating program execution.
Explanation	The configuration file specifies the data that has to be inquired from the source registry. If the result of the inquiry does not have any data, then the federation cannot proceed and the program will terminate.
Action	Make sure that the configuration file specifies the correct data that is needed for federation.
INMFEI0002	Results of inquiring the source registry :
Explanation	CentraSite is currently inquiring the source registry and will display the results of the inquiry.
Action	No action required.
INMFEI0003	Obtained number of {0} : {1}
Explanation	This message displays the number of business objects obtained from inquiring the source registry {0} - Business(es) {1} - Number
Action	No action required.
INMFEI0004	Timestamp based update will be performed
Explanation	The federated objects will be compared with the modification timestamp and the update will be performed based on that.
Action	No action required.

INMFEI0005	Timestamp based update will not be performed
Explanation	The federated objects will be published, irrespective of whether the object to be published is the same or modified.
Action	No action required.
INMFEI0006	Key generator processor : Modifying the keys to belong to the domain {0}
Explanation	The UDDI keys of the federated objects will go through the key generator processor which will modify the UDDI keys such that they belong to the provided domain {DomainKey} {0} - Domain Key
Action	No action required.
INMFEI0007	The federated data is received as the following event :
Explanation	The Federation framework enables event emission. So the data is federated as events. This message informs that the emitted event is received for publishing to the target registry.
Action	No action required.
INMFEI0008	Time taken for publishing the data : {0} seconds
Explanation	The time taken for publishing the UDDI objects to the target registry is displayed by this message {0} - Time taken.
Action	No action required.
INMFEI0009	The given UDDI object(s) were federated to this target registry.
Explanation	The federation operation has completed and the required UDDI objects were published to this target registry.
Action	No action required.
INMFEI0010	Trying to update/publish {0} : {1}, {2}
Explanation	This message is displayed when an attempt is made to publish a UDDI object. The object can be identified by the object name and the UDDI key which will be displayed in the message. {0} Business / Service / TModel {1} Name of the UDDI object {2} UDDI key.
Action	No action required.

INMFEI0015	Taxonomy processor : Categories (Concepts) and Taxonomies (Classification Schemes) were identified and published to the target registry
Explanation	The taxonomies and categories were identified from the provided data and published to the target registry.
Action	No action required.
INMFEI0016	No {0} were found with the provided UDDIv3 Inquiry API parameters
Explanation	The UDDI object to be inquired should be specified in the configuration file for federation. It is provided as UDDI v3 Inquiry API calls, find_business, find_service, find_tModel. If no UDDI object could be inquired with the provided Inquiry API, then this message is displayed. {0} - Business(es) / Service(s) / TModel(s).
Action	Make sure that the Inquiry API adheres to the UDDI standards and that the inquiry parameters can inquire the data from the registry.
INMFEI0017	UDDI registry configured for {0} with the following properties: user {1}, {2} Authentication.
Explanation	This message is displayed if a connection could be established to the UDDI registry with the provided details. {0} - host {1} - user {2} - AuthToken, Basic
Action	No action required.
INMFEI0019	The above mentioned {0} is published to the target registry
Explanation	The UDDI object identified by the given name and the UDDI key has been updated/published in the target registry. {0} Business / Service / TModel.
Action	No action required.
INMFEI0020	Not updating {0} : {1}, {2} in the target registry
Explanation	While the program was performing timestamp based updates in the target registry, the UDDI object identified by the given name and the UDDI key was not updated/published in the target registry because it is already available in the target. {0} - Business, Service, TModel {1} - Name of the UDDI object {2} - UDDI key.
Action	No action required.
INMFEI0021	Number of {0} received for publishing : {1} , number published : {2}
Explanation	This message displays the number of {0} that were published to the target registry. {0} - Business(es) / Service(s) / TModel(s) {1} - Number of objects received {2} - Number published.
Action	No action required.

INMFEI0024	The federated data has reached the target : {0}
Explanation	There can be multiple targets configured for federation. This message displays the details of the target which has received the federated data through the federation ID {0}.
Action	No action required.
INMFEW0025	An error occurred while trying to close a resource - {0}
Explanation	Occasionally an error might be encountered while trying to close open connections, streams, etc. This is just a warning that an error was encountered and can be ignored.
Action	Make sure that the resource in question is not opened and/or modified by another program/application.
INMIEE0001	The call to the registry layer of CentraSite has failed.
Explanation	During export and import, access to the registry layer of CentraSite is required. The call to the registry layer of CentraSite has failed.
Action	Please contact your software supplier.
INMIEE0002	The archive file {0} could not be opened.
Explanation	The archive file is used to store the registry objects for export and import. The access to this archive file has failed.
Action	Please make sure that the archive file name is correct and you have sufficient access rights to access this file.
INMIEE0003	The archive file {0} could not be closed.
Explanation	The archive file is used to store the registry objects for export and import. The closing of this archive file has failed.
Action	Please make sure that the archive file has not been removed meanwhile.
INMIEE0005	The object with name {0}, type {1} and key {2} references another object in the context {3}. The referenced object has the key {4}, but it does not exist in the registry.
Explanation	Referenced object cannot be resolved, neither from the import set nor by existing objects.
Action	Add the referenced object.

INMIEE0006	The registry object cannot be imported, because it is older than the existing registry object.
Explanation	The import of the registry object has been rejected, because the timestamp of the existing registry object is newer than the timestamp of the import registry object. You can set the replace option of the import operation to overwrite the existing registry object with an older import object.
Action	You can set the replace option of the import operation to overwrite the existing registry object with an older import object.
INMIEE0007	The import object refers to the invalid object "{0}" and thus cannot be imported either.
Explanation	The import object refers to the specified invalid object, and thus cannot be imported either.
Action	Check why the referenced object is invalid by analyzing its error message.
INMIEE0013	The object cannot be imported because the embedded object {0} which is embedded in the existing object does not exist and is referenced by object {1}.
Explanation	The existing object contains an embedded object which is not defined in the object to be imported. This embedded object is referenced by another object either directly or through one of its embedded objects.
Action	Please add the missing object and try importing the object.
INMIEE0014	The external link with URI {0} could not be found.
Explanation	Specified resource could not be found. It may have been previously deleted.
Action	No action required.
INMIEE0016	The user has no read/write privilege to access/modify already existing registry objects
Explanation	The user wants to access or write an object for which the user has no privileges.
Action	The action must be performed by a more privileged user.
INMIEE0017	The user has no write privilege to modify existing registry objects
Explanation	The user wants to modify an object for which the user has no modify privileges.
Action	The action must be performed by a more privileged user.

INMIEE0018	The database with the URL {0} cannot be accessed.
Explanation	A connection to the database cannot be established.
Action	Check whether the URL is correct.
INMIEE0019	The connection to database {0} cannot be closed.
Explanation	The database connection has been lost and cannot be closed.
Action	Please contact your software supplier.
INMIEE0021	The registry object could not be deleted.
Explanation	The registry object should have been deleted after the export, but the deletion has failed.
Action	Please contact your software supplier.
INMIEE0022	The lifecycle stage URL of the registry object does not match the URL of the import registry, which is {0}
Explanation	The registry object carries information about valid target registries. This information is called the lifecycle stages of the particular lifecycle state of this registry object. This registry object thus can only be imported into matching target registries.
Action	The registry object can be imported into matching target registries only.
INMIEE0025	The import of a user registry object has failed, because a user with identical name and key {0} already exists.
Explanation	The user registry object already exists.
Action	No action required.
INMIEE0026	The import of a group registry object has failed, because a group with identical name and key {0} already exists.
Explanation	The group registry object already exists.
Action	No action required.
INMIEE0027	The import operation has failed, because the update of the security information has failed, object "{0}" ({1}).
Explanation	The update of the security information has failed.
Action	Please contact your software supplier.

INMIEE0028	The import archive does not have the expected compatibility level of {0}.
Explanation	The import archive must contain a file named MANIFEST.TXT which contains the compatibility level of the import archive. The compatibility level of the import archive must be the same as the compatibility level of the CentraSite version used.
Action	Use the same CentraSite version for exporting and importing.
INMIEE0030	The provided import organization key {0} does not exist in the registry.
Explanation	The lookup of this key in the registry was not successful.
Action	Please provide a valid import organization key.
INMIEE0031	The provided import organization key {0} does not refer to an organization.
Explanation	The provided key exists in the registry, but the referred object is not an organization object.
Action	Please provide a valid import organization key.
INMIEE0032	The setting of the import organization {0} has failed.
Explanation	During import, the setting of the import organization has failed.
Action	Please contact your software supplier.
INMIEE0034	The deletion of the repository resource {0} has failed.
Explanation	The option delete after export has been set and the deletion of a repository resource has failed.
Action	Please contact your software supplier.
INMIEE0035	The query to find all external links with the external URI {0} has failed.
Explanation	The option delete after export has been set and the query to find all external links with the same URI has failed.
Action	Please contact your software supplier.
INMIEE0036	The collection of the registry objects of the policy {0} has failed.
Explanation	The delete after export option is active and the policy is to be deleted after export. The collection of the registry objects belonging to the policy has failed.
Action	Please contact your software supplier.

INMIEE0040	The import of a role registry object has failed, because a role with identical name and key {0} already exists.
Explanation	Role objects cannot be replaced.
Action	Re-establish the organization's roles.
INMIEE0041	The import of a permission registry object has failed, because a permission with identical name and key {0} already exists.
Explanation	Permission objects cannot be replaced.
Action	Re-establish the organization's permission.
INMIEE0044	The user has no privilege to create/update an asset type ({0})
Explanation	The user has not enough permission to create or update an asset type.
Action	Check the roles of the user.
INMIEE0046	The import of the organization with key {0} has failed, because the organization has not been exported with the option to include users, groups, roles and permissions.
Explanation	You can only import an organization together with its users, groups, roles and permissions. However, if the organization already exists, then it is possible to just import an organization without its users, groups, roles and permissions.
Action	Export the organization with the option to include users, groups, roles and permissions.
INMIEE0048	Creating/updating of asset type "{0}" failed with internal error: {1}
Explanation	An asset type cannot be imported or updated because of an internal registry problem.
Action	View the internal error reason and the stack trace in the log.
INMIEE0049	Replacement of asset type "{0}" failed due to layout mismatch
Explanation	The asset type cannot be replaced because the layout of the importing type is incompatible with the existing one.
Action	View the stack trace for the details.
INMIEE0050	The asset type "{0}" references another object with key {1}, but it does not exist in the registry.
Explanation	A reference from the asset type to be imported is not in the registry. This is usually a referenced asset type and must be present. Due to internal reasons the import cannot continue.
Action	Check that the referenced object (asset type) is present in the target registry.

INMIEE0055	Asset to be imported does not fit to Asset type definition with attribute mismatch, attribute: {0}
Explanation	The asset does not match the asset type. Possibly the asset has an attribute which is not defined for the given asset type.
Action	Check the asset type for missing attributes. Import the asset type which matches the asset.
INMIEE0057	Selective import not supported with old export archives
Explanation	No selective import is possible, only importing the whole archive is supported.
Action	Do not select particular keys.
INMIEE0061	User {0} not found
Explanation	The requested user name was not found in the registry.
Action	Use a valid user name.
INMIEE0063	The document cannot be imported, because the associated asset type will be rejected
Explanation	The schema file of an asset type cannot be imported because the asset type itself will be rejected for another reason.
Action	Analyze the existing asset type.
INMIEE0064	Replacement of asset type {0} failed due to layout mismatch, reason: {1}
Explanation	The given asset type cannot be replaced because it would change or remove used information, e.g. attributes.
Action	Check the attributes of the existing asset type. There are assets with attributes which would be removed by the import.
INMIEE0066	The document cannot be imported, because its parent was rejected
Explanation	The repository document will not be imported because its parent object (e.g. an ExternalLink object) was rejected.
Action	Check why the parent object was rejected.
INMIEE0067	The object cannot be replaced, because it would lose its attribute {0}, which is referenced within registry by: {1}
Explanation	The given object cannot be replaced, because the object that is already present has an attribute which would disappear as a result of the replacement. This attribute is referenced by others, therefore the attribute must be kept.
Action	Check the existing object and its references.

INMIEE0068	No privilege to update object
Explanation	The user has no privilege to update an object, present in the archive, to the registry. This could happen when updating asset types or taxonomies.
Action	Check if you can import the archive as a user with more privileges.
INMIEE0072	Cannot update asset type because of version mismatch ("{0}" / "{1}")
Explanation	The asset type to be imported has a lower version number than the one in the registry. The type is incompatible to the registry and therefore a replacement would destroy relevant information.
Action	The asset type from a previous version cannot be imported.
INMIEI0010	The registry object is not imported, because it has the same timestamp as the existing object.
Explanation	The object to be imported already exists with the same timestamp.
Action	No action required.
INMIEI0011	The imported registry object has replaced the existing object.
Explanation	The registry object to be imported already exists and has been replaced.
Action	No action required.
INMIEI0012	The imported registry object has been created.
Explanation	The registry object to be imported has been created.
Action	No action required.
INMIEI0020	The registry object with key {0} was deleted after it has been exported.
Explanation	The option delete after export has been set and the registry object has been deleted after the export.
Action	Please contact your software supplier.
INMIEI0023	The document cannot be imported, because it is older than the existing document.
Explanation	The import of the document has been rejected, because the timestamp of the existing document is newer than the timestamp of the import document. You can set the replace option of the import operation to overwrite the existing document with an older import document.
Action	You can set the replace option of the import operation to overwrite the existing document with an older import document.

INMIEI0024	The document was not imported, because it has the same timestamp as the existing document.
Explanation	The import document and the existing document have the same timestamp. No import is necessary.
Action	No action required.
INMIEI0033	The repository resource was deleted after it has been exported.
Explanation	The option delete after export has been set and the registry object has been deleted after the export.
Action	No action required.
INMIEI0039	Referenced object not in export set: {0} --> {1}
Explanation	The target object is not in the export set.
Action	Before importing, the referenced (target) objects must be present in the registry.
INMIEI0065	
INMIEI0069	The document cannot be imported because it is already present
Explanation	The document, which contains executable code, is not imported because it is already present.
Action	No action required.
INMIEI0070	The registry object is not imported, because it is already present
Explanation	The object cannot be replaced because the root object was not imported.
Action	No action required.
INMIEW0008	Embedded objects cannot be exported.
Explanation	Embedded objects like Classification, AuditableEvent, ExternalIdentifier, ServiceBinding, SpecificationLink and Association cannot be exported.
Action	Deselect object from list of objects to be exported.

INMIEW0009	Export of selected object does not find any objects to be exported.
Explanation	Export of selected object does not find any objects to be exported.
Action	Remove object from list of objects to be exported.
INMIEW0029	The referenced registry object with key {0} is not part of the export archive.
Explanation	A referenced object is not selected for export. Therefore there might be problems at import.
Action	Check your associated objects and decide whether to add them to the export.
INMIEW0037	Delete of registry objects failed, reason: {0}
Explanation	The deletion of one or more registry objects has failed during the export with delete option. The export archive however is complete.
Action	See the reason for the rejection within the message.
INMIEW0038	The referenced registry object with key {0} is not part of the export archive. It is referenced from object: "{1}"
Explanation	A referenced object is not selected for export. Therefore there might be problems later when you try to import the archive.
Action	Check your associated objects and decide whether to add them to the export.
INMIEW0042	Delete after export of object "{0}" is not supported
Explanation	It is currently not supported to delete specified object with the delete-after-export function.
Action	Delete the object manually.
INMIEW0043	User "{0}" could not be deleted from organization
Explanation	The user cannot be deleted from an organization after import because this user is already in use.
Action	Clean up the user manually with the imported organization.
INMIEW0047	Object {0} modified due to unreferenced association
Explanation	The association to an unreferenced target object was removed from the object.
Action	Check the object and repair it if necessary.

INMIEW0051	Unprivileged reference to key: {0}
Explanation	An exported object has a reference to an object that the user has no privilege to access. This means for import that the referenced object must be present and the importing user must have privileges to access this object.
Action	Keep this situation in mind for a later import.
INMIEW0052	One ore more asset types may be corrupted, key: {0}
Explanation	Due to resolving an access violation situation, it may happen that asset types may be corrupted.
Action	Import the archive as CentraSite Administrator.
INMIEW0053	{0} association to object "{1}" removed
Explanation	The association to the given object has been removed during import because the target object is not present.
Action	Re-establish the removed association if possible.
INMIEW0054	Classification "{0}" removed because of unreferenced category
Explanation	The classification has been removed from the object because its concept is not present in the registry.
Action	Re-establish the classification if possible.
INMIEW0058	External link reference removed from object "{0}"
Explanation	An external link reference which does not exist for the object has been removed.
Action	Check if the external link can be re-inserted manually.
INMIEW0059	Lifecycle state removed because of missing model
Explanation	The object has a lifecycle state at import, however the associated lifecycle model is not present in the target registry.
Action	Import the lifecycle model first.
INMIEW0060	User object cannot be imported because of a missing name, key: {0}
Explanation	The import processing detected an invalid user element and ignored the import.
Action	Verify the user entry in the archive.

INMIEW0062	contains unprivileged reference
Explanation	The object given contains a reference to an object which cannot be exported because the user has no privilege of that object. Only the reference gets exported. At import, this reference is checked and possibly removed from the object if the referenced object is not present.
Action	Check if a more privileged user should export the object.
INMIEW0071	ServiceBinding "{0}" removed because of unreferenced specificationObject
Explanation	A service binding points to a specification object, which is not present in the archive or registry. Therefore the service binding gets removed from the service.
Action	Check the service and its specification objects.
INMIME0001	ObjectType {0} does not exist.
Explanation	The required object type does not exist in CentraSite.
Action	Make sure the required object type is available in CentraSite and create an instance of it.
INMIME0002	Asset {0} not found.
Explanation	A required asset is not available in CentraSite.
Action	Create the required asset.
INMIME0003	Error while executing JAXR operation.
Explanation	An internal JAXR operation failed.
Action	Retry your request.
INMIME0004	XPDL file {0} not found.
Explanation	An XPDL file does not exist in the location specified.
Action	Make sure the given XPDL file is in the specified location.
INMIME0005	Error while parsing the XPDL file.
Explanation	The XPDL file does not match the XPDL format.
Action	Make sure the given XPDL format is valid.

INMIME0006	Error while connecting to CentraSite.
Explanation	It is not possible to establish a connection to the CentraSite database.
Action	Make sure the CentraSite database URL and CentraSite user credentials are valid.
INMIME0007	Given XPDL File not supported.
Explanation	The given XPDL file is not supported by CentraSite. CentraSite supports only XPDL 2.x.
Action	Make sure the given XPDL version is 2.x.
INMIME0008	Specified process {0} is not available
Explanation	There is no process with the specified asset ID
Action	Check the asset ID provided in the request
INMIME0009	Required id is missing in Pool
Explanation	While parsing the XPDL file, a pool element has been found but the attribute "id" is missing.
Action	Please make sure the specified XPDL file is valid.
INMIME0010	From reference is missing in Transition
Explanation	While parsing the XPDL, a transition element has been found but the "from reference" is missing in the transition element.
Action	Please make sure the "from reference" element contains a proper value.
INMIME0011	To reference is missing in Transition
Explanation	While parsing the XPDL, a transition element has been found but the "to reference" is missing in the transition element.
Action	Please make sure the "to reference" element contains a proper value.
INMIME0012	Id is missing in Transition
Explanation	While parsing the XPDL, a transition element has been found but the "id" is missing in the transition element.
Action	Please make sure "id" is present in the transition element and contains a proper value.

INMIME0013	Id is missing in lane element
Explanation	While parsing the XPDL, a lane element has been found but the "id" is missing in the transition element.
Action	Please make sure the "id" is present in the lane element and contains a proper value.
INMIME0014	Id is missing in activity element
Explanation	While parsing the XPDL, a lane element has been found but the "id" is missing in the activity element.
Action	Please make sure "id" is present in the activity element and contains a proper value.
INMJRE0001	Database access error: {0}
Explanation	An error occurred while accessing the database. The corresponding stack trace contains a "caused by" message with the reason of the failure.
Action	Please contact your software supplier if you can't analyze the reason of the database access error.
INMJRE0002	Expected {0} objects
Explanation	Certain operations that accept a collection of input objects (such as for example LifeCycleManager.saveOrganizations()) expect certain object types ("Organization" in this example). The affected operation can be found in the stack trace.
Action	Correct the client program.
INMJRE0003	Invalid property name "{0}"
Explanation	The name of a property must be a valid NCName as in XML schema, e.g. it must not contain colon or whitespace.
Action	Correct the name.
INMJRE0004	Invalid object in {0} parameter
Explanation	Certain operations that accept a collection of input objects expect certain object types. The affected operation can be found in the stack trace.
Action	Correct the client program.

INMJRE0005	Mutually exclusive find qualifiers: {0}, {1}
Explanation	The listed find qualifiers are mutually exclusive with respect to the performed operation.
Action	Correct the client program.
INMJRE0006	Found multiple matches
Explanation	The performed query method is supposed to return zero or one result object, however the database contains multiple matches.
Action	Please contact your software supplier.
INMJRE0007	The javax.xml.registry.queryManagerURL property is not set
Explanation	Before creating a new Connection, the javax.xml.registry.queryManagerURL property has to be set to a non-null value.
Action	Correct the client program.
INMJRE0008	The credentials parameter must not be null
Explanation	The setCredentials() method was called with a null value for the credentials parameter.
Action	Correct the client program.
INMJRE0009	Re-connect failed
Explanation	An error occurred while recreating the database connection according to the given credentials. The stack trace contains a "caused by" message with the reason of the failure.
Action	Please contact your software supplier.
INMJRE0010	Invalid credentials: expected PasswordAuthentication
Explanation	The credentials have to be passed as an instance of java.net.PasswordAuthentication.
Action	Correct the client program.
INMJRE0011	User name is not unique: {0}, only readonly access granted
Explanation	For each user, there should be only one user object in the database. For the given user however, several objects with the same name were found. When the user tries to log in he is granted readonly access.
Action	Log in using a different user (probably an administrator) and delete or rename the duplicate user objects.

INMJRE0012	The declarative query manager is not supported by this implementation
Explanation	The declarative query manager is not supported by this implementation.
Action	See the documentation for the available query functionality.
INMJRE0013	Invalid interface name parameter: {0}
Explanation	The method LifecycleManager.createObject() was called with an illegal interface name.
Action	Correct the client program.
INMJRE0014	Invalid XML response when saving documents
Explanation	This is an internal error.
Action	Please contact your software supplier.
INMJRE0015	The object to be undeprecated ({0}) is not in deprecated state
Explanation	Only deprecated objects may be undeprecated.
Action	Select only deprecated objects for undeprecation.
INMJRE0016	Illegal object type: {0}
Explanation	A delete operation was called with an illegal object type.
Action	Correct the client program.
INMJRE0017	Internal error: object with key "{0}" lost from cache
Explanation	This internal error indicates an inconsistency in the object cache.
Action	Please contact your software supplier.
INMJRE0018	Invalid null value in {0} parameter
Explanation	The method QueryManager.getRegistryObjects() was called with a null value.
Action	Correct the client program.
INMJRE0019	The object identified by the ConnectionFactory property {0}="{1}" is not a classification scheme
Explanation	The default postal scheme was not specified correctly.
Action	Specify a correct default postal scheme.

INMJRE0020	This implementation does not support makeRegistrySpecificRequest()
Explanation	This implementation does not support makeRegistrySpecificRequest().
Action	See the documentation for the available query functionality.
INMJRE0021	Invalid schema name "{0}", please consult the documentation for correct syntax
Explanation	The schema name of a type must be a valid NCName as in XML schema, e.g. it must not contain colon or whitespace.
Action	Correct the name.
INMJRE0022	An association cannot have itself as source object
Explanation	An association cannot have itself as source object.
Action	Specify a correct association.
INMJRE0023	An association cannot have itself as target object
Explanation	An association cannot have itself as target object.
Action	Specify a correct association.
INMJRE0024	Association type must not be null
Explanation	When creating a new association the association type must not be null.
Action	Specify a correct association.
INMJRE0025	The object to be deleted is not of type {0}
Explanation	The delete operation specified that only objects of a particular type should be deleted, however at least one of the given keys points to a different object.
Action	Specify only keys of the requested type.
INMJRE0026	An auditable event object cannot be deleted
Explanation	It is not allowed to delete an auditable event.
Action	Correct the client program.
INMJRE0027	Concept must have a classification scheme ancestor
Explanation	The concept used for an internal classification has to belong to a classification scheme.
Action	Supply a correct concept for an internal classification.

INMJRE0028	{0} parameter must not be null
Explanation	The function shown on the call stack must not be called with a null value.
Action	Correct the client program.
INMJRE0029	Concept must not have a parent
Explanation	If a ClassificationScheme is created from a concept, then this concept must not have a parent.
Action	Supply a correct concept.
INMJRE0030	Invalid value type: {0}
Explanation	ClassificationScheme.setValueType() was called with an invalid value type.
Action	Supply a valid value type.
INMJRE0031	The classification scheme to be deleted still has children
Explanation	A classification scheme cannot be deleted if it has child concepts.
Action	Delete the child concepts before deleting the classification scheme.
INMJRE0032	Parent not allowed for concept
Explanation	The parent of a concept has to be a classification scheme or another concept.
Action	Supply a valid parent.
INMJRE0034	The concept to be deleted still has children
Explanation	A concept cannot be deleted if it has child concepts.
Action	Delete the child concepts before deleting the concept.
INMJRE0035	Invalid value for {0} ({1})
Explanation	An internal error occurred during the XML serialization of Java objects.
Action	Please contact your software supplier.
INMJRE0036	Invalid string value for {0} ({1})
Explanation	An internal error occurred while deserializing an XML document to a Java object.
Action	Please contact your software supplier.

INMJRE0037	The external link to be deleted still has linked objects
Explanation	An external link cannot be deleted if it has linked objects.
Action	Remove the external link from its linked objects before deleting it.
INMJRE0039	Cannot add a non-KeyRef to a KeyRefList
Explanation	Internal error.
Action	Please contact your software supplier.
INMJRE0040	toArray failed with attached JAXRException while resolving an object reference
Explanation	An exception occurred while copying a collection to an array. See the "caused by" message in the stack trace for the cause of the problem.
Action	Please contact your software supplier.
INMJRE0041	RegistryObjectIterator failed with attached JAXRException while resolving an object reference
Explanation	An exception occurred while iterating a query result. See the "caused by" message of the stack trace for the cause of the problem.
Action	Please contact your software supplier.
INMJRE0042	Invalid locale
Explanation	An internal error occurred while deserializing an XML document to a Java object.
Action	Please contact your software supplier.
INMJRE0043	The organization to be deleted still has child organizations
Explanation	An organization cannot be deleted if it has child organizations.
Action	Delete the child organizations before deleting the organization.
INMJRE0044	The organization to be deleted still has services
Explanation	An organization cannot be deleted if it has child services.
Action	Remove the services before deleting the organization.

INMJRE0045	The organization to be deleted still has users
Explanation	An organization cannot be deleted if it has users.
Action	Remove the users before deleting the organization.
INMJRE0046	Invalid stability value: {0}
Explanation	The setStability() method was called with an invalid stability value.
Action	Supply a valid stability value.
INMJRE0047	This registry provider does not support client supplied keys
Explanation	This registry provider does not support client supplied keys.
Action	Do not call the setKey() method.
INMJRE0048	Internal error: duplicate key in object cache "{0}"
Explanation	This internal error indicates an inconsistency in the object cache.
Action	Please contact your software supplier.
INMJRE0049	Cannot modify object type classification
Explanation	An instance of a user-defined type cannot be assigned another object type classification.
Action	Correct the client program.
INMJRE0050	Duplicate object type classification
Explanation	An instance of a user-defined type can only be classified with one concept from the "ObjectType" classification scheme.
Action	Correct the client program.
INMJRE0051	Cannot remove object type classification
Explanation	For instances of user-defined types it is not allowed to remove the classification that represents the object type.
Action	Correct the client program.
INMJRE0052	This object ({0}) is deprecated and must not be referenced
Explanation	A deprecated object must not be referenced in any way by another object.
Action	Do not create references to deprecated objects.

INMJRE0053	An object to be deleted has not been previously saved
Explanation	Only objects that have been previously saved can be deleted.
Action	Correct the client program.
INMJRE0054	The "{0}" object to be deleted ({1}) is the target of the "{2}" association "{3}". The source of the association is the {4} object "{5}" with key "{6}".
Explanation	An object cannot be deleted if it is still the target of an association.
Action	Delete the association before deleting the object.
INMJRE0055	The registry package to be deleted still has members
Explanation	A registry package cannot be deleted if it has member objects.
Action	Remove the member objects from the package before deleting it.
INMJRE0056	Cannot modify the name of a slot after it was added to a registry object
Explanation	The name of a slot cannot be changed after the slot was added to a registry object.
Action	Correct the client program.
INMJRE0057	Invalid namespace "{0}" of type
Explanation	The namespace of a type must be a valid URI.
Action	Correct the namespace.
INMJRE0058	Invalid XML stream
Explanation	An internal error occurred while deserializing an XML document to a Java object.
Action	Please contact your software supplier.
INMJRE0059	XML parsing error
Explanation	An internal error occurred while deserializing an XML document to a Java object.
Action	Please contact your software supplier.
INMJRE0060	STAX configuration error
Explanation	An internal error occurred while deserializing an XML document to a Java object.
Action	Please contact your software supplier.

INMJRE0061	Invalid URL value
Explanation	An internal error occurred while deserializing an XML document to a Java object.
Action	Please contact your software supplier.
INMJRE0062	Invalid boolean value for attribute {0}
Explanation	An internal error occurred while deserializing an XML document to a Java object.
Action	Please contact your software supplier.
INMJRE0063	Incomplete object ({0} is missing or does not have a value)
Explanation	The indicated required part of an object was missing when an object was to be saved.
Action	Correct the client program.
INMJRE0064	Cannot add an existing association to another object
Explanation	It is not possible to add the same association object to several separate registry objects.
Action	Create a new association object.
INMJRE0065	Cannot add an existing classification to another object
Explanation	It is not possible to add the same classification object to several separate registry objects.
Action	Create a new classification object.
INMJRE0066	Cannot add an existing external identifier to another object
Explanation	It is not possible to add the same external identifier object to several separate registry objects.
Action	Create a new external identifier object.
INMJRE0067	Unexpected owner type
Explanation	This is an internal error.
Action	Please contact your software supplier.
INMJRE0068	Cannot delete the pre-defined object with key "{0}"
Explanation	The CentraSite Registry/Repository database is installed with some pre-defined JAXR objects that are required for CentraSite operation. These objects must not be deleted.
Action	Do not delete pre-defined objects.

INMJRE0069	Incomplete principal
Explanation	A CentraSitePrincipal has to be either an href representing a user or a group, or an "all" indicator, or an "authenticated" indicator, or an "unauthenticated" indicator. None of these were set.
Action	Create a correct CentraSitePrincipal object.
INMJRE0070	Cannot set instance based security for objects of type {0}
Explanation	Instance based security cannot be set for the following object types: AuditableEvent, Association, Classification, ExternalIdentifier, ServiceBinding and SpecificationLink.
Action	Do not try to set instance based security for these object types.
INMJRE0071	Failed with attached JAXRException
Explanation	Comparison of two key references failed. See the "caused by" message in the stack trace for the cause of the failure.
Action	Please contact your software supplier.
INMJRE0072	A ServiceBinding cannot have both a TargetBinding and an AccessURI
Explanation	For a ServiceBinding object, TargetBinding and AccessURI are mutually exclusive.
Action	Choose either TargetBinding or AccessURI.
INMJRE0073	Expected empty XML element {0}, but found content "{1}"
Explanation	An internal error occurred while deserializing instance based security information to a Java object.
Action	Please contact your software supplier.
INMJRE0074	Trying to use a closed connection (created by {0} at "{1}", closed at "{2}")
Explanation	A previously closed connection must not be used any more.
Action	Open a new connection.
INMJRE0075	A concept object must not have a HasParent association
Explanation	In order to allow for a proper mapping between JAXR and UDDI, a concept object must not have a HasParent association.
Action	Do not create HasParent associations for concept objects.

INMJRE0076	Internal error: object type concept not found
Explanation	Internal error.
Action	Please contact your software supplier.
INMJRE0077	The operation "{0}" can only be called for objects of type "{1}"
Explanation	Each operation belongs to one object type, and it can only be executed on objects of that type.
Action	Call the operation only for objects of the correct type.
INMJRE0078	Internal error: method should not be called
Explanation	Internal error.
Action	Do not call this method.
INMJRE0079	Invalid status value: {0}
Explanation	An invalid status value was specified.
Action	See the JAXR javadoc for correct status values.
INMJRE0080	The status of the deprecated object ({0}) cannot be modified
Explanation	The status of a deprecated object cannot be modified.
Action	Undeprecate the object before modifying its status.
INMJRE0082	A concept ({0}) in the ObjectType classification scheme is to be saved without an external link to an XML schema file
Explanation	Concepts in the ObjectType classification scheme represent JAXR object types. These concepts have to have an external link to an XML schema file (XSD).
Action	Supply an XSD file for this concept.
INMJRE0087	Invalid value "{0}" of property "{1}"
Explanation	The given value does not match the declared datatype of the property.
Action	Correct the value.

INMJRE0088	The concept to be deleted ({0}) is used by a classification ({1}). The classification belongs to the {2} object with key "{3}".
Explanation	A concept must not be deleted if it is used by a classification.
Action	Remove the classification before deleting the concept.
INMJRE0089	Trying to add a concept with the already existing value "{0}" under the parent object with key "{1}".
Explanation	Concepts under the same parent object must have unique values.
Action	Choose a different value for the new concept.
INMJRE0090	Invalid slot name: "{0}"
Explanation	In the CentraSite JAXR implementation a JAXR slot name has to have the format {uri}localname, where the {uri} part is optional. The localname has to be a valid NCName according to the XML specification. Basically this means it may start with a letter or an '_' character, followed by letters, digits, or the characters '_', '.', '-'. In particular, the localname must not contain any whitespace characters.
Action	Supply a valid slot name.
INMJRE0091	Invalid concept used as association type: "{0}"
Explanation	Only concepts from the classification scheme "AssociationType" may be used as association types.
Action	Choose a valid concept.
INMJRE0092	Commit or rollback not allowed if connection does not have client controlled transactions
Explanation	Only JAXR connections that were created with com.centrasite.jaxr.ClientTransaction=yes support commit and rollback operations.
Action	Correct the JAXR client program.
INMJRE0093	The value "{0}" of slot "{1}" is not a valid "{2}".
Explanation	The given value does not conform to the datatype as specified in the type definition.
Action	Specify a valid value.

INMJRE0094	Trying to modify the value of the ObjectType concept "{0}".
Explanation	It is not allowed to modify the value of a concept in the classification scheme ObjectType.
Action	Correct the client program.
INMJRE0095	Invalid concept value: {0}
Explanation	As described in the JAXR standard, a concept value has to be a valid NCName.
Action	Provide a valid concept value.
INMJRE0096	Trying to use an internal classification scheme ({0}) for an external classification.
Explanation	An external classification requires an external classification scheme.
Action	Supply a correct classification scheme.
INMJRE0097	Trying to save object "{0}" which is marked to be modified without lock.
Explanation	Objects which are marked to be modified without lock cannot be saved.
Action	Correct the client program.
INMJRE0098	Trying to modify an outdated object ("{0}")
Explanation	The application tried to modify a registry object which has been modified by someone else in the meantime.
Action	Make sure to modify only the latest version of a registry object.
INMJRE0099	Repository access error.
Explanation	An error occurred accessing the repository.
Action	Ensure the repository is available. Check there are no resource issues (e.g. lack of disk space).
INMJRE0100	Lock not available for object "{0}"
Explanation	The requested lock could not be granted.
Action	Wait until the lock is available.

INMJRE0103	Cannot handle a collection of values with a simple ParameterInstance
Explanation	A simple non-array ParameterInstance is associated with a single value.
Action	Use a single value.
INMJRE0104	ParameterType mismatch: requested {0}, present {1}
Explanation	The value(s) of a ParameterInstance have to correspond to the type of the respective ParameterTemplate.
Action	Read / set values according to the ParameterType.
INMJRE0105	The readonly property "{0}" must not be modified.
Explanation	Readonly properties can only be added to new objects. Existing property values must not be changed.
Action	Do not modify readonly properties. Do not add readonly properties to existing objects.
INMJRE0106	Login rejected, user "{0}" not registered
Explanation	Each user has to be registered before being used for login.
Action	Register the user.
INMJRE0107	The "login user" option must not be modified for existing users.
Explanation	The "login user" option can only be assigned to new users.
Action	Do not modify an existing user's "login user" option.
INMJRE0108	For an existing user with "login user" option, the name must not be changed.
Explanation	A user with "login user" option has to keep his name.
Action	Do not modify the name of a user with "login user" option.
INMJRE0109	Invalid URI specified for principal: {0}.
Explanation	The URI specified for the principal is not valid. It must be an absolute URI or one with an absolute path. The scheme of "ino:" is not a valid scheme.
Action	Ensure that the URI is valid.

INMJRE0110	"post insert" policy event failed for RegistryObject ("{0}")
Explanation	The enclosed exception explains the reason of the failure.
Action	Analyze the enclosed exception.
INMJRE0111	"post update" policy event failed for RegistryObject ("{0}")
Explanation	The enclosed exception explains the reason of the failure.
Action	Analyze the enclosed exception.
INMJRE0112	"post delete" policy event failed for RegistryObject ("{0}")
Explanation	The enclosed exception explains the reason of the failure.
Action	Analyze the enclosed exception.
INMJRE0113	Please set the mandatory parameter {0} before activating the policy
Explanation	The policy activation verifies whether all mandatory parameters are set. 0 - Name of the mandatory parameter which was not set.
Action	Please set all the mandatory parameters before activating the policy
INMJRE0114	Action {0} does not match the scope of the policy {1}
Explanation	The selected action does not match the scope of the policy 0 - Name of the action 1 - Name of the policy.
Action	Please ensure that the selected action matches the scope of the policy.
INMJRE0115	The name of the default organization must not be changed.
Explanation	The name of the default organization must not be changed.
Action	None
INMJRE0117	Name not specified for user with "login user" option
Explanation	A user without a name cannot have the "login user" option.
Action	Specify a user name.
INMJRE0119	Enumeration not allowed for data type {0}
Explanation	Enumerations are not allowed for data types InternationalString and InternationalRichText.
Action	Do not specify the enumeration option for these data types.

INMJRE0120	Internal error: missing ExternalLink to schema document
Explanation	This is an internal error.
Action	Please contact your software supplier.
INMJRE0121	Internal error: target of {0} external link does not exist.
Explanation	This is an internal error.
Action	Please contact your software supplier.
INMJRE0122	Duplicate type name {0}
Explanation	Each object type is identified by a name consisting of a namespace and a schema name. This name has to be unique.
Action	Provide a unique type name.
INMJRE0123	Trying to remove the primary contact from organization {0} ({1}).
Explanation	Each organization has to have a primary contact. It is not allowed to remove the primary contact.
Action	Do not remove the primary contact from an organization.
INMJRE0124	Cannot delete an ObjectType concept ({0})
Explanation	The taxonomy "ObjectType" contains concepts that represent object types. It is not allowed to delete these concepts.
Action	Do not delete ObjectType concepts.
INMJRE0125	The user "{0}" ({1}) is the owner of, or modified the "{2}" object "{3}" ({4})
Explanation	A user who still owns an object cannot be deleted. Also, if the user modified some object, and the corresponding audit trail entry is still present, deletion is rejected. However, the audit trail can be purged, and after all modification audit trail entries are purged, user deletion will be allowed.
Action	Delete all of the user's objects before deleting the user.
INMJRE0126	Attempt to modify a readonly privilege
Explanation	Readonly privileges must not be modified.
Action	Do not modify a readonly privilege.

INMJRE0127	Unsupported data type '{0}'
Explanation	The requested datatype is not supported.
Action	This is an internal error. Please contact your software supplier.
INMJRE0128	Illegal usage of deny ACE
Explanation	An ACE with deny can only be used with principal ALL and privilege ALL.
Action	Correct the ACE.
INMJRE0129	Not a valid revision object
Explanation	The object specified is not a object from the revision part.
Action	Check objects for the revision restore.
INMJRE0130	Expected revision object not present
Explanation	Unexpectedly a revision object could not be located. Obviously there is no version present of the actual object.
Action	Contact your software supplier because there is a structural problem with the revision part.
INMJRE0131	Revision object must not be modified ("{0}")
Explanation	Revision object must not be modified, these objects are readonly.
Action	Check your objects.
INMJRE0132	Invalid revision object encountered ("{0}")
Explanation	Invalid revision object encountered. The keys must be the same but are different.
Action	Check registry objects.
INMJRE0133	The "{0}" to be deleted ({1}) is an intermediate version object
Explanation	The object to be deleted is a target of a version association and must not be explicitly deleted.
Action	To delete objects of old versions use the purge() methods of the VersionManager interface.

INMJRE0134	Login rejected, user "{0}" not active
Explanation	Deactivated users cannot log in.
Action	Activate the user.
INMJRE0135	Association type "{0}" already used in this asset type
Explanation	There can be only one association of type "Implements" per asset type. You attempted to create such an attribute, but one exists already.
Action	Use a different association type.
INMJRE0136	Uploaded computed profile zip does't contain computed implementation
Explanation	the zip does not the class which implements the interfaces like {0}
Action	Make sure the computed profile implementation bundled in zip
INMJRE0138	User "{0}" is still the primary contact of organization "{1}"
Explanation	A user cannot be deleted if this user is still the primary contact of an organization.
Action	Do not delete primary contact users.
INMJRE0139	Taxonomy "{0}" still used to classify object "{1}"
Explanation	An external taxonomy cannot be deleted as long as it is referenced by classifications.
Action	Remove the classifications before deleting the taxonomy.
INMJRE0140	The association type to be deleted ({0}) is used by an association ({1}). The association belongs to the {2} object "{3}".
Explanation	An association type cannot be deleted if there are still associations of that type.
Action	Delete all associations of that type before deleting the association type.
INMJRE0141	Untyped RegistryEntry "{0}" must not be saved
Explanation	Java RegistryEntry objects are used to represent instances of user-defined types. In order to make a RegistryEntry an instance of a type, it has to be classified with the corresponding type concept.
Action	Save only typed RegistryEntries.

INMJRE0142	must not replace existing type concept
Explanation	This is an internal error.
Action	Please contact your software supplier.
INMJRE0143	duplicate target type "{0}"
Explanation	For a Relationship attribute the same target type was specified twice.
Action	Specify each target type only once.
INMJRE0144	invalid maxOccurs value "{0}"
Explanation	Allowed values for maxOccurs are "1" and "unbounded".
Action	Specify a valid value.
INMJRE0145	invalid minOccurs value "{0}"
Explanation	Allowed values for minOccurs are "0" and "1".
Action	Specify a valid value.
INMJRE0146	Missing taxonomy for classification attribute "{0}"
Explanation	Each classification attribute needs a taxonomy.
Action	Specify a taxonomy.
INMJRE0147	For the classification attribute "{0}", the default value "{1}" does not belong to the taxonomy "{2}".
Explanation	The default value needs to belong to the taxonomy.
Action	Select a concept from the taxonomy as the default value.
INMJRE0148	Missing association type for relationship attribute "{0}"
Explanation	Each relationship attribute needs an association type.
Action	Specify an association type.
INMJRE0149	duplicate attribute name "{0}"
Explanation	Attribute names have to be unique within classification, relationship, and file attributes.
Action	Choose a unique attribute name.

INMJRE0150	trying to access a deleted type
Explanation	After a type was deleted, the corresponding Java instance must no longer be used.
Action	Correct the client program.
INMJRE0151	must not rename existing type's schema name
Explanation	The schema name uniquely identifies a type, it must not be modified.
Action	Do not rename an existing schema name.
INMJRE0152	Cannot save object due to missing lifecycle state. The object "{0}" is classified with lifecycle state "{1}" which does not exist.
Explanation	A call to saveObjects fails, when a saved object contains a lifecycle state classification which does not exist. This can occur after importing objects, when the lifecycle model data has not been imported beforehand.
Action	Make sure that any referenced lifecycle models are available in the registry before importing objects that refer to them.
INMJRE0153	Invalid attribute "{0}" applied to object of type "{1}"
Explanation	A setAttributeValue() or getAttributeValue() operation was issued against a registry object whose type does not contain the specified attribute.
Action	Correct the application.
INMJRE0154	Conflicting aggregation settings
Explanation	A relationship attribute can be aggregating, or reversely aggregating, but not both.
Action	Choose a correct aggregation setting.
INMJRE0155	"{0}" is not a virtual type
Explanation	The given type concept is not a virtual type.
Action	Please supply a virtual type.
INMJRE0156	The delete operation failed due to a hidden association.
Explanation	The object to be deleted is still the target of an association. However, the user that tries to delete the object does not have view permissions on the association and its source object. Probably a CentraSite administrator with full permissions is required to perform the delete operation.
Action	Please contact your CentraSite administrator.

INMJRE0158	The locale {0} is not contained in the set of restricted locales.
Explanation	The set of restricted locales defines which locales may be used when creating a value for an InternationalString.
Action	Choose a different locale.
INMJRE0159	Invalid or missing default locale
Explanation	When defining the set of restricted locales, exactly one locale needs to be marked as the default locale.
Action	Specify a proper default locale.
INMJRE0160	The "{0}" package to be deleted ({1}) still has members, e.g. the {2} object "{3}" with key "{4}".
Explanation	A registry package cannot be deleted if it still has members.
Action	Delete the members before deleting the registry package.
INMJRE0161	no value provided for required attribute {0} of {1} "{2}"
Explanation	The attribute is defined with the "required" option, but the attribute value was not supplied when storing the object.
Action	Provide a value for the attribute.
INMJRE0162	too many values provided for single-value attribute {0} of {1} "{2}"
Explanation	For single-value attributes, at most one value may be provided.
Action	Provide a correct attribute value.
INMJRE0163	Internal error: cannot construct a RegistryObject from {0}.
Explanation	This is an internal error.
Action	Contact your software provider.
INMJRE0164	Internal error: missing object id for {0}
Explanation	This is an internal error.
Action	Contact your software provider.

INMJRE0165	Cannot modify attribute {0} of type {1} to be required, because it does not exist in the object with key "{2}"
Explanation	While updating a type description, an attribute was modified to be a required attribute. This modification however can only be done when the attribute is already present in all existing objects of the type (which is trivially true if there are no existing objects), or it has been equipped at the same time with a default value.
Action	Define a default value for the attribute, or refrain from setting the attribute to "required", then retry the modification only after the attribute has been added to all existing objects of the given type.
INMJRE0166	Failed to check that the given profile is a computed profile
Explanation	While parsing the uploaded zip file, an unexpected exception occurred.
Action	Please make sure the uploaded zip file is not corrupted.
INMJRE0167	Uploaded computed profile implementation zip file does not contain profile implementation class, which implements the interface like {0}
Explanation	The uploaded computed profile implementation zip file does not contain the class that implements the interface like {0}.
Action	Please make sure the zip file contains the computed profile implementation.
INMJRE0168	Default value should be given for all required attributes when the types have instances. Please provide the default value for the required attribute "{0}".
Explanation	When updating an asset type which already has instances, all the required attributes of that type should be provided with default values.
Action	Ensure that all the required attributes of the edited asset type have default values.
INMJRE0169	Predefined attributes cannot be deleted.
Explanation	You cannot delete the predefined attributes.
Action	You cannot delete the predefined attribute.
INMJUE0001	Check your access rights and the proxy settings
Explanation	The accessing user does not have sufficient privileges for the target object.
Action	Do the action as a more privileged user.

INMJUE0005	No privilege to access target object from object: {0}
Explanation	The accessing user does not have sufficient privileges for the target object.
Action	Do the action with a more privileged user.
INMJUE0006	Uploaded computed profile implementation zip doesn't contain profile implementation class, which implements the interface like {0}
Explanation	The uploaded computed profile implementation zip file does not contain the class that implements the interface like the one shown.
Action	Make sure the zip file contains the computed profile implementation.
INMJUE0007	Failed to check that a given profile is a computed profile
Explanation	While parsing the uploaded zip file an unexpected exception occurred.
Action	Make sure that the uploaded zip file is not corrupted.
INMJUW0002	The associated object of type "External Link" could not be deleted
Explanation	This can happen while deleting virtual services.
Action	No action required.
INMJUW0003	The associated object of type "WS-Policy attachment" could not be deleted
Explanation	This can happen when deleting virtual services.
Action	No action required.
INMJUW0004	The associated object of type "Associated with" could not be deleted
Explanation	This can happen when deleting virtual services.
Action	No action required.
INMLFE0001	Provider not set for {0}
Explanation	The LCM factory could not be initialized since the property for the provider class is not set appropriately.
Action	Please check the javadoc of the LCM API to set the appropriate property.

INMLFE0002	Provider {0} not found
Explanation	The LCM provider class could not be loaded.
Action	Please check that the name of provider class is appropriately set and is available for class loading.
INMLFE0003	Provider {0} could not be instantiated
Explanation	An exception occurred while trying to load the provider class.
Action	Please check that the name of provider class is appropriately set and is available for class loading
INMLFE0004	No initial state defined
Explanation	There should be an initial state defined for any lifecycle model.
Action	Please make sure that there is an initial state defined for the lifecycle model.
INMLFE0005	The state(s) {0} are unreachable
Explanation	It should be possible to traverse to each state within a lifecycle model from the initial state 0 - name(s) of the state(s) unreachable from the initial state.
Action	Please make sure that each state is reachable from the initial state in the lifecycle model.
INMLFE0006	A lifecycle model should have at least one end state
Explanation	Any lifecycle model should have at least one state that does not have a next state.
Action	Please make sure that the lifecycle model has at least one end state.
INMLFE0007	The given object type {0} cannot be LCM enabled
Explanation	Only asset types, policies and lifecycle models can be LCM enabled 0 - name of the invalid object type
Action	Please make sure that an appropriate object type that can be LCM enabled is used.
INMLFE0008	The state {0} cannot be set as an initial state. The state is currently not present in the lifecycle model.
Explanation	Only states which are already part of the lifecycle model can be set as an initial state.
Action	Please make sure that you add the state to the lifecycle model before setting it as the initial state.

INMLFE0009	The state {0} cannot be set as a preferred next state. The state is currently not a next state.
Explanation	Only states which are part of the next states can be set as preferred next state 0 - name of the invalid preferred next state.
Action	Please ensure that the state is part of the next states before setting it as the preferred next state.
INMLFE0010	Each lifecycle model should belong to an organization
Explanation	Each LCM should belong to one organization.
Action	Please assign an organization to which the lifecycle model belongs.
INMLFE0011	It is only possible to define a lifecycle model for lifecycle models in CentraSite Active SOA version
Explanation	A lifecycle model for lifecycle models can only be defined in the CentraSite Active SOA edition.
Action	No action required.
INMLFE0012	{0} is not a type in CentraSiteRegistryTypes taxonomy
Explanation	The concept used for the registry type should belong to the predefined CentraSiteRegistryTypes taxonomy 0 - key of the invalid concept.
Action	Please use a concept that belongs to the predefined CentraSiteRegistryTypes taxonomy.
INMLFE0014	A type with the given name {0} was not found
Explanation	No object type was found with the given name 0 - name of the given object type.
Action	Please specify a valid type name.
INMLFE0015	No active lifecycle model for the given registry object found
Explanation	The given registry object is not associated with any active lifecycle model.
Action	No action required.
INMLFE0016	The given state {0} is not a valid follow up state of {1} for the given registry object {2}
Explanation	The current state of the registry object does not have a state transition to the specified target state. 0 - specified target state 1 - current state of the registry object 2 - name of the registry object.
Action	Please ensure that there is a valid state transition from the current state of the registry object to the specified target state.

INMLFE0017	The given registry object is never in a work flow to change its state
Explanation	The given registry object cannot be approved or rejected since it was never in a work flow to change its state.
Action	No action required.
INMLFE0018	For each object type, only one lifecycle model can be active per organization
Explanation	For any object type and organization, there can be at most one active LCM.
Action	Please make sure that there are no active LCMs associated with the given object type and organization, before trying to activate this LCM.
INMLFE0019	A promotion node can be set only on the final states of the lifecycle model
Explanation	Promotion nodes be only be set for final states of a lifecycle model.
Action	Please make sure that promotion nodes are set only for final states.
INMLFE0020	The registry object is in a workflow to change its state
Explanation	Next states cannot be determined for a registry object with a pending state change.
Action	No action required.
INMLFE0021	The given registry object is not a user or a role or a group that could be used to restrict transitions to the state
Explanation	The registry object used to restrict transitions to the state should be either a user or group or role. No other type of registry object can be used.
Action	Please make sure that the registry object used to restrict transitions to the state is either a user or a group or a role.
INMLFE0022	The current user is not allowed to perform the state transition
Explanation	The current user does not have the necessary permissions to perform the requested state transition.
Action	Please make sure that the current user has the necessary permissions to perform the requested state transition.
INMLFE0024	Failed to set the initial state for the registry object {0}
Explanation	The registry object could not be set to the initial state of the life cycle model since there is an approval work flow.
Action	Please make sure that there are no approval work flows triggered for the initial state of the LCM.

INMLFE0026	The lifecycle model is deleted!
Explanation	Deleted lifecycle models cannot be reused.
Action	Please use an existing lifecycle model and do not refer to deleted lifecycle models.
INMLFE0027	The lifecycle model is not associated with any types
Explanation	Each lifecycle model should be associated with at least one object type.
Action	Please choose at least one object type which will be associated with the lifecycle model.
INMLFE0028	Internal error: User {0}/{1} does not belong to any organization
Explanation	The logged in user does not belong to any organization 0 - Name of the user 1 - Key of the user.
Action	Please make sure that the logged in user belongs to some organization.
INMLFE0029	Internal error: please specify the organization for which the lifecycle model has to be found
Explanation	A lifecycle model can be found only in the context of an organization for which the registry object is to be created.
Action	Please specify the organization for which the lifecycle model has to be found.
INMLFE0030	{0} lifecycle model cannot be modified
Explanation	A lifecycle model which is active or in a state after active cannot be modified.
Action	Please ensure that the lifecycle model is in a state before active so that it can be modified.
INMLFE0031	The lifecycle model cannot be deleted!
Explanation	The lifecycle model could not be deleted because of an internal exception.
Action	Please look at the exception for more details.
INMLFE0032	The model cannot be set to state {0}
Explanation	The lifecycle model could not be set to the given state since it is not a valid transition from the current state of the model 0 - name of the invalid state.
Action	Please make sure that the model is set to a state that is a valid transition from its current state.

INMLFE0033	Transition from any state to initial state is not allowed
Explanation	Transition from any state to initial state is not allowed.
Action	Transition from any state to initial state is not allowed.
INMLFE0034	The lifecycle model cannot be activated since the older version of this model could not be superseded
Explanation	The lifecycle model which is a newer version of some other model could not be activated since the older version model could not be marked as superseded.
Action	Please ensure that the older version model can be marked as superseded before activating the newer lifecycle model.
INMLFE0035	An active lifecycle model cannot be deleted
Explanation	An attempt was made to delete an active lifecycle model.
Action	An active lifecycle model cannot be deleted.
INMLFE0036	State transition can only be made between states which belong to the same lifecycle model
Explanation	There are state transitions which have been made between states which belong to different lifecycle models.
Action	Please ensure that the state transitions are not made between states of two different lifecycle models.
INMLFE0037	Lifecycle Model for Lifecycles cannot be deleted
Explanation	The predefined lifecycle model for lifecycles cannot be deleted.
Action	No action required.
INMLFE0038	Policy Lifecycle cannot be deleted
Explanation	The predefined lifecycle model for policies cannot be deleted.
Action	No action required.
INMLFE0041	Intermediate versions of a Lifecycle cannot be deleted using 'Delete' option
Explanation	There are two options to delete a lifecycle and its version objects, namely 'Delete' and 'Purge'. The 'Delete' option can be used only for the latest version of the lifecycle.
Action	Deletion will not be allowed.

INMLYE0002	Lifecycle Model Name should not be empty
Explanation	The model name is mandatory.
Action	Enter the model name.
INMLYE0003	Stage Name should not be empty
Explanation	The stage name is mandatory.
Action	Enter the stage name.
INMLYE0005	Only one row can be moved down
Explanation	For the order of the lifecycle state, only one row can be moved up or down.
Action	While moving down any lifecycle state, please ensure that only one state is selected.
INMLYE0007	Only one row can be moved up
Explanation	To order the LC State, only one row can be moved up.
Action	Lifecycle state order.
INMLYE0008	Lifecycle model(s) should be selected for saving report
Explanation	Saving a report should have one LCM object.
Action	Saving a report should have one LCM object.
INMLYE0009	Two state names cannot have the same name
Explanation	There is a duplicate state name.
Action	Choose a unique state name.
INMPPEE0003	Namespace {0} does not match any of the possible namespaces {1}
Explanation	Service namespace is validated against the set of possible namespaces as specified by the policy. 0 - Namespace of the service 1 - Allowed namespaces from policy.
Action	Please ensure that the namespace of the service matches at least one of the allowed namespaces.
INMPPEE0009	Policy {0} cannot be deactivated since an approval triggered by the policy for {1} {2} is in progress
Explanation	Since there is an approval which is in progress, this policy cannot be deactivated. 0 - Name of the policy 1 - Type of the object which is pending 2 - Name of the object which is pending.
Action	Please complete the approval flow for the specific object and then deactivate the policy.

INMP EE0013	Organization {0} should have Administrator
Explanation	Every organization should have an administrator assigned 0 - Name of the organization
Action	Please ensure that the organization has an administrator assigned to it.
INMP EE0016	{0} {1} must be classified by taxonomy {2}
Explanation	The given registry object is validated to be classified by the given taxonomy. 0 - Type name of the object 1 - Registry Object name 2 - Taxonomy node name.
Action	Please ensure that the registry object is classified by the given taxonomy.
INMP EE0021	Policy without any actions cannot be executed
Explanation	A policy without any actions cannot be executed.
Action	Please assign some actions to this policy.
INMP EE0030	Service WSDL size {0} does not conform with the specified size {1}
Explanation	The service WSDL size does not match the size specified by the policy. 0 - WSDL size of the service 1 - WSDL size specified in the policy.
Action	Please ensure that the WSDL size of the service conforms with the specified size.
INMP EE0031	{0} name {1} does not conform with the pattern {2}
Explanation	The registry object name does not match the specified pattern. 0 - Type of the registry object 1 - Name of the registry object 2 - Name pattern specified in the policy.
Action	Please ensure that the name of registry object conforms to the specified pattern.
INMP EE0039	Service Binding Type(s) {0} are missing in the WSDL. The mandatory bindings specified in the policy are {1}
Explanation	The binding types of the service are validated against the specified bindings. 0 - Violating binding types of the service 1 - Binding types specified by the policy.
Action	Please ensure that the service binding types conform to the specified binding types.
INMP EE0043	User does not have the permission to create {0}
Explanation	The user does not have the required permission to create an object of the given type. {0} refers to the object type for which the user is creating an instance.
Action	Please assign the necessary permissions to the user before trying to create an object of the type.

INMP EE0045	Namespace cannot be empty for {0} {1}
Explanation	The namespace of the applied object is empty. {0} - type of the applied object {1} - name of the applied object.
Action	Please ensure that the namespace is provided for the object.
INMP EE0046	Description is empty for {0} {1}
Explanation	The description of the registry object is empty. 0 - Type of the registry object 1 - Name of the registry object.
Action	Please make sure that the registry object has a non-empty and valid description.
INMP EE0047	Name is empty for {0}
Explanation	The name of the registry object is empty 0. - Type of the registry object.
Action	Please make sure that the registry object has a non-empty and valid name.
INMP EE0048	Policy {0} cannot be activated since there is a newer active version of this policy
Explanation	Since there is a newer version of this policy which is active, the policy cannot be activated.
Action	Please use the newest active version of the policy for enforcement.
INMP EE0049	Policy {0} cannot be activated since the older version of the policy could not be superseded
Explanation	The policy which is a newer version of some other policy could not be activated since the older version could not be marked as superseded.
Action	Please ensure that the older version policy can be marked as superseded before activating the newer policy.
INMP EE0052	{0} description {1} does not conform with the pattern {2}
Explanation	The registry object description does not conform to the pattern specified in the policy. 0 - Type of the registry object 1 - Description of the registry object 2 - Description pattern specified in the policy.
Action	Please ensure that the description of the registry object conforms to the specified pattern.

INMP EE0057	{0} {1} does not belong to an LCM state
Explanation	The registry object does not belong to an LCM state. 0 - Type name of the object 1 - Name of the object.
Action	Please ensure that the registry object is set to an appropriate LCM state.
INMP EE0059	{0} {1} belongs to state {2} which does not conform to the allowed states {3}
Explanation	The LCM state of the registry object is validated against the allowed states specified in the policy. 0 - Type name of the registry object 1 - Name of the registry object 2 - Current state name of the registry object 3 - Allowed states specified in the policy.
Action	Please ensure that the registry object is set to an appropriate LCM state.
INMP EE0064	{0} {1} does not have a value set for attribute {2}
Explanation	The registry object does not have a value set of the specified attribute. 0 - Type of the registry object 1 - Name of the registry object 2 - Attribute name specified in the policy.
Action	Please ensure that the object has a value set for the specific attribute.
INMP EE0066	{0} {1} has value {2} set for attribute {3} which does not conform to the allowed values {4}
Explanation	The registry object has a value set of the specified attribute which does not conform to the allowed values. 0 - Type of the registry object 1 - Name of the registry object 2 - Attribute value of the registry object 3 - Attribute name specified in the policy 4 - Allowed attribute values specified in the policy.
Action	Please ensure that the object has an appropriate value set for the specific attribute.
INMP EE0069	Policy {0} cannot be activated as some mandatory action parameters are not set
Explanation	The policy has some mandatory parameters which are not set, so the policy cannot be activated. 0 - Name of the policy.
Action	Please ensure that all mandatory parameters of the policy are set before activation.
INMP EE0071	Priority for a policy should be between {0} and {1}
Explanation	The priority for a policy should be within the specified limits.
Action	Please enter a priority within the specified limits.

INMP0072	Policy action rule {0} is invalid
Explanation	The action.properties file is not accessible for this policy action rule. 0- name of the policy action.
Action	Please enter the correct rule file for the policy action.
INMP0073	{0} is not a valid Groovy script
Explanation	The action file is not a valid Groovy script. 0 – name of the Groovy script.
Action	Please upload a valid Groovy script.
INMP0074	Result message not set for Groovy action {0}
Explanation	The Groovy script did not set the result object. 0 – name of the Groovy action.
Action	Set the result inside the Groovy action.
INMP0087	Active user {0} cannot be deleted.
Explanation	Only deactivated users can be deleted in CentraSite. {0} specifies the user name.
Action	Deactivate the user before deletion.
INMP0089	Organization level permission for {0} is not created yet for organization {1}
Explanation	Firstly we have to create an organization before creating any registry object for an organization. This is because organization level permissions of that organization are used in instance level permission for those registry objects. 0 – name of the registry object 1 – name of the organization.
Action	Create the organization first.
INMP0091	User cannot update the role {0} with permissions that he does not have
Explanation	A user can assign permissions that he has to a role. If a user tries to update a role with a permission that he does not have, then this error will be thrown. 0 – name of the role.
Action	Please ensure that the user has the permissions that he is assigning to a role.
INMP0092	{0} cannot be deleted
Explanation	The default organization cannot be deleted.
Action	Do not try to delete the default organization.

INMPEE0094	Policy {0} cannot be activated since an active older version of the policy has a pending approval
Explanation	Since there is an older version of this policy which is active and has a pending approval, this newer policy version cannot be activated. 0 – name of the policy.
Action	Please ensure that any approval triggered by the older active version of this policy gets completed before activating the newer version.
INMPEE0102	Organization Primary Contact has to be an active user
Explanation	A deactivated user cannot become the primary contact of an organization.
Action	Please assign an active user as the primary contact of an organization.
INMPEE0104	User cannot assign the role {0} to a user/group that he cannot manage
Explanation	If a user with "Manage Users" permission in one organization tries to assign a role from another organization or a system level role to his own organization's user, then this error message will be thrown.
Action	The user needs to have the "Manage Users" permission of the role's organization (if it is an organization level role) or the user should have the "Manage System-wide Roles" permission if it is a system level role. Only then can the user assign that role to a user.
INMPEE0105	User cannot create the Role {0} with permissions that the user does not have
Explanation	A user can update the role only with the permissions that he possesses. If a user with Organization level "Manage Users" permission or "Manage System-wide Roles" permission tries to update a role then this user can assign only the permission that he/she already has, otherwise this error message will be thrown.
Action	Please ensure that the user has the permissions that he/she is assigning to a role.
INMPEE0106	Action class {0} not found in {1}
Explanation	The action class mentioned in the properties file should be present in the action rule archive. 0 – name of the executable class, 1 – name of the action rule archive.
Action	The action class mentioned in the properties file is not present in the action rule archive. Please make sure the class mentioned in the property file is present in the archive.

INMP00110	WS-I actions should not be combined with other actions in a single policy
Explanation	A policy containing WS-I actions cannot contain any actions other than WS-I policy actions
Action	Make sure WS-I actions are not combined with other actions in a single policy.
INMP00111	Dependent actions {0} for {1} is not included
Explanation	Dependent actions of a WS-I action are not included. 0 – name of the missing dependent WS-I action, 1 - name of the included WS-I action.
Action	Dependent actions of a WS-I action should be included in a policy.
INMP00113	There are no lifecycle states associated with the {0} event for the policy {1} and hence this policy cannot be activated
Explanation	The pre/post state change policy does not have any lifecycle states associated with it and hence the policy will not be executed for any state transition. Hence this policy cannot be activated. 0 - Pre/Post State Change event, 1 - Name of the policy.
Action	Please ensure that the policy is associated with the appropriate lifecycle states for the pre/post state change events
INMP00114	Lifecycle state {0} from {1} does not match the scope of the policy {2}
Explanation	The lifecycle state associated with the policy does not correspond to the object types specified in the scope of the policy. 0 - Name of the lifecycle state associated with this policy, 1 - Name of the lifecycle model to which this state belongs, 2 - Name of the policy.
Action	Please ensure that the lifecycle states associated to the policy belong to a lifecycle model whose object type conform to the object types specified in the policy scope
INMP00115	Consumer Registration Request {0} is not associated with any asset
Explanation	A consumer registration request object must be associated with an asset. 0 – Name of the consumer registration request.
Action	Associate the consumer registration request object with an asset using an association with the association type "relatedTo". The source object of the association is the consumer registration request. The target object of the association is the asset.
INMP00118	{0} {1} is pending on state change. So it cannot be modified or deleted.
Explanation	The object has a pending state change. So this object cannot be modified or deleted. 0 - Type of the object 1 - Name of the object.
Action	If you want to modify or delete the object, release the object from the pending state. If there are pending approvals, get them completed.

INMP EE0120	Attribute {0} is read only and hence cannot be set for {1} {2}
Explanation	Since the attribute is read only, the given attribute value cannot be set for the registry object. 0 - Name of the read only attribute, 1 - Type of the registry object, 2 - Name of the registry object.
Action	Please ensure that the chosen attribute is not a read only attribute.
INMP EE0129	Initial State {0} cannot be used to define policy on Pre-State Change event
Explanation	Pre-state change policies cannot be defined on initial states of any lifecycle model. 0 - Name of the initial state associated with the policy.
Action	Please use a lifecycle state other than the initial state to define the pre-state change policy.
INMP EE0136	Policy action {0} is used, so it cannot be edited or deleted
Explanation	If the policy action is used by any other policy, the policy action can't be edited or deleted.
Action	Before editing or deleting any policy action, the user has to verify whether any policy is using this action or not.
INMP EE0142	{0} {1} has a pending approval and hence cannot be moved
Explanation	The registry object has an approval in pending state. So it cannot be moved to a new owner and/or organization. 0 - Type of the registry object 1 - Name of the registry object.
Action	Please complete the pending approval for the registry object before moving it.
INMP EE0143	{0} {1} has a pending consumer registration request and hence cannot be moved
Explanation	The registry object has a pending consumer registration, so it cannot be moved to a new owner and/or organization. 0 - Type of the registry object 1 - Name of the registry object.
Action	Please complete the consumer registration request for the registry object before moving it.
INMP EE0144	{0} {1} is an internal object of CentraSite and hence cannot be moved
Explanation	Internal objects of CentraSite cannot be moved.
Action	Internal objects of CentraSite cannot be moved.

INMP EE0145	{0} {1} cannot be moved to inactive or internal users of CentraSite
Explanation	Ownership of the registry object cannot be transferred to inactive or internal users of CentraSite. 0 - Type of the registry object 1 - Name of the registry object.
Action	Please ensure that the new owner for the registry object is an active and non-internal user of CentraSite.
INMP EE0146	The mandatory attribute {0} does not have value for this object
Explanation	An attribute should have a value for a registry object if it is marked as required.
Action	Provide appropriate value(s).
INMP EE0148	Only user with CentraSite Administrator role can do the change ownership action
Explanation	Only a user with the CentraSite Administrator role can do the change ownership action.
Action	Please make sure that you log in as a user who has CentraSite Administrator role to perform the ownership change.
INMP EE0149	Only user with CentraSite Administrator role can do the change organization action
Explanation	Only a user with the CentraSite Administrator role can do the change organization action for assets.
Action	Please make sure that you log in as a user who has the CentraSite Administrator role to perform the organization change.
INMP EE0150	Internal users cannot be moved across organizations.
Explanation	If the user is trying to move any of the predefined or internal users from one organization to another organization, this error message will be displayed.
Action	Remove the predefined/internal users from the list for moving users across organizations.
INMP EE0151	Owner for the object {0} of type {1} is not present in CentraSite
Explanation	The owner for the object is not present in CentraSite. {0} - Name of the object {1} - Type of the object.
Action	The owner should not be allowed to be removed from CentraSite while owning some objects. So, identify how the owner was removed from CentraSite with this object dependency and report a bug.

INMP EE0153	View permission on {0} {1} is not available for {2} {3}
Explanation	The view permission on the registry object is not available for the specific user or group. 0 - Type of the registry object for which the profile permissions are being set 1 - Name of the registry object 2 - User or Group 3 - Name of the user or group.
Action	Please set the view permission on the registry object for the specific user or group before setting the profile permissions.
INMP EE0154	Modify permission on {0} {1} is not available for {2} {3}
Explanation	The modify permission on the registry object is not available for the specific user or group. 0 - Type of the registry object for which the profile permissions are being set 1 - Name of the registry object 2 - User or Group 3 - Name of the user or group.
Action	Please set the modify permission on the registry object for the specific user or group before setting the profile permissions.
INMP EE0156	The new owner {0} does not have create asset permission in organization {1}
Explanation	An attempt was made to move an asset to a user who does not have "create assets" permission in the asset's organization.
Action	Assign the Asset Provider role or any custom role which contains the "create assets" permission in the asset' organization to the target user.
INMP EE0167	The RejectHandler policy prohibited the operation for {0} {1}
Explanation	Operations like "move", "delete", etc. are only allowed for specific object types.
Action	Correct the application program.
INMP EE0175	Virtual Service {0} cannot be deleted because it has been deployed to the target.
Explanation	This error message is thrown when you are attempting to delete the virtual service which is deployed to a target.
Action	Undeploy the virtual service before attempting to delete.
INMP EE0176	Target Information not available for the Deployment Operation
Explanation	A target is mandatory for deployment operations of Virtual Service/Virtual XML service/Virtual REST service/Consumer Application.
Action	Trigger deployment from the deployment profile.

INMP EE0180	IS Service Interface {0} should have at least one associated IS Service Object, hence the corresponding REST service is not created.
Explanation	The IS Service Interface object should have at least one associated IS Service Object.
Action	Make sure at least one IS Service Object (HTTP methods get, put, post and delete) is associated to the IS Service Interface and also make sure the name of the IS Service Object should contain the following strings (get, put, post and delete) appropriate to the method definition.
INMP EE0181	REST Service {0} should have at least one native endpoint, hence the corresponding REST service is not created.
Explanation	The REST service published from the webMethods product suite should have at least one native endpoint.
Action	Make sure the port attribute (IS Server object) has a value defined.
INMP EE0184	Cannot remove the existing life cycle state from the object {0}
Explanation	It is not possible to remove the existing life cycle state from the given object
Action	No action required.
INMP EE0185	{0} {1} must be classified by at least one of {2}
Explanation	The given registry object is validated to be classified by the given taxonomy or category. 0 - Type name of the object 1 - Registry Object name 2 - Taxonomy node name or category node name.
Action	Please ensure that the registry object is classified by the given taxonomy or category.
INMP EE0190	Unable to delete the exported archive file
Explanation	The intermediate archive file created for asset promotion could not be deleted.
Action	No action required.
INMP EE0204	The mandatory attribute {0}, of {1} "{2}" does not have a value
Explanation	The mandatory attribute {0} of {2} created from type {1} does not have a value. Attribute {0} has been marked "required" in the definition of type {2} and hence should have a value.
Action	Provide a value for the attribute {0} or provide a default value for the attribute in the definition of type {2}.

INMPEE0206	The validation pattern "{0}" is invalid for policy "{1} at {2}". Repair the regular expression pattern.
Explanation	The validation policy action of the specified policy contains an invalid/unsupported regular expression pattern.
Action	Specify a syntactically correct regular expression for the policy action.
INMPEE0210	Key Generator Policy is not enabled for the API {0}
Explanation	The Key Generator Policy for the given API is not generated.
Action	Contact the API provider.
INMPEE0211	Onboarding Organization {0} with Administrator User {1} has failed
Explanation	Onboarding the given organization with the given administrator user of that organization has failed.
Action	Contact the CentraSite administrator.
INMPEE0212	Onboarding User {0} in Organization {1} has failed
Explanation	Onboarding of the given user has failed in the given organization.
Action	Contact the organization administrator.
INMPEE0218	API key revocation failed.
Explanation	The specified API key could not be revoked. This problem can occur because the requestor does not have the required permission to revoke API key.
Action	Only a user with Administrator or Asset Provider role can revoke API keys.
INMPEI0002	Namespace {0} matches one of the possible namespaces {1}
Explanation	The service namespace validated against the set of possible namespaces as specified by the policy. 0 - Namespace of the service 1 - Allowed namespaces from policy.
Action	No action required.
INMPEI0004	User {0} does not have the role specified in the policy
Explanation	Since the user does not have the role specified in the policy, the role group policy is not applicable for the user 0 - Name of the user.
Action	No action required.

INMPEI0005	Attribute {0} is not applicable for {1} {2}
Explanation	The specified attribute is not applicable for the given object. 0 - Name of the attribute 1 - Type of the object 2 - Name of the object.
Action	No action required.
INMPEI0006	Policy {0} was successfully validated for activation
Explanation	The policy was successfully validated for activation. 0 - Name of the policy.
Action	No action required.
INMPEI0007	LC Model {0} was successfully validated for activation
Explanation	The lifecycle was successfully validated for activation. 0 - Name of the lifecycle model.
Action	No action required.
INMPEI0008	Policy {0} was successfully validated for deactivation
Explanation	The policy was successfully validated for deactivation. 0 - Name of the policy.
Action	No action required.
INMPEI0010	Permissions assigned successfully for {0} {1}
Explanation	Default permissions were assigned successfully for the given registry object. 0 - Type of the object 1 - Name of the object.
Action	No action required.
INMPEI0012	User {0} was assigned to organization groups successfully
Explanation	The user was assigned to organization groups successfully. 0 - Name of the user.
Action	No action required.
INMPEI0014	Organization {0} has Administrator
Explanation	The given organization has an administrator assigned to it. 0 - Name of the organization.
Action	No action required.

INMPEI0015	{0} {1} is classified by taxonomy {2}
Explanation	The given registry object is validated to be classified by the given taxonomy. 0 - Type name of the object 1 - Registry object name 2 - Taxonomy node name.
Action	No action required.
INMPEI0017	Default Roles, Permissions and Groups created successfully for Organization {0}
Explanation	Default roles, permissions and groups were created successfully for the given organization. 0 - Name of the organization.
Action	No action required.
INMPEI0018	Default Roles, Permissions and Groups deleted successfully for Organization {0}
Explanation	Default roles, permissions and groups were deleted successfully for the given organization. 0 - Name of the organization.
Action	No action required.
INMPEI0019	Adding {0} privilege for {1} {2} on {3} {4}
Explanation	The chosen privilege on the given registry object was successfully added for the particular user/group. 0 - View/Modify 1 - User/Group 2 - Name of the user/group 3 - Type of the registry object 4 - Name of the registry object.
Action	No action required.
INMPEI0022	Default roles, groups, permissions and SDL for organization {0} created successfully
Explanation	Default roles, groups, permissions and SDL were created successfully for the given organization. 0 - Name of the organization.
Action	No action required.
INMPEI0023	Default roles, groups, permissions for organization {0} removed successfully
Explanation	Default roles, permissions and groups were removed successfully for the given organization. 0 - Name of the organization.
Action	No action required.
INMPEI0024	User creation policy for User {0} was successful
Explanation	The user was successfully added to the default groups of the organization to which the user belongs. 0 - Name of the user.
Action	No action required.

INMPEI0025	Request Approval Flow {0} for {1} created successfully
Explanation	Request approval flow with the specified name was created successfully for the object. 0 - Approval Flow Name 1 - Name of the object for which approval is triggered.
Action	No action required.
INMPEI0026	Default instance level permissions for Asset {0} were assigned successfully
Explanation	Default instance level permissions were successfully assigned for the given asset. 0 - Name of the asset.
Action	No action required.
INMPEI0027	Email with subject {0} successfully sent to {1}
Explanation	An email with the given subject was successfully sent to the recipients. 0 - Subject of the sent email 1 - email address of the recipient(s).
Action	No action required.
INMPEI0029	Service WSDL size {0} conforms with the specified size {1}
Explanation	The service WSDL size validated against the size specified by the policy. 0 - WSDL size of the service 1 - WSDL size specified in the policy.
Action	No action required.
INMPEI0032	{0} name {1} conforms with the pattern {2}
Explanation	The registry object name matches the specified pattern. 0 - Type of the registry object 1 - Name of the registry object 2 - Name pattern specified in the policy.
Action	No action required.
INMPEI0033	Default instance level permissions for Group {0} were assigned successfully
Explanation	Default instance level permissions were successfully assigned for the given group. 0 - Name of the group.
Action	No action required.
INMPEI0034	Default instance level permissions for Lifecycle Model {0} were assigned successfully
Explanation	Default instance level permissions were successfully assigned for the given lifecycle model. 0 - Name of the lifecycle model.
Action	No action required.

INMPEI0035	Default instance level permissions for Policy {0} were assigned successfully
Explanation	Default instance level permissions were successfully assigned for the given policy. 0 - Name of the policy.
Action	No action required.
INMPEI0036	Default instance level permissions for Report Template {0} were assigned successfully
Explanation	Default instance level permissions were successfully assigned for the given report template. 0 - Name of the report template.
Action	No action required.
INMPEI0037	Default instance level permissions for Role {0} were assigned successfully
Explanation	Default instance level permissions were successfully assigned for the given role. 0 - Name of the role.
Action	No action required.
INMPEI0038	Default instance level permissions for Taxonomy {0} were assigned successfully
Explanation	Default instance level permissions were successfully assigned for the given taxonomy. 0 - Name of the taxonomy.
Action	No action required.
INMPEI0040	Service Binding Type(s) conform with the specified bindings {0}
Explanation	The binding types of the service validated against the specified bindings. 0 - Binding types specified by the policy.
Action	No action required.
INMPEI0041	Default instance level permissions for User {0} were assigned successfully
Explanation	Default instance level permissions were successfully assigned for the given user 0 - Name of the User
Action	No action required
INMPEI0042	Default instance level permissions for Policy Action {0} were assigned successfully
Explanation	Default instance level permissions were successfully assigned for the given policy action. 0 - Name of the policy action.
Action	No action required.

INMPEI0050	{0} {1} successfully classified by specified taxonomies {2}
Explanation	The given registry object has been classified with the specified taxonomy nodes. 0 - Type name of the registry object 1 - Name of the registry object 2 - Name(s) of the taxonomy nodes.
Action	No action required.
INMPEI0051	{0} {1} successfully unclassified from specified taxonomies {2}
Explanation	The given registry object has been unclassified from the specified taxonomies. 0 - Type name of the registry object 1 - Name of the registry object 2 - Name(s) of the taxonomies.
Action	No action required.
INMPEI0053	{0} description {1} conforms with the pattern {2}
Explanation	The registry object description validated with the specified pattern. 0 - Type of the registry object 1 - Description of the registry object 2 - Description pattern specified in the policy.
Action	No action required.
INMPEI0054	{0} {1} was triggered to change to initial state {2}
Explanation	The registry object has been triggered to change to initial state of the corresponding lifecycle model. 0 - Type name of the object 1 - Name of the registry object 2 - Name of the initial state of the corresponding lifecycle model.
Action	No action required.
INMPEI0055	Object type of {0} - {1} is not LCM-enabled
Explanation	The type of the registry object is not lifecycle-enabled. 0 - Name of the object 1 - Type name of the object.
Action	No action required.
INMPEI0056	{0} {1} was triggered to change activation to {2}
Explanation	The registry object has been triggered to change activation to Active/Inactive. 0 - Type name of the object 1 - Name of the object 2 - Change activation to Active/Inactive.
Action	No action required.

INMPEI0058	{0} {1} belongs to state {2} which conforms to the allowed states {3}
Explanation	The lifecycle state of the registry object is validated against the allowed states specified in the policy. 0 - Type name of the registry object 1 - Name of the registry object 2 - Current state name of the registry object 3 - Allowed states specified in the policy.
Action	No action required.
INMPEI0060	State change to {0} is not applicable for {1} {2}
Explanation	The state change to the specified state is not applicable for the given object. 0 - Change to state name specified in the policy 1 - Type of the registry object 2 - Name of the registry object.
Action	No action required.
INMPEI0061	State change to {0} is initiated for {1} {2}
Explanation	The state change to the specified state has been initiated for the given object. 0 - Change to state name specified in the policy 1 - Type of the registry object 2 - Name of the registry object.
Action	No action required.
INMPEI0062	{0} {1} cannot be applied role groups policy
Explanation	Role groups policy can be applied only to user objects. 0 - Type of the registry object 1 - Name of the registry object.
Action	No action required
INMPEI0063	User {0} was added or removed from group {1}
Explanation	The given user was added or removed from the specified group. 0 - Name of the user 1 - Name of the group where the user was added or removed.
Action	No action required.
INMPEI0065	{0} {1} has value {2} set for attribute {3} which conforms to the allowed values {4}
Explanation	For the specified attribute of the given registry object, a value has been set which conforms to the allowed values. 0 - Type of the registry object 1 - Name of the registry object 2 - Attribute value of the registry object 3 - Attribute name specified in the policy 4 - Allowed attribute values specified in the policy.
Action	No action required.

INMPEI0067	Attribute {2} of {0} {1} was set to value {3}
Explanation	The specified attribute of the registry object was set to the specified value. 0 - Type of the registry object 1 - Name of the registry object 2 - Attribute name specified in the policy 3 - Attribute value specified in the policy.
Action	No action required
INMPEI0068	LC Model {0}'s enabled object type instances were initiated into initial state {1}
Explanation	The instances of the object types which are LCM enabled by the given LC Model have been triggered to change to the initial state of the LC Model. 0 - Name of the LC Model 1 - Name of the initial state of the LC Model.
Action	No action required
INMPEI0076	Default instance level permissions for Target {0} were assigned successfully
Explanation	Default instance level permissions were successfully assigned for the given target. 0 - Name of the target
Action	No action required.
INMPEI0077	Default instance level permissions for Lifecycle State {0} were assigned successfully
Explanation	Default instance level permissions were successfully assigned for the given lifecycle state. 0 - Name of the lifecycle state.
Action	No action required.
INMPEI0078	Default instance level permissions for Asset Type {0} were assigned successfully
Explanation	Default instance level permissions were successfully assigned for the given asset type. 0 - Name of the asset type.
Action	No action required.
INMPEI0079	Default instance level permissions for Taxonomy {0} were assigned successfully
Explanation	Default instance level permissions were successfully assigned for the given taxonomy. 0 - Name of the taxonomy.
Action	No action required.

INMPEI0080 Default instance level permissions for Event Type {0} were assigned successfully

Explanation Default instance level permissions were successfully assigned for the given event type. 0 - Name of the event type

Action No action required.

INMPEI0081 Default instance level permissions for Profile {0} were assigned successfully

Explanation Default instance level permissions were successfully assigned for the given profile. 0 - Name of the profile

Action No action required.

INMPEI0082 Default instance level permissions for UDDI Subscription {0} were assigned successfully

Explanation Default instance level permissions were successfully assigned for the given UDDI subscription. 0 - Name of the UDDI subscription

Action No action required.

INMPEI0083 Default instance level permissions for Federation {0} were assigned successfully

Explanation Default instance level permissions were successfully assigned for the given federation. 0 - Name of the federation.

Action No action required.

INMPEI0084 Default instance level permissions for Concept {0} were assigned successfully

Explanation Default instance level permissions were successfully assigned for the given concept. 0 - Name of the concept.

Action No action required.

INMPEI0085 Taxonomy {0} instance level permissions were assigned successfully to its child objects

Explanation The instance level permissions of the taxonomy were successfully assigned to its children concepts. 0 - Name of the taxonomy.

Action No action required.

INMPEI0086	Policy {0} instance level permissions were assigned successfully to its child objects
Explanation	Policy has child objects like Policy Condition and Policy Parameter. When we assign the instance level permission to a Policy, the permission should be assigned also to its child objects. The message states that this action was performed successfully.
Action	No action required.
INMPEI0088	User {0} is not active
Explanation	The user is not active and hence can be deleted. 0 - Name of the user.
Action	No action required.
INMPEI0095	Pending state transition was terminated by CSA
Explanation	The CentraSite administrator has terminated the pending state transition on the registry object.
Action	No action required.
INMPEI0103	Organization Primary Contact is an active user
Explanation	The primary contact of the organization is an active user and hence the validation for updating the organization is successful.
Action	No action required.
INMPEI0119	Default instance level permissions for ConsumerRegistrationRequest {0} were assigned successfully
Explanation	Default instance level permissions for the consumer registration request were assigned successfully. 0 – Name of the consumer registration request.
Action	No action required.
INMPEI0134	Default instance level permissions for ExternalLink {0} were assigned successfully
Explanation	Default instance level permissions were successfully assigned for the given external link. 0 - Name of the external link.
Action	No action required.
INMPEI0135	Default instance level permissions for ExtrinsicObject {0} were assigned successfully
Explanation	Default instance level permissions were successfully assigned for the given extrinsic object. 0 - Name of the extrinsic object.
Action	No action required.

INMPEI0137	Collector was successfully executed for {0} {1}
Explanation	The collector policy was executed successfully for the given object. 0 - Type of the object 1 - Name of the object.
Action	No action required.
INMPEI0138	Default delete handler was successfully executed for {0} {1}
Explanation	The default delete handler policy was executed successfully for the given object. 0 - Type of the object 1 - Name of the object.
Action	No action required.
INMPEI0140	WSDL regeneration skipped for Service {0} since the service is not a VirtualService, VirtualXMLService or VirtualRESTService
Explanation	WSDL regeneration can be performed only for a virtual service, virtual XML service or virtual REST service.
Action	Make sure the asset is a virtual service, virtual XML service or virtual REST service.
INMPEI0141	{0} {1} moved successfully
Explanation	The registry object has been moved successfully to the new owner and/or organization. 0 - Type of the registry object 1 - Name of the registry object.
Action	No action required.
INMPEI0147	Registry Object {0} has been validated successfully against its mandatory attributes of type Classification, File and Relationship
Explanation	All the mandatory classification, file and relationship attributes for the given registry object have been populated. 0 - Name of the registry object.
Action	No action required.
INMPEI0155	Profile permissions for {0} {1} were assigned successfully
Explanation	The profile level permissions for the given registry object were successfully assigned.
Action	No action required.
INMPEI0158	Organization export handler was successfully executed for {0}
Explanation	The organization export handler was executed successfully for the given organization.
Action	No action required.

INMPEI0159	Taxonomy/Concept export handler was successfully executed for {0} {1}
Explanation	The Taxonomy/Concept export handler was executed successfully for the given object.
Action	No action required.
INMPEI0160	Default export handler was successfully executed for {0} {1}
Explanation	The default export handler policy was executed successfully for the given object. 0 - Type of the object 1 - Name of the object.
Action	No action required.
INMPEI0161	Asset type export handler was successfully executed for {0} {1}
Explanation	The asset type export handler policy was executed successfully for the given object. 0 - Type of the object 1 - Name of the object.
Action	No action required.
INMPEI0164	Metrics does not contain serviceKey hence will not be saved in Runtime Metrics Collection
Explanation	Metrics must be saved against a service. But the user is trying to save a metrics object without classifying it with a proper service key. This metrics will be discarded.
Action	Please classify the metrics objects with the classificationScheme "uddi:centrasite.com:management:service.key". The value of the classification must be the key of the service to which the metrics belongs.
INMPEI0168	The required permissions are already available for {0} {1}
Explanation	The permissions to be set by the policy are already available in the registry object. 0 - Type of the registry object 1 - Name of the registry object.
Action	No action required.
INMPEI0169	Request Approval Flow {0} for {1} was automatically approved
Explanation	The approval flow for the registry object was automatically approved since the triggering user is part of the approver group.
Action	No action required.

INMPEI0170	CentraSite does not contain an object of type {0} and with name {1}
Explanation	The policy executed successfully, since CentraSite does not contain an object of the specified type and with specified name.
Action	No action required.
INMPEI0171	CentraSite already contains an object of type {0} and with name {1}
Explanation	This policy enforces uniqueness in names of the object. As the user tried to create an object using a name which already exists in CentraSite, this policy failed.
Action	Please use a different name
INMPEI0173	Notified Webservice endpoint {0} hosted in application server {1} successfully.
Explanation	A Webservice request has been published to the endpoint successfully.
Action	No action required.
INMPEI0174	Failed to notify Webservice endpoint {0} hosted in application server {1}: Error Message {2}
Explanation	The Webservice request could not be published to the specified endpoint.
Action	Provide a valid webservice endpoint which can accept the SOAP message configured in the notify policy.
INMPEI0177	{0} {1} has kept the current LCM state
Explanation	The LCM state has been retained during the import.
Action	No action required.
INMPEI0178	Successfully deleted the rest service of IS Service Interface '{0}'
Explanation	Rest service deletion has completed successfully while retracting the IS Service Interface from the Designer.
Action	No action required.
INMPEI0179	Failed to delete the rest service '{0}' ({1}) used by IS Service Interface '{2}'
Explanation	The deletion of the Rest Service failed while retracting the IS Service Interface from the Designer.
Action	No action required.

INMPEI0182	IS Service Interface {0} object has been transformed successfully into REST service {1}.
Explanation	The IS Service Interface object has been transformed successfully into a REST service in CentraSite.
Action	No action required.
INMPEI0183	The given object {0} does not contain the state
Explanation	The given object 0 does not contain the state.
Action	No action required.
INMPEI0186	Target Group not applicable for the operation
Explanation	The target group is not applicable for the operation.
Action	No action required.
INMPEI0187	Target Group created for the Target
Explanation	The target group was created for the target.
Action	No action required.
INMPEI0188	Target Group not created for the Target
Explanation	The target group was not created for the target.
Action	No action required.
INMPEI0189	{0} {1} promoted successfully
Explanation	The registry object has been promoted successfully to the specified target stage. 0 - Type of the registry object 1 - Name of the registry object.
Action	No action required.
INMPEI0191	Not updating Consumer WSDL for VirtualService {0} as it does not contain WSDL or Consumer WSDL is already contains the proper WSDL file.
Explanation	The Consumer WSDL attribute will not get updated if the Virtual Service does not have WSDL associated with it. Also the attribute will get updated if it contains the proper value in it.
Action	No Action Required, as this policy get triggered when WSDL is attached to the Virtual Service

INMPEI0193	Consumer WSDL attribute is populated with proper WSDL
Explanation	Policy Action successfully executed by populated the Consumer WSDL attribute with proper WSDL
Action	No action required
INMPEI0194	Not updating Consumer WSDL for {0} since it is not a Service
Explanation	Consumer WSDL attribute is applicable only for Virtual Service and hence it can't be updated for other objects
Action	Please make sure applicable object for "Consumer WSDL Generator" policy is set only to Virtual Service
INMPEI0201	,
Explanation	This is a user display name separator.
Action	No action required.
INMPEI0202	{0} {1} {2}
Explanation	This is a user display name.
Action	No action required.
INMPEI0203	Ownership of {0} {1} was changed successfully to user {2}
Explanation	The ownership of the given asset was changed successfully to the specified user. 0 - Type of the object; 1 - Name of the object; 2 - New owner of the object.
Action	No action required.
INMPEI0205	{0} of type {1} has been validated for all mandatory Slot, Classification, File and Relationship attribute types.
Explanation	The "required" attributes of the registry object {0} of type {1} have been identified and all such "required" attributes have been provided with values.
Action	No action required.
INMPEI0207	The API Key is deployed successfully to target {0}
Explanation	The specified API key was successfully deployed to the specified target.
Action	No action required.

INMPEI0208	A new API Key is generated.
Explanation	A new API key has been generated.
Action	No action required.
INMPEI0209	Onboarded user {0} proceeds with consume API request for {1}
Explanation	The onboarding of the user was successful, and the consume API request for the API has been triggered.
Action	User registration completion information will be sent as an email.
INMPEI0213	Onboarding User {0} in Organization {1} is successful
Explanation	Onboarding of the user in API Management solution was successful.
Action	The Consume API request will be generated automatically for the onboarded user.
INMPEI0214	Onboarding Organization {0} with Administrator User {1} is successful
Explanation	Onboarding of the given Organization with the given User in API Management solution was successful.
Action	The Consume API request will be generated automatically for the the onboarded administrator user.
INMPEI0215	Congratulations from API management team
Explanation	Email subject for successful onboarding of user.
Action	No action.
INMPEI0216	API key deleted successfully from target {0}.
Explanation	The API key is deleted successfully from the target {0}.
Action	None. Informational only.
INMPEI0220	WSDL Regeneration skipped for virtual service {0} as WSDL related objects are not modified
Explanation	WSDL Regeneration is needed only if JAXR Binding is updated. Else no need to update the WSDL. Updating WSDL is costly. So CentraSite updates it only if it really requires
Action	No Action required from user

INMPEI0221	API key has been renewed successfully.
Explanation	API key has been renewed successfully.
Action	No action required
INMPEI0222	A new OAuth2 Client is generated
Explanation	A new OAuth2 Client has been generated
Action	No action required
INMPEI0223	The OAuth2 Client is deployed successfully to target {0}
Explanation	The specified OAuth2 Client was successfully deployed to the specified target
Action	No action required
INMPEW0028	WSDL URL is empty for {0}
Explanation	The service WSDL URL is empty. 0 - Name of the service.
Action	Please ensure that the service has a WSDL URL.
INMPEW0172	Could not send notification to application server as it is not configured with APG_SERVICE_ENDPOINT
Explanation	The notification will be send only if the application server is configured with APG_SERVICE_ENDPOINT in the object specific property.
Action	Configure a valid webservice endpoint to the application server which is associated to the registry object.
INMPEW0192	Consumer WSDL attribute is not found Virtual Service type
Explanation	This policy action will update the Consumer WSDL attribute with WSDL which may contain WS Policy in it. So this policy action requires Consumer WSDL attribute
Action	Please make sure Consumer WSDL file attribute exists for Service type
INMPEW0217	Failed to delete API key from target {0} .
Explanation	The specified API key could not be deleted from the target {0}. This problem can occur because the requestor does not have the required permisison to delete API key.
Action	Only a user with Administrator role can delete API key from targets.

INMPUE0219	The API key has already been revoked.
Explanation	The API key could be revoked only once per session.
Action	None. Informational only.
INMPUE0003	Action category and action template types are mismatched
Explanation	For a design time/ change time category, the action template type should be programmatic. If the action template type does not match the design time/ change time category, this causes an error.
Action	Ensure that the action category and action template types are matched.
INMPUE0006	Action template name already exists
Explanation	An action template name should be unique across the system, otherwise this will create confusion for the user. So this error occurs if a user tries to create an action template with a name that is already in use.
Action	Use a different action template name.
INMPUE0015	WS-I actions cannot be combined with other actions
Explanation	While creating a policy, WS-I actions should not be combined with other actions. If a user tries to do so, this problem will happen.
Action	WS-I actions cannot be combined with other actions.
INMPUE0020	Reordering multiple actions is not allowed
Explanation	While assigning actions to the policy, a user can re-order the actions. If the user tries to re-order multiple actions at a time, this error will be thrown.
Action	Reordering multiple actions is not allowed.
INMPUE0028	Select an action to move
Explanation	If a user tries to re-order the actions without selecting anything, this error will be thrown. For this the user has to first select any action and then do the re-ordering.
Action	Select an action to move.
INMPUE0029	Action category with name {0} already available
Explanation	Action category names are unique across the system. If a user tries to create an action category with a name that exists already, this error will be thrown.
Action	Enter a valid action category name.

INMPUE0030	Provide the URL of ZIP file
Explanation	When creating an action template with the selected rule type of Java, the user has to provide a valid zip file, otherwise this error will be thrown.
Action	Enter the URL of the ZIP file.
INMPUE0032	Set Profile Permission action cannot be applied to multiple object types
Explanation	If the policy applies to multiple object types, then the set profile permission action cannot be applied
Action	Change the object types or create a new policy with a single object type
INMPUE0033	Provide the correct Attribute Values
Explanation	The attribute value provided is incorrect for the chosen type.
Action	Provide the correct attribute value for the chosen type.
INMPUE0034	You must specify a value for Attribute Name
Explanation	The required value for the duration attribute name is missing.
Action	Supply a correct value for the duration attribute name.
INMRAE0001	Cannot obtain {0} from closed Resource Access Manager.
Explanation	The Resource Access Manager is closed and thus not yet initialized.
Action	Make sure that the Resource Access Manager is opened before using it.
INMRAE0002	No configuration set.
Explanation	No configuration info set was found.
Action	Please provide a configuration info set. Refer to the Resource Access javadoc for additional information.
INMRAE0003	No valid credentials found.
Explanation	No valid credentials were found.
Action	Please provide valid credentials.

INMRAE0004	Found {0} while expecting instance of XmlServerRoleManager.
Explanation	Failed authentication against CentraSite server or absence of XmlServerLoginModule from security configuration.
Action	Check logs and security configuration.
INMRAE0005	SagRoleManagementPrincipal instance not available for the authenticated subject.
Explanation	The SagRoleManagementPrincipal security artefact is missing.
Action	Check the security configuration.
INMRAE0006	Authenticated Subject cannot be null.
Explanation	After successful authentication, the Subject instance was not found.
Action	Contact your software supplier.
INMRAE0007	No representation of the Group to be associated in external user repository.
Explanation	The external group, to be associated with a local group, is no longer present in the external repository.
Action	External user repositories are managed outside of CentraSite.
INMRAE0008	Error during System level permission copy.
Explanation	Error during System level permission copy.
Action	Contact your software supplier.
INMRAE0009	An organization must be set.
Explanation	A permission has to belong to an organization.
Action	Assign an organization to the permission instance.
INMRAE0010	Organization level permission needs to have a corresponding system level permission.
Explanation	An organization level permission needs to have a corresponding system level permission.
Action	Assign the system level permission to the organization level permission instance.

INMRAE0011	A Role needs to belong to an Organization.
Explanation	A role needs to belong to an organization.
Action	Assign an organization to the role instance.
INMRAE0012	The user does not have a working Organization set.
Explanation	The user does not have a working organization set.
Action	Set the working organization of the user.
INMRAE0013	Roles can be assigned only to registered users.
Explanation	Roles can be assigned only to registered users associated with an external user repository.
Action	Register a user instance to CentraSite.
INMRAE0014	Unsupported collection type.
Explanation	The passed collection is of an unsupported type.
Action	The collection expected is a list-backed one.
INMRAE0015	Got {0} while expecting {1}
Explanation	Passed in Registry Object instance is not of group type.
Action	Make sure that passed in Registry Object instance is of group type.
INMRAE0016	Cannot obtain external user repository type.
Explanation	Cannot retrieve the currently effective external user repository type.
Action	Check the security configuration.
INMRAE0017	Unsupported external user repository type {0}.
Explanation	The currently effective external user repository type is unknown.
Action	Check the security configuration.
INMRAE0018	Currently effective external user repository type {0} does not support custom predicate.
Explanation	Currently effective external user repository type does not support custom predicate.
Action	Use predicates instead.

INMRAE0019	Currently effective external user repository type {0} does not support predicates.
Explanation	Currently effective external user repository type does not support predicates.
Action	Use custom predicate instead.
INMRAE0020	SagUserPrincipal instance not available for the authenticated subject.
Explanation	The SagUserPrincipal security artefact is missing. It is possible that authentication against the external user repository is not performed, for example internal user accounts such as the Guest user account.
Action	Check the security configuration.
INMRAE0021	PersonName must be added
Explanation	A user instance must have PersonName.
Action	When creating a User object, the first name, middle name and last name of the user object need to be provided.
INMSOE0001	HTTP Routing Protocol not enabled
Explanation	During configuration of routing protocol, if any of the routing types are StraightThrough/LoadBalance/ContentBased/ContextBased routing, then the transport of the routing should be HTTP enabled.
Action	Enable the HTTP transport for routing protocol.
INMSOE0002	JMS Routing Protocol not enabled
Explanation	During configuration of the routing protocol, if the routing type is JMS routing, then the transport of the routing should be JMS enabled.
Action	Enable the JMS transport for routing protocol.
INMSOE0007	TargetType definition file missing
Explanation	The input JAR file provided does not contain the relevant TargetType definition XML.
Action	Add the relevant TargetType definition XML to the input JAR file.
INMSOE0008	Transformation definition file missing
Explanation	The input JAR file provided does not contain the relevant transformation file.
Action	Add the relevant transformation file to the input JAR file.

INMSOE0010	Target Type name should not be empty
Explanation	The input JAR file provided does not contain the target type name in the Target Type Definition file.
Action	Provide the Target Type name.
INMSOE0011	Event Type definition file missing
Explanation	The input JAR file provided does not contain the relevant Event Type definition.
Action	Add the relevant Event Type definition to the input JAR file.
INMSOE0012	Target Type name already exists
Explanation	The Target Type already exists with the provided name in Target Type definition file.
Action	Change the Target Type name.
INMSOE0013	Service WSDL does not contain the WSDL Service Element
Explanation	The imported WSDL does not contain the service element.
Action	Make sure service element is present in the service WSDL.
INMSOE0015	Service WSDL is mandatory for deployment operations
Explanation	The WSDL is not present for the created virtual service.
Action	Make sure the created virtual service contains the WSDL.
INMSOE0016	Deployment activity {0} is the current activity log for {1} {2}
Explanation	An activity log which is the latest deployment log for a deployed asset cannot be deleted.
Action	Unselect the particular deployment log from the deployment history before deleting other old entries.
INMSOE0019	The consumer application configured in the routing rule of the asset to be deployed is not available
Explanation	The consumer application used as part of the context based routing condition of the asset to be deployed is not available in the CentraSite Repository.
Action	Change the consumer application selected in the routing condition.

INMSOE0020	Data type mismatch during attribute mapping for RuntimeEventType: {0}. Expected data type for attribute {1} is {2}, while the supplied data type is {3}.
Explanation	This exception is thrown when a data type mismatch is encountered when mapping SNMP Trap attributes from EventType.xml to RuntimeEventType attributes.
Action	Ensure the data type matches.
INMSOE0021	Entry protocol not defined for asset {0}
Explanation	The inbound transport information is not defined for the asset to be deployed to the Mediator.
Action	Configure the entry protocol in the processing steps profile of the asset to be deployed.
INMSOE0022	WSDL not found for native service
Explanation	A WSDL is not available for the native service to be virtualized.
Action	Attach the WSDL for the native service to be virtualized.
INMSOE0023	Cannot virtualized this WebService since the service does not contain any wsdl:bindings
Explanation	Service must contain at least one service binding, otherwise it cannot be virtualized
Action	Getting error while virtualizing the service without service binding
INMSOE0027	TrapOID (Object Identifier) {0} is duplicated in the EventType.xml inside the provided Target Type definition jar file
Explanation	During target type creation, if the SNMP Trap OID is duplicated in EventType.xml, this exception is thrown.
Action	SNMP Trap OIDs should be unique within and across target types.
INMSOE0028	TrapOID {0} already defined in existing Target Type {1}
Explanation	During target type creation, if the SNMP Trap OID is already present in an existing target type, this exception is thrown.
Action	SNMP Trap OIDs should be unique within and across target types.
INMSOE0031	Scoped Virtual Service deployment will not be triggered since dependent assertion {0} does not exist
Explanation	Scoped Virtual Service deployment will not be triggered since some of the dependent assertions are missing in the Runtime Policy.
Action	Ensure dependent assertions exist.

INMSOE0033 **Scoped Virtual Service deployment will not be triggered since dependent assertion {0} does not exist**

Explanation Virtual Service will have policies associated with it. These policies may be dependent on other policies. If the dependent policies are not applied for the virtual service, this exception will arise.

Action Please create the dependent runtime policy and make sure it is applicable for the virtual service to be deployed.

INMSOE0036 **Error in API Key Creation**

Explanation An error occurred while creating an API Key instance.

Action Check if there are any related messages in the log to determine the cause of the problem.

INMSOE0037 **Mandatory parameters are not present for creation of API Key instance**

Explanation Mandatory parameters were not provided while creating API Key object

Action Provide the mandatory parameters.

INMSOE0039 **Invalid parameter {0} is selected which is not supported in the version of Mediator installed**

Explanation The version of mediator to which the asset is being deployed does not support the parameter {0}.

Action Change the parameter to one that is supported in the mediator version installed.

INMSOE0041 **Error occurred during creation of OAuth2 Client asset**

Explanation An error was encountered while creating the OAuth2 Client asset.

Action Check if there are any related messages in the log to determine the cause of the problem.

INMSOE0042 **Mandatory parameters are missing for creation of OAuth2 client instance**

Explanation Mandatory parameters were missing while creating OAuth2 client object.

Action Check if the mandatory parameters 'Service' and 'Consumer' are missing.

INMSOE0043	Cannot enforce Evaluate actions ApiKey and OAuth2 for the service
Explanation	When both API Keys and OAuth2 are enforced for an API in AND condition, this exception is thrown
Action	Change the Enforce condition to OR
INMSOI0017	Connection to deployment endpoint failed
Explanation	This occurs if no connection can be established to the deployment endpoint defined in a target during deployment/undeployment/synconsumers operations. This could be because the deployment endpoint is down or the credentials used for accessing the deployment endpoint are wrong.
Action	Check if the deployment endpoint is up and running. Also check if the credentials defined in the target for accessing the deployment endpoint are correct.
INMSOI0035	API Key for {0} of {1}
Explanation	This is how the name of the API key will be generated where the service name is passed as a parameter.
Action	No action required.
INMSOI0040	OAuth2 Client for {0} of {1}
Explanation	This is how the name of the OAuth2 Client is created when the service name and consumer name are passed as parameters.
Action	No action required.
INMSOW0034	The parameter(s)/action(s) {0} were ignored as it is not supported by Mediator {1}
Explanation	Virtual Service can be deployed from latest version of CentraSite to Mediator version 8.2.2 and above. If you deploy any service to older version of Mediator from latest version of CentraSite, some policy parameters or actions cannot be executed on older version of Mediator. Such policy parameters or actions will be ignored. This warning message will list those ignored parameter/actions.
Action	If the ignored parameters or actions need to be executed, then Mediator has to be upgraded to version in which CentraSite is running. If the ignored parameter or actions are not needed, then this warning message can be ignored.
INMSTE0001	Referenced service does not exist ("{0}")
Explanation	Internal error.
Action	Please contact your software supplier.

INMSTE0002	Dangling reference ("{0}")
Explanation	Internal error.
Action	Please contact your software supplier.
INMSTE0003	Conflicting state ({0})
Explanation	Internal error.
Action	Please contact your software supplier.
INMSTE0004	Invalid Reference ("{0}")
Explanation	Internal error.
Action	Please contact your software supplier.
INMSTE0005	Type concept is not found in ImportList
Explanation	Internal error.
Action	Please contact your software supplier.
INMSTE0006	No schema definition generated
Explanation	Internal error.
Action	Please contact your software supplier.
INMSTE0007	schemaName for selected concept is null
Explanation	Internal error.
Action	Please contact your software supplier.
INMSTE0008	At least one instance does not comply with the type modifications.
Explanation	A type is being modified in a way that is not compliant with the existing instances of that type.
Action	Modify the type in a compliant way.
INMSTE0009	Type concept not found for "{0}"
Explanation	While updating or deleting a JAXR object type, the corresponding type concept was not found in the registry.
Action	This is an internal error. Please contact your software supplier.

INMSUE0001	Reordering multiple actions is not allowed
Explanation	Reordering multiple actions not allowed.
Action	Reordering multiple actions not allowed.
INMSUE0002	You must select valid jar file
Explanation	The selected jar file(s) are not valid.
Action	Select valid jar files.
INMSUE0003	Enter unique name
Explanation	The event type name already exists.
Action	Enter a unique name for the event type
INMSUE0004	Target name should not be empty
Explanation	An attempt was made to add a target object without a name.
Action	Supply a target name.
INMSUE0005	Target type should not be empty
Explanation	An attempt was made to add a target type object without a name.
Action	Supply a target type name.
INMSUE0006	Policy name cannot be empty
Explanation	An attempt was made to add a policy object without a name.
Action	Supply a policy name.
INMSUE0007	Select an Asset Type for the policy
Explanation	For creating a runtime policy object, the object needs an associated object type.
Action	Select an object type for the policy.
INMSUE0008	Select a target type for the policy
Explanation	The target type for the policy is missing.
Action	Select a target type for the policy.

INMSUE0009	Default route cannot be empty
Explanation	The default route is missing.
Action	Define a default route.
INMSUE0010	XPath expression cannot be empty
Explanation	An empty XPath expression was supplied.
Action	Supply an XPath expression.
INMSUE0011	Enter the valid XPath to the 'Element Required to be Signed'
Explanation	The correct XPath to the 'Element Required to be Signed' is required.
Action	Enter the valid XPath to the 'Element Required to be Signed'.
INMSUE0012	Virtual Service name should not be empty
Explanation	The required name is missing.
Action	Supply the name.
INMSUE0013	Version cannot be empty
Explanation	A version was not entered.
Action	Enter a version.
INMSUE0014	No WSDL Found
Explanation	For the given URL, there is no WSDL available.
Action	Supply a WSDL for the URL.
INMSUE0015	Virtual service with name {0} already exists
Explanation	A virtual service with the given name already exists.
Action	Supply a different name for the virtual service.
INMSUE0016	Assign actions for the policy
Explanation	The actions required for the runtime policy object are missing.
Action	Assign actions for the policy.

INMSUE0017	Create target type before creating runtime policy
Explanation	The target type required for creating the runtime policy is not available.
Action	Create the target type before creating the runtime policy.
INMSUE0018	Create target type before creating target
Explanation	The target type must be created before the target can be created.
Action	Create the target type before creating the target.
INMSUE0019	Select at least one target to deploy
Explanation	No target was selected to deploy.
Action	Select at least one target to deploy.
INMSUE0020	Default route cannot be empty
Explanation	The default route was not specified.
Action	Specify a default route
INMSUE0022	JMS alert destination cannot be empty
Explanation	The JMS alert destination was not specified.
Action	Specify the JMS alert destination.
INMSUE0023	Select at least one consumer application
Explanation	No consumer applications have been selected.
Action	Select at least one consumer application.
INMSUE0024	Rule name already exists
Explanation	The specified rule name already exists.
Action	Specify a different rule name.
INMSUE0025	Endpoint URL cannot be empty
Explanation	An empty endpoint URL was specified.
Action	Specify a value for the endpoint URL.

INMSUE0026	Consumer application cannot be empty
Explanation	The consumer application was not specified.
Action	Specify the consumer application.
INMSUE0027	Invalid hour given
Explanation	The input for hour is invalid.
Action	Enter a valid hour.
INMSUE0028	Invalid minute given
Explanation	The input for minute is invalid.
Action	Enter a valid minute.
INMSUE0029	Date cannot be empty
Explanation	A date was not entered.
Action	Enter a date.
INMSUE0030	Assertion type not found
Explanation	The assertion type was not found.
Action	Specify an assertion type.
INMSUE0031	Virtual service name cannot be same as web service name
Explanation	The virtual service name should not be the same as the web service name.
Action	Specify a different virtual service name.
INMSUE0032	HTTP header value cannot be empty
Explanation	An HTTP header value was not entered.
Action	Enter an HTTP header value.
INMSUE0033	HTTP header name cannot be empty
Explanation	The HTTP header name is empty.
Action	Enter an HTTP header name.

INMSUE0034	JMS message property name cannot be empty
Explanation	The JMS message property name is empty.
Action	Enter a JMS message property name.
INMSUE0035	JMS message property value cannot be empty
Explanation	The JMS message property value is empty.
Action	Enter a JMS message property value.
INMSUE0036	Virtual service name cannot have # character
Explanation	The virtual service name contains the "#" character.
Action	Ensure that the name of the virtual service does not contain the "#" character.
INMSUE0037	JMS header name cannot be empty
Explanation	The JMS header name is empty.
Action	Enter the JMS header name.
INMSUE0038	JMS header value cannot be empty
Explanation	The JMS header value is empty.
Action	Enter the JMS header value.
INMSUE0039	Select a policy to delete
Explanation	No policy has been selected for deletion.
Action	Select a policy to delete.
INMSUE0062	Undeploy the Service(s) before deleting the Target
Explanation	Before deleting the target, undeploy all virtual services from the target.
Action	Make sure that the target instance has no deployed virtual services before trying to delete the target.
INMSUE0066	Virtual XML Service with name {0} already exists
Explanation	A virtual XML service with the given name already exists.
Action	Supply a different name for the virtual XML service.

INMSUE0067	HTTP Methods not declared for the native XML Service
Explanation	HTTP methods required for the XML service being virtualized were not declared.
Action	Update the HTTP methods of the native XML service being virtualized.
INMSUE0068	HTTP Methods are not declared for the XML Service
Explanation	The HTTP methods cannot be empty when creating an XML service.
Action	Select any one of the HTTP methods provided to create an XML Service.
INMSUE0069	Select an HTTP Method for Entry Protocol
Explanation	HTTP Methods for an entry protocol policy of a virtual XML service cannot be empty
Action	Select any one of the options available for HTTP Methods for an Entry Protocol policy
INMSUE0070	Select the data type for predefined context variable
Explanation	The data type for the predefined context variable should be selected.
Action	Select either the String or Int data type for the predefined context variable.
INMSUE0071	Select the name for predefined context variable
Explanation	The context variable name cannot be empty.
Action	Select any of the available context variable names.
INMSUE0072	Enter the value for predefined context variable
Explanation	The context variable value cannot be empty.
Action	Enter the value of the selected context variable.
INMSUE0073	Select the data type for custom context variable
Explanation	The data type for the selected custom context variable is invalid.
Action	Select the data type of the custom context variable.
INMSUE0074	Enter the name for custom context variable
Explanation	The name of the custom context variable cannot be empty.
Action	Enter the custom context variable name.

INMSUE0075	Enter the value for custom context variable
Explanation	The value for the custom context variable cannot be empty.
Action	Enter the value for the custom context variable.
INMSUE0076	Virtual REST Service with name {0} already exists
Explanation	A virtual REST service with the given name already exists.
Action	Supply a different name for the virtual REST service.
INMSUE0077	Select at least one asset to deploy
Explanation	There are no assets selected for deployment
Action	Please select the assets to be deployed
INMSUE0078	User does not have permission to create groups in the organization
Explanation	When a target is created, a corresponding synchronization group is created in the organization selected with the given target name, but the user who is trying to create the target does not have permission to create a group in the organization he belongs to or the selected organization.
Action	Grant manage users permission to the user.
INMSUE0079	Abstract WSDL services cannot be virtualized
Explanation	The chosen service is an abstract service and hence cannot be virtualized
Action	Please choose a service which has concrete service definitions to virtualize
INMSUE0080	Reserved characters except _ and - and non-ASCII characters are not allowed in the virtual service name.
Explanation	The virtual service name can only contain the letters A-Z, a-z, numbers from 0-9, _ and - characters.
Action	Remove the special characters from the virtual service name.
INMSUE0081	Logged in user {0} does not have permission to deploy the asset
Explanation	To deploy an asset to the target, the user must have manage targets permission.
Action	Request the manage targets permission from the CentraSite administrator and try again.

INMSUE0083	Hard Limit value should not be empty
Explanation	Number. Required. Specifies the maximum number of invocations allowed per Interval before stopping the processing of further requests and issuing an alert. Typically, this limit should be higher than the soft limit.
Action	On Save of Throttling Policy
INMSUE0085	Select Consumer Application to Limit traffic
Explanation	Specifies the consumer application(s) that this action applies to. To specify multiple consumer applications, use the plus button to add rows, or select Any Consumer
Action	Specifies the consumer application(s) that this action applies to. To specify multiple consumer applications, use the plus button to add rows, or select Any Consumer
INMSUE0086	Soft Limit value should not be empty
Explanation	Number. Optional. Specifies the maximum number of invocations allowed per Interval before issuing an alert. Reaching the soft limit will not affect further processing of requests (until the Hard Limit is reached).
Action	On Save of Throttling Policy
INMSUE0087	Soft Limit should not be higher than the Hard Limit
Explanation	Hard limit should be higher than the soft limit
Action	On Save of Throttling Policy
INMSUE0089	Reserved characters except _ and - and non-ASCII characters are not allowed in the target name.
Explanation	The target name can only contain the letters A-Z, a-z, numbers from 0-9, _ and - characters.
Action	Remove the special characters from the target name.
INMSUI0082	Service URL is invalid
Explanation	Service URL should not contain characters like *
Action	Replace character ' * ' with a valid character.

INMSUI0084	Interval should not be empty.
Explanation	Specifies the amount of time for the soft limit and hard limit to be reached.
Action	Specifies the amount of time for the soft limit and hard limit to be reached.
INMSUI0088	Please enter a valid URL or URI
Explanation	A URL or URI was specified that is an invalid endpoint.
Action	Specify a valid URL or URI.
INMUCE0001	Error while creating Axis2 SOAP Service Stub for UDDI Security API
Explanation	This error may happen if the host or port specified in RegistryConfiguration is not valid or if there is an incorrect version of Axis jars in the classpath.
Action	Please make sure the host and port of the registry provided in RegistryConfiguration are valid. And also make sure that the classpath has the correct version of Axis2 jars.
INMUCE0002	Error while creating Axis2 SOAP Service Stub for UDDI Inquiry API
Explanation	This error may happen if the host or port specified in RegistryConfiguration is not valid or if there is an incorrect version of Axis jars in the classpath.
Action	Please make sure the host and port of the registry provided in RegistryConfiguration are valid. And also make sure the classpath has the correct version of Axis2 jars.
INMUCE0003	Error while creating Axis2 SOAP Service Stub for UDDI Publish API
Explanation	This error may happen if the host or port specified in RegistryConfiguration is not valid or if there is an incorrect version of Axis jars in the classpath.
Action	Please make sure the host and port of the registry provided in RegistryConfiguration are valid. And also make sure the classpath has the correct version of Axis2 jars.
INMUCE0004	Error while creating Axis2 SOAP Service Stub for UDDI Subscription API
Explanation	This error may happen if the host or port specified in RegistryConfiguration is not valid or if there is an incorrect version of Axis jars in the classpath.
Action	Please make sure the host and port of the registry provided in RegistryConfiguration are valid. And also make sure the classpath has the correct version of Axis2 jars.

INMUCE0005	Error while creating Axis2 SOAP Service Stub for Taxonomy API
Explanation	This error may happen if the host or port specified in RegistryConfiguration is not valid or if there is an incorrect version of Axis jars in the classpath.
Action	Please make sure the host and port of the registry provided in RegistryConfiguration are valid. And also make sure the classpath has the correct version of Axis2 jars.
INMUCE0006	Not able to connect to the UDDI Registry. get_authToken call failed.
Explanation	Remote exception thrown while connecting to UDDI registry.
Action	Please make sure the host and port provided in RegistryConfiguration are valid.
INMUCE0007	Not able to connect to the UDDI Registry. discard_authToken call failed.
Explanation	Remote exception thrown while connecting to UDDI registry.
Action	Please make sure the host and port provided in RegistryConfiguration are valid.
INMUCE0008	Not able to fetch the modified date of service with key {0}. get_operationalInfo call failed due to RemoteException.
Explanation	Remote exception was thrown while getting operational info for the given service.
Action	Please make sure the registry is running the host and port provided in RegistryConfiguration.
INMUCE0009	Not to able to fetch the virtual services for the specified target {0}
Explanation	Not to able to fetch the virtual services for the specified target {0}, as remote exception was caught in find_service call.
Action	Please make sure the registry is running the host and port provided in RegistryConfiguration.
INMUCE0011	Not able to fetch the service with name {0}. find_service call failed due to RemoteException.
Explanation	Remote exception was thrown while inquiring the registry for services.
Action	Please make sure the registry is running the host and port provided in RegistryConfiguration.

INMUCE0012	Not able to fetch the details of the service {0}. get_serviceDetail call failed due to RemoteException.
Explanation	Remote exception was thrown while inquiring the registry for service details.
Action	Please make sure the registry is running the host and port provided in RegistryConfiguration.
INMUCE0013	Not able to fetch the details of the tModel {0}. get_tModelDetail call failed due to RemoteException.
Explanation	Remote exception was thrown while inquiring the registry for tModel details.
Action	Please make sure the registry is running the host and port provided in RegistryConfiguration.
INMUCW0010	Unable to find the virtual service with specified name {0}
Explanation	There is not virtual service with the specified name in the UDDI registry.
Action	Please make sure the UDDI registry has a virtual service with the specified name. If it exists please make sure the user provided in RegistryConfiguration has the privilege to view the virtual service.
INMVSE0001	Internal JAXR error happened
Explanation	An exception inside JAXR occurred.
Action	Analyze the JAXR exception given by the stack.
INMVSE0002	Invalid NULL parameter given
Explanation	A version interface method was called with invalid parameters containing NULL.
Action	Correct the usage of the version management interface.
INMVSE0003	Object of type {0} not supported for External Link versioning
Explanation	This object must not be used for duplicating external links.
Action	Do not use this kind of object.
INMVSE0004	Invalid external link for versioning, must be a WebDAV one. URI: {0}
Explanation	The external link object provided for versioning is not supported. It must be an external link of a WebDAV resource.
Action	Do not use this kind of external link.

INMVSE0005	Unexpected external link. URI: {0}
Explanation	During external link versioning the external link handling was unexpected.
Action	Check your WebDAV resources of external links.
INMVSE0006	Object of type {0} not supported for a versioning operation
Explanation	A non-versionable object was found during a versioning operation.
Action	Check your registered objects.
INMVSE0007	Unexpected: no new external link in duplication list
Explanation	Internal error: an element was not properly duplicated during versioning.
Action	Contact your software supplier.
INMVSE0008	Object to be versioned ({0}) does not have the highest version number
Explanation	The registry object to be versioned is an intermediate one in the versioning hierarchy, which is not permitted.
Action	Use only the highest versioned object for a versioning action.
INMVSE0009	Object ({0}) is not granted for a versioning operation.
Explanation	A registered listener rejected the object for the given versioning operation.
Action	Check your registry entries and why the listener has denied the action.
INMVSE0010	Invalid association ID specified: {0}
Explanation	An invalid association type was specified by the user of the API.
Action	Correct the association type, e.g. for HasParent, Uses, etc.
INMVSE0011	Invalid WebDAV URL: {0}
Explanation	The WebDAV URL has an invalid format.
Action	Correct the format.
INMVSE0012	WebDAV cannot be accessed
Explanation	Failure on WebDAV access.
Action	Inspect the original exception.

INMVSE0013	Resource cannot be stored to WebDAV
Explanation	Internal error on storing a file to WebDAV.
Action	Inspect the original exception.
INMVSE0014	Unexpected: copied object not found in list
Explanation	An object which was duplicated was not found in the list holding those elements.
Action	No action required.
INMVSE0015	Unsupported copy mode for a Package object
Explanation	The copy mode for versioning a package is not supported.
Action	Use only supported copy modes.
INMVSE0016	Error retrieving checkpoint objects for ID: {0}
Explanation	The revision or checkpoint object cannot be determined.
Action	See the embedded exception description.
INMVSE0017	Error finding checkpoint records
Explanation	Checkpoint records couldn't be determined during a find with qualifiers.
Action	See the embedded exception description.
INMVSE0018	The restore of revision objects failed
Explanation	The replacement of the current object with an older revision of the object was not successful.
Action	See the embedded exception description.
INMVSE0019	The method is not allowed if revision feature not enabled
Explanation	The revision feature must be enabled in CentraSite before using certain methods.
Action	Enable CentraSite's revision feature.
INMVSE0020	Checkpoint label {0} already in use
Explanation	A checkpoint label must only be used once in the system.
Action	Use another label or delete the label first.

INMVSE0021	Setting of checkpoint label '{0}' failed
Explanation	Setting of checkpoint label to revision objects failed.
Action	See embedded exception description.
INMVSE0022	Error reading checkpoint with label '{0}'
Explanation	Reading revision objects failed due to an internal reason.
Action	See embedded exception description.
INMVSE0023	Error on finding checkpoint label names
Explanation	Retrieving all checkpoint label names was not successful.
Action	See embedded exception description.
INMVSE0024	Error during deletion of checkpoint label '{0}'
Explanation	Deleting checkpoint labels from objects was not successful.
Action	See embedded exception description.
INMVSE0025	Checkpoint label count cannot be determined
Explanation	The checkpoint label count cannot be determined due to internal problems.
Action	Please contact your software supplier.
INMVSE0026	Error getting minor version of object: {0}
Explanation	Error getting minor version of object.
Action	See embedded exception description.
INMVSE0027	Error getting checkpoint label of object: {0}
Explanation	Error getting checkpoint label of object.
Action	See embedded exception description.
INMVSE0028	Invalid keepCount parameter
Explanation	Invalid keepCount parameter.
Action	Correct the keepCount parameter.

INMVSE0029	Error purging checkpoints of object: {0}
Explanation	Error purging checkpoints of object.
Action	See embedded exception description.
INMVSE0030	Revision and Checkpoint enablement failed
Explanation	Revision and Checkpoint enablement failed.
Action	See embedded exception description.
INMVSE0031	Disable of Revision and Checkpoint failed
Explanation	Disable of Revision and Checkpoint failed.
Action	See embedded exception description.
INMVSE0032	Base collection not present
Explanation	The base CentraSite collection is not available. The registry seems to be inconsistent.
Action	Please contact your software supplier.
INMVSE0033	The common CentraSite schema is not present.
Explanation	Schema CentraSiteObjects is not present.
Action	Check the CentraSite environment.
INMVSE0034	Asset Type ({0}) does not support the Versioning Capability
Explanation	An instance of an asset type should get a new version, but the asset type does not support this.
Action	Check the properties of your asset type.
INMWSE0001	Unable to connect to {0} using the provided username and password.
Explanation	The service was unable to connect to the provided CentraSite address.
Action	Make sure the CentraSite address is valid and the username and password are correct.
INMWSE0002	Error reading {0}.
Explanation	The service was unable to read the document.
Action	Make sure that the document is accessible and valid.

INMWSE0003	Unable to import service.
Explanation	The application was unable to import the service in the CentraSite registry.
Action	Make sure the arguments are correct or manually check the CentraSite registry for problems.
INMWSE0004	Error retrieving product with name {0}.
Explanation	The service was unable to find the product with the provided product name.
Action	Make sure that the product name is correct and exists in the CentraSite registry.
INMWSE0005	Unable to import {0} {1}.
Explanation	The service was unable to import the file.
Action	Make sure the arguments are correct or manually check the CentraSite registry for problems.
INMWSE0006	Failed to retrieve the imported service ID.
Explanation	Unable to retrieve the UDDI key of the service which has been imported.
Action	Check connection to CentraSite server. Check the logs for errors.
INMWSE0007	Unable to retrieve the registered BPEL process ID.
Explanation	The application was unable to retrieve the imported BPEL process ID.
Action	Check connection to CentraSite server. Check the logs for errors.
INMWSE0008	Unable to import BPEL process.
Explanation	The application was unable to import the BPEL process in the CentraSite registry.
Action	Make sure the arguments are correct or manually check the CentraSite registry for problems.
INMWSE0009	Unable to import XSD schema.
Explanation	The service was unable to import the XSD schema in the CentraSite registry.
Action	Make sure the arguments are correct or manually check the CentraSite registry for problems.

INMWSE0010	Missing attachment with content ID {0}.
Explanation	The service was unable to retrieve the attachment.
Action	Make sure the content ID of the attachment is valid.
INMWSE0011	Invalid file descriptor. Missing file type.
Explanation	The value for file type was missing.
Action	Make sure the arguments are valid.
INMWSE0012	Invalid file descriptor. Missing file name.
Explanation	The value for the file name was missing.
Action	Make sure the arguments are valid.
INMWSE0013	Invalid file descriptor. Missing content ID string.
Explanation	The value for the content ID string was missing.
Action	Make sure the arguments are valid.
INMWSE0014	Invalid file type. Must be XSD, WSDL, BPDL, XPD, META_INFO, DOCUMENT or REFERENCED.
Explanation	CentraSite web services will only accept the following file types: XSD, WSDL, BPDL, XPD, META_INFO, DOCUMENT or REFERENCED.
Action	Please provide valid file type.
INMWSE0015	Missing Authorization header.
Explanation	Authorization header for HTTP basic authentication was not found in the request.
Action	Provide username and password to connect to the CentraSite server.
INMWSE0016	The creation of a folder in the temp directory has failed.
Explanation	The creation of a folder in the temp directory has failed. The folder could not be created in the temp directory which is determined by the system property java.io.tmpdir.
Action	Please make sure that the temp directory has enough free space.

INMWSE0017	The creation of folder {0} has failed.
Explanation	The specified folder could not be created.
Action	Please make sure that you have sufficient privileges to create the folder.
INMWSE0018	Exception while importing XPDL
Explanation	An exception occurred while importing the XPDL file.
Action	Please make sure the SOAP request has all required parameters filled with proper values.
INMWSE0019	Referenced file {0} not found
Explanation	The XPDL file to be imported has a reference to a web service. But the WSDL file for the referenced file was not passed to the XPDL importer service.
Action	Please create a file descriptor for the referenced WSDL file and send it to ImportXPDLService.
INMWSE0020	Response from XPDL importer does not contain any registry objects
Explanation	The XPDL Importer didn't report any error. Also it didn't return any response which needs to be filled for a web service response.
Action	Please make sure the XPDL file contains the Process element which will be created in CentraSite and returned in the web service response.
INMWSE0021	Error while fetching LCM state for process
Explanation	A system error has occurred while loading the LCM state of the process.
Action	Please check whether the Process object is in a valid state. If it is in a valid state, please retry the request.
INMWSE0022	Parameter name (wild card) is mandatory input
Explanation	This operation requires a keyword as a parameter. In the request, the keyword is not set.
Action	Please set the keyword in the SOAP request.
INMWSE0023	Error while fetching processes from CentraSite
Explanation	A system error has occurred while fetching process objects from CentraSite. Perhaps the connection to the CentraSite Server has been lost.
Action	Please check whether the CentraSite Server is up and running.

INMWSE0024	Error while fetching services from CentraSite
Explanation	A system error has occurred while fetching services from CentraSite. Perhaps the connection to the CentraSite Server has been lost.
Action	Please check whether the CentraSite Server is up and running.
INMWSE0025	Error while fetching organizations from CentraSite
Explanation	A system error has occurred while fetching organizations from CentraSite. Perhaps the connection to the CentraSite Server has been lost.
Action	Please check whether the CentraSite Server is up and running.
INMWSE0026	Invalid LCM states {0} are used in search filters
Explanation	At least one lifecycle state provided in the search filter is not valid.
Action	Please provide proper lifecycle states in the search filter.
INMWSE0027	Invalid file descriptor.
Explanation	The value for file type was missing.
Action	Make sure the arguments are valid.
INMWSE0028	The XPDL is not passed as FileDescriptor in the request
Explanation	The request does not contain a file descriptor.
Action	Please pass the XPDL content as the file descriptor in the request.
INMWSE0029	Specified organization key {0} is not valid
Explanation	CentraSite does not contain an organization with the provided key.
Action	Please make sure the organization key provided in the request is valid.
INMWSE0030	Specified product {0} is not valid
Explanation	CentraSite does not contain the product concept with the specified key.
Action	Please make sure the product specified in the request is valid.
INMWSE0031	Exception while fetching the properties from META-INFO
Explanation	The user can provide attributes with values in the request. CentraSite is not able to fetch the properties from the provided META-INFO file descriptor.
Action	Please provide the properties in the format which is supported by CentraSite. Please refer http://localhost:53307/wsstack/services/Property.xsd for the CentraSite supported format. Please replace the host and port in the above URL accordingly.

INMWSE0032	Referenced file {0} not found
Explanation	The WSDL file to be imported imports another WSDL/XSD. But the other imported WSDL/XSD file was not passed to the WSDL importer service.
Action	Please create a file descriptor for the referenced WSDL/XSD file and send it to ImportWSDLService.
INMWSE0033	Exception occurred while executing getApprovalHistory operation
Explanation	An internal issue occurred while performing the getApprovalHistory operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
Action	Please make sure the web service operation is executed with right set of parameters.
INMWSE0034	Exception occurred while executing getPendingApprovals operation
Explanation	An internal issue occurred while performing the getPendingApprovals operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
Action	Please make sure the web service operation is executed with right set of parameters.
INMWSE0035	Exception occurred while approving the approval flow using approve operation
Explanation	An internal issue occurred while performing the approve operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
Action	Please make sure the web service operation is executed with right set of parameters.
INMWSE0036	Exception occurred while executing getApprovalRequests operation
Explanation	An internal issue occurred while performing the getApprovalRequests operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
Action	Please make sure the web service operation is executed with right set of parameters.
INMWSE0037	Exception occurred while executing getApprovalActions operation
Explanation	An internal issue occurred while performing the getApprovalActions operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
Action	Please make sure the web service operation is executed with right set of parameters.
INMWSE0038	Revert Pending State operation can only be performed by CentraSite Administrator
Explanation	Not all users have permission to revert the pending state of a registry object. The user should have the CentraSite Administrator role to perform a revert pending state operation.
Action	Please provide the user with CentraSite Administrator role for the revert pending state operation.

INMWSE0039	CentraSite does not contain a registry object with the specified key {0}.
Explanation	The revert pending state operation requires a key of the registry object which exists in CentraSite. The pending state change cannot be reverted for a registry object that does not exist in CentraSite.
Action	Please make sure a registry object exists in CentraSite with the specified key.
INMWSE0040	Exception occurred while executing revertPendingStateChange operation
Explanation	An internal issue occurred while reverting a pending state change. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
Action	Please make sure the web service operation is executed with right set of parameters.
INMWSE0041	Exception occurred while executing reject operation
Explanation	An internal issue occurred while performing the reject operation. It might be a CentraSite issue or the data provided to the CentraSite is not sufficient.
Action	Please make sure the web service operation is executed with right set of parameters.
INMWSE0042	applicationServeKeyOrName parameter is missing in the request
Explanation	This error happens when the user does not set the applicationServerKeyOrName in the request parameter.
Action	Set the applicationServerKeyOrName in the request parameter.
INMWSE0043	serviceKey parameter is missing in the request message
Explanation	This error happens when the user does not set serviceKey in the request parameter.
Action	Set the serviceKey in the request parameter.
INMWSE0044	Invalid product {0} has been specified in the request
Explanation	The value given as product parameter is invalid.
Action	Give a valid product name in the product parameter.
INMWSE0045	Found {0} {1} application server instances during search. Use application server key to find unique instance.
Explanation	This error happens if the search result matches more than one application server instance.
Action	Use the key to find a unique application server instance in the web service request operation.

INMWSE0046	Failed to associate the given application server {0} and service {1}
Explanation	This error may happen if the given CentraSite location is wrong or because of invalid credentials.
Action	Check the CentraSite location and its credentials. Also check if the application server instance exists.
INMWSE0047	Invalid application server {0}
Explanation	The given application server key or name is not valid.
Action	Give the correct application server key in the request parameter.
INMWSE0048	Parameter name (serviceKeys) is mandatory input
Explanation	The serviceKeys element is mandatory for the GetServiceDetails request.
Action	Specify at least one service key for the GetServiceDetails request.
INMWSE0049	Error while retrieving service detail
Explanation	Verify that the given request parameters are appropriate for the getServiceDetails call.
Action	Validate the parameters supplied for the getServiceDetails operation.
INMWSE0050	Error while retrieving associated type for Lifecycle model {0}
Explanation	An error occurred while retrieving an associated type for a lifecycle model.
Action	Verify that the associated types for the lifecycle model are appropriate.
INMWSE0051	Error while retrieving transition state for the Lifecycle model {0}
Explanation	An error occurred while retrieving the transition state for the lifecycle state and lifecycle model.
Action	Verify that the transition states are appropriate for the retrieved lifecycle state.
INMWSE0052	Error while retrieving LC State for the LC Model {0}
Explanation	An error occurred while retrieving a lifecycle state for the lifecycle model.
Action	Verify that the lifecycle states are appropriate for the retrieved lifecycle model.

INMWSE0053	Error while retrieving LC Model {0}
Explanation	An error occurred while retrieving the lifecycle model.
Action	Verify that the retrieved lifecycle model is correct.
INMWSE0054	Failed to process getLifecycleModels operation
Explanation	The getLifecycleModels operation could not be processed.
Action	Verify that the parameters are appropriately specified in the request.
INMWSE0055	Error while registering the application server {0}
Explanation	An error occurred while registering the application server.
Action	Verify that the parameters are appropriately specified in the request.
INMWSE0056	Error while deregistering the application server
Explanation	An error occurred while deregistering the application server.
Action	Verify that the parameters are appropriately specified in the request.
INMWSE0057	Error while reading product version information
Explanation	An error occurred while getting the application server version.
Action	Verify that the parameters are specified in the request.
INMWSE0058	Error while retrieving installed language information from CentraSite
Explanation	Error while retrieving installed language information from CentraSite.
Action	Validate the web service request or contact the CentraSite administrator.
INMWSE0059	Invalid owner key {0} specified in request
Explanation	The request XML contains an invalid owner key.
Action	Specify the appropriate owner key in the request XML.
INMWSE0060	Invalid organization key {0} specified in request
Explanation	The request contains an invalid organization key.
Action	Specify an appropriate organization key in the request.

INMWSE0061	Invalid object type {0} specified in request
Explanation	The request contains an invalid object type.
Action	Specify an appropriate object type string in the request.
INMWSE0062	Object Type is mandatory when Organization Key is specified in request
Explanation	The object type is mandatory when the organization key is specified in the request.
Action	Specify a valid object type string in the request.
INMWSE0063	Service {0} is not available in organization {1}
Explanation	The organization key specified for this service is not correct.
Action	Provide the correct organization key of this service.
INMWSE0064	Invalid asset key {0} passed in the request
Explanation	The request contains an invalid asset key.
Action	Pass a valid asset key in the request.
INMWSE0065	Error while processing getAssociatedServices request
Explanation	An error occurred while processing a getAssociatedServices request.
Action	Check if the given request parameters are correct.
INMWSE0066	Error while processing releaseProcesses request
Explanation	It was not possible to process the releaseProcesses request.
Action	Check if the given request parameters are correct.
INMWSE0067	CentraSite does not contain an Application Server with the specified key or name {0}.
Explanation	A CentraSite web service received a RegisterApplicationServer request with a key or name specified. The web service tried to update the object with the specified key or name, but the web service was not able to find any Application Server object with the specified key or name.
Action	Please check whether an Application Server object exists in CentraSite with the specified key or name. If an object exists in CentraSite, please make sure the requested user has view/edit permission on the Application Server object.

INMWSE0068	Specified application server {0} does not exist
Explanation	The application server name or key given in the request is not valid.
Action	Check the given application server name or key and correct it.
INMWSE0073	Invalid application server key {0}
Explanation	The request contains an invalid application server key.
Action	Specify a valid application server key.
INMWSE0074	Exception while parsing XPDL file {0}
Explanation	CentraSite will parse the specified XPDL file to create corresponding objects in CentraSite. CentraSite is not able to parse the specified the XPDL file as the given XPDL file does not comply with the XML and XPDL specification.
Action	Please make sure the specified XPDL file is in accordance with the XML and XPDL specification.
INMWSE0075	The given organization key {0} in the request does not match the key of the existing asset's organization {1}
Explanation	The organization key given in the importWSDL request does not match the organization key of the existing asset's organization.
Action	Provide the existing asset's organization key in the request.
INMWSE0077	Failed to find application server in given name {0}.
Explanation	This exception is unexpected. The cause is not immediately known.
Action	If the problem persists, contact CentraSite administrator.
INMWSE0078	Application Server name is empty
Explanation	No name was supplied for the application server.
Action	Provide a valid application server name.
INMWSE0079	Unsupported Association Type {0}
Explanation	The specified association type is not supported.
Action	Correct the association type.

INMWSE0080	Check your access rights and proxy settings.
Explanation	You do not have sufficient privileges to access the target object.
Action	Execute the action with sufficient privileges.
INMWSE0081	The {0} parameter value is null.
Explanation	The function shown on the call stack is called with a null value.
Action	Correct the client program.
INMWSE0082	The credentials parameter value is null.
Explanation	The setCredentials() method is called with a null value for the credentials parameter.
Action	Correct the client program.
INMWSE0083	Specified process {0} is unavailable.
Explanation	Process with the specified asset ID is not available.
Action	Check the asset ID provided in the request.
INMWSI0069	Asset {0} is already associated with the server {1}
Explanation	The given asset key request is already associated with the specified application server.
Action	Remove the asset key from the request.
INMWSI0070	Asset {0} has been associated with the server {1} successfully
Explanation	The asset {0} has been associated with the server {1} successfully.
Action	The association between the asset key and the server was created successfully.
INMWSI0071	The asset {0} has not been associated with the server {1}
Explanation	The asset is not associated with the specified server.
Action	Associate the asset and the server first before disassociating.
INMWSI0072	Asset {0} has been disassociated from the server {1} successfully
Explanation	The given asset has been disassociated from the server successfully.
Action	The given asset has been disassociated from the server successfully.

INMWSI0076	Application server does not exist for given name {0}.
Explanation	An application server does not exist in the given name.
Action	Create an application server in the given name.
INOQJE0001	XQConnection for {0} is closed!
Explanation	The connection to the specified database is closed.
Action	Make sure that the connection in use is not closed prior to any later operation.
INOQJE0002	XQExpression is closed!
Explanation	The underlying expression is already closed.
Action	Make sure that the expression / connection in use is not closed prior to any later operation.
INOQJE0003	XQItemType mismatch! Item is not of type {0}.
Explanation	The specified item is not of the declared item type.
Action	Check for the compatibility of item types.
INOQJE0004	No cursor handle given!
Explanation	The cursor associated with the query handle was not found.
Action	This happens if there is no proper result set associated with the specified query.
INOQJE0005	Error reading from file - {0}
Explanation	This exception is thrown by the Java run-time architecture when an input error has occurred while reading from the specified file.
Action	Possible causes for this exception are an error reading from the specified file or the specified file is not found.
INOQJE0006	Error while parsing the XMLStream - {0}
Explanation	This is an error for unexpected errors during processing / XML handling, namely, to report well-formedness errors as well as unexpected processing conditions.
Action	The error message contains the explanation from the StAX parser. Modify the XML accordingly.

INOQJE0007	Parser configuration error - {0}
Explanation	Indicates a serious configuration error. An exception occurred during configuration of the XML parser being used.
Action	Add the corresponding XML parser jars in the CLASSPATH.
INOQJE0008	Factory Configuration Error - {0}
Explanation	A problem with configuration of the Parser Factories exists. This error will typically be thrown when the class of a parser factory specified in the system properties cannot be found or instantiated.
Action	Add the XML parser jars to the CLASSPATH and set the JAXP factory names.
INOQJE0009	Cannot access the XQItem of type XQITEMTYPE_ATTRIBUTE
Explanation	Indicates that the base item type of the current item is an attribute while writing the current item to a SAX stream.
Action	The current item should not be of type attribute.
INOQJE0010	SAX Parse Error - {0}
Explanation	Represents a general SAX error or warning.
Action	Possible causes for this error are if the value of the "org.xml.sax.driver" system property is null or the class cannot be loaded and instantiated.
INOQJE0011	I/O Error - {0}
Explanation	This exception is thrown by the Java run-time architecture when an input / output error of some kind has occurred while reading from the specified input source.
Action	Refer to the Java documentation for the error message.
INOQJE0012	End of the sequence is reached
Explanation	Execution of an XQuery returns a sequence of results. You can traverse the sequence of results using the XQResultSequence API.
Action	Reading or trying to modify items in the sequence after reaching the end of the sequence will result in this error.

INOQJE0013	Positioned before the start of the sequence
Explanation	Execution of an XQuery returns a sequence of results. You can traverse the sequence of results using the XQResultSequence API. Invoking the next() method for the first time will get to the first item in the sequence. If any operations are tried before this, this will result in this error.
Action	Invoke the next() method to get the first item.
INOQJE0014	Server {0} unavailable
Explanation	The specified database or server is not running.
Action	Provide the correct database URL, and check if the database is stopped.
INOQJE0015	Error when attempting to change the transaction mode
Explanation	The attempt to change the transaction mode failed.
Action	Check the Server documentation for the specified error code in the error message.
INOQJE0016	Error closing the {0}
Explanation	An attempt to close the underlying connection or result sequence that is specified along with the error failed.
Action	Make sure that the underlying connection is not closed before closing the result sequence.
INOQJE0017	Transaction failed while committing the changes
Explanation	Committing the changes failed.
Action	Check the Server documentation for the specified error code in the error message.
INOQJE0018	Transaction failed while rolling back the changes
Explanation	Rolling back the changes failed.
Action	Check the Server documentation for the specified error code in the error message.
INOQJE0019	The scrollability type {0} is not supported
Explanation	The mentioned scrollability type is not supported.
Action	Set a valid value for the scrollability type.

INOQJE0020	The property {0} is not supported
Explanation	The mentioned property is not supported.
Action	Provide a valid property.
INOQJE0021	A property mentioned in the list is not supported
Explanation	One of the mentioned properties in the property list is not supported.
Action	Check if all the properties in the property list are supported by the current implementation.
INOQJE0022	Error executing the server command : {0}
Explanation	An error occurred while executing the specified database command.
Action	Please refer to the documentation of the specified command.
INOQJE0023	XQTypeException thrown - Error Code : {0} Message : {1}
Explanation	External variable binding to XQuery failed.
Action	Check the server documentation for the error code displayed in the error.
INOQJE0024	Error fetching cursor
Explanation	Indicates a cursor based failure when fetching a number of documents from a cursor.
Action	Check the server documentation for the error code displayed in the error.
INOQJE0025	XQuery exception: {0}
Explanation	Error in the XQuery.
Action	Please check the XQuery for errors.
INOQJE0026	Error while opening cursor
Explanation	Indicates a failure when opening a cursor.
Action	Check the server documentation for the error code displayed in the error.
INOQJE0027	Error executing XQuery {0}: {1}
Explanation	Executing the XQuery failed. See the error code for more information.
Action	Check the server documentation for the error code displayed in the error.

INOQJE0028	Sequence is non-scrollable
Explanation	Cannot scroll on a non-scrollable sequence.
Action	Avoid scrolling, because the sequence is non-scrollable.
INOQJE0029	Failed because of following exception
Explanation	The cause of the exception is specified in the error message.
Action	Check the server documentation for the specified error code in the error message.
INOQJE0030	Error creating the cached item
Explanation	Creating a cached item failed.
Action	Check if the items are closed.
INOQJE0031	Error binding the {0} Message - {1}
Explanation	Binding the specified value to the expression / prepared expression failed.
Action	Check if the values declared and bound to the query are the same.
INOQJE0032	Error executing the request with error [{0} {1} {2} {3}]
Explanation	The message appears with the specific error code and information from the server.
Action	Refer to the server documentation for the specified error code.
INOQJE0033	Sequence not scrollable
Explanation	Cannot scroll a non scrollable sequence.
Action	Avoid scrolling, because the sequence is non-scrollable.
INOQJE0034	Expected type {0} Current type {1} Location {2}
Explanation	The expected type and the current type specified do not match.
Action	Check the types mentioned in the error at the specified location.
INOQJE0035	Expected start or end tag {0}
Explanation	When trying to move to the next tag in the resulting XML Stream, any white space , COMMENT, or PROCESSING_INSTRUCTION is skipped until a START_ELEMENT or END_ELEMENT is reached. If anything other than white space characters, COMMENT, PROCESSING_INSTRUCTION, START_ELEMENT, END_ELEMENT is encountered, this error is thrown along with the location number.
Action	Check the error message for the missing start or end in the XML.

INOQJE0036	{0} cannot be null!
Explanation	The underlying object specified is null.
Action	Make sure that the underlying object is properly initialized.
INOQJE0037	The {0} method is not supported
Explanation	The method specified in the error message is not supported.
Action	The specified method is not supported by the current XQJ implementation.
INOQJE0038	XQPreparedExpression is closed!
Explanation	The underlying prepared expression is already closed.
Action	Make sure that the XQPreparedExpression is not closed before any usage.
INOQJE0039	XQSequence is closed!
Explanation	The underlying sequence is already closed.
Action	Make sure that the XQSequence is not closed before any usage.
INOQJE0040	XQItem is closed!
Explanation	The underlying item is already closed.
Action	Make sure that the XQItem is not closed before any usage.
INOQJE0041	The value for the property {0} cannot be null
Explanation	The value for the specified property in the error message cannot be null.
Action	Mention a property value for the specified property name in the error message.
INOQJE0042	Access Failure Exception - {0}
Explanation	The cause for the exception is specified in the error message.
Action	Check the server documentation for the specified error code in the error message.
INOQJE0043	Invalid user ID or password
Explanation	The supplied user ID and password combination is invalid.
Action	Check the user ID and password.

INOQJE0044	Cannot access the XQItem of type XQITEMKIND_ATTRIBUTE
Explanation	This indicates that the item kind of the current item is an attribute while writing the current item to a SAX stream.
Action	The current item should not be of type attribute.
INOQJE0045	Error creating the XQ item
Explanation	An error occurred while creating an XQ item.
Action	Check if the items are closed.
INOQJE0046	Binding to {0} not supported
Explanation	While binding an external variable to an XQuery, the type specification was not valid. Either the type is not supported at all for binding external variables, or it was used with a binding method that does not support this specific type.
Action	Use one of the supported types with a proper binding method.
UDDIE00002	No businessKey was defined
Explanation	Keys have to be specified to fetch the details.
Action	Please provide keys in the UDDI request to fetch the details.
UDDIE00005	At least keyBag or transferToken should be specified
Explanation	The discard_transferToken request is not valid. It has to be according to the UDDI v3 specification.
Action	Please specify transferToken to discard it.
UDDIE00006	The value of the attribute maxRows is not a valid number.
Explanation	The value for the maxRows attribute in the UDDI request should be a number.
Action	Please specify an integer value for the maxRows attribute in the UDDI request.
UDDIE00007	{0} is not a valid find qualifier value in version {1}.
Explanation	The find qualifier is not supported in the specified version.
Action	Please specify find qualifiers corresponding to the UDDI version.

UDDIE00008	No entityKey was defined
Explanation	Keys have to be specified to fetch the operationa info.
Action	Please provide keys in the get_operationalInfo request to fetch the operational information.
UDDIE00011	Publisher assertions are null
Explanation	The add_publisherAssertions, delete_publisherAssertions and set_publisherAssertions requests should have publisher assertions in them.
Action	Please add the publisherAssertions element in add_publisherAssertions, delete_publisherAssertions and set_publisherAssertions requests.
UDDIE00012	Exactly one BusinessKey must be defined.
Explanation	Either fromKey, toKey or businessKey should be specified.
Action	Please specify a value for the toKey or fromKey or businessKey attribute of the find_relatedBusiness call.
UDDIE00013	Only one keyedReference element may be defined in a find_relatedBusinesses message.
Explanation	The publisher assertion should contain only one keyedReference element.
Action	Please provide one KeyedReference in the find_relatedBusiness call.
UDDIE00014	{0} is not a valid UUID.
Explanation	The specified key is not valid.
Action	Please make sure the key is valid according to the UDDI standard.
UDDIE00015	The specified names are not valid for version
Explanation	The names are not specified according to the UDDI specification.
Action	Please specify valid names.
UDDIE00016	Only one key may be defined
Explanation	Multiple keys are defined for the UDDI entity.
Action	Please specify a single key for the UDDI entity.

UDDIE00017	The fromKey element is mandatory in a publisherAssertion document
Explanation	The fromKey element does not contain a valid value.
Action	Please provide values for the fromKey element in the publisherAssertion element.
UDDIE00018	The toKey element is mandatory in a publisherAssertion document
Explanation	The toKey element does not contain valid value.
Action	Please provide values for the toKey element in the publisherAssertion element.
UDDIE00019	The keyedReference element is mandatory in a publisherAssertion document
Explanation	The keyedReference element does not contain valid value.
Action	Please provide values for the keyedReference element in the publisher assertion element.
UDDIE00020	The keyedReference element in a publisherAssertion must be defined exactly one time
Explanation	The publisher assertion should contain only one keyedReference element.
Action	Please provide one KeyedReference in the publisher assertion element.
UDDIE00022	{0} is not a valid findQualifier value
Explanation	Provided findQualifier is not valid. The valid qualifiers can be found in UDDI specification.
Action	Please provide findQualifiers according to the UDDI specification
UDDIE00024	The string representation may not be empty.
Explanation	A value for the element in the UDDI request is not according to the UDDI specification.
Action	Please make sure the UDDI request is valid according to UDDI specification.
UDDIE00025	A tag of the language code must have at least one character and no more than eight characters.
Explanation	A value for the language code in the UDDI request does not comply with the UDDI specification.
Action	Please make sure the UDDI request is valid according to UDDI specification.

UDDIE00026	A language code may only contain ASCII alphanumerics.
Explanation	A value for the language code in the UDDI request does not comply with the UDDI specification.
Action	Please make sure the UDDI request is valid according to UDDI specification.
UDDIE00027	Could not authenticate the user {0}
Explanation	The user specified in the UDDI request is not valid.
Action	Please specify a valid CentraSite user.
UDDIE00042	{0} does not represent a businessKey.
Explanation	CentraSite does not contain any business entity with the specified key.
Action	Please make sure the business key specified in the request is valid.
UDDIE00043	No businessKey in the registry matches the key {0}.
Explanation	CentraSite does not contain any business entity with the specified key.
Action	Please make sure the business key specified in the request is valid.
UDDIE00045	No entity in the registry matches the key {0}.
Explanation	CentraSite does not contain any UDDI entity with the specified key.
Action	Please make sure the key specified in the request is valid.
UDDIE00047	The value of maxRows parameter is not a valid number.
Explanation	The value for the maxRows attribute in the UDDI request should be a number.
Action	Please specify an integer value for the maxRows attribute in the UDDI request.
UDDIE00049	The contact {0} already exists. Please specify a different contact.
Explanation	The specified contact already exists in the CentraSite. A contact cannot be present in multiple businesses
Action	Please make sure the contact is not present in any other business
UDDIE00050	The value of maxEntities parameter is not valid
Explanation	The maxEntities attribute of the subscription should contain an valid non-negative number.
Action	Please provide valid non-negative number for the maxEntities attribute.

uddi:107e04bd-bdf4-11e2-b6b3-c566c3aaf997 – Verify Required Attributes

Explanation During asset instance creation and modification, verifies whether the required attributes of that Asset Type are provided with values

uddi:18bf0e3d-bdf4-11e2-b6b3-886f1ce73523 – Verify Required Attributes Policy

Explanation During asset instance creation and modification, this policy verifies whether the required attributes of that Asset Type are provided with values.

uddi:44e3e2de-064c-432f-b67a-8fbca0fb04d6 – Invoke webMethods Integration Server

Explanation Processing steps calling an Integration Server (IS) Service which will be executed when the consumer invokes the Virtual Service.

6 CloudStreams Messages

0010.0715E	CloudStreams Upgrade, did not complete successfully.
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. This message indicates the upgrade was not successful. There should be a previous error message in the server log that indicates the problem.
Action	See actions for message ID '0010.0702'
0030.0092	PublisherPropsObserver - Unknown sender data type ({0})
Explanation	The properties observer received an invalid sender type.
Action	This indicates a coding error. Non-Mediator code should never call this method.
0030.0094	PublisherPropsObserver - Unknown parameters data type ({0})
Explanation	The properties observer received an invalid update object type.
Action	This indicates a coding error. Non-Mediator code should never call this method.
0030.0099	PublisherPropsObserver - Unknown wrapper factory data type ({0})
Explanation	This message has incorrect text. It should indicate an invalid data type for UDDP publisher bean.
Action	Update the pg configuration file to use a proper UDDI publisher data type.

0030.0100	PublisherPropsObserver - Unable to find wrapper factory
Explanation	There is no UDDI publisher configured, but its properties are being changed.
Action	Update the configuration file. Either configure a UDDI publisher or unregister the UDDI properties observer.
0030.0104	Exception encountered initializing logging resource: {0}
Explanation	A problem was encountered while setting up a logger for Mediator to use. There should be an exception message with more details.
Action	Fix the problem identified by the exception message.
0030.0109	PublisherPropsObserver - Can't convert string ({0}) to integer for publishing interval, ignoring input
Explanation	The value received for performance data reporting interval was not a valid numeric string.
Action	Make sure a numeric value is input.
0030.0113	PublisherPropsObserver - Unknown pg service deployer data type ({0})
Explanation	The data type of the PG Service Deployer bean is invalid.
Action	Update the pg configuration file to use a proper PG Service Deployer data type.
0030.0301	ConsumerApplicationManager.convert - cannot handle null request
Explanation	Unable to create Consumer deployment object for update.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0302	ConsumerApplicationManager.convert - cannot convert consumer with null {0}
Explanation	Invalid Consumer deployment object was found.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0303	VirtualServiceDeployer.{0} - cannot handle null {1}
Explanation	A null reference was found during a deployment activity. The object and activity are identified in the message.
Action	Probably bad SOAP request for deployment, fix request.

0030.0304 Action	VirtualServiceDeployer.deploy - service ({0}) already deployed, undeploying Info level message, no action required.
0030.0305 Explanation Action	VirtualServiceDeployer.undeploy - cannot undeploy service ({0}), not deployed Attempt to undeploy virtual service failed. Verify that Mediator and CentraSite agree that the service is no longer deployed. If not, try undeploying this service again, or restarting Mediator/IS.
0030.0306 Explanation Action	VirtualServiceDeployer.{0} - caught this: type({1}) message({2}) Unable to deploy virtual service. See exception message for more details. Address the problem indicated by exception and try to deploy again.
0030.0309 Explanation Action	ClusteredServiceDeployer{0} - cannot handle null {1} Unable to create VS deployment object for update. Probably bad SOAP request to Deployer, fix request.
0030.0315 Explanation Action	ClusteredConsumerManager.updateConsumer - cannot handle null consumer Unable to create Consumer object for update. Probably bad SOAP request to Deployer, fix request.
0030.0318 Explanation Action	ClusteredServiceDeployer - cannot deploy null info to cache A problem occurred while attempting to convert a PGService for deployment to shared cache. There should be another message describing the conversion or deployment issue. Fix the conversion or deployment problem.
0030.0319 Explanation Action	ClusteredServiceDeployer - cannot undeploy null service name from cache Virtual service undeployment requires a non-empty service name. This is problem with undeployment request payload. Fix the undeployment request payload.

0030.0328	ConsumerApplicationManager.{0} - cannot handle null update request
Explanation	Invalid Consumer deployment request for update.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0330	ConsumerApplicationManager - not updating consumer ({0}), modification date, ({1}), is no more recent
Action	Info level message, no action required.
0030.0333	ConsumerApplicationManager.{0} - caught this: type({1}) message({2})
Explanation	Unable to create and persist Consumer object for update.
Action	Either bad SOAP request to Deployer, fix Request. Or file system problem, check file system permissions. See logged message text for specific error details.
0030.0336	Consumer Application Update Failed; requested update has invalid {0} field
Explanation	Invalid consumer name or key in remove request.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0337	Consumer Application Remove Failed; consumer ({0}) does not exist
Explanation	Attempt to remove consumer failed.
Action	Reply to CentraSite Deployment attemp should indicate error. Try redeploying this consumer or resynchronizing all consumers.
0030.0343	RegisteredConsumerNamesManager.{0} - cannot handle null update request
Explanation	Invalid RegisteredConsumerNames deployment request for update.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0344	Registered Consumer Names Update Failed; requested update has invalid {0} field
Explanation	Invalid service name or consumer names in registered consumer names update request.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0346	RegisteredConsumerNamesManager - not updating consumer names registered to ({0}), modification date, ({1}), is no more recent
Action	Info level message, no action required.

0030.0347	RegisteredConsumerNamesManager.{0} - cannot handle null update request
Explanation	Invalid RegisteredConsumerNames deployment request for remove.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0348	Registered Consumer Names Remove Failed; requested update has invalid {0} field
Explanation	Invalid service consumer name in remove request.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0350	Registered Consumer Names Remove Failed; service ({0}) has no registered consumers
Explanation	Invalid request to remove RegisteredConsumerNames, must include at least one consumer name.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0352	RegisteredConsumerNamesManager.{0} - caught this: type({1}) message({2})
Explanation	Unable to create and persist RegisteredConsumerNames object for update.
Action	Either bad SOAP request to Deployer, fix Request. Or file system problem, check file system permissions. See logged message text for specific error details.
0030.0356	VirtualServiceDeployer - unable to get endpoints for {0}, caught this: type({1}), msg({2})
Explanation	Unable to obtain endpoint for deployed service.
Action	Probably bad SOAP request to Deployer or bad VSD, fix one or both.
0030.0357	ClusteredRegisteredConsumerNamesDeployer.updateConsumerNames - cannot handle null reg names object
Explanation	Unable to create RegisteredConsumerNames object for update.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0358	Consumer Application Remove Failed; requested update has invalid name and key fields, both are empty
Explanation	Consumer remove request must have either name or key to identify consumer; both were null or empty.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0359	ConsumerApplicationManager - Consumer update request has invalid IP range; from {{0}} to {{1}}
Explanation	Consumer update request had invalid IP address range.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0361	VirtualServiceDeployer - redeploying undeployed service {{0}}, deployment failed for newer version
Action	Info level message, no action required.
0030.0362	VirtualServiceDeployer - a problem was encountered during deployment, {{0}} will be undeployed and replaced if necessary
Action	Info level message, no action required.
0030.0363	VirtualServiceDeployer.{{0}} - service{{1}} caught this: type{{2}} message{{3}}
Explanation	Message context encountered an exception while attempting to redeploy or undeploy a virtual service. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0030.0364	Deployment request for service: {{0}}. Registered consumer name element was processed, but the existing modification date is the same as the request. {{1}}
Action	Info level message, no action required.
0030.0366	UddiPropertiesObserver - Password lookup failed; type {{0}}, message {{1}}
Explanation	A problem was encountered by attempting to retrieve stored password. There should be an exception with more specific trouble description.
Action	Fix the problem identified by the exception message.
0030.0367	UddiPropertiesObserver - Unable to activate performance date policies; type {{0}}, message {{1}}
Explanation	The performance data deployer was unable to run. This message should include more details regarding the reason.
Action	Fix the problem identified by the exception message.

0030.0370	UddiPropertiesObserver - Unable to connect to UDDI: ({0}); property updates saved, but data collection is OFF.
Explanation	A problem was encountered during publisher test.
Action	This is probably a bad configuration parameter, fix it.
0030.0371	UddiPropertiesObserver - Unable to convert port string ({0}) to integer, using default port {1}
Explanation	The value input for 'UDDI port' number is non-numeric.
Action	Input an numeric port value.
0050.0001	Unable to find Policy Element in the VSD:{0}
Explanation	An exception was encountered while attempting to extract a policy element from VSD. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0002	Unable to create Rampart properties:{0}
Explanation	An exception was encountered while attempting to assemble Rampart keystore properties. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0003	Unable to replace static Rampart configuration with configured properties:{0}
Explanation	An exception was encountered while attempting to re-configure Rampart keystore properties. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0004	Unable to create Rampart Configuration Element:{0}
Explanation	An exception was encountered while attempting to convert Rampart configuration string to XML. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0005	Unable to create XPath to select first Policy Alternative:{0}
Explanation	An exception was encountered while attempting to create an Xpath object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0006	Error while removing existing RampartConfig elements:{0}
Explanation	An exception was encountered while attempting to remove configuration elements. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0007	Required configuration information to enable WS-Security processing is missing. Unable to process service: {0}. Please ensure Keystore/Truststore information is configured
Explanation	Service could not be initialized due to a problem with keystore/truststore configuration.
Action	Fix the security configuration.
0050.0011	Exception while determining hostname or IP address of the server:{0}
Explanation	An exception was encountered while attempting to resolve a host name or IP address. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0013	CloudStreams needs the repository location of the SOAP stack
Explanation	Configuration does not include a valid location for Axis2 repositoryconfiguration.
Action	Fix the axis2 configuration.
0050.0016	ServerManager ready for processing
Action	Info level message, no action required.
0050.0017	CloudStreams encountered exception while starting ServerManager:{0}
Explanation	An exception was encountered during configuration of Axis2 listeners. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0018	Invalid Port specified. Using default configuration: {0}
Explanation	The 'port' property has a non-numeric string value, the value configured in Axis is used.
Action	Make sure the property value to numeric.
0050.0019	Port {0} is already in use. Trying alternate
Explanation	The port indicated in the message is not available to use with a new socket.
Action	Specify another port value in the system 'port' property or Axis configuration.
0050.0020	Exception while creating "id" selection XPath: {0}
Explanation	Message context encountered an exception while attempting to create an XPath object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0021	Found Element within Resources element with id: {0}
Action	Info level message, no action required.
0050.0022	Exception while selecting element with id:{0} in Resources Element: {1}
Explanation	Message context encountered an exception while attempting to extract the indicated element from XML. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0023	CloudStreams received a response for the request with message Id :{0} But a callback is not registered (anymore) to process this response
Explanation	No callback was registered at the time this response was processed.
Action	This is probably a VS configuration problem.
0050.0024	CloudStreams received a response message without a message Id
Explanation	There was a problem relating the native service response to a virtual service request.
Action	Look for previously logged message indicating that message Id was not used.

0050.0025	CloudStreams encountered an exception: {0}. No error handlers found - [Message Dropped]
Explanation	This could be a configuration problem. An exception was encountered while attempting to handle a fault. The associated exception message should include more details regarding the problem.
Action	Fix the configuration, or other problem identified by the exception message.
0050.0026	Outbound client can't locate policy from the property :{0}
Explanation	The Synapse message context does not contain an entry for the property key identified in the message.
Action	This is a policy configuration problem.
0050.0027	CloudStreams outbound client encountered error:{0}
Explanation	Client encountered an exception while attempting to send a message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0029	VSD with incorrect Namespace:{0}. Unable to create PGService.
Explanation	The namespace found in the VSD is unknown.
Action	This is a virtual service configuration problem.
0050.0031	The {0} element is required for a CloudStreams service
Explanation	Some element used during service deployment was found to be null. The specific element should be identified in the message text.
Action	This is a virtual service configuration problem.
0050.0032	The {0} sequence element is required for a CloudStreams service
Explanation	The VSD is missing the sequence element identified in the message.
Action	This is a virtual service configuration problem.
0050.0033	The inSequence for VSD:{0} is invalid.
Explanation	The sequence identified in the message failed validation. Look for recent error message with more validation failure details.
Action	This is a virtual service configuration problem.

0050.0034	The outSequence for VSD:{0} is invalid.
Explanation	The sequence identified in the message failed validation. Look for recent error message with more validation failure details.
Action	This is a virtual service configuration problem.
0050.0035	Exception while parsing Virtual Service String Definition:{0}
Explanation	An exception was encountered while attempting to parse the virtual service description. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0036	Unable to create Virtual Service Definition
Explanation	Unable to create XML object from the VSD string.
Action	This is a virtual service configuration or deployment problem.
0050.0037	PGServiceFactory encountered and exception while creating the PGService: {0}
Explanation	An exception was encountered while attempting to validate input or output sequence or during WSDL URI processing. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0038	Invalid parameter specified for PGService: {0}
Explanation	The attribute named in the message has no value in the VSD.
Action	This is a virtual service configuration problem.
0050.0039	Exception {0} for PGService: {1}
Explanation	An exception was encountered while attempting during service creation. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0040	No PGService found with name: {0}
Explanation	Attempting to undeploy or get endpoints for a service that does not exist.
Action	Make sure the virtual service exists before operating on it.

0050.0041	WSStack exception processing service: {0} Cause: {1}
Explanation	An AxisFault was encountered while attempting to either undeploy or get endpoints for the virtual service named in the message. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.
0050.0042	Unable to locate the WSStack configuration. Can't deploy Virtual Service:{0}
Explanation	The Synapse configuration cannot supply an Axis configuration.
Action	This is an Axis2/Synapse/WS-Stack configuration problem.
0050.0043	A Virtual Service with name:{0} already exists. Unable to deploy.
Explanation	Cannot deploy an Axis service when one already exists with the same name.
Action	Undeploy the existing service before attempting to redeploy or use the same name.
0050.0044	Unable to locate WSStack configuration. Please check if WSStack is enabled/correctly configured.
Explanation	Unable to retrieve the configuration context supplier bean.
Action	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
0050.0045	Invalid parameter passed for Virtual Service creation:{0}
Explanation	An attempt to persist the VSD for a service found a null element. The VSD is not allowed to be null.
Action	This may be the result of invalid deployment payload; fix the VSD.
0050.0046	Unable to persist VSD:{0} to disk. Encountered error:{1}
Explanation	An exception was encountered while attempting to serialize the VSD for the service identified in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0047	Unable to {0} VSD:{1}. Error:{2}
Explanation	This message is used in several different error conditions, as indicated by the object of 'unable to...'.
Action	Fix the 'unable to...' problem for the service identified by 'VSD:'.

0050.0048	Error getting endpoints for service:{0}, Cause: {1}
Explanation	An exception was encountered while attempting to get endpoints. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0049	Exception while creating PGService: {0}, Cause: {1}
Explanation	An AxisFault was encountered while checking if deploying service already exists or while attempting to register service with Axis2. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0050	Error while engaging module: {0}
Explanation	An AxisFault was encountered while attempting to engage the Axis2 module indicated in the message. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.
0050.0052	Axis was unable to load module {0}
Explanation	An exception was encountered while attempting to load and engage module identified in message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0053	Loading the WSDL : {0}
Action	Info level message, no action required.
0050.0055	PGService {0} encountered error while converting wsdl element to a StreamSource:{0}
Explanation	An exception was encountered while attempting to read WSDL from manifest. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0057	Unknown WSDL format for PGService:{0}, neither WSDL 1.1 nor WSDL 2.0
Explanation	The current WSDL element has unknown or no namespace associated.
Action	This is a virtual service configuration problem.

0050.0060	Populating SOAP service using WSDL
Action	Info level message, no action required.
0050.0061	Unable to find a WSDL for the PGService:{0}. Assuming a POX or Legacy service
Action	Info level message, no action required.
0050.0062	PGService: {0} is available on transports {1}
Action	Info level message, no action required.
0050.0063	Adding PGService:{0} to the SOAP Stack
Action	Info level message, no action required.
0050.0064	Removing PGService:{0} due to error: axisFault.getMessage()
Action	Info level message, no action required.
0050.0065	Exception while setting policy on PGService:{0}
Explanation	An exception was encountered while attempting to engage WS-Policy module. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0066	Setting policy with id:{0} on CloudStreams service:{1}
Action	Info level message, no action required.
0050.0068	Successfully created service in SOAP Stack for PGService:{0} containing {1} endpoint(s).
Action	Info level message, no action required.
0050.0069	Error{1} on setting parameter :{0} on CloudStreams service
Explanation	An exception was encountered while attempting to set a parameter into an Axis service. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0070	creating new CloudStreams service: {0}
Action	Info level message, no action required.
0050.0071	Unable to find service directory for service {0}
Explanation	Unable to persist WSDL assets because the virtual service directory does not exist.
Action	Redeploying the virtual service should create the service directory.
0050.0074	Error: {0} while reading from file {1}
Explanation	An exception was encountered while attempting to read the proxy file identified in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0076	Scheduled task[{0}] with startup delay of {1} ms and interval of {2} ms
Action	Info level message, no action required.
0050.0077	Error initializing JMS transport listener. Cause: {0}
Explanation	An exception was encountered while attempting to register JMS listener. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0078	Unable to stop TransportListener called:{0}. Exception:{1}
Explanation	An AxisFault was encountered while attempting to stop the JMS transport listener during bean initialization. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.
0050.0083	Error {0} occurred while updating the load balancer properties
Explanation	An AxisFault was encountered while attempting to add load balancer URL to an Axis transport description. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.

0050.0084	Loadbalanced Endpoint: [{0}] failed!
Explanation	A mediation operation to a load balanced endpoint has failed. The endpoint indicated in the message is not available. This usually indicates a communication problem with the targeted server.
Action	Fix the targeted server.
0050.0086	Unable to get the IS keystore manager - please check your configuration!
Explanation	Unable to retrieve the keystore manager bean.
Action	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
0050.0087	Keystore initialization failed! Please check the server log for more details
Explanation	Unable to load the keystore file.
Action	This is a Mediator security configuration problem.
0050.0088	Truststore initialization failed! Please check the server log for more details
Explanation	Unable to load the truststore file.
Action	This is a Mediator security configuration problem.
0050.0089	Unable to get the Rampart Configuration Handler - please check your configuration!
Explanation	Unable to retrieve the Rampart creation handler bean.
Action	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
0050.0099	VSD proxy loader, Unable to delete file: {0}
Explanation	The file or directory indicated in the message could not be deleted.
Action	Determine why the file or directory could not be deleted and make it deletable.
0050.0100	VSD proxy loader, Unable to delete directory: {0}
Explanation	The directory indicated in the message could not be deleted.
Action	Determine why the directory could not be deleted and make it deletable.
0050.0101	VSD proxy loader, Unable to create directory: {0}
Explanation	The file or directory indicated in the message could not be created.
Action	Delete the directory so that Mediator can create it again.

0050.0105	Unable to determine fault cause. Please check the log file for more information!
Explanation	This error indicates that Mediator could not determine the cause for the error when trying to extract the soap fault message from the response. Additional errors if any would be present in the IS log file (server.log)
0050.0208	Error resolving WSDL URI. Cause {0}
Explanation	An exception was encountered while attempting to resolve URI elements into XML source. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0209	Error initializing virtual service factory. Cause: {0}
Explanation	An exception was encountered while attempting to initialize XPath elements. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0210	Error setting location of virtual service proxies directory. Path: {0} Cause: {1}
Explanation	An exception was encountered while attempting to use the directory identified in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0211	Unable to determine service endpoint URI for this service: {0} No transport listener defined for the virtual service's transport protocol.
Explanation	The configuration context's listener manager cannot find an endpoint for the current service. This may indicate that the hosting IS does not have an appropriate listener registered.
Action	This is a configuration problem, either in IS ports or VSD
0050.0212	Unknown exception deploying virtual service: {0} Cause: {1}
Explanation	An exception was encountered while attempting to get an endpoint reference from the context listener manager. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0214 **Error {0} manifest from external resources associated with virtual service: {1}. Cause: {2}**

Explanation An exception was encountered while attempting to read WSDL from manifest. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0215 **Error initializing virtual service transformation bean with this xslt: {0} Cause: {1}**

Explanation An exception was encountered while attempting to read the transformation file. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0216 **Error transforming raw virtual service string. Cause: {0} virtual service xml: {1}**

Explanation An exception was encountered while attempting to read the Mediator's transformation file. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0221 **CloudStreams has an internal configuration error. It's deploy-time xslt transformation file path does not exist. Path: {0}**

Explanation An exception was encountered while attempting to read the file identified in the message. The associated exception message should include more details regarding the problem.

Action This is a configuration problem; make sure the file identified in the message exists and contains the transformation.

0050.0235 **URI creation error: {0}**

Explanation An exception was encountered while attempting to resolve an endpoint URI. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0250 **Could not find user-specified value for HTTP method! Defaulting to inbound request HTTP method {0}**

Explanation The 'routing method' context variable has an invalid value.

Action If the value indicated in the message is acceptable, no action is required. Otherwise virtual service configuration must be changed.

0050.0252	Could not set HTTP method for outgoing request for endpoint: {0}
Explanation	The outgoing request's message context is null.
Action	This is a virtual service/policy configuration problem.
0050.0300	Context variable name "{0}" is already declared. Multiple declarations in the same context is not allowed.
Explanation	Context variable names must be unique for a service.
Action	This is a service configuration problem.
0050.0303	Attempt to reference context variable without providing a message context. Custom context variables may only be declared with a 'session' scope at this time. Other scopes are not supported.
Explanation	Attempting to get context variable or context variable map, but the message context (or session) is null.
Action	Earlier error messages should provide clues to help determine why a valid message context is null.
0050.0306	Context variable name is required for variable declaration.
Explanation	Variable name validation failed, QName is null or is missing a local part.
Action	This is a context variable configuration problem.
0050.0307	Namespace URI and prefix is required for custom variable declaration. varName: {0}
Explanation	Variable name validation failed, Namespace URI and prefix must both be neither null nor empty.
Action	This is a context variable configuration problem.
0050.0308	Context variable name must be a valid identifier (alpha-numeric, \$, or _ permitted) Found: {0}
Explanation	Variable name validation failed, name has invalid characters.
Action	This is a context variable configuration problem.

0050.0309 **Core Context variables cannot have a namespace or prefix as part of its declaration. varName: {0}**

Explanation Variable name validation failed, prefix for core variables must be empty.

Action This is a context variable configuration problem.

0050.0310 **Either a Message context or axis service name is required when creating a custom context variable. varName: {0}**

Explanation Both service name and Axis2 message context are null, this is not acceptable. This is probably the result of attempting to deploy a service with no service name.

Action Verify that service configuration is correct.

0050.0311 **Attempt to create a custom variable using a message context with no AxisService. varName: {0}**

Explanation The axis2 message context is corrupted, it should identify a service.

Action Earlier error messages should provide clues to help determine why a valid message context could not be created.

0050.0312 **Unexpected error creating custom CloudStreams context variable. varName: {0} reason: {1}**

Explanation An exception was encountered while attempting to create a custom context variable. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0313 **Unexpected error removing custom CloudStreams context variable for service: {0} reason: {1}**

Explanation An exception was encountered while attempting to remove or inject a custom context variable. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0314 **Unexpected error initializing core CloudStreams context variables. reason: {0}**

Explanation An exception was encountered while attempting to create a context variable. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0316	Unexpected error getting CloudStreams context variable value. varName: {0} reason: {1}
Explanation	An exception was encountered while attempting to get the value of the context variable named in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0317	Unexpected error setting CloudStreams context variable value. varName: {0}, value:{1}, reason: {2}
Explanation	An exception was encountered while attempting to set the context variable value named in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0318	Expected a virtual service name for this method operation, but none was provided.
Explanation	Attempting to get context variable map for a null service name.
Action	Earlier error messages should provide clues to help determine why a valid service name is null.
0050.0321	CloudStreams context variable adapter unable to locate this type: {0}
Explanation	The context variable type indicated in the message is unknown.
Action	This is a context variable configuration problem.
0050.0322	Unexpected error getting core CloudStreams context variable value from adapter. type: {0}
Explanation	An exception was encountered while attempting to get the context variable value named in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0323	Only string and int schema types are supported at this time. Type: {0}, declared with "{1}" context variable is not supported.
Explanation	The context variable schema type is not among the accepted types.
Action	This is a service configuration problem.

0050.0324	Context variable name declarations cannot contain \$ sign symbols in the name since that is used as a reference operator. varName: {0}
Explanation	Variable name validation failed, name must include substitution character, (dollar sign).
Action	This is a context variable configuration problem.
0050.0325	Unable to return list of context variables declared for this service: {0} Reason: {1}
Explanation	An AxisFault was encountered while attempting to retrieve a list of context variable names. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.
0050.0326	Unable to return list of context variables declared for this message context: {0} Reason: {1}
Explanation	An AxisFault was encountered while attempting to get a list of context variables or list of variable keys. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.
0050.0327	Context variable name deployed with virtual service {0} references an unknown namespace prefix. name attribute: {1}
Explanation	Context variable identified in message has invalid namespace.
Action	This is a context variable configuration problem.
0050.0328	Exception while copying context variables from request to response message context. Reason: {0}
Explanation	An AxisFault was encountered while attempting to copy context variable names between contexts. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.
0050.0329	Could not create backup directory for failed services! Dir tried = {0}
Explanation	An attempt to create the 'failed services' directory has failed.
Action	Determine why the directory could not be created. Either fix the creation problem or specify a different directory.

0050.0331	Error occurred when getting backup directory for path {0}
Explanation	An exception was encountered while attempting to determine directory for backing up failed services. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0333	Error occurred while resolving URI; message = {0}
Explanation	An exception was encountered during URI resolution. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0337	Previously selected {0} port {1} is no longer enabled or available!
Explanation	The message indicates port number and type. The requested port is not available.
Action	Select a new port number for the indicated port type.
0050.0343	Context variable API expected an IData object for ctx variable, {0}, but received this: {1}
Explanation	The data element from which a context variable is to be extracted has an unknown data type.
Action	This is probably a flow configuration problem; where the pipeline was populated with an invalid value.
0050.0344	Attempt to insert {0} core ctx variable with invalid value type: {1}. Expected a collection of this type: {2}
Explanation	.The allowable data type for a core context variable is restricted, depending on variable type.
Action	.This is a context variable configuration problem.
0050.0345	Unable to access array element [{0}] in SOAP_HEADERS core ctx variable. Cause: {1}
Explanation	The index value indicated in the message must be numeric.
Action	This is a context variable configuration problem.

0050.0346	Invalid array or key reference for core ctx variable. This substitution string has mismatched braces: {0}
Explanation	The context variable substitution string is invalid, mismatched brace characters were found.
Action	This is a context variable configuration problem.
0050.0347	Attempt to create an IData value for a ctx variable from an unsupported class type. CtxVar: {0} Bad type: {1}
Explanation	The context variable to be converted to IData has an unknown data type.
Action	This is a context variable configuration problem.
0050.0348	Unable to append header block to the end of the soap header. Cause: {0}, soapHeader element: {1}
Explanation	An exception was encountered while attempting to add append new SOAP header block. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0349	Unable to prepend header block to the beginning of the soap header. Cause: {0}, soapHeader element: {1}
Explanation	An exception was encountered while attempting to add prepend new SOAP header block. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0350	Unable to remove header block from the soap header. Cause: {0}, soapHeader: {1}
Explanation	An exception was encountered while attempting to remove a SOAP header block. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0351	Unable to set header block at position {0} of the soap header. Cause: {1}, soapHeader element: {2}
Explanation	An exception was encountered while attempting to replace a SOAP header block with a new one. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0355	Could not create STS configuration directory! Dir tried = {0}
Explanation	The file or directory indicated in the message could not be created.
Action	Delete the directory so that Mediator can create it next time it is required.
0050.0357	Error occurred when getting STS configurations directory for path {0}
Explanation	An exception was encountered while attempting to create the directory indicated in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0362	Error occurred when creating STS client
Explanation	An exception was encountered while attempting to create an STS client object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0364	Error occurred when initializing default STS configuration store
Explanation	An exception was encountered while attempting to create JAXB marshaller/unmarshaller pair. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0365	Could not find STS configuration file with path {0}
Explanation	An attempt to delete the file indicated in the message failed because the file does not exist.
Action	Check this directory [IS_INSTALL_DIR\packages\WmMediator\config\resources\security\sts] to make sure there is an xml file with the STS config name being deleted. For e.g. if the STS config being deleted is MySTS, then there should be an XML file called MySTS.xml in the mentioned directory
0050.0366	Could not delete STS configuration file with path {0}
Explanation	An attempt to delete the file indicated in the message returned 'false'. The file was not deleted.
Action	Make sure the STS config file present under [IS_INSTALL_DIR\packages\WmMediator\config\resources\security\sts] is present and not locked by any other application (e.g. opened in an editor like Windows Notepad). Check the log file to see if there is any java IOException related to disk errors.

0050.0367	Error occurred when saving STS configuration to disk
Explanation	An exception was encountered while attempting to marshal configuration object into file. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0368	Error occurred when reading STS configuration from file {0}
Explanation	An exception was encountered while attempting to unmarshal configuration file indicated in the message into JAXB object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0371	Error getting IS keystore manager instance!
Explanation	An exception was encountered while attempting to get a reference to the keystore manager. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0373	Error occurred when adding rampart configuration to STS policy
Explanation	An exception was encountered while attempting to configure the STS policy. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0379	Error occurred when adding assertion to STS policy
Explanation	An exception was encountered while attempting to add an assertion to a WS-Policy artifact. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0382	Error occurred when adding OnBehalfOf element to WS-Trust request element
Explanation	An exception was encountered while attempting to add the WS-Trust element to a request. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0383	Error occurred when sending WS-Trust request to STS to obtain SAML assertion
Explanation	An exception was encountered while attempting to add SAML assertion to pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0384	Could not find required property {0} for SAML sender-vouches action!
Explanation	The pub.mediator.security.ws.AddSamlSenderVouchesToken ESB service is missing the required 'ConfigName' input value
Action	Make sure that the 'ConfigName' service input has a valid STS config name (must match one of the configured STS names)
0050.0386	Could not find any STS client configuration with name {0}. Check to see if such an STS configuration exists!
Explanation	This error occurs if the configured ESB service that calls the pub.mediator.security.ws.AddSamlSenderVouchesToken specifies the STS config name incorrectly.
Action	Check if the specified STS config name matches one of the configured STSs in Mediator. The "ConfigName" service input value should be the same name (case-sensitive) as the STS name specified in Mediator Admin configuration page
0050.0388	Could not get SAML assertion from STS!
Explanation	A null assertion element was found in the STS client.
Action	Mediator sent a request to the configured STS to obtain a SAML assertion, but no valid assertion was obtained by the client. Please check the log file for any errors related to sending the WS-Trust request to the STS to obtain the token.
0050.0389	Adding OnBehalfOf element in WS-Trust request for IS user {0}
Action	Info level message, no action required.
0050.0390	Could not find base STS policy file: {0} !
Explanation	An exception was encountered while attempting to load a WS-Policy artifact from the file indicated in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0391	Error occurred when getting STS configurations! Check to see if the ISTSClientConfigManager bean is configured!
Explanation	The STS configuration manager bean could not be found.
Action	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
0050.0392	Could not find any STS configuration with the name {0}
Explanation	The STS client configuration identified in the message to be loaded or deleted could not be found.
Action	Verify that the STS configuration being loaded or deleted has an equivalent configuration file present under [IS_INSTALL_DIR\packages\WmMediator\config\resources\security\sts] directory. E.g. if the configuration being deleted is called MySTS, then there should be a file with name MySTS.xml in the mentioned directory
0050.0394	Error occurred when getting key aliases for keystore {0}: Error: {1}
Explanation	An exception was encountered while attempting to add a list of certificate aliases to the pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0395	Error occurred when getting keystore handles {0}
Explanation	An exception was encountered while attempting to add a list of keystore handles to the pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0396	Error when signing SAML assertion and SOAP request body
Explanation	An exception was encountered while attempting to sign a SAML assertion and request body. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0397	Error occurred when adding ws-addressing headers to outbound soap request; Error: {0}
Explanation	An exception was encountered while attempting to add WS-Addressing headers. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0400	Using default timestamp value of 300s, because input TTL {0} is invalid (-ve or too big)
Explanation	The input value was not valid, a default was used.
Action	If the default is acceptable, no action is required. Otherwise update the configuration.
0050.0404	Response content type was empty! Falling back to original request content-type [{0}]
Explanation	The response message context contained an empty 'ContentType', so the type from the original request was used.
Action	This may be acceptable. If not, then configuration update will be required.
0050.0507	ScaDeploymentPayload.extractParts found no virtual service requests
Action	Info level message, no action required.
0050.0508	Unexpected exception, attempting to {0}, caught: type({1}), msg({2})
Explanation	An exception was encountered while attempting to process a deployment request. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0509	ScaDeploymentPayload.extractParts - Unable to find consumer file {0}, for component {1}
Explanation	The SCA deployment package was expected to contain a file to define the consumer identified in the message. The file was not found.
Action	This is a deployment payload construction problem.
0050.0510	Unexpected exception, attempting to process {0} request, caught: type({1}), msg({2})
Explanation	An exception was encountered while attempting to process a deployment request. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0515	ScaCompositeConfiguration found component with implementation type ({0})
Action	Info level message, no action required.

0050.0516	{0} - unable to convert string ({1}) to XMLGregorianCalendar: exception message ({2})
Explanation	The date element from the deployment payload has an unexpected format.
Action	This is problem with the contents of the deployment payload.
0050.0517	DeploymentPayload.{0} - input pipeline does not contain expected key ({1})
Explanation	The deployment payload must include an element with the key indicated in the message.
Action	This is problem with the contents of the deployment payload.
0050.0519	ScaDeploymentPayload - unable to delete temporary zip file: ({0})
Explanation	The file indicated in the message could not be deleted.
Action	Determine why the file could not be deleted and make it deletable.
0050.0520	DeploymentPayload - invalid request type: {0}
Explanation	The deployment payload type is unknown.
Action	This is a deployment payload construction problem.
0050.0528	DeploymentPayload - found null/empty virtual service descriptor for service {0}
Explanation	The deployment payload must contain a VSD. The VSD for the service identified in the message was not found.
Action	This is a deployment payload construction problem.
0050.0603	Error occurred when adding UsernameToken to SOAP Envelope: {0}
Explanation	An exception was encountered while attempting to add username token to the pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0605	Error occurred when adding X.509 token to SOAP Envelope: {0}
Explanation	An exception was encountered while attempting to add X509 token to the pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0101.0311	Error occured while validating certificate "{0}". Error is "{1}"
Explanation	An error occured while validating a certificate. This can be due to an invalid certificate or a non-existent certificate.
Action	Ensure that the certificate specified is valid and exists in filesystem.
0300.0129	Invalid proxy server alias specified "{0}". Ensure that proxy server alias "{0}" exists and is valid.
Explanation	Invalid proxy server alias is provided in the cloud connection.
Action	Ensure that proxy server alias exists and is valid.
0501.0005Error	Error while initializing the connector "{0}". Details: {1}
Explanation	An error occurred while trying to initialize the specified connection definition. The Details describe the exact cause of the error.
Action	For more information, see the Integration Server logs. Try to correct the error and reload the provider package.
0501.0009Error	I/O exception, while trying to load manifest for connector: {0}. Details: {1}
Explanation	An error occurred while reading the connector manifest file at the specified location. The error occurs if the manifest file is missing or corrupted, or the manifest file does not contain the required attribute definitions.
Action	Re-install the connector.
0501.0025Warning	Duplicate definition found for operation: {0} in connector definition for: {1}. Ignoring!
Explanation	The specified connector descriptor contains more than one operation definition against the specified name {0}. The duplicate definition will be ignored.
Action	Correct the connector descriptor and ensure that each operation name definition is unique.
0501.0026Warning	No definition found for operation: {0} in connector definition for: {1}. Ignoring!
Explanation	The WSDL contains an operation definition, but the connector definition does not include the corresponding operation definition and the operation is ignored.
Action	Consider including the operation definition, if required to be included, as part of the connector definition.

0501.0028Warning	No operations defined in the connector definition: {0}, while the WSDL model contains {1} operation(s).
Explanation	The connector descriptor does not include any valid operation definition, while the WSDL definition contains one or more operation definitions.
Action	Include one or more valid operation definitions in the connector descriptor.
0501.0030Warning	No abstract type defined in service: {0}. Ignoring complex type check for operation: {1}, connector: {2}
Explanation	One or more operations are marked as COMPLEX, but the connector descriptor does not define any 'abstractObject' definition. The operation will be treated as a SIMPLE operation.
Action	Consider either including an 'abstractObject' definition for the specified service or mark the operation type as SIMPLE.
0501.0031Warning	Exception while populating the abstract definition for operation: {0}. Details: {1}
Explanation	Unable to populate the abstract definition for the specified operation. The operation will be treated as SIMPLE operation.
Action	For more information, see the Integration Server log. Correct the error based on the information from the log or mark the operation type as SIMPLE.
0501.0052Error	Unable to {0} the document type package "{1}" for connector: {2}. Details: {3}
Explanation	The error occurred while performing the specified operation on the connector.
Action	For more information, see the Integration Server log.
0501.0080Error	Error loading the model for resource: {0}
Explanation	A parsing error occurred while loading the connector descriptor for the specified resource.
Action	For more information, see the Integration Server log.
0501.0082	Unable to load resource file {0}. Details: {1}
Explanation	Error occurred while loading the resource file or no schema definition file found at {0}. No schema validation would be performed.
Action	Ensure that the necessary XML Schema file {0} exists at the location

0501.0202Warning	At least one connection for the connector: {0} is enabled. Disable all the connections for this connector.
Explanation	You tried to disable a connector that contains one or more enabled connections.
Action	You must disable all the connections created for the connector, before disabling the connector.
0501.0218Warning	No provider registered with name: {0}
Explanation	No provider with the specified name is registered with webMethods CloudStreams.
Action	Check the provider name. Typically, the provider name is the same as the provider package name for the package that contains the connector definitions.
0501.0219Warning	No connector registered with name: {0}
Explanation	No connector descriptor is registered with webMethods CloudStreams for the specified identifier.
Action	Check the connector identifier. See the 'connector-Key' in the manifest.cpd file for the connector unique identifier.
0501.0224Warning	Unable to delete the connector: {0}, the connector is enabled.
Explanation	The connector cannot be deleted, because it is currently enabled.
Action	When you want to delete the connector, you must first disable the connector. You cannot recover a connector after deleting it and you lose all the connector-related artifacts.
0501.0227Error	Error initializing the provider registry and meta-data handler factory. Details: {0}
Explanation	Unable to initialize and load the provider registry.
Action	For more information, see the Integration Server log.
0501.0231Error	Error {0} provider: {1}. Details: {2}
Explanation	The error occurred when registering or unregistering the provider.
Action	For more information, see the Integration Server log.
0501.0262	Invalid mapping "{0}" found. Source type "{1}" and target type "{2}".
Explanation	The specified mapping defined in connector XML of a Provider is invalid.
Action	Correct the mapping and ensure source and target types are valid and source type supports the output to given target type. Refer to CloudStreams Server documentation for more details.

0502.0004Error	Error occurred while registering connection node: "{0}".
Explanation	If the connection is enabled as per the node definition, Integration Server tries to enable the connection during restart or package reload. During this process, no connection is established with the SaaS provider and an exception occurs.
Action	Check if the connection parameters are valid and if a connection can be established using those parameters. Also, in the connector configuration file, check if the mappings and operation names/document types are configured correctly for the connection type.
0502.0006Error	Error while unregistering connection alias: "{0}".
Explanation	This error may occur under different circumstances. The Integration Server log contains the details of the error that explain the root cause for the error.
Action	For more information, see the Integration Server error log.
0502.0007Error	Error while making a copy of connection alias: "{0}".
Explanation	If you make a copy of a connection node using Designer, the copy of the source connection node might not be available in the file system.
Action	Check if the node.ndf file of the source connection node is available for read and that it is valid.
0502.0017Error	Unable to create node "{0}" in the server namespace.
Explanation	This error may occur under different circumstances. The Integration Server log contains the details of the error that explain the root cause for the error.
Action	For more information, see the Integration Server error log.
0502.0047Error	Error occurred while destroying a connection instance of the alias: "{0}". Details: {1}
Explanation	The error occurs when disabling a connection and 1/ The SaaS provider is not accessible. 2/ The logout request can not be created successfully, because of incorrect mappings or document types specified in the connector configuration file.
Action	For more information, see the Integration Server logs.
0502.0056Error	Updating the connection alias {0} failed because the connection is enabled. Disable the connection and try updating again.
Explanation	The error occurs when you attempt to delete or update a connection alias when the connection is enabled.
Action	Disable the connection alias and try updating or deleting the connection again.

0502.0062Error	Error occurred while enabling the connection.
Explanation	This error may occur under different circumstances. The Integration Server log contains the details of the error that explain the root cause for the error.
Action	For more information, see the Integration Server error log.
0502.0224	Error occurred while initializing connection metadata builder for the given connection "{0}"
Explanation	An error occurred while loading connection metadata (connection attributes) associated with the specified connection.
Action	Ensure all the connection attributes are valid for the specified connection. Check Integration Server server log for more details.
0503.0101	Error while retrieving the service list from provider. Connection name "{0}". Details: {1}
Explanation	The CloudStreams server cannot load the connector model for the specified connection name.
Action	Ensure that the associated connector model is valid or exists, and that the model loads without an error.
0503.0106	Error creating CloudStreams connector service: "{0}". Details: {1}
Explanation	The inputs provided or configured when creating the connector service are incomplete, invalid, or not supported. The error also occurs when the CloudStreams server is trying to load an existing CloudStreams service node that is corrupted.
Action	Ensure that the service is configured properly. If you are using a custom connector, ensure that it is valid and that the service node is not corrupted.
0503.0108	Error occurred while registering the cloud connector service {0} with connector virtual service.
Explanation	A CloudStreams connector service is registered with a connector virtual service whenever the cloud connector service is created or updated. The registration is required for generating Analytics information.
Action	Ensure that the connector virtual service that the CloudStreams connector service refers to is valid and available.

0503.0109	Unable to invoke CloudStreams connector service "{0}". Details: {1}.
Explanation	Internal error while executing the cloud connector service.
Action	Contact Software AG Global Support.
0503.0112	Unable to invoke CloudStreams connector service "{0}" because the associated connection "{1}" is not found.
Explanation	The connection associated with the specified CloudStreams connector service or the connection alias passed at runtime does not exist.
Action	Ensure that the associated or specified connection exists and that the connection is enabled.
0503.0113	Unable to invoke CloudStreams connector service "{0}" because the associated connection "{1}" is disabled.
Explanation	The connection associated with the CloudStreams connector service or the connection alias passed at runtime exists, but is disabled.
Action	Ensure that the associated or specified connection exists and that the connection is enabled.
0503.0116	Unable to retrieve virtual service runtime instance while executing CloudStreams connector service "{0}"
Explanation	Internal error while executing the cloud connector service.
Action	Contact Software AG Global Support.
0503.0120	Error occurred while invoking CloudStreams connector service "{0}" using virtual service "{1}". Details: {2}
Explanation	Internal error while executing the cloud connector service.
Action	Contact Software AG Global Support.
0503.0121	Error occurred while registering CloudStreams connector service "{0}" with cloud virtual service "{1}".
Explanation	A CloudStreams connector service is registered with a connector virtual service whenever the connector service is created or updated. The registration is required for generating Analytics information.
Action	Ensure that the connector virtual service that the CloudStreams connector service refers to is valid and available.

0503.0122	Error occurred while unregistering CloudStreams connector service "{0}" with cloud virtual service "{1}".
Explanation	A CloudStreams connector service is un-registered with a connector virtual service whenever the connector service is deleted. This is required for generating Analytics information.
Action	Ensure that the connector virtual service that the CloudStreams connector service refers to is valid and available.
0503.0123	Error while retrieving the default virtual service name for "{0}" based connector service. Details: {1}
Explanation	The error occurred while retrieving the connector virtual services list because of an internal error.
Action	Ensure that WmCloudStreams package is loaded without any warnings. If the problem persists, contact Software AG Global Support.
0503.0124	Error retrieving business object list. Connection name "{0}". Details: {1}
Explanation	The error occurs because of one of the following reasons: 1/ The connection does not exist or is disabled. 2/ The session ID for the connection has expired. 3/ The backend is not available or it cannot be reached to retrieve the metadata from the backend SaaS provider.
Action	To resolve this error, ensure that: 1/ The connection exists and is enabled. 2/ The connection is enabled and has a valid session ID. You can turn on the session management connection option. 3/ Ensure that the backend is reachable and metadata is retrieved successfully from the backend SaaS provider.
0503.0125	Error retrieving business object description. Connection name "{0}". Details: {1}
Explanation	The error occurs because of one of the following reasons: 1/ The connection does not exist or is disabled. 2/ The session ID for the connection has expired. 3/ The backend is not available or cannot be reached to retrieve metadata from the backend SaaS provider.
Action	To resolve the error, ensure that: 1/ The connection exists and is enabled. 2/ The connection is enabled and has a valid session ID. You can turn on the session management connection option. 3/ The backend is reachable and metadata is retrieved successfully from the backend SaaS provider.
0503.0126	Invalid lookup service "{0}" specified.
Explanation	Lookup services are invoked during the cloud connector service definition. The lookup services should exist in the Integration Server namespace.
Action	Ensure that the lookup service specified in the error message exists in the Integration Server namespace and it is accessible.

0503.0127	Invalid service specification "{0}". The lookup service "{1}" must use the specification "{2}".
Explanation	Every lookup service must implement the specified service specification.
Action	Ensure that the specified lookup service implements the required service specification.
0503.0128	Unable to invoke CloudStreams connector service "{0}".
Explanation	Cloud connector services access the connection from a connection pool during service invocation. The error occurs when the CloudStreams framework cannot obtain a connection from a connection pool.
Action	Analyze the cloud service usage and ensure that the connection is properly configured. Also, the connection pool should have a free available connection whenever a CloudStreams connector service is invoked.
0503.0212	Invalid REST resource end point: "{0}"
Explanation	The REST resource end point is not resolved correctly. It may have entries in brackets({}) that should be resolved.
Action	Check if the required Parameters are passed during the cloud connector service execution. You can also set any default values on the "Parameter" tab in Designer.
0503.0213	Error in ServiceDispatcher, invalid input.
Explanation	One of the key inputs for service execution is missing, such as a connection that is enabled or a virtual service.
Action	Check if the connection exists and is enabled. In Designer, check if the virtual service is available. Also, check that the values you specified for the inputs are correct.
0503.0217	Unable to apply mapping on CloudStreams connector service "{0}", for operation "{1}". Details: "{2}"
Explanation	Error while reading or applying the mappings.
Action	Check the mappings available in the Cloud Provider Descriptor.
0503.0233	Could not execute the map service "{0}". Exception: {1}
Explanation	The map service associated with the mapping could not be executed.
Action	Check the server log for more details.

0601.0002	Error:{0}
Explanation	An exception occurred while parsing the fetched data from database
Action	Check whether CloudStreams 'JDBC Pool alias ' is configured properly

AuditLogger_Editor_Name – Logged Fields

Bundle-Name **CloudStreams Service Editors**

Bundle-Vendor **Software AG**

BusinessObjectPage_Available_Obj_Label – Available Business Objects

BusinessObjectPage_Description – Select the business object to be associated with the operation "{0}".

BusinessObjectPage_Filter_Text – type filter text

BusinessObjectPage_Title – Select the Business Object

BusinessObjectWizard_Title – Operation and Business Object Configuration

CLS.0010.0014E	PolicyGateway.shutdownMyService - Unable to remove service:{0}. Error:{1}
Explanation	A virtual service was not completely removed during Mediator package unload.
Action	No action is necessary if the error occurred during Integration Server server shutdown.

CLS.0010.0020W	Consumer file [{0}] could not be found! Could not load Consumer information into CloudStreams.
Explanation	Consumer definitions defined in the CloudStreams admin are persisted in an XML file in a directory under the WmCloudStreams package.
Action	No action is necessary if no consumers have been defined; otherwise, please contact support.

CLS.0010.0062E	Unable to get password for callback identifier: {0}
Explanation	Error while retrieving cleartext password from encrypted passman file store.
Action	Review Mediator STS configuration; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0010.0083W	Non-fatal CloudStreams package initialization error. {0}, {1}
Explanation	CloudStreams encountered an error during an upgrade processing step after the package initialization completed.
Action	Verify the overinstall upgrade steps were followed as defined in the documentation; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0010.0085E	CloudStreams - Unable to find ClusterStateCache
Explanation	CloudStreams defines a cache for this information even when the product is not clustered.
Action	Contact support.
CLS.0010.0190E	Error initializing CloudStreams keystore manager's keystore. Path:{0}, Cause: {1}
Action	Verify a valid keystore file exists for this path, and the file permissions allow for the Integration Server to read the file.
CLS.0010.0212E	Endpoint connection timeout duration expected as a number but was not a number ({0})
Explanation	A virtual service was deployed with an invalid connection timeout specified for its native provider endpoint.
Action	Review the advanced endpoint configuration in CentraSite and redeploy the service if necessary.
CLS.0010.0214E	Both keystore and key alias must be specified or none at all for SSL configuration; KeyStore alias = [{0}]; Key alias = [{0}]
Explanation	A virtual service with a native provider SSL endpoint was deployed with an invalid advanced endpoint configuration. The endpoint must have a valid alias for both the keystore file and the keystore entry aliases as defined in the Integration Server or it can have no aliases defined at all.
Action	Update the advanced endpoint configuration and redeploy the virtual service to Mediator.

CLS.0010.0217E	Error occurred when getting the password for handle {0} from passman!
Explanation	An attempt to retrieve a cleartext password from a passman encrypted file store failed.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0010.0218E	Error occurred when storing the password for handle {0} in passman!
Explanation	An attempt to save a password in a passman encrypted file store failed during Mediator STS configuration.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0010.0220E	Error converting given WS-Policy component to string
Explanation	Mediator was unable to parse policy elements used in producing request security tokens (RST) to a configured security token service (STS).
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0010.0702E	CloudStreams Upgrade, CloudStreams migration interrupted due to error. Details: {0}
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. It indicates the upgrade was not successful and further actions are required.
Action	Depending on the error message, one of the three options are available. 1) Resolve the issue causing the upgrade to fail, and restart the Integration Server again to see if the upgrade completes successfully. 2) Delete the mediatorUpgrade.xml file from installation path: \${IS_HOME}/packages/WmMediator/ directory. This is the file that causes Mediator to perform its upgrade step. If this action is taken, the Mediator configuration will have to be re-entered manually through the IS admin UI. 3) Contact support. Everytime the Integration Server is restarted, Mediator will attempt to perform an upgrade as long as its mediatorUpgrade.xml file is present in the package directory.

CLS.0010.0706E	CloudStreams Upgrade, unable to read required file. {0}
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. This message implies that the OS user running the Integration Server does not have adequate permissions to read the file referenced in the error message.
Action	Review user and file permissions and make necessary adjustments to ensure the file can be read.
CLS.0010.0707E	CloudStreams Upgrade, configuration file is missing a required entry element key attribute. {0}, File path: {1}
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file used to control a CloudStreams overinstall upgrade is corrupted. It is missing a reference to an attribute containing a path to an archive of the previous Mediator version prior to the overinstall.
Action	Contact support.
CLS.0010.0708E	CloudStreams Upgrade, configuration file entry element key attribute: {0}, expected this value: {1}, but found: {2}, File path: {3}
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file used to control a CloudStreams overinstall upgrade is corrupted.
Action	Contact support.
CLS.0010.0709E	CloudStreams Upgrade, unable to find the required file. Expected location: {0}
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. The backup file archive containing the CloudStreams package prior to the overinstall upgrade cannot be found.
Action	Contact support.
CLS.0010.0711E	CloudStreams Upgrade, unable to delete configuration file. CloudStreams upgrade task will continue to execute after each Integration Server startup until this file is removed. Path: {0}
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. Verify that the OS user account running the Integration Server has the necessary permissions to delete the file.
Action	If the log messages suggest the upgrade ran successfully, this file can be deleted; otherwise, contact support.

CLS.0010.0712E	CloudStreams Upgrade, configuration file is not valid xml. Unable to parse it. {0}, Details: {1}
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file is corrupted.
Action	Contact support.
CLS.0010.0717W	CloudStreams Upgrade, Could not find Default STS configuration file: {0} in archived zip file
Explanation	The default STS configuration file was not found when performing an overinstall upgrade.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the CloudStreams package's list of services in IS Admin's package management menu if available.
CLS.0010.0718E	CloudStreams Upgrade, configuration file has unexpected element key attribute, {0}, with value. {1}, and configuration file path: {2}
Explanation	This log message may occur when the CloudStreams package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file is corrupted.
Action	Contact support.
CLS.0010.0719E	CloudStreams Upgrade, Could not find Default STS configuration file: {0} following upgrade; Skipping migrating configuration data!
Explanation	CloudStreams was unable to locate the default STS configuration file during an overinstall upgrade.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in IS Admin's package management menu if available.
CLS.0010.0720W	CloudStreams Upgrade, Could not load Default STS client configuration; Skipping migrating configuration data
Explanation	The default STS configuration file was not found when performing an overinstall upgrade.
Action	This is an internal error. Contact Customer Care. Please produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in IS Admin's package management menu if available.

CLS.0050.0279D	Callback not removed for message id, "{0}". Receiver: {1}, Properties: {2}
Explanation	When a service is invoked, the state for the invocation is stored in a callbackStore map until the response is returned. The callback object was not found in the map for the given message id.
Action	No action is necessary unless memory runs low. In that event, please contact support.
CLS.0050.0280D	Message receiver not found for message id: "{0}", Properties: {1}
Explanation	Synapse callback receiver used to process the provider response is not found.
Action	Please contact support.
CLS.0050.0281D	Outbound message id not found. "{0}", Properties: {1}
Explanation	The message id used to correlate a native provider request was not found.
Action	Please contact support.
CLS.0050.0408E	Authentication failed for user {0}
Explanation	Invalid basic authentication credentials were included in the Authorization header sent to a virtual service that has a "Require HTTP Basic Authentication" runtime security policy.
Action	The web service consumer should include proper credentials and resend the service request.
CLS.0050.0608E	Error occurred when adding Timestamp to SOAP Envelope: {0}
Explanation	Mediator was unable to insert a WS security timestamp element to the request's security header sent to the native provider.
Action	Review the configured ESB "AddTimestamp" service call for virtual service and redeploy if incorrect. Otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0070.0010E	Incoming SOAP request does not contain the 'Authorization' header. This service requires the HTTP Basic Authentication token to be present!
Explanation	No Authorization header was sent to a virtual service that has a "Require HTTP Basic Authentication" runtime security policy.
Action	The web service consumer should include proper credentials and resend the service request.

CLS.0070.0032E	Unable to create Schema for this service "{0}" Schema validation may not succeed!
Explanation	Mediator was unable to initialize the schema parser for a virtual service with a "Validate Schema" runtime policy. This error occurs when a consumer sends Mediator a service request.
Action	Review the schemas defined in the virtual service, make corrections, and redeploy the virtual service if necessary; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0070.0071W	The ESB service name specified for InvokeESB mediator cannot be empty!
Explanation	A virtual service was deployed containing an ESB service invocation step containing an invalid or missing service name.
Action	Review all service invocations from the "Processing steps" configuration for the virtual service and redeploy if necessary.
CLS.0070.0072E	The 'service' attribute is required for the InvokeESB mediator definition
Explanation	The deployed virtual service configuration is corrupted.
Action	This is an internal error. Contact Customer Care. Please produce a diagnostic zip file by running the cloudstreams.util:diagnosticZip service from the WmCloudStreams package's list of services in IS Admin's package management menu if available.
CLS.0070.0073W	Did not invoke ESB service, because the service name was either empty or invalid (must be of the form folder1.folder2:service)
Explanation	A virtual service was deployed containing an ESB service invocation step with an invalid or missing service name.
Action	This warning is logged when a virtual service request is executed. See the action defined for CLS.0070.0071.
CLS.0070.0074E	Unknown mediator : {0}
Explanation	Synapse mediators are used in the in, out and error sequence steps defined for virtual services. These Mediators are predefined and registered in CloudStreams.
Action	Contact support.

CLS.0101.0099D	Unable to remove session context for connector service with this session token. "{0}"
Explanation	The CloudStreams transport listener should remove the session context for a connector service when it is no longer needed.
Action	Please contact support if available IS heap memory runs low.
CLS.0102.0056E	Package name and service name must be specified for deploying service(s)
Action	Verify the service has an associated package and redeploy; otherwise, please contact support.
CLS.0102.0057E	Unable to deploy! A virtual service with the name "{0}" already exists in the package "{1}"
Action	Confirm package association is correct and consider undeploying previous virtual service before deployment. Otherwise, please contact support.
CLS.0200.0045E	Error saving EhCache configuration file: {0}
Explanation	Mediator was unable to save its configuration file used for the Terracotta cache component.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0200.0046E	Could not find specified EhCache configuration file: {0}
Explanation	The Terracotta cache configuration file for Mediator's caches could not be found during package startup.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0201.0003E	PgMen incoming handler found no sie event for {0}, mep: {1}
Explanation	A service invoke event (sie) contains basic attributes of a service invocation. The sie should have been created by another Axis2 handler, but it was not or is no longer accessible from this handler.
Action	The service request will be permitted to execute, but the invocation may not be accurately tracked by the policy engine.

CLS.0201.0004E	Exception in Outgoing fault handler while creating sie. serviceName: {0} cause: {1}
Explanation	An error occurred while trying to create a service invoke event (sie) in a policy engine's Axis2 fault handler.
Action	The original service fault will be returned to the caller, but the service invocation may not be accurately tracked by the policy engine.
CLS.0201.0005E	Unable to create an sie event in outgoing fault handler. serviceName: {0}
Explanation	A service invoke event (sie) contains basic attributes of a service invocation. The sie should have been created by this or another Axis2 handler, but it was not or is no longer accessible.
Action	The original service fault will be returned to the caller, but the service invocation may not be accurately tracked by the policy engine.
CLS.0201.0006E	PgMen incomingHandler found an event with unexpected state {0}
Explanation	The policy engine relies on Axis2 handlers executing during specific phases in order to capture all the attributes of a service invocation. These attributes are stored in a service invoke event (sie) for each inbound or outbound phase.
Action	The sie data for this specific service invocation may be corrupted. The data contained in dependent policy engine events may be affected. Contact support.
CLS.0201.0007E	Exception in incomingHandler. msgId: {0} details {1}
Explanation	An error occurred while executing a policy engine Axis2 handler.
Action	A service fault will be returned to the caller, but the service invocation may not be accurately tracked by the policy engine.
CLS.0201.0008E	PgMen incoming handler had no service name in message context for this msgId {0}
Explanation	The inbound policy engine Axis2 handler did not find an Axis2 service registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
Action	Since the virtual service was not identified for this service request, the invocation will not be tracked by the policy engine.
CLS.0201.0011E	PgMen incoming handler could not find service operation in axis2 message context. Service name: {0}
Explanation	The inbound policy engine Axis2 handler did not find an Axis operation registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
Action	Since the virtual service operation was not identified for this service request, the invocation will not be tracked by the policy engine.

CLS.0201.0013E	PgMen outgoing handler found an event with unexpected state {0}, sie Dump: {1}
Explanation	The policy engine relies on Axis2 handlers executing during specific phases in order to capture all the attributes of a service invocation. These attributes are stored in a service invoke event (sie) for each inbound or outbound phase.
Action	The sie data for this specific service invocation may be corrupted. The data contained in dependent policy engine events may be affected. Contact support.
CLS.0201.0015E	Policy {0} forbids invocation of service {1} for scope {2}
Explanation	This service invocation was rejected because a policy rule was breached in the policy engine.
Action	No action is necessary.
CLS.0201.0016E	PgMen outgoing handler expected service {0} and invokeId: {1}, but cached event had {2} and {3}
Explanation	The invocation id for this execution thread's handler does not match the id that is stored on the current service invocation event (sie).
Action	This error suggests that data corruption may have occurred. Please contact support.
CLS.0201.0017E	PgMen outgoing handler had no service name in message context for this msgId {0}
Explanation	The inbound policy engine Axis2 handler did not find an Axis2 service registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
Action	Since the virtual service was not identified for this service request, the invocation will not be tracked by the policy engine.
CLS.0201.0018E	Axis service object not found in message context.
Explanation	The inbound policy engine Axis2 handler did not find an Axis2 service registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
Action	Since the virtual service was not identified for this service request, the invocation will not be tracked by the policy engine.
CLS.0201.0023W	No native service provider endpoint for {0}.
Explanation	The policy engine's Axis2 outbound handlers found no endpoint reference in message context.
Action	No further action is necessary if an endpoint was located at a later point during execution and the service was invoked.

CLS.0201.0024E	Exception caught while constructing the reason expression: {0}
Explanation	An error occurred while processing a virtual service's error sequence step.
Action	No further action is necessary. The soap fault will be returned without the fault's reason content.
CLS.0201.0034W	BaseHandler - No PolicyViolationDetector found, skipping analysis
Explanation	The spring component for detecting policy violations is missing.
Action	Verify the WmCloudStreams package loaded successfully; otherwise please contact support to verify the CloudStreams spring configuration is not corrupted.
CLS.0201.0040E	PgMen incoming event handler encountered an error executing PgMen outgoing FAULT handler. Cause: {0}
Explanation	An error occurred while processing one of the Axis2 fault handlers used by the policy engine during a service invocation.
Action	A service fault will be returned to the caller, but the service invocation may not be accurately tracked by the policy engine.
CLS.0201.0041E	PgMen outgoing handler could not find service operation in axis2 message context. Service name: {0}
Explanation	The outbound policy engine Axis2 handler did not find an Axis operation registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
Action	Since the virtual service operation was not identified for this service request, the invocation will not be tracked by the policy engine.
CLS.0201.0042E	PgMen outgoing FAULT handler could not find service operation in axis2 message context. Service name: {0}
Explanation	The outbound policy engine Axis2 fault handler did not find an Axis operation registered in the message context; however, the service request will be permitted to execute and the response will be returned to the caller.
Action	Since the virtual service operation was not identified for this service request, the invocation may not be accurately tracked by the policy engine.
CLS.0201.0043E	PgMen outgoing handler encountered error publishing an event. Missing sie event.
Explanation	A service invoke event (i.e. sie) contains basic attributes of a service invocation. The sie should have been created by another Axis2 handler, but it was not or is no longer accessible from this handler.
Action	The service request will be permitted to execute, but the invocation may not be accurately tracked by the policy engine.

CLS.0201.0044E **PgMen outgoing handler encountered error publishing an event. sie event is missing service name.**

Explanation A service invoke event (i.e. sie) contains basic attributes of a service invocation. The sie should have been created by another Axis2 handler, but it was not or is no longer accessible from this handler.

Action The service request will be permitted to execute, but the invocation may not be accurately tracked by the policy engine.

CLS.0201.0046E **No UUID generator bean (bean id={0}) configured, using java.util.UUID**

Explanation The spring configuration is missing an expected component for UUID generation.

Action CloudStreams is falling back to an alternate UUID factory; however, this error suggests the configuration may be corrupted. Verify the WmCloudStreams package loaded successfully; otherwise, please contact support to verify.

CLS.0202.0003E **Cannot create a PolicyEnforcer using a null/empty service name {0}**

Explanation A virtual service must be associated to a policy before it may be applied at runtime.

Action Verify the policy configuration filter is correct, the policy is active, and redeploy the affected virtual services.

CLS.0202.0004E **Cannot create a PolicyEnforcer using a null PolicyInfo reference**

Explanation The policy enforcer is a runtime object that requires a policy info configuration element.

Action This should not happen under normal circumstances. Please contact support.

CLS.0203.0062E **ControllingNodeLocker.run, thread id({0}), expected Ehcache, found ({1})**

Explanation Unexpected content was returned in the Terracotta cluster status cache.

Action This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

CLS.0203.0065E **ControllingNodeLocker.run, thread id({0}), caught ({1}/{2}) attempting to get a lock, thread dies**

Explanation Mediator encountered an error trying to obtain a lock on the controlling node in a Terracotta cluster.

Action This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

CLS.0203.0070I	ClusterStatusCache - cache manager for {0} returned null CacheCluster reference, not clustered?
Explanation	Mediator was unable to obtain a reference to the configured Terracotta cluster.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0203.0071I	{0} - getCluster(ClusterScheme.TERRACOTTA) threw exception {1}, using schema NONE
Explanation	An attempt to get Terracotta cluster configuration details failed.
Action	If Mediator is configured for a Terracotta cluster, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0203.0072E	ClusterStatusCache - thread id({0}) attempts to release {1} lock, but does not hold it
Explanation	An attempt to release the lock on the node controller in a Terracotta cluster failed.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0203.0073E	Error initializing JAXB Context: {0}
Explanation	Initialization for the cached global or registered consumers deployed to Mediator has failed.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0203.0075E	ControllingNodeLocker.run, thread id({0}), caught {1} attempting to ask about lock status, thread dies
Explanation	The thread defining the controlling node in a Mediator cluster encountered an error.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

CLS.0203.0076E	Unable to get cache named {0} from cache manager {1}
Explanation	Mediator encountered an error accessing one of the Terracotta caches.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0203.0081E	{0}, thread id({1}), caught {2}/{3} attempting to release lock, thread dies
Explanation	Mediator encountered an error releasing the lock on the controlling node in the Terracotta cluster.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0203.0082E	EhcacheClusterStatusCache, thread id({0}), caught {1}/{2} attempting to update controlling lock in cache
Explanation	Mediator encountered an error updating the controlling node in a Terracotta cluster.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
CLS.0203.0100W	Thread interrupted when trying to obtain {0} lock for cache {1}
Explanation	While Mediator was attempting to obtain a lock on a cache entry key, its thread was interrupted.
Action	No action may be necessary if Mediator is functioning normally.
CLS.0203.0101E	Unable to {0} lock the {1} cache for key {2} after waiting {3} mSecs
Explanation	Mediator failed to lock a cache key in the expected period of time.
Action	No action may be necessary if Mediator is functioning normally
CLS.0203.0103E	{0} task in thread {1} threw this: {2}
Explanation	An error occurred in the controlling node of a Terracotta cluster during Mediator shutdown.
Action	Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

CLS.0204.0008E	Unable to access spring bean config bean : {0}. Is there a problem with CloudStreams spring config file?
Explanation	The interval manager thread pool is missing from its spring configuration file.
Action	Contact support.
CLS.0204.0013W	No value defined in {0} cache for this key: {1}
Explanation	The policy engine's interval manager component creates and updates a global interval counter that is used for both clustered and non-clustered installations.
Action	It is normal for this warning to appear once or twice when the WmCloudStreams package is reloaded or during Integration Server startup. If this warning message continues to occur, verify the WmCloudStreams package loaded successfully; otherwise, please contact support.
CLS.0205.0062E	UddiPerformanceMetricsSender - unable to publish metrics over UDDI for service: {0}, message: {1}
Explanation	This log message is produced when Mediator is unable to publish performance metrics results to Mediator. When reviewing the content, please be aware that some exception details may have originated from the CentraSite product hosting the UDDI server. Errors can range from improper Mediator configuration, OS resource issues, network connectivity, or issues with the CentraSite installation.
Action	Depending on the errors logged in the Mediator UI, one of the following actions may prove more relevant. Verify CentraSite configuration information regarding UDDI is correct for the Mediator UI. Verify the hostname or IP address is reachable from the computer running the Mediator instance. Verify the CentraSite instance and its repository is up and accessible.
CLS.0205.0063E	Unable to initialize UddiClientAdapter due to a missing password for username: {0}.
Explanation	This log message is produced when Mediator is unable to publish performance metrics results to Mediator. A password was not found in the encrypted store for the user configured in the CentraSite panel of the Mediator UI.
Action	Verify the password is entered and the configuration was successfully saved for the CentraSite configuration screen in the Mediator UI.
CLS.0205.0064E	Error connecting to CentraSite UDDI registry running on {0}://{1}:{2}. Error: {3}
Explanation	This log message may be produced under the following situations: During Mediator package startup. CentraSite configuration entered in Mediator UI is saved, but a connection to the UDDI server fails for these settings. Mediator attempts to publish performance metrics but fails during its regularly scheduled interval.
Action	Verify the CentraSite configuration values in the Mediator UI are correct and CentraSite is up and running.

CLS.0205.0067E	Error disconnecting to CentraSite UDDI registry running on {0}://{1}:{2}. Error: {3}
Explanation	This log message may be produced during the following situations: During Mediator package shutdown. While Mediator is initializing communications with the CentraSite UDDI server after encountering an error during runtime or saving configuration values in the Mediator UI.
Action	Please see the Action for 0205.0064
CLS.0205.0602E	Missing "{0}" Jdbc destination pool from spring configuration
Explanation	One of the Mediator configuration files is corrupted and a necessary configuration element is missing.
Action	Contact support.
CLS.0205.0603E	Jdbc destination sender expected a JdbcEvent object but received: "{0}"
Explanation	The JDBC destination sender event component received an unexpected event type.
Action	Contact Support.
CLS.0205.0604E	Jdbc destination sender encountered a Sql Exception while generating "{0}" events. Error Code: {1} Cause: {2}
Explanation	The Mediator JDBC destination sender component encountered a SQL exception while sending a runtime event.
Action	Verify the CloudStreams functional alias in the Integration Server admin is configured for a JDBC pool. Verify the database is operational and restart the functional alias pool. Verify the MediatorEvents database component tables installed using the Common Database Component are still defined, and the Jdbc pool credentials and URL defined in Integration Server are correct. If all else fails, please contact Support.
CLS.0205.0605D	Jdbc destination sender took {0} msec to get a connection out of data source.
Explanation	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to get a Jdbc connection exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 50 milliseconds.
Action	No action is necessary.
CLS.0205.0606D	Jdbc destination sender took {0} msec to get a prepared statement out of connection with this SQL: {1}.
Explanation	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to get a Jdbc prepared statement exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 50 milliseconds.
Action	No action is necessary.

CLS.0205.0609D	Jdbc destination sender took {0} msec to close the prepared statement and connection.
Explanation	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to close a Jdbc connection exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 50 milliseconds.
Action	No action is necessary.
CLS.0205.0610E	Jdbc event requires at least one sql clause to be valid.
Explanation	The Mediator Jdbc component is in an invalid state.
Action	Contact Support.
CLS.0205.0611D	Jdbc destination sender took {0} msec to insert a batch of {1} "{2}" events. AutoCommit enabled on driver? {3}, Transaction Isolation level? {4}
Explanation	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to execute a batch of runtime event inserts into the database exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 500 milliseconds.
Action	No action is necessary unless the time is extremely large. In that case, consider reducing the 'pg.jdbc.batchSize' property in Mediator's pg-config.properties file. This will cause the Jdbc destination sender to send updates to the database server in smaller batches.
CLS.0205.0612E	Jdbc destination sender cannot use a read-only connection object to insert events.
Explanation	The functional alias used by Mediator's Jdbc destination sender is configured for a read-only transaction model in the Integration Server admin.
Action	Change the configured transaction model so it supports updates to the database.
CLS.0205.0614E	Jdbc event sql range should be between 0 and {0}, {1} is out of range.
Explanation	Mediator Jdbc component is in an invalid state.
Action	Contact Support.
CLS.0205.0615E	Jdbc performance metrics processor expected only one return key, but "{0}" were found.
Explanation	The Mediator Jdbc component is in an invalid state.
Action	Contact Support.

CLS.0205.0616E	Jdbc performance metrics processor expected two SQL statements, but "{0}" were found.
Explanation	The Mediator Jdbc component is in an invalid state.
Action	Contact Support.
CLS.0205.0617E	Jdbc performance metrics processor is missing returned primary key upon SQL insert
Explanation	Database did not return the 'event_pk' primary key column for the event inserted into the mediator_metrics_event table.
Action	Verify database is functioning properly; otherwise, contact Support.
CLS.0205.0618E	Jdbc event is in a bad state. Data type count "{0}" does not equal column value count "{1}"
Explanation	The Jdbc event destination component is in an invalid state.
Action	Contact Support.
CLS.0205.0619W	Jdbc driver doesn't support returned named SQL columns from Insert statement. Trying "Statement.RETURN_GENERATED_KEYS" mode.
Explanation	The Jdbc event destination component will attempt to use named columns for returning the database-generated primary key after inserting a row. If the database driver does not support this feature, this log message is raised, and the component will use another method to return the inserted primary key.
Action	No action required unless other SQLException errors are raised.
CLS.0206.0035W	MAC cache update {0} operation took {1} milliseconds to complete for {2} SIEs. This could cause lock attempts for tallying metrics statistics in MAC cache to fail.
Explanation	An update to the policy engine metrics data took longer than expected. When the duration of this task is longer than the configured lock request timeout, tasks can be lost when they fail to obtain exclusive locks.
Action	Review Integration Server performance and increase the advanced property for lock timeout pg.PgMenSharedCacheManager.lockTimeOut and restart IS. Otherwise, if this happens very frequently, contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

CLS.0207.0002E	DCPool spring configuration {0} missing a workQueue property? No workQueue was instantiated.
Explanation	The referenced policy engine thread pool is missing its in-memory work queue configuration.
Action	Possibly the *-pgmen.xml spring configuration file is corrupted. Contact support.
CLS.0207.0003E	Work queue capacity must be greater than 0. Value {0} is invalid.
Explanation	One of the advanced configuration properties in the *-config.properties file has an invalid queue size.
Action	These values are not exposed in the admin UI. Review the values in the pg-config.properties or wst-config.properties file and verify the policy engine work queue sizes are greater than 0.
CLS.0207.0009W	{0} thread pool shutdown - caught {1} while awaiting pool termination.
Explanation	A policy engine pool's thread was interrupted while waiting for graceful shutdown to complete.
Action	No action is needed.
CLS.0300.0001E	"{0}" is an unknown connection factory alias
Explanation	The classname specified in wst-core.xml spring bean configuration for the implementation map of the 'clientConnectionFactoryManager' bean is not in the classpath.
Action	Contact support.
CLS.0300.0002E	Class "{0}" for alias "{1}" does not implement the IConnectionManager interface.
Action	Contact support.
CLS.0300.0003E	"{0}" is an unknown connection pool alias
Action	Contact support.
CLS.0300.0004E	Unknown configuration group alias, "{0}"
Explanation	A CloudStreams connector descriptor has a configurable group in its connection configuration that is not valid for the connection manager.
Action	Contact support.

CLS.0300.0007E	Error creating connection alias "{0}".
Explanation	A CloudStreams connection manager had an error during its initialization phase.
Action	Contact support.
CLS.0300.0010E	Unknown field key "{0}" from connection factory alias "{1}"
Explanation	All managed connection configuration fields must have a unique key name including custom configuration fields. 'cn.providerURL' is an example.
Action	Review CloudStreams connector configuration to locate source of the unknown field name.
CLS.0300.0011E	Attempt to unregister an unregistered connection configuration instance, "{0}"
Action	Contact support.
CLS.0300.0012E	Attempt to reference an unregistered connection configuration instance, "{0}"
Action	Contact support.
CLS.0300.0013T	Duplicate field "{0}" exists in configurable group "{1}" of connection factory
Explanation	Each managed connection configuration field may only exist once for the select configurable groups.
Action	In normal cases, some common fields are shared across groups intended to be mutually exclusive (e.g. Amazon Web Service groups) when used with service configurations.
CLS.0300.0014E	Duplicate custom field "{0}" exists in configurable group "{1}" of connection factory
Explanation	Each managed connection configuration custom field must have a unique key name associated with it.
Action	Review all custom configuration fields created in CloudStreams and verify each name is unique.
CLS.0300.0016E	Unexpected connection configuration implementation type, {0}
Action	Contact support.
CLS.0300.0017W	Error {0}, while releasing resources for connection configuration "{0}"
Explanation	An error was encountered while releasing a managed connection pool instance during connection manager shutdown.
Action	No action is necessary.

CLS.0300.0019E	Invalid HTTP method selected, "{0}"
Explanation	An invalid HTTP method was referenced.
Action	Locate the source of the invalid method and change it to a valid HTTP method.
CLS.0300.0020E	Unknown service method implementation: {0}
Action	Contact support.
CLS.0300.0021E	Missing connection configuration alias is required.
Explanation	CloudStreams connector services must have a configured managed connection alias.
Action	Configure or recreate the connector service so it has a managed connection pool alias.
CLS.0300.0022E	Connection configuration alias "{0}" requires at least one configurable group.
Action	Review CloudStreams connectors and locate the connector that does not have at least one configurable group for all of its connections.
CLS.0300.0025E	Unknown service request implementation: {0}
Action	Contact support.
CLS.0300.0026E	Error getting property value for "{0}" from class {1}, Error: {2}
Explanation	CloudStreams was unable to access the value for one of its managed connection's configurable fields.
Action	Inspect the configuration value and verify it is valid for the specified field.
CLS.0300.0027E	Error setting property value "{0}" for "{1}" from class {2}, Error: {3}
Explanation	CloudStreams was unable to access the value for one of its managed connection's configurable fields.
Action	Inspect the configuration value and verify it is valid for the specified field.
CLS.0300.0028E	Error introspecting class {0}, Error: {1}
Action	Contact support.

CLS.0300.0029E	Custom config field "{0}" expected group alias "{1}" instead of "{2}"
Action	Contact support.
CLS.0300.0030E	Custom config field is missing required key property.
Explanation	All managed connection custom configuration fields must have a unique key name.
Action	Review CloudStreams connector configuration to locate source of the missing field key.
CLS.0300.0031E	Illegal attempt to binding or register a connection configuration "{0}". It is already registered.
Explanation	When a connection configuration (e.g. a managed connection pool) is enabled, its alias name must be unique.
Action	Change the connection configuration alias name so it will be unique.
CLS.0300.0032E	Attempt to create a connection configuration instance "{0}" with missing required groups. Required groups: {1}
Action	Review the affected CloudStreams connection configuration and ensure it includes the required configurable group.
CLS.0300.0033W	Error unloading connection manager alias "{0}" from factory. Details: {1}
Explanation	An error was encountered while releasing a managed connection pool instance during connection manager shutdown.
Action	No action is necessary.
CLS.0300.0034E	Connection factory manager overwrote key "{0}" for implementation. Old value: {1}, New value: {2}
Action	Contact support.
CLS.0300.0035E	Missing connection configuration instance for the alias "{0}"
Explanation	An error occurred while attempting to obtain a socket connection for an unknown connection configuration instance.
Action	Confirm a connection configuration exists and is enabled with this alias name.

CLS.0300.0036E	The config value "{0}" for field "{1}" is not supported.
Action	Contact support.
CLS.0300.0038E	Configuration value missing for required field "{0}" in connection configuration "{1}"
Action	Provide a value for the connection configuration's required field and re-enable.
CLS.0300.0039E	Configuration value for field "{0}" is not serializable. Value: {1}
Action	Contact support.
CLS.0300.0040E	Error creating native service provider endpoint, {0} with service context, {1} Error: {2}
Explanation	The native provider endpoint could not be defined as a valid URI.
Action	Review the configured value and ensure it is properly formatted as a URI.
CLS.0300.0041E	IO or timeout exception encountered for invoke "{0}" method for connection alias "{1}". Please check the network connectivity/proxy setting. Details: {2}
Explanation	A service invocation error occurred due to a network IO exception on the socket.
Action	Verify connection configuration is correct, endpoint is valid, service is up, connect and read timeouts are not too short, network connectivity and proxy setting etc.
CLS.0300.0042E	Unexpected exception encountered for invoke "{0}" method for connection alias "{1}". Details: {2}
Explanation	An unexpected service invocation error occurred that is not caused by an IO socket exception.
Action	Verify connection configuration is correct.
CLS.0300.0044E	Error while activating Authentication scheme, "{0}" for connection alias, "{1}". Details: {2}
Explanation	An error occurred activating an authentication scheme (e.g. OAuth, Basic Auth, etc.).
Action	Review configuration details if the authentication scheme has its own configuration; otherwise, please contact support.

CLS.0300.0045E	HTTP version "{0}" is not supported. Must be HTTP/0.9, HTTP/1.0 or HTTP/1.1
Action	Ensure the connection configuration specifies the correct HTTP version.
CLS.0300.0046E	Error in request headers configuration for "{0}" alias. Names: {1}, Values: {2}, Details: {3}
Explanation	Error validating request headers encountered while enabling a connection configuration.
Action	Verify the comma-delimited list of request headers and values are valid.
CLS.0300.0047E	Error in request headers configuration for "{0}" alias. Names: {1}, Values: {2}, Names and values are required.
Action	Verify the comma-delimited list of header names and values have non-whitespace characters for each entry.
CLS.0300.0051E	Error invoking connection from connection configuration instance "{0}". It is configured for an unknown web proxy alias "{1}"
Explanation	A connection configuration has a configuration field for an unknown IS proxy server.
Action	Confirm the proxy alias entered for the connection configuration exists in the Integration Server 'Proxy Server' configuration.
CLS.0300.0052W	Unable to register scheme for web proxy alias, "{0}", in connection configuration: "{1}"
Explanation	A connection configuration's web proxy alias could not be initialized when it was enabled, so the configuration is enabled with no proxy server support.
Action	Verify the Integration Server proxy server configuration identified by the alias is valid.
CLS.0300.0054E	Cannot create OAuthCredentials for OAuth version {0}
Action	Contact support.
CLS.0300.0055E	Cannot create SchemeFactory for OAuth version {0}
Action	Contact support.

CLS.0300.0056E	OAuthAliasHelperFactory cannot work with null token alias name
Explanation	A connection configuration instance requires a valid OAuth alias.
Action	Verify the oauth token configuration in the CloudStreams admin has a proper alias.
CLS.0300.0057E	OAuthAliasHelperFactory cannot find token alias name {0}
Explanation	A connection configuration instance references an unknown OAuth token alias.
Action	Verify the connection configuration references the correct alias as defined in the oauth token configuration in the CloudStreams admin.
CLS.0300.0058E	OAuthAliasHelperFactory cannot work with null OAuthAccessDetailsManager bean, not configured?
Action	Contact support.
CLS.0300.0059I	CloudStreams outbound connector "{0}" encountered an IO exception while reading native provider response. Consider setting the advanced connection configuration 'Retry on Response Failure' to true while 'Connection Retry Count ' is greater than 0 if it is safe to send requests more than once.
Explanation	The default settings for the default connector outbound connection factory will not attempt to resend a request if it believes it was received by the provider. If there is no harm to send a request more than once to a provider, enable the 'Retry on Response Failure' advanced property. (cn.retryIfRequestSentOk)
CLS.0300.0061E	Error instantiating object for hostname verifier: "{0}", Details: {1}
Explanation	This configuration field must be set to a fully qualified classname that implements the Apache HttpClient interface: org.apache.http.conn.ssl.X509HostnameVerifier. This field is used to perform validation checks between a native provider host and its server SSL certificate.
Action	Specify "org.apache.http.conn.ssl.AllowAllHostnameVerifier" to accept all hosts or "org.apache.http.conn.ssl.StrictHostnameVerifier" for strict enforcement. Leaving this field blank implies using the "AllowAllHostnameVerifier" option.
CLS.0300.0062E	Hostname verifier class, "{0}", must implement org.apache.http.conn.ssl.X509HostnameVerifier interface.
Action	Specify a valid fully qualified classname in the CloudStream package's java classpath that implements the interface or leave the field blank to disable hostname verification. See CLS.0300.0061 for more details.

CLS.0300.0063E	Error initializing registered provider's SSL context for the "{0}" algorithm. Details: {1}
Action	Contact support.
CLS.0300.0064E	Error reading a key store for this file: {0}, Details: {1}
Action	Verify the file path exists, the file is a valid keystore file, and IS has privileges to read the file.
CLS.0300.0065E	Error reading a trust store for this file: {0}, Details: {1}
Action	Verify the file path exists, is a valid trust store file, and the Integration Server has OS privileges to read the file; otherwise, please contact support.
CLS.0300.0066E	Error initializing entrust security provider's socket factory "{0}" algorithm. Details: {1}
Action	Unless this is a correctable error with one of the keystore files, please contact support.
CLS.0300.0069E	Unable to verify hostname. unknown SSL socket type: {0}
Explanation	Unable to perform hostname verification on a native provide endpoint.
Action	Contact support.
CLS.0300.0070E	Unknown HCAdapter event type: {0}
Explanation	An enabled connection configuration instance has received a notification event from an unknown origin. (These events are used to keep configuration instances in synch with related Integration Server configuration changes when possible.)
Action	Contact support.
CLS.0300.0072E	Error creating socket factory, "{0}". Details: {1}
Explanation	Unable to create the SSL socket factory for use with a connection configuration.
Action	Review the configuration and make corrections if possible; otherwise, please contact support.
CLS.0300.0073D	Error during onCleanup for socket factory for "{0}". Details: {1}
Explanation	Nonfatal error encountered while release resources associated with a connection configuration's SSL socket factory.
Action	No action should be necessary for this debug message.

CLS.0300.0075E	Unable to initialized key store for file: {0}, Details: {1}
Action	Ensure the file path exists, is a valid keystore file, and the Integration Server has OS privileges to read the file; otherwise, please contact support.
CLS.0300.0076E	Unable to create key store object from this file. {0}, exists? {1}, readable? {2}
Action	Ensure the file path exists, is a valid keystore file, and the Integration Server has OS privileges to read the file; otherwise, please contact support.
CLS.0300.0077E	Unable to access client's private key and certificate for this key alias: {0}, in this keystore file: {1}, Details: {2}
Action	Ensure the configuration alias used to access the client key is correct for the specified keystore; otherwise, please contact support.
CLS.0300.0081E	Unable to register or unregister connfactory event subscriber instance, {0}. Event type: {1} Details: {2}
Explanation	An error occurred while the connection factory registered its event listener used to receive notifications for some Integration Server configuration changes.
Action	Contact support.
CLS.0300.0082E	Error during onInit for socket factory, "{0}". Details: {1}
Explanation	Error during SSL socket factory initialization.
Action	Contact support.
CLS.0300.0083E	Error initializing security provider's socket factory. Key store alias: {0}, trust store alias: {1}, details: {2}
Explanation	Error during SSL socket factory initialization.
Action	Contact support.
CLS.0300.0093E	Error initializing connfactory cert chain verifier for trust store file: {0}, Details: {1}
Explanation	Error occurred while building the list of certificates that the connection configuration will trust.
Action	Contact support.

CLS.0300.0096E	Error attempted to verify trust for this cert: {0}, Cert will not be trusted. Details: {1}
Action	No action is necessary unless this certificate should have been trusted; otherwise, please contact support.
CLS.0300.0099E	Credentials configurable group failed to bind configuration field "{0}", with an illegal value "{1}".
Explanation	The "cr.authSchemeType" configuration field is limited to a closed set of possible values.
Action	It should not be possible to specify an unknown value through the CloudStreams connection admin UI, so please contact support.
CLS.0300.0100E	Protocol configurable group failed to bind configuration field "{0}", with an illegal value "{1}".
Explanation	The "pr.protocolVersion" configuration field is limited to a closed set of possible values.
Action	It should not be possible to specify an unknown value through the CloudStreams connection admin UI, so please contact support.
CLS.0300.0105E	Error creating buffered entity for request message. Details: {0}
Action	If problem persists, please contact support.
CLS.0300.0106E	Connection configuration instance "{0}" contains a custom key "{1}" with no prefix. Suggest "cx.{1}"
Explanation	All connection fields including custom fields must have a key name that may be used to identify the field. A dot-separated prefix must be prepended to the field name's key. 'cx.' is the suggested convention for custom fields.
Action	Change the specified key for the custom configuration field so it contains a valid prefix.
CLS.0300.0107E	AWSActivator called with wrong token instance. {0}
Explanation	The Amazon web service auth scheme requires auth tokens to produce the content necessary to invoke an AWS service.
Action	Please contact support.

CLS.0300.0108E	Missing auth token required field for Amazon Web Service authentication. {0}
Explanation	The Amazon web services require auth tokens to build a proper service request that can be authenticated.
Action	Review configuration and ensure all token fields are provided.
CLS.0300.0110E	AWS v2 signature auth scheme requires application/x-www-form-urlencoded content.
Explanation	Amazon web service signature version 2 cannot be used unless request message is using the required Content-Type.
Action	Correct service configuration to use the appropriate content type for the request.
CLS.0300.0111E	Unable to update native provider URI for AWS {0} signature auth scheme.
Explanation	The Amazon signature auth scheme appends additional security tokens as query parameters on the native provider endpoint.
Action	Please contact support.
CLS.0300.0112E	Unexpected request type received in AWS {0} auth scheme. {1}
Action	Please contact support.
CLS.0300.0114E	Unsupported algorithm. {0} AWS {1} signature scheme must be one of these. {2}
Explanation	The service must be configured to use one of the valid algorithms for signing the request.
Action	Review connection configuration.
CLS.0300.0115E	"{0}" header is missing from {1} AWS signature auth scheme.
Explanation	The AWS authentication scheme requires this header.
Action	Verify the service configuration is correct.
CLS.0300.0117D	Expected one value for AWS Param key: {0}, Found: {1}
Explanation	This AWS auth scheme parameter was expected to have only one value.
Action	Please contact support.

CLS.0300.0118T	Provider endpoint: {0}, AWS Canonical Request: {1}
Explanation	AWS signature calculations require requests to be in a specific format.
Action	Use this message to debug AWS signature authentication failures.
CLS.0300.0119T	Provider endpoint: {0}, AWS String to sign: {1}
Explanation	AWS signature calculations create a specific string to sign when generating signatures for the request.
Action	Use this message to debug AWS signature authentication failures.
CLS.0300.0120T	Provider endpoint: {0}, AWS Canonical Request: {1}
Explanation	AWS v2 signatures calculations require requests to be in a specific format.
Action	Use this message to debug AWS signature authentication failures.
CLS.0300.0122T	Added 'Host' header: {0}
Explanation	Amazon v4 signature requests require a "Host" header be sent with request.
Action	Use this message to debug AWS signature authentication failures.
CLS.0300.0123E	Unknown AWS auth scheme type.
Explanation	The AuthSchemeActivatorFactory received auth tokens for an unsupported signature scheme. type: {0}
Action	Please contact support.
CLS.0300.0124E	Unsupported AWS auth scheme type. {0}
Explanation	An auth scheme must be declared for the service, so it can be properly authenticated by the AWS server.
Action	Verify the connector configuration is correct.
CLS.0300.0125E	Unexpected error binding configuration authTokens to AWS configuration. Details: {1}
Explanation	Unable to enable a connection configuration with AWS configuration group because of an unexpected error.
Action	Please contact support.

CLS.0301.0001E	This IData request is missing NSRecord metadata. Namespace details may be impacted.
Explanation	NSRecord metada (document types) are used to marshal between IData and Axiom (XML) data models.
Action	Contact support.
CLS.0301.0002E	IdataBuilder error translating IData message into an Axiom element. Details: {0}
Explanation	An error occurred while translating a message from IData to the Axiom (XML) data model.
Action	Verify the IData content is valid.
CLS.0301.0003E	IDataBuilder missing required parameters. Either an input stream or an IData object is needed to process a message.
Explanation	The component that translates IData to Axiom (XML) data model is missing a required value.
Action	Review service that produced this error and verify a reference to either an input stream or IData content was provided.
CLS.0301.0005E	IDataMessageFormatter error translating Axiom element to IData for service: {0} and operation: {1}. Details: {2}
Explanation	An error occurred while translating a message from Axiom (XML) to the IData data model.
Action	Review service that produced this error and verify the message content is valid.
CLS.0301.0006E	IDataMessageFormatter error encoding IData message to stream for service: {0} and operation: {1}. Details: {2}
Explanation	An error occurred while serializing a message.
Action	Review service that produced this error and verify the message content is valid.
CLS.0301.0008E	IDataMessageFormatter unable to resolve provider targetAddress as a valid URL. {0}
Action	Verify the target address endpoint is a valid URL.

CLS.0301.0009E	CloudStreams message mappings for CloudStreams virtual service invocation "{0}" is invalid. Details: {1}
Explanation	A CloudStreams service has one or more message mapping steps which are invalid.
Action	Review the errors and correct the message mapping statements for this connector.
CLS.0301.0010D	CloudStreams mapping step, Error applying map step to message. Service invocation aborted? {0}. Source: {1}, Target: {2}, Details: {3}
Explanation	Debug message showing an exception that occurred while executing a mapping step.
Action	If the mapping step is not required, then no additional action is necessary.
CLS.0301.0011E	CloudStreams mapping step, Unknown map type "{0}".
Explanation	There are various categories of mapping steps. (e.g. HEADER, COOKIE, XPATH, IDATA, etc.).
Action	Review the connector configuration and fix the invalid mapping step.
CLS.0301.0012E	CloudStreams mapping step, Illegal attempt to set a value on a LITERAL mapping step named, "{0}"
Explanation	A mapping step cannot have a 'LITERAL' target. In other words, a LITERAL cannot have a value assigned to it; it can only be used as a source value in mapping expressions.
Action	Review the connector configuration and fix the invalid mapping step.
CLS.0301.0013E	CloudStreams mapping step, mapping step is missing "{0}" map value.
Explanation	The mapping step is not properly configured. It is missing required elements.
Action	Review the connector configuration and fix the invalid mapping step.
CLS.0301.0014E	CloudStreams mapping step, mapping step is missing "context" for map value. Must be IN or OUT.
Explanation	A mapping step has a specific context depending on where it is used during service invocations. The 'IN' context implies the expression executes before the service invocation. The 'OUT' context implies the expression executes after the service invocation.
Action	Review the connector configuration and fix the invalid mapping step.

CLS.0301.0016E	CloudStreams mapping step, XPath map value expression contains namespace prefix, but no namespaces were provided with map. {0}
Explanation	An XPATH mapping step must include a namespace prefix and URI declaration(s) if the XPath expression contains a colon-delimited prefix reference.
Action	Review the connector configuration and fix the invalid mapping step.
CLS.0301.0017E	CloudStreams mapping step, XPath map step unable to set value on node. "{0}" did not find any nodes in message.
Explanation	An XPATH mapping step executed but the expression returned no matching nodes from the Axiom (XML) message.
Action	Review the connector configuration and verify the expression is valid if matches were expected.
CLS.0301.0019E	CloudStreams mapping step, Error executing XPath map step to set value for this XPath: "{0}" and this value: {1}, Details: {2}
Explanation	An error occurred while executing an XPath expression meant to set a value on an Axiom (XML) message.
Action	Review the connector configuration and fix the invalid mapping step if this error was unexpected.
CLS.0301.0020E	CloudStreams mapping step, XPath map step unable to set value on node. "{0}" found {1} nodes in message.
Explanation	An XPATH mapping step's XPath expression against an Axiom (XML) message did not resolve to a single node.
Action	Review the connector configuration and fix the invalid mapping step if this error was unexpected.
CLS.0301.0021E	CloudStreams mapping step, Error executing XPath map step to get value for this XPath: "{0}", Details: {1}
Explanation	An error occurred while executing an XPath expression meant to get a value from a message.
Action	Review the connector configuration and fix the invalid mapping step if this error was unexpected.

CLS.0301.0023E	CloudStreams mapping step, Error executing validation for mappings. Details: {0}
Action	Review the connector configuration and fix the invalid mapping step(s).
CLS.0301.0025E	CloudStreams mapping step, XPath "{0}" expression returned unsupported XML element type, "{1}". Expressions must resolve to a single element or attributes only.
Explanation	CloudStreams XPATH mapping expressions may only reference text or attributes nodes in the XML message.
Action	Review the connector configuration and fix the invalid mapping step.
CLS.0301.0031E	No validator instance to validate CloudStreams message content using IS doc type validation.
Explanation	CloudStreams was unable to create a validator for a message against its associated doc type(s).
Action	Review the doctypes for the affected request or response message.
CLS.0301.0032E	Error while validating CloudStreams message content using IS doc type validation. Details: {0}
Explanation	An unexpected error occurred while validating a message against its associated doctype(s).
Action	Review the doctypes for the affected request or response message.
CLS.0301.0033E	Cloudstreams message is not valid based on expected doc type. Details: {0}
Explanation	A CloudStreams request or response message did not have the expected structure as defined by its associated doctype(s).
Action	Review the connector service configuration and state of the native provider to resolve the underlying error with the unexpected message structure.
CLS.0301.0034E	The configured translator service "{0}" is missing "static" method declaration for its "translate" method.
Explanation	A mapping statement may have an optional attribute that defines a fully qualified classname for a java class. This class must contain a public static method named 'translate'.
Action	Verify the connector configuration's mapping statement is correct and the class has the expected 'translate' public static method and is in the CloudStreams class loader.

CLS.0301.0035E	Error resolving configured translate service "{0}", Details: {1}
Action	Verify the connector configuration's mapping statement is correct and the class is in the CloudStreams class loader. See CLS.0301.0034 for additional details.
CLS.0301.0037E	Unknown builder type "{0}" for message data handler.
Explanation	No Axis2 message Builder implementation is registered for this builder type (key).
Action	Contact support.
CLS.0301.0038E	Unknown message formatter type "{0}" for message data handler.
Explanation	No Axis2 MessageFormatter implementation is registered for this message type (key).
Action	Contact support.
CLS.0301.0042E	No response code and method mapping found for connector "{0}" and response code "{1}" and httpMethod "{2}"
Explanation	The invoked connector service has returned an unexpected response code for the httpMethod used to execute the request. So it is considered to be a fault condition regardless of the provider response code.
Action	A fault message will be returned to the pipeline. If the virtual service is configured to return the native provider fault, then this provider response will be included.
CLS.0301.0045E	Unknown message handler phase. {0}
Explanation	CloudStreams message handlers have predefined inbound and outbound phases for both request and response message processing.
Action	Contact support.
CLS.0301.0046E	Unknown message builder content type, "{0}" for "{1}" message phase
Explanation	The message mapping in CloudStreams wst-transport.xml configuration file is incorrect.
Action	Contact support.
CLS.0301.0047E	Unknown message formatter content type, "{0}" for "{1}" message phase
Explanation	The message mapping in CloudStreams wst-transport.xml configuration file is incorrect.
Action	Contact support.

CLS.0301.0062E **Error instantiating builder class: {0} for content type: {1}. Details: {2}**
Explanation The message mapping in CloudStreams wst-transport.xml or Integration Server's axis2.xml configuration file is incorrect.
Action Contact support.

CLS.0301.0063E **Error instantiating message formatter class: {0} for content type: {1}. Details: {2}**
Explanation The message mapping in CloudStreams wst-transport.xml or Integration Server's axis2.xml configuration file is incorrect.
Action Contact support.

CSHeaderTreeTable_Active_Label – Active

CSHeaderTreeTable_Add_Header_Label – Add Header

CSHeaderTreeTable_Add_Label – Add

CSHeaderTreeTable_Add_Row_Label – Add Row

CSHeaderTreeTable_Default_Value_Label – Default Value

CSHeaderTreeTable_Delete_Header_Label – Delete Header

CSHeaderTreeTable_Delete_Row_Label – Delete Row

CSHeaderTreeTable_Headers_Label – Header(s)

CSHeaderTreeTable_Headers_Not_Available_Message – No headers are available to select because no operation is selected on the Operation tab.

CSHeaderTreeTable_Headers_Not_Available_Title – Headers Not Available

CSHeaderTreeTable_Headers_Not_Found_Message – No headers are available to select, either because the headers for this operation are mandatory and cannot be edited or all available headers have already been added.

CSHeaderTreeTable_Headers_Not_Found_Title – Headers Not Found

CSHeaderTreeTable_Insert_Row_Label – Insert Row

CloudServiceCreationPage_Error – Error

CloudServiceCreationPage_Page_Description – Specify the location and name for the new cloud connector service.

CloudServiceCreationPage_Page_Title – Create a New Cloud Connector Service

CloudServiceCreationPage_Warning – Warning

ConnectionAliasSelectionPage_Cloud_Pkg_Not_Installed – A cloud connector service cannot be created because the webMethods CloudStreams package, WmCloudStreams, is not installed.

ConnectionAliasSelectionPage_No_Connections_Error_Message – No connection pools have been created for the selected cloud application provider.

ConnectionAliasSelectionPage_Page_Description – Select the connection pool that the cloud connector service "{0}" will use to connect to the cloud provider.

ConnectionAliasSelectionPage_Page_Title – Select the Connection Pool

ConnectionAliasSelectionPage_Search_Message_Text – type connection name

ConnectionAliasSelectionPage_Text_Available_Connection_Pool – Available Connection Pools

ConnectionAliasSelectionPage_Text_Name – Name

ConnectorParameterTable_6 – Add Parameter

ConnectorParameterTable_8 – Delete Parameter

ConnectorParameterTable_Add_Parameter_Label – Add Parameter

ConnectorParameterTable_Data_Type_Label – Data Type

ConnectorParameterTable_Default_Value_Label – Default Value

ConnectorParameterTable_Delete_Parameter_Label – Delete Parameter

ConnectorParameterTable_Name_Label – Name

ConnectorParameterTable_Shift_Down – Shift Down

ConnectorParameterTable_Shift_Down_Label – Shift Down

ConnectorParameterTable_Shift_Up – Shift Up

ConnectorParameterTable_Shift_Up_Label – Shift Up

ConnectorParameterTable_Type_Label – Type

ConnectorServiceWizard_Wizard_Title – New Cloud Connector Service

ECLS.0300.0008 **Connection configuration alias "{0}" already registered. Original config was replaced with alias "{1}"**

Explanation Managed connection pool aliases must be unique across all CloudStreams connectors.

Action Locate the duplicate alias name and change its name to ensure no two pool configurations share the same alias.

HeaderPage_Page_Name – Headers**HeaderPage_Section_Input – Input****HeaderPage_Section_Output – Output****HeaderSelectionPage_Available_Headers_Label – Available Headers****HeaderSelectionPage_Description – Select Header****HeaderSelectionPage_Filter_Text_Message – type filter text****HeaderSelectionPage_Header_Label – Header****HeaderSelectionPage_Title – Header****HeaderSelectionWizard_Title – Select Header****IOEditor_Editor_Name – Input/Output****ISCloudConnectionNode_Node_Name – Cloud Connection**

OperationPage_Business_Object_Label – Business Object:

OperationPage_Con_Pool_Label – Connection Pool:

OperationPage_Name Operation

OperationPage_Operation_Change_Message – Are you sure you want to change the operation and the associated metadata? Click OK to confirm. Click Cancel to discard the changes.

OperationPage_Operation_Change_Title – Operation change confirmation

OperationPage_Provider_Type_Label – Connector Type:

OperationPage_Virtual_Svc_Label – Connector Virtual Service:

OperationPage_operation_Label – Operation:

ParameterPage_Form_Text_Parameters – Parameters

ParameterPage_Page_Name – Parameters

ParameterWizardPage_Available_Params – Available Fields

ParameterWizardPage_Description – Select the fields to use for the business object "{0}".

ParameterWizardPage_Field_Column – Field

ParameterWizardPage_Field_Label_Column – Field Label

ParameterWizardPage_Getting_Business_Details – Getting Field details...

ParameterWizardPage_Native_Column – Native

ParameterWizardPage_SOAP_TYPE_Column – SOAP Type

ParameterWizardPage_Title – Select Fields

ProviderSelectionPage_Cloud_Pkg_Not_Installed – A cloud connector service cannot be created because the webMethods CloudStreams package, WmCloudStreams, is not installed.

ProviderSelectionPage_Name – Name

ProviderSelectionPage_No_Providers_Error_Message – No CloudStreams connectors are installed.

ProviderSelectionPage_Page_Description – Select a CloudStreams Connector instance to use for the cloud connector service "{0}".

ProviderSelectionPage_Page_title – Select the Connector

ProviderSelectionPage_SearchLabel – Available Connectors

ProviderSelectionPage_Search_Message_Text – type connector name

ProviderSelectionPage_Type – Type

ProviderSelectionPage_Version – Version

RetrieveBusinessObjs_Operation_Cancelled – Business Objects retrieval operation was canceled.

RetrieveBusinessObjs_TaskName – Getting Business Objects...

ServiceSelectionPage_No_Services_Error_Message – No services exist for the selected cloud application provider.

ServiceSelectionPage_Page_Description – Select the service that will be used for the cloud connector service "{0}".

ServiceSelectionPage_Page_Title – Select the Service

ServiceSelectionPage_Search_Label – Available Services

ServiceSelectionPage_Search_Message_Text – type service name

ServiceSelectionPage_Text_Name – Name

SummaryPage_Business_Object – Business Object:

SummaryPage_ConnectionPool – Connection Pool:

SummaryPage_Name Name:

SummaryPage_Namespace – Namespace:

SummaryPage_Operation – Operation:

SummaryPage_Package_Name – Package:

SummaryPage_Page_Name – Summary

SummaryPage_Provider – Connector:

SummaryPage_Provider_Type – Connector Type:

SummaryPage_Service_Name – Service Name:

SummaryPage_Version_Number – Version Number:

TCLS.0300.0121 Added 'X-Amz-Date' header: {0}

Explanation Amazon v4 signature requests require a 'Date' or 'X-Amz-Date' header be sent with request.

Action Use this message to debug AWS signature authentication failures.

category.name ESB

content-type.name CloudService

service.editor.name – CloudStreams Service Multi-page Editor

wizard.name Cloud Connector Service

7 Command Central Messages

CCECCUI0143	No ports configured for the specified runtime.
Explanation	There are no ports configured for the specified runtime.
Action	Configure a port.
CCECCUI0288	No rows were selected. You are about to download all Log Sources.
Explanation	No rows were selected in the Log Sources table before clicking the Download Selected Files menu option.
Action	No action required.
CCECFRE0000	The content of the response is not acceptable according to the accept headers
Explanation	The response content cannot be converted into the requested media type that is specified in the HTTP Accept header. For example, the response is in text format and cannot be converted into XML or JSON format.
Action	Try to load the configuration again and specify a supported media type.
CCECFRE0001	The ConfigurationTypeId "{1}" does not exist for RuntimeComponentId "{0}".
Explanation	One or more configuration types specified do not match or are not valid for the specified properties.
Action	Provide valid configuration types for the specified properties. You can determine the valid configuration types using the following command: <code>cc list configuration types</code>

CCECFRE0002	The ConfigurationTypeId "{0}" does not exist for RuntimeComponentId "{1}".
Explanation	There is no registered ConfigurationType with the provided ID for the specified runtime component.
Action	Provide a valid ConfigurationTypeId for the specified runtime component. You can determine the IDs for configuration types using the following command: <code>cc list configuration types</code>
CCECFRE0005	LandscapeConfigurationUiBindingService is not available.
Explanation	The LandscapeConfigurationUiBindingService is not registered.
Action	Ensure that the bundle that contains this service is active.
CCECLTE0012	A resource was not specified.
Explanation	The REST call failed because a remote resource location was not specified in the REST service.
Action	Specify a valid resource in the REST service, for example, <code>spm/inventory/components</code> .
CCECLTE0013	A URL was not specified.
Explanation	The REST call to the remote host failed because the URL was not specified.
Action	Specify a valid URL, for example, <code>http://localhost:8092</code> .
CCECNFE0000	LandscapeDefinition service is not available.
Explanation	The LandscapeDefinition service is not registered.
Action	Ensure that the bundle that contains this service is active and the service is properly configured.
CCECNFE0001	Landscape inventory service not available.
Explanation	The landscape inventory service was not configured.
Action	Ensure that the bundle that contains this service is active.
CCECNFE0002	Configuration service factory not available.
Explanation	A configuration service factory is not configured.
Action	Ensure that the bundle that contains the configuration service factory is active and that the component definition is correct.

CCECNFE0003	The configuration service encountered a remote request failure.
Explanation	The remote request for a configuration item failed.
Action	Ensure that the node in the request is active.
CCECNFE0004	The remote request encountered a concurrency error.
Explanation	The system could not execute parallel remote requests.
Action	Contact Software AG Global Support.
CCECOME0000	Cannot perform an operation on nodes that are not accessible. The offline nodes are {0}.
Explanation	The specified nodes cannot be accessed because they are offline.
Action	Check the status of the specified nodes. Command Central can only access nodes that are online.
CCECOME0002	{0} on {1} ({2}) became unresponsive. Component restart may help to resolve this quickly.
Explanation	Specified components became unresponsive.
Action	Component restart may help to resolve this quickly.
CCECOME0003	{0} on {1} ({2}) crashed. You will need to start it again and investigate the cause of the failure.
Explanation	Specified components crashed.
Action	You will need to start it again and investigate the cause of the failure.
CCECOME0007	{0} of {1} on {2} ({3}) spiked into critical zone. The component may become overloaded!
Explanation	The specified component becomes overloaded.
Action	Try to release the load on the specified component.
CCECOME0015	Node {0} was not found.
Explanation	The specified node was not found.
Action	Check if the correct alias is used. If the node is not present in the landscape it can be added using the landscape service. If the node has been added but is still not accessible, contact Software AG Global Support.

CCECOME0016	Node {0} could not be created.
Explanation	A node with alias {0} could not be created because another node with alias {1} already exists.
Action	Provide a different alias for the new node.
CCECOME0017	Environment {0} could not be created.
Explanation	An environment with alias {0} could not be created because another environment with alias {1} already exists.
Action	Provide a different alias for the new environment.
CCECORE0001	Exceeded the maximum nodes allowed as per the configured license.
Explanation	You have exceeded the nodes allowed to you as per the license configured for Command Central.
Action	Contact Software AG support to upgrade the license.
CCECORE0002	Invalid License found. The system is going to shutdown in 30 minutes.
Explanation	The configured license is invalid. You need to configure a valid license immediately else the system will shutdown in 30 mintures.
Action	Configure a valid license immediately. If you do not have one, contact your system dministrator or Software AG support.
CCECORE0003	Invalid License found. The system is shutting down.
Explanation	The system is shutting down as the configured license is invalid.
Action	Contact your Administrator or Software AG support.
CCECORE0004	The license has expired.
Explanation	The configured license has expired.
Action	Contact your system administrator or Software AG support.
CCECORE0005	The license is not valid for the current operating system.
Explanation	The configured license is not valid for the current operating system.
Action	Contact your Administrator or Software AG support.

CCECORE0006	The number of nodes has exceeded as per the configured license.
Explanation	As per the configured license, you are not allowed to add more nodes as you have exhausted the licensed number of nodes.
Action	Contact your system administrator or Software AG support to get the license upgraded to add more nodes.
CCECORE0007	Failed to get the node count from the license.
Explanation	This issue may occur when your license file is corrupt.
Action	Contact your system administrator or Software AG support.
CCECORE0008	The configured license is not valid for this product.
Explanation	Either the license file is not for Command Central or it may have be a corrupt file.
Action	Contact your system administrator or Software AG support.
CCECORE0009	Failed to read the product code from the license.
Explanation	This issue may occur when your license file is corrupt.
Action	Contact your system administrator or Software AG support.
CCECORE0010	The configured license is not valid for this product version.
Explanation	This issue may occur when your license file is corrupt.
Action	Contact your system administrator or Software AG support.
CCECORE0011	Failed to read the product version from the license.
Explanation	Either the license file is not for current version of Command Central or teh license file may be corrupt.
Action	Contact your system administrator or Software AG support.
CCECORE0012	Node with alias {0} is not found.
Explanation	The specified node is not found in Command Central.
Action	Ensure that the node alias is spelled correctly. You can view a list of installations and their aliases using either the Command Central Web user interface, the cc list landscape nodes command, or the REST API.

CCECORE0013	The specified search query is not valid. The supported search attributes are: {0}
Explanation	One or more attributes are not supported for this type of search.
Action	Ensure that the search attributes are supported for the type of search you want to perform. Make sure that the attributes are spelled correctly. The supported search attributes are listed in the error message. Note that search attributes are case-sensitive.
CCECORE0014	Task "{0}" for node "{1}" failed.
Explanation	The specified task failed to execute for the specified node.
Action	Read through the details provided in the error message and the logs, then take corrective steps.
CCECORE0015	Tasks execution has failed.
Explanation	Some or all of the tasks failed to execute.
Action	Read through the details provided in the error message and the logs, then take corrective steps.
CCEIMPE0004	You cannot update the license location for the configuration type COMMON-LICLOC in Command Central.
Explanation	You cannot update the license location for the configuration type COMMON-LICLOC in Command Central.
Action	Use the default license location.
CCEIMPE0005	You cannot create a license location for the configuration type COMMON-LICLOC in Command Central.
Explanation	You cannot create a license location for the configuration type COMMON-LICLOC in Command Central.
Action	Use the default license location.
CCEIMPE0006	You cannot delete the license location for the configuration type COMMON-LICLOC in Command Central.
Explanation	You cannot delete the license location for the configuration type COMMON-LICLOC in Command Central.
Action	Use the default license location.

CCEIMPE0007	The product version is invalid.
Explanation	In Command Central, when the license is created or updated for Command Central Engine, if the product version in license validation does not match the version of the product installed, this error is thrown.
Action	Provide a new license file with the product version matching the installed product.
CCEIMPE0009	The product code is invalid.
Explanation	In Command Central, when the license is created or updated for the Command Central Engine, if the product code does not match the Command Central Engine product code, this error is thrown.
Action	Provide a new license file with the product code matching with the Command Central Engine product code.
CCEINRE0001	A node with the specified alias does not exist.
Explanation	An installation (node) with the specified alias name does not exist.
Action	Specify the valid alias name for an existing installation (node).
CCEINRE0002	The specified runtime component is not a process!
Explanation	The specified run-time component is not a PROCESS. Run-time components that are in the PROCESS category are components that function on their own. In contrast, run-time components that are in the ENGINE category cannot function on their own, but rather run within a PROCESS run-time component.
Action	Specify a PROCESS run-time component.
CCEJMRE0000	A job with ID {0} cannot be found.
Explanation	A job with the specified ID may have never existed or it may have completed long before this request.
Action	Use the following URI to list all jobs that are running or recently completed: <code>/cce/jobmanager/jobs</code>
CCEJMRE0001	A node with alias {0} does not exist.
Explanation	There is no node with the given alias in the landscape.
Action	Add the node to the landscape.

CCEJMRE0002	A job with ID {0} on node {1} cannot be found.
Explanation	A job with the specified ID may have never existed or it may have completed long before this request.
Action	Use the following URI to list all jobs that are running or recently completed: /cce/jobmanager/landscapejobs/local where "local" is the node alias
CCELCRE0000	The lifecycle operation to execute is unknown.
Explanation	You specified a lifecycle operation that is not valid. Valid lifecycle operations are start, stop, restart, pause, resume, start in debug mode, and start in safe mode. Note, however, that a run-time component might support only a subset of the valid lifecycle operations.
Action	Specify a valid lifecycle operation.
CCELIRE0000	Error deleting license report with id: {0}
Explanation	An unexpected error occurred when trying to delete the License Report with the given ID.
Action	Check the report id provided and if valid, check the server log for any exception messages.
CCELIRE0001	Error deleting license reports.
Explanation	At least one of the license reports was not deleted successfully.
Action	Retry the delete operation later or contact Software AG Global Support.
CCELIRE0003	Exception while building license report Document, {0}: caught type({1}), msg({2})
Explanation	A problem was encountered while attempting to build a License Report XML document from its string representation.
Action	Consult Software AG Global Support.
CCELIRW0002	Error deleting the following reports: {0}
Explanation	The specified reports could not be deleted successfully.
Action	Check the server log for more details and try to delete the reports individually.

CCELITE0000	Error generating license report id!
Explanation	An error occurred when trying to generate a unique report ID for the license report snapshot.
Action	Retry the operation or contact Software AG Global Support.
CCELITE0001	Could not find a report with id {0}
Explanation	No license report with the specified report ID was found in the system.
Action	Check the report ID value and try again.
CCELITE0002	Error creating license snapshots directory {0}
Explanation	An error occurred when trying to create a filesystem directory to store the license snapshots.
Action	Check if there is enough disk space and/or contact Software AG Global Support.
CCELITE0003	Unable to get runtime component {0}/{1} caught: {2}
Explanation	During license data collection, an attempt to retrieve information about this runtime component failed. The issue may indicate a communication issue between Command Central and Platform Manager.
Action	This could be a temporary communications issue. If the problem persists, contact Software AG Global Support.
CCELITE0004	Unable to get configuration types for {0}/{1} caught: {2}
Explanation	During license data collection, an attempt to retrieve information about this runtime component failed. The issue may indicate a communication issue between Command Central and Platform Manager.
Action	This could be a temporary communications issue. If the problem persists, contact Software AG Global Support.
CCELITE0005	Unable to get configuration instances for {0}/{1} caught: {2}
Explanation	During license data collection, an attempt to retrieve information about this runtime component failed. The issue may indicate a communication issue between Command Central and Platform Manager.
Action	This could be a temporary communications issue. If the problem persists, contact Software AG Global Support.

CCELITE0006	Unable to get configuration data for {0}/{1}/{2} caught: {3}
Explanation	During license data collection, an attempt to retrieve information about this runtime component failed. The issue may indicate a communication issue between Command Central and Platform Manager.
Action	This could be a temporary communications issue. If the problem persists, contact Software AG Global Support.
CCELITE0007	Found null value for license configuration data for {0}/{1}/{2}
Explanation	During license data collection, an attempt to retrieve license information about this runtime component found an invalid license.
Action	Contact Software AG Global Support.
CCELITE0008	Expected a String value for license configuration data for {0}/{1}/{2}, found type {3}
Explanation	During license data collection, an attempt to retrieve license information about this runtime component found an invalid license.
Action	Contact Software AG Global Support.
CCELITE0010	Checksum verification failed for License Report with id {0}
Explanation	The license report file may be corrupted or been tampered with, which has resulted in an integrity check failure.
Action	Regenerate the license report and/or contact Software AG Global Support with the affected license report file.
CCELITE0011	Unable to generate and store license snapshot report; caught type: {0}, msg: {1}
Explanation	An issue was encountered either when generating, or saving the generated license report snapshot.
Action	Check the exception and message to identify the exact cause, or contact Software AG Global Support.
CCELITE0012	Unable to generate report, no report generator configured
Explanation	The issue occurred because of incorrect component configuration.
Action	Check the license report configuration or contact Software AG Global Support.

CCELITE0013	Error getting license report!
Explanation	An error occurred when trying to retrieve the requested license report.
Action	Check the cause and retry the operation.
CCELITE0014	Unable to parse license XML for {0}/{1} from string that follows; except msg: {2}. XML: {3}
Explanation	The license content retrieved from the Platform Manager could not be parsed.
Action	Check the exception message for the exact cause and/or contact Software AG Global Support. The error may occur if a license file is found that is not in a standard Software AG format.
CCELITE0015	Error generating pdf report for this reportId "{0}". Cause: {1}
Explanation	The attempt to transform the XML data failed to produce a PDF data stream.
Action	Generate another report and verify whether the XML response is well-formed.
CCELITE0016	Error generating pdf license report. No XML data stream available for "{0}"
Explanation	The license reports module cannot produce a pdf report unless its canonical data is provided.
Action	Verify that the pdf generation task was executed properly using an existing report ID.
CCELITE0017	Error generating pdf license report. Unable to locate XSLT style sheet for pdf generation. "{0}"
Explanation	The license tools bundle could not locate the XSLT style used to produce a pdf report.
Action	Contact Software AG Global Support.
CCELITE0018	Error applying license pdf report stylesheet "{0}" to XML data "{1}". Cause: {2}
Explanation	Unexpected errors were encountered while generating the license pdf report.
Action	Contact Software AG Global Support.
CCELITE0019	Unable to serialize a license report data object for "{0}". Cause: {1}
Explanation	The license report data object could not be serialized as input for pdf report generation.
Action	Contact Software AG Global Support.

CCELITE0020	Error verifying license report checksum.
Explanation	An error occurred when trying to verify the license report checksum when retrieving the report.
Action	Retry request later or contact Software AG Global Support.
CCELITE0022	Unable to open extended rights table ({0})
Explanation	The indicated value is not available.
Action	Contact Software AG Global Support.
CCELITE0023	Unable to load extended rights properties from {0}; caught: type({1}). message({2})
Explanation	A problem was encountered while loading the indicated file into memory.
Action	Contact Software AG Global Support.
CCELITE0024	Unable to close input stream from {0}; caught: type({1}). message({2})
Explanation	A problem was encountered while cleaning up after loading the indicated file into memory.
Action	Contact Software AG Global Support.
CCELITW0021	Unable to translate extended rights code ({0}), not found
Explanation	The table used to look up license Extended Rights codes does not contain the indicated value.
Action	Contact Software AG Global Support.
CCELITW0025	LicenseReportFactory - unable to determine runtime status for component ({0}) on node ({1}); caught this: type({2}), msg({3})
Explanation	Command Central can not determine if the identified component is up or down.
Action	This behavior could occur when the Platform Manager node is down, or because of some other communication issue. If this problem persists when the Platform Manager node is up, contact Software AG Global support.
CCELNDE0000	The node alias is invalid.
Explanation	An installation (node) with the specified alias name does not exist.
Action	Specify the valid alias name for an existing installation (node).

CCELNDE0001	The node alias or the runtime component ID is invalid.
Explanation	No runtime components are found by the search criteria.
Action	Use a combination of existing runtime component ID and node alias.
CCELNDE0002	Invalid node alias or url.
Explanation	The specified alias name or URL for an installation (node) is not valid.
Action	Specify a valid alias name or URL.
CCELNDE0003	Specify a valid URL.
Explanation	The URL field in NodeInfo contains an invalid value.
Action	Check if the URL syntax of the node is valid.
CCELNDE0004	A node with a different alias for the same host:port already exist.
Explanation	An installation (node) with a different alias name already exists for the installation with the specified host name and port number.
Action	None.
CCELNDE0006	Node {0} could not be created.
Explanation	A node with alias {0} could not be created because another node with alias {1} already exists.
Action	Provide a different alias for the new node.
CCELNDI0005	You have exhausted the number of licensed nodes that can be configured. To add more nodes, contact your system administrator or Software AG support to get the license upgraded.
Explanation	You have exhausted the number of licensed nodes that can be configured.
Action	To add more nodes, contact your system administrator or Software AG support to get the license upgraded.
CCELSRE0001	The node alias cannot be updated.
Explanation	You cannot update the alias name for an installation (node).
Action	Create a new installation or update the existing installation without changing the alias name.

CCELSRE0002	The environment alias cannot be updated.
Explanation	You cannot change the alias name of an environment.
Action	Create a new environment or update the existing environment without changing the alias name.
CCELSRE0004	Node Aliases not specified!
Explanation	To add installations (nodes) to an environment, you must specify the alias names of the installations that you want to add.
Action	Try again, this time specifying the installation (node) alias names as query parameters.
CCELSRE0005	Alias not specified or invalid.
Explanation	The environment could not be created or updated because the alias is invalid.
Action	Specify a valid alias. You can view a list of installations and their aliases using the following command: <code>cc list landscape nodes</code>
CCELSRE0006	Node {0} could not be created.
Explanation	A node with alias {0} could not be created because another node with alias {1} already exists.
Action	Provide a different alias for the new node.
CCELSRE0007	Environment {0} could not be created.
Explanation	An environment with alias {0} could not be created because another environment with alias {1} already exists.
Action	Provide a different alias for the new environment.
CCELSRI0000	A node with the specified alias does not exist.
Explanation	No node alias matches {0}
Action	Provide a valid node alias.
CCELSRI0003	The environment with the provided alias doesn't exist.
Explanation	An environment with the specified alias name does not exist.
Action	Specify the valid alias name of an existing environment.

CCEMIGE0019	Extracting source version failed.
Explanation	Command Central failed to extract the source version from the bundles.info file.
Action	Ensure that the bundles.info file is at the correct location.
CCEMONE0001	{0} on {1} ({2}) became unresponsive. Component restart may help to resolve this quickly.
Explanation	{0} on {1} ({2}) became unresponsive.
Action	Component restart may help to resolve this quickly.
CCEMONE0002	{0} on {1} ({2}) crashed. You will need to start it again and investigate the cause of the failure.
Explanation	RuntimeStatus of {0} went from ONLINE to FAILED.
Action	Try to restart it. Have a look on {1} ({2}) for additional information on its status.
CCEMONE0006	{0} of {1} on {2} ({3}) spiked into critical zone. The component may become overloaded!
Explanation	The kpi {0} of {1} went from MARGINAL into CRITICAL status.
Action	Please have a look on {2} ({3}) to find out why this is happening.
CCEMONE0011	Node with alias {0} does not exist.
Explanation	There is no node with the specified alias registered with Command Central.
Action	Ensure that the node alias is spelled correctly and that it is registered with Command Central.
CCEMONE0012	No runtime monitoring information could be found for component {0}.
Explanation	The landscape nodes do not have monitoring information for the specified component.
Action	Check the landscape nodes for the for the specified component. Ensure that the specified component exists on the nodes and that it is spelled correctly.
CCEMONE0013	Component {0} does not exist on node {1}.
Explanation	The specified runtime component does not exist on the specified SPM node.
Action	Ensure that the specified component is spelled correctly and exists on the specified node.

CCEMONE0014	Removing alert with id {0} failed.
Explanation	The specified alert could not be found.
Action	Ensure that the alert with the specified ID exists in the Command Central landscape.
CCEPROE0000	No node with alias, {0}, exists in the environment.
Explanation	The node alias specified in the request does not exist.
Action	Resubmit the request with an existing node alias.
CCEPROE0001	No artifacts specified in uninstall request.
Explanation	The uninstall request did not specify any artifacts.
Action	Resubmit the request with a list of valid artifacts.
CCEPROE0002	{0} is an invalid/unsupported type for artifacts.
Explanation	Only Product and Fix are valid artifact types.
Action	Resubmit the request with valid artifacts.
CCEREMW0000	Error producing zipped log source contents. Node alias: {0}, RuntimeComponent: {1}, Log Source Aliases: {2} Details: {3}
Explanation	An error occurred while producing the zipped archive containing a collection of log source contents on the Command Central server.
Action	Try again. If the problem persists, contact Software AG Global Support.
CCEREMW0001	Error attempting to close a file store used to produce zipped collection of log source contents.
Explanation	An error occurred while closing the zip file system object containing a collection of log source file contents.
Action	No action required.
CCEREMW0002	Error attempting to delete a temporary file used to create a zipped collection of log source contents. Filename: {0}
Explanation	An attempt to delete the specified file has failed.
Action	Locate the file on the server hosting Command Central and delete the file if it still exists.

CCEREMW0004	Error producing zipped log source contents. Node alias: {0} Details: {1}
Explanation	An error occurred while producing the zipped archive containing a collection of log source contents on the Command Central server.
Action	Try again. If the problem persists, contact Software AG Global Support.
CCEREPE0000	No repository with id, {0}, exists on managed node, {1}
Explanation	The specified repository does not exist.
Action	Ensure the correct repository id is specified in the request, or add the desired repository to the managed node.
CCEREPE0001	No repository with id, {0}, exists on managed node, {1}
Explanation	The specified repository does not exist.
Action	Ensure the correct repository id is specified in the request, or add the desired repository to the managed node.
CCEREPE0002	No such node, {0}
Explanation	The node alias specified in the request does not exist.
Action	Specify the correct node alias, or add the relevant node to the environment.
CCEREPE0003	The specified image location does not exist.
Explanation	The specified location for an image repository was not found on the file system.
Action	Provide a valid location for the image repository.
CCEREPE0004	The specified repository does not exist.
Explanation	The specified repository was not found.
Action	Check the repository name and provide the name of an existing repository.
CCEREPE0005	Parameters cannot be empty or missing.
Explanation	All parameters are required.
Action	Specify values for all parameters.

CCEREPE0006	A repository with this name already exists.
Explanation	The name of the repository should be unique.
Action	Check the repository name and provide a unique name for the repository.
CCEREPE0007	A repository at the same location already exists.
Explanation	Two or more repositories cannot point to the same location.
Action	Provide a unique location for the new repository.
CCEREPE0008	The specified repository points to an image file but the repository type is not image.
Explanation	The specified repository cannot point to an image file, because the repository type is not image.
Action	Specify the correct repository type.
CCERPPE0000	The repository name is not specified.
Explanation	The requested operation requires a repository name.
Action	Check the input and provide a repository name.
CCERPPE0001	Repository with the specified name {0} already exists.
Explanation	The repository name must be unique.
Action	Check the repository name and provide a unique name for the repository.
CCERPPE0002	Repository with the specified name {0} does not exist.
Explanation	Editing the repository failed, because a repository with the specified name was not found.
Action	Check the repository name and provide the name of an existing repository.
CCESREE0000	Error occurred during retrieving user credentials
Explanation	This error might occur due to the following reasons: - Users attempt to get credentials when the credentials data store is empty; - While setting credentials, the communication with the remote SPM failed; - While deleting credentials, the communication with the remote SPM failed.
Action	Ensure that: - If you are attempting to get the credentials, the credentials data store is not empty. - If you are setting the credentials, the remote SPM is accessible. - If you are deleting the credentials, the remote SPM is accessible.

CCETEME0000	A job with ID {0} cannot be found.
Explanation	The job with the specified ID may have completed long before this request.
Action	Use the following URI to list all recently completed or running jobs: /cce/jobmanager/jobs
CCETEME0001	The remote request encountered a concurrency error.
Explanation	The system could not execute parallel remote requests.
Action	Contact Software AG Global Support.
CCETEME0002	A job with ID {0} did not completed successfully in {1} seconds.
Explanation	The job with the specified ID may require more time to complete.
Action	Use the following URI to list all recently completed or running jobs: /cce/jobmanager/jobs
CCETEME0003	Template metadata cannot be empty.
Explanation	The template metadata is required for creating a template.
Action	Ensure that you have provided metadata for the template. The metadata.Alias and nodeAlias fields are required.
CCETEME0004	Template alias cannot be empty.
Explanation	The template alias is a required attribute of the template metadata.
Action	Specify a value for the template alias attribute.
CCETEME0005	Template nodeAlias cannot be empty.
Explanation	The template nodeAlias is a required attribute of the template metadata.
Action	Specify a value for the nodeAlias attribute.
CCETEME0006	Template options cannot be empty.
Explanation	The template options attribute is required in the template metadata.
Action	Specify at least one option and retry.
CCETEME0007	Error occurred during template creation {0}
Explanation	Creating the template failed with an error.
Action	Check the error logs for more details.

CCETEME0008	Error occurred during template creation on the remote managed node with alias : {0}. Remote task status is {1}
Explanation	Creating a template on the remote managed node with the specified ID failed with an error.
Action	Check the job status.
CCETEME0009	A template with alias: {0} already exists.
Explanation	Another template with the same alias already exists.
Action	To overwrite the existing template, add the OVERWRITE_TEMPLATE option in the template metadata. To create a new template and keep the existing template, change the template alias.
CCETEME0010	Node with alias : {0} does not exist.
Explanation	A managed installation (node) with the specified alias name does not exist.
Action	Specify a valid alias name for an existing installation (node).
CCETEME0011	A problem occurred while downloading template with alias {0} on Command Central.
Explanation	Command Central could not create a folder for the template on the file system.
Action	Contact the Command Central Administrator.
CCETEME0012	A template with alias {0} could not be found.
Explanation	Command Central could not find a template with the specified alias.
Action	Check if the specified alias for the template you want to delete is correct.
CCETEME0013	Error occurred while creating a template on the remote managed node with alias: {0}. Remote task status is {1}
Explanation	Creating the template fails with a "Nothing to download on Command Central" error.
Action	See the error logs for the error details.
CCETEME0014	Template with alias {0} was not found.
Explanation	Command Central could not find a template with the specified alias.
Action	Verify that the alias is spelt correctly and that a template with this alias is already created. If the template is not created, execute a create template operation.

CCETEME0015	Template already exists.
Explanation	A template with the specified alias already exists.
Action	Change the alias of the imported template or delete the existing template with the same alias.
CCETEME0016	A problem occurred while importing the template.
Explanation	Command Central could not create a folder for the template on the file system.
Action	Contact the Command Central Administrator.
CCETEME0017	Could not import template because a required file was not found.
Explanation	Command Central could not find or access the file from which to import the template.
Action	Contact the Command Central Administrator.
CCETEME0018	Template data is invalid.
Explanation	The provided template data could not be deserialised.
Action	Check if the provided template data is corrupted.
CCETEME0019	Template options cannot be empty.
Explanation	The template options attribute is required in the template metadata.
Action	Specify at least one option and retry.
CCETMRE0000	Specify template alias, options, and target node.
Explanation	Template alias, target node alias, and options are required parameters for this template.
Action	Specify values for all required parameters.
CCETMRE0001	{0} option is specified but a repository for the option is not specified.
Explanation	A repository for the option is not specified.
Action	Specify a repository for the option. For example, if the option is PRODUCTS, specify a product repository.
CCETMRE0002	The specified repository is not applicable for this option {0}
Explanation	The specified repository is not applicable for the specified option.
Action	Specify a proper repository. For example, if the option is PRODUCTS, specify a product repository.

CCETMRE0003	There is no repository that supports the specified option {0}.
Explanation	The specified option is not supported by the specified repositories. For example, the error occurs if the FIXES option is specified, but the repository for this option does not support fixes.
Action	Specify a proper repository. For example, if the specified option is FIXES, specify a repository that contains fixes.
CCEWCME0009	Display name cannot be empty.
Explanation	Display name is required.
Action	Provide the display name.
CCEWCME0010	Alias {0} cannot be empty.
Explanation	Environment alias and node alias cannot be empty.
Action	Provide a valid alias name.
CCEWCME0011	{0} cannot exceed {1} characters.
Explanation	The specified field input is incorrect.
Action	Check the error message and provide the correct input to the specified field.
CCEWCME0012	Environment name or alias cannot be {0}.
Explanation	Incorrect environment name/alias provided.
Action	Check the error message and provide the correct input.
CCEWCME0013	{0} alias cannot contain {1} non-ASCII characters.
Explanation	Environment alias cannot contain non-ASCII characters.
Action	Make sure the value of the alias field is correct.
CCEWCME0014	Alias {0} cannot contain spaces.
Explanation	Environment alias cannot contain spaces.
Action	Make sure the value of the alias field is correct.

CCEWCME0015	{0} already exists.
Explanation	The specified node/environment already exists.
Action	Specify a correct node/environment.
CCEWCME0017	Installation name cannot be empty. It must be less than 100 characters.
Explanation	Node name cannot be empty or contain more than 100 characters.
Action	Enter a valid node name.
CCEWCME0018	Alias cannot be empty. It should not have spaces. Only ASCII characters, numbers, -, _ and . are allowed.
Explanation	Node alias cannot be empty.
Action	Enter a valid node alias.
CCEWCME0019	Host name cannot be empty. The host name should be between two and 253 characters characters long. Do not use any special characters, except period(.) and minus(-). Do not start or end the host name with a period(.) or minus(-).
Explanation	The host name field cannot be empty.
Action	Provide a valid host name. The host name should be between two and 253 characters characters long. Do not use any special characters, except period(.) and minus(-). Do not start or end the host name with a period(.) or minus(-).
CCEWCME0020	Port number cannot be empty. It must be a positive number.
Explanation	Port number cannot be empty.
Action	Enter a valid port number.
CCEWCME0028	Installation alias {0} already exists. Please provide a different alias for the installation.
Explanation	Installation node already exists.
Action	Provide a different alias for the installation node you want to add.
CCEWCME0039	Null returned while retrieving the configuration types for comparison.
Explanation	This intermittent error occurs while retrieving the configuration types from Platform Manager.
Action	Retry configuration comparison.

- CCEWCME0047** **Specify a name for the template. No spaces allowed. Use only ASCII characters, numbers, "-", "_", and ".".**
- Explanation** The alias field for the template cannot be empty.
- Action** Provide a valid template alias. No spaces allowed. Use only ASCII characters, numbers, "-", "_", and ".".
-
- CCEWCME0048** **Encryption password cannot be empty.**
- Explanation** The template encryption password cannot be empty.
- Action** Provide a valid password.
-
- CCEWCME0049** **The passwords you entered do not match.**
- Explanation** The encryption passwords that you entered do not match.
- Action** Retype the encryption passwords.
-
- CCEWCME0050** **Select at least one include option.**
- Explanation** You cannot clear all include option check boxes.
- Action** You must select at least one include option check box.
-
- CCEWCME0051** **No license reports were selected for deletion.**
- Explanation** At least one report must be selected in the view before clicking the delete button.
- Action** Select one or more reports and click the delete button.
-
- CCEWCME0052** **A request to create a license report is currently executing.**
- Explanation** Only one report may be created at a time while in the license report view.
- Action** Wait for the report to complete or click the refresh button to try again.
-
- CCEWCME0053** **No repositories configured. Add at least one repository.**
-
- CCEWCME0069** **Specify a name for the repository. No spaces allowed. Use only ASCII characters, numbers, "-", "_", and ".".**
- Explanation** The alias field for the repository cannot be empty.
- Action** Provide a valid repository alias. No spaces allowed. Use only ASCII characters, numbers, "-", "_", and ".".

CCEWCME0072	Repository {0} creation failed.
Explanation	Creating the repository failed.
Action	Check the server logs or contact your system administrator.
CCEWCME0073	Repository {0} update failed.
Explanation	Updating the specified repository failed.
Action	Check the server logs or contact your system administrator.
CCEWCME0074	Version cannot be empty.
Explanation	The Version field is a required field.
Action	Click the Advanced button and specify a valid server in the Enter server URL field. Leave this field empty to use the Software AG Download Center.
CCEWCME0075	Image file path cannot be empty.
Explanation	The Image file on server field is a required field.
Action	In the Image file on server field, provide a valid path to an image file on the Command Central server.
CCEWCME0076	An image file should be selected.
Explanation	Specifying an image file is required.
Action	In the Upload image file field, select an image file.
CCEWCME0077	A repository with location {0} was not found in the Software AG Download Center.
Explanation	The repository that you are trying to update was not found in the Software AG Download Center.
Action	Contact your system administrator.
CCEWCME0099	Applying template {0} on installation {1} failed.
Explanation	The apply template operation on the target installation has failed.
Action	Check the logs and jobs on the target installation.

CCEWCME0103	Error while creating a new license report. {0}
Explanation	An error occurred while invoking the service action responsible for creating a new report.
Action	Check the Command Central server logs to determine the root cause for the error.
CCEWCME0104	Error while deleting license report(s). {0}
Explanation	An error occurred while invoking the service action responsible for deleting reports.
Action	Check the Command Central server logs to determine the root cause for the error.
CCEWCME0105	Error while refreshing the license reports view. {0}
Explanation	An error occurred while invoking the service action responsible for retrieving the reports from the Command Central server.
Action	Check the Command Central server logs to determine the root cause for the error.
CCEWCME0114	Saving of template {0} from installation {1} failed.
Explanation	The save template operation on the target installation has failed.
Action	Check the logs and jobs on the target installation.
CCEWCMI0021	Installation {0} already exists in environment {1}.
Explanation	The selected node already exists in the environment. Drag and drop not possible.
Action	Verify if you have selected the correct nodes and the environment for drag and drop.
CCEWCMI0040	{0} must be a non-negative integer.
Explanation	Specified field must be a non-negative integer.
Action	Enter a valid field value.
CCEWCMI0041	{0} cannot be empty.
Explanation	Specified field cannot be empty.
Action	Enter a valid field value.
CCEWCMI0046	Alias cannot be empty.
Explanation	The port alias field cannot be empty.
Action	Provide a valid port alias name.

CCEWCMI0057	User credentials saved successfully.
Explanation	The provided user credentials are successfully saved.
Action	None.
CCEWCMI0058	User credentials deleted successfully.
Explanation	The provided user credentials are successfully deleted.
Action	None.
CCEWCMI0098	Template {0} successfully saved from installation {1}.
Explanation	The save template operation completed successfully.
Action	No action required.
CCEWCMI0100	Type a keyword to display only the reports that contain the keyword in the report id, creator, create date or compliance status. The search is case-insensitive.
Explanation	License report search filter help text.
Action	None.
CCEWCMI0101	Do you wish to continue?
Explanation	Part of the license report confirmation dialog for creating a new report.
Action	None.
CCEWCMI0110	It may take a few moments to generate the report.
Explanation	Part of the license report confirmation dialog for creating a new report.
Action	None.
CCEWCMI0111	delete
Explanation	Part of 'delete license report(s)' confirmation dialog.
Action	None.
CCEWCMI0112	license report(s)
Explanation	Part of 'delete license report(s)' confirmation dialog.
Action	None.

CCEWCMI0113	Report Id(s): {0}
Explanation	License report confirmation dialog for deleting one or more reports.
Action	None.
CCEWCMI0115	Template {0} successfully applied on installation {1}.
Explanation	The apply template operation completed successfully.
Action	No action required.
CCEWCMI0117	Scheduled job did not complete within status checker's allotted time.
Explanation	The client job status checker stopped polling for an executing job's status before it completed. This does not necessarily mean the job did not complete successfully.
Action	Confirm if job completed via other means.
CCEWCMW0107	No license report selected for delete.
Explanation	You must select a license report ID for deletion.
Action	Select at least one report ID from the report list.
CCEWCMW0108	License report delete request failed, but no ErrorInfo was found.
Explanation	A problem occurred when executing a delete request, but the server did not provide details about the problem.
Action	Check the server-side log files for details. Contact Software AG Global Support.
CCEWCMW0109	Request to delete license reports failed for these report IDs: {0}
Explanation	The server was not able to delete the license reports identified here. The request may have included other report IDs for which deletion was successful.
Action	Refresh the display of license reports to see which were deleted. Check the server-side error log for details about why the attempt to delete failed.
CCEWCMW0118	Unable to determine job status due to unexpected error while checking status. {0}
Explanation	Job status checking encountered an error. This does not necessarily mean the job did not complete successfully.
Action	Confirm if job completed via other means.

8

Common Monitoring Provider Messages

CMPAPIE0000	{0}: The input parameter {1} is null or empty.
Explanation	A required input parameter is null or empty.
Action	Please provide the required input parameter.
CMPAPIE0001	{0}: The input parameter {1} is null.
Explanation	A required input parameter is null.
Action	Please provide the required input parameter.
CMPAPIE0003	{0}: Cannot load XSD file {1}
Explanation	A required input parameter is null.
Action	Please provide the required input parameter.
CMPBKRE0000	Error initializing Broker Attribute Values. Broker Monitoring Context cannot be null.
Explanation	Broker Monitoring Context is required for initializing Broker Attribute Values.
Action	Verify Broker Connection parameters.
CMPBKRE0001	Error while retrieving attribute value. MetaModel Type Name cannot be null or empty.
Explanation	MetaModel Type Name is required for retrieving attribute value.
Action	Verify metadata model type name is provided.

CMPBKRE0002	Error while retrieving attribute value. MetaModel instance name cannot be null or empty.
Explanation	MetaModel instance name is required to retrieve attribute value.
Action	Verify metadata model instance name is provided.
CMPBKRE0003	Error while retrieving attribute value. Attribute ID cannot be null or empty.
Explanation	Attribute ID is required to retrieve attribute value.
Action	Verify Attribute ID is provided.
CMPBKRE0004	Error while retrieving attribute values. Attribute query object cannot be null.
Explanation	Attribute query object is required to retrieve attribute values.
Action	Verify attribute query object is provided.
CMPBKRE0005	Error while retrieving attribute value due to invalid model type.
Explanation	An invalid model type was provided while retrieving attribute values.
Action	Verify a valid model type is provided.
CMPBKRE0006	Error while destroying Monitoring Context. Monitoring Context cannot be null.
Explanation	Error while destroying Monitoring Context. Monitoring Context cannot be null.
Action	Verify Monitoring Context is provided
CMPBKRE0007	Error while destroying Monitoring Context. Invalid Broker Monitoring Context provided.
Explanation	Error while destroying Monitoring Context. Invalid Broker Monitoring Context provided.
Action	Verify valid Broker Monitoring Context is provided.
CMPBKRE0008	Error while getting meta model. Model type name cannot be null.
Explanation	Error while getting meta model. Model type name cannot be null.
Action	Verify Model type name is provided.

CMPBKRE0009	Error while validating Broker Monitoring Context. Broker Monitoring Context cannot be null.
Explanation	Error while validating Broker Monitoring Context. Broker Monitoring Context cannot be null.
Action	Verify Broker Monitoring Context is provided.
CMPBKRE0010	Error while validating Broker Monitoring Context. Invalid Broker Monitoring Context provided.
Explanation	Error while validating Broker Monitoring Context. Invalid Broker Monitoring Context provided.
Action	Verify a valid Broker Monitoring Context is provided.
CMPBKRE0011	Error while validating Broker Monitoring Context. Context object is null.
Explanation	Error while validating Broker Monitoring Context. Context object is null.
Action	Verify Broker Monitoring Context is provided.
CMPBKRE0012	Error while validating Broker Monitoring Context. Context is invalid.
Explanation	Error while validating Broker Monitoring Context. Context is invalid.
Action	Verify valid Broker Monitoring Context is provided.
CMPBKRE0013	Error while validating Broker Monitoring Context. Context host attribute cannot be null or empty.
Explanation	Error while validating Broker Monitoring Context. Context host attribute cannot be null or empty.
Action	Verify host attribute is provided in Broker Monitoring Context
CMPBKRE0014	Error while validating Broker Monitoring Context. Context port attribute is invalid.
Explanation	Error while validating Broker Monitoring Context. Context port attribute is invalid.
Action	Verify valid port attribute is provided in Broker Monitoring Context.
CMPBKRE0015	Error while creating Broker Server client. Host name cannot be null or empty.
Explanation	Error while creating Broker Server client. Host name cannot be null or empty.
Action	Verify host name is provided.

CMPBKRE0016	Error while creating Broker Server client. Port cannot be null or empty.
Explanation	Error while creating Broker Server client. Port cannot be null or empty.
Action	Verify port is provided.
CMPBKRE0017	Error while destroying Broker Server client. Broker Name cannot be null or empty.
Explanation	Error while destroying Broker Server client. Broker Name cannot be null or empty.
Action	Verify Broker Name is provided.
CMPBKRE0018	Error while creating Broker Admin client. Broker Name cannot be null.
Explanation	Error while creating Broker Admin client. Broker Name cannot be null.
Action	Verify Broker Name is provided.
CMPBKRE0019	Error while setting Broker Admin client. Broker Name cannot be null.
Explanation	Error while setting Broker Admin client. Broker Name cannot be null.
Action	Verify Broker Name is provided.
CMPBKRE0020	Error while setting Broker Admin client. Broker Admin Client cannot be null.
Explanation	Error while setting Broker Admin client. Broker Admin Client cannot be null.
Action	Verify Broker Admin Client is specified.
CMPBKRE0021	Error while initializing Broker Client model. Broker Monitoring Context is null.
Explanation	Error while initializing Broker Client model. Broker Monitoring Context is null.
Action	Verify Broker Monitoring Context is provided.
CMPBKRE0022	Error while getting Broker Client attributes. Model Instance List cannot be null.
Explanation	Error while getting Broker Client attributes. Model Instance List cannot be null.
Action	Verify Model Instance List is provided.
CMPBKRE0023	Error while getting Broker Client attributes. Attribute List cannot be null.
Explanation	Error while getting Broker Client attributes. Attribute List cannot be null.
Action	Verify Attribute List is provided.

CMPBKRE0024	Error while getting Broker Client attribute. Attribute ID cannot be null.
Explanation	Error while getting Broker Client attribute. Attribute ID cannot be null.
Action	Verify Attribute ID is provided.
CMPBKRE0025	Error while initializing Broker Document Type model. Broker Monitoring Context is null.
Explanation	Error while initializing Broker Document Type model. Broker Monitoring Context is null.
Action	Verify Broker Monitoring Context is provided.
CMPBKRE0026	Error while getting Broker Document Type attributes. Model Instance List cannot be null.
Explanation	Error while getting Broker Document Type attributes. Model Instance List cannot be null.
Action	Verify Model Instance List is provided.
CMPBKRE0027	Error while getting Broker Document Type attributes. Attribute List cannot be null.
Explanation	Error while getting Broker Document Type attributes. Attribute List cannot be null.
Action	Verify Attribute List is provided.
CMPBKRE0028	Error while getting Broker Document Type attribute. Attribute ID cannot be null.
Explanation	Error while getting Broker Document Type attribute. Attribute ID cannot be null.
Action	Verify Attribute ID is provided.
CMPBKRE0029	Error while initializing Broker Gateway model. Broker Monitoring Context is null.
Explanation	Error while initializing Broker Gateway model. Broker Monitoring Context is null.
Action	Verify Broker Monitoring Context is provided.
CMPBKRE0030	Error while initializing Broker Gateway model. Broker Monitoring Context is null.
Explanation	Error while initializing Broker Gateway model. Broker Monitoring Context is null.
Action	Verify Broker Monitoring Context is provided.

CMPBKRE0031	Error while getting Broker Gateway attributes. Model Instance List cannot be null.
Explanation	Error while getting Broker Gateway attributes. Model Instance List cannot be null.
Action	Verify Model Instance List is provided.
CMPBKRE0032	Error while getting Broker Gateway attributes. Attribute List cannot be null.
Explanation	Error while getting Broker Gateway attributes. Attribute List cannot be null.
Action	Verify Attribute List is provided.
CMPBKRE0033	Error while getting Broker Gateway attribute. Attribute ID cannot be null.
Explanation	Error while getting Broker Gateway attribute. Attribute ID cannot be null.
Action	Verify Attribute ID is provided.
CMPBKRE0034	Error while initializing Broker model. Broker Monitoring Context is null.
Explanation	Error while initializing Broker model. Broker Monitoring Context is null.
Action	Verify Broker Monitoring Context is provided.
CMPBKRE0035	Error while getting Broker attributes. Model Instance List cannot be null.
Explanation	Error while getting Broker attributes. Model Instance List cannot be null.
Action	Verify Model Instance List is provided.
CMPBKRE0036	Error while getting Broker attributes. Attribute List cannot be null.
Explanation	Error while getting Broker attributes. Attribute List cannot be null.
Action	Verify Attribute List is provided.
CMPBKRE0037	Error while getting Broker attribute. Attribute ID cannot be null.
Explanation	Error while getting Broker attribute. Attribute ID cannot be null.
Action	Verify Attribute ID is provided.
CMPBKRE0038	Error while initializing Broker model instance. Broker Monitoring Context is null.
Explanation	Error while initializing Broker model instance. Broker Monitoring Context is null.
Action	Verify Broker Monitoring Context is provided.

CMPBKRE0039	Error while getting model instances. MetaModel Type name is null or empty.
Explanation	Error while getting model instances. MetaModel Type name is null or empty.
Action	Verify MetaModel Type Name is provided.
CMPBKRE0040	Error while getting model instances. Invalid MetaModel Type Name.
Explanation	Error while getting model instances. Invalid MetaModel Type Name.
Action	Verify valid MetaModel Type Name is provided.
CMPBKRE0041	Error while initializing Broker Server model. Broker Monitoring Context is null.
Explanation	Error while initializing Broker Server model. Broker Monitoring Context is null.
Action	Verify Broker Monitoring Context is provided.
CMPBKRE0042	Error while getting Broker Server attributes. Model Instance List cannot be null.
Explanation	Error while getting Broker Server attributes. Model Instance List cannot be null.
Action	Verify Model Instance List is provided.
CMPBKRE0043	Error while getting Broker Server attributes. Attribute List cannot be null.
Explanation	Error while getting Broker Server attributes. Attribute List cannot be null.
Action	Verify Attribute List is provided.
CMPBKRE0044	Error while getting Broker Server attribute. Attribute ID cannot be null.
Explanation	Error while getting Broker Server attribute. Attribute ID cannot be null.
Action	Verify Attribute ID is provided.
CMPBKRE0045	Error while getting Broker SSL Stats attributes. Attribute ID cannot be null.
Explanation	Error while getting Broker SSL Stats attributes. Attribute ID cannot be null.
Action	Verify valid Attribute ID is provided.
CMPBKRE0046	Error while initializing Broker Territory model. Broker Monitoring Context is null.
Explanation	Error while initializing Broker Territory model. Broker Monitoring Context is null.
Action	Verify Broker Monitoring Context is provided.

CMPBKRE0047 **Error while getting Broker Territory attributes. Model Instance List cannot be null.**
Explanation Error while getting Broker Territory attributes. Model Instance List cannot be null.
Action Verify Model Instance List is provided.

CMPBKRE0048 **Error while getting Broker Territory attributes. Attribute List cannot be null.**
Explanation Error while getting Broker Territory attributes. Attribute List cannot be null.
Action Verify Attribute List is provided.

CMPBKRE0049 **Error while getting Broker Territory attribute. Attribute ID cannot be null.**
Explanation Error while getting Broker Territory attribute. Attribute ID cannot be null.
Action Verify Attribute ID is provided.

CMPBKRE0050 **Error while initializing Territory Broker model. Broker Monitoring Context is null.**
Explanation Error while initializing Territory Broker model. Broker Monitoring Context is null.
Action Verify Broker Monitoring Context is provided.

CMPBKRE0051 **Error while getting Territory Broker attributes. Model Instance List cannot be null.**
Explanation Error while getting Territory Broker attributes. Model Instance List cannot be null.
Action Verify Model Instance List is provided.

CMPBKRE0052 **Error while getting Territory Broker attributes. Attribute List cannot be null.**
Explanation Error while getting Territory Broker attributes. Attribute List cannot be null.
Action Verify Attribute List is provided.

CMPBKRE0053 **Error while getting Territory Broker attribute. Attribute ID cannot be null.**
Explanation Error while getting Territory Broker attribute. Attribute ID cannot be null.
Action Verify Attribute ID is provided.

CMPBKRE0054 **Error while getting Territory Broker Stats attribute. Could not retrieve attribute value.**
Explanation Error while getting Territory Broker Stats attribute. Could not retrieve attribute value.

CMPBKRE0055	Error while getting Territory Broker Stats Event attribute. Could not retrieve attribute value.
Explanation	Error while getting Territory Broker Stats Event attribute. Could not retrieve attribute value.
CMPBKRE0056	Error during Broker ping. Invalid Ping Context.
Explanation	Error during Broker ping. Invalid Ping Context.
Action	Verify valid Ping Context is provided.
CMPBKRE0057	Error during Broker Client ping. Broker Name not set in Broker Monitoring Context.
Explanation	Error during Broker Client ping. Broker Name not set in Broker Monitoring Context.
Action	Verify Broker Name is set in Broker Ping Context.
CMPMWSE0000	MWS HTTP URL Method Name cannot be empty or null.
Explanation	MWS HTTP URL Method Name cannot be empty or null.
Action	Please provide MWS HTTP URL Method Name.
CMPMWSE0001	Error while validating MWS Monitoring Context. MWS Monitoring Context cannot be null.
Explanation	MWS Monitoring Context is required.
Action	Please provide MWS Monitoring Context.
CMPMWSE0002	Error while validating MWS Monitoring Context. MWS Monitoring Context cannot be null.
Explanation	MWS Monitoring Context is required.
Action	Please provide valid MWS Monitoring Context.
CMPMWSE0003	Error while validating Broker Monitoring Context. Context object is null.
Explanation	MWS Monitoring Context is required.
Action	Please provide MWS Monitoring Context.

CMPMWSE0004	Error while validating MWS Monitoring Context. Context is invalid.
Explanation	MWS Monitoring Context is required.
Action	Please provide valid MWS Monitoring Context.
CMPMWSE0005	Error while validating MWS Monitoring Context. Context host attribute cannot be null or empty.
Explanation	MWS Monitoring Context host attribute cannot be null or empty.
Action	Please provide host attribute for MWS Monitoring Context.
CMPMWSE0006	Error while validating Broker Monitoring Context. Context port attribute is invalid.
Explanation	MWS Monitoring Context port attribute cannot be null or empty.
Action	Please provide port attribute for MWS Monitoring Context.
CMPMWSE0007	MWS Monitoring Context cannot be null.
Explanation	MWS Monitoring Context is required for getting MWS model instances.
Action	Please provide MWS Monitoring Context.
CMPMWSE0008	Error while getting meta model. MWS Meta model type ID cannot be null or empty.
Explanation	MWS Meta model type ID cannot be null or empty.
Action	Please provide MWS meta model type ID.
CMPMWSE0009	MWS Monitoring Context cannot be null.
Explanation	MWS Monitoring Context cannot be null.
Action	Please provide MWS Monitoring Context.
CMPMWSE0010	Input parameter mbean name cannot be null.
Explanation	Input parameter mbean name is required.
Action	Please provide input parameter mbean name.
CMPMWSE0011	MWS Monitoring Context cannot be null.
Explanation	MWS Monitoring Context is required for getting MWS model instances.
Action	Please provide MWS Monitoring Context.

CMPMWSE0012	Model instance list or attribute list cannot be null.
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.
CMPMWSE0013	MWS Monitoring Context cannot be null.
Explanation	MWS Monitoring Context is required for getting MWS model instances.
Action	Please provide MWS Monitoring Context.
CMPMWSE0014	Model instance list or attribute list cannot be null.
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.
CMPMWSE0015	MWS Monitoring Context cannot be null.
Explanation	MWS Monitoring Context is required for getting MWS model instances.
Action	Please provide MWS Monitoring Context.
CMPMWSE0016	Model instance list or attribute list cannot be null.
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.
CMPMWSE0017	MWS Monitoring Context cannot be null.
Explanation	MWS Monitoring Context is required.
Action	Please provide MWS Monitoring Context.
CMPMWSE0018	Model instance list or attribute list cannot be null.
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.
CMPMWSE0019	MWS Monitoring Context cannot be null.
Explanation	MWS Monitoring Context is required.
Action	Please provide MWS Monitoring Context.

CMPMWSE0020 Model instance list or attribute list cannot be null.

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPMWSE0021 MWS Monitoring Context cannot be null.

Explanation MWS Monitoring Context is required.

Action Please provide MWS Monitoring Context.

CMPMWSE0022 Model instance list or attribute list cannot be null.

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPMWSE0023 MWS Monitoring Context cannot be null.

Explanation MWS Monitoring Context is required.

Action Please provide MWS Monitoring Context.

CMPMWSE0024 Model instance list or attribute list cannot be null.

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPMWSE0025 MWS Monitoring Context cannot be null.

Explanation MWS Monitoring Context is required.

Action Please provide MWS Monitoring Context.

CMPMWSE0026 Model instance list or attribute list cannot be null.

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPMWSE0027 MWS Monitoring Context cannot be null.

Explanation MWS Monitoring Context is required.

Action Please provide MWS Monitoring Context.

CMPMWSE0028 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPMWSE0029 **MWS Monitoring Context cannot be null.**

Explanation MWS Monitoring Context is required.

Action Please provide MWS Monitoring Context.

CMPMWSE0030 **MWS Monitoring Context cannot be null.**

Explanation MWS Monitoring Context is required.

Action Please provide MWS Monitoring Context.

CMPMWSE0031 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPMWSE0032 **MWS Monitoring Context cannot be null.**

Explanation MWS Monitoring Context is required.

Action Please provide MWS Monitoring Context.

CMPMWSE0033 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPMWSE0034 **Input parameter mbean name cannot be null.**

Explanation Input parameter mbean name is required.

Action Please provide input parameter mbean name.

CMPMWSE0035 **Model instance list or attribute list cannot be null.**

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPMWSE0036	Invalid response from server: {0}
Explanation	Invalid response from server.
Action	Please resolve the issue with output.
CMPMWSE0037	Model instance list cannot be null.
Explanation	Model instance list cannot be null.
Action	Please provide model instance list.
CMPMWSE0038	Attribute instance list cannot be null.
Explanation	Attribute instance list cannot be null.
Action	Please provide attribute instance list.
CMPMWSE0039	Method Name cannot be empty or null.
Explanation	Method Name cannot be empty or null.
Action	Please provide method name.
CMPMWSE0040	Attribute query string cannot be null.
Explanation	Attribute query string cannot be null.
Action	Please provide attribute query string.
CMPMWSE0041	MWS Monitoring Context cannot be null.
Explanation	MWS Monitoring Context cannot be null.
Action	Please provide monitoring context.
CMPMWSE0042	Attribute value is invalid or not available.
Explanation	Attribute value is invalid or not available.
Action	Please provide valid attribute value.
CMPMWSE0043	MWS Monitoring Context cannot be null.
Explanation	MWS Monitoring Context is required.
Action	Please provide MWS Monitoring Context.

CMPMWSE0044	Input metaModelTypeID cannot be null or empty.
Explanation	Input metaModelTypeID cannot be null or empty.
Action	Please provide meta model type ID.
CMPMWSE0045	Input modelInstanceID cannot be null or empty.
Explanation	Input modelInstanceID cannot be null or empty.
Action	Please provide model instance ID.
CMPMWSE0046	Input attributeID cannot be null or empty.
Explanation	Input attributeID cannot be null or empty.
Action	Please provide attribute ID.
CMPMWSE0047	AttributeQuery cannot be null.
Explanation	AttributeQuery cannot be null.
Action	Please provide attribute query.
CMPUMIE0000	UM HTTP URL Method Name cannot be empty or null.
Explanation	UM HTTP URL Method Name cannot be empty or null.
Action	Please provide UM HTTP URL Method Name.
CMPUMIE0001	Error while validating UM Monitoring Context. UM Monitoring Context cannot be null.
Explanation	UM Monitoring Context is required.
Action	Please provide UM Monitoring Context.
CMPUMIE0002	Error while validating UM Monitoring Context. UM Monitoring Context cannot be null.
Explanation	UM Monitoring Context is required.
Action	Please provide valid UM Monitoring Context.
CMPUMIE0003	Error while validating UM Monitoring Context. Context object is null.
Explanation	UM Monitoring Context is required.
Action	Please provide UM Monitoring Context.

CMPUMIE0004	Error while validating UM Monitoring Context. Context is invalid.
Explanation	UM Monitoring Context is required.
Action	Please provide valid UM Monitoring Context.
CMPUMIE0005	Error while validating UM Monitoring Context. Context host attribute cannot be null or empty.
Explanation	UM Monitoring Context host attribute cannot be null or empty.
Action	Please provide host attribute for UM Monitoring Context.
CMPUMIE0006	Error while validating UM Monitoring Context. Context port attribute is invalid.
Explanation	UM Monitoring Context port attribute cannot be null or empty.
Action	Please provide port attribute for UM Monitoring Context.
CMPUMIE0007	UM Monitoring Context cannot be null.
Explanation	UM Monitoring Context is required for getting UM model instances.
Action	Please provide UM Monitoring Context.
CMPUMIE0008	Error while getting meta model. UM Meta model type ID cannot be null or empty.
Explanation	UM Meta model type ID cannot be null or empty.
Action	Please provide UM meta model type ID.
CMPUMIE0009	UM Monitoring Context cannot be null.
Explanation	UM Monitoring Context cannot be null.
Action	Please provide UM Monitoring Context.
CMPUMIE0010	Input parameter mbean name cannot be null.
Explanation	Input parameter mbean name is required.
Action	Please provide input parameter mbean name.
CMPUMIE0011	UM Monitoring Context cannot be null.
Explanation	UM Monitoring Context is required for getting UM model instances.
Action	Please provide UM Monitoring Context.

CMPUMIE0012	Model instance list or attribute list cannot be null.
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.
CMPUMIE0013	UM Monitoring Context cannot be null.
Explanation	UM Monitoring Context is required for getting UM model instances.
Action	Please provide UM Monitoring Context.
CMPUMIE0014	Model instance list or attribute list cannot be null.
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.
CMPUMIE0015	UM Monitoring Context cannot be null.
Explanation	UM Monitoring Context is required for getting UM model instances.
Action	Please provide UM Monitoring Context.
CMPUMIE0016	Model instance list or attribute list cannot be null.
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.
CMPUMIE0017	UM Monitoring Context cannot be null.
Explanation	UM Monitoring Context is required.
Action	Please provide UM Monitoring Context.
CMPUMIE0018	Model instance list or attribute list cannot be null.
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.
CMPUMIE0019	UM Monitoring Context cannot be null.
Explanation	UM Monitoring Context is required.
Action	Please provide UM Monitoring Context.

CMPUMIE0020 Model instance list or attribute list cannot be null.

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPUMIE0021 UM Monitoring Context cannot be null.

Explanation UM Monitoring Context is required.

Action Please provide UM Monitoring Context.

CMPUMIE0022 Model instance list or attribute list cannot be null.

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPUMIE0023 UM Monitoring Context cannot be null.

Explanation UM Monitoring Context is required.

Action Please provide UM Monitoring Context.

CMPUMIE0024 Model instance list or attribute list cannot be null.

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPUMIE0025 UM Monitoring Context cannot be null.

Explanation UM Monitoring Context is required.

Action Please provide UM Monitoring Context.

CMPUMIE0026 Model instance list or attribute list cannot be null.

Explanation Model instance list or attribute list cannot be null.

Action Please provide model instance list or attribute list.

CMPUMIE0027 UM Monitoring Context cannot be null.

Explanation UM Monitoring Context is required.

Action Please provide UM Monitoring Context.

CMPUMIE0028	Model instance list or attribute list cannot be null.
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.
CMPUMIE0029	UM Monitoring Context cannot be null.
Explanation	UM Monitoring Context is required.
Action	Please provide UM Monitoring Context.
CMPUMIE0030	UM Monitoring Context cannot be null.
Explanation	UM Monitoring Context is required.
Action	Please provide UM Monitoring Context.
CMPUMIE0031	Model instance list or attribute list cannot be null.
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.
CMPUMIE0032	UM Monitoring Context cannot be null.
Explanation	UM Monitoring Context is required.
Action	Please provide UM Monitoring Context.
CMPUMIE0033	Model instance list or attribute list cannot be null.
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.
CMPUMIE0034	Input parameter mbean name cannot be null.
Explanation	Input parameter mbean name is required.
Action	Please provide input parameter mbean name.
CMPUMIE0035	Model instance list or attribute list cannot be null.
Explanation	Model instance list or attribute list cannot be null.
Action	Please provide model instance list or attribute list.

CMPUMIE0036	Invalid response from server: {0}
Explanation	Invalid response from server.
Action	Please resolve the issue with output.
CMPUMIE0037	Model instance list cannot be null.
Explanation	Model instance list cannot be null.
Action	Please provide model instance list.
CMPUMIE0038	Attribute instance list cannot be null.
Explanation	Attribute instance list cannot be null.
Action	Please provide attribute instance list.
CMPUMIE0039	Method Name cannot be empty or null.
Explanation	Method Name cannot be empty or null.
Action	Please provide method name.
CMPUMIE0040	Attribute query string cannot be null.
Explanation	Attribute query string cannot be null.
Action	Please provide attribute query string.
CMPUMIE0041	UM Monitoring Context cannot be null.
Explanation	UM Monitoring Context cannot be null.
Action	Please provide monitoring context.
CMPUMIE0042	Attribute value is invalid or not available.
Explanation	Attribute value is invalid or not available.
Action	Please provide valid attribute value.
CMPUMIE0043	UM Monitoring Context cannot be null.
Explanation	UM Monitoring Context is required.
Action	Please provide UM Monitoring Context.

CMPUMIE0044 **Input metaModelTypeID cannot be null or empty.**
Explanation Input metaModelTypeID cannot be null or empty.
Action Please provide meta model type ID.

CMPUMIE0045 **Input modelInstanceID cannot be null or empty.**
Explanation Input modelInstanceID cannot be null or empty.
Action Please provide model instance ID.

CMPUMIE0046 **Input attributeID cannot be null or empty.**
Explanation Input attributeID cannot be null or empty.
Action Please provide attribute ID.

CMPUMIE0047 **AttributeQuery cannot be null.**
Explanation AttributeQuery cannot be null.
Action Please provide attribute query.

9

Database Component Configurator Messages

CAN_NOT_RUN_MIGRATE_MSG – Can not run migrate to version {0}

Explanation The user tried to migrate a database component that does not exist.

Action Make sure the database component exists using the catalog action before trying to migrate it.

CMP_STORE_INIT_ERROR – Error initializing definition store instance

Explanation The Database Component Configurator could not initialize all database component definitions.

Action Contact Software AG Global Support.

DCI_INFO_ERROR_MSG Error in getting DCI about information.

Explanation The user displayed the About information, but build information is missing.

Action Contact Software AG Global Support.

ERROR_ENCODING Error in checking database encoding

Explanation The checkEncoding action failed.

Action Make sure the the RDBMS is running.

10

Deployer Messages

185I	Successfully stored the password entry.
186I	Successfully retrieved the password.
187I	Successfully deleted the password entry.
188I	Successfully retrieved the list of password handles.
189I	Successfully updated the password entry.
190E	Existing password does not match the specified old password.
Explanation	The specified old password does not match the password handle.
Action	Supply the correct existing password.
191E	Password handle {0} does not exist.
Explanation	An error occurred while retrieving the password entry for the password handle.
Action	Supply a valid password handle.

192E	An error occurred while listing password handles.
Explanation	An error occurred while getting the list of available password handles from the password store.
Action	Check the Integration Server logs for more details.
193E	An error occurred while storing the password entry for handle {0}.
Explanation	An error occurred while storing the entry for the specified handle and password values.
Action	Check the Integration Server logs for more details.
194	An error occurred while deleting the password entry for handle {0}.
Explanation	An error occurred while deleting the password entry for the supplied password handle.
Action	Check the Integration Server logs for more details.
195E	The current user is not authorized to access password store operations.
Explanation	Only an authorized user can perform create/delete/update/fetch operations on password stores.
Action	Obtain the proper authorization.
DEP.0000.1205E	Repository-based deployment does not support the simulate operation for target servers of version 8.2 or earlier.
Explanation	Repository-based projects do not support simulate operations for target servers of version 8.2 or earlier.
Action	Select target servers of version 8.2 or later.
DEP.0001.0002E	Deployer could not connect to server aliases {0}. Make sure the server alias information is correct and the server is running.
Explanation	Deployer could not connect to the specified server when executing the CreateBuild command-line script.
Action	Make sure the connection information specified to the script is correct and that the server is running.

DEP.0001.0003E	You are not authorized to extract the {0} project. Ask an administrator or user that has build authorization for the project to perform this task, or ask an administrator to update the authorization for the specified project to give you build authorization.
Explanation	You do not have build authority for the specified project.
Action	Ask an administrator or user that has build authorization for the project to perform this task or ask an administrator to update the authorization for the specified project to give you build authorization.
DEP.0001.0005E	Error checking authorization: {0}. Make sure the service exists and the permissions for the service are adequate to allow execution of the service.
Explanation	An error occurred while invoking the <code>wm.deployer.authorization:isAuthorized</code> service on the Integration Server that is running Deployer.
Action	Make sure the service exists and the permissions for the service are adequate to allow execution of the service.
DEP.0001.0006E	Error writing project file into build file {0}. Make sure there is sufficient disk space, memory, and operating system privileges.
Explanation	An error occurred while trying to write the project file in the build archive file.
Action	Make sure there is sufficient disk space, memory, and that you have the proper operating system privileges.
DEP.0001.0007E	Error writing properties file into build file {0}. Ensure that the project name was correctly specified and that there is sufficient disk space, memory, and operating system privileges.
Explanation	An error occurred while attempting to write the build properties file in the build archive file.
Action	Ensure there is sufficient disk space, memory, and operating system privileges.
DEP.0001.0008E	Error closing build file {0}. Make sure there is sufficient disk space, memory, and operating system privileges to close the build file.
Explanation	An error occurred while attempting to close the build file.
Action	Make sure there is sufficient disk space, memory, and operating system privileges to close the build file.

DEP.0001.0009E	Error creating build report {0}. Make sure there is sufficient disk space, memory, and operating system privileges to create a build report.
Explanation	An error occurred when attempting to create a build report.
Action	Make sure there is sufficient disk space, memory, and operating system privileges to create a build report.
DEP.0001.0010E	Error during extraction: {0}
Explanation	An error occurred while attempting to create a build for a project. The extraction error can be any error that occurred when attempting to create a build. This error can be caused by an object that is listed in the project, but does not exist on the source system.
Action	Ensure that all objects listed in the project exist on the source system.
DEP.0001.0011E	Error extracting IS package {0}: {1}. Make sure the service exists and that the permissions are adequate to allow execution of the service.
Explanation	An error occurred while invoking the <code>wm.deployer.resource.extractor.is:extractPackage</code> service.
Action	Make sure the service exists and that the permissions are adequate to allow execution of the service.
DEP.0001.0012E	Error extracting IS ACL(s) on source system {0}: {1}. Make sure the service exists and the permissions are adequate to allow execution of the service.
Explanation	An error occurred while invoking the <code>wm.deployer.resource.extractor.is:extractAcls</code> service on the specified source system.
Action	Make sure the service exists and that the permissions are adequate to allow execution of the service.
DEP.0001.0013E	Integration Server ACL {0} does not exist on the source system.
Explanation	The identified asset does not exist on the source system.
Action	Either remove the asset from the project or add it to the source system.
DEP.0001.0014E	Deployer encountered the following error while extracting Integration Server users from source system {0}: {1}
Explanation	An error occurred while invoking the <code>wm.deployer.resource.extractor.is:extractUsers</code> service on the specified source system.
Action	Make sure the service exists and that you have the proper permissions to execute the service.

DEP.0001.0015E	The Integration Server user account {0} does not exist on the source system. Either remove the user account from the project or create it on the source system.
Explanation	The identified IS user account does not exist on the source system.
Action	Either remove the user account from the project or create it on the source system.
DEP.0001.0016E	Deployer encountered the following error while extracting Integration Server groups from source system {0}: {1}
Explanation	An error occurred while invoking the wm.deployer.resource.extractor.is:extractGroups service on the specified source system.
Action	Make sure the service exists and that the permissions are adequate to allow execution of the service.
DEP.0001.0017E	The Integration Server group {0} does not exist on the source system. Either remove the group from the project or create the group on the source system.
Explanation	The identified Integration Server group does not exist on the source system.
Action	Either remove the group from the project or create the group on the source system.
DEP.0001.0018E	Deployer encountered the following error while extracting Integration Server ports from source system {0}: {1}
Explanation	An error occurred while invoking the wm.deployer.resource.extractor.is:extractPorts service on the specified source system.
Action	Make sure the service exists and the permissions are adequate to allow execution of the service.
DEP.0001.0020E	Deployer encountered the following error while extracting Integration Server scheduled service {0} ({1}) from source system {2}: {3}
Explanation	An error occurred while invoking the pub.scheduler:getTaskInfo service on the specified source system.
Action	Make sure the service exists and the permissions are adequate to allow execution of the service. If the error message indicates that the scheduled service is not on the source system, either remove the scheduled service from the project or add it to the source system.
DEP.0001.0021E	Deployer encountered the following error while extracting assets from Trading Networks from source system {0}: {1}
Explanation	An error occurred while invoking the wm.tn.admin:exportData service on the specified source Trading Networks system.
Action	Make sure the source Trading Networks system is running, the service exists, and the permissions are adequate to allow execution of the service.

DEP.0001.0035E	Error invoking service "{0}".
Explanation	An error occurred invoking a service on the Integration Server that is running Deployer.
Action	Verify that the service exists and that the permissions are adequate to execute the service. For more information, see the Integration Server error message in the Integration Server error log.
DEP.0001.0036E	An error occurred while invoking service "{0}" on system "{1}".
Explanation	An error occurred while invoking a service on a remote system.
Action	Verify that the service exists and that the permissions are adequate to execute the service. For more information, see the Integration Server error message in the Integration Server error log.
DEP.0001.0038E	Project {0} is empty; it does not contain any assets to extract. Use the Deployer user interface to add assets to the project.
Explanation	The specified project does not contain any assets to extract.
Action	Use the Deployer user interface to add assets to the project.
DEP.0001.0039E	The following source servers are currently unavailable: {0}. Check your network connection and make sure the source servers are running.
Explanation	The source servers are not responding to a ping. To ping a server, Deployer executes services as follows: <ul style="list-style-type: none"> - For an Integration Server system, Deployer uses the wm.server:ping service. - For a Trading Networks system, Deployer uses the wm.tn:ping service. - For any other system, Deployer uses the ping plug-in Web service.
Action	Check the network connection and make sure the source servers are running.
DEP.0001.0041E	Deployment set {0} has unresolved dependencies and could result in an incomplete deployment. Use the Deployer user interface to resolve the dependencies
Explanation	The deployment set has unresolved dependencies and could result in an incomplete deployment.
Action	Use the Deployer user interface to resolve the dependencies.

DEP.0001.0042E	Integration Server package files {0} do not exist. Use the Deployer user interface to verify and edit the list of files for the package.
Explanation	The list of files specified for the package do not exist.
Action	Use the Deployer user interface to verify and edit the list of files for the package.
DEP.0001.0043E	Integration Server package {0} does not exist on the source system. Either remove the package from the project or add it to the source system.
Explanation	The identified Integration Server package does not exist on the source system.
Action	Either remove the package from the project or add it to the source system.
DEP.0001.0044E	Deployer encountered the following error while extracting assets from {0} on source system {1}: {2}
Explanation	An error occurred while invoking the Deployer plug-in web service getObjects on the specified source system.
Action	Make sure the source system is running, the service exists, and the permissions are adequate to execute the service.
DEP.0001.0045E	Build file {0} does not contain a properties file. Build cannot load because the file is incomplete. Make sure the build file is not corrupted and has not been manually updated.
Explanation	Build cannot load because the file is incomplete.
Action	Make sure the build file is not corrupted and has not been manually updated.
DEP.0001.0053E	Integration Server port {0} does not exist on the source system and was not extracted into the build. Make sure the port exists in the source system.
Explanation	The Integration Server port was not extracted into the build.
Action	Make sure the port exists in the source system.
DEP.0001.0054E	The Integration Server scheduled service does not exist on source system {0}: {1}
Explanation	The scheduled service does not exist on the source server.
Action	Either remove the scheduled service from the project or add it to the source system.

DEP.0001.0068E	Deployer encountered the following error while extracting Integration Server package {0} node ACLs: {1}
Explanation	Error when executing the <code>wm.deployer.resource.gui.IS:getTypedPackageContents</code> service.
Action	Make sure the service exists on the Integration Server and the user has the necessary privileges to execute the service.
DEP.0001.0069E	Error writing to the build file {0}. Make sure the build file exists, that it has read/write permission, and that the file system has adequate space.
Explanation	An error occurred while trying to write to the build file.
Action	Read the error message to determine the possible causes. Make sure the build file exists, that it has read/write permission, and there is adequate space for it on the file system.
DEP.0001.0070E	Trading Networks field group {0} does not exist on the specified source Trading Networks system. Either remove the profile field group from the project or add it to the source Trading Networks system.
Explanation	The identified Trading Networks profile field group does not exist on the specified source Trading Networks system.
Action	Either remove the profile field group from the project or add it to the source Trading Networks system.
DEP.0001.0071E	Trading Networks field definition {0} does not exist on the source Trading Networks system. Either remove the profile field definition from the project or add it to the source Trading Networks system.
Explanation	The identified Trading Networks profile field definition does not exist on the source Trading Networks system.
Action	Either remove the profile field definition from the project or add it to the source Trading Networks system.
DEP.0001.0072E	Trading Networks Profile {0} does not exist on the source Trading Networks system. Either remove the profile from the project or add it to the source Trading Networks system.
Explanation	The identified Trading Networks profile does not exist on the source Trading Networks system.
Action	Either remove the profile from the project or add it to the source Trading Networks system.

DEP.0001.0073E	Trading Networks TPA {0} does not exist on the source Trading Networks system. Either remove the TPA from the project or add it to the source Trading Networks system.
Explanation	The identified Trading Networks trading partner agreement (TPA) does not exist on the source Trading Networks system.
Action	Either remove the TPA from the project or add it to the source Trading Networks system.
DEP.0001.0074E	Trading Networks document attribute {0} does not exist on the source Trading Networks system. Either remove the document attribute from the project or add it to the source Trading Networks system.
Explanation	The identified Trading Networks document attribute does not exist on the source Trading Networks system.
Action	Either remove the document attribute from the project or add it to the source Trading Networks system.
DEP.0001.0075E	Trading Networks document type {0} does not exist on the source Trading Networks system. Either remove the Trading Networks document type from the project or add it to the source Trading Networks system.
Explanation	The identified Trading Networks document type does not exist on the source Trading Networks system.
Action	Either remove the Trading Networks document type from the project or add it to the source Trading Networks system.
DEP.0001.0076E	Trading Networks processing rule {0} does not exist on the Trading Networks source system. Either remove the processing rule from the project or add it to the source Trading Networks system.
Explanation	The identified Trading Networks processing rule does not exist on the Trading Networks source system.
Action	Either remove the processing rule from the project or add it to the source Trading Networks system.
DEP.0001.0077E	Trading Networks external ID type {0} does not exist on the source Trading Networks system. Either remove the external ID type from the project or add it to the source Trading Networks system.
Explanation	The identified Trading Networks external ID type does not exist on the source Trading Networks system.
Action	Either remove the external ID type from the project or add it to the source Trading Networks system.

DEP.0001.0078E	Trading Network contact type {0} does not exist on the source Trading Networks system. Either remove the contact type from the project or add it to the source Trading Networks system.
Explanation	The identified Trading Networks contact type does not exist on the source Trading Networks system.
Action	Either remove the contact type from the project or add it to the source Trading Networks system.
DEP.0001.0079E	Trading Networks binary type {0} does not exist on the source Trading Networks system. Either remove the binary type from the project or add it to the source Trading Networks system.
Explanation	The identified Trading Networks binary type does not exist on the source Trading Networks system.
Action	Either remove the binary type from the project or add it to the source Trading Networks system.
DEP.0001.0080E	Trading Networks profile group {0} does not exist on the source Trading Networks system. Either remove the profile group from the project or add it to the source Trading Networks system.
Explanation	The identified Trading Networks profile group does not exist on the source Trading Networks system.
Action	Either remove the profile group from the project or add it to the source Trading Networks system.
DEP.0001.0081E	Trading Networks extended field {0} for profile {1} does not exist on the source Trading Networks system for the specified profile. Either remove the extended field from the project or add it to the appropriate profile in the source Trading Networks system.
Explanation	The identified Trading Networks extended field does not exist on the source Trading Networks system for the specified profile.
Action	Either remove the extended field from the project or add it to the appropriate profile in the source Trading Networks system.
DEP.0001.0082E	Trading Networks security data item {0} does not exist on the source Trading Networks system. Either remove the security data item from the project or add it to the source Trading Networks system.
Explanation	The identified Trading Networks security data item does not exist on the source Trading Networks system.
Action	Either remove the security data item from the project or add it to the source Trading Networks system.

DEP.0001.0085W	Warning creating build {0}. See build report for details.
Explanation	Deployer issued a warning while creating the build.
Action	Check the build report for details.
DEP.0001.0087E	Deployer encountered the following error while extracting Integration Server extended settings from source system {0}: {1}
Explanation	An error occurred while invoking the <code>wm.deployer.resource.extractor.is:extractExtendedSettings</code> service on the specified source system.
Action	Make sure the service exists and that the permissions are adequate to allow execution of the service.
DEP.0001.0093	Trading Networks queue {0} does not exist on the source system. Either remove the asset from the project or add it to the source system.
Explanation	The identified asset does not exist on the source system.
Action	Either remove the asset from the project or add it to the source system.
DEP.0001.0094E	Integration Server extended setting {0} does not exist on the source server.
Explanation	The indicated extended setting does not exist on the source server.
Action	Either remove the extended setting from the project or add the extended setting to the source server.
DEP.0001.0109	TN processing rule {0} does not exist on the source system. Either remove the asset from the project or add it to the source system.
Explanation	The identified asset does not exist on the source system.
Action	Either remove the asset from the project or add it to the source system.
DEP.0001.0114	TN extended field {0} for profile {1} does not exist on the source system. Either remove the asset from the project or add it to the source system.
Explanation	The identified asset does not exist on the source system.
Action	Either remove the asset from the project or add it to the source system.

DEP.0001.0117	Cannot write to build directory: {0}. The Integration Server user does not have privileges to create or write to a file. Make sure the user has the correct privileges.
Explanation	The Integration Server user does not have privileges to create or write to a file.
Action	Make sure the user has the correct privileges.
DEP.0001.0118	Error writing checkpoint report: {0}. An error occurred while attempting to close the build file. Make sure there is sufficient disk space, memory, and operating system privileges.
Explanation	An error occurred while attempting to close the build file.
Action	Make sure there is sufficient disk space, memory, and operating system privileges.
DEP.0001.0119	IS scheduled service {0} ({1}) does not exist on the source server. Either remove the scheduled service from the project or add it to the source system.
Explanation	The identified asset was not found on the source system.
Action	Either remove the asset from the project or add it to the source system.
DEP.0001.0122	TN DIs {0} does not exist on the source server. Either remove the asset from the project or add it to the source system.
Explanation	The identified asset does not exist on the source system.
Action	Either remove the asset from the project or add it to the source system.
DEP.0001.0125	TN Fp {0} does not exist on the source system.
Explanation	The identified asset does not exist on the source system.
Action	Either remove the asset from the project or add it to the source system.
DEP.0001.0128	TN Archival Service {0} does not exist on the source system.
Explanation	The identified asset does not exist on the source system.
Action	Either remove the asset from the project or add it to the source system.
DEP.0001.0130	The Target Server/Group {0} is not currently available; skipping that Target Server/Group. Check your network connection, and verify that the Target Server/Group is running.
Explanation	Deployer cannot ping a target server or some servers in a target group. This might occur because the servers in question are not running or because of network latency.
Action	Make sure that the servers in question are running.

DEP.0001.0131	{0} {1} {2} does not exist on the source system.
Explanation	The identified objects do not exist on the source system.
Action	Either remove the identified objects from the project or add them to the source system.
DEP.0001.0133	Could not rebuild project {0} because the specific build in the project could not be rebuilt. See the Integration Server logs for more information.
Explanation	Deployer could not migrate the project because the specific build in the project could not be rebuilt.
Action	See the Integration Server logs for more information.
DEP.0001.0135	Deployer could not migrate project {0}. Make sure all source servers specified in project {0} are running. See the Integration Server logs for more information.
Explanation	Deployer could not migrate the project.
Action	See the Integration Server logs for more information.
DEP.0001.0136	Could not migrate projects data. See the Integration Server logs for more information.
Explanation	Deployer was unable to migrate the project data.
Action	See the Integration Server logs for more information.
DEP.0001.0139	Some of the projects could not be migrated. See the Integration Server logs for more information.
Explanation	Deployer could not migrate all projects.
Action	See the Integration Server logs for more information.
DEP.0001.0144E	The source servers hosting the deployment sets are from different releases. Make sure all source servers are from the same release.
Explanation	Deployer issues this message and ends the build process when you modify the version of the source server alias for existing projects.
Action	Make sure all source servers are from the same release.
DEP.0001.0145E	Deployer did not migrate the following target groups because the alias servers were not migrated to the correct version. Change the version of the server alias or target group so that the two match.
Explanation	You migrated a target group to a different version than that of its server alias.
Action	Change the version of the server alias or target group so that the two match.

DEP.0001.0153W **Marked {0} {1} for deletion. The indicated server, or the network connection to that server, is not available. Alternatively, the command-line values for user and password might not be valid on the indicated server. Confirm that the server is running and reachable, and that the user/password values are valid.**

Explanation The indicated server, or the network connection to that server, is not available. Alternatively, the command-line values for user and password might not be valid on the indicated server.

Action Confirm that the server is running and reachable, and that the user/password values are valid.

DEP.0001.0154W **Streamed file {0} for file {1} in deployment set {3} not found. The Integration Server, or the network connection to that server, might be shut down. Confirm that the server is running and that the network connection is up.**

Explanation The Integration Server, or the network connection to that server, might be shut down.

Action Confirm that the server is running and that the network connection is up.

DEP.0001.0155 **Error while reading streamed file {0} for file {1} in deployment set {3}. See the Integration Server logs for more information.**

Explanation An error occurred while reading the streamed file.

Action See the Integration Server logs for more information.

DEP.0001.0156 **Deployer could not connect to the source server aliases specified in the project. Deployer could not rebuild and upgrade the project {0}. Make sure the server alias information is correct and the servers are running.**

Explanation Deployer could not migrate the project because the specific build in the project could not be rebuilt.

Action Make sure the source servers for the deployment set in the build are running.

DEP.0001.0158E **Build name {0} contains one or more of the following invalid characters: # & @ ^ ! % * : \$ / \ ' ; , ~ + = > < " ' " Remove the invalid characters from the build name.**

Explanation The build name contains one or more of the following invalid characters: # & @ ^ ! % * : \$ / \ ' ; , ~ + = > < " ' "

Action Remove the invalid characters from the build name.

DEP.0001.0159E	Deployer could not migrate the Deployer settings. See the Integration Server logs for more information.
Explanation	Deployer encountered an error while migrating the Deployer settings.
Action	Check the Integration Server logs for more information.
DEP.0001.0161E	Deployer could not migrate settings.
Explanation	Deployer did not receive the settings during migration.
Action	Reload the Deployer package.
DEP.0002.0004E	Project {0} does not contain a deployment set named {1}.
Explanation	The Deployer user interface referenced a deployment set name that is not recognized by the Deployer. Another Deployer session might have deleted this deployment set, or the project might be corrupted on the file system.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.
DEP.0002.0006E	Deployer did not find a dependency on component {0} was found.
Explanation	The Deployer user interface attempted to delete a dependency that is not recognized by Deployer. Another Deployer session might have deleted the dependency, or the project might be corrupted on the file system.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.
DEP.0002.0007E	Deployer cannot access server alias {0} in deployment set {1}.
Explanation	The Deployer user interface referenced a source server name that is not recognized by Deployer. Another Deployer session might have deleted the source server from the project, or the project might be corrupted on the file system.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.
DEP.0002.0008E	Package {0} from server alias {1} does not exist in deployment set {2}.
Explanation	The Deployer user interface referenced a package or server name that is not recognized by Deployer. Another Deployer session might have deleted the package or server name from the project, or the project might be corrupted on the file system.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.

DEP.0002.0009E	Server {0} already exists in deployment set {1} as a non-Integration Server server. You cannot add Integration Server objects to it.
Explanation	You passed an incorrect value for the parameter.
Action	Avoid executing the service outside of the Deployer user interface.
DEP.0002.0010E	Package {0} already exists in deployment set {1} as a complete package. Cannot add package components or files to it.
Explanation	You attempted to add package components to a deployment set that already exists on the deployment set.
Action	If you want to include the entire package in a deployment set, no action is necessary because it is already included. If you want the deployment set to contain only a partial package, first remove the entire package from the deployment set before trying to add specific package components.
DEP.0002.0011E	Project {0} already contains a deployment set named {1}. Use a different name for the new deployment set.
Explanation	You attempted to add a deployment set to the specified project, but the project already has a deployment set that uses the same name that you specified.
Action	Use a different name for the new deployment set.
DEP.0002.0012E	Project name {0} contains illegal characters.
Explanation	The project name contains spaces or one or more of the following invalid characters: # & @ ^ ! % * : \$ / \ \ ` ' ; , ~ + = > < \ "
Action	Specify another name for the project that does not include the illegal characters.
DEP.0002.0013E	Could not complete project copy due to file system error. Check your Integration Server's disk space. If you believe there is sufficient space, try the copy again. As a final option, manually recreate the project.
Explanation	Deployer encountered an error writing the project to disk.
Action	Check your Integration Server's disk space. If you believe there is sufficient space, try the copy again. As a final option, manually recreate the project.
DEP.0002.0014E	Project {0} already exists. Use a different, unique name for the new project.
Explanation	A project with the name you specified already exists.
Action	Use a different, unique name for the new project.

DEP.0002.0015E	Deployer was unable to invoke service {0}.
Explanation	Deployer was unable to find the specified Integration Server service.
Action	Determine whether a required Integration Server package is disabled, missing, or whether parts are missing. Check for the following packages: WmDeployer, WmAdmin, WmRoot, WmDeployerResource, and WmModeler.
DEP.0002.0016E	Unable to delete build {0}. The build file is probably in use. This file exists in the <serverDirectory>/packages/WmDeployer/persist/projects/<YourProjectName>/builds directory. Locate the process that is accessing this file and stop it. Then try to delete the build again.
Explanation	Deployer was unable to delete the specified build file.
Action	The build file is probably in use. This file exists in the <serverDirectory>/packages/WmDeployer/persist/projects/<YourProjectName>/builds directory. Locate the process that is accessing this file and stop it. Then try to delete the build again.
DEP.0002.0017E	Project {0} does not contain a build named {1}.
Explanation	The Deployer user interface referenced a build name that is not recognized by Deployer. Another Deployer session might have deleted this build, or the project might be corrupted on the file system.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.
DEP.0002.0018E	Deployer could not load build {0}.
Explanation	The build file is corrupted.
Action	Use Windows Explorer to locate the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\builds directory and manually remove the corrupted build file. Then use Deployer to rebuild.
DEP.0002.0019E	Deployment map {0} already exists in project {1}.
Explanation	You attempted to create a deployment map with the same name as an existing deployment map.
Action	Use a different name for the new deployment map.

DEP.0002.0020E	Deployment map {0} does not exist in project {1}.
Explanation	The Deployer user interface referenced a deployment map name that is not recognized by the Deployer. Another Deployer session might have deleted this deployment map, or the project on the file system might be corrupted.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.
DEP.0002.0021E	Deployer could not load deployment map {0} from project {1}.
Explanation	The deployment map file is corrupted.
Action	Use Windows Explorer to locate the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\targets directory and manually remove your deployment candidate file. Then use Deployer to recreate it.
DEP.0002.0026E	Deployer could not save deployment map {0}.
Explanation	Deployer encountered an error writing to disk.
Action	Check your Integration Server's disk space. If you believe there should be sufficient space, try to save again. If this is not successful, try one or both of the following: Restart the server. Recreate the deployment map.
DEP.0002.0028E	Deployment set {0} is not mapped to target {1}.
Explanation	The Deployer user interface referenced a deployment set name that is not recognized by the Deployer. Another Deployer session might have deleted this deployment set, or the project might be corrupted on the file system.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.
DEP.0002.0031	Could not invoke service {0} remotely.
Explanation	An integration service invocation failed.
Action	Ensure that the Integration Server is running and that the service exists on that Integration Server. Also ensure that you have the proper privileges to execute the service.

DEP.0002.0032E	Server Alias cannot be blank.
Explanation	You left the required Server Alias field blank.
Action	Specify a value for the Server Alias field and try again.
DEP.0002.0054E	The value specified for the task parameter is not valid.
Explanation	You passed an incorrect value for the task parameter. The task must be either DEFINE, MAP, EXTRACT, DEPLOY, or VIEW.
Action	Avoid executing the service outside of the Deployer user interface.
DEP.0002.0058E	Deployer cannot perform export operation because the file {0} already exists under WmDeployer/outbound
Explanation	You attempted to export a build with the same name as an existing build.
Action	Use a different name when you export the build.
DEP.0002.0059E	The Deployer import map file {0} is not accessible or does not exist.
Explanation	You attempted to import a build that does not exist.
Action	Refresh the Import Build page and try again.
DEP.0002.0060E	User is not authorized to export builds from project {0}.
Explanation	You are not authorized to export builds for the specified project. You must have build authorization for the project.
Action	Ask an administrator or user that has build authorization for the project to perform this task or have an administrator assign you build authorization.
DEP.0002.0061E	User is not authorized to import builds to project {0}.
Explanation	You are not authorized to import builds for the specified project. You must have build authorization for the project.
Action	Ask an administrator or user that has build authorization for the project to perform this task or have an administrator assign you build authorization.
DEP.0002.0064E	Deployment set {0} already exists in project {1}.
Explanation	You attempted to create a deployment set in a project that already contains a deployment set of the same name.
Action	Use a different name for the new deployment set.

DEP.0002.0065E	Deployer encountered an error and did not save deployment {0}.
Explanation	Deployer encountered an error while writing to disk.
Action	Check your Integration Server's disk space. If you believe there should be sufficient space, try to save again. If Deployer still cannot save the deployment, restart the server or recreate the deployment candidate.
DEP.0002.0067E	Deployment candidate {0} does not exist in project {1}.
Explanation	The Deployer user interface referenced a deployment candidate that is not recognized by Deployer. Another Deployer session might have deleted the deployment candidate, or the project might be corrupted on the file system.
Action	Refresh the page and try again. If the same error occurs, this project might be corrupted on the file system and you might have to discard it.
DEP.0002.0068E	Unable to delete deployment map {0}.
Explanation	Deployer was unable to delete the specified deployment map file.
Action	The deployment map file is probably in use. This file exists in the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\targets directory. Locate the process that is accessing this file and stop it. Then try to delete the deployment candidate again.
DEP.0002.0069E	Unable to delete deployment candidate {0}.
Explanation	Deployer was unable to delete the deployment candidate file.
Action	The deployment candidate file is probably in use. This file exists in the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\deployments directory. Locate the process that is accessing this file and stop it. Then try to delete the deployment candidate again.
DEP.0002.0072E	Deployer could not load deployment {0} from project {1}.
Explanation	The deployment candidate file is corrupted.
Action	Use Windows Explorer to locate to the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\deployments directory and manually remove the deployment candidate file. Then use Deployer to recreate it.

<p>DEP.0002.0073E</p> <p>Explanation</p> <p>Action</p>	<p>Deployer could not add component {0} of type {1}.</p> <p>Deployer does not recognize the specified Integration Server component.</p> <p>Rather than attempting to add the component to the project, add the files that comprise the component (example, "ns" directory). You can also try adding the entire package rather than individual components of the package.</p>
<p>DEP.0002.0075E</p> <p>Explanation</p> <p>Action</p>	<p>When you specify "deploymentName", you cannot specify additional arguments .</p> <p>You specified incorrect arguments when running the deploy.bat or deploy.sh script.</p> <p>The deploy script can either reference an existing deployment candidate or create a new deployment candidate. When you specify the "deploymentName" argument to reference an existing deployment candidate do not supply other arguments.</p>
<p>DEP.0002.0076E</p> <p>Explanation</p> <p>Action</p>	<p>When you specify "newDeploymentName", "buildName" and "deploymentMapName" are required.</p> <p>You specified incorrect arguments for the deploy.bat or deploy.sh script.</p> <p>You can specify the deploy script to either reference an existing deployment candidate or to create a new deployment candidate. If you use the "newDeploymentName" argument to create a new deployment candidate, you must also specify the "buildName" and "deploymentMapName" arguments.</p>
<p>DEP.0002.0077E</p> <p>Explanation</p> <p>Action</p>	<p>You are not authorized to modify the project definition.</p> <p>You are not authorized to define a project.</p> <p>Ask an administrator or user that has define authorization to perform the action for you or have an administrator assign you define authorization.</p>
<p>DEP.0002.0078E</p> <p>Explanation</p> <p>Action</p>	<p>You are not authorized to modify the project target mapping.</p> <p>You are not authorized to map a project.</p> <p>Ask an administrator or user that has map authorization to perform the action for you or have an administrator assign you map authorization.</p>
<p>DEP.0002.0079E</p> <p>Explanation</p> <p>Action</p>	<p>You are not authorized to modify project deployments.</p> <p>You are not authorized to deploy a project.</p> <p>Ask an administrator or user that has deploy authorization to perform the action for you or have an administrator assign you deploy authorization.</p>

- DEP.0002.0080E** **You are not authorized to remove project builds.**
Explanation You are not authorized to build a project.
Action Ask an administrator or user that has build authorization to perform the action for you or have an administrator assign you build authorization.
- DEP.0002.0081E** **Deployer cannot delete build {0} because it is being used by deployment candidate {1}.**
Explanation You attempted to delete a build that is referenced by a deployment candidate.
Action Delete or modify the deployment candidate that references the build or do not delete this build.
- DEP.0002.0082E** **Deployer cannot delete deployment map {0} because it is being used by deployment candidate {1}.**
Explanation You attempted to delete a deployment map that is referenced by another deployment candidate.
Action Delete or modify the deployment candidate that references the deployment map.
- DEP.0002.0083E** **Deployer encountered the following exception while parsing project {0}: {1}**
Explanation An exception occurred while trying to load the project. The exception be due to an input/output error.
Action Review the exception message to determine the cause of the error.
- DEP.0002.0085E** **Deployer could not add package {0} to the deployment set.**
Explanation Deployer was unable to determine which components in the package were available for variable substitution. The problem might be that the source Integration Server was temporarily unavailable.
Action Check the Integration Server Error log to determine the reason that Deployer was unable to access information about the package components.
- DEP.0002.0086E** **Deployment map {0} in project {1} is corrupted and must be removed. It references deployment set {2} which does not exist.**
Explanation The deployment map file is corrupted.
Action Use Windows Explorer to locate the <serverDirectory>\packages\WmDeployer\persist\projects\<YourProjectName>\targets directory and manually remove the deployment map file. Then use Deployer to recreate it.

DEP.0002.0087E	Deployer cannot remove deployment set {0}. It is referenced by deployment map {1}.
Explanation	You attempted to delete a deployment set that is being referenced by a deployment map.
Action	Perform one of the following: <ul style="list-style-type: none"> - Delete or modify the deployment map that references the deployment set. - Do not delete the deployment set.
DEP.0002.0089E	Deployer could not save adapter connection metadata for project {0}
Explanation	The project is corrupted.
Action	Retry the last action taken on the deployment project. If the action is unsuccessful, create a new project.
DEP.0002.0092E	Deployer cannot update package {0} version in the deployment set.
Explanation	Deployer was unable to access the specified package on the server.
Action	Retry the action. If the action is unsuccessful, investigate why Deployer is unable to locate the specified package on the remote server. If the package appears to be available on the remote server, shut down the Deployer window (as well as the window that launched Deployer) and restart the browser.
DEP.0002.0093E	Both the {0} and the {1} Deployer plug-ins contain the Deployer plug-in type {2}.
Explanation	More than one plug-in for the same type of deployment asset has been detected. This indicates a problem with the configuration of the Deployer.
Action	Update the configuration of the Deployer to remove extraneous plug-ins for the same type of deployment asset. Alternatively, you can uninstall, then reinstall Deployer.
DEP.0002.0096E	Deployer is currently unable to access Trading Networks system: {0}.
Explanation	No data was returned from the specified Trading Networks server. This indicates that the Trading Networks server is not accessible.
Action	Ensure that the Trading Networks server is accessible over the network and that you have correctly configured the server alias.

DEP.0002.0097E	Deployer is currently unable to access target system: {0}.
Explanation	The target Trading Networks Server is not available. The server did not respond to a server ping.
Action	Ensure that the Trading Networks Server is accessible over the network and that you have correctly configured the server alias for the Trading Networks server.
DEP.0002.0098E	Deployer cannot check target cluster configuration. The target is missing the Deployer resource package. This can be installed from the Servers > IS & TN screen.
Explanation	An error occurred while Deployer attempted to access a service on the target WmDeployerResource package.
Action	Install the current version of WmDeployerResource package on the target server.
DEP.0002.0099E	Cluster node details not available.
Explanation	An error occurred when the Deployer attempted to access a service on the target WmDeployerResource package.
Action	Install the current version of the WmDeployerResource package on the target server. Also, ensure that the target server is running and that Deployer can access it over the network.
DEP.0002.0101E	The source servers hosting the deployment sets are different versions.
Explanation	The source servers hosting the deployment sets are different versions.
Action	Modify the source servers to use the same versions.
DEP.0002.0102E	The target server or target group is a different version than the project source. Select servers that use the same version.
Explanation	Deployer issues this error message when you add a target server or target group to a deployment map and the version of the target server or group is different than that of the project source server.
Action	Use a target server or target group that is the same version as the project source server.
DEP.0002.0106E	Dependencies may not contain the \$ character.
Explanation	You added a manual dependency that contains the \$ character.
Action	Remove the \$ character.

DEP.0002.0109E	Failed to install resource package on Integration Server {0}: {1}
Explanation	Deployer is trying to install the WmDeployerResource package on the IntegrationServer indicated by <serverName>, but the attempt failed. The <exceptionMessage> provides more information.
Action	Make sure the server is running and connected to the network, and that the system has sufficient disk space, memory, and necessary operating system privileges.
DEP.0002.0110E	Deployer could not locate resource package {0}. Make sure the WmDeployerResource package has been installed on the Integration Server that hosts Deployer and that the system has sufficient disk space, memory, and the necessary operating system privileges.
Explanation	An error occurred when the Deployer tried to locate the WmDeployerResource package. The <exceptionMessage> provides information about why that attempt failed. The resource package might not exist on your Integration Server or might require more memory.
Action	Make sure the WmDeployerResource package has been installed on the Integration Server that hosts Deployer and that the system has sufficient disk space, memory, and the necessary operating system privileges.
DEP.0002.0112	Unable to import the XML document {0} nl{1}. The XML file you passed in either the import map or the import varsub flow is invalid. Correct the XML file as necessary.
Explanation	The XML file you passed in either the import map or the import varsub flow is invalid.
Action	Correct the XML file as necessary.
DEP.0002.0114	Input XML varsub information is not valid. It might contain an asset type for which varsub is not supported. Validate the XML file against the wm.deployer.flows:DeploymentMap_Definition or wm.deployer.flows:Varsub_Definition XSD.
Explanation	The varsub XML file is not valid. It might contain an asset type for which varsub is not supported. The assets for which varsub is supported are AdapterConnection, ScheduledService, ExtendedSettings, Port, AdapterNotification, AdapterListener, eform, and webServiceDescriptor.
Action	Validate the XML file against the wm.deployer.flows:DeploymentMap_Definition or wm.deployer.flows:Varsub_Definition XSD.

DEP.0002.0116 **Exporting of map {0} failed; the exported map file already exists in the WmDeployer/replicate/inbound folder. Make a backup of the map file in another location, delete the map file from the inbound folder, and then export the map file again.**

Explanation The exported map file already exists in the WmDeployer/replicate/inbound folder.

Action Make a backup of the map file in another location, delete the map file from the inbound folder, and then export the map file again.

DEP.0002.0118 **Importing of map {0} failed. Make sure the wm.deployer.gui.UITarget:addMapSetToProject service exists and that the user has the necessary privileges for executing the service, and then try again.**

Explanation This error might occur for no specific reason.

Action Make sure the wm.deployer.gui.UITarget:addMapSetToProject service exists and that the user has the necessary privileges for executing the service, and then try again.

DEP.0002.0119 **Deployment map {0} already exists in project {1} and cannot be overwritten.**

Explanation You attempted to import a map file for a map that already exists.

Action Delete the existing map and then import the map. If you need a backup of the existing map export the map and store it in a different location.

DEP.0002.0120 **Unable to list remote server aliases.**

Explanation This error might occur for no specific reason.

Action Make sure the wm.deployer.Util:listAliases service exists and the user has the necessary privileges for executing the service. then try again.

DEP.0002.0121 **Unable to list target group aliases.**

Explanation This error might occur for no specific reason.

Action Make sure the wm.deployer.gui.UITargetGroup:listTargetGroups service exists and the user has the necessary privileges for executing the service. Then try again.

DEP.0002.0124 **Deployment set {0} is not valid for project {1}.**

Explanation One or more deployment sets defined in the map file you are importing are not included in the project definition.

Action Make sure the map file you are trying to import is consistent with the define step of the project.

DEP.0002.0125	The target server {0} is not valid for plugin type {1}. Either define the target server alias on the Deployer where you are trying to import the map file or remove the target server alias from the exported map file.
Explanation	This error is shown when you attempt to import a map file that contains a target server alias that is not defined on that Deployer.
Action	Either define the target server alias on the Deployer where you are trying to import the map file or remove the target server alias from the exported map file.
DEP.0002.0126	The target group {0} is not valid for plugin type {1}. Define the target group on the Deployer where you are trying to import the map file or else remove the target group from the exported map file.
Explanation	This error is shown when you try to import a map file that contains a target group not defined on that Deployer.
Action	Define the target group on the Deployer where you are trying to import the map file or else remove the target group from the exported map file.
DEP.0002.0129	Either the number passed is not a number or is negative. Enter an integer value for the flag -id for the command --showReport.
Explanation	This error is thrown by the Deployer command line interface for the --showReport command. The --showReport command requires an integer value for the flag -id. If an integer is not entered for this flag then the above error is thrown.
Action	Enter an integer value for the flag -id for the command --showReport.
DEP.0002.0133	Error exporting properties for the project {0}.
Explanation	This error might occur for no specific reason.
Action	Make sure the <code>wm.deployer.gui.UIProject:getFormattedProjectInfo</code> service exists and the user has the necessary privileges for executing the service.
DEP.0002.0135	Error retrieving properties for the project {0}.
Explanation	This error might occur for no specific reason.
Action	Make sure the <code>wm.deployer.gui.UIProject:getFormattedProjectInfo</code> service exists and the user has the necessary privileges for executing the service.
DEP.0002.0136	Unable to import zip file; zip file might be corrupt. Copy the build file from the source Deployer again. If this does not fix the problem, rebuild the original project and export the build again.
Explanation	The build file placed in the <code>WmDeployer/replicate/inbound</code> is corrupted. This can occur because of error while copying the build file.
Action	Copy the build file from the source Deployer again. If this does not fix the problem, rebuild the original project and export the build again.

DEP.0002.0137 **Install of WmDeployerResource package cannot proceed. All the nodes in this cluster are not online. The following nodes are offline: {0}. Installing the package on the local node only.**

Explanation This error occurs when you try to install the WmDeployerResource package on a cluster node and some of the nodes of the cluster are offline.

Action Make sure all the nodes in the cluster are online.

DEP.0002.0138E **You tried to add a target server or a target group of the same name as one that already exists in the deployment map.**

Explanation You tried to add a target server or a target group of the same name as one that already exists in the deployment map.

Action Rename the target server or target group alias and add it to the map.

DEP.0002.0139 **Cannot import the deployment map. Make sure the field names, values and the structure of the XML file are valid.**

Explanation The exported map does not have the expected structure.

Action If you modified the XML, validate the exported XML with the service `wm.deployer.flows:validateXMLWithXSD`.

If you are exporting a map, pass the schema file as `wm.deployer.flows:DeploymentMap_Definition`.

If you are exporting a varsub, pass the schema file as `wm.deployer.flows:Varsub_Definition`.

DEP.0002.0140 **Cannot import variable substitution values. Make sure the field names and values and the structure of the XML file are valid.**

Explanation This error occurs when the exported map does not have the expected structure.

Action If you have modified the XML, validate the exported xml with the service `wm.deployer.flows:validateXMLWithXSD`.

If you are exporting a map then pass the schema file as `wm.deployer.flows:DeploymentMap_Definition`.

If you are exporting a varsub then pass the schema file as `wm.deployer.flows:Varsub_Definition`.

DEP.0002.0142	Project {0} already contains a deletion set named {1}. Rename the deployment or deletion set you are trying to create or delete the existing deployment or deletion set from the project. Then retry your action.
Explanation	You tried to add a deployment or deletion set of the same name as one of the deployment or deletion sets already in the project.
Action	Rename the deployment or deletion set you are trying to create or delete the existing deployment or deletion set from the project. Then retry your action.
DEP.0002.0143	A project can have only one deletion set for each server type. Deletion set {0} already exists for {1}. You can add assets to existing deleting sets, or delete the existing deletion set before trying to create another deletion set.
Explanation	You attempted to create a deletion set on a project that already contains one. Only one deletion set can be created for a project.
Action	You can add assets to existing deleting sets, or delete the existing deletion set before trying to create another deletion set.
DEP.0002.0144E	Deployer encountered an error while trying to get dependent assets for deletion set {0}. See the Integration Server logs.
Explanation	This error might occur for no specific reason.
Action	Ensure the <code>wm.deployer.gui.UITarget:checkTargetDependencies</code> service exists and the user has the necessary privileges for executing the service.
DEP.0002.0146	Deletion sets definition file {0} already exists for this project. Make a back up of the existing file in another location and then delete the file. Then export the deletion set again.
Explanation	The exported file already exists and another export for the same deletion set would cause this error.
Action	Make a back up of the existing file in another location and then delete the file. Then export the deletion set again.
DEP.0002.0147	Rollback on deployment candidate {0} failed. Check the rollback report for more information.
Explanation	This error might occur for no specific reason.
Action	Check the rollback report for further information.

DEP.0002.0148	No such deployment candidate {0} found in project {1}. Delete and recreate the deployment candidate.
Explanation	This error might occur for no specific reason.
Action	Delete and recreate the deployment candidate.
DEP.0002.0149	Deployment candidate {0} in project {1} is not checkpointed. Use the Deployer command-line interface to create a checkpoint for the deployment candidate. If you want to deploy without creating a checkpoint, use the -force flag.
Explanation	This error is shown when you attempt to deploy without creating a checkpoint from the Deployer command-line interface.
Action	Use the Deployer command-line interface to create a checkpoint for the deployment candidate. If you want to deploy without creating a checkpoint, use the -force flag.
DEP.0002.0150	The WmDeployerResource package is not installed on the target Integration Server. Install the WmDeployerResource package on the target Integration Server from the Deployer user interface on the Integration Server alias page.
Explanation	The WmDeployerResource package is not installed on the target Integration Server.
Action	Install the WmDeployerResource package on the target Integration Server from the Deployer user interface on the Integration Server alias page.
DEP.0002.0158E	Deployer did not save the versions for the aliases {0} because the aliases do not exist. Make sure the alias for which you specified the version is valid.
Explanation	The alias for which you tried to update the version does not exist.
Action	Make sure the alias for which you specified the version is valid.
DEP.0002.0159E	The deployment set contains source servers of different versions. Source servers in a deployment set must be the same version. Remove the source servers with the wrong version from the deployment set or change the versions to match.
Explanation	The source servers in the deployment set are different versions.
Action	Remove the source servers with the wrong version from the deployment set or change the versions to match.
DEP.0002.0160E	The deployment maps contain target servers of different versions. Target servers in deployment maps must be the same version. Remove the target servers with the wrong version from the deployment maps or change the versions to match.
Explanation	The target servers in the deployment maps are different versions.
Action	Remove the target servers with the wrong version from the deployment maps or change the versions to match.

DEP.0002.0162E	Repository name {0} contains illegal characters.
Explanation	The repository name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : \$ / \ \ ` ' ; , ~ + = > < \ "
Action	Remove the invalid characters from the repository alias name.
DEP.0002.0163E	Deployment set name {0} contains illegal characters.
Explanation	The deployment set name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : \$ / \ \ ` ' ; , ~ + = > < \ "
Action	Remove the invalid characters from the deployment set name.
DEP.0002.0164E	Deployment map name {0} contains illegal characters.
Explanation	The deployment map name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : \$ / \ \ ` ' ; , ~ + = > < \ "
Action	Remove the invalid characters from the deployment map name.
DEP.0002.0165E	Deployment candidate name {0} contains illegal characters.
Explanation	The deployment candidate name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : \$ / \ \ ` ' ; , ~ + = > < \ "
Action	Remove the invalid characters from the deployment candidate name.
DEP.0002.0166E	Component {0} not found in composite {1} from repository source {2}.
Explanation	The contents of the repository have been modified.
Action	Run the build script again or recreate the repository.
DEP.0002.0167E	There is an error in deployment candidates(s) {0} from project {1}. See the Integration Server logs for more information.
Explanation	Deployer displays this error for various reasons.
Action	See the Integration Server logs for an explanation of the exception.
DEP.0002.0168E	Cannot save variable substitutions. There are no servers selected.
Explanation	Deployer requires that you select at least one server for variable substitutions.
Action	Select at least one server from the list of selected servers.

DEP.0002.0172W **When adding a new target server to the map, Deployer will remove any checkpoints created for the associated deployment candidates. You must recreate any checkpoints you want to use. Do you want to continue?**

Explanation Adding new target servers to the map will cause Deployer to remove any checkpoints previously created for the deployment candidates associated with this map.

Action If you continue with the change, you must recreate any checkpoints you want to use for the associated deployment candidates.

DEP.0002.0173W **When modifying the deployment set, Deployer will remove any checkpoints created for the associated deployment candidates. You must recreate any checkpoints you want to use. Do you want to continue?**

Explanation Modifying the deployment set will cause Deployer to remove any checkpoints previously created for the deployment candidates associated with this project.

Action If you continue with the change, you must recreate any checkpoints you want to use for the project.

DEP.0002.0180E **Repository {0} is not connected. The specified flat file directory does not exist.**

Explanation The specified repository does not exist.

Action Ensure that the repository exists in the specified location.

DEP.0002.0183W **When modifying the deletion set, Deployer will remove any checkpoints created for the associated deployment candidates. You must recreate any checkpoints you want to use. Do you want to continue?**

Explanation If you modify the deletion set, Deployer will remove any checkpoints previously created for the deployment candidates associated with this project.

Action If you continue with the change, you must recreate any checkpoints you want to use for the project.

DEP.0002.0201E **Checkpoint for Deployment Candidate {0} failed. For more information, see the checkpoint report.**

Explanation Possible causes for this error:

- 1) The project file could not be found in, or loaded from, the build.
- 2) The target file or deployment candidate could not be loaded from disk.
- 3) The user is not authorized to create a checkpoint.
- 4) Another reason shown in the checkpoint report.

Action Verify that the build is available and correct and that there is sufficient disk space and memory. Also review the checkpoint report and verify that the necessary operating system privileges are set and that the user has authorization to create a checkpoint.

DEP.0002.0202W	Checkpoint for deployment candidate {0} completed with warnings. For more information, see the checkpoint report.
Explanation	Deployer encountered a warning while extracting objects from source system.
Action	Review the checkpoint report to determine any further action to take. Most warnings require no action by the user.
DEP.0002.0206E	Checkpoint for deployment candidate {0} failed: {1}
Explanation	Deployer encountered an exception while extracting objects from the source system. The following are possible causes for the exception: <ol style="list-style-type: none"> 1) Deployer could not find project file in, or load it from, the build. 2) Deployer could not load the target file or deployment candidate from disk. 3) The user is not authorized to create a checkpoint. 4) Other reasons as shown in the checkpoint report.
Action	Verify that the build is available and correct, and that there is sufficient disk space and memory. Also review the checkpoint report to verify that the necessary operating system privileges are set and that the user has authorization to create a checkpoint.
DEP.0002.0300E	User is not authorized to create variable substitution file for project {0}.
Explanation	You are not authorized to perform the action of variable substitution for the specified project. You must have map authorization for the project.
Action	Ask an administrator or user that has map authorization for the project to perform this task or have an administrator assign you map authorization.
DEP.0002.0301E	Could not save variable substitution file {0}.
Explanation	Deployer encountered an error writing to disk.
Action	Check your Integration Server's disk space. If you believe there should be sufficient space, try to save again. If saving again is not successful, perform one or both of the following and retry the action: <p>Restart the server.</p> <p>Recreate the variable substitution information.</p>

DEP.0002.0302E	Variable substitution object type {0} is invalid.
Explanation	Deployer attempted to create a variable substitution item that is not valid. This might occur if the service that is attempting to create the variable substitution item is invoked by something other than the Deployer user interface.
Action	Contact Software AG Global Support to report this issue and request a fix.
DEP.0002.0306E	Deployer cannot import the substitute configuration values into the deployment map. The .vs file does not exist.
Explanation	There are no .vs files in the WmDeployer/replicate/inbound folder.
Action	Copy the variable substitution file to the WmDeployer/replicate/inbound folder and then import it into the deployment map.
DEP.0002.0309E	Unable to export variable substitution information.
Explanation	This error occurs when the exported map already exists in the WmDeployer/replicate/inbound folder.
Action	Backup the file to a different location and delete the original. Then export the map again.
DEP.0002.0311E	The Deployer {0} file is not accessible or does not exist.
Explanation	The XML file name you passed for importing the varsub is not present in the WmDeployer/replicate/inbound folder.
Action	Check and correct the file name you passed in the command-line.
DEP.0004.0001E	Version Mismatch Error: The server alias is a different version number than the other source/target servers. Source and target servers must use the same version as the server alias.
Explanation	The versions of the source or target servers are different than the version selected for the alias version.
Action	Remove the aliases with the wrong version from the deployment set or change the version to match the source servers.
DEP.0004.0002W	The target Integration Server is part of a cluster, but is not properly configured to support clustered deployment. See the product documentation for instructions on proper cluster configuration.
Explanation	One of the target Integration Servers is not properly configured for clustering.
Action	See the webMethods Integration Server documentation for a description of the proper configuration settings for clustering.

DEP.0005.0105I	No publishable document types needed to be synchronized in the following package(s): "{0}"
Explanation	The packages with document types are deployed. However, there are no unsynchronized document types.
Action	Make sure that no unsynchronized document types are used for process development.
DEP.0005.0111E	The source user has no username. Deployer cannot deploy an undefined user.
Explanation	This error occurs when Deployer cannot deploy or roll back a target server due to an undefined user.
Action	Verify that the user exists on the source server and that configuration details are correct.
DEP.0005.0113E	The source user "{0}" has a non-ASCII password. Deployer cannot deploy assets to an undefined user.
Explanation	Deployer is attempting to deploy an invalid user.
Action	Verify that the selected user is valid.
DEP.0005.0115E	An error occurred while attempting to deploy user "{0}" with the following error message follows: <p>"{1}"</p>
Explanation	An error occurred while attempting to deploy a user.
Action	Check the Integration Server logs and error messages in the output report for more information.
DEP.0005.0118E	Deployer encountered the following exception while attempting to put package "{0}" into the inbound directory: "{1}"
Explanation	There might be network connectivity problems between Deployer and each target Integration Server. Alternatively, the target Integration Servers might not be currently running.
Action	Verify network connectivity between the Deployer server and each target server. Also, verify that the target Integration Servers are running.
DEP.0005.0131E	Deployment completed with errors. Following is a path to the output report, followed by an error message: "{0}" <p>Error message: "{1}"</p>
Explanation	Deployment completed with errors.
Action	Check the Integration Server logs, as well as error messages in the output report.

DEP.0005.0134E	Deployer encountered an error while synchronizing documents in the following packages: "{0}"
Explanation	This error occurs when a Broker mapped with an Integration Server is unavailable.
Action	Ensure that the mapped JMS Broker is available.
DEP.0005.0156E	Deployer encountered an error during deployment. Deployer did not find package "{0}" in the build zip file "{1}".
Explanation	Deployer invoked the wm.server.util:putPackageFile service and the service returned an error.
Action	See the deployment or simulation report to determine which error putPackageField service returned.
DEP.0005.0157E	Deployer encountered an error during deployment. "{0}" package was not found in the build zip file: "{1}".
Explanation	The specified package was not found in the build. Typically, this indicates that the deployment set is not current with the build.
Action	Re-create your deployment set and build files.
DEP.0005.0160E	While attempting to install package "{0}" an exception with the following error message occurred: <p>"{1}"</p>
Explanation	Deployer invoked the pub.packages:installPackage service, and the service returned an error.
Action	Verify network connectivity between the Deployer server and each target server. Verify that the target Integration Servers are running. For more information about the error returned by the installPackage service, see the deployment or simulation report. For more information about the installPackage service, see Integration Server Built-In Services Reference.
DEP.0005.0161E	The number of bytes read from package "{0}" was not correct.
Explanation	An I/O exception occurred while reading the specified package. As a result, all data from the package could not be read. This exception can occur for the following reasons: <ul style="list-style-type: none"> - The I/O operation failed or was interrupted while accessing the build file. - A security violation has occurred, which typically means that the user running Deployer does not have correct privileges to access the files.
Action	Verify that the file system and the build file that contains the source package are not corrupt. Verify that the user attempting this action has the proper authority to read files on the file system. You might need to re-create the build.

DEP.0005.0164E	The scheduled service type "{0}" for service name "{1}" is unknown and could not be processed.
Explanation	Your version of Deployer is out of date.
Action	Ensure that you have the latest version of the WmDeployer package.
DEP.0005.0170E	Deployer encountered the following error while retrieving the scheduled service with service name "{0}" from target "{1}": "{2}".
Explanation	This error occurs when Deployer fails to get details for a scheduled service for the variable substitution.
Action	Verify that the scheduled service exists under the specified name on the target server.
DEP.0005.0187E	Deployer encountered the following exception while performing a remote invoke of the service "{0}": "{1}"
Explanation	This error occurs when Deployer cannot invoke a service on a remote server, which indicates that the remote server might be offline.
Action	Verify that the remote server is running and available.
DEP.0005.0190E	Deployer encountered the following error while attempting to deploy Group: "{0}": "{1}"
Explanation	An error occurred while attempting to deploy the group.
Action	Recreate the build and deploy the group again.
DEP.0005.0193E	Deployer encountered the following error while attempting to deploy ACL "{0}": "{1}"
Explanation	An error occurred while attempting to deploy an ACL.
Action	Check Integration Server logs and error messages in the Deployment report.
DEP.0005.0197E	Deployer encountered the following error while attempting to deploy Port "{0}" associated with package "{1}": "{2}".
Explanation	An error occurred while attempting to deploy a port associated with a package.
Action	Check for error messages in the output report and Integration Server logs. Verify that the specified port is available on the target server. Recreate the build if problems persist.

DEP.0005.0199E	Deployment failed.
Explanation	The deployment failed.
Action	Review the deployment report and Integration Server logs to determine the cause of the failure, and take the appropriate action.
DEP.0005.0204E	Deployer encountered the following Trading Networks error while attempting to import "{0}" with name "{1}": "{2}", message: "{3}"
Explanation	An error occurred attempting to import one of the following Trading Network object types: Document Attributes, Document Types, Field Groups, ID Types, Contact Types, Binary Types, or Profile Groups. Possible causes include: <ul style="list-style-type: none"> - A network connection error occurred between the Deployer server and the target Integration Server. - The target Integration Server is not running. - The target WmTN package on the target Integration Server is not loaded or enabled. - There could be problems with the Trading Networks object type being imported to the target.
Action	Verify the following: <ul style="list-style-type: none"> - There are no network connectivity errors between the Deployer server and each target Integration Server. - All target Integration Servers are running. - The WmTN package on each target Integration Server is loaded and enabled. - The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible Trading Networks object types.
DEP.0005.0231	There are no required patches specified for the target Integration Server.
Explanation	This message occurs when a user deploys unrequired patches into a target.
Action	See the patch details for more information.
DEP.0005.0234E	Deployer encountered the following error while pausing the listener "{0}" associated with package "{1}": "{2}"
Explanation	Could not pause the listener associated with the package.
Action	Check the Integration Server logs and error messages in the output report for more information.

DEP.0005.0235E	Deployer encountered an error while disabling of port "{0}" associated with package "{1}".
Explanation	An exception occurred while disabling the port associated with the package.
Action	Check the Integration Server logs and error messages in the output report for more information.
DEP.0005.0236E	Deployer encountered an error while enabling the listener "{0}" associated with package "{1}": "{2}"
Explanation	Deployer could not enable the specified listener.
Action	See the webMethods Integration Server documentation for specific instructions on how to enable a listener.
DEP.0005.0240E	Deployer encountered the following error while suspending the triggers: "{0}"
Explanation	Deployer could not suspend the triggers on the target Integration Server. Deployer attempts to suspend all triggers by setting the maximum percentage of document retrieval threads and the maximum percentage of trigger execution threads to zero.
Action	Verify network connectivity between Deployer and each target Integration Server. Also, verify that the target Integration Servers are running. For more information about the configuration settings for document retrieval threads and trigger execution threads, see information about configuring the server in the webMethods Integration Server documentation.
DEP.0005.0242E	Could not resume the Integration Server triggers. Error message follows: "{0}"
Explanation	Deployer could not resume the triggers on the target Integration Server. Deployer attempts to resume all triggers by resetting the maximum percentage of document retrieval threads and the maximum percentage of trigger execution threads to the values they had before Deployer suspended the triggers.
Action	Verify network connectivity between the Deployer server and each target Integration Server. Verify that the target Integration Servers are running. For more information about configuration settings for document retrieval threads and trigger execution threads, see information about configuring the server in the webMethods Integration Server documentation.
DEP.0005.0243E	Deployer did not deploy deployment set "{0}" because it contains the following unsatisfied dependencies: "{1}"
Explanation	The dependencies required by the specified deployment set are missing on the target system.
Action	Either install the necessary components on the target system, or change the Deployer project so that it no longer requires the missing dependencies.

DEP.0005.0244E	Deployer encountered the following exception while checking dependencies on target "{0}" for deployment set "{1}": "{2}"
Explanation	An exception occurred while checking dependencies for the deployment set at the target.
Action	Check Integration Server logs and error messages in the output report for exception details.
DEP.0005.0250E	Simulation failed.
Explanation	The deployment simulation failed.
Action	Refer to the simulation report and Integration Server logs to determine the cause of the failure and take the appropriate action.
DEP.0005.0256E	There are no targets mapped for the current deployment set.
Explanation	There are no valid target servers mapped for the deployment set.
Action	Verify that the specified target servers are mapped appropriately for the current deployment set.
DEP.0005.0257E	Deployer cannot deploy the deployment set because there are no source servers specified.
Explanation	There are no source servers mapped for the deployment set to define assets for deployment.
Action	Verify that source servers are defined appropriately for assets to be deployed.
DEP.0005.0263E	The following Trading Networks error occurred while attempting to import processing rules: class: "{0}", message: "{1}"
Explanation	An error occurred when attempting to import processing rules into Trading Networks. Possible causes include: <ul style="list-style-type: none"> - A network connection error between the Deployer server and the target Integration Server running Trading Networks. - The target Integration Server is not running. - The WmTN package is not loaded or enabled on the target Integration Server. - The Trading Networks object type being imported to the target might be in error.
Action	Verify the following: <ul style="list-style-type: none"> - There are no network connectivity errors between the Deployer server and each target Integration Server. - All target Integration Servers are running. - The WmTN package on each target Integration Server is loaded and enabled.

- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible processing rules.

DEP.0005.0265E **Deployer encountered the following Trading Networks error while attempting to import "{0}" with a group code "{1}" and name "{2}": class: "{3}", message: "{4}"**

Explanation An error occurred when attempting to import field groups into Trading Networks. Possible causes include:

- An error in the network connection between the Deployer server and the target Integration Server running Trading Networks.
- The target Integration Server is not running.
- The WmTN package is not loaded or enabled on the target Integration Server.
- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.
- All target Integration Servers are running.
- The WmTN package on each target Integration Server is loaded and enabled.
- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible field groups.

DEP.0005.0266E **Deployer encountered the following Trading Networks error while attempting to import field definitions: class: "{0}", message: "{1}"**

Explanation An error occurred when attempting to import field definitions into Trading Networks. Possible causes include:

- An error in the network connection between the Deployer server and the target Integration Server running Trading Networks.
- The target Integration Server is not running.
- The WmTN package is not loaded or enabled on the target Integration Server.
- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.
- All target Integration Servers are running.
- The WmTN package on each target Integration Server is loaded and enabled.

- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible field definitions.

DEP.0005.0270E **Deployer encountered the following Trading Networks error while attempting to import partner profiles: class: "{0}", message: "{1}"**

Explanation An error occurred when attempting to import partner profiles into Trading Networks. Possible causes include:

- A network connection error between the Deployer server and the target Integration Server running Trading Networks.
- The target Integration Server is not running.
- The WmTN package is not loaded or enabled on the target Integration Server.
- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.
- All target Integration Servers are running.
- The WmTN package on each target Integration Server is loaded and enabled.
- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible partner profiles.

DEP.0005.0274E **Deployer encountered the following Trading Networks error while attempting to import trading partner agreements: class: "{0}", message: "{1}"**

Explanation An error occurred when attempting to import trading partner agreements (TPAs) into Trading Networks. Possible causes include:

- A network connection error between the Deployer server and the target Integration Server running Trading Networks.
- The target Integration Server is not running.
- The WmTN package is not loaded and/or enabled on the target Integration Server.
- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.
- All target Integration Servers are running.
- The WmTN package on each target Integration Server is loaded and enabled.

- The TN object type is allowed. See the webMethods Trading Networks documentation for details about permissible trading partner agreements (TPAs).

DEP.0005.0277E **Deployer encountered an error while attempting to import "{0}" with a type code "{1}" and a name "{2}". The following is the error information from Trading Networks: class: "{3}", message: "{4}"**

Explanation An error occurred when attempting to import external ID types, contact types, or binary types into Trading Networks. Possible causes include:

- A network connection error between the Deployer server and the target Integration Server running Trading Networks.
- The target Integration Server is not running.
- The WmTN package is not loaded or enabled on the target Integration Server.
- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.
- All target Integration Servers are running.
- The WmTN package on each target Integration Server is loaded and enabled.
- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible external ID types, contact types, and binary types.

DEP.0005.0280E **Triggers were not suspended prior to package deployment. Failure to suspend a trigger during deployment could cause problems on the target server.**

Explanation Triggers were not suspended prior to package deployment.

Action Not suspending a trigger during deployment can cause problems on the target. Check the Integration Server logs for more information.

DEP.0005.0282E **Scheduled services were not suspended prior to deployment. Failure to suspend scheduled services during deployment could cause problems on the target server.**

Explanation Scheduled services were not suspended prior to deployment. Failure to suspend scheduled services during deployment can cause problems at the target.

Action Check the Integration Server logs and error messages in the output report for more information.

DEP.0005.0284E	Scheduled services were not started after deployment.
Explanation	Scheduled services were not started after deployment. There might be an issue with a target server.
Action	For more information, check the Integration Server logs and error messages in the output report.
DEP.0005.0286E	Listeners were not suspended prior to deployment. Failure to suspend listeners during deployment could cause problems on the target server.
Explanation	Listeners were not suspended prior to deployment. Failure to suspend listeners during deployment could cause problems on the target server.
Action	Check the Integration Server logs for errors in suspending the listeners.
DEP.0005.0288E	Listeners were not started after deployment.
Explanation	Listeners were not started after deployment. It happens when the ports are disabled or if they will be used for the first time.
Action	Check the Integration Server logs and error messages in the output report.
DEP.0005.0296E	Deployer did not deploy the {0}, which is required for source package "{1}" and it does not already exist at the target. Although the source package would be deployed to the target, some services in that package will not run correctly until that ACL is created at the target.
Explanation	The Read, Write, List, or Execute ACLs required for the deployed package to run correctly are not being deployed to the target Integration Server, and that ACL does not already exist on the target Integration Server. Typically, this indicates that the ACLs associated with the package were not extracted.
Action	Repeat the extraction step using Deployer to ensure that all ACLs are included.
DEP.0005.0297E	Deployer did not deploy the {0}, which is required for source package "{1}" and it does not already exist on the target. Some services in that source package will not run correctly until that ACL is created at the target.
Explanation	The Read, Write, List, or Execute ACLs that are necessary for the deployed package to run correctly are not being deployed to the target Integration Server, and the specified ACL does not already exist on the target Integration Server. Typically, this problem indicates that the ACLs associated with the package were not extracted.
Action	Perform the extraction step again using Deployer to ensure that all ACLs are included.

DEP.0005.0298E	Deployer encountered the following exception while invoking of the service "{0}": "{1}"
Explanation	This exception occurs when Deployer invokes a service on a remote server.
Action	Verify that the source or target server is available.
DEP.0005.0302E	Deployer encountered the following exception while creating the directory "{0}": "{1}"
Explanation	An exception occurred while attempting to create a directory.
Action	Ensure that the appropriate write permissions exist to allow for the creation of the new directory and that adequate free space is available.
DEP.0005.0303E	Deployer encountered an exception while creating one of the temporary jar files in "{0}": "{1}"
Explanation	An exception occurred while attempting to create one of the temporary jar files.
Action	Ensure that the appropriate write permissions exist for the new file location and that adequate free space is available.
DEP.0005.0304E	Target Server {0} is unavailable.
Explanation	Deployer could not connect to the specified target server.
Action	Verify the following: <ul style="list-style-type: none"> - Network connectivity between Deployer and each target Integration Server. - The target Integration Servers are running. - The target Integration Server alias is defined on the Deployer host server.
DEP.0005.0305E	An exception occurred while getting a Trading Networks docType object. This is most likely caused by a user-defined extension to the Trading Networks type BizDocType. Copy the jar files containing the extensions from the webM_install_dir/IntegrationServer/packages/WmTN/code/jars directory into the WmDeployer/code/jars directory.
Explanation	There is a user-defined extension to a Trading Networks document type and Deployer does not have access to the associated jar files.
Action	To ensure Deployer has access to the associated jar files, copy the jar files containing the extensions from the webM_install_dir/IntegrationServer/packages/WmTN/code/jars directory into the WmDeployer/code/jars directory.

DEP.0005.0306E **An error occurred while attempting to import extended field definitions; error information from Trading Networks: class: "{0}", message: "{1}"**

Explanation An error occurred when attempting to import extended field definitions into Trading Networks. Possible causes include:

- An error in the network connection between the Deployer server and the target Integration Server that is running Trading Networks.
- The target Integration Server is not running.
- The WmTN package is not loaded and/or enabled on the target Integration Server.
- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.
- All target Integration Servers are running.
- The WmTN package on each target Integration Server is loaded and enabled.
- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible extended field definitions.

DEP.0005.0307E **Deployer encountered the following Trading Networks error while attempting to import security data for profile: "{0}": class: "{1}", message: "{2}"**

Explanation Deployer encountered an error occurred while attempting to import the security data for the specified profile into Trading Networks. Possible causes include:

- A network connection error between the Deployer server and the target Integration Server running Trading Networks.
- The target Integration Server is not running.
- The WmTN package is not loaded or enabled on the target Integration Server.
- The Trading Networks object type being imported to the target might be in error.

Action Verify the following:

- There are no network connectivity errors between the Deployer server and each target Integration Server.
- All target Integration Servers are running.
- The WmTN package on each target Integration Server is loaded and enabled.
- The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible Trading Networks Security Data.

DEP.0005.0308E	An error occurred while attempting to import queues: class: "{0}", message: "{1}"
Explanation	<p>An error occurred when attempting to import the public queues into Trading Networks. Possible causes include:</p> <ul style="list-style-type: none"> - A network connection error between the Deployer server and the target Integration Server running Trading Networks. - The target Integration Server is not running. - The WmTN package is not loaded and/or enabled on the target Integration Server. - The Trading Networks object type being imported to the target might be in error.
Action	<p>Verify the following:</p> <ul style="list-style-type: none"> - There are no network connectivity errors between the Deployer server and each target Integration Server. - All target Integration Servers are running. - The WmTN package on each target Integration Server is loaded and enabled. - The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible public queues.
DEP.0005.0309E	An error occurred while attempting to import profile group "{0}" with value "{1}". class: "{2}", message: "{3}"
Explanation	<p>An error occurred when attempting to import the profile groups into Trading Networks. Possible causes include:</p> <ul style="list-style-type: none"> - A network connection error between the Deployer server and the target Integration Server running Trading Networks. - The target Integration Server is not running. - The WmTN package is not loaded and/or enabled on the target Integration Server. - The Trading Networks object type being imported to the target might be in error.
Action	<p>Verify the following:</p> <ul style="list-style-type: none"> - There are no network connectivity errors between the Deployer server and each target Integration Server. - All target Integration Servers are running. - The WmTN package on each target Integration Server is loaded and enabled. - The Trading Networks object type is allowed. See the webMethods Trading Networks documentation for details about permissible profile groups.

DEP.0005.0326E **An error occurred while deploying package "{0}". Item "{1}" could not be loaded because of reason "{2}". The package may have partially loaded; please check your target server.**

Explanation The specified package did not load due to the reason returned from the target Integration Server.

Action See the webMethods Integration Server documentation for the specific requirements for loading a package.

DEP.0005.0328E **The JVM "{0}" on the target server is older than the "{1}" JVM recommended on the source for package "{2}".**

Explanation The JVM version running on the target is older than the minimum JVM version property specified by the source.

Action Change the minimum JVM property for the package being deployed and redeploy the package.

DEP.0005.0329E **The "{0}" target JVM is older than the JVM recommended "{1}" on the source for package "{2}".**

Explanation The JVM version running on the target is older than the minimum JVM version property required by the source.

Action Change the minimum JVM property for the package being deployed, and then deploy again.

DEP.0005.0330E **The target package version is null.**

Explanation For partial deployment, Deployer requires that the package is present on the target server and that version of the package is not null and matches that of the source server.

Action Verify that the package version defined on the target server is appropriate for partial package deployment.

DEP.0005.0334E **Source package is of type Patch and package does not exist on target. The package: "{0}" will not be deployed. Re-define package to Full to deploy the package on target**

Explanation This message indicates that the target partial mode package is undefined.

Action Verify that the specified package exists on the target server and that it is valid for partial package deployment.

DEP.0005.0337E	An error occurred while deploying package: "{0}"
Explanation	Deployer invoked the pub.packages:installPackage service and the installPackage service returned an error.
Action	For more information about the error that the installPackage service returned, see the deployment or simulation report. For more information about the installPackage service and the requirements for installing packages, see the Integration Server Built-In Services Reference.
DEP.0005.0338E	Deployer issued the following exception while attempting to activate the package: "{0}"
Explanation	Deployer invoked the pub.packages:activatePackage service, and the activatePackage service returned an error.
Action	Verify the network connectivity between the Deployer server and each target Integration Server. Also, verify that the target Integration Servers are up and running. For more information about the error that the activatePackage service returned, see the deploy or simulation report. For more information about the activatePackage service, see the documentation for webMethods Integration Server documentation.
DEP.0005.0352E	The package name "{0}" contains the invalid "{1}" character. For more information about illegal characters, see the webMethods Integration Server documentation.
Explanation	The package name contains illegal characters.
Action	See the webMethods Integration Server documentation for information about how to name a package.
DEP.0005.0353E	"{0}" is an invalid value for the Cleanup File Age parameter. Valid values are 1-9999.
Explanation	The value specified for the Cleanup File Age parameter is invalid.
Action	Specify a valid value between 1 and 9999 for the Cleanup File Age parameter.
DEP.0005.0354E	Invalid File Age parameter "{0}". Valid values are 0-9999.
Explanation	The value specified for the File Age parameter is invalid.
Action	Specify a value between 0 and 9999 for the File Age parameter.
DEP.0005.0355E	The Allow Recursive Polling parameter "{0}" is invalid. Valid values are "yes" and "no".
Explanation	The specified Allow Recursive Polling parameter is neither "yes" nor "no".
Action	Specify either "yes" or "no" for the Allow Recursive Polling parameter.

DEP.0005.0356E **The Run As User value "{0}" contains invalid character "{1}". For more information about illegal characters, see the webMethods Integration Server documentation.**

Explanation The Run As User value contains illegal characters.

Action For more information about illegal characters, see the webMethods Integration Server documentation.

DEP.0005.0357E **No value was provided for the required Run services as user parameter.**

Explanation The Run services as user parameter value is not specified.

Action Specify a value for the Run services as user parameter. For more information, see the webMethods Integration Server documentation.

DEP.0005.0358E **"{0}" is an invalid value for the File Polling Interval parameter. Valid values are 1-9999.**

Explanation The value specified for the File Polling Interval parameter is invalid.

Action Specify a valid value between 1 and 9999 for the File Polling Interval parameter.

DEP.0005.0359E **No value is specified for the File Polling Interval parameter. Valid values are 1-9999.**

Explanation No value is specified for the File Polling Interval parameter.

Action Specify a value between 1 through 9999 for the File Polling Interval parameter.

DEP.0005.0360E **"{0}" is an invalid value for the Cleanup Interval parameter. Valid values are 1-9999.**

Explanation The value specified for the Cleanup Interval parameter is invalid.

Action Specify a value between 1 and 9999 for the Cleanup Interval parameter.

DEP.0005.0361E **"{0}" is an invalid value for the Maximum Number of Invocation Threads parameter. Valid values are 1-10.**

Explanation The value specified for the Maximum Number of Invocation Threads parameter is invalid.

Action Specify a value between 1 and 10 for the Maximum Number of Invocation Threads parameter.

DEP.0005.0362E **No value provided for the required Maximum Number of Invocation Threads parameter.**

Explanation No value was specified for the Maximum Number of Invocation Threads parameter.

Action Specify a value between 1 and 10 for the Maximum Number of Invocation Threads parameter.

DEP.0005.0363E	"{0}" is an invalid value for the Port parameter. The Port parameter requires an integer value.
Explanation	The value specified for the Port parameter is not an integer.
Action	Specify a valid value for the Port parameter.
DEP.0005.0364E	"{0}" is an invalid value for the Port parameter. The value for the Port parameter must be greater than -1.
Explanation	The value for the Port parameter is not valid.
Action	Specify a valid value for the Port parameter.
DEP.0005.0365E	No value was specified for the required Port parameter. Specify a value for the Port parameter.
Explanation	No value was specified for the Port parameter.
Action	Specify a valid integer type value that is greater than -1 for the Port parameter.
DEP.0005.0366E	The Client Authentication value: "{0}" is invalid. Valid values are 'true' and 'false'.
Explanation	The specified Client Authentication value is neither "true" nor "false".
Action	Specify either "true" or "false" for the Client Authentication value.
DEP.0005.0367E	The Host parameter requires a value.
Explanation	The value for the Host parameter was not specified.
Action	Specify a value for the Host parameter.
DEP.0005.0368E	"{0}" is an invalid value for the Type parameter. Valid values are "pop3" and "imap".
Explanation	The value specified for the Type parameter is invalid.
Action	Specify either "pop3" or "imap" for the Type parameter.
DEP.0005.0369E	Specify a value for the Type parameter. Valid values are "pop3" and "imap".
Explanation	No value is specified for the required Port parameter.
Action	Specify either "pop3" or "imap" for the Port parameter.

- DEP.0005.0370E** **The user name value: "{0}" contains an invalid character: "{1}". Refer to the Administering Integration Server guide for listed illegal characters.**
- Explanation** The user name value contains illegal characters.
- Action** For information about legal characters for user accounts, see the Administering Integration Server guide.
-
- DEP.0005.0371E** **No value provided for user name. This field is mandatory.**
- Explanation** No value is provided for user name.
- Action** Specify a value for the user name. For information about the legal characters for user accounts, see the Administering Integration Server guide.
-
- DEP.0005.0372E** **Invalid value provided for the "Log out after each mail check" parameter: "{0}". Valid values are "yes" and "no".**
- Explanation** The specified value for the "Log out after each mail check" parameter is neither "yes" nor "no".
- Action** Specify a valid value for the "Log out after each mail check" parameter. Valid values are "yes" and "no".
-
- DEP.0005.0373E** **The Authorize value "{0}" is invalid. Valid values are Yes and No.**
- Explanation** The specified Authorize value is neither Yes and No.
- Action** Specify either Yes or No for the Authorize value.
-
- DEP.0005.0374E** **"{0}" is an invalid value for the Time Interval parameter. Valid values are 1-9999.**
- Explanation** The value specified for the Time Interval parameter is invalid.
- Action** Specify a valid value between 1 and 9999 for the Time Interval parameter.
-
- DEP.0005.0375E** **Specify a value for the required Time Interval parameter. Valid values are 1-9999.**
- Explanation** The required Time Interval parameter has not been specified.
- Action** Specify a value from 1 through 9999 for the Time Interval parameter.
-
- DEP.0005.0376E** **The Reply value: "{0}" is invalid. Valid values are "yes" and "no".**
- Explanation** The specified Reply value is neither "yes" nor "no".
- Action** Specify either "yes" or "no" for the Reply value.

DEP.0005.0377E	The Send reply e-mail on error value "{0}" is invalid. Valid values are Yes and No.
Explanation	The Send reply e-mail on error value is set to a value other than Yes or No.
Action	Specify either Yes or No for the Send reply e-mail on error value.
DEP.0005.0378E	The Remove value: "{0}" is invalid. Valid values are "yes" and "no".
Explanation	The specified Remove value is neither "yes" nor "no".
Action	Specify either "yes" or "no" for the Remove value.
DEP.0005.0379E	"{0}" is an invalid value for the Delete invalid messages parameter. Valid values are Yes and No.
Explanation	The value specified for the Delete invalid messages parameter is invalid.
Action	Specify a valid value of Yes or No for the Delete invalid messages parameter.
DEP.0005.0380E	The Multithread processing value "{0}" is invalid. Valid values are Yes and No.
Explanation	The Multithread processing is set to a value other than Yes or No.
Action	Specify either Yes or No for the Multithread processing value.
DEP.0005.0381E	"{0}" is an invalid value for the Number of threads if multithreading is turned on parameter. Valid values are 1-99.
Explanation	The value specified for the Number of threads if multithreading is turned on field is invalid.
Action	Specify a value between 1 and 99 for the Number of threads if multithreading is turned on field.
DEP.0005.0382E	Enter a value for the Number of threads if multithreading is turned on parameter. Valid values are 1-99.
Explanation	There is no value set for the Number of threads if multithreading is turned on parameter.
Action	Specify a value between 1 and 99 for the Number of threads if multithreading is turned on parameter.
DEP.0005.0383E	The Break Mmsg value: "{0}" is invalid. Valid values are "yes" and "no".
Explanation	The specified Break Mmsg value is neither "yes" nor "no".
Action	Specify either "yes" or "no" for the Break Mmsg value.

DEP.0005.0384E	The Include Headers value: "{0}" is invalid. Valid values are "yes" and "no".
Explanation	The specified Include Headers value is neither "yes" nor "no".
Action	Specify either "yes" or "no" for the Include Headers value.
DEP.0005.0421E	Unknown system type: "{0}".
Explanation	The source system type is unknown, which indicates that your version of Deployer is out of date.
Action	Ensure that you have the latest version of the WmDeployer package.
DEP.0005.0422E	Unable to invoke "{1}" because the connection object is of an unknown type. Its value is: "{0}".
Explanation	The system type object is set to a value that is not recognized. This issue might occur if the user manually edits the project XML file.
Action	Rebuild the project file and map the steps again. Do not manually edit the project file.
DEP.0005.0423E	Deployer encountered an exception while writing the bytes for package "{0}" to the output stream in preparation for deployment to the target "{1}".
Explanation	An exception occurred when Deployer tried to write the package data to disk. That exception can occur for the following reasons: - The I/O operation failed or was interrupted while accessing the build file. - A security violation occurred, which typically means that the user running Deployer lacks the correct privileges to access the files.
Action	Verify that the file system is not corrupt and that adequate disk space is available for writing new files. Also verify that the user has appropriate privileges to write files on the file system.
DEP.0005.0430	There is no logical server defined for the specified Server ID.
Explanation	Either no logical server is defined in the WmDesigner service on the target Integration Server server, or the server is not up and running and available for process model deployment.
Action	Verify that the logical server is defined in the WmDesigner service on the target Integration Server server and that the server is available.

DEP.0005.0431	. The most-likely fix for that is to use webMethods Administrator on your target server to define a logical server with the name: "{0}".
Explanation	This problem occurs when the logical server is not defined in the WmDesigner service on the target Integration Server server for process model deployment.
Action	Verify that the logical server is defined in the WmDesigner service on the target Integration Server server.
DEP.0005.0433E	Cannot associate {0} ACL "{1}", with "{2}" because user "{3}" is not in the Write ACL: "{4}" .
Explanation	Cannot associate the ACL because the user is not a member of the Write ACL.
Action	Add the user to the Write ACL.
DEP.0005.0435E	Deployer cannot suspend selected triggers. You can suspend selected triggers only with Integration Server 6.0.1 Fix 144, Integration Server 6.1 Fix 22, or Integration Server 6.5 and later. Alternatively, you can suspend all triggers in the project properties.
Explanation	Selected trigger suspension is supported only in the following releases: <ul style="list-style-type: none"> - Integration Server 6.0.1 Fix 144 - Integration Server 6.1 Fix 22. - Integration Server 6.5 and later
Action	You can suspend all triggers in the project properties.
DEP.0005.0447I	The "{0}" file was deployed.
Explanation	This message occurs when a user deploys files.
Action	Check whether the files are deployed or not.
DEP.0005.0449E	Deployer could not suspend the adapter notifications. Adapter suspension is supported only with Integration Server 6.5 and later.
Explanation	Adapter notifications could not be suspended because this functionality is only supported for Integration Server 6.5 and later.
Action	None.

DEP.0005.0457E	Suspend adapter notifications prior to deploying packages. Failure to suspend adapter notifications during deployment can cause problems on the target.
Explanation	Adapter notifications were not suspended prior to package deployment.
Action	Check the Integration Server logs and error messages in the output report for more information.
DEP.0005.0458E	Deployer suspended adapter notification "{0}" but could not verify status.
Explanation	Deployer suspended the adapter notification but was unable to verify its status after the suspension.
Action	For more information, check the Integration Server logs and error messages in the output report.
DEP.0005.0459E	Deployer resumed adapter notification "{0}" but could not verify status.
Explanation	Deployer resumed adapter notification but could not verify the status.
Action	Check the Integration Server logs and error messages in the output report for more information.
DEP.0005.0460E	Suspend trigger "{0}" failed: {1}
Explanation	Deployer could not suspend the trigger.
Action	Check the Integration Server logs and error messages in the output report for more information.
DEP.0005.0461E	Suspend adapter notification "{0}" failed: {1}
Explanation	Suspension of adapter notification failed.
Action	Recreate the build and deploy again. If the problem persists, check the target server adapter settings.
DEP.0005.0477E	The source group has no name. Deployer cannot deploy an undefined group.
Explanation	This message occurs when Deployer attempts to roll back an undefined group.
Action	Verify that the specified group is defined on the source server.
DEP.0005.0482E	The source ACL has no name. Deployer cannot deploy an undefined ACL.
Explanation	Deployer attempted to roll back an undefined ACL.
Action	Verify that the specified ACL exists on the source server.

DEP.0005.0492	The Extended Setting in the source has no name. Deployer cannot deploy an undefined Extended Setting.
Explanation	This message occurs when Deployer attempts to roll back of an undefined Extended Setting.
Action	Verify that the specified Extended Setting exists on the target server.
DEP.0005.0496E	The Trading Networks instance is not currently available on the target server "{0}". Please check your network connection and verify that the Trading Networks instance is installed, configured, and running.
Explanation	The target Trading Networks server is not accessible due to a network connection problem.
Action	Check your network connection. Verify that the Trading Networks instance is installed, configured, and running.
DEP.0005.0501E	Deployer issued the following exception after it failed to load the variable substitution object {0}.
Explanation	The map file: <srcDir>\packages\WinDeploy\src\projName\src\mapName<depName>_agf\srcName.xml is either corrupt or not present.
Action	Verify that the map file exists. If it does, you might need to use Deployer to recreate your map and variable substitution actions.
DEP.0005.0505E	ERROR: Failed to generate IData for Port. The following exception was thrown: {0}
Explanation	The port type is unknown. This indicates that your version of Deployer is out of date.
Action	See the error log of the Deployer server.
DEP.0005.0600E	The target server is Integration Server {0}, which does not support this feature. Deployer cannot update the following adapter connections with the variable substitution values: {1}
Explanation	The version of the target Integration Server is a version prior to version 6.1. Versions of the Integration Server prior to 6.1 do not support the APIs that are required to update the adapter connections.
Action	Either upgrade the target Integration Server to version 6.1 or later, or manually update the Adapter connections on the target system.

DEP.0005.0615E	Deployer encountered an error while retrieving current values for adapter connection "{0}".
Explanation	Deployer invoked the <code>wm.art.admin.connection:getResourceConfiguration</code> service but was unable to get current values for the adapter connection in the vars sub page.
Action	The <code>wm.art.admin.connection:getResourceConfiguration</code> service might not be operational or the WmART package is not installed on the target machine. Verify that both the service and the package are installed and operational.
DEP.0005.0706	Rollback failed. For more information, see the rollback report and the Integration Server log.
Explanation	This message occurs when a rollback operation fails.
Action	Review the rollback report and take appropriate action.
DEP.0005.0850E	Deployer issued the following error while rolling back the contact type: "{0}"
Explanation	Deployer issued an exception while rolling back the contact type.
Action	Contact the Trading Networks target administrator.
DEP.0005.0851E	Deployer issued the following exception while deleting the document type during rollback: "{0}"
Explanation	An exception occurred while deleting the document type.
Action	Contact the administrator of the target Trading Networks system for assistance.
DEP.0005.0852E	Deployer issued the following exception while deleting the field group during rollback: "{0}"
Explanation	An exception occurred while deleting the field group.
Action	Contact the administrator of the target server for assistance.
DEP.0005.0854E	Deployer issued the following exception while deleting the external ID type during rollback: "{0}".
Explanation	An exception occurred while deleting the external ID type during rollback.
Action	Verify that target server is running, then try the deleting the external ID type again.

DEP.0005.0856E	Deployer issued the following exception while deleting the processing rule during rollback: "{0}"
Explanation	An exception occurred while deleting the processing rule.
Action	Contact the administrator of the target server for assistance.
DEP.0005.0858E	Deployer issued the following exception while deleting the profile during rollback: "{0}"
Explanation	An exception occurred while deleting the profile.
Action	Verify that the target server is running. Then try the deletion again.
DEP.0005.0859E	Deployer could not suspend the "{0}" scheduled service type with service name "{1}" because it was deployed to a clustered Integration Server.
Explanation	The service was deployed to a clustered Integration Server and could not be suspended.
Action	Suspend the service manually at each target.
DEP.0005.0860E	Deployer could not resume the scheduled service type "{0}" with service name "{1}". The service was deployed to a clustered Integration Server and could not be resumed. You must resume the service manually at each target.
Explanation	The service was deployed to a clustered Integration Server and could not be resumed.
Action	Resume the service manually at each target.
DEP.0005.0861E	Scheduled services are being deployed to a clustered Integration Server and cannot be started after deployment.
Explanation	Scheduled services cannot be started on the clustered target.
Action	Start the services manually on each clustered target.
DEP.0005.0862E	Scheduled services have been deployed to a clustered Integration Server and were not suspended after deployment. If suspension is required, then do so manually at each target.
Explanation	Scheduled services could not be suspended at the clustered target after deployment
Action	Suspend the services manually at each target.

DEP.0005.0864E	Deployer requires that scheduled services be updated at a clustered Integration Server, but this is not supported with this release. You can update the scheduled services by deploying them to each of the individual Integration Servers in the cluster.
Explanation	This deployment candidate requires that scheduled services be updated at a clustered Integration Server, which is not supported with this release.
Action	Update the services by deploying to each of the individual Integration Servers in the cluster.
DEP.0005.0869E	The deployment failed and Deployer is performing an automatic rollback. Please see the separate rollback report for more information about the failed deployment.
Explanation	This message occurs when a deployment fails and an automatic rollback occurs.
Action	Please see the Rollback report and take appropriate action.
DEP.0005.1003E	An IO exception occurred while attempting to access: "{0}". Exception details follow: "{1}".
Explanation	An exception occurred when Deployer tried to create, write data to, or save a file. This exception can occur for the following reasons: <ul style="list-style-type: none"> - The I/O operation failed or was interrupted while accessing the build file. - A security violation has occurred, which typically means that the user running Deployer lacks appropriate privileges to access the files.
Action	Verify that the file system is not corrupt and that adequate disk space is available for creating, writing, and/or saving new files. Also verify that the user has proper privileges to create, write, and save files on the file system.
DEP.0005.1004E	An exception occurred while attempting to access "{0}". Exception details follow: "{1}".
Explanation	An exception occurred when Deployer tried to access (that is, create, save, read, or load) the indicated <object>, where <object> is one of the following: checkpoint, deployment, build, deployReport, targetFileName, or targetServer. Possible causes of the exception include the following: <ul style="list-style-type: none"> - The deployment, reportFiles, or targetFile Object could not be loaded from the file system. - An I/O operation failed or was interrupted while accessing the build or checkpoint file. - A security violation has occurred, which typically means that the user running Deployer does not have privileges to access files necessary to perform the deploy operation. - A target Integration Server Adapter and/or Trigger could not be suspended/resumed.

	<ul style="list-style-type: none"> - A variable substitution failed. - Deployer could not obtain a connection to a target server.
Action	<p>Verify the following:</p> <ul style="list-style-type: none"> - The file system is not corrupt. - Adequate disk space is available for creating and/or saving new files. - The user attempting this action has the proper authority to create and save files on the file system. - The target server is running, and is reachable on the network.
DEP.0005.1005E	You are not authorized to deploy the "{0}" project.
Explanation	The user does not have the authorization to deploy the specified project.
Action	Ask an administrator or user that has deploy authorization to perform the action for you. Alternatively, have an administrator update your authorization to assign you deploy authorization for the project.
DEP.0005.1006E	You are not authorized to deploy the "{0}" project for the following reason: "{1}".
Explanation	An error occurred when invoking the service on the host Integration Server. Integration Server cannot determine whether the user is authorized to deploy the specified project.
Action	Verify that the host Integration Server is still running. If you are running Deployer from a remote location, verify the network connectivity between the Deployer user interface and the server.
DEP.0005.1007E	The following exception occurred while attempting to process "{0}": "{1}"
Explanation	<p>In the message, <subMessage> is one of the following sub-messages that Deployer displays to provide additional information about the exception: -<targetFileName> - An exception occurred while performing a [remote] invoke of the service: <ISServiceName>. Exception details follow: <exceptionInfo> - An exception occurred while attempting to XMLDecode the file: <buildFileName>. Exception details follow: <exceptionInfo>. - <errorMessageReturnedFromIS> - An exception occurred getting a Trading Networks, TN, docType object. That is most likely caused by a user-defined extension to the TN type BizDocType. Copy the jar files, which should be found in the <webM install dir> \ \IntegrationServer \ \packages \ \WmTN \ \code \ \jars directory, containing those extensions into the WmDeployer/code/jars directory. - Source package is of type upgrade and required target package version is null. - Error: no Logical Server for Server ID" The most-likely fix for that is to use webMethods Administrator on your target server to define a logical server with the name: <sourceSystemName>. - An Exception occurred while attempting to IDataBinCoder the file: '<buildFileName>'. Exception details follow: <exceptionInfo> - Overwrite 'everything else' field is set to <overwriteEverythingElseString>, which is invalid. - The Port: <sourcePortName>, associated with Package: <packageName> - Disabling</p>

of the Port: <sourcePortName>, associated with Package: <packageName> - Enabling of the Port: <sourcePortName>, associated with Package: <packageName> - Resuming the scheduled-service: " + scheduledServiceName - Suspending the scheduled-service: " + scheduledServiceName - <serviceName> - A SOAP fault occurred while performing a remote invoke of the service: <ISServiceName>.The SOAP Fault string follows: <faultString> - Getting information about the Port: <sourcePortName>, associated with Package: <packageName> The reason for the exception can be one of the following:

- There is a problem with connectivity to the target Integration Server.
- The target Integration Server is not running.
- The target Integration Server requires a Broker Server, but no Broker Server is connected to it.
- There is a user-defined extension to a Trading Networks document type, and Deployer does not have access to the associated jar files.
- You specified a partial package for deployment; however, the package does not exist on the target.
- You specified a logical server that is not defined on the target.
- The overwrite flag is invalid, which can only occur if the build file was manually edited.

Action

Based on the reason for the exception, perform one of the following:

- Verify the network connectivity between the Deployer server and each target server.
- Verify that each target server is running.
- If the target Integration Server requires that a Broker be connected to it, ensure that a Broker is connected.
- If a user-defined Trading Networks document type is in use, ensure Deployer has access to the associated jar files. To do so copy the jar files located in the <serverDirectory>\packages\WmTN\code\jars directory (which contain the Trading Networks document type extensions) to the <serverDirectory>\packages\WmDeployer\code\jars directory.
- If you specified a partial package and the package does not exist on the target, either remove the package from the deployment or specify a full package for deployment.
- If the definition of a logical server is missing, use webMethods Administrator on your target server to define a logical server with the name indicated in the error message.
- If the overwrite flag is invalid, ensure that your build file has not been manually edited.

DEP.0005.1008E	The deploy report: "{0}" already exists. Please move it to a different directory.
Explanation	The deploy report already exists.
Action	Move the existing deploy report file to a different directory.
DEP.0005.1010	An error occurred interacting with server: "{0}". Exception details follow: "{1}"
Explanation	This error occurs if the servers in a cluster are not up and running or if the cluster is invalid for some reason.
Action	Verify that the cluster is configured correctly and that all servers are up and running.
DEP.0005.1011E	Error invoking service wm.deployer.UIAuthorization. Contact Software AG support.
Explanation	Error invoking service wm.deployer.UIAuthorization.
Action	Contact Software AG support.
DEP.0005.1014E	An exception occurred while attempting to close the file "{0}". This will not affect deployment, but will keep a lock on the file. Exception details follow: "{1}"
Explanation	The build file could not be closed because an I/O exception occurred. The exception can occur for the following reasons: <ul style="list-style-type: none"> - The I/O operation failed or was interrupted while accessing the build file. - A security violation has occurred, which typically means that the user running Deployer does not have correct privileges to access the files.
Action	Verify that the file system is not corrupt and that adequate disk space is available for saving new files. Also verify that the user attempting this action has proper privileges to save files on the file system.
DEP.0005.1015E	The Overwrite Existing field is set to {0}, which is invalid.
Explanation	The overwrite flag was set to a value that the code did not recognize. This occurs when a user has manually edited the XML in the target file.
Action	Repeat the build and map steps. Do not manually edit the target file.
DEP.0005.1018E	A null aliasValues IData was returned from the invocation of wm.server.remote:getAliasValue against remote host: {0} Cannot continue with deployment of Trading Networks. Make sure the WmTN package and the Trading Networks JDBC pool on the target server are enabled.
Explanation	Deployer invoked the wm.server.remote:getAliasValue service while deploying Trading Networks assets, and a null value was returned.
Action	Make sure the WmTN package and the Trading Networks JDBC pool on the target server are enabled.

DEP.0005.1024E **The target cluster {0} is not currently available. Deployer is skipping that cluster. Check your network connection and make sure all target servers ({1}) are running within the cluster.**

Explanation Deployer cannot connect to the target cluster servers due to network connection problems.

Action Check your network connection. You should be able to access the target server machines.

DEP.0005.1025W **webMethods Deployer does not support deployment of certificates. Certificates for profile "{0}" will not be deployed.**

Explanation Deployer does not support the deployment of certificates.

Action Deployer does not support deployment of certificates. Certificates for profile "{0}" will not be deployed.

DEP.0005.1026E **Deployer cannot enable adapter connection {0} on target {1}. Make sure the pub.art.connection:enableConnection service is operational and the WmART package is installed on the target server.**

Explanation Deployer invoked the pub.art.connection:enableConnection service but could not enable adapter notification on the target server after deployment.

Action Make sure the pub.art.connection:enableConnection service is operational and the WmART package is installed on the target server.

DEP.0005.1027E **Adapter connection {0} on target {1} is not enabled. Make sure the pub.art.connection:queryConnectionState service is operational and the WmART package is installed on the target server.**

Explanation Deployer invoked the pub.art.connection:queryConnectionState service but could not enable adapter connections on the target server after deployment.

Action Make sure the pub.art.connection:queryConnectionState service is operational and the WmART package is installed on the target server.

DEP.0005.1028E **Deployer cannot update adapter connection "{0}" on target "{1}".**

Explanation Deployer invoked the wm.art.dev.connection:updateConnectionNode service but could not update adapter connections on the target server after deployment.

Action Make sure the wm.art.dev.connection:updateConnectionNode service is operational and the WmART package is installed on the target server.

DEP.0005.1029E	Unable to disable adapter connection {0} on target {1}. Check the Integration Server logs and error messages in the output report for more information.
Explanation	Unable to disable adapter connection on target.
Action	Check the Integration Server logs and error messages in the output report for more information.
DEP.0005.1030E	Deployer encountered an error retrieving current values for adapter connection {0} on target {1}. Make sure the <code>wm.art.admin.connection:getResourceConfiguration</code> service is operational and the WmART package is installed on the target server.
Explanation	Deployer invoked the <code>wm.art.admin.connection:getResourceConfiguration</code> service but could not get current values for the adapter connection in the varsub page.
Action	Make sure the <code>wm.art.admin.connection:getResourceConfiguration</code> service is operational and the WmART package is installed on the target server.
DEP.0005.1031E	Deployer cannot set the adapter notification for {0} on target {1}. The selected adapter notification might be active on the target server. Review the project settings.
Explanation	Deployer could not set variable substitution values for adapter notification.
Action	The selected adapter notification might be active on the target server. Review project settings to make sure they are appropriate.
DEP.0005.1032E	The adapter notification for {0} on target {1} is not enabled.
Explanation	Deployer invoked the <code>pub.art.notification:queryPollingNotificationState</code> service but could not enable adapter notification on the target server after deployment.
Action	Make sure the <code>pub.art.notification:queryPollingNotificationState</code> service is operational and the WmART package is installed on the target server.
DEP.0005.1033E	Deployer cannot enable adapter notification for {0} on target {1}.
Explanation	Deployer invoked the <code>pub.art.notification:enablePollingNotification</code> service, but could not enable adapter notification on the target server after deployment.
Action	Make sure the <code>pub.art.notification:enablePollingNotification</code> service is operational and the WmART package is installed on the target server.
DEP.0005.1034E	Deployer cannot disable the adapter notification for {0} on target {1}. Check the Integration Server logs for more information. Re-create the build and redeploy if necessary.
Explanation	Deployer cannot disable adapter notification.
Action	Check the Integration Server logs for more information. Re-create the build and deploy again if necessary.

DEP.0005.1039E	Deployer cannot find the deployment reports for deployment candidate {0}.
Explanation	There are no reports for the deployment candidate.
Action	Try to view the reports using a simulate or deploy operation.
DEP.0005.1040E	Invalid ID for deployment report. Please use the list command to verify your inputs.
Explanation	This message occurs when a Deployer user attempts to view the deployment report through command line interface and the report ID does not exist.
Action	Perform simulate and deploy operations and refer to the report ID shown.
DEP.0005.1041E	Deployer cannot read report {0}.
Explanation	This message occurs when Deployer is unable to display reports in a browser.
Action	Ensure that the report HTML or XML files are valid and not corrupted.
DEP.0005.1045E	An error occurred while attempting to import functional permissions: class: "{0}", message: "{1}"
Explanation	This error occurs when Deployer is unable to deploy Trading Network functional permissions, and it indicates that there might be a problem with the build.
Action	Verify that the selected functional permissions are valid on the source server, and rebuild if necessary.
DEP.0005.1049E	An exception occurred while deleting DLS "{0}"
Explanation	An exception occurred while deleting DLS.
Action	Contact the administrator of the target Trading Networks system for assistance.
DEP.0005.1050E	An exception occurred while deleting the "{0}" functional permission.
Explanation	An exception occurred while deleting the functional permission.
Action	Verify that the target server is running and try the deletion again.
DEP.0005.1055E	An error occurred while attempting to import DLSs. The following is the error information from Trading Networks: class: "{0}", message: "{1}"
Explanation	Deployer displays this error when it cannot deploy Trading Network DLSs. It indicates that there might be a problem with the build.
Action	Verify that the selected DLSs are valid on the source server and rebuild if necessary.

DEP.0005.1057E	Invalid ID for build report. Use the list command to verify your inputs.
Explanation	Deployer displays this message when a Deployer user attempts to view the build report through the command line interface and the specified report ID does not exist.
Action	Perform a build operation on the deployment sets and refer to the build report ID shown.
DEP.0005.1058E	Unable to read JMS trigger {0}.
Explanation	Deployer is unable to read the JMS trigger files from the source server.
Action	Ensure that the JMS trigger was created properly on the source server.
DEP.0005.1059E	Unable to read build zip file.
Explanation	Deployer is unable to read the build zip file while deploying.
Action	Verify that the project build file is correct, and ensure that it has not been corrupted.
DEP.0005.1060E	Error deploying to cluster. One or more of the nodes in the cluster are not running. Check the cluster configuration and the extended settings for further information.
Explanation	Not all of the nodes in the cluster are running.
Action	Check the cluster configuration and the extended settings.
DEP.0005.1063	Action failed: The target server is unavailable. See the Integration Server logs for more information.
Explanation	The target server is not available.
Action	Check the Integration Server logs for any relevant errors or messages.
DEP.0005.1067E	An error occurred while attempting to import archival services. The following is the error information from Trading Networks:<p>class: "{0}", message: "{1}"</p>
Explanation	This error occurs when Deployer is unable to deploy the Trading Networks archival services and indicates that there might be a problem with the build.
Action	Verify that the selected archival services are valid on the source server and rebuild if necessary.
DEP.0005.1068E	Automatic rollback in logical cluster group {0} failed because the connection to target server {1} was refused.
Explanation	Deployer displays this message when an automatic rollback fails.
Action	Ensure that the specified server is online and that the network connection works. For more information, see the rollback report and take appropriate action.

DEP.0005.1069E **Deployment in logical cluster group {0} failed. Connection to target server {1} was refused. Deployer will perform rollback on logical group {2}.**

Explanation This error occurs when Deployer is unable to deploy assets to a logical cluster group of target servers.

Action Verify that the servers in the logical cluster group are online and available.

DEP.0005.1074E **Deployer cannot import Trading Networks partner profiles without a My Enterprise profile.**

Explanation Deployer was unable to deploy the Trading Networks partner profile.

Action Verify that a My Enterprise profile exists on the target server. If not, you must deploy the My Enterprise profile first.

DEP.0005.1076E **Deployer encountered an exception while trying to delete {0}. Exception details follow: "{1}"**

Explanation An exception occurred while trying to delete the node.

Action Refresh the node list and try deleting again.

DEP.0005.1125E **Assets in deletion set {0} have unresolved dependencies. Either add the dependent assets or remove the existing assets from the deletion set.**

Explanation Assets in the deletion set have unresolved dependencies.

Action Add the dependent assets, or remove the existing assets from the deletion set.

DEP.0005.1126E **Deployment to a logical cluster failed and Deployer performed a rollback. Refer to the deployment and rollback reports for more details.**

Explanation Deployment to a logical cluster failed and rollback has occurred.

Action See the deployment and rollback reports for more details.

DEP.0005.1129E **Error occured when deploying file to a Target. Please check the target Integration Server logs for details. {0}**

Explanation This error occurs when deploying large files. It indicates that the target server WmDeployerResource package is not operational.

Action Verify that the WmDeployerResource package is installed on the target server. If it is already installed, try re-installing.

DEP.0005.1130E	An error occurred while creating or reading the streaming file {0} corresponding to {1} in the build. Check the target Integration Server logs for details.
Explanation	This error occurs when extracting large files from a source server. It indicates that the WmDeployerResource package is not operational.
Action	Verify that the WmDeployerResource package is installed on the target server. If it is already installed, try re-installing.
DEP.0005.1135E	The deployment or deletion set "{0}" contains unresolved dependencies or references. Please resolve the unresolved dependencies to continue with deployment.
Explanation	The deployment or deletion set contains unresolved dependencies or references.
Action	Resolve the unresolved dependencies or references for the deployment or deletion sets in your project.
DEP.0005.1152E	The delivery of artifacts to the {0} target server failed. For details, check the logs of the target server.
Explanation	The delivery of artifacts to the target server failed.
Action	For more information, check the deployment report and the Integration Server log.
DEP.0005.1153E	The activation of artifacts on the {0} target server failed. For details, check the logs of the target server.
Explanation	The activation of artifacts on the target server failed.
Action	For details, check the deployment report and the Integration Server log.
DEP.0005.1161E	Deployer could not deliver artifacts to {0} because the server is unavailable.
Explanation	The target server is unavailable.
Action	Ensure the target server is running.
DEP.0005.1167E	Unable to delete artifacts previously delivered to {0} because the server is unavailable.
Explanation	The target server is unavailable.
Action	Make sure the target server is running.

DEP.0005.1173E	Skipping the activation of deployment on {0} because the target server is unavailable.
Explanation	Target server is unavailable.
Action	Ensure target server is running.
DEP.0005.1183E	A simulation initiated by user {0} for deployment candidate {1} of project {2} is in progress. Wait until the simulation in progress is complete.
Explanation	Another user is running an operation for this project.
Action	Wait until the other operation finishes.
DEP.0005.1184E	A deployment initiated by the user {0} for deployment candidate {1} of project {2} is in progress. Wait until the deployment in progress is complete.
Explanation	Another user is running an operation for this project.
Action	Wait until the other operation finishes.
DEP.0005.1185E	A rollback initiated by user {0} for deployment candidate {1} of project {2} is in progress. Wait until the rollback in progress is complete.
Explanation	Another user is running an operation for this project.
Action	Wait until the other operation finishes.
DEP.0005.1186E	A checkpoint initiated by user {0} for deployment candidate {1} of project {2} is in progress. Wait until the checkpoint in progress is complete.
Explanation	Another user is running an operation for this project.
Action	Wait until the other operation finishes.
DEP.0005.1187E	You cannot deploy the {0} project because it is not locked.
Explanation	The project was not locked before deployment.
Action	Lock the project.
DEP.0005.1188E	You cannot deploy the {0} project because it is locked by another user.
Explanation	Another user has locked the project.
Action	Wait until the project is unlocked by the other user.

DEP.0005.1189E	You cannot simulate the deployment for the {0} project because it is not locked.
Explanation	The project was not locked before simulation.
Action	Lock the project.
DEP.0005.1190E	You cannot simulate the deployment for the {0} project because it is locked by another user.
Explanation	Another user has locked the project.
Action	Wait until the project is unlocked by the other user.
DEP.0005.1191E	You cannot rollback the deployment for the {0} project because it is not locked.
Explanation	The project was not locked before you attempted to roll back the deployment.
Action	Lock the project.
DEP.0005.1192E	You cannot rollback the deployment for the {0} project because it is locked by another user.
Explanation	Another user has locked the project.
Action	Wait until the project is unlocked by the other user.
DEP.0005.1193E	You are not authorized to generate a checkpoint for the {0} project because it is not locked.
Explanation	The project was not locked before you attempted to generate a checkpoint.
Action	Lock the project.
DEP.0005.1194E	You are not authorized to generate a checkpoint for the {0} project because it is locked by a different user.
Explanation	Another user has locked the project.
Action	Wait until the project is unlocked by the other user.
DEP.0005.1195E	The deletion of delivered to the {0} target server artifacts failed. For details, check the logs of the target server.
Explanation	The deletion of delivered to the target server artifacts failed.
Action	Check the deployment report for details. There might be additional information in the log of Integration Server.

DEP.0005.1201E	Repository-based deployment does not support the rollback operation for target servers of version 8.2 or earlier.
Explanation	Repository-based projects do not support rollback operations for target servers of version 8.2 or earlier.
Action	Select target servers of version 8.2 or later.
DEP.0005.1203E	There are no target servers or target groups mapped for deployment candidate {0}.
Explanation	There are no target servers or target groups mapped to the deployment set in the map step.
Action	Map at least one deployment set to a target server or a target group in the map step.
DEP.0005.1204E	The success flag does not match any messages returned by the target server {0}.
Explanation	Either the target server returned the success flag of true and the messages from the target server contains error messages, or the target returned a success flag of false and the message from the target server does not contain an error message.
Action	Check the target server logs or contact Software AG Global Support.
DEP.0005.1206E	An error occurred while saving deployment candidate {0}.
Explanation	An error encountered while saving the deployment candidate.
Action	Contact Software AG Global Support.
DEP.0005.1210E	Deployer did not delete the assets from {0} because the server is unavailable.
Explanation	The target server is unavailable.
Action	Ensure target server is running.
DEP.0005.1212E	Deployer failed to delete the assets on the target server {0}. For more information, see the target server's logs.
Explanation	The deletion of assets on the target server failed.
Action	Check the deployment report and the Integration Server log for details.
DEP.0005.1215E	Deployer failed to delete the assets on the target server {0}. For more information, see the target server's logs.
Explanation	The deletion of assets on the target server failed.
Action	Check the deployment report for details. There might be additional information in the Integration Server log.

DEP.0005.1216E	Target server {0} did not return any messages.
Explanation	Deployer did not receive any messages from target server {0}.
Action	Check the target server log for details.
DEP.0005.1217E	Deletion set {0} contains unresolved dependencies. Please resolve the dependencies to proceed with deployment.
Explanation	The deletion set contains unresolved dependencies.
Action	Resolve the unresolved dependencies for the deletion set.
DEP.0005.1218E	Repository-based deployment does not support the rollback operation for target servers of types {0}.
Explanation	Repository-based deployment does not support rollback operation for target servers of the given type.
Action	Remove the assets of the unsupported runtimes from the deployment and deletion sets and update the deployment map accordingly.
DEP.0005.1219E	Repository-based deployment does not support the simulate operation for target servers of types {0}.
Explanation	Repository-based deployment does not support simulate operation for target servers of the given type.
Action	Remove the assets of the unsupported runtimes from the deployment and deletion sets and update the deployment map accordingly.
DEP.0005.1220E	Repository-based deployment does not support deletion sets for target servers of types {0}.
Explanation	Repository-based deployment does not support deletion sets for target servers of the given type.
Action	Remove the assets of the unsupported runtimes from the deletion set and update the deployment map accordingly.
DEP.0005.1221E	Repository-based deployment does not support deletion sets for target servers of version 8.2 or earlier.
Explanation	Repository-based deployment does not support deletion sets for target servers of version 8.2 or earlier.
Action	Remove the deletion set from the project.

DEP.0005.1222E **The repository is corrupted. The binary file for composite {0} of type {1} is missing from repository {2}.**

Explanation The binary file is missing from the repository.

Action Rebuild the repository using Asset Build Environment.

DEP.0005.1227E **Deployer issued the following exception while deleting the field definition during rollback: "{0}"**

Explanation An exception occurred while deleting the field definition.

Action Contact the administrator of the target server for assistance.

DEP.0005.1230 **No value was specified for the required package parameter. Specify a value for the package parameter.**

Explanation No value was specified for the package parameter.

Action Specify a valid package value for the package parameter.

DEP.0006.0011E **Plugin {0} does not exist.**

Explanation The specified plug-in is not correctly configured in the Deployer plugin configuration file. This indicates an incomplete or damaged installation, or possibly a modification to the plugin configuration file located in
<serverDirectory>\packages\WmDeployer\config\plugin folder.

Action Make sure a file named <pluginName>.cnf exists in the
<serverDirectory>\packages\WmDeployer\config\plugin directory.

DEP.0006.0025E **The versions for the aliases {0} were not persisted successfully. Verify that the specified version is valid.**

Explanation The specified versions are not valid.

Action Ensure that the specified versions are valid.

DEP.0006.0026E **The version {0} reported by the {1} plugin for the server alias {2} does not match the version {3} set by the user.**

Explanation The version reported by the plugin is different from the version set for the server alias.

Action Set the correct version for the server alias.

DEP.0006.0028E	Plugin server name {0} contains illegal characters.
Explanation	The plugin server name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : \$ / \ \ ` ' ; , ~ + = > < \ "
Action	Remove the invalid characters from the plugin server name.
DEP.0006.0030E	Plugin server {0} of type {1} does not exist for the specified runtime type. Create a new plugin server or remove it from the project map.
Explanation	The plugin server does not exist for the specified runtime type.
Action	Create a new plugin server or remove it from the project map.
DEP.0007.0001E	A target group with the name {0} already exists.
Explanation	You specified a name for a target group that already exists. Deployer requires that target groups be uniquely named.
Action	Specify a unique name for the target group.
DEP.0007.0002E	Target group {0} does not exist.
Explanation	The specified target group does not exist
Action	Verify that the target group exists in the Deployer server target groups.
DEP.0007.0005E	Error invoking service {0}. This usually indicates a problem with the Integration Server installation. On the local Deployer server, determine whether the following Integration Server packages are disabled, missing, or missing parts: WmDeployer, WmAdmin, WmRoot, WmDeployerResource, WmModeler.
Explanation	Deployer was unable to invoke a required Integration Server service. This usually indicates a problem with the Integration Server installation.
Action	On the local Deployer server, determine whether the following Integration Server packages are disabled, missing, or missing parts:
	WmDeployer
	WmAdmin
	WmRoot
	WmDeployerResource
	WmModeler

DEP.0007.0006E **Deployer encountered the following error while invoking getConnectionInfo for system {0}: {1}**

Explanation Deployer could not retrieve the logical server connection information from the source server. The source server might not be running or the logon credentials might be incorrect.

Action Make sure the specified source server is running and that the logon credentials in the plug-in server configuration, including the Port value, are correct.

DEP.0007.0007E **The call to getConnectionInfo for system {0} returned the following exception for host name {1}: {2}**

Explanation Deployer was unable to retrieve the logical server connection information from the source server. The source server might not be running or the logon credentials might be incorrect.

Action Make sure the specified source server is running and that the logon credentials in the plug-in server configuration, including the Port value, are correct.

DEP.0007.0008E **The call to getConnectionInfo for system {0} returned the following missing data: {1} Make sure the specified source server is running and that the logon credentials in the plug-in server configuration, including the Port value, are correct.**

Explanation Deployer was unable to retrieve the logical server connection information from the source server. The source server might not be running or the logon credentials might be incorrect.

Action Make sure the specified source server is running and that the logon credentials in the plug-in server configuration, including the Port value, are correct.

DEP.0007.0009E **Deployer encountered the following error while connecting to Integration Server {0}: {1}**

Explanation Deployer was unable to connect to the specified remote Integration Server. The Integration Server might not be running, or the logon credentials might be incorrect.

Action Make sure the Integration Server is running and that the logon credentials in the remote server configuration, including the Port value, are correct.

DEP.0007.0010E **Deployer encountered the following error while invoking the required Integration Server service {0} on system {1}: {2} This usually indicates an incomplete or error with the installation of a plug-in on the remote server. On the specified remote server, determine whether the following required Integration Server packages are disabled, missing, or incomplete:**

Explanation Deployer was unable to invoke a required Integration Server service. This usually indicates an incomplete or error with the installation of a plug-in on the remote server.

Action On the specified remote server, determine whether the following required Integration Server packages are disabled, missing, or incomplete:

- WmDeployer
- WmAdmin
- WmRoot
- WmDeployerResource
- WmModeler

DEP.0007.0011 **A Target Server with name {0} already exists. Rename the target server alias or use a different name for the Target Group.**

Explanation Target servers and target groups cannot have the same names.

Action Rename the target server alias or use a different name for the Target Group.

DEP.0007.0012E **Failed to load the plug-in server configuration file {0}. This indicates that the configuration file has been modified and Deployer can no longer parse the configuration file. Try to delete and then re-add the plug-in server. This should correctly recreate the configuration file. If this fails, send the contents of the server configuration file, located in "<serverDirectory>/packages/WmDeployer/config/pluginServer/<pluginName>" to Software AG Global Support.**

Explanation When Deployer started, it could not successfully load the plug-in server configuration file. This indicates the configuration file has been modified and Deployer can no longer parse the configuration file.

Action Try to delete and then re-add the plug-in server. This should correctly recreate the configuration file. If this fails, send the contents of the server configuration file, located in "<serverDirectory>/packages/WmDeployer/config/pluginServer/<pluginName>" to Software AG Global Support.

DEP.0007.0013E **Failed to save plugin server config file {0}. The plug-in configuration file provided by Software AG does not contain the entry identifying the class necessary to remotely install the communication component. The configuration file may have been altered incorrectly. Reinstall Deployer. Your project data will remain unchanged.**

Explanation The plug-in configuration file provided by Software AG does not contain the entry identifying the class necessary to remotely install the communication component. The configuration file might have been altered incorrectly.

Action Reinstall Deployer. Your project data will remain unchanged.

DEP.0007.0014E	{0} target group {1} dependencies have been resolved. See the Integration Server error log for details. Contact webMethods Global Support if the problem cannot be resolved locally.
Explanation	The invocation of the Communication Component Installation class has failed.
Action	See the Integration Server error log for details. Contact Software AG Global Support if the problem cannot be resolved locally.
DEP.0007.0015E	{0} Target Group {1} validation failed. Unable to resolve some servers within the group. Your installation could be damaged or corrupt. Reinstall Deployer. Your project data will remain unchanged.
Explanation	The remote installation of the communication component was unable to locate the component file on the file system. Your installation could be damaged or corrupt.
Action	Reinstall Deployer. Your project data will remain unchanged.
DEP.0007.0018E	Deployer encountered the following error while pinging plug-in server {0}: {1} Deployer cannot contact the remote server hosting the identified plug-in. The host could be down or the host name could be incorrect. Verify the host name (or IP address) and ensure that the system is available.
Explanation	Deployer cannot contact the remote server hosting the identified plug-in. The host could be down or the host name could be incorrect.
Action	Verify the host name (or IP address) and ensure that the system is available.
DEP.0007.0019E	Plug-in {0} on target group {1} does not contain any servers.
Explanation	You have attempted to add a target group with no servers.
Action	Add target servers in that target group.
DEP.0007.0029	Cannot create a Target Group with same name as that of a Target Server. Either rename the target group or delete the existing target group or target server with the same name.
Explanation	You cannot create a target group with same name as one used by a target server.
Action	Either rename the target group or delete the existing target group or target server with the same name.
DEP.0007.0030	{0} Target Group {1} validation failed. Unable to resolve some servers within the cluster {2} in the group {3}. Make sure all nodes in the cluster are running and the WmDeployerResource package is installed on all of these nodes. If the WmDeployerResource package is not installed, install it using the Deployer user interface.
Explanation	Deployer cannot ping some of the cluster servers.

Action	Make sure all nodes in the cluster are running and the WmDeployerResource package is installed on all of these nodes. If the WmDeployerResource package is not installed, install it using the Deployer user interface.
DEP.0007.0031E	Validation of plug-in {0} on target group {1} failed. Deployer cannot resolve server {2} which is a part of the cluster {3}. Remove this server manually from target group.
Explanation	A server in the cluster could not be resolved.
Action	Manually remove the server from the tagret group.
DEP.0007.0032E	Invalid version specified for the target group {0} of type {1}. The valid versions can be {2}.
Explanation	The version specified for the target group is not valid.
Action	Specify the correct version.
DEP.0007.0033E	The server aliases {0} version do not match the target group {1} version. Server aliases and target groups must be of the same version. Modify either the definition of the targets within the target group or modify the version of the target group.
Explanation	The version of the targets in the target group do not match the version of the parent target group.
Action	Modify either the definition of the targets within the target group or modify the version of the target group.
DEP.0007.0034E	Target group name {0} contains illegal characters.
Explanation	The target group name contains one or more spaces or the following invalid characters: # & @ ^ ! % * : \$ / \ \ ` ' ; , ~ + = > < \ "
Action	Remove the invalid characters from the target group name.
DEP.0007.0035	Target group {0} does not exist.
Explanation	A target group was mapped for deployment but is either not defined or was deleted.
Action	Define the target group.
DEP.0008.0001E	You are not authorized to checkpoint the {0} project. Use the Deployer user interface to grant the user the right to deploy the project.
Explanation	The user is not authorized to generate a checkpoint for the project.
Action	Use the Deployer user interface to grant the user the right to deploy the project.

DEP.0008.0003E	Error invoking service "{0}".
Explanation	An exception occurred while invoking the wm.deployer.UIAuthorization:isAuthorized service. This could mean that Integration Server is either not running or that it cannot be reached on the network.
Action	Verify that the Integration Server is running and available on the network.
DEP.0008.0004E	Error cloning source system "{0}": {1}
Explanation	The project contains a source system of an unknown type.
Action	Rebuild the project.
DEP.0008.0006E	Checkpoint summary file "{0}" does not exist.
Explanation	The checkpoint file does not exist on the disk.
Action	Use Deployer to create a checkpoint.
DEP.0008.0007E	Cannot write to checkpoint directory "{0}".
Explanation	You cannot create or write to the specified directory.
Action	Ensure that you have the correct privileges to create and write to the directory and that the file system has enough space for the creation of a new directory.
DEP.0008.0009E	Error creating checkpoint "{0}": {1}
Explanation	An exception occurred while creating the checkpoint report.
Action	Ensure that you have the correct privileges to create and write to files and that the file system has enough space for the new file.
DEP.0008.0010E	Error saving checkpoint project {0}: {1}. Make sure you have the correct privileges to create and write to files and that the file system has enough space for the new file
Explanation	The specified file could not be saved to disk.
Action	Make sure you have the correct privileges to create and write to files and that the file system has enough space for the new file.
DEP.0008.0013E	Deployer cannot generate a checkpoint at {0} because the target server is unavailable
Explanation	The target server is unavailable.
Action	Ensure that the target server is running.

DEP.0008.0015E	Checkpoint on the target server {0} failed. Please check the target server's logs for details.
Explanation	The checkpoint operation failed due to the reason specified in the checkpoint report.
Action	Check the checkpoint report for details. There might also be additional information in the Integration Server log.
DEP.0008.0018E	Skipping the delete checkpoint for {0} because the server is unavailable.
Explanation	The target server is unavailable.
Action	Ensure that the target server is running.
DEP.0008.0022E	Failed to delete checkpoint for target server {0}.
Explanation	Deletion of checkpoint failed.
Action	Check Deployer and Integration Server logs.
DEP.0008.0023E	Repository-based deployment does not support the checkpoint operation for target servers of version 8.2 or earlier.
Explanation	Repository-based projects do not support checkpoint operations for target servers of version 8.2 or earlier.
Action	Select target servers of version 8.2 or later.
DEP.0008.0024I	Deployer does not allow you to create checkpoints for transactional deployment.
Explanation	You cannot create a checkpoint for projects that use transactional deployment. Deployer creates checkpoints automatically for transactional deployment.
Action	See the webMethods Deployer documentation for more information.
DEP.0008.0025E	Repository-based deployment does not support checkpoint operation for target servers of type {0}.
Explanation	Repository-based deployment does not support checkpoint operation for target servers of the given type.
Action	Remove the assets of the unsupported runtimes from the deployment and deletion sets and update the deployment map accordingly.

DEP.0100.3.42E **The simulate, checkpoint, deploy, or rollback operation encountered an error while generating the report. Contact Software AG Global Support.**

Explanation The simulate, checkpoint, deploy, or rollback operation encountered an error while generating the report.

Action Contact Software AG Support.

DEP.0100.5.37 **Deployer cannot retrieve the project specified on the command. Make sure the user is authorized to view this information.**

Explanation Deployer cannot retrieve the project specified on the command.

Action Make sure the user is authorized to view this information.

DEP.0100.5.38 **Deployer cannot retrieve the build information specified on the command. Make sure the user is authorized to view this information.**

Explanation Deployer cannot retrieve the build information specified on the command.

Action Make sure the user is authorized to view this build information.

DEP.0100.5.39 **Deployer cannot retrieve the map specified on the command. Make sure the user is authorized to view this information.**

Explanation Deployer cannot retrieve the map the user specified on the command.

Action Make sure the user is authorized to view this information.

DEP.0100.5.40 **Deployer cannot retrieve the deployment candidates specified on the command. Make sure the user is authorized to view this information.**

Explanation Deployer cannot retrieve the deployment candidates specified on the command.

Action Make sure the user is authorized to view this information.

DEP.0100.5.41 **Deployer cannot retrieve the map for the user and project specified on the command. Make sure the user is authorized to view this information.**

Explanation Deployer cannot retrieve the map for the user and project specified on the command.

Action Make sure the user is authorized to view this information.

DEP.0100.5.42 **Deployer cannot retrieve the build information specified on the command. Make sure the user is authorized to view this information**

Explanation Deployer cannot retrieve the build information specified on the command.

Action Make sure the user is authorized to view this information.

DEP.0100.5.43 **There are no .map files in the IntegrationServer/packages/WmDeployer/replicate/inbound folder. Make sure the file you want to import exists in the specified folder.**

Explanation There are no .map files in the IntegrationServer/packages/WmDeployer/replicate/inbound folder.

Action Make sure the file you want to import exists in the specified folder.

DEP.0100.5.63 **The Integration Server to which you are trying to connect is configured to accept only secure connections on the UNIX platform. Use the correct digital certificates to establish the connection.**

Explanation The Integration Server to which you are trying to connect is configured to accept only secure connections on the UNIX platform.

Action Use the correct digital certificates to establish the connection.

DEP.0100.5.64E **Deployer encountered an error while invoking the service. Make sure the Integration Server to which you are trying to connect is up and running and you have properly installed all required components.**

Explanation This error is encountered when trying to invoke the service from CLI.

Action Make sure the Integration Server to which you are trying to connect is up and running and you have properly installed all required components.

InputValidationMessages.0001E – Parameter {0} cannot be null or empty

Explanation The specified parameter is either null or empty.

Action Provide a valid value for the parameter.

InputValidationMessages.0002E – Parameter {0} cannot be null.

Explanation The specified parameter is null.

Action Provide a valid value for the parameter.

InputValidationMessages.0003E – Parameter {0} cannot be a negative integer

Explanation The specified value is a negative integer.

Action Provide a positive integer value for the parameter.

InputValidationMessages.0004E – File {0} does not exist.

Explanation The specified file does not exist in the specified location.
Action Provide a valid file.

InputValidationMessages.0005E – SSL-enabled connections require that either the TrustClientCertificatesByDefault parameter be set to true or that both TrustStoreFileName and TrustStorePassword are specified.

Explanation Either the TrustClientCertificatesByDefault parameter is set to false or either the TrustStoreFileName, TrustStorePassword, or both are not specified.
Action Set the TrustClientCertificatesByDefault parameter to true or provide valid values for both the TrustStoreFileName and TrustStorePassword parameters.

OperationMessages.0002E – Failed to ping the target {0} of type {1}. Either the target is unavailable or the credentials provided are invalid.

Explanation Either the target is unavailable or the credentials provided are invalid.
Action Verify that the server is up and running, and that the specified parameters are valid.

OperationMessages.0003E – An unexpected error occurred while pinging the target {0}. Error details : {1}

Explanation An unexpected error occurred while pinging the target.
Action Check the server logs for more details.

OperationMessages.0011E – An unexpected error occurred while delivering the deployment set with ID {0} to target {1}. Error details : {2}

Explanation An unexpected error occurred while delivering assets to the target.
Action Check server logs for more details.

OperationMessages.0012E – An unexpected error occurred while performing variable substitutions for the asset with ACDL file name {0}. Error details : {1}

Explanation An unexpected error occurred while substituting values.
Action Check server logs for more details.

OperationMessages.0021E – An unexpected error occurred while deleting the delivered assets for the deployment with ID {0} from target {1}. Error details : {2}

Explanation An unexpected error occurred while deleting the delivered assets.

Action Check the server logs for more details.

OperationMessages.0030E – An unexpected error occurred while activating the deployment with ID {0} for target {1}. Error details : {2}

Explanation An unexpected error occurred while activating the delivered assets.

Action Check the server logs for more details.

OperationMessages.0050E – Runtime type of the artifact {0} is different from the target runtime type {1}

Explanation The runtime type of the specified artifact is different than the target runtime type.

Action Ensure that the runtime type of the asset to be deployed is same as the target server type.

11 Designer Common Plugin Pool Messages

CommonWizardFragmentComposite.EnterDir – Please, check if there is a server installed in the specified directory

CommonWizardFragmentComposite.EnterUrl – Platform manager cannot locate the server

CommonWizardFragmentComposite.InvalidDir – The selected directory is invalid

CommonWizardFragmentComposite.InvalidUrl – The URL is invalid

CommonWizardFragmentComposite.SmpConnection – Cannot connect to the Platform Manager. Check the URL and the credentials

12 Designer Service Development Messages

IOEditor_couldNotBeFoundE – Node name "{0}" is invalid. [ITD.0004.0002] Specified node "{1}" not found.

Explanation The node name that you specified in the Specification Reference, Input, and Output fields in the Input/Output tab is invalid.

Action Provide a valid node name in the Specification Reference, Input, and Output fields in the Input/Output tab.

RestFolderWizardPage_Resource_Already_ExistsE – {0} already exists.

Explanation A REST resource with the same name already exists in the Integration Server. The REST resource name must be unique.

Action Provide a unique name for the REST resource that you are creating.

TransformerAction_Expand_Error_TextE – Could not expand transformer because it was not found. Use the Properties view to rename the transformer.

Explanation Designer could not expand the transformer in the Pipeline view because the transformer no longer exists.

Action Use the Properties view to rename or update the Service property of the transformer.

13

Event-Driven Architecture Tools Messages

EDAESIE0004	The selected Integration Server Document Type is recursive and its conversion results in a recursive Event Type which is not supported.
Explanation	The Integration Server Document type which has been selected is recursive. After the conversion a recursive Event Type is produced. Recursive Event Types are not supported.
Action	Remove recursion from the Integration Server Document type prior to creating an event type from it.
EDAESIE0006	Restrictions not supported for {0}
Explanation	Union and List are not supported for restrictions.
Action	Please contact your software supplier.
EDAESIE0007	Unsupported facet {0} with value {1}
Explanation	The called restriction facet is not supported.
Action	Please contact your software supplier.
EDAESIE0029	Event Types without a target namespace are not allowed outside the root "Event Types" directory.
Explanation	An event type which does not define target namespace exists outside the root of the event types directory.
Action	Either move this event type in the "Event Types" directory or manually create a target namespace definition for it.

EDAESIE0034	Node {0} is not filterable because node {1} is not of cardinality 0..1 or 1..1.
Explanation	The node is not filterable, since the node path can have several values (and not only a unique one).
Action	Set the node to not filterable, or set the cardinality of all nodes on the node path to cardinality 1..1.
EDAESIE0035	Node {0} is not filterable because nodes {1} are not of cardinality 0..1 or 1..1.
Explanation	The node is not filterable, since the node path can have several values (and not only a unique one).
Action	Set the node to not filterable, or set the cardinality of all nodes on the node path to cardinality 1..1.
EDAETE0211	Event Types without a target namespace are not allowed outside the root "Event Types" directory.
Explanation	An event type which does not define target namespace exists outside the root of the event types directory.
Action	Either move this event type in the "Event Types" directory or manually create a target namespace definition for it.
EDAISE0012	The selected IS Document Type is recursive and its conversion results in a recursive Event Type which is not supported.
Explanation	The IS Document type which has been selected is recursive. After the conversion a recursive Event Type is produced. Recursive Event Types are not supported.
Action	Remove recursion from the IS Document type prior to creating an event type from it.
EDANCE0000	Failed to parse date string "{0}" within {1}
Explanation	Failed to parse date string.
Action	Check the format of the supplied data.
EDANCE0001	Failed to parse date string "{0}" within {1}
Explanation	Failed to not parse date string.
Action	Check the format of the supplied data.

EDANCE0003	Specified value "{0}" for property "{1}" is not of type integer.
Explanation	Required property is not of required type.
Action	Check the format of the supplied data.
EDANCE0004	Specified value "{0}" for property "{1}" is not of type long.
Explanation	Specified value for a property is not of type long.
Action	Check whether the specified property is of the required type.
EDANCE0005	Specified value "{0}" for property "{1}" is not of the supported types: "{2}", "{3}", "{4}", "{5}", "{6}", "{7}".
Explanation	The specified guaranteed delivery level in your NERV configuration file is not of the supported ones.
Action	Go to the NERV configuration file and specify one of the valid values: NORMAL, HIGH, MAXIMUM_STRONG, MAXIMUM_EVENTUAL, SHARED for the com.softwareag.eda.nerv.guaranteed.delivery.level property.
EDANCW0002	Not a date: {0} {1}
Explanation	The passed argument is not a date.
Action	Check whether the passed argument is of the required type.
EDANIE0002	Failed to propagate NERV properties change to NERV errorhandler because the JMX helper is not initialized.
Explanation	Failed to propagate NERV properties change to NERV errorhandler because the JMX helper is not initialized.
Action	Check that NERV is properly initialized.
EDANIE0005	Failed to handle notification.
Explanation	Failed to handle route changed notification or unrecognized notification type.
Action	Check that NERV is properly initialized.
EDANIE0006	NERV could not close JMS connection factory successfully.
Explanation	NERV could not close JMS connection factory successfully.
Action	Close JMS connection factory.

EDANIE0011	Failed to register service "{0}"
Explanation	Failed to register Destination Support Service
Action	Make sure that NERV is properly configured.
EDANIE0013	Failed to propagate NERV properties change to NERV component updater because it is not available.
Explanation	Failed to propagate NERV properties change to NERV component updater because it is not available.
Action	Check the log files for errors during Component Updater initialization.
EDANIE0014	Failed to propagate NERV properties change to NERV errorhandler updater because it is not available.
Explanation	Failed to propagate NERV properties change to NERV errorhandler updater because it is not available.
Action	Check the log files for errors during Error Handler initialization.
EDANIE0015	Failed to restart file watcher for NERV deployment directory.
Explanation	Failed to restart file watcher for NERV deployment directory.
Action	Check that NERV is properly configured.
EDANIE0018	Failed to update NERV component "{0}" in "{1}".
Explanation	Failed to update NERV Default JMS component Event Consumer Service.
Action	Make sure that NERV is properly configured.
EDANIE0019	Failed to update NERV component "{0}" in "{1}".
Explanation	Failed to update NERV Default JMS component Event Emitter Service.
Action	Make sure that NERV is properly configured.
EDANIE0021	Failed to configure NERV Default Component "{0}" via properties because the property "{1}" is missing or has an empty value.
Explanation	Failed to configure NERV Default Component via properties because com.softwareag.eda.nerv.default.jms.provider property is missing or has an empty value.
Action	Make sure that NERV is properly configured.

EDANIE0022	Unsubscribe failed for endpoint: <<{0}>>. No such subscription found.
Explanation	Unsubscribe failed for endpoint. No such subscription found.
Action	Check endpointURI.
EDANIE0023	Failed to find any NERV errohandler MBeans.
Explanation	Failed to find any NERV errohandler Services.
Action	Check that NERV error handling is properly configured.
EDANIE0024	Failed to configure NERV errorhandlers.
Explanation	Failed to configure NERV errorhandlers.
Action	Check that NERV error handling is properly configured.
EDANIE0025	Failed to obtain pub/sub "toEndpoint" for: {0}
Explanation	Failed to obtain pub/sub "toEndpoint" for specified url.
Action	Check that NERV Components are properly configured.
EDANIE0026	Failed to set tracing for object name "{0}" to: {1}
Explanation	Failed to set tracing for object name to value.
Action	Check that NERV Components are properly configured.
EDANIE0027	Failed to find existing in-memory endpoint object name for: {0}
Explanation	Failed to find existing in-memory endpoint object name for the specified url.
Action	Check that NERV Components are properly configured.
EDANIE0028	Failed to resolve component: "{0}". NERVSingleton.loadAssets() method has to be invoked prior to obtaining EventEmitter or EventConsumer references.
Explanation	Failed to resolve specified component. NERVSingleton.loadAssets() method has to be invoked prior to obtaining EventEmitter or EventConsumer references.
Action	Make sure NERVSingleton.loadAssets() has been invoked before obtaining Consumer/Emitter references.

EDANIE0029	Failed to resolve component: "{0}". There is no such bean loaded by NERV.
Explanation	Failed to resolve the specified component. No such bean is loaded by NERV.
Action	Check NERV configuration.
EDANIE0030	Failed to resolve component: "{0}". The bean exists, but it is not a NERV component.
Explanation	Failed to resolve specified component. The bean exists, but it is not a NERV component.
Action	Check that the bean is a NERV component.
EDANIE0031	The event type is not specified in the headers of event: {0}
Explanation	The event type is not specified in the event headers.
Action	Message headers map should contain an "\$Event\$Type" entry.
EDANIE0032	No Event Type Store has been set.
Explanation	No Event Type Store has been set.
Action	Check that the Event Type Store location is configured properly.
EDANIE0033	The event type is not specified in the message headers.
Explanation	The event type is not specified in the event headers.
Action	Message headers map should contain an "\$Event\$Type" entry.
EDANIE0034	No OSGi bundle context is set.
Explanation	No OSGi bundle context is set. The bundle has not been initialized correctly.
Action	Restart bundle/OSGi/Product instance.
EDANIE0035	Failed to resolve component with id "{0}". The JMS provider might be down.
Explanation	Failed to resolve specified component. Possible cause: the JMS provider is unreachable due to incorrectly set address in the NERV component configuration properties file or due to the JMS provider being down.
Action	Check NERV Component configuration. Check if the JMS provider is running and reachable.

EDANIE0036	Failed to resolve component with id "{0}".
Explanation	Failed to resolve the specified component.
Action	Check NERV Component configuration.
EDANIE0037	Failed to create NERV default component "{0}": unknown JMS provider "{1}".
Explanation	Failed to create NERV default component: NERVDefaultJms unknown JMS provider.
Action	Check the value of the com.softwareag.eda.nerv.default.jms.provider property in the NERV configuration file.
EDANIE0038	No OSGi bundle context is set.
Explanation	No OSGi bundle context is set. The bundle has not been initialized correctly.
Action	Restart bundle/OSGi/Product instance.
EDANIE0039	Failed to get NERV default component status.
Explanation	Failed to get NERV default component status.
Action	Check that NERV is properly configured.
EDANIE0040	Failed to subscribe to an empty endpoint URI: <<{0}>>
Explanation	Failed to subscribe to an empty endpoint URI.
Action	Check that endpointURI is not null or empty.
EDANIE0041	Failed to subscribe to endpoint URI: <<{0}>>
Explanation	Failed to subscribe to the specified endpoint URI.
Action	Check that the endpointURI is valid.
EDANIE0042	Processor must not be null.
Explanation	When making a subscription, the provided Processor must not be null.
Action	Make sure the processor is not null.
EDANIE0043	End-Points must be more than zero.
Explanation	When making a subscription, the list of the End-Points must contain at least one entry.
Action	Check endpointURIs.

EDANIE0044	Processor must not be null.
Explanation	When unsubscribing, the provided Processor must not be null.
Action	Make sure the processor is not null.
EDANIE0045	No route with id:<<{0}>> found while trying to stop!
Explanation	No route with the specified id is found while trying to stop!
Action	Make sure the route ID is correct.
EDANIE0046	Event Type must be specified in the message headers.
Explanation	The event type is not specified in the event headers.
Action	Message headers map should contain a valid "\$Event\$Type" entry.
EDANIE0047	Message should not be null.
Explanation	Message should not be null or empty.
Action	Make sure the message is not null or empty.
EDANIE0048	Message should not be null and at least one endpoint should be specified.
Explanation	Message should not be null and at least one endpoint should be specified.
Action	Check that the message is not null or empty and that the endpointURIs is not null or empty.
EDANIE0049	<<{0}>> is mandatory header.
Explanation	The "\$Event\$EventID" entry is not specified in the headers of the event.
Action	Message headers map should contain an "\$Event\$EventID" entry.
EDANIE0050	Failed to set {0} header.
Explanation	Failed to set "\$Event\$Start" header.
Action	Expect events with a missing start header.
EDANIE0051	Error while emitting event to endpoint: {0}
Explanation	Error while emitting event to endpoint.
Action	Check the log file for more details.

EDANIE0052	Error while emitting event to endpoint: {0}
Explanation	Error while emitting event to endpoint.
Action	Check the log file for more details.
EDANIE0053	Error while emitting event to endpoint: {0}
Explanation	Error while emitting event to endpoint.
Action	Check the log file for more details.
EDANIE0054	Failed to create route from: {0} to: {1}.
Explanation	Failed to create default routing.
Action	Check the log file for more details.
EDANIE0055	NERV Default Error Handler "{0}" has not been set. Please make sure a valid instance of type "{0}" is provided during Event Emitter instantiation.
Explanation	No ErrorHandlerBuilder instance has been provided during Event Emitter instantiation.
Action	Check that a service/bean of type ErrorHandlerBuilder is exposed/registered by NERV.
EDANIE0056	Failed to remove default route for endpoint: {0}
Explanation	Failed to remove default route for endpoint.
Action	Check the log file for more details.
EDANIE0057	Component Resolver has not been set. Please make sure a valid instance of type "{0}" is provided during Event Emitter instantiation.
Explanation	No Component Resolver instance has been provided during Event Emitter instantiation.
Action	Check that a service/bean of type ComponentResolver is exposed/registered by NERV.
EDANIE0058	EDAEventTypeID must not be null.
Explanation	EDAEventTypeID must not be null.
Action	When making a subscription, check that eventTypeID is not null.

EDANIE0059	No route with id:<<{0}>> found while trying to stop.
Explanation	No route with specified id found while trying to stop.
Action	Check the log file for more details.
EDANIE0060	Message should not be null.
Explanation	Message should not be null.
Action	Check that the message is not null.
EDANIE0061	Message should not be null.
Explanation	Message should not be null.
Action	Check that the message is not null.
EDANIE0062	Event type is missing from the provided event envelope. It should be specified under the /Event/Header/Type element of the XML string. The following tag should exist <Type>...</Type>. Provided event envelope: {0} {1}
Explanation	Event type is missing from the provided event envelope. It should be specified under the /Event/Header/Type element of the XML string. The following tag should exist <Type>...</Type>.
Action	Check that the eventContent matches the specified pattern.
EDANIE0063	Could not find body element in the following string: {0}
Explanation	Could not find body element in the specified string.
Action	Check that eventAsXMLString matches the specified pattern.
EDANIE0064	Event type is either missing or has incorrect format. Provided event type: {0}
Explanation	Event type is either missing or has incorrect format.
Action	Check that eventType is not null or empty or invalid.
EDANIE0065	Event helper is null. It must be set prior to using it.
Explanation	Event helper is null. It must be set prior to using it.
Action	Message Creator service is not configured properly. Check the NERV configuration.

EDANIE0066	Event type store has not been set. Please make sure a valid reference to the Event Type Store is provided during Message Creator instantiation.
Explanation	Event type store has not been set. Please make sure a valid reference to the Event Type Store is provided during Message Creator instantiation.
Action	Check that the Event Type Store location is configured properly.
EDANIE0067	Failed to marshal event.
Explanation	Failed to marshal event.
Action	Check the log file for more details.
EDANIE0068	Event type is either missing or has incorrect format. It should be specified in the message headers map using key {0}.
Explanation	Event type is either missing or has an incorrect format.
Action	Message headers map should contain an "\$Event\$Type" entry.
EDANIE0069	Event should not be null or empty.
Explanation	Event should not be null or empty.
Action	Check that eventAsXMLString is not null or empty.
EDANIE0070	Failed to extract headers and filterable properties from event: {0} {1}
Explanation	Failed to extract headers and filterable properties from the specified event.
Action	Check the log file for more details.
EDANIE0071	{0}
Explanation	Invalid headers.
Action	Check that the headers are not null or empty.
EDANIE0072	{0}
Explanation	Invalid headers.
Action	Check that the headers are not null or empty.

EDANIE0073	{0}
Explanation	Invalid body.
Action	Check that the body is not null or empty.
EDANIE0077	Failed to resolve XSD parser.
Explanation	An error has occurred while trying to provide an XSD parser instance.
Action	Please review the exception stacktrace for detailed explanation of the failure.
EDANIE0078	Failed to resolve XSD parser due to missing Event Type Store bean with name "{0}".
Explanation	The default Event Type Store bean has not been found.
Action	Please make sure that you have specified a correct Event Type Store location in the NERV configuration file.
EDANIE0083	Error while emitting event to endpoint: {0}
Explanation	Error while emitting event to endpoint.
Action	Check the log file for more details.
EDANIE0088	Guaranteed delivery level is set to "{0}", but the configuration directory specified via property "{1}" at "{2}" does not contain a configuration file with name "{3}".
Explanation	No configuration XML file with name equal to the selected guaranteed level is found at the specified configuration directory.
Action	Make sure that a file with name equal to the specified guaranteed mode exists in the configuration directory.
EDANIE0090	Event Emitter has not been set. Please make sure a valid instance of type "0" is provided during Event Consumer instantiation.
Explanation	No Event Emitter instance has been provided during Event Consumer instantiation.
Action	Check that a service/bean of type Event Emitter is exposed/registered by NERV.
EDANIE0091	Failed to flush NERV caches.
Explanation	During initialization NERV flushes all cached events.
Action	Check the exception stacktrace in the log file for more details. Restarting NERV would trigger another flush attempt.

EDANIW0000	{0} does not denote an existing directory.
Explanation	Specified directory does not exist.
Action	Make sure that "com.softwareag.eda.nerv.dead.letter.channel.uri" property denotes a directory.
EDANIW0001	Failed to initialize NERV JMX helper.
Explanation	Failed to initialize NERV JMX helper.
Action	Check log file for more details.
EDANIW0003	Failed to configure NERV Default Error Handler "{0}" with the specified configuration properties.
Explanation	Failed to configure NERV Default Error Handler with the specified configuration properties.
Action	Check that NERV error handling is properly configured.
EDANIW0004	Failed to add event headers to message body.
Explanation	Failed to add event headers to message body.
Action	Check log file for more details.
EDANIW0007	Failed to process NERV Default Component "{0}" change.
Explanation	Failed to process NERV Default Component change.
Action	Check log file for more details.
EDANIW0008	Failed to configure NERV Default Component "{0}" with specified configuration properties: {1}
Explanation	Failed to configure NERV Default Component with the specified configuration properties.
Action	Check NERV configuration.
EDANIW0009	Failed to configure NERV Default Component "{0}" with specified configuration properties: {1}
Explanation	Failed to configure NERV Default Component with the specified configuration properties.
Action	Check NERV configuration.

EDANIW0010	Failed to update NERV Default Component "{0}".
Explanation	Failed to update NERV Default Component.
Action	Check NERV configuration and log file for more details.
EDANIW0012	Failed to register service "{0}" because NERV component "{1}" does not configure a webMethods Broker or Universal Messaging connection.
Explanation	Failed to register Destination Support service because the specified NERV component does not configure a webMethods Broker or Universal Messaging connection.
Action	If you are configuring a Broker or Universal Messaging connection, double check that the configuration is correct. Otherwise ignore this message.
EDANIW0016	Failed to process a bundle lifecycle change because no bundle component updater has been set.
Explanation	NERVService Listener has not been properly initialized. Failed to process a bundle lifecycle change because no bundle component updater has been set.
Action	Restart bundle/OSGi/Product instance.
EDANIW0017	NERV component "{0}" is not properly configured. Shutting down all routes consuming from component "{1}". In order to restart the routes, please provide a valid configuration and restart your consume bundles or restart the whole OSGi instance.
Explanation	NERV component is not properly configured.
Action	Shutting down all routes consuming from specified component. In order to restart the routes, please provide a valid configuration and restart your consume bundles or restart the whole OSGi instance.
EDANIW0020	Failed to load NERV assets from "{0}". Reason: {1}
Explanation	Failed to load NERV assets from NERV asset folder.
Action	Check nervAssetFolder and log file more details.
EDANUE0000	Failed to create JNDI entry for topic "{0}".
Explanation	Failed to create JNDI entry.
Action	Check your JMS provider configuration.

EDANUE0001	No {0} instance available - no attempts will be made for creating JNDI entry for topic "{1}".
Explanation	Failed to create JNDI entry.
Action	Check your JMS provider configuration.
EDANUE0002	Failed to create topic with name "{0}" on the JMS Provider.
Explanation	Failed to create topic on the JMS Provider.
Action	Check your JMS provider configuration.
EDANUE0003	No {0} instance available - no attempts will be made for creating topic with name "{1}" on the JMS Provider.
Explanation	Failed to create topic on the JMS Provider.
Action	Check JMS Provider configuration.
EDANUE0007	{0} instance is not configured properly.
Explanation	The JNDI settings of your NERV component configuration are not correct.
Action	Check the JNDI settings of your NERV component configuration.
EDANUE0008	Mandatory property "{0}" is missing.
Explanation	Mandatory property is missing.
Action	Check your NERV configuration.
EDANUE0009	NERV default component "{0}" could not create connection factory.
Explanation	NERV default component could not create connection factory.
Action	Check your NERV configuration.
EDANUE0010	Failed to bind connection factory with name "{0}" to JNDI registry at "{1}".
Explanation	Failed to bind connection factory with name to JNDI registry.
Action	Check your JMS provider and NERV configuration.
EDANUE0011	Failed to bind topic "{0}" at "{1}".
Explanation	Failed to bind topic.
Action	Check your JMS provider configuration.

EDANUE0012	Failed to create topic "{0}" on Universal Messaging Realm server at "{1}".
Explanation	Failed to create topic.
Action	Check your JMS provider configuration.
EDANUE0013	Failed to process the specified JMS provider url: "{0}". The expected format is "{1}'{broker.name}'@'{broker.host}':'{broker.port}'".
Explanation	Failed to process the JMS provider URL.
Action	Check your NERV configuration.
EDANUE0014	No {0} instance available
Explanation	No instance of the NERV destination support service is available. This service is available only for webMethods Broker and Universal Messaging components.
Action	Check NERV configuration and make sure Universal Messaging or Broker are configured and running.
EDANUE0020	Failed to ping Universal Messaging Realm server at "{0}".
Explanation	Universal Messaging Realm server is currently unreachable.
Action	Please check your provider url configuration and make sure that a Universal Messaging Realm server is running at the specified address.
EDANUW0004	Unsupported JMS Provider. No attempts will be made for configuring the JMS Provider.
Explanation	Unsupported JMS Provider.
Action	Check documentation for the list of supported JMS Providers.
EDANUW0005	Unable to get hostname during localhost substitution operation.
Explanation	Unable to get hostname during localhost substitution operation.
Action	Check your network configuration.
EDANUW0006	Unable to configure ACL for Universal Messaging Realm channel "{0}" at "{1}'. Any subsequent JNDI operations might not work due to insufficient security permissions.
Explanation	Unable to configure ACL for Universal Messaging Realm channel.
Action	Check your Universal Messaging Realm ACL configuration.

EDANUW0023	JMS Provider URL is set to "{0}" and the hostname denotes a loopback address. Remote clients will not be able to establish a connection to the JMS server.
Explanation	This property is used for creating a connection factory that clients can look up remotely.
Action	To use NERV to connect remotely to a JMS provider, you must change the value of the JMS Provider URL property to the actual hostname of the JMS server.

14 Installer Messages

CommandLineArgs.missingMaxLogSize – You changed the default maximum log size using `-maxLogSize` but did not provide the new value for new log size. Provide the new value for the maximum log size, followed by either 'k' or 'm'.

Explanation You changed the default maximum log size using `-maxLogSize` but did not provide the new value for log size.

Action Provide the new value for the maximum log size, followed by either 'k' or 'm'.

DLInitFilesProgressPanel.cannotLoadJNI – Unable to load resource {0}. Run the installer again with a 32-bit JDK instead of a 64-bit JDK.

Explanation This message is displayed when the user uses 64-bit JDK to install an older version that did not support 64-bit JDK. The 64-bit library will be missing.

Action Run the installer again with a 32-bit JDK instead of a 64-bit JDK.

DLInitFilesProgressPanel.unsupportedPlatformInternal – The installer has requested files for {0} but no files are available for that operating system at {1}.

DLInitFilesProgressPanel.unsupportedPlatformProduction – The selected product release does not support the operating system {0} on which you are trying to install.

Explanation The user is trying to install on a platform that not supported on the current install machine.

Action The user should select a different product suite that does support the current platform.

DLJarsProgressPanel.errorImagePlatformAs400 – April 2011 and later Software AG Installers do not support creation of images for IBM AS/400 systems. The installer will now exit.

DistManInstallMain.relaunchBadJavaHome – The JDK located at {0} is version {1}, which only supports classes up to major.minor version {2}. You must execute the installer or uninstaller with a JDK that supports classes with a major.minor of at least {3}. You can use the `-javaHome` command line option to launch the uninstaller using a different JDK. The JDK located in {4} is not working; verify that the path is correct.

Explanation This message is displayed when the user gave the installer or uninstaller an alternate JDK to launch the installer or uninstaller, and the path was incorrect. See 'DistManInstallMain.relaunchNoJavaHome' for more details -- {4} is the location the user gave for the JDK installation.

Action The user should provide a proper JDK installation directory.

DistManInstallMain.relaunchJavaHomeSetText – The JDK located at {0} is version {1}, which only supports classes up to major.minor version {2}. However, you must execute the installer or uninstaller with a JDK that supports classes with a major.minor of at least {3}. Please provide a JDK installation directory that meets these requirements; the JDK located at {4} does not meet these requirements or does not exist.

Explanation This message displayed when the user provides an alternate JDK to execute the installer or uninstaller, and the given path is too old or is not a proper directory. {0} - the JDK that is running this client {1} - the current JDK version {2} the major.minor class version that this JDK supports {3} - the required major.minor {4} - the location the user gave as an alternate JDK to run the installer or uninstaller.

Action Supply a proper JDK directory.

DistManInstallMain.relaunchJavaHomeText – The JDK located at {0} is version {1}, which only supports classes up to major.minor version {2}. However, you must execute the installer or uninstaller with a JDK that supports classes with a major.minor of at least {3}. Provide a JDK installation directory that meets these requirements.

Explanation If the user tries to launch the installer or uninstaller with a JDK that is too old, this message will be shown. The user will be queried to supply an alternate location for a more recent JDK. {0} - location of the current JDK executing the installer or uninstaller {1} -- version of the current JDK {2} major.minor class version the current version of JDK supports, {3} -- the minimum that is required to execute the client classes.

Action Enter the newer JDK installation directory and the installer or uninstall will execute themselves again using that JDK.

DistManInstallMain.relaunchNoJavaHome – The JDK located at {0} is version {1}, which only supports classes up to major.minor version {2}. You must execute the installer or uninstaller with a JDK that supports classes with a major.minor of at least {3}. You can use the `-javaHome` command line option to launch the uninstaller using a different JDK.

Explanation This message is displayed when the user tries to execute the installer or uninstaller with a JDK version that is too old. This can happen, for example, if the user installs webMethods 6 (which includes JDK 1.3 or 1.3.1) and tries to run the uninstaller. The message parameters are {0} - Installation home directory for java, {2} major.minor version of the java the user used to run the installer or uninstaller {3} - the major.minor version that is required as an absolute minimum.

Action As long as the user is not using console mode and running the installer, the user can point the installer or uninstaller at a newer JDK installation; the installer or uninstaller will launch again using that JDK.

InstallDirWizardPanel.cannotFindRegistryKeys – The Software AG Uninstaller cannot find the proper registry keys for this installation and cannot continue.

LockedFilesWizardPanel.explainText – The installer has detected running processes that must be stopped before you can continue. First shut down the listed products; this might also automatically shut down other listed processes. Shut down products by stopping services or exiting applications. Do not use Task Manager. If you need shutdown instructions, see the product documentation.

SAGEnvironmentManagerUnix.configFileNotReadable – The installation user has no permissions to read the config file "{0}"! Change the permissions and try again or exit the current installation.

Explanation The message that pops up when the current installation user has no read permission for the config file '/etc/sagconf.xml' on Unix systems.

ZipManager.errorLockedFile – The process cannot access the file because another process has locked a portion of the file.

15 Integration Server Messages

0701.002E	Mobile application "{0}" version {1} is already registered.
Explanation	A mobile application with this name and version already exists.
Action	Provide a different application name or version.
0701.003E	Upload service "{0}" is not available.
Explanation	The upload service supplied during mobile sync component creation does not exist in the specified namespace.
Action	Make sure the service exists within the specified namespace and that the namespace and service name are typed correctly.
0701.004E	Download service "{0}" is not available.
Explanation	The download service supplied during mobile sync component creation does not exist in the specified namespace.
Action	Make sure the service exists within the specified namespace and that the namespace and service name are typed correctly.
0701.005E	Document type "{0}" is not available.
Explanation	The business doc type supplied during mobile sync component creation does not exist in the specified namespace.
Action	Make sure the document type exists within the specified namespace and that the namespace and document type are typed correctly.

0701.006E	Mobile sync component "{0}" is suspended and cannot be changed.
Explanation	An attempt was made to edit the mobile sync component, but changes cannot be made to a mobile sync component when the component is suspended.
Action	Disable the mobile sync component and try to edit the component again.
0701.007E	Mobile sync component "{0}" is associated with mobile application "{1}" version {2}. Remove association before deleting mobile sync component.
Explanation	An attempt was made to delete a mobile sync component that is associated with a mobile application.
Action	Remove the association between the mobile sync component and the mobile application. In the Integration Server Administrator, navigate to the Solutions > Mobile Support > Mobile Apps screen, click the name of the application to edit its associations, and deselect the mobile sync component from the Mobile Sync Component Alias list. Then, try deleting the mobile sync component again.
0701.008E	Error: {0}
Explanation	Mobile Support encountered an error while validating the namespaces for the download service, upload service, or business doc type supplied during creation of a mobile sync component.
Action	Make sure that the service or doc type exists within the specified namespace and that the entry is typed correctly.
0701.009E	Mobile application "{0}" version {1} was not found.
Explanation	Mobile Support could not find the specified mobile application and version while retrieving, updating, or deleting the mobile application or processing a synchronization request.
Action	Specify a valid mobile application and version.
0701.012E	Mobile sync component "{0}" could not be suspended. Error: {1}
Explanation	Mobile Support could not suspend the mobile sync component for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.
0701.014E	Conflict resolution rule is not valid.
Explanation	The conflict resolution rule specified during mobile sync component creation is not valid.
Action	Specify a conflict resolution rule of either "Client wins" or "Server wins".

0701.015E	Mobile sync component "{0}" already exists.
Explanation	Mobile Support could not create the mobile sync component because the specified alias already exists.
Action	Specify a different alias for the mobile sync component.
0701.016E	Mobile sync component "{0}" was not found.
Explanation	Mobile Support could not find the specified mobile sync component while retrieving, updating, enabling or disabling, or deleting the mobile sync component or associating a mobile application with the component.
Action	Specify the alias of an existing mobile sync component.
0701.022E	Mobile sync component "{0}" could not be created. Error: {1}
Explanation	Mobile Support could not create the mobile sync component for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.
0701.023E	Mobile sync component "{0}" could not be deleted. Error: {1}
Explanation	Mobile Support could not delete the mobile sync component for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.
0701.024E	Mobile sync component "{0}" could not be updated. Error: {1}
Explanation	Mobile Support could not update the mobile sync component for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.
0701.025E	Mobile sync component "{0}" could not be enabled. Error: {1}
Explanation	Mobile Support could not enable the mobile sync component for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.
0701.026E	Mobile sync component "{0}" could not be disabled. Error: {1}
Explanation	Mobile Support could not disable the mobile sync component for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.

0701.027E	Mobile sync components could not be retrieved.
Explanation	Mobile Support could not retrieve the list of mobile sync components.
Action	Check the server log for details about this error.
0701.028E	Mobile sync component "{0}" could not be retrieved. Error: {1}
Explanation	Mobile Support could not retrieve the mobile sync component for the reason indicated.
Action	Check the reason detailed in the message and take appropriate corrective action.
0701.029E	Mobile sync component "{0}" could not be deleted or edited.
Explanation	The mobile sync component cannot be deleted or edited because the component is still enabled.
Action	Disable the mobile sync component and try to edit or delete the component again.
0701.030E	Upload service "{0}" is not implementing the "{1}" specification.
Explanation	The upload service provided during mobile sync component creation is not implementing the Mobile Support upload specification.
Action	Edit the upload service to include a reference to the <code>wm.mobile.datasync.specs:uploadSpec</code> specification.
0701.031E	Download service "{0}" is not implementing the "{1}" specification.
Explanation	The download service provided during mobile sync component creation is not implementing the Mobile Support download specification.
Action	Edit the download service to include a reference to the <code>wm.mobile.datasync.specs:downloadSpec</code> specification.
0701.032E	"{0}" is not a valid Integration Server service node.
Explanation	The download or upload service specified during mobile sync component creation is not a valid Integration Server service node.
Action	Ensure that element specified for the download or upload service is an Integration Server flow service (that is, a node type of <code>NSService</code>) and not another type of element.
0701.033E	Mobile sync component state "{0}" is not valid.
Explanation	Mobile Support detected that an external attempt was made to invoke a mobile sync component that is in a state other than "enabled," "disabled," or "suspended." As a result, Mobile Support has rejected the request to invoke the mobile sync component.
Action	No action is necessary.

0701.034E	Mobile application "{0}" version {1} could not be created. Error: {2}
Explanation	Mobile Support encountered an error while associating the mobile application with a mobile sync component.
Action	Check the reason detailed in the message and take appropriate corrective action.
0701.035E	Mobile application "{0}" version {1} could not be updated. Error: {2}
Explanation	Mobile Support encountered an error while updating the mobile application.
Action	Check the reason detailed in the message and take appropriate corrective action.
0701.036E	Mobile application "{0}" version {1} could not be retrieved. Error: {2}
Explanation	Mobile Support encountered an error while retrieving details about the association between the mobile application and a mobile sync component.
Action	Check the reason detailed in the message and take appropriate corrective action.
0701.037E	Mobile applications could not be retrieved. Error: {0}
Explanation	Mobile Support encountered an error while retrieving details about the associations between mobile applications and mobile sync components.
Action	Check the server log for details and take appropriate corrective action.
0701.038E	Mobile application "{0}" version {1} could not be removed. Error: {2}
Explanation	Mobile Support encountered an error while removing the association between the mobile application and a mobile sync component.
Action	Check the reason detailed in the message and take appropriate corrective action.
0701.041E	Row identifier "{0}" is not present in business doc type "{1}".
Explanation	The business doc type does not contain the specified row identifier.
Action	When specifying row identifiers during mobile sync component creation, be sure the row identifiers are present in the specified business doc type.
0701.042E	Row identifier "{0}" must be a string or an object.
Explanation	A row identifier was provided that is not a string or an object.
Action	When specifying row identifiers during mobile sync component creation, be sure the row identifiers are strings or objects.

0701.043E	"{0}" is not a document type node.
Explanation	A business doc type was provided that is not of type NSRecord.
Action	When specifying a business doc type during mobile sync component creation, be sure the business doc type is of type NSRecord.
0701.044E	Mobile application "{0}" version {1} is not associated with the mobile sync component "{2}".
Explanation	Mobile Support could not complete the synchronization operation because the mobile application is not associated with the specified mobile sync component.
Action	In Integration Server Administrator, go to the Mobile Support > Mobile App page and associate the mobile application with the specified mobile sync component.
0701.045E	Mobile sync component "{0}" could not be suspended. Only enabled mobile sync components can be suspended.
Explanation	An attempt was made to suspend the mobile sync component, but the attempt failed because the mobile sync component was not enabled.
Action	Ensure that the mobile sync component is enabled before attempting to suspend it.
0701.046E	Requested mobile sync component "{0}" is not enabled.
Explanation	Mobile Support could not process the synchronization request because the specified mobile sync component is not enabled.
Action	In Integration Server Administrator, go to the Mobile Support > Mobile Sync Components page and enable the mobile sync component. Then, resubmit the synchronization request.
0701.047E	No mobile sync component was specified.
Explanation	Mobile Support could not process the synchronization request because no mobile sync component was specified.
Action	Ensure that the synchronization request includes a mobile sync component alias and a mobile application name and version.
0701.057E	Error occurred while processing record "{0}".
Explanation	Mobile Support encountered an error while processing the specified record.
Action	Check the server log for details and take appropriate corrective action.

0701.068E	"{0}" is not locked by thread "{1}".
Explanation	The thread attempted to unlock the specified record, but the record is not owned by the thread.
Action	Try the request again. If the issue recurs, contact Software AG Global Support.
0701.069E	Thread "{0}" could not unlock record "{1}" because record is already unlocked.
Explanation	The thread attempted to unlock the specified record, but the record was not locked.
Action	Try the request again. If the issue recurs, contact Software AG Global Support.
0701.080E	Could not refresh mobile sync component "{0}". Mobile sync component is in "{1}" state.
Explanation	Mobile Support could not refresh the mobile sync component because the component is not suspended.
Action	Suspend the mobile sync component.
0701.093E	Error occurred while initializing sync store.
Explanation	Mobile Support experienced an error while initializing the sync store.
Action	Check the server log for details and take appropriate corrective action.
0701.095E	Validation Error occurred: {0}.
Explanation	Mobile Support could not process the data row because the data that was submitted was not valid.
Action	Correct the validation error.
0701.096E	Message "{0}" skipped. Unique ID is missing.
Explanation	Mobile Support could not process the data row because the data does not contain row identifier(s).
Action	Supply one or more row identifiers.
0701.097E	Unable to synchronize the mobile device. Exception: {0}
Explanation	Mobile Support could not synchronize the mobile device for the reason specified.
Action	Check the server log for details and take appropriate corrective action.

0701.112E **Unable to save the record associated with unique ID and mobile sync component of "{0}". Exception: {1}**

Explanation Mobile Support could not save the record for the reason indicated.

Action Check the reason detailed in the message and take appropriate corrective action.

0701.113E **Unable to save record data. Exception: {0}**

Explanation Mobile Support could not save the record data for the reason indicated.

Action Check the reason detailed in the message and take appropriate corrective action.

0701.114E **Unable to write record data. Exception: {0}**

Explanation Mobile Support could not write the record data for the reason indicated.

Action Check the reason detailed in the message and take appropriate corrective action.

0701.117E **Unable to delete record associated with unique ID "{0}" and mobile sync component "{1}". Reason: {2}**

Explanation Mobile Support could not delete the record for the reason indicated.

Action Check the reason detailed in the message and take appropriate corrective action.

0701.118E **Unable to delete record associated with mobile sync component "{0}". Reason: {1}**

Explanation Mobile Support could not delete the record for the reason indicated.

Action Check the reason detailed in the message and take appropriate corrective action.

0701.119E **Unable to get records from sync store. Reason: {0}**

Explanation Mobile Support could not retrieve records from the sync store for the reason indicated.

Action Check the reason detailed in the message and take appropriate corrective action.

0701.121E **Unable to obtain connection from connection pool. Exception: {0}**

Explanation Mobile Support could not obtain a connection from the connection pool for the reason indicated.

Action In Integration Server Administrator, on the Settings > JDBC Pools screen, select the pool alias associated with the MobileSupport functional alias. On the Connection Aliases > Edit screen, increase the number of maximum connections.

0701.122E	Unable to obtain database connection from connection pool for sync store.
Explanation	Mobile Support could not obtain a connection to the database configured for the sync store.
Action	In Integration Server Administrator, on the Settings > JDBC Pools screen, test the connection from the MobileSupport functional alias to the database. Take appropriate corrective action to resolve any errors.
12.31	Invalid SAML assertion. The trust/signature validation failed with exception: {0}
Explanation	Integration Server received a SAML assertion that either failed during signature validation or it did not come from a trusted issuer.
Action	Review the request and work with the sender to correct the issues.
24.23	Central User Manager queried for group "{0}" of type {1} and returned "{2}".
24.24	Central User Manager queried for user "{0}" and returned "{1}".
24.25	Central User Manager queried for membership. User "{0}" {1} a member of "{2}".
24.26	Central User Manager found user "{0}" in "{1}" of type {2}.
24.27	Central User Manager searched for group "{0}" and returned "{1}".
24.28	Central User Manager searched for user "{0}" and returned "{1}".
53.9999	{0}
62.38	pub.flow:setResponse is using the value from parameter "{0}" because no value specified for "responseString" or "responseBytes".
96.8	JDBC Connection pool threshold {0}, {1} available for pool {2}:{3}

96.9 **JDBC Connection pool waiting threads threshold {0}, {1} threads waiting for connection for pool {2}:{3}**

ALREADY_MARKED_ROLLBACK – tran was rolled back because tran was marked for rollback

APLog.string(APLog.AP_CONNECTION_TEST_FAILED) – Test of CentraSite connection failed.

Explanation An attempt was made to connect to CentraSite, but a connection could not be made.
Action Check the connection parameters in Integration Server Administrator. Check the error log in both Integration Server and CentraSite.

ART.0114.0002E Unable to get adapter type information. Internal error.

Explanation An error occurred while fetching the list of supported services for a particular adapter.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0003E Unable to get information about adapter type {0}.

Explanation An error occurred while retrieving a service's localized deployment values (adapter name, adapter version, adapter JCA version) from the specified adapter's metadata.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0004E Error getting available packages.

Explanation An error occurred while retrieving a list of packages available for node creation.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0005E Error(s) during Adapter Runtime startup.

Explanation An error occurred during the initialization of the com.wm.pkg.art.AdapterRuntimeGlobals class.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0006E	Unable to initialize transaction manager. Transaction manager already initialized.
Explanation	WmART has attempted to initialize the Transaction Manager twice.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0007E	Unable to get managed connection factories for adapter type {0}.
Explanation	WmART was unable to obtain a list of connection factories for the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0008E	Unable to get the description and display name for connection type "{0}" of adapter type "{1}".
Explanation	An error occurred while getting the display name and description for the specified connection/listener in the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0009E	Error(s) while registering adapter type {0}.
Explanation	An error occurred while loading the specified adapter.
Action	This might be due to a connection that failed to initialize properly. Ensure that the adapter's connections can communicate with their respective resources. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0010E	Error(s) while unregistering adapter type {0}.
Explanation	An error occurred while shutting down the specified adapter's connection resources.
Action	This might be due to problems in one or more connections. Ensure that all adapter connections shut down properly when the adapter was unloaded.
ART.0114.0011E	Error occurred while Adapter Runtime was loading an adapter type. Missing required input, "{0}".
Explanation	The class name of an adapter was not present as the first item in the pipeline given to com.wm.pkg.art.deployment.Service.registerAdapterType.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0012E **Error occurred while Adapter Runtime was loading an adapter type. Unexpected adapter type object "{0}" for input "{1}".**

Explanation The class name of the object passed to `com.wm.pkg.art.deployment.Service.registerAdapterType` is not derived from `WmAdapter`.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0013E **Error occurred while Adapter Runtime was loading adapter type "{0}".**

Explanation An error occurred while loading the specified adapter.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0014E **Error occurred while Adapter Runtime was unloading an adapter type. Missing required input, "{0}".**

Explanation The class name of an adapter was not present as the first item in the pipeline given to `com.wm.pkg.art.deployment.Service.unregisterAdapterType`.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0015E **Error occurred while Adapter Runtime was unloading an adapter type. Unexpected adapter type object "{0}" for input "{1}".**

Explanation The class name of the specified object passed to `com.wm.pkg.art.deployment.Service.unregisterAdapterType` is not derived from `WmAdapter`.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0016E **Error occurred while Adapter Runtime was unloading adapter type "{0}".**

Explanation An error occurred while loading the specified adapter.

Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0017E	Error occurred while registering XidFactory for adapter type "{0}".
Explanation	WmART was unable to locate the Transaction Manager or Transaction ID Factory class for the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0018E	Unable to get XidFactories for adapter type "{0}".
Explanation	WmART was unable to locate the class loader while retrieving the Transaction ID Factory map for the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0019E	Unable to get XidFactory {0} for XAResource {1} in adapter type "{2}".
Explanation	WmART was unable to determine the corresponding XidFactory class for the specified XAResource class while loading the adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0020E	Error occurred while loading online help system for adapter type "{0}".
Explanation	An error occurred while WmART was attempting to fetch the path to the specified adapter's online help file.
Action	Ensure that a help page key exists in your AdapterResourceBundle for ADKGLOBAL.RESOURCEBUNDLEKEY_LISTRESOURCES, ADKGLOBAL.RESOURCEBUNDLEKEY_LISTCONNECTIONTYPES, ADKGLOBAL.RESOURCEBUNDLEKEY_LISTPOLLINGNOTIFICATIONS, ADKGLOBAL.RESOURCEBUNDLEKEY_LISTPOLLINGNOTIFICATIONDETAILS, and ADKGLOBAL.RESOURCEBUNDLEKEY_ABOUT.
ART.0114.0021E	Error occurred while loading copyright for adapter type "{0}".
Explanation	Failed to read a third-party copyright file for the specified adapter.
Action	If you have explicitly specified ADKGLOBALS.RESOURCEBUNDLEKEY_THIRDPARTYCOPYRIGHTURL in the adapter's resource bundle, ensure that the file this key references is in the pub directory in the adapter's directory tree. Also ensure that this file is readable by Integration Server.

ART.0114.0022E	Error in {0}. Missing or invalid parameter: {1}.
Explanation	A value was not specified for the parameter of the specified method.
Action	If you explicitly invoked the specified method, check your parameter values and resubmit. Otherwise, look in the error log for related errors.
ART.0114.0030E	Unable to create node {0} in the namespace.
Explanation	WmART failed to create the specified connection or listener node in the namespace.
Action	The connection/listener information you provided in Integration Server Administrator is invalid, or perhaps duplicates an existing connection/listener in the same namespace. Refer to adjacent log entries for specifics.
ART.0114.0031E	Unable to update node {0}. Package not found.
Explanation	WmART attempted to save changes to the specified namespace node, but could not determine its package.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0032E	Unable to update resource {0}.
Explanation	An error occurred when updating a value in the specified namespace.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0033E	Invalid folder name {0}.
Explanation	While creating a new connection node, a null folder name was passed to <code>com.wm.pkg.art.util.ServiceHelper.checkInterfaceName</code> .
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0034E	Unable to create folder {0}.
Explanation	WmART was unable to create the specified folder in the adapter's namespace.
Action	Ensure that the folder name conforms to naming conventions in your server's local file system, and that Integration Server has permissions to create folders under the packages folder. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0035E	Unable to create record for {0}.
Explanation	An error occurred in ServiceHelper.createRecordFromBean while creating an NSRecord from the specified object. Adjacent log messages might contain additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0036E	Unable to create folder for service {0}.
Explanation	An error occurred in ServiceHelper.registerService while creating the file system infrastructure for the specified adapter service. Adjacent log messages might contain additional details.
Action	Ensure that the local operating system access permissions within the Integration Server packages folder will allow WmART to create folders and files dynamically.
ART.0114.0037E	Unable to create service {0}.
Explanation	An error occurred in ServiceHelper.registerService while registering the adapter service. Adjacent log messages might contain additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0038E	Unable to create flow {0}.
Explanation	An error occurred in ServiceHelper.createFlowService. Adjacent log messages might contain additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0040E	Unable to create interaction input record.
Explanation	An error occurred in RecordFactoryBridgeImpl.createInputRecord while creating a mapped Record. Adjacent log messages might contain additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

- ART.0114.0041E Unable to create input record. createMappedRecord() returned {0}.**
Explanation A call to RecordFactory.createMappedRecord returned an object of the specified class rather than a WmRecord or IDataCodable object.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0042E Unable to convert interaction output record into IData. Output record is {0}.**
Explanation RecordFactoryBridgeImpl.createOutputData was passed an instance of the specified class rather than a WmRecord, IData, or IDataCodable instance.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0050E Unable to convert string to specific data type. The data type is not specified or the string value is null.**
Explanation While configuring a new connection or listener, WmART detected that the type or value of one of the connection's properties is null.
Action Ensure that you enter values for all required properties. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0051E Unable to convert string to specific data type. Unsupported data type {0}.**
Explanation You omitted a value when configuring a connection or listener property from Integration Server Administrator.
Action Reconfigure the connection/listener, entering valid values for all properties on the Integration Server Administrator page.
- ART.0114.0053E Unable to convert string array to specific data type array. The data type is not specified.**
Explanation While configuring a new connection or listener, WmART detected that the type of a property array is null.
Action This condition indicates a coding error in the adapter or the Adapter Runtime (WmART) itself. Ensure that the adapter is handling connection and listener properties correctly. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0054E	Unable to convert string array to specific data type array. Unsupported data type {0}.
Explanation	The Adapter Runtime (WmART) has detected a property array in a connection or listener that has an unsupported data type.
Action	Change your connection/listener to use only supported data types for all properties.
ART.0114.0055E	Unable to convert string array to data type {0} array.
Explanation	An unexpected property array conversion error has occurred while configuring a connection or listener.
Action	This might be due to invalid data in a property array on the Integration Server Administrator page, such as non-numeric data in a numeric property. Reconfigure the connection/listener to ensure that the entered data matches the expected data types for all properties.
ART.0114.0056E	Unable to convert string array to primitive int array.
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java int type.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
ART.0114.0057E	Unable to convert string array to primitive long array.
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java long data type.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
ART.0114.0058E	Unable to convert string array to primitive float array.
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java float type.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
ART.0114.0059E	Unable to convert string array to primitive double array.
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java double type.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0060E	Unable to convert string array to primitive boolean array.
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java Boolean type.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
ART.0114.0061E	Unable to convert string array to primitive short array.
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java short type.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
ART.0114.0062E	Unable to convert string array to primitive char array.
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java char type.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
ART.0114.0063E	Unable to convert string array to Integer array.
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java integer instance.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
ART.0114.0064E	Unable to convert string array to Long array.
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java long instance.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
ART.0114.0065E	Unable to convert string array to Float array.
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java float instance.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.

ART.0114.0066E	Unable to convert string array to Double array.
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java double instance.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
ART.0114.0067E	Unable to convert string array to Boolean array.
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java Boolean instance.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
ART.0114.0068E	Unable to convert string array to Short array.
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java short instance.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
ART.0114.0069E	Unable to convert string array to Character array.
Explanation	A value has been entered in a connection or listener property array that cannot be converted to a Java character instance.
Action	Reconfigure the connection/listener to ensure that the data entered conforms to the expected data types for all properties.
ART.0114.0072E	Unable to set JavaBean properties.
Explanation	WmART has detected an error while setting the properties on a listener or listener notification bean.
Action	Ensure that the adapter's listener and listener notification implementations adhere to the JavaBean standard.
ART.0114.0073E	Unable to set property {0} to value {1} on class {1}.
Explanation	WmART failed to set the specified property on the specified (bean) class because it could not introspect the class.
Action	Ensure that the adapter's service template implementations adhere to the JavaBean standard. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

- ART.0114.0074E** **Property {0} not found in class {1}.**
Explanation After introspecting the specified class, WmART failed to find the specified property in that class.
Action Ensure that the adapter's service template implementations support the JavaBean standard. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0075U** **Unable to set property descriptor.**
Explanation WmART failed to introspect an unspecified bean.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0076E** **Unable to set {0} to {1} because property is not writable.**
Explanation WmART was unable to locate the "set" method for the specified property on a bean class. The property appears to be read only.
Action Ensure that the adapter's service template implementations support the JavaBean standard. To make the specified property writable, implement a "set" method for it.
- ART.0114.0077E** **Error while setting property {0} of class {1} to {2}.**
Explanation An error occurred while setting the specified property on the specified class instance.
Action Ensure that the adapter's service template implementations support the JavaBean standard. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0078E** **Unable to get JavaBean properties for {0}.**
Explanation An error occurred while reading the properties from the specified bean class.
Action Ensure that the adapter's service template implementations support the JavaBean standard. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0081E	Unable to create instance of {0}.
Explanation	WmART was unable to create a new instance of the specified class.
Action	Ensure that the adapter's service and notification template implementation classes expose a default public constructor and are not abstract. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0082E	Unable to get JavaBean property {0} of class {1}.
Explanation	WmART failed to determine or invoke the "get" method for the property in the specified class.
Action	Ensure that the adapter's service template implementations support the JavaBean standard. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0083E	Exception encountered attempting to load fix information for adapter type {0}.
Explanation	The Adapter Runtime (WmART) failed while attempting to load the installed update information for the adapter.
Action	This error is generated when an exception is caught during execution. Check the error logs for information on the original exception.
ART.0114.0084E	Missing or invalid value. {0} is not a valid value for field {1}.
Explanation	An error occurred while validating the common values for a connection pool. The common values are settings, such as, Minimum Pool Size, Maximum Pool Size, etc.
Action	Change the invalid value. Then attempt to save and enable your connection.
ART.0114.0201E	Unable to introspect "{0}". This service introspects the parameters of connection only.
Explanation	WmART failed to create a WmManagedConnectionFactory instance from the specified class name. The current WmART implementation does not allow this condition to occur.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0202E	Failure when introspecting the connection properties.
Explanation	An error occurred while introspecting connection properties. Additional details are logged.
Action	Check adjacent log messages for specific error details. Correct any problems with your connection metadata. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0203E	Unable to introspect "{0}"
Explanation	The Adapter Runtime (WmART) failed to create an instance of an adapter service, notification, or listener from the specified class name.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0204E	Unable to introspect the parameters of service template.
Explanation	An error occurred while attempting to introspect a template or listener. Additional details are logged.
Action	Ensure that the adapter's implementation .class files are installed properly under the packages folder. If you modify the .class files for the adapter while the Integration Server is running, you must reload that adapter.
ART.0114.0205E	Unable to lookup the resource domain values.
Explanation	This is a general processing error message. Details should appear in adjacent log messages.
Action	Refer to the Action column for the accompanying messages.
ART.0114.0206E	Connection alias was not specified in "{0}".
Explanation	The connection, adapter, or listener could not be found in the request to the specified method.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0207E	The connection alias "{0}" does not support webMethods metadata extensions. The adapter could be a third-party adapter.
Explanation	The specified connection alias is not derived from com.wm.adk.cci.connection.WmConnection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0208E	The connection alias "{0}" isn't configured or failed.
Explanation	WmART failed to create a ConnectionDataNode instance based on the specified connection alias.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0209E	Cannot get the connection instance of connectionAlias "{0}".
Explanation	An error occurred while creating a WmConnection instance from the specified connection alias. Additional details are provided in adjacent log messages.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0213E	Cannot get the listener instance of listenerNode "{0}".
Explanation	The method getListenerAdapterMetadata in com.wm.pkg.art.metadata.ConnectionMetadataService failed to locate and create a listener object for the specified listener node.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0216E	Unable to validate the resource domain value.
Explanation	An error occurred while validating a resource domain. This is a general processing error message. Details should appear in adjacent log messages.
Action	Refer to the Action column for the accompanying messages.

- ART.0114.0218E** **Failure when introspecting the parameters of the notification listener.**
Explanation WmART failed to lookup a resource domain. Additional details should appear in adjacent log messages.
Action Ensure that the adapter's implementation(s) of WmNotification.fillWmTemplateDescriptor sets resource domains correctly.
- ART.0114.0219E** **Failure when validating the resource domain "{0}". Null checkValues returned.**
Explanation WmART was unable to locate internal check values for the specified resource domain.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0220E** **Error occurred when closing the connection handle.**
Explanation An error occurred when closing a connection. Additional details are logged.
Action Ensure that the connection is configured properly and is able to communicate with the back-end resource. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0221E** **No adapter type name specified in "{0}".**
Explanation The specified method in com.wm.pkg.art.metadata.ConnectionMetadataService failed to retrieve connection metadata because no adapter name was provided.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0222E** **No class name of WmManagedConnectionFactory specified in "{0}".**
Explanation The specified method in com.wm.pkg.art.metadata.ConnectionMetadataService failed to retrieve connection metadata because no connection factory class name was provided.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0225E	Cannot get the connection handle of "{0}".
Explanation	WmART failed to create a WmConnection instance based on the specified connection alias.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0226E	No class name of service template specified in "{0}".
Explanation	The specified method failed to retrieve metadata from an adapter template, notification template, or listener because no service class was provided in the request.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0227E	No resource domain name specified in "{0}".
Explanation	The specified method failed because no resource domain was provided in the request.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0228E	No statement specified in "{0}".
Explanation	The specified method in com.wm.pkg.art.metadata.InteractionMetadataService failed because the AdapterRuntimeGlobals.STATEMENT value was not provided in the request.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0230E	Unable to get the list of service template metadata.
Explanation	The method getInteractionAdapterMetadataList in com.wm.pkg.art.metadata.InteractionMetadataService failed because the list of service templates supported by a connection was not provided in the request.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0231E	Unable to get the list of notification template metadata.
Explanation	An error occurred in <code>com.wm.pkg.art.metadata.InteractionMetadataService.getNotificationAdapterMetadataList</code> . This is a general processing error message. Details should appear in adjacent log messages.
Action	Refer to the Action column for the accompanying messages.
ART.0114.0232E	Unable to get the adapter type "{0}".
Explanation	The method <code>getConnectionAdapterMetadata</code> in <code>com.wm.pkg.art.metadata.ConnectionMetadataService</code> was unable to create a <code>WmAdapterType</code> instance using the specified adapter name.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0233E	Unable to get the connection type "{0}".
Explanation	The method <code>getConnectionAdapterMetadata</code> in <code>com.wm.pkg.art.metadata.ConnectionMetadataService</code> was unable to create a connection factory using the specified class name.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0234E	Unable to get a connection for resource "{0}".
Explanation	<code>WmART</code> failed to create a <code>WmConnection</code> instance based on the specified connection alias.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0235E	Error in {0}. Missing parameter: {1}.
Explanation	The method in <code>com.wm.pkg.art.metadata.InteractionMetadataService</code> failed to retrieve notification metadata because the specified request parameter was missing.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0236E	The connectionAlias or listenerNodeName must be specified.
Explanation	The method in com.wm.pkg.art.metadata.InteractionMetadataService failed to lookup/validate notification values because neither the connection node alias nor the listener node was provided in the request.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0237E	Value for parameter missing: {0}.
Explanation	The operation input requires the metadata parameter listed in the message text, but the value was not provided.
Action	Add the metadata property and a value to the operation inputs and resubmit.
ART.0114.0238E	Value for parameter {0} does not match data type {1}.
Explanation	The value submitted with the operation input does not match the metadata parameter listed in the message text.
Action	Change the type of the value for the operation and resubmit.
ART.0114.0239E	Number of fields does not match number of types in a record definition.
Explanation	The operation input requires a field type and a field name for each output field specification.
Action	Ensure that the number of entries in the array of values for the field names and field types are equal and resubmit.
ART.0114.0240E	Parameter missing: {0}.
Explanation	The operation input is missing the required parameter listed in the message text.
Action	Ensure that the input contains an entry for the parameter and resubmit.
ART.0114.0241E	Unrecognized parameter {0} specified.
Explanation	The operation input contains the parameter listed in the message text, which is not defined for this template.
Action	Remove the parameter from the operation input and resubmit.

ART.0114.0242E	Required parameter "{0}" is missing, or has no value.
Explanation	The operation is missing a required parameter.
Action	Provide the missing parameter value, and resubmit the operation.
ART.0114.0243E	Failed to run {0} service. Details provided in error log.
Explanation	An exception was caught while executing the service.
Action	Look in the error log for details on the original exception.
ART.0114.0244E	Resource domain "{0}" is not recognized by provider "{1}".
Explanation	The specified resource domain is not registered for the template.
Action	This error should only be encountered while using the webMethods ADK for adapter development. If you are developing an adapter, ensure that the specified resource domain is registered for your template. If you are not developing an adapter, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0245E	Failed to update IO properties in template "{0}"
Explanation	An exception was caught while updating IO properties in the specified template.
Action	Look in the error log for details on the original exception.
ART.0114.0300	Unable to start transaction {0}.
Explanation	An error occurred during the initiation of a transaction.
Action	Make sure that there is connectivity to the adapter backend, and that the connection associated with the transaction is enabled.
ART.0114.0301E	Unable to commit transaction. A transaction name must be specified.
Explanation	WmART failed to determine the name of a transaction.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0302E	Error while committing transaction {0}. The transaction in progress is {1}.
Explanation	The transaction name does not match the specified connection state.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0303E	Unable to commit transaction.
Explanation	An error occurred while committing a transaction.
Action	If the adapter uses a connection that supports LocalTransaction, ensure that it is implemented properly. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0304E	Unable to rollback transaction. A transaction name must be specified.
Explanation	WmART failed to determine the name of a transaction.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0305E	Error while rolling back transaction {0}. The transaction in progress is {1}.
Explanation	The specified transaction name does not match the specified connection state.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0306E	Unable to rollback transaction.
Explanation	An error occurred while committing a transaction.
Action	If the adapter uses a connection that supports LocalTransaction, ensure that it is implemented properly. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.0307E	Retryable Error during commit transaction.
Explanation	An unexpected system error occurred while committing a transaction. The transaction can be re-tried.
Action	Ensure that the back-end resource for the transaction can be reached from the server and is in a valid state. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

- ART.0114.0350E** **Unable to set transaction timeout to {0} seconds.**
Explanation WmART has detected that an XAResource failed to set the transaction timeout to the specified number of seconds.
Action Verify that the back-end resource for the transaction can be reached from the server and is in a valid state. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0351E** **Unable to create Transaction Manager.**
Explanation WmTransactionManagerFactory failed to create a TransactionManager.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0352E** **Unable to create Transaction Manager with transaction timeout set to {0} seconds.**
Explanation WmTransactionManagerFactory failed to create a TransactionManager with the specified number of timeout seconds.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0353E** **Unable to set transaction timeout. Invalid timeout value {0}.**
Explanation com.wm.pkg.art.transaction.Service.setTransactionTimeout could not cast the specified object to type Integer.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0114.0700E** **Errors occurred in cluster coordination repository access for {0}.**
Explanation An exception was caught during processing.
Action Look in the error log for details on the original exception.
- ART.0114.0701E** **Unable to retrieve ART instance/session ID.**
Explanation The Adapter Runtime (ART) session ID failed to initialize.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.0702E	Errors occurred attempting to stop {0}. See error log for details.
Explanation	An exception was caught when attempting to stop the notification.
Action	Look in the error log for details on the original exception.
ART.0114.0703E	Errors occurred attempting to confirm cluster member. See error log for details.
Explanation	An exception was caught trying to validate Adapter Runtime (ART) cluster members.
Action	Look in the error log for details on the original exception.
ART.0114.0704E	Internal Error-assert failed - node: {0}, detail:{1}.
Explanation	An unexpected exception occurred during processing.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, error logs with the stack trace exposed, and the detail in this error message.
ART.0114.0705E	Errors occurred attempting to start {0}. See error log for details.
Explanation	An exception was caught when attempting to start the notification.
Action	Look in the error log for details on the original exception.
ART.0114.0707E	"{0}" is an invalid setting for the cluster coordination mode of {1}. Valid values: {2}.
Explanation	An unsupported mode was encountered.
Action	Change the mode to one of the supported settings, and restart the notification.
ART.0114.0708E	{0} is an invalid setting for max process time of {1}. Value must be a number between {2} and {3}.
Explanation	An invalid maximum process time was encountered for the notification.
Action	Change the maximum process time to a value within the specified range, and restart the notification.
ART.0114.0709E	{0} is an invalid setting for max setup time of {1}. Value must be a number between {2} and {3}.
Explanation	An invalid maximum setup time was encountered for the notification.
Action	Change the maximum setup time to a value within the specified range, and restart the notification.

ART.0114.0710E	Adapter cluster properties files are not the same across the cluster. Please synchronize all cluster properties files and restart servers.
Explanation	The Adapter Runtime encountered inconsistent cluster property files.
Action	Ensure the cluster property files are the same for the adapter on each clustered Integration Server.
ART.0114.0711E	Notification {0} was unexpectedly removed from cluster.
Explanation	Another instance of this notification erroneously determined that this current instance failed. The current instance was removed.
Action	Check the logs on other servers in the cluster. A log on one of the servers will include message 1405, which indicates that this instance was removed. Check clock synchronization and network connectivity between the two servers.
ART.0114.0712E	Operation failed because notification {0} was unexpectedly removed from cluster.
Explanation	Another instance of this notification erroneously determined that this current instance failed. The current instance was removed. Note that this error is similar to ART.0114.0711E; however, in this case the node was changing states.
Action	Check the logs on other servers in the cluster. A log on one of the servers will include message 1405, which indicates that this instance was removed. Check clock synchronization and network connectivity between the two servers.
ART.0114.1004E	Parameter parsing error.
Explanation	WmART attempted to encrypt or decrypt a null string value.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.1005E	Parameter parsing error.
Explanation	WmART failed to encrypt a string value.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.1006E	Parameter parsing error.
Explanation	WmART failed to decrypt a string value.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0114.1008D	Jar file {0} is not an update jar file. Unable to read the {1} entry.
Explanation	This message applies to adapters that use update jar files to deliver updates. The update.cnf file is not readable in the update jar file.
Action	No action is required.
ART.0114.1009D	Jar file {0} is not an update jar file. It does not contain the {1} entry.
Explanation	This message applies to adapters that use update jar files to deliver updates. The update.cnf file is missing from the update jar file.
Action	No action is required.
ART.0114.1010D	File {0} is not an update file. It is not a jar file.
Explanation	This message applies to adapters that use update jar files to deliver updates. A file was found in the adapters update directory that is not a jar file.
Action	No action is required.
ART.0114.1011D	Error initializing UpdateFile. Missing required parameter.
Explanation	This message applies to adapters that use update jar files to deliver updates. A null value was supplied for the file name parameter. A value is required.
Action	No action is required.
ART.0114.1012D	No updates found for adapter: {0}.
Explanation	No installed updates were found for the adapter.
Action	No action is required.
ART.0114.1013E	Unable to locate the package name for adapter: {0}.
Explanation	The Integration Server package name for the adapter could not be determined.
Action	Ensure the adapter package depends on the WmART package, and reload the adapter package.
ART.0114.1014W	Adapter {0} is missing required fix {1}.
Explanation	This message applies to adapters that use update jar files to deliver updates. A fix required by the adapter was not found.
Action	Install the required fix, and reload the adapter.

ART.0114.1015E	Error loading update jar file {0}. An exception was encountered loading the {1} file.
Explanation	This message applies to adapters that use update jar files to deliver updates. An exception occurred trying to load the update.cnf file in the update jar.
Action	Look in the error log for details on the original exception.
ART.0114.1016E	Error loading update jar file {0}. The {1} file is missing the required property updateName.
Explanation	This message applies to adapters that use update jar files to deliver updates. The update.cnf file associated with the fix is missing a required value.
Action	Re-apply the fix, and reload the adapter.
ART.0114.1017E	Error loading update jar file {0}. The update name contains the illegal character ';'.
Explanation	This message applies to adapters that use update jar files to deliver updates. The fix name in the update.cnf file contains an illegal semicolon (;) character.
Action	Re-apply the fix, and reload the adapter.
ART.0114.1018E	Error loading update information. The '{0}' tag is missing.
Explanation	The fix name is missing.
Action	Re-apply the fix, and reload the adapter.
ART.0114.1019E	Illegal value is set for page size in watt.art.page.size - "{0}".
Explanation	An invalid value was specified for the watt.art.page.size parameter. This parameter must be a positive integer greater than or equal to 1.
Action	Set the value of watt.art.page.size to an integer greater than or equal to 1.
ART.0114.1020	Error while storing/retrieving/removing the password for the connection "{0}".
Explanation	An error occurred while storing, retrieving or removing the password for the connection from the Integration Server passman store. The error can occur when creating, updating, or deleting an adapter connection respectively.
Action	Make sure that the latest fix is installed on Integration Server. Try to restart Integration Server and perform the operation again. Also, make sure that the package containing the connection is imported properly into Integration Server.

ART.0114.1103E	Facility {0} - {1} error. Log handler not found.
Explanation	WmART failed to get a Log Handler from the Integration Server for the specified facility.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.1105E	No LogProducer for facility {0} - {1}.
Explanation	WmART attempted to log a message, but no Log Producer exists for the specified facility.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.1106E	Facility {0} - {1} error. No facilities registered.
Explanation	WmART failed to get the list of facility codes from the Log Handler.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.1112E	Unable to instantiate class {1} in adapter {0}. See error log for details.
Explanation	An exception occurred trying to instantiate a template for the adapter.
Action	Ensure package dependencies are set correctly, and reload the adapter
ART.0114.1113E	Class {0} is not a Service or Notification template class.
Explanation	An invalid class was registered as a template.
Action	If you are using the webMethods ADK to develop an adapter, ensure your class is properly registered and coded to be a template. If this message is being issued from a webMethods adapter, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0114.1401W	Coordination data for {0} is invalid. Coordination will revert to a default state.
Explanation	Coordination data in the repository was not valid. If the server was recently upgraded, this might simply represent a change in record formats, and the operation you are performing will automatically correct the data for you. If you have not recently upgraded or the problem persists, it is likely that the repository is corrupted.
Action	If you recently performed a server upgrade, no action is required. If you have not recently upgraded or the problem persists, check repository logs for errors.

ART.0114.1405W	Processing for {0} on server {1} has timed-out or failed. Local instance will take over.
Explanation	Remote failure detected.
Action	Check logs on indicated server for messages ART.0114.0711E or ART.0114.0712E. If the messages are in the log, refer to those error messages for a resolution. If the messages do not appear in the logs, no action is required.
ART.0114.1407W	Illegal overlap occurred in node {0}. Please verify clock synchronization with cluster member '{1}'
Explanation	An illegal overlap exception was detected.
Action	Ensure the clocks are synchronized for all Integration Servers in the cluster.
ART.0114.1411E	Unable to access {0} file for adapter "{1}". Please check the file permissions. Running with default configuration.
Explanation	The cluster property file could not be read.
Action	Ensure the cluster property file exists and is readable for the specified adapter.
ART.0114.1412E	Unable to parse {0} file for adapter "{1}". Please correct file format. Running with default configuration.
Explanation	The cluster property file could not be parsed.
Action	Validate the cluster property file format for the specified adapter.
ART.0114.1415E	An internal error occurred while rendering cluster settings for adapter {0}. Updated settings will not be persisted.
Explanation	The settings could not be saved to the cluster property file.
Action	Ensure the directory and the cluster file are writable.
ART.0114.1416E	Error attempting to save cluster settings for adapter {0}. Error {1}
Explanation	An exception occurred trying to save the cluster settings.
Action	Look in the error log for details on the original exception.
ART.0114.1418W	Illegal overlap occurred in node {0}. Please increase setup timeout. Current setting: {1}, actual time: {2} seconds
Explanation	The requested operation took longer than the allotted time; the operation had no other errors.
Action	Increase the node's timeout value as indicated by the actual time.

ART.0114.1419W	Illegal overlap occurred in node {0}. Please increase execute timeout. Current setting: {1}, actual time: {2} seconds
Explanation	A polling operation took longer than the allotted time; the polling operation had no other errors.
Action	Increase the node's timeout value as indicated by the actual time.
ART.0115.3202E	Listener error releasing connection for {0}. Error: {1}.
Explanation	An error occurred while closing the connection associated with the specified listener.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3203E	Error creating listener object: Null argument on init call.
Explanation	The method WmNotificationListener.initListenerNodeProperties was passed a null ListenerNode instance.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3204E	Error creating listener object: NSName null.
Explanation	The method WmNotificationListener.initListenerNodeProperties was unable to derive the name of a listener node from the ListenerNode instance.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3207E	Illegal event type received: {0}.
Explanation	The method WmNotificationListener.doNotify was passed the specified invalid event ID.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3208E	Error during listener event. Error: {0}.
Explanation	An error occurred while processing a listener event. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3209E	Error creating listener object {0}. Error: {1}.
Explanation	An error occurred creating the specified listener or initializing its properties.
Action	Ensure that the listener and its properties are configured correctly. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3211E	Existing transaction rolled back before execution of {0}.
Explanation	WmART detected an incomplete transaction for the specified listener prior to executing it. The transaction has been rolled back.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3212E	Listener error during execution of {0}. Error: {1} rolling back existing transaction.
Explanation	WmART detected an incomplete transaction for the specified listener prior to executing it. WmART attempted to rollback the transaction, but failed. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3213E	Listener error during execution of {0}. Error: {1} checking transaction.
Explanation	WmART failed to determine whether the specified listener has an open transaction. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3214E	Listener {0} not Found.
Explanation	WmART failed to lookup the specified listener.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3215E	Unable to create listener {0}. Listener node already exists.
Explanation	There was an attempt to create a duplicate listener node.
Action	Enter a new listener node name that is unique to its folder.
ART.0115.3217E	Error creating listener object: {0}. Invalid package name: {1}.
Explanation	ListenerManager.createListener failed to create an instance of the listener because it could not find the package name in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3218E	Error creating listener object: {0}. Invalid node name.
Explanation	ListenerManager.createListener failed to create an instance of the listener because the specified node name is missing or invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3219E	Error creating listener object: {0}. Error: {1}.
Explanation	An error occurred while creating the listener. This might be due to an invalid listener node name. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3220E	Unable to get list of listener types supported by node {0}.
Explanation	An error occurred in ListenerManager.queryListenerTemplatesSupported for the specified adapter. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3221E	Unable to get listener node properties {0}.
Explanation	An error occurred while querying the specified listener's properties. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3223E	Unable to update listener {0}: Error: {1}.
Explanation	An error occurred while updating the specified listener's properties. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3225E	Unable to delete listener {0}: Error: {1}.
Explanation	An error occurred while deleting the specified listener. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3226E	Unable to copy listener {0}: Error: {1}.
Explanation	An error occurred while copying the specified listener. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3227E	Unable to copy listener. Error: Source nodeName is required.
Explanation	The method ListenerManager.copyAdapterListener failed because the source listener node name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3228E	Unable to copy listener {0}. Error: newNodeName is required.
Explanation	The method ListenerManager.copyAdapterListener failed because the destination listener node name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3229E	Unable to copy listener {0}. Error: publishableDocumentName is required.
Explanation	The method ListenerManager.copyAdapterListener failed because the destination listener publishable document name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3230E	Unable to copy listener {0}. Error: newPkg is required.
Explanation	The method ListenerManager.copyAdapterListener failed because the destination listener node package name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3231E	Unable to copy listener {0} to {1}. Error: Unable to get source listener node.
Explanation	The method ListenerManager.copyAdapterListener failed because the source listener node name is invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3232E	Unable to copy listener {0}. Error: New name already exists {1}.
Explanation	The method ListenerManager.copyAdapterListener failed because the specified destination listener node name already exists in the package.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3235E	Unable to rename listener {0}. Error: {1}.
Explanation	An error occurred while renaming the specified listener. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3236E	Unable to find listener {0}.
Explanation	The method ListenerManager.queryListenerStatistics failed because it could not locate the specified listener node.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3237E	Unable to get listener {0}. Error: Listener class name is not specified.
Explanation	The method ListenerNode.getListener failed because it could not locate the WmConnectedListener implementation class name.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3238E	Error in Listener Callback:{0} notification {1}.
Explanation	An error occurred while processing a listener notification event for the specified listener. If there is a callback name in the error message, it corresponds to the notification event.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3239E	Missing required parameter on service: {0}
Explanation	The specified parameter is not present in the pipeline. This is an internal error.
Action	Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3240E	Unable to retrieve listener data. No listener name specified.
Explanation	The method ARTAdmin.retrieveListenerData failed because no listener was present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3241E	Error retrieving listener: {0}. Error: {1}
Explanation	An error occurred while retrieving information about the listener. Refer to the error text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3242E	Unable to get listener properties for adapter: {0}, listener type: {1}.
Explanation	An error occurred while retrieving properties of the listener in the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3243E	Error retrieving listeners. Missing parameter: {0}
Explanation	The method ARTAdmin.retrieveListeners failed because the adapter name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3244E	Error setting listener status. Missing parameter: {0}
Explanation	The method ARTAdmin.setListenerStatus failed because the listener name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3245E	Error retrieving listener types. Missing parameter: {0}
Explanation	The method ARTAdmin.retrieveListenerTypes failed because the adapter name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3246E	Error retrieving listener types. Error: {0}
Explanation	An error occurred while retrieving the listener types supported by an adapter. Refer to the error text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3247E	Error deleting listener. Missing parameter: {0}
Explanation	The method ARTAdmin.deleteListener failed because the listener name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3248E	Error deleting listener: {0}. Unable to find the node.
Explanation	The method ARTAdmin.deleteListener failed because the specified listener node name is invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3249E	Error deleting listener: {0}.
Explanation	An error occurred while deleting the specified listener. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3250E	Error setting properties for listener: {0}.
Explanation	An error occurred while setting the properties of the specified listener. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0115.3251E	Invalid listener node name: {0}.
Explanation	The specified listener name is missing or invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3252E	Unable to commit transaction for listener {0}. Error: {1}.
Explanation	WmNotificationListener failed to commit a transaction for the specified listener. Refer to the error text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3253E	Listener {0} did not process notification.
Explanation	The listener received a notification and was unable to find a listener notification to process it.
Action	Check to ensure that the listed listener has listener notifications registered with it and that at least one of them is enabled.
ART.0115.3255E	Unable to start listener: {0}. Cannot retrieve connection from connection node: {1}
Explanation	The listener requires a connection to start. The startup processing could not get a connection from the listed connection node.
Action	Check to ensure that the listed connection is enabled. If the connection is pooled, increase the maximum connections allowed in the pool.
ART.0115.3256E	Unable to start listener: {0}. Error: {1}
Explanation	An unexpected exception occurred while trying to enable a notification.
Action	Check the Integration Server error log for details on the unexpected exception.
ART.0115.3257E	Exceeded max retries. Shutting down listener {0}. Error: {1}
Explanation	A retryable error occurred while attempting to execute the listener. The maximum number of retries is exceeded.
Action	Check the Integration Server error log for details on the retryable exception. Correct the error and try to enable the listener.

ART.0115.3258E	Fatal error in listener {0}. See error log for details
Explanation	An unexpected exception occurred during listener operation.
Action	Check the Integration Server error log for details on the unexpected exception.
ART.0115.3259E	Unable to enlist connection transactional resource
Explanation	An unexpected exception occurred while trying to start a transaction within the listener.
Action	Check the Integration Server error log for details on the unexpected exception. If no related exceptions are found, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0115.3260E	Unable to commit transaction for listener {0}. Listener disabled
Explanation	An unexpected exception occurred while trying to commit a transaction within the listener.
Action	Check the Integration Server error log for details on the unexpected exception.
ART.0115.3261E	Connection Node {0} not enabled.
Explanation	An error occurred while trying to retrieve a connection for the listener.
Action	Check to ensure the connection is enabled and restart the listener.
ART.0115.3262E	Fatal error initiating transaction in listener {0}. See error log for details
Explanation	An unexpected exception occurred while trying to start a transaction within the listener.
Action	Check the Integration Server error log for details on the unexpected exception.
ART.0115.3263E	Connection error while retrieving metadata in listener {0}. See error log for details
Explanation	An error occurred while trying to retrieve a connection for the listener.
Action	Check to ensure the connection is enabled. Check the Integration Server error log for more information about the connection error.
ART.0115.3264E	Unable to stop listener: {0}. Error: {1}
Explanation	An unexpected exception occurred while trying to stop the listener.
Action	Check the Integration Server error log for details on the unexpected exception.

ART.0115.3265E	Errors occurred. {0} listeners were not suspended. See error log for details.
Explanation	While attempting to suspend all listeners, some of the listeners reported errors.
Action	Look in the error log for details on the specific exceptions.
ART.0115.3266E	Errors occurred. {0} listeners were not enabled. See error log for details.
Explanation	While attempting to enable all suspended listeners, some of the listeners reported errors.
Action	Look in the error log for details on the specific exceptions.
ART.0115.3267E	Cannot update adapter-defined settings in suspended listener {0}.
Explanation	The user attempted to update adapter-defined settings for a listener; however, the listener is currently suspended.
Action	Disable the listener, and retry the operation.
ART.0115.3268E	{0} is in an invalid state for requested operation.
Explanation	The user attempted an operation on a listener; however, the listener was not in the proper state for the operation.
Action	Change the state of the listener to an acceptable state, and retry the operation.
ART.0115.3269E	Unable to complete update. Setting connection for listener {0} is not supported.
Explanation	The user attempted to change the connection associated with a listener; however, the listener does not require a connection.
Action	This operation is not supported.
ART.0115.3270E	Unable to create listener. Setting connection for listener type {0} is not supported.
Explanation	The user attempted to create a listener with a connection; however the listener does not require a connection.
Action	This operation is not supported.
ART.0115.3271E	Unable to create listener. Must specify connection for listener type {0}.
Explanation	A user attempted to create a listener that requires a connection; however no connection was specified.
Action	Specify a connection, and retry the operation.

ART.0115.3272E	Unable to identify adapter for listener type {0}.
Explanation	Integration Server cannot determine the adapter associated with the specified listener type.
Action	Ensure your package dependencies are set properly. Reload the adapter package, and retry the operation.
ART.0115.3712E	Error during listener execution.
Explanation	Either a fatal error has occurred while executing a listener, or the maximum number of non-fatal errors has been exceeded while executing a listener.
Action	Ensure that the connection from the listener to the back-end EIS is still valid, and that a communications path between them exists.
ART.0115.3716W	Failed to retrieve connection for callback in listener {0}. Error: {1}
Explanation	An error occurred while trying to retrieve a connection for the listener shutdown callback processing.
Action	Check to ensure the connection is enabled. Check the Integration Server error log for details on the unexpected exception.
ART.0115.3717W	Failure in shutdown callback in listener {0}. Error: {1}
Explanation	An error occurred during the listener shutdown callback processing.
Action	Details on the error are included in the message. The shutdown will attempt to continue.
ART.0116.3001E	Notification error during execution of {0}. Error: {1}.
Explanation	An error occurred while executing the specified notification. Refer to the text in the error message for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3002E	Notification error releasing connection for {0}. Error: {1}.
Explanation	WmART failed to release the specified notification's connection back to the connection pool.
Action	For custom adapters, check the connection's implementation for possible blocking situations. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3003E	Error creating notification object: Null argument on init call.
Explanation	The method WmNotification.initNotificationNodeProperties failed because it was passed a null NotificationNode object.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3004E	Error creating notification object: NSName null.
Explanation	The method WmNotification.initNotificationNodeProperties failed because it was unable to get the node name from the NotificationNode object.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3005E	Error creating notification object: {0}. Publishable Document name not set.
Explanation	The method WmNotification.initNotificationNodeProperties failed because it was unable to get the publishable document node name for the specified notification.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3006E	Error creating notification object: {0}. UUID not set.
Explanation	The method WmNotification.initNotificationNodeProperties failed because it was unable to get the specified notification's universal unique identifier (UUID) from the NotificationNode object.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3007E	Illegal event type received: {0}.
Explanation	The method WmNotification.notifyEvent was passed the specified invalid event ID.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3008E	Error during notification event. Error: {0}.
Explanation	An error occurred in the method WmNotification.notifyEvent. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3009E	Error creating notification object {0}. Error: {1}.
Explanation	An error occurred in the method NotificationNode.getNotification while creating the notification. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3010E	Error publishing notification {0}. Error: {1}.
Explanation	An error occurred in the method WmAsynchronousNotification.publishToDispatcher while publishing a non-duplicate document from the specified notification. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3011E	Existing transaction rolled back before execution of {0}.
Explanation	WmART detected an incomplete transaction for the notification prior to processing a notification event. The transaction has been rolled-back.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3012E	Notification error during execution of {0}. Error: {1} rolling back existing transaction.
Explanation	WmART detected an incomplete transaction for the specified notification prior to processing a notification event. It attempted to rollback the transaction, but failed. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3013E	Notification error during execution of {0}. Error: {1} checking transaction.
Explanation	WmART failed to determine whether the specified notification has an open transaction. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3014E	Notification {0} not Found.
Explanation	WmART failed to locate the specified notification.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3015E	Unable to create notification {0}. Notification node already exists.
Explanation	WmART failed to create the specified notification because a notification with this name already exists.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3016E	Unable to create publishable document {0}. Error: {1}.
Explanation	The method NotificationFactory.createPublishableDocument failed to create a document for the specified notification. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3018E	Error creating notification object: {0}. Invalid node name.
Explanation	The specified notification node name is missing or improperly formatted.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3019E	Error creating notification object: {0}. Error: {1}.
Explanation	An error occurred while creating the specified polling or listener notification. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3020E	Unable to get list of notification types supported by node {0}.
Explanation	An error occurred in NotificationManager.queryNotificationTemplatesSupported for the specified adapter. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3021E	Unable to get notification node properties {0}.
Explanation	An error occurred while querying the specified notification's properties. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3022E	Unable to update notification {0}. Error: Notification must be disabled.
Explanation	NotificationManager received a request to update the properties of an active notification.
Action	Disable the notification from Integration Server Administrator prior to updating it.
ART.0116.3023E	Unable to update notification {0}.
Explanation	An error occurred while updating the notification's properties. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3024E	Unable to delete notification {0}. Error: Notification must be disabled.
Explanation	NotificationManager received a request to delete an active notification.
Action	Disable the notification from Integration Server Administrator prior to deleting it.
ART.0116.3025E	Unable to delete notification {0}.
Explanation	An error occurred while deleting the specified notification. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3026E	Unable to copy notification {0}.
Explanation	An error occurred while copying the specified notification. See adjacent error messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3027E	Unable to copy notification {0}. Error: nodeName is required.
Explanation	The specified notification node name is missing or incorrectly formatted.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3031E	Unable to copy notification {0}. Error: Invalid node name {1}.
Explanation	Notification Manager failed to validate the specified node name. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3032E	Unable to copy notification {0}. Error: New name already exists {1}.
Explanation	The method NotificationManager.copyAdapterNotification failed because the specified destination notification node name already exists in the package.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3033E	Unable to copy notification {0}. Error: New document name already exists {1}.
Explanation	The method NotificationManager.copyAdapterNotification failed because the specified new publishable document name already exists in the package.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3034E	Unable to rename notification {0}. Error: Notification must be disabled.
Explanation	NotificationManager received a request to rename an active notification.
Action	Disable the notification from Integration Server Administrator prior to renaming it.
ART.0116.3035E	Unable to rename notification {0}. Error: {1}.
Explanation	An error occurred while renaming the notification. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3036E	Unable to find notification {0}.
Explanation	The method NotificationManager.queryNotificationStatistics failed because the specified notification could not be located in the namespace.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3037E	Unable to get notification {0}. Error: Notification class name is not specified.
Explanation	The method NotificationNode.getNotification failed to determine the implementation class name for the specified notification.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3038E	Error in Notification Callback:{0} notification {1}.
Explanation	An error occurred in method WmNotification.notifyEvent while processing the specified callback.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3039E	Missing required parameter on service: {0}
Explanation	The method NotificationManager.queryNotificationTemplatesSupported failed because the adapter name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3040E	Error creating notification object: {0}. Missing parameter: {1}.
Explanation	NotificationManager failed to create the notification because the specified parameter was not in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3041E	Error creating notification object: {0}. Invalid Package Name {1}.
Explanation	NotificationManager failed to create the notification because the specified package name is invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3042E	Error creating notification object: {0}. Invalid Service Name {1}.
Explanation	NotificationManager failed to create the notification because the service name is missing, improperly formatted, or otherwise invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3043E	Error deleting notification object. Invalid node name: {0}.
Explanation	The specified notification node name is missing or incorrectly formatted.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3044E	Error deleting notification object: {0}. Error: {1}.
Explanation	NotificationManager failed to validate the specified node name. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

- ART.0116.3045E** **Error deleting notification object: {0}. The specified node is not a Listener Notification node.**
- Explanation** NotificationManager.deleteListenerNotification was called to delete the specified notification, which is a polling notification, not a listener notification.
- Action** This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
-
- ART.0116.3046E** **Unable to create document {0}. Error: {1}.**
- Explanation** An error occurred while creating a document for the specified notification. Refer to the error message text for more details.
- Action** This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
-
- ART.0116.3047E** **Unable to create notification {0}. Error deleting an existing record: {1}.**
- Explanation** NotificationFactory failed to create the notification because it could not delete existing document records. Refer to the error message text for more details.
- Action** This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
-
- ART.0116.3048E** **Unable to create notification {0}. The specified Listener does not exist: {1}.**
- Explanation** NotificationManager.createListenerNotification failed to create the notification because it could not locate the corresponding listener node. Refer to the error message text for more details.
- Action** This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
-
- ART.0116.3049E** **Unable to create notification {0}. The specified notification template is not synchronous: {1}.**
- Explanation** NotificationFactory failed to create the notification because the underlying specified implementation class is not derived from WmSynchronousNotification. Refer to the error message text for more details.
- Action** This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3050E	Unable to create notification {0}. The specified notification template is not asynchronous: {1}.
Explanation	NotificationFactory failed to create the specified notification because the underlying specified implementation class is not derived from WmAsynchronousNotification. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3051E	Unable to query properties for {0}. Invalid node name.
Explanation	The specified notification node name is missing or improperly formatted.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3052E	Unable to query properties for {0}. Error: {1}.
Explanation	NotificationManager failed to validate the node name. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3053E	Unable to update notification {0}. Invalid node name.
Explanation	The specified notification node name is missing or incorrectly formatted.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3054E	Unable to update notification {0}. Error: {1}.
Explanation	NotificationManager failed to validate the node name. Refer to the error message text for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3055E	Error copying notification: {0}. Missing parameter: {1}.
Explanation	NotificationManager failed to copy the notification because the specified parameter was not in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3056E	Error copying notification: {0}. Invalid Package Name {1}.
Explanation	NotificationManager failed to copy the notification because the specified package name is invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3057E	Error updating notification object: {0}. Missing parameter: {1}.
Explanation	NotificationManager failed to update the notification because the specified parameter was not in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3058	Unable to copy notification {0}. Error: New node name is invalid {1}.
Explanation	Invalid connection name specified.
Action	Remove any unsupported special characters from the connection name.
ART.0116.3059	Error trying to enable notification {0}. Error: Listener not found {1}.
Explanation	The error occurs when trying to enable or disable a listener notification, and the associated listener is not available.
Action	Make sure that the associated listener is not deleted. If the associated listener is deleted, create the listener again with the same name.
ART.0116.3060E	Error setting notification schedule property {0}
Explanation	An unexpected exception occurred while trying to set the schedule parameter listed in the message.
Action	Check the Integration Server error log for details about the unexpected exception.

ART.0116.3061E	Unable to move notification. Error: Invalid node name {0}.
Explanation	The name of the notification you are trying to move is invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3062E	Unable to move notification {0}. Error: Invalid Node Name Format.
Explanation	The name of the notification listed in the message text is not in folder:nodename format.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3063E	Error moving notification: {0}. Error: Missing parameter: {1}.
Explanation	The move operation is missing the required parameter listed in the message text.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3064E	Error moving notification: {0}. Error: Invalid Package Name {1}.
Explanation	The name of the destination package for the move operation is invalid on Integration Server.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3065E	Unable to move notification {0}. Error: Src/Dest Node names not the same.{1}
Explanation	The notification node name was changed during the move operation.
Action	Only the package name and folder are allowed to change during a move operation, while the actual node name is not allowed to change. This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3066E	Unable to move notification {0}. Error: Notification must be disabled.
Explanation	This notification cannot be moved because it is enabled. To move a notification, it first must be disabled.
Action	In Integration Server Administrator, disable the notification and retry the move operation.

ART.0116.3067E	Unable to move notification {0}.
Explanation	An unexpected exception occurred while trying to move a notification.
Action	Check the Integration Server error log for details about the unexpected exception.
ART.0116.3068E	Unable to move notification {0}. Error: nodeName is required.
Explanation	The node name specified for the move operation is either missing or invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3069E	Unable to move notification {0}. Error: New node name is invalid {1}.
Explanation	The new node name specified for the move operation is either missing or invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3100	Unable to obtain list of polling notifications for adapter type.
Explanation	The adapter type passed is null or invalid while retrieving, suspending, or resuming the adapter notifications.
Action	Ensure that a valid adapter type is passed.
ART.0116.3101E	Unable to obtain detailed information for polling notification.
Explanation	The method ARTAdmin.retrievePollingNotificationData failed because the notification name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3102E	Unable to set status for polling notification.
Explanation	The method ARTAdmin.forceNotificationDisable failed because the notification name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3103E	Unable to set schedule for polling notification.
Explanation	The method ARTAdmin.setNotificationSchedule failed because the notification name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3104E	Unable to retrieve listener notification list. Missing parameter: {0}
Explanation	The method ARTAdmin.retrieveListenerNotifications failed because the adapter name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3105E	Unable to set notification status. Missing parameter: {0}
Explanation	The method ARTAdmin.setNotificationStatus failed because the notification name was not present in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3106E	Unable to set notification status. Notification not found: {0}
Explanation	The method ARTAdmin.setNotificationStatus failed because it was unable to locate the node for the specified notification.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3107E	Unable to set notification status for {0}. Error: {1}
Explanation	The method ARTAdmin.setNotificationStatus failed because it was unable to enable or disable the specified listener notification.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0116.3108E	Unable to publish notification. Message ID {0} exceeds maximum length of {1}.
Explanation	The message ID specified by the adapter is longer than the allowed maximum length.
Action	Integration Server restricts the length of the message ID for a published document. Contact Software AG Global Support to see how to increase this setting. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0116.3115E	Errors occurred. {0} notifications reported errors while attempting to suspend. See error log for details.
Explanation	While attempting to suspend all notifications, some of the notifications reported errors.
Action	Look in the error log for details on the specific exceptions.
ART.0116.3116E	Errors occurred. {0} notifications were not enabled. See error log for details.
Explanation	While attempting to enable all suspended notifications, some of the notifications reported errors.
Action	Look in the error log for details on the specific exceptions.
ART.0116.3117E	Non-fatal errors encounter while disabling notification {0}. Details recorded in error log.
Explanation	An exception was encountered during the disable callback for a notification.
Action	Look in the error log for details on the specific exception.
ART.0116.3118E	Non-fatal errors encounter while suspending notification {0}. Details recorded in error log.
Explanation	An exception was encountered during the suspend callback for a notification.
Action	Look in the error log for details on the specific exception.
ART.0116.3119E	Non-fatal errors encounter while stopping notification {0}. Details recorded in error log.
Explanation	An exception was encountered during the shutdown callback for a notification.
Action	Look in the error log for details on the specific exception.

ART.0116.3120E	{0} is not a valid node type for this operation.
Explanation	An attempt was made to change the connection associated with a polling notification; however, the specified node is not a polling notification node.
Action	Select a polling notification node, and retry the operation.
ART.0116.3121E	{0} is in an invalid state for the requested operation.
Explanation	An attempt was made to perform an operation on a notification; however, the notification was not in the correct state. Typically this occurs when you attempt to perform an update type of operation when the notification is not in a disabled or suspended state.
Action	Change the state of the notification to disabled or suspended, and retry the operation.
ART.0116.3533	Error while executing Polling Notification {0}. Check if the notification is present in all clusters.
Explanation	The error occurs when a polling notification does not exist on all nodes in an Integration Server cluster.
Action	Make sure that all clustered Integration Server nodes have the same set of adapter polling notifications.
ART.0117.4000E	Unable to invoke adapter service {0}. Unable to establish connection to connection {1}.
Explanation	WmART failed to create or locate the connection object associated with the specified adapter service.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4001E	Unable to invoke adapter service {0}. Connection.createInteraction() returned null.
Explanation	WmART failed to create a new instance of WmInteraction for the specified adapter service.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4002E	Unable to invoke adapter service {0}.
Explanation	An error occurred while running the specified adapter service and processing its output. Additional information might appear in adjacent log messages.
Action	Determine whether the implementation of the adapter's WmAdapterService.execute method is throwing an exception at run time, and correct as needed.
ART.0117.4005E	Connection not available.
Explanation	WmART failed to locate the connection data node for the specified connection and adapter service. This message will always appear in conjunction with 117.4020.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4006E	Invalid adapter type {0}.
Explanation	WmART failed to create an instance of the specified adapter service. This message will always appear in conjunction with 117.4021.
Action	Ensure that the implementation class for the adapter service is installed correctly in the package. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4007E	Unable to get record factory bridge.
Explanation	WmART failed to create or locate an input/output record factory bridge object.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4008E	Unable to get connection factory from connection.
Explanation	WmART failed to locate the connection factory associated with a ConnectionResource.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4009E	Unable to get record factory required for interaction input.
Explanation	An error occurred while locating a RecordFactory associated with a ConnectionFactory. Additional details might appear in adjacent log messages.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4010E	Unable to get adapter record factory. ConnectionFactory.getRecordFactory() returned null.
Explanation	WmART failed to locate a RecordFactory associated with a ConnectionFactory.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4011E	Unable to connect to resource {0}. The resource is already being used in a parent transaction.
Explanation	WmART attempted to create a new connection to the specified resource, but detected that the resource is currently enrolled in an ongoing transaction.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4012E	Unable to run adapter service. Error occurred when connecting to resource {0}.
Explanation	An error occurred while creating a new connection to the specified resource. Additional details might appear in adjacent log messages.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4013E	Internal Error: Unable to nest connection states.
Explanation	WmART attempted to start a new transaction, but detected that a parent transaction already exists.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4014E	Error while starting nested transaction. The name {0} is already in use.
Explanation	WmART attempted to start a new transaction, but detected that the specified transaction ID is already in use.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

- ART.0117.4015E** **Error(s) occurred while closing adapter connections.**
Explanation Error(s) occurred while closing one or more connections involved in a transaction. Separate log messages are listed for each connection.
Action Ensure that all EIS resources used in the transaction can communicate with the adapter. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0117.4018E** **Error while closing transactions at service completion Error:{0}.**
Explanation The specified error occurred while closing the connections involved in a successful transaction.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0117.4019E** **Error while rolling back transaction Error:{0}.**
Explanation The specified error occurred while closing the connections involved in a failed transaction.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0117.4020E** **Unable to invoke adapter service {0}. Connection resource {1} not found.**
Explanation WmART failed to locate the connection data node for the specified connection and adapter service.
Action This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
- ART.0117.4021E** **Unable to invoke adapter service {0}. Unable to get adapter service template.**
Explanation WmART failed to create an instance of the specified adapter service.
Action Ensure that the implementation class for the adapter service is installed correctly in the package. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4022E	Unable to invoke adapter service {0}. Unable to get connection state.
Explanation	WmART failed to determine the connection state for the specified adapter service. This will prevent a resource connection from being created.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4023E	Unable to properly handle adapter connection error for connection {0}.
Explanation	WmART was unable to successfully handle an error that occurred on the specified connection while executing a service.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4024E	Unable to invoke adapter service {0}. An error occurred on connection {1}. Unable to recover from connection error.
Explanation	An error occurred in the error handling logic while invoking the specified service. Additional details might appear in adjacent log messages.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4026E	Unable to rollback transaction Error:{0}.
Explanation	The specified error occurred while marking a failed transaction for rollback.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4027E	Unable to create adapter service {0}. Invalid package name {1}.
Explanation	WmART failed to create the specified adapter service because it could not locate the Package object for the specified package name.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4028E	Unable to create adapter service {0}. Invalid service name.
Explanation	WmART failed to create the specified adapter service because the service node name is missing or invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4029E	Unable to create adapter service {0} with connection {1}. Connection not found.
Explanation	WmART AdapterServiceManager failed to create the adapter service because it could not locate the ConnectionDataNode object for the connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4030E	Unable to create adapter service {0}.
Explanation	An error occurred while creating the specified adapter service. Additional details should appear in adjacent log messages.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4032E	Unable to find adapter service {0}.
Explanation	WmART failed to locate the namespace node (NSNode) for the adapter service.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4033E	Retryable Error while closing transactions at service completion Error:{0}.
Explanation	The specified retryable run-time exception occurred while completing a successful service invocation.
Action	Ensure that all EIS resources used in the transaction can communicate with the adapter. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0117.4034E	Retryable Error(s) occurred while closing adapter connections.
Explanation	One or more retryable errors have occurred while closing connections used in a transaction. Additional log messages might be listed.
Action	Ensure that all EIS resources used in the transaction can communicate with the adapter. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4035E	Error while completing service listener Error:{0}.
Explanation	An error occurred while calling method <code>com.wm.pkg.art.transaction.ServiceListener.listenComplete</code> .
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4036E	Unable to commit transaction. Transaction state:{0} .
Explanation	WmART was unable to commit a transaction because the transaction was in the specified, unexpected state.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0117.4037E	Unable to invoke adapter service {0}. Unable to create Input record.
Explanation	An unexpected exception occurred during the adapter service execution.
Action	Check the Integration Server error log for details on the unexpected exception.
ART.0117.4038E	Unable to delete adapter service {0}.
Explanation	An unexpected exception occurred trying to delete the adapter service.
Action	Check the Integration Server error log for details on the unexpected exception.
ART.0117.4039E	Unable to update adapter service {0}.
Explanation	An unexpected exception occurred trying to update the adapter service.
Action	Check the Integration Server error log for details on the unexpected exception.

ART.0117.4040E	Unable to create adapter service {0}. Adapter service node already exists.
Explanation	It is illegal to create an adapter service with the same folder and node name.
Action	Use a different name for the adapter service and retry the create operation.
ART.0117.4048E	Unable to update adapter service {0}.
Explanation	An exception was encountered while attempting to update the adapter service.
Action	Check the Integration Server error log for details on the original exception.
ART.0117.4049E	Unable to retrieve connection from resource {0}. See error log for details.
Explanation	An exception was encountered while trying to retrieve a connection.
Action	Check the Integration Server error log for details on the original exception.
ART.0118.5000E	Unable to retrieve and process connection properties from pipeline.
Explanation	WmART failed to process a connection's properties. Additional log messages might be listed.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5001E	Error processing connection property {0}. Unable to get property name.
Explanation	WmART failed to locate an expected connection property in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5002E	Error processing connection property {0}. Invalid value entered. The minimum string length is {1}.
Explanation	The size of the specified connection property value is less than the specified minimum size.
Action	Reconfigure the connection from Integration Server Administrator using values that are within the constraints set by the connection.

ART.0118.5003E	Error processing connection property {0}. Invalid value entered. The maximum string length is {1}.
Explanation	The value of the specified property is not valid.
Action	Reconfigure the connection from Integration Server Administrator using values that are within the constraints set by the connection.
ART.0118.5004E	Error processing connection property {0}.
Explanation	An error occurred when converting a connection property value to its internal Java representation. Additional log messages might be listed.
Action	Reconfigure the connection from Integration Server Administrator ensuring that all data entered conforms to the underlying types in the connection class. If the problem persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5005E	Unable to configure connection properties. Error occurred while processing connection properties.
Explanation	This is a general processing error message. See adjacent log messages for details.
Action	Refer to the Action column for the accompanying messages.
ART.0118.5006E	Unable to get list of connections for adapter type: {0}.
Explanation	An error occurred while retrieving the list of configured connections for the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5007E	Unable to get list of connection types for adapter type: {0}.
Explanation	An error occurred while retrieving the list of connection factories for the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5008E	Unable to get properties for connection {0}.
Explanation	An error occurred while retrieving the configuration details for a specific connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5009E	Unable to get connection properties for adapter: {0}, connection type: {1}.
Explanation	An error occurred while retrieving the connection properties for the specified connection factory and adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5010E	Invalid connection name. The connection name must have a valid folder name and node name.
Explanation	An invalid folder and/or connection name was entered on the Integration Server Administrator Configure Connection Type page.
Action	Re-enter the new connection type information making sure that the Folder Name and Connection Name fields have valid entries.
ART.0118.5011E	Unable to create new connection {0}.
Explanation	An error occurred while configuring a new connection type.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5012E	Unable to update connection {0}.
Explanation	An error occurred while editing the connection type.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5013E	Unable to find connection {0}.
Explanation	WmART was unable to locate the specified connection while deleting it.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5014E	Unable to delete connection {0}.
Explanation	An error occurred while deleting a connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5015E	Unable to get connection manager properties.
Explanation	An error occurred while getting a list of Connection Manager properties.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5016E	Unable to get configured values for connection manager.
Explanation	An error occurred while processing Connection Manager property values.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5017E	Error occurred while getting connection manager properties.
Explanation	This is a general processing error message. See adjacent log messages for details.
Action	Refer to the Action column for the accompanying messages.
ART.0118.5018E	Error getting connection properties.
Explanation	An error occurred while fetching connection property values.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5019E	Error getting connection metadata. Missing required parameter: adapterTypeName.
Explanation	WmART was unable to determine the adapter type name while processing a connection's metadata.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5020E	Unable to process connection properties. Internal error.
Explanation	WmART failed to set properties for a connection node. The expected connection form fields were not found in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5021E	Unable to process connection properties. Internal error.
Explanation	WmART failed to get properties for a connection node. The expected connection form fields were not found in the pipeline.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5022E	Cannot create connection {0}. Adapter type {1} does not exist.
Explanation	WmART failed to start the specified connection because it was unable to locate the specified adapter type.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5023E	Unable to configure connection manager. No connection manager properties provided.
Explanation	WmART was unable to validate Connection Manager properties because they were null.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5024E	Unable set connection {0} state to {1}. Invalid state specified.
Explanation	WmART was unable to modify the connection's state because the intended state is missing or invalid.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5025E	Unable to enable connection {0}.
Explanation	This is a general processing error message. See adjacent log messages for details.
Action	Refer to the Action column for the accompanying messages.
ART.0118.5026E	Unable to stop connection {0}.
Explanation	This is a general processing error message. See adjacent log messages for details.
Action	Refer to the Action column for the accompanying messages.
ART.0118.5027E	Unable to enable connection {0}. Connection is already enabled or is being shutdown.
Explanation	WmART is enabling a connection that is not currently in a disabled state.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5028E	Unable to shutdown connection{0}. Connection is already disabled or in the process of being shutdown.
Explanation	WmART is attempting to shut down a connection that is not currently in an enabled state.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5029E	Unable to disable connection {0}. Connection is already disabled.
Explanation	WmART is attempting to disable a connection that is already disabled.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5030E	Unable to create connection {0}. Package {1} does not exist.
Explanation	WmART was unable to create the connection node because it could not locate the specified package.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5031E	Unable to delete connection {0}. Internal error.
Explanation	An error occurred while deleting the specified connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5032E	Unable to set connection resource properties. Internal error: ConnectionPropertiesBridge not found.
Explanation	WmART failed to create a configured managed connection factory because it could not locate the WmConnectionPropertiesBridge instance needed to set its properties.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5033E	Error disabling connection resources.
Explanation	An error occurred while stopping the connection resources. See adjacent log messages for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5034E	Connection type {0} does not exist in adapter {1}.
Explanation	WmART was unable to locate the specified connection factory in the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5035E	Unable to create connection {0}. Internal error occurred while creating connection factory of type {1}.
Explanation	WmART was unable to create the specified connection factory for the connection. See adjacent log messages for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5036E	Unable to configure connection manager.
Explanation	WmART was unable to create a Connection Manager. See adjacent log messages for more details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5037E	Cannot create ResourceAdapterMetaData object. CCI Connection Factory is not an instance of WmConnectionFactory.
Explanation	The method ConnectionDataNodeManager.createCCIConnectionFactory could not get the ResourceAdapterMetaData object for a connection factory.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5040E	Unable to get adapter service templates for connection {0}.
Explanation	WmART failed to locate any adapter service templates for the specified connection.
Action	Do not configure an adapter service with a connection for which no adapter service templates exist. Try another connection.
ART.0118.5041E	Unable to get connection status for connection resource {0}.
Explanation	WmART was unable to obtain connection state information for the specified connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5042E	Unable to enable connection resource {0}.
Explanation	This is a general processing error message. See adjacent log messages for details.
Action	Refer to the Action column for the accompanying messages.
ART.0118.5043E	Unable to disable connection resource {0}.
Explanation	This is a general processing error message. See adjacent log messages for details.
Action	Refer to the Action column for the accompanying messages.

ART.0118.5044E	Unable to shutdown connection resource {0}.
Explanation	This is a general processing error message. See adjacent log messages for details.
Action	Refer to the Action column for the accompanying messages.
ART.0118.5046E	Unable to get a connection to resource {0}. Resource not available.
Explanation	WmART could not locate a connection factory for the specified connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5047E	Unable to get a connection to resource {0}. Internal error occurred while restarting connection.
Explanation	An error occurred while creating the connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5048E	Unable to get adapter service templates for connection resource {0}.
Explanation	WmART failed to locate any adapter service templates for the connection.
Action	Do not configure an adapter service with a connection for which no adapter service templates exist. Try another connection.
ART.0118.5049E	Unable to reset adapter connection {0}. Connection {1} is not supported.
Explanation	The method <code>ConnectionResource.handleAdapterConnectionException</code> reports that the specified connection class is not derived from <code>WmConnection</code> .
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5050E	Unable to reset adapter connection {0}. Unable to configure connection manager.
Explanation	The method <code>ConnectionResource.handleAdapterConnectionException</code> was unable to locate the <code>ConnectionManager</code> or <code>ConnectionManagerPropertiesBridge</code> for this connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5051E	Unable to reset adapter connection {0}. Adapter type {1} does not exist.
Explanation	The method <code>ConnectionResource.handleAdapterConnectionException</code> was unable to determine the adapter type for this connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5052E	Unable to create connection. Connection resource {0} is restarting.
Explanation	The method <code>ConnectionResource.createConnection</code> has been called against a connection resource in the restarting state.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5053E	Unable to get a connection to resource {0}.
Explanation	WmART failed to create a connection because it could not communicate with the back-end connection resource.
Action	Check independently that the target resource is communicating and that it can be reached from the connection. If the condition persists, contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5054E	Unable to reset adapter connection {0}.
Explanation	An error occurred while trying to restart the specified connection. See adjacent log messages for additional details.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5055E	Unable to get adapter service templates for connection resource {0}.
Explanation	The method <code>ConnectionResourceState.getInteractionSpecsSupported</code> failed to locate the <code>ResourceAdapterMetaData</code> associated with specified connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5056E	Unable to create connection for connection resource {0}, connection type {1}.
Explanation	The method <code>ConnectionResourceState.createConnection</code> failed to get the <code>Connection</code> object for the specified connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5057E	Adapter Runtime was unable to initialize {0} connection resources for the adapter "{1}".
Explanation	<code>com.wm.pkg.art.ns.ConnectionDataNodeManager.startConnectionResources</code> detected failures in starting connection nodes for the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5058E	Adapter Runtime was unable to stop {0} connection resources for the adapter "{1}".
Explanation	<code>com.wm.pkg.art.ns.ConnectionDataNodeManager.stopConnectionResources</code> detected failures in shutting down connection nodes for the specified adapter.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5059E	Adapter Runtime was unable to stop connection resources for the {0} adapter types.
Explanation	<code>com.wm.pkg.art.ns.ConnectionDataNodeManager.stopAllConnectionResources</code> detected failures in shutting down connection nodes.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5060E	Unable get properties for connection resource {0}.
Explanation	An error occurred while fetching the specified connection's properties.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5061E	Unable to configure Connection Manager: Poolable property not set.
Explanation	WmART failed to determine whether a connection should be pooled.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5062E	Unable to find connection {0}: error {1}.
Explanation	An error was encountered while validating the specified connection.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.
ART.0118.5063E	Unable to start connection {0}: after {1} attempt(s).
Explanation	The startup of a connection pool has exceeded the maximum number of retries.
Action	Check the Integration Server error log for details on the retryable exception.
ART.0118.5064E	Cannot reconfigure connection {0}: it must be disabled first.
Explanation	To update a connection, it must be disabled.
Action	Disable the connection and retry the update operation.
ART.0118.5065E	Cannot delete connection {0}: it must be disabled first.
Explanation	To delete a connection, it must be disabled.
Action	Disable the connection and retry the delete operation.
ART.0118.5066E	Exception encountered processing {0} connection callback method. The {1} operation will proceed.
Explanation	An exception was encountered while executing the specified connection callback method.
Action	Look in the error log for details on the original exception. The callback processing did proceed even though the error was encountered.
ART.0118.5067E	Unknown callback event type received on connection node: {0}
Explanation	An unknown connection callback was made.
Action	This is an internal error. Contact Software AG Global Support. Please have the following information available: system and setup specifics, journal logs, and error logs with the stack trace exposed.

ART.0118.5068E	Exception encountered processing {0} connection callback method.
Explanation	An exception was encountered while executing the specified connection callback method.
Action	Look in the error log for details on the original exception. When this error is received, the callback processing does not continue.
ART.0118.5069E	Cannot create connection factory for connection {0}. Adapter type {1} does not exist.
Explanation	The adapter associated with this connection is not registered.
Action	Verify the package dependencies are set correctly. Reload the adapter package, and retry the operation.
ART.0118.5070E	Exception encountered creating the connection factory for connection {0}.
Explanation	An exception was encountered creating the connection factory.
Action	Look in the error log for details on the original exception.
ART.0118.5071W	A non-fatal exception was encountered attempting to unregister {0}. The operation will proceed. See the error log for more details.
Explanation	An exception was encountered trying to unregister the connection node.
Action	Look in the error log for details on the original exception. The unregister processing continued.
ART.0118.5072E	Adapter service {0} cannot use connection {1}. The adapter service and connection are from different adapters.
Explanation	The user attempted to set the connection associated with an adapter service; however, the adapter service and connection were not from the same adapter.
Action	Retry the operation using a connection from the same adapter.
ART.0118.5073E	Adapter service {0} cannot use connection {1}. The connection is already being used by a listener.
Explanation	The user attempted to use a connection in an adapter service; however, the connection is already being used by a listener.
Action	Retry the operation using a connection that is not already being used by a listener.

ART.0118.5074E	"{0}" is not a valid connection name for adapter {1}
Explanation	The user attempted to use a connection in a polling notification or listener; however, the connection was not part of the same adapter.
Action	Retry the operation using a connection from the same adapter.
ART.0118.5075E	Listener {0} cannot use connection {1}. The connection is already being used by an adapter service or polling notification.
Explanation	The specified listener cannot use the specified connection because the connection is already being used by a polling notification or an adapter service.
Action	Retry the operation using a connection that is not being used by a polling notification or adapter service.
ART.0118.5076E	Polling notification {0} cannot use connection {1}. The connection is already being used by a listener.
Explanation	The user attempted to use a connection in a polling notification; however, the connection is already being used by a listener.
Action	Retry the operation using a connection that is not already being used by a listener.
ART.0118.5077E	Adapter service {0} cannot use connection {1}. The connection does not support this adapter service template.
Explanation	The user attempted to use a connection for an adapter service; however, the connection does not support the adapter service.
Action	Retry the operation using a connection that supports the adapter service.
ART.0118.5078E	Minimum pool size must not be greater than maximum pool size.
Explanation	The user attempted to set the minimum pool size to a value that is greater than the maximum pool size.
Action	Retry the operation specifying a minimum pool size that is lower than the maximum pool size.
ART.0118.5079	Exception encountered while removing {0} connection from Connection cache.
Explanation	An error occurred while invalidating a failed XA transaction.
Action	Make sure that there is connectivity to the adapter backend, and that the connection associated with the transaction is enabled. Check the server logs for transaction details.

ART.0118.5080	Exception encountered while updating connection {0}.
Explanation	An error occurred while updating a connection node from an old version to a new one.
Action	Make sure that the connection parameters are valid. Make sure that the user updating the connection has been assigned the appropriate ACL.
ART.0118.5083	Invalid value {0} specified for {1} property, hence using default value as {2}
Explanation	The value of the watt.art.connection.nodeVersion watt property is invalid. Hence, when creating the connection node, the specified node version is ignored and the default value for node version is used instead.
Action	Make sure the watt.art.connection.nodeVersion property has a valid value. For details, see the Integration Server administration guide.
AUTH055	Did not add user(s) {0}. Password was empty.
Explanation	The Password field requires a value.
Action	Enter a valid password.
BAB.0002.0000E	Wrapped Exception:
Explanation	A communication failure occurred between Integration Server and a client resulting in the exception.
Action	Verify that the communication parameters are correct. Check the setup for any network issues.
BAB.0006.0001E	CommException: LinkServer closed
Explanation	A client sent a request to Integration Server after a previous connection between the client and Integration Server was closed.
Action	Make sure that the client is not designed to send new requests to Integration Server when communication with the server is closed.
BAD_AUDIT_DIRE	The value supplied for watt.server.audit.logDir does not identify an existing directory that Integration Server can write to. watt.server.audit.logDir was not changed.
Explanation	The audit log directory was not changed because the watt.server.audit.logDir parameter refers to a directory that either does not exist or Integration Server does not have permission to write to.
Action	Specify a directory that exists on the server and that Integration Server can write to. You can specify the full path name, or a relative path in relation to the Integration Server.

BAF.0000.0001E	No file or properites specified
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0002E	Illegal set_mode: {2}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0003E	FSDirCursor_encode exception
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0004E	A minimum of three log segments required only {2} found
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0005E	Unsupported BlockDevice specified: {2}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0006E	BlockDevice Exception:
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0007E	Unable to open FSData devices
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0008E	Wrong number of Data Extents:{2} != {3}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0000.0009E	Invalid dataMaxExtents specified:{2}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0010E	Invalid indexMaxExtents specified:{2}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0011E	Invalid dataMaxExtents:{2} must be between 1 and {3}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0012E	Invalid indexMaxExtents:{2} must be between 1 and {3}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0013E	Invalid dataThreshold specified:{2}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0014E	Invalid indexThreshold specified:{2}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0015E	Invalid dataThreshold:{2} must be between 50% and 99%
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0016E	Invalid indexThreshold:{2} must be between 50% and 99%
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0000.0017E	Log offset:{2} inside Superblock
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0018E	Log offset:{2} > Meta offset:{3}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0019E	Meta offset{2} > Data offset:{3}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0020E	Error during create - Data store already exists
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0021E	Exception during checkDataDevices:
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0022E	Exception during newHashCode:
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0023E	Unknown log type:{2}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0024E	NOT RETURNABLE in finalize:{2}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0000.0025E Finalizing undestroyed cursor (p={2} d={3})

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0026E No more null entries after {2} in {3}

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0027E Filesystem full ({2} < {3})

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0028E Block write failure

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0029E Unable to locate block of sufficient size

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0030E Cannot unlink last remaining empty

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0031E Data Expansion required but Maximum Data Exceeded

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0032E Index expansion requested but maximum are allocated

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0000.0033E	CreateIndexExtent, unable to alloc block
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0034E	Mismatch:{2} {3} != {4}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0046E	Warning {2} failed
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0047E	Notify() on null ref idx={2} hc={3} : {4}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0048E	Transaction has no members:{2}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0072E	Error during open - Log File does not exist
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0073E	Error during create - Log File already exists
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0074E	Error during create - Average Block Size or entries must be specified
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0000.0075E	Error during create - NumEntries exceeds size of integer
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0076E	Error during open - data file segments do not match, input {2}, output {3}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0102E	The FSData is damaged, see the journal log for details
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0000.0103E	FSData checker. Bad NULL entry chain
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0001.0035E	Fatal Runtime Exception:{2}
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0001.0036E	No open TXN for dirty entry
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0001.0037E	Filesystem is in an invalid state
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0001.0038E	Improper deleted type:{2}
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0001.0039E	Can't unlink:{2}
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0001.0040E	Can't add first empty back to empty list
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0001.0041E	FreeBytes mismatch:{2} != {3}
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0001.0042E	Out of order merge:{2} & {3}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0001.0043E	First null entry cannot be null
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0001.0044E	First empty entry cannot be null
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0001.0045E	Transaction has no members:{2}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0001.0049E	Cannot use destroyed cursor
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0001.0050E **EndTXN called outside of a transaction**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0001.0051E **AbortTXN called outside of a transaction:{2}**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0001.0052E **Log is not open**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0001.0053E **Log is not closed**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0001.0054E **Log is smaller than max block ({2} < {3})**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0001.0055E **Transaction larger than total log**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0001.0056E **Cursors already @ 0:{2}**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0001.0057E **References negative!:{2}**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0001.0058E	Entry is already unlinked!:{2}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0001.0059E	No backup to revert to:{2}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0001.0060E	Type mismatch: {2} != {3} on {4}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0001.0061E	Data length ({2}) != expected length:{3}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0001.0076E	Illegal state change from {2} to {3}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0002.0000E	Wrapped Exception:
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0003.0070E	TransactionException: Wait to start transaction interrupted
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0003.0071E	TransactionException: Resource already in a transaction
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0003.0072E TransactionException: Wait to start transaction not allowed

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0062E Data: Unable to get cursor lock

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0063E Data: Cannot get key, cursor is unpositioned

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0064E Data: Cannot get value, cursor is unpositioned

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0065E Data: Cannot get value reference, cursor is unpositioned

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0066E Data: Cursor is unpositioned

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0067E Data: Unable to delete: {2}

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0068E Data: Can not clone a destroyed cursor

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAF.0004.0069E	Data: Referenced object has been deleted
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0005.0077E	IOException: No Properties provided to JDBCBlockDev
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0005.0078E	IOException: No JDBC Driver provided to JDBCBlockDev
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0005.0079E	IOException: No URL provided to JDBCBlockDev
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0005.0080E	IOException: Unable to create table:{2}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0005.0081E	IOException: {2} JDBCBlockDevice doesn't support Logical Devices - offset:{3}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0005.0082E	IOException: {2} Attempted to write past final segment: {3}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0005.0083E	IOException: {2} Attempted to read past final segment: {3}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0005.0084E **IOException: {2} Blob length: {3} != Segment size:{4}**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0005.0085E **IOException: {2} Not Found:**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0005.0086E **IOException: {2} Unable to Connect - Retries Exhausted**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0005.0087E **IOException: All component files must be the same length**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0005.0088E **IOException: Invalid logical position specified**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0005.0089E **IOException: Read error**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0005.0090E **IOException: Write error**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0005.0091E **IOException: Invalid Physical position**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

BAF.0005.0092E	IOException: SplitExtent failed - Extent not found:{2}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0005.0093E	IOException: Unable to allocate new IBlockDevice in Device Group
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0005.0094E	IOException: Invalid Log Region detected - Timestamp mismatch
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0005.0095E	IOException: CompositeBlockDevice read error
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0005.0096E	IOException: missing {2} properties file
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0005.0097E	IOException: Illegal mode {2}. Must be 'rw' or 'r'
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0005.0098E	IOException: block device has 0 length
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0005.0099E	IOException: Unable to read {2} bytes
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAF.0005.0100E	IOException: Unable to allocate write buffer
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAF.0005.0101E	IOException: Native library unavailable
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAQ.0002.0000	Wrapped Exception:
BAQ.0003.0001	TransactionException: Resource already in a transaction
BAR.0001.1401	RuntimeException: unsupported cursor {2}
BAR.0002.0000	Wrapped Exception:
BAR.0005.1600	RepoDirCodec: DecodeParms must be called before decode
BAR.0005.1601	RepoDirCodec: Unserializable repo object
BAR.0005.1602	RepoDirCodec: Repo Must be Standalone
BAR.0006.1700	CommException: sendRequest() failed
BAR.0006.1701	CommException: ConnectionServer closed
BAR.0006.1702	CommException: Missing keyword:{2}
BAR.0010.0001	Directory: insert exception:

BAR.0010.0002	Directory: update exception:
BAR.0010.0003	Directory: rename exception:
BAR.0010.0004	Directory: get queue failed, invalid object type
BAR.0010.0005	Directory: entry version "{2}" does not exist for entry "{3}"
BAR.0010.0007	Directory: delete exception:
BAR.0010.0008	Directory: "{2}" already exists
BAR.0010.0009	Directory: entry "{2}" is not a symbolic link
BAR.0010.0011	Directory: object has been destroyed
BAR.0010.0012	Directory: null not allowed in compound directory path expression
BAR.0010.0013	Directory; key "{2}" not found
BAR.0010.0014	Directory: key "{2}" is not a repository directory
BAR.0010.0015	Directory: "{2}" can not be versioned
BAR.0010.0016	Directory: illegal state, directory may have been destroyed
BAR.0010.0017	Directory: "{2}" is an invalid symbolic link target

- BAR.0010.0018 Directory: "{2}" is a repository directory and an invalid symbolic link target

- BAR.0010.0019 Directory: "{2}" is a repository IData object and an invalid symbolic link target

- BAR.0010.0021 Directory: new key {2} can not be a compound key

- BAR.0010.0022 Directory: RepoQueue {2} can not be versioned

- BAR.0010.0023 Directory: "{2}" is a symbolic link and is invalid as a symbolic link target

- BAR.0010.0024 Directory: Entry {2} not versioned

- BAR.0010.0025 Directory: reconnect attempt failed

- BAR.0010.0026 Directory: get queue failed, object is null

- BAR.0010.0027 Directory: can not be target of an update for entry {2}

- BAR.0010.0028 Directory: invalid version number {2}

- BAR.0010.0029 Directory: invalid relative version number {2}

- BAR.0010.0030 Directory: cannot delete current version for entry {2}

- BAR.0010.0031 Directory: illegal transaction state, {2} not allowed in active transaction

- BAR.0010.0032 Directory: testAndSet failed for entry {2}:

BAR.0010.0033	Directory: testAndSet failed for entry {2} - Invalid Entry Type
BAR.0010.0034	Directory: key "{2}" is not a repository stream
BAR.0010.0035	Directory: internal error, unknown repository container type, {2}
BAR.0011.0100	Queue: constructor failure:
BAR.0011.0101	Queue: enqueue failure:
BAR.0011.0102	Queue: dequeue failure:
BAR.0012.0200	Stream: Invalid length key type: {2}
BAR.0012.0201	Stream: DataException: {2}
BAR.0012.0202	Stream: Invalid Object: {2} missing {3}
BAR.0012.0203	Stream: Invalid Segments key type: {2}
BAR.0012.0204	Stream: Segment {2} not found in {3}
BAR.0012.0205	Stream: Invalid Status key type: {2}
BAR.0012.0206	Stream: EOF - Pending stream
BAR.0012.0207	Stream: {2} already open for output

- BAR.0012.0208** **Stream: {2} closed**

- BAR.0012.0209** **Stream: Error Writing byte[] to OutputStream: {2}**

- BAR.0012.0210** **Stream: Error Flushing OutputStream: {2}**

- BAR.0012.0211** **Stream: Error Closing OutputStream: {2}**

- BAR.0012.0212** **Stream: Error Reading InputStream: {2}**

- BAR.0012.0213** **Stream: Error Closing InputStream: {2}**

- BAR.0013.0300** **NameParser: missing component key**

- BAR.0013.0301** **NameParser: invalid key syntax: "{2}"**

- BAR.0013.0302** **NameParser: index missing from key "{2}"**

- BAR.0013.0303** **NameParser: index not numeric "{2}"**

- BAR.0013.0304** **NameParser: bad array index syntax "{2}"**

- BAR.0014.0400** **Illegal argument: Directory object cannot be stored**

- BAR.0014.0403** **Illegal argument: Key must be specified**

- BAR.0014.0404** **Illegal argument: Action must be ADD, DELETE, or CHANGE**

BAR.0015.0500	Session: Logon required
BAR.0015.0505	Session: RepoStream object in use, RepoAPI calls not allowed
BAR.0015.0510	Session: Invalid logon URL "{2}" specified
BAR.0015.0511	Session: No default server specified
BAR.0015.0515	Session: Active repository session, logon not allowed
BAR.0015.0516	Session: Internal Error, invalid Transaction Resource object
BAR.0015.0518	Session: Duplicate logon not allowed
BAR.0015.0519	Session: Session not logged on
BAR.0015.0520	Session: Session disabled due to LUW timeout
BAR.0015.0521	Session: Previous LUW timeout still in progress, try again later
BAR.0016.0600	Internal Error: local server connection config invalid
BAR.0016.0601	Internal Error: during server initialization exception:
BAR.0016.0603	Internal Error: connection to repository server failed, missing remote refid
BAR.0016.0604	Internal Error: Repository server shutdown failed:

- BAR.0016.0605** Internal Error: Repository server is not the primary server
- BAR.0017.0700** RepoStore: Internal Error creating Repo Server object:
- BAR.0017.0701** RepoStore: Unable to initialize Repository backing store
- BAR.0017.0702** RepoStore: Repository server has been destroyed
- BAR.0017.0703** RepoStore: Repository backing store not initialized
- BAR.0017.0704** RepoStore: Missing 'persiststore' config parm
- BAR.0018.0900** RepoConnection: Secondary server could not find primary repository server
- BAR.0018.0901** RepoConnection: Could not find primary repository server: {2}
- BAR.0018.0904** RepoConnection: Reconnect failed, no remote server cluster connection information available
- BAR.0019.1100** Transaction: Resource already participating in a transaction
- BAR.0019.1101** Transaction: Illegal transaction state, transaction destroyed
- BAR.0019.1102** Transaction: Illegal transaction state, session mismatch
- BAR.0019.1103** Transaction: Illegal transaction state, IDataSharedCuror Transactions not supported
- BAR.0019.1104** Transaction: TransactionException: Cursor has been destroyed

BAR.0020.1200	SharedCursor: illegal state, cursor destroyed
BAR.0020.1201	SharedCursor: reconnect attempt failed
BAR.0020.1202	SharedCursor: invalid resource specified
BAR.0020.1203	SharedCursor: Reconnect Exception detected
BAR.0020.1204	SharedCursor: Can not get key, cursor is unpositioned.
BAR.0020.1205	SharedCursor: Can not get value, cursor is unpositioned.
BAR.0021.1300	Queue: reconnect attempt failed
BAR.0021.1301	Queue: illegal state, queue destroyed
BAR.0021.1302	Queue: object has been destroyed
BAR.0021.1303	Queue: Repository Queue entry corrupted
BAR.0022.1400	Data: illegal state, IData destroyed
BAR.0023.1500	Migration: export not implemented in RepoMigrate, use Repov2Migrate or Repov3Migrate to export your specific Repo version
BAR.0023.1501	Migration: exception:{2}
BAR.0023.1502	Migration: Error During Import, probably Coder mismatch between Export and Import utilities: exception:{2}

BAR.0023.1503 **Migration: import not implemented in {2}, use RepoMigrate to import**

BAS.0123.0004E **FSDData checker repair attempted. Zero length file deleted. {0}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAS.0123.0007E **FSDData checker. {0} entrys not in any chain.**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAS.0123.0008E **FSDData checker repair attempted. Bad NULL list entry removed. {0}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAS.0123.0009E **FSDData checker. Entry in {0} list has bad prev pointer. {1}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAS.0123.0010E **FSDData checker. Entry in {0} list has wrong type. {1} != {2} {3}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAS.0123.0011E **FSDData checker. Duplicate entry in {0} list. {1}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAS.0123.0012E **FSDData checker. Entry in {0} list contains bad reference count. {1}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

BAS.0123.0013E	FSData checker. Data node has wrong type. {0}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAS.0123.0014E	FSData checker. Hash tree node has wrong type. {0}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAS.0123.0015E	FSData checker. Free byte count is wrong. {0} != {1}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAS.0123.0016E	FSData checker repair attempted. {0} orphaned NULLs recovered.
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAS.0123.0017E	FSData checker. Entry is in multiple chains. {0}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAS.0123.0018E	FSData checker. Repair attempted - full check will be run again.
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAS.0123.0019E	FSData checker. Attempting to recover orphaned NULL and EMPTY entries.
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAS.0123.0021E	FSData checker. Dir entry has bad last node pointer. {0}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

BAS.0123.0022E	FSDData checker repair attempted. Bad EMPTY list entry removed. {0}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
BAT.0000.0001	duplicate endpoint id {2}
BAT.0000.0002	endpoint {2} not found.
BAT.0000.0003	endpoint {2} can not be deleted it has producers/consumers with active or pending messages.
BAT.0000.0004	duplicate producer id {2}
BAT.0000.0005	producer {2} not found.
BAT.0000.0006	producer {2} can not deleted, it has active or pending messages.
BAT.0000.0007	duplicate consumer id {2}
BAT.0000.0008	consumer {2} not found.
BAT.0000.0009	consumer {2} can not deleted, it has active or pending messages.
BAT.0000.0010	duplicate message store id {2} for producer {3}
BAT.0000.0011	consumer {2} message store id {3} not found.
BAT.0000.0012	consumer {2} message store {3} can not deleted, it has active or pending messages.

BAT.0000.0013	no active transaction for message store id {2} for parent container id {3}
BAT.0000.0014	transactions not enabled for message store id {2} for parent container id {3}
BAT.0000.0015	method disabled because transactions are enabled for message store id {2} for parent container id {3}
BAT.0000.0016	consumer {2} message store {3} this method requires transactions to be enabled.
BAT.0000.0017	duplicate sequence number {2} for message id {3} in store id {4} in parent container id {5}
BAT.0000.0018	message id {2} not found in message store id {3} for parent container id {4}
BAT.0000.0019	out of sequence message seq {2}, last seq {3} id {4} in store id {5} in parent container id {6}
BAT.0000.0020	argument arrays must be same length, message store id {2} for parent container id {3}
BAT.0000.0021	invalid timeout value {2}, must be > 0
BAT.0000.0022	invalid message sequence number {2}, must be >= 0
BAT.0000.0023	invalid message acknowledge mode {2}
BAT.0000.0024	message id can not be null, {2}
BAT.0000.0025	illegal state change request from {2} to {3}

- BAT.0000.0026 {2} {3} has been closed

- BAT.0000.0027 thread has been interrupted

- BAT.0000.0028 method [{2}] is not allowed from a rejected message handler.

- BAT.0000.0029 the transient store type {2} specified could not be initialized.

- BAT.0000.0030 IData backing store is null, required

- BAT.0000.0031 IDATASTORE type requires a transacted IData implementation

- BAT.0000.0032 duplicate message for store id {2} in parent container id {3}

- BAT.0000.0033 {2} {3} is already started.

- BAT.0000.0034 {2} {3} has been stopped.

- BAT.0000.0035 Invalid reference: MessageStore[{{2}}] is null.

- BAT.0000.0036 A ISimpleQueueProducer has already been created for this SimpleQueue

- BAT.0000.0037 A ISimpleQueueConsumer has already been created for this SimpleQueue

- BAT.0000.0038 Cannot ack not allowed for a zero-or-more SimpleQueue

- BAT.0000.0039 Cannot nack not allowed for a zero-or-more SimpleQueue

BAT.0000.0040	SimpleQueue {2} not found.
BAT.0000.0041	SimpleQueue {2} can not be deleted it is not empty.
BAT.0002.0000	Wrapped Exception:
BAT.0127.0001	Recoverable Error skipped because warnonopen = continue. Db:{0} Error:{1}
BAT.0127.0002	Recoverable Error encountered but warnonopen = fail. Db:{0} Error:{1}
BAT.0127.0003	Error deleting damaged data file. Db:{0} Error:{1}
BAT.0127.0004	Error renaming damaged data file. Db:{0} Error:{1}
BAT.0127.0005	Error re-creating damaged data file. Db:{0} Error:{1}
BAT.0127.0006	Damaged data file renamed. Db:{0} renamed:{1}
BAT.0127.0007	Damaged data file deleted. Db:{0}
BAT.0127.0008	Damaged data file re-created. Db:{0}
BAT.0127.0009	Error during checkDataDevice. Db:{0} Error:{1}
BAT.0127.0010	Damaged data file detected. Db:{0} Error:{1}
BAT.0127.0011	Data file resize required. Db:{0}

BAT.0127.0012 Error cleaning up resized Data file. Db:{0} Error:{1}

BAT.0127.0013 Error creating resized Data file. Db:{0} Error:{1}

BAT.0127.0014 Error copying resized Data file. Db:{0}

BAT.0127.0015 Error renaming original data file. Db:{0} Error:{1}

BAT.0127.0016 Error closing resized data file. Db:{0} Error:{1}

BAT.0127.0017 Error renaming resized data file. Db:{0} Error:{1}

BAT.0127.0018 Error restoring original data file. Db:{0} Error:{1}

BAT.0127.0019 Error cleaning up copied Data file. Db:{0} Error:{1}

BAT.0127.0020 Error closing original Data file. Db:{0} Error:{1}

BAT.0127.0021 Data file resize completed. Db:{0}

BAT.0127.0022 Resized Data file recovered. Db:{0}

BROKER_NOT_REACHABLE – Broker not connected.

CACHE_CACHE_MANAGER_NOT_INITIALIZED – Cache manager {0} is not loaded or initialized.

CACHE_CACHE_NOT_FOUND – Cache {1} for cache manager {0} not found.

CACHE_CANNOT_ACQUIRE_READ_LOCK – Could not acquire a read lock for key {0} in cache {1} contained within the cache manager {2}.

CACHE_CANNOT_ACQUIRE_WRITE_LOCK – Could not acquire a write lock for key {0} in cache {1} contained within the cache manager {2}.

CACHE_INVALID_INPUT – Invalid value for input parameter {0}. Error:{1}.

CACHE_MISSING_PARAM_NAME – Missing required parameter: {0}

CAN_NOT_RESUME can not resume due to state:

CAN_NOT_SUSPEND can not suspend due to state:

CURRENT_EVENT_IS_NOT_A_START_ELEMENT – Current event is not a START_ELEMENT

CURRENT_STATE_NOT_START_ELEMENT – Current state not START_ELEMENT

CURRENT_STATE_NOT_START_ELEMENT_END_ELEMENT_OR_ENTITY_REFERENCE – Current state not START_ELEMENT, END_ELEMENT or ENTITY_REFERENCE

CURRENT_STATE_NOT_START_ELEMENT_OR_END_ELEMENT – Current state not START_ELEMENT or END_ELEMENT

DEPLOYER_PACKAGE_DISALLOW_INSTALL_ON_ENABLED – Package"{0}" will not be deployed because deploying to an enabled package is disallowed

DEPLOYER_PACKAGE_NOT_ENABLED – The deployed package {0} is disabled. Check the Integration Server logs for any errors that may have occurred during deployment. If the package contains Adapter or .NET assets for which variable substitution parameters were specified, you must perform the variable substitutions manually on the Integration Server for the changes to take effect.

DEPLOYER_PACKAGE_SERVICE_EXECUTION_CHECK – Package "{0}" will not be deployed because at least one of the Package services is in execution

DISABLEDE **Messaging Synchronizer has been disabled**

Explanation The Broker Synchronizer has been disabled.

Action Check the status of the Broker and the Broker Settings in Integration Server Administrator.

DUPE_EVENT_TYPE_NAME – Document type {0} has failed to load. Duplicate Broker document type name {1} is also referenced by {2}

DUP_XID_RESOURCE_UPDT – Failed attempt to store resource status={0} for xid={1}, resource={2}. XID not found.

DUP_XID_START Transaction start for xid={0} failed. Transaction for this xid has already been started.

EDA_EID_ROOT_NODE Parameter xmldata must be XML with a root node element named "Event {http://namespaces.softwareag.com/EDA/Event}".

EGDOS002E **Error occurred while updating global Denial of Service options for Enterprise Gateway rules. Details: {0}.**

Explanation Enterprise Gateway Server could not update the global Denial of Service options for Enterprise Gateway rules for the reason indicated.

Action Ensure that the correct input parameters are provided to the service. Then, try to update the global Denial of Service options again.

EGDOS006E **Error occurred while updating Denial of Service by IP address options for Enterprise Gateway rules. Details: {0}.**

Explanation Enterprise Gateway Server could not update DoS by IP address options for Enterprise Gateway rules for the reason indicated.

Action Check the reason detailed in the message and take appropriate corrective action.

EGMAPP02E	Error occurred while updating device types. Details: {0}.
Explanation	Enterprise Gateway Server could not update the list of device types. Possible reasons are: The device name is too long (exceeds 255 characters) or contains special characters; the device type was deleted by another user while the current user tried to update the list; the device type is specified in one or more Enterprise Gateway rules; or there was a problem saving the device types to the Enterprise Gateway rules configuration file.
Action	If you are adding a device type, use the correct format. If you are deleting a device type and the device type is used in one or more Enterprise Gateway rules, remove or change the condition in the mobile application protection filter where the device type is specified.
EGMAPP04E	Error occurred while updating mobile applications. Details: {0}.
Explanation	Enterprise Gateway Server could not update the list of mobile applications. Possible reasons are: The application name is too long (exceeds 255 characters) or contains special characters; the application was deleted by another user while the current user tried to update the list; the application is specified in one or more rules; or there was a problem saving the application to the Enterprise Gateway rules configuration file.
Action	If you are adding a mobile application, use the correct format. If you are deleting a mobile application and the application is used in one or more Enterprise Gateway rules, remove or change the condition in the mobile application protection filter where the application is specified.
EGRULE002E	Enterprise Gateway rule could not be created. Details: {0}.
Explanation	Enterprise Gateway Server could not create the Enterprise Gateway rule for the reason indicated.
Action	Ensure that the correct input parameters are provided to the rule creation service.
EGRULE004E	Enterprise Gateway rule could not be updated. Details: {0}.
Explanation	Enterprise Gateway Server could not update the Enterprise Gateway rule for the reason indicated.
Action	Ensure that the correct input parameters are provided to the rule update service.
EGRULE006E	Enterprise Gateway rule could not be deleted. Details: {0}.
Explanation	Enterprise Gateway Server could not delete the Enterprise Gateway rule for the reason indicated.
Action	Ensure that the correct input parameters are provided to the rule deletion service.

EGRULE007E	A rule violation occurred for Enterprise Gateway rule "{0}". Filter: "{1}", message: "{2}", request IP: {3}, request URL: {4}, request time: {5}.
Explanation	Enterprise Gateway Server could not process the request because an Enterprise Gateway rule violation occurred.
Action	Either change the rule filter settings or modify the request so a rule violation does not occur.
EGRULE008E	A rule violation occurred for Enterprise Gateway rule "{0}". Request IP: {1}, request URL: {2}, request time: {3}.
Explanation	Enterprise Gateway Server could not process the request because an Enterprise Gateway rule violation occurred.
Action	Either change the rule settings or modify the request so a rule violation does not occur.

ELEMENT_IS_NOT_A_TEXT_ONLY_ONE – Element is not a text-only one

ELEMENT_TEXT_CONTENT_MAY_NOT_CONTAIN_START_ELEMENT – element text content may not contain START_ELEMENT

ERROR_DRIVER_CONTAINS_INVALID_CHARSI – Driver alias cannot contain any of these characters: {0}

ERROR_POOL_CONTAINS_INVALID_CHARSI – Pool alias cannot contain any of these characters: {0}

EXPECTED_LOCAL_NAME_NOT_MATCHING – Expected local name '{0}'; current local name '{1}'

EXPECTED_NON_NULL_LOCAL_NAME – Expected non-null local name, but current token not a START_ELEMENT, END_ELEMENT or ENTITY_REFERENCE (was {0})

FAC+ ". "+ERROR_READING_SJO_FILE_FOR_CONNECTIONFACTORY – Error occurred during lookup for SonicMQ ConnectionFactory object from "{0}".

FAC+."."+ERROR_READING_SJO_FILE_FOR_DESTINATION – Error occurred during lookup for SonicMQ Destination object from "{0}".

FAC+."."+PRODUCER_RETRY_FAILED – Producer Retry for destination {0} alias {1} failed after {2} attempt(s): {3}

FAC+."."+PRODUCER_RETRY_FAILED_ATTEMPT – Producer Retry for destination {0} alias {1} failed retry attempt {2}: {3}

FAC+."."+PRODUCER_RETRY_INTERRUPT_DISABLED – Producer Retry for destination {0} alias {1} has been interrupted because the alias is now disabled.

FAC+."."+PRODUCER_RETRY_INTERRUPT_DISCONNECTED – Producer Retry for destination {0} alias {1} has been interrupted because the connection is closed.

FAC+."."+PRODUCER_RETRY_INTERRUPT_SHUTDOWN – Producer Retry for destination {0} alias {1} has been interrupted because the server is shutting down.

FAC+."."+PRODUCER_RETRY_NOTRUN_DISABLED – Producer Retry not attempted for destination {0} alias {1} because the alias is disabled: {2}

FAC+."."+PRODUCER_RETRY_NOTRUN_DISCONNECTED – Producer Retry not attempted for destination {0} alias {1} because the connection is closed: {2}

FAC+."."+PRODUCER_RETRY_NOTRUN_SHUTDOWN – Producer Retry not attempted for destination {0} alias {1} because the server is shutting down: {2}

FAC+."."+PRODUCER_RETRY_STARTED – Attempting Producer Retry for destination {0} alias {1}. Max Retry Attempts: {2}, Retry Interval: {3}, Error: {4}

FAC+."."+PRODUCER_RETRY_SUCCESS – Producer Retry for destination {0} alias {1} was successful after {2} attempt(s).

FAC_ART+ART726 MSGPREFIX_ART+"Unable to acquire lock on key:{1} in shared cache:{0}."

FAC_ART+ART727 MSGPREFIX_ART+"Error occurred while removing key:{1} from the cache:{0}"

FAC_LISTENER+ALIS3300 – MSGPREFIX_LISTENER+"Unable to handle the state change event of the listener {0} acrosss the cluster"

Explanation An error occurred while processing a state change event for a listener in the cluster.

Action Check the details for the error in the Integration Server error log.

FAC_LISTENER+ALIS3311 – MSGPREFIX_LISTENER+"The cluster event can't be acted upon since the listener {0} is not present"

Explanation The error occurs when a listener is not available on a cluster node because of incorrect cluster setup. The correct cluster setup requires copying the same package on all cluster nodes.

Action Check if the package containing the listener is loaded properly. Verify if the WmART package dependency is set properly.

FAC_LISTENER+ALIS3312 – MSGPREFIX_LISTENER+"unable to activate the listener {0}. "

FAC_LISTENER+ALIS3313 – MSGPREFIX_LISTENER+"Unable to perform the listener failover since the listener node {0} is not available."

FAC_LISTENER+ALIS3314 – MSGPREFIX_LISTENER+"Unable to perform the listener failover due to an error while accessing the listener state cache."

FAC_LISTENER+ALIS3315 – MSGPREFIX_LISTENER+"Unable to synchronize the listener {0} across the cluster since the shared cache isn't available."

Explanation In a clustered environment, shared cache is used to synchronize the state of the listeners. The error occurs when the shared cache is not available.

Action Check the connection of the shared cache server to the specified Integration Server node.

FAC_LISTENER+ALIS3316 – MSGPREFIX_LISTENER+"Unable to mark the status as enabled after creating a listener thread"

FAC_LISTENER+ALIS3718 – MSGPREFIX_LISTENER+"Failed to get the data from the Listener Data Store for listener {0}"

FAC_NOTIFICATION+ANOT3132 – MSGPREFIX_NOTIFICATION+"Unable to set Publish Event status. Missing parameter: {0}"

Explanation The Notification name input parameter is missing.

Action Specify the notification name for which you want to set the Publish Event status.

FAC_NOTIFICATION+ANOT3133 – MSGPREFIX_NOTIFICATION+"Unable to set Publish Event status. Notification not found: {0}"

Explanation The specified notification does not exist.

Action Check if the notification with the specified name exists in the system.

FASHHASH_NOSUCHELEMENT – FastHashEnumerator

FFP.0001.9001E Child at index [{0}] is cannot be added to this row.

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9002E Cannot add child

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9003E Cannot add child

Explanation The Integration Server encountered an internal error.

Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

- FFP.0001.9004E** **Cannot put a record inside another record**
Explanation The Integration Server encountered an internal error.
Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.
- FFP.0001.9005E** **Cannot add unknown type to a record**
Explanation The Integration Server encountered an internal error.
Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
- FFP.0001.9006E** **Fields cannot have children**
Explanation The Integration Server encountered an internal error.
Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.
- FFP.0001.9007E** **Composites cannot contain composites**
Explanation The Integration Server encountered an internal error.
Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.
- FFP.0001.9008E** **Cannot add record to a composite**
Explanation The Integration Server encountered an internal error.
Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9009E	Cannot add unknown type to a composite
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
FFP.0001.9010E	Cannot add child
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
FFP.0001.9011E	Cannot add children to detail view
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.
FFP.0001.9012E	Cannot add children to detail view
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.
FFP.0001.9013E	Cannot add child of type: {0}
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.

- FFP.0001.9014E The first child of the Record Usage must be the Record Definition**
Explanation The Integration Server encountered an internal error.
Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.
- FFP.0001.9015E Cannot set the children of a usage node. The only child is the used node definition**
Explanation The Integration Server encountered an internal error.
Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
- FFP.0001.9016E Node is not editable**
Explanation The Integration Server encountered an internal error.
Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
- FFP.0001.9017E Cannot modify the children of a reference**
Explanation The Integration Server encountered an internal error.
Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
- FFP.0001.9018E Cannot add child. Child must be of type: {0}**
Explanation The Integration Server encountered an internal error.
Action Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.

FFP.0001.9019E	Cannot add node, node with name {0} already exists
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
FFP.0001.9020E	Cannot edit a broken link
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
FFP.0001.9021E	Server cannot be null
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support. Keep the following information handy before contacting the Software AG Global Support: server and error logs, a copy of the Support Action Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
FFP.0018.0001	The mark method is not supported by the supplied InputStream.
FFP.0018.0002	The reset method is not supported by the supplied InputStream.
FFP.0018.0003	{0} must be greater than zero (0).
FFP.0018.0004	{0} is required and must be greater than zero (0).
FFP.0018.0005	{0} is required and must be greater than one (1).
FFP.0018.0006	{0} is required and must be zero (0) or greater.

- FFP.0018.0007 If `{0}` is supplied, it must be zero (0) or greater.

- FFP.0018.0008 `{offset}` + `{length}` cannot exceed the size of `{buffer}`.

- FFP.0018.0009 Input parameter ffData cannot be null.

- FFP.0018.0010 Cannot process ffData of type: {0}.

- FFP.0018.0011 Could not find flat file Schema: {0}.

- FFP.0018.0012 Not validating, not keeping results, invalid settings.

- FFP.0018.0013 Encoding not supported: {0}.

- FFP.0018.0014 Name and package are required.

- FFP.0018.0015 Could not find dictionary: {0}.

- FFP.0018.0016 Flat File Schema name must be specified.

- FFP.0018.0017 No input signature presented.

- FFP.0018.0018 Document Type `{0}` already exists. Please delete it before re-creating.

- FFP.0018.0019 Value specified for maxErrors must be an integer. Value specified: `{0}`.

- FFP.0018.0020 Could not find record definition `{0}` in dictionary {1}.

FFP.0018.0021	Could not find composite definition `{0}` in dictionary {1}.
FFP.0018.0022	Could not find field definition `{0}` in dictionary {1}.
FFP.0018.0023	Please specify a valid value for entryType.
FFP.0018.0024	{0} is not a flat file dictionary.
FFP.0018.0025	{0} is not a flat file schema.
FFP.0018.0026	Could not find root tag <FFSchmea>
FFP.0018.0027	Could not find a valid value for input parameter `EntryType`
FFP.0018.0028	Could not find root tag <FFDictionary>
FFP.0018.0029	Flat file dictionary {0} already exists in package {1}, cannot create it in package {2}.
FFP.0018.0030	Flat file schema {0} already exists in package {1}, cannot create it in package {2}.
FFP.0018.0031	Values are required for input parameters `FFDictionaryName` and `PackageName`.
FFP.0018.0032	Could not find entry `{0}` in dictionary `{1}`.
FFP.0018.0033	Could not find record entry `{0}`, in dictionary `{1}`.
FFP.0018.0034	Could not find composite entry `{0}` in dictionary `{1}`.

- FFP.0018.0035 **Could not find field entry `{0}` in dictionary `{1}`.**

- FFP.0018.0036 **Document Type name `{0}` is not valid**

- FFP.0018.0037 **The following input parameters are required:{0}**

- FFP.0018.0038 **Cannot create document type. Referenced {0} {1} in flat file dictionary {2} could not be found**

- FFP.0018.0042 **Please specify a value for name**

- FFP.0018.0043 **Could not find {0}**

- FFP.0018.0044 **Specified value {0} must be a flat file dictionary or flat file schema.**

- FFP.0018.0045 **Could not find package: {0}**

- FFP.0018.0046 **Package {0}, is not enabled. Please enable the package, or specify a different package**

- FFP.0018.0047 **{0} was saved with the following warning(s):**

- FFP.0018.0048 **{0} was saved with the following error(s):**

- FFP.0018.0049 **{0} is not a flat file dictionary.**

- FFP.0018.0052 **Cannot encode the delimiter character `{0}` (U+{1}) using specified encoding: {2}}. Please select a different delimiter character.**

- FPL.0001.0000E Error processing Cleanup service: {0}**

Explanation An error occurred during the execution of the user-specified cleanup service.

Action Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written, cleanup service, which is identified in the message.

FPL.0001.0001E	Listener key not provided. Cleanup service not running
Explanation	Internal Error
Action	Contact Software AG Global Support. Please have the following information available: server and error logs, a copy of the Support Information page from the Developer, and the contents of the packages\WmFlatFile\config directory.
FPL.0001.0002E	Cleanup service access denied. User {0} not allowed to run service {1}
Explanation	The user specified in the message attempted to run the service specified in the message, but the user does not have the privileges required to run the service.
Action	Modify the "Run services as user" parameter on the file polling listener configuration page to specify a user that has the appropriate privileges. Make certain that the user you specify has the permissions to execute the processing service.
FPL.0001.0003E	Error processing service: {0}
Explanation	An error occurred during the execution of the user-specified cleanup service.
Action	Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written cleanup service, which is identified in the message.
FPL.0001.0004E	Could not delete file: {0} - {1}
Explanation	An error occurred while attempting to delete the specified file.
Action	Check the file system to determine why the specified file has not been deleted. It might be necessary to delete the file manually.
FPL.0001.0012E	Could not move source file {0} to working directory {1}
Explanation	The system was unable to move the file from the monitoring directory to the working directory.
Action	On a Windows operating system this can be normal behavior because the operating system will not allow a file to be moved while the file is being written to. For Windows, this is an error if the file listed is never processed. On a non-Windows operating system, this error might occur because the source and destination directories are on different file systems. Specify the source and destination directories to be on the same file system.

FPL.0001.0013E	Error processing monitoring file. {0}.
Explanation	An error occurred during the execution of the user-specified processing service.
Action	Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written cleanup service, which is identified in the message.
FPL.0001.0014E	Error processing cleanup. {0}.
Explanation	An error occurred during the execution of the user-specified cleanup service.
Action	Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written cleanup service, which is identified in the message.
FPL.0001.0020E	Could not get canonical path for monitoring directory: {0} - {1}
Explanation	The system could not obtain the canonical path for the monitoring directory, which is identified in the message. The message also displays the reason.
Action	Take the appropriate action based on the reason for the error shown in the message.
FPL.0001.0030E	Error processing file: {0}
Explanation	An error occurred during the execution of the user-specified processing service.
Action	Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written cleanup service, which is identified in the message.
FPL.0001.0031E	Listener key not provided. File polling listener not running
Explanation	Internal Error
Action	Contact Software AG Global Support. Please have the following information available: server and error logs, a copy of the Support Information page from Developer, and the contents of the packages\WmFlatFile\config directory.
FPL.0001.0032E	File polling processing service access denied. User {0} not allowed to run service {1}
Explanation	The specified user does not have privileges to run the specified service.
Action	Modify the "Run services as user" parameter in the file polling listener configuration page to specify a user that has the appropriate privileges. Make certain that the user you specify has the permissions to execute the processing service.

FPL.0001.0033E	Error processing service: {0}
Explanation	An error occurred during the execution of the user-specified processing service.
Action	Check the server error log for more detailed information. This error is most likely caused by an exception that occurred in the user-written cleanup service, which is identified in the message.
FPL.0001.0034E	Could not move file to finished directory. {0}
Explanation	The system was unable to move the file from the working directory to the finished directory.
Action	On a Windows operating system this can be normal behavior because the operating system will not allow a file to be moved while the file is being written to. For Windows, this is an error if the file listed is never processed. On a non-Windows operating system, this error might occur because the source and destination directories are on different file systems. Specify the source and destination directories to be on the same file system.
FPL.0001.0035	File polling processing service indicated error - [{0}]
Explanation	The processing service flagged an error to indicate there is an error.
Action	No action is required.
FPL.0001.0036	File polling processing file: {0}
Explanation	The indicated file is being processed.
Action	No action is required.
FPL.0001.0037E	Could not rename file {0} to {1}.
Explanation	The system was unable to move the file from the monitoring directory to the working directory.
Action	On a Windows operating system this can be normal behavior because the operating system will not allow a file to be moved while the file is being written to. For Windows, this is an error if the file listed is never processed. On a non-Windows operating system, this error might occur because the source and destination directories are on different file systems. Specify the source and destination directories to be on the same file system.

FPL.0002.0001E	Invalid processing service: {0}
Explanation	The specified processing service does not exist.
Action	Specify a service name that exists on the Integration Server.
FPL.0002.0002	No such service: {0}
FPL.0002.0003E	Unknown content type: {0}
Explanation	No content handler is defined for the given content type.
Action	Specify a content type for which a content handler has been defined or define a content handler for the specified content type. For more details, see the Javadoc for the class <code>com.wm.app.b2b.server.ServerAPI</code> .
FPL.0002.0004E	Server Error: {0}
Explanation	This is an internal error.
Action	Contact Software AG Global Support. Please have the following information available: server and error logs, a copy of the Support Information page from the Developer, and the contents of the <code>packages\WmFlatFile\config</code> directory.
FPL.0002.0005E	Invalid Cleanup service: {0}
Explanation	The specified processing service does not exist.
Action	Specify a service name that exists on the Integration Server.
FPL.0003.0001E	Must provide Monitoring Directory
Explanation	No monitor directory was specified.
Action	Specify a monitor directory.
FPL.0003.0004E	Monitoring Directory does not exist
Explanation	The monitoring directory does not exist.
Action	Create the monitoring directory.
FPL.0003.0005E	Working Directory does not exist
Explanation	The working directory does not exist.
Action	Create the working directory.

FPL.0003.0006E	Must provide User Name
Explanation	The user did not specify a value for the input "Run services as user".
Action	Specify a user to run the service as.
FPL.0003.0007E	Must provide Processing service
Explanation	The processing service was not specified.
Action	Specify a processing service.
FPL.0003.0008E	Invalid processing service {0}
Explanation	The specified processing service does not exist.
Action	Specify a service name that exists on the webMethods Integration Server.
FPL.0003.0009E	Monitor Directory {0} does not exist
Explanation	The monitor directory does not exist.
Action	Create the monitor directory.
FPL.0003.0010E	Completion Directory does not exist or can not be created
Explanation	The completion directory does not exist or cannot be created.
Action	Determine whether the server has permissions to create the indicated directory, or create the directory manually.
FPL.0003.0011E	Error Directory does not exist or can not be created
Explanation	The error directory does not exist or cannot be created.
Action	Determine whether the server has permissions to create the indicated directory, or create the directory manually.
FPL.0003.0012E	Invalid Cleanup service {0}
Explanation	The specified clean up service does not exist.
Action	Specify a clean up service that exists on the webMethods Integration Server.
FPL.0003.0013E	Invalid Working Directory
Explanation	The specified working directory is the same as either the monitoring directory or the completion directory.
Action	Specify a working directory that is not the same as the completion or monitoring directories.

FPL.0003.0015E	Invalid Error Directory
Explanation	The specified error directory is the same as either the monitoring directory or the completion directory.
Action	Specify an error directory that is not the same as the completion or monitoring directories.
FPP.0100.0001	No condition string defined for the conditional validator.
FPP.0100.0004	Internal Error: Unable to handle type: {0}.
FPP.0100.0005	Unable to handle recordIdentifier of type: {0}.
FPP.0100.0006	Code list validator contained no valid choices
FPP.0100.0007	Composite does not contain any subfields.
FPP.0100.0008	Cannot contain both a definition and a reference.
FPP.0100.0009	A <RecordElement> tag cannot have both a <CompositeUsage> and a <FieldUsage> tag
FPP.0100.0010	A field can only have one validator
FPP.0100.0011	A field can only have one extractor
FPP.0100.0012	Too many record parsers defined. A <RecordParser> tag can only contain one record parser.
FPP.0100.0013	Too many record identifiers defined. A <RecordIdentifier> tag can only contain one record identifier.

FPP.0100.0014	Flat file schema must have a record identifier defined.
FPP.0100.0015	Flat file schema must have a record parser defined.
FPP.0100.0016	Value {0} must be integer greater than or equal to zero.
FPP.0100.0017	<MaxOccur> value must be either "Unlimited" or a positive integer greater than zero. `{0}` is not a valid value.
FPP.0100.0018	<Position> value must be either "NoPosition" or an integer. `{0}` is not a valid value.
FPP.0100.0019	<Area> must be either "NoArea" or a positive integer greader than zero. `{0}` is not a valid value.
FPP.0100.0020	Value {0} must be integer greater than or equal to one.
FPP.0100.0021	Either <{0}> or <{1}> is required.
FPP.0100.0022	The end position ({1}) must be greater than the start position ({0}).
FPP.0100.0023	The flat file schema has no records defined.
FPP.0100.0024	This element contains a reference to the flat file dictionary {0}, which does not exist
FPP.0100.0025	The {0} entry called {1} in flat file dictionary {2} in package {3} could not be found
FPP.0100.0026	Record has no fields or composites defined
FPP.0100.0027	Must have a record delimiter defined when using delimited record parser

FPP.0100.0028 **Must have a field delimiter defined when using Nth field extractors**

FPP.0100.0029 **Must have a subfield delimiter defined when using composite extractors**

FPP.0100.0030 **Element has no extractor defined**

FPU.0002.0001 **Unable to load resource bundle: {0}**

FTP_CMD_ERR **Command {0} failed**

IMPROPER_URI_AND_XMLOBJECTID – The uri provided must be #{0} as [#idXmlObject] for an enveloping signature.

INT_XASTORE_NULL The XA store could not be initialized.

INVALID_ALLOW_HOSTNAME – Invalid character/s found in host name, {0}, in IP Access Allow list.

INVALID_JOIN_TYPE Invalid Join type

INVALID_XML_CHARACTER – The character {0} is not allowed in XML.

INVOKE_IFCNAME_MISSING – Service interface name required.

INVOKE_SVCNAME_MISSING – Service name required.

IS.0088.9446E **Access denied to use the web service endpoint alias {0}.**

Explanation User does not have permission to use the specified web service endpoint alias.

Action Using the Integration Server Administrator, examine the Execute ACL property of the web service endpoint alias. Make sure that the current user has the proper ACL to use the web service endpoint alias.

ISC.0006.0004S	Error in SSL setup: {0}
Explanation	The server cannot configure SSL listener or SSL Sockets connections, most likely because of a problem with the SSL configuration settings.
Action	Review the exception message in the log and correct the configuration.
ISC.0006.0006I	SSL listener restricted to 128 bit or better encryption.
Explanation	Integration Server configuration properties <code>watt.net.ssl.client.strongcipheronly</code> or <code>watt.net.ssl.server.strongcipheronly</code> or both are set to "true".
Action	No action is necessary. This message indicates that Integration Server is using strong encryption.
ISC.0006.0013E	Peer certificate chain is not present
Explanation	Integration Server cannot retrieve the peer certificate chain from a client.
Action	Update your client program so that it provides a valid peer certificate to Integration Server.
ISC.0006.0014E	SSL handshake failed on port {0} because peer certificate is not in IS Certificate Map, transfer is terminated
Explanation	While trying to connect to Integration Server, a client presented a certificate that is not contained in the store of client certificates that are mapped to Integration Server users.
Action	To import the client certificate to Integration Server and map it to a valid user, go to the Integration Server Administrator and click <code>Security>Certificates>Configure Client Certificates</code> . For additional information about certificate mapping, refer to the <code>webMethods Integration Server</code> documentation.
ISC.0006.0015E	Peer certificate chain is not trusted
Explanation	While trying to connect to Integration Server, a client presented a certificate that is not trusted by Integration Server.
Action	Add the certificate to the trusted certificates directory for Integration Server. The name of this directory is specified on the Integration Server Administrator under <code>Security>Certificates</code> . For more information about trusted certificates, refer to the <code>webMethods Integration Server</code> documentation.

ISC.0006.0016E	SSL handshake failed on port {0}, transfer is terminated
Explanation	An IOException occurred during the SSL handshake portion of a client's attempt to connect to Integration Server at the indicated port.
Action	Check the server log and error log for possible causes for the error.
ISC.0006.0017S	Error in adding trusted certificates: {0}
Explanation	The Integration Server failed to add the specified CA certificate because it is not in the correct format. The CA certificate must be DER or PEM encoded.
Action	Check the certificate format. Configure CA certificates in DER or PEM format.
ISC.0006.0018S	Error in initializing certificate chain verifier: {0}
Explanation	An error occurred when Integration Server initialized the certificate chain verifier while setting up the specified secure listener.
Action	Check the server log and error log to determine the cause of the error.
ISC.0006.0019W	Not including Cipher {0} because it is not a strong Cipher.
Explanation	Integration Server generates this warning when either the <code>watt.net.ssl.server.strongcipheronly</code> or <code>watt.net.ssl.client.strongcipheronly</code> property is set to "true", and if any of the ciphers identified in either the <code>watt.net.ssl.client.cipherSuiteList</code> or <code>watt.net.ssl.server.cipherSuiteList</code> property are weak.
Action	To stop receiving this warning, remove the specified cipher from the <code>watt.net.ssl.server.cipherSuiteList</code> or <code>watt.net.ssl.client.cipherSuiteList</code> property.
ISC.0006.0020W	Cipher ({0}) is not a valid CipherSuiteList.
Explanation	A CipherSuite specified as a value to either the <code>watt.net.ssl.client.cipherSuiteList</code> or <code>watt.net.ssl.server.cipherSuiteList</code> property is not valid. The invalid CipherSuite is shown in the log message. One of the CipherSuite that is specified as a value to either <code>watt.net.ssl.client.cipherSuiteList</code> or <code>watt.net.ssl.server.cipherSuiteList</code> property is not a valid CipherSuite. The invalid CipherSuite is shown in the log message.
Action	Remove the invalid CipherSuite.

ISC.0009.0012E	Failed to create certificate: {0}
Explanation	The certificate specified in the Configure Client Certificates settings has a bad X509Certificate format.
Action	Make sure that the .der file specified in Configure Client Certificates settings is valid.
ISC.0009.0014E	A certificate with the same issuer, serial number and usage is already mapped to user {0}.
Explanation	For a given usage type, only one user can be mapped to a certificate with the same issuer and serial number.
Action	To reassign this certificate to different user, edit the previously mapped certificate and change the user.
ISC.0009.0015E	The certificate is already mapped to user {0}.
Explanation	Integration Server failed to map the client certificate to the user because the client certificate is already mapped to the user specified.
Action	To reassign this certificate to different user, edit the previously mapped certificate and change the user.
ISC.0009.0016E	The ISInternal functional alias is not configured properly on the JDBC Pools page. Assign a valid database pool and restart the Integration Server.
Explanation	Integration Server failed to initialize client certificate mappings because it could not access the ISInternal JDBC Pool.
Action	Assign a valid database pool to ISInternal JDBC functional alias and restart the Integration Server.
ISC.0009.0017W	Certification chain trust verification failed.
Explanation	At least one of the certificates present in the certificate chain is not trusted by Integration Server.
Action	Check the certificate chain presented to Integration Server for trust verification.
ISC.0009.9001E	Certificate chain broken: not linked properly
Explanation	The certificate chain is out of order.
Action	Obtain a valid certificate chain.

ISC.0009.9003E	Certificate contains an unsupported critical extension
Explanation	When <code>watt.security.cert.wmChainVerifier.enforceExtensionsChecks</code> property is set to "true", Integration Server checks the presented certificate for unsupported critical extensions. If Integration Server finds a certificate containing unsupported critical extensions, it will reject the certificate and fail the request.
Action	If you enabled Integration Server to perform a certificate extensions check, advise your clients to use certificates that do not contain unsupported critical extensions. Whether Integration Server enforces a certificate check is configured on the <code>watt.security.cert.wmChainVerifier.enforceExtensionsChecks</code> configuration property.
ISC.0009.9004E	Certificate issued to {0} has expired
Explanation	Unless configured to ignore expired certificates, Integration Server will reject any expired certificates. Whether Integration Server ignores expired certificates is configured on the <code>watt.security.ssl.ignoreExpiredChains</code> configuration property.
Action	Review the server log to see which client's certificate has expired. That client should renew their certificates and resubmit the request with the valid certificate.
ISC.0009.9102E	User does not exist for certificate : {0}.
Explanation	The user associated with the imported client certificate in Integration Server has been deleted.
Action	Ensure that all imported client certificates in Integration Server are associated with a user. If you have deleted the user associated with a client certificate, you can take one of the following actions: 1) Modify the certificate mapping using Security > Certificates > Client Certificates > Details > Change Mapping in the Integration Server Administrator. 2) Add a user with the same name as the deleted user that was associated with the imported client certificate.
ISC.0012.0040E	OSGi service for SAML authentication not initialized.
Explanation	There was a problem while attempting to access Integration Server from the Command Central user interface.
Action	Check the logs located in the <code>Software_AG_directory/profiles/IS/logs</code> directory and make sure that no errors were encountered during the initialization of the OSGi service specified in the error message.

ISC.0012.0041E	Unable to initialize SAML authentication module. Cannot get reference of the OSGi service {0}.
Explanation	There was a problem while attempting to access Integration Server from the Command Central user interface.
Action	Check the logs located in the Software_AG_directory/profiles/IS/logs directory and make sure that no errors were encountered during the initialization of the OSGi service specified in the error message.
ISC.0018.0001U	Unable to read MIME types file
Explanation	During startup, Integration Server was unable to read the MIME types from the file "mime.types", which is located on the <IntegrationServer_dir>\lib directory. The most likely reason is that this file is corrupted.
Action	Contact Software AG Global Support for a copy of this file.
ISC.0018.0002	Deleted group {0} was removed from {1} ACL lists
ISC.0018.9301E	Unlocking thread is not owner
ISC.0018.9401E	target directory does not exist
Explanation	Directory specified to make the tar (zip) file does not exist in the file system.
Action	Ensure that the directory exists in the file system.
ISC.0018.9402E	target is not a directory
Explanation	Only directories can be zipped. The File name field do not contain the path to a directory.
Action	Ensure that the File name field contains the path to a directory.
ISC.0018.9403E	extraction target is not a directory
Explanation	File name specified to extract a tar file is not a directory. A tar file can be extracted only to a directory.
Action	Enter the directory to which the tar file is to be extracted.

ISC.0018.9404E	field length exceeded: {0} > {1} ({2})
Explanation	Integration Server encountered an internal error while adding a file to tar file.
Action	Contact Software AG Global Support.
ISC.0018.9405E	expected {0} bytes but got {1}
Explanation	While adding a file to a tar archive, the number of bytes added to the archive is less than the actual size of the file.
Action	Contact Software AG Global Support.
ISC.0018.9406E	No Tar Entry specified
Explanation	No directory is provided for zipping.
Action	Ensure that a directory is provided for zipping.
ISC.0018.9407E	data length is greater than entry specification: {0}
Explanation	Integration Server encountered an internal error while adding a file to the tar file.
Action	Contact Software AG Global Support.
ISC.0037.0001	Unable to Initialize {0}
ISC.0037.0002	Unable to Shutdown {0}
ISC.0037.0005	Unable to reset job manager {0}
ISC.0037.0006	Unable to reset logfile {0}
ISC.0037.0007	Unable to reset logstream {0}
ISC.0037.0012	Unable to accept requests
ISC.0037.9101E	Guaranteed Delivery Disabled - Please correct error and reinitialize

ISC.0042.0002E	Unsupported Encoding: {0}
Explanation	Integration Server did not recognize the encoding of the document. Therefore, the default encoding will be used.
Action	If Integration Server successfully uses the default encoding, no action is necessary. Otherwise, change the supplied document so that it has a valid encoding.
ISC.0042.9001	Cannot uniquely identify the root element : Every element may be contained in at least one other element -- Try loading the DTD from a sample XML document having a DOCTYPE declaration.
ISC.0042.9002	Cannot uniquely identify the root element : Multiple elements are topmost elements ({0}) -- Try loading the DTD from a sample XML document having a DOCTYPE declaration.
ISC.0042.9003	<ELEMENT {0} {1}> contains the following error at character {2} of the contentspec: {3}
ISC.0042.9005U	URI {0} not declared at node {1}
Explanation	webMethods Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0042.9006U	Node reference is null
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0042.9007U	Node is not XML
Explanation	The pub.xml:getXMLNodeIterator service failed to execute because the node object supplied was not an XML node.
Action	Examine the service input and make sure the "node" parameter represents an XML node, not an HTML node.
ISC.0042.9008U	Moving window mode is only available when iterating over XML nodes
Explanation	The pub.xml:getXMLNodeIterator service failed to execute because the XML node supplied did not represent a whole XML document.
Action	Examine the service input and make sure the "node" parameter represents an entire XML document, not an element of an XML document.

ISC.0042.9009U	Moving window mode is not available with SAX parsers
Explanation	The pub.xml:getXMLNodeIterator service failed to execute because the moving window mode is not available with SAX parsers.
Action	Switch to the webMethods parser instead of the SAX parser.
ISC.0042.9011U	SAX parsers do not expose enough DTD info; try selecting the expandDTD option
Explanation	The pub.xml:loadXMLNode service failed to execute because it used a SAX parser. Integration Server does not support SAX parsers because they do not expose enough DTD information.
Action	Switch to the webMethods parser instead of the SAX parser.
ISC.0042.9012U	First node of region not found in node parameter
Explanation	The pub.web:createRegions service failed to execute because the "regions" parameter did not correctly specify the first node of the region.
Action	Examine the service input for the "regions" parameter and check the query specified for identifying the first node. Make sure the query specified will correctly identify the first node.
ISC.0042.9013U	Last node of region not found in node parameter
Explanation	The pub.web:createRegions service failed to execute because the "regions" parameter did not correctly specify the last node of the region.
Action	Examine the service input for the "regions" parameter and check the query specified for identifying the ending node. Make sure the query specified will correctly identify the ending node.
ISC.0049.0001	Branch {0}: child {1} not found, default child not found for switch {2}
ISC.0049.0002	Branch {0}: child {1} not found, invoking default child {2}
ISC.0049.0010	Loop {0}: in-array {1} is not an array type.
ISC.0049.0012	Set: invalid encoding: {0}

ISC.0049.0013E	Set: {0}
Explanation	While saving or loading a flow service, Integration Server encountered a problem with the base64 encoding of a Map operation.
Action	Contact Software AG Global Support.
ISC.0049.0015	Loop {0}: out-array is not the same length as in-array.
ISC.0049.0016	Flow timed-out at {0}
ISC.0049.0018	Branch {0}: no expressions evaluated true and no default child found
ISC.0049.0019	Branch {0}: no expressions evaluated true, but default child found
ISC.0049.9001E	FlowExit "{0}" -- no valid ancestor to exit from \$loop
Explanation	In a flow service, the Exit operation failed because an ancestor loop was not found.
Action	Move the Exit operation to be a child of a Loop or Repeat step. Alternatively, set the exit-on property for the Exit operation to a value other than \$loop.
ISC.0049.9002E	get: complex path is not supported
Explanation	A flow service tried to perform a get operation on a complex path, but Integration Server does not support complex path types. This is an internal error.
Action	Contact Software AG Global Support.
ISC.0049.9003E	put: complex path is not supported
Explanation	A flow service tried to perform a put operation on a complex path type, but Integration Server does not support complex path types. This is an internal error.
Action	Contact Software AG Global Support.
ISC.0049.9004E	delete: complex path is not supported
Explanation	A flow service tried to perform a delete operation on a complex path, but Integration Server does not support complex path types. This is an internal error.
Action	Contact Software AG Global Support.

ISC.0049.9005E	Input validation for service "{0}" failed: "{1}"
Explanation	During service execution, Integration Server detected that the contents of the pipeline did not conform to the defined input signature of the service.
Action	Ensure that the inputs in the pipeline match the input signature of the flow service, or disable input validation for this service.
ISC.0049.9006E	Output validation for service "{0}" failed: "{1}"
Explanation	Upon completion of a service, Integration Server detected that the contents of the pipeline did not conform to the defined output signature .
Action	Ensure that the outputs in the pipeline match the defined output signature or disable output validation for this service.
ISC.0049.9007E	Failure creating input validator for "{0}"
Explanation	During execution of a flow service, Integration Server determined that it could not create an input Validator from the parameters provided.
Action	Contact Software AG Global Support.
ISC.0049.9008E	Failure creating output validator for "{0}"
Explanation	During execution of a Flow service, Integration Server determined that it could not create an output Validator from the parameters provided. This is an internal error.
Action	Contact Software AG Global Support.
ISC.0049.9009E	Missing required property 'switch' at "{0}"
Explanation	The Branch step has no switch property value.
Action	Specify the name of an pipeline object that is to be used as the switch value for the Branch step.
ISC.0049.9010E	Service "{2}" invoking unknown service "{1}" at "{0}". The service may have been renamed, moved or disabled.
Explanation	The failing flow service attempted to execute another servcie that could not be located or could not be executed. The most likely cause is that the target service has been removed or renamed.
Action	Determine the new name or location of the target service and modify the failing flow service to correctly identify the target service.

ISC.0049.9011E	Missing required property 'in-array' at "{0}"
Explanation	The Loop step has no input array property.
Action	Specify the name of a pipeline object to use as the input array.
ISC.0049.9012E	Cannot define 'switch' and use label conditions at "{0}"
Explanation	Integration Server tried to execute a Branch step, but the Branch properties were specified incorrectly. Specifically, the "evaluate labels" property was set to "true" while the "switch" property specified an expression. This is not a valid combination.
Action	Change the Branch step properties to either specify a switch value and set "evaluate-labels" to false, or do not specify a switch value and set "evaluate-labels" to true.
ISC.0049.9013E	Timeout at "{0}"
Explanation	A step in a flow service exceeded its timeout value before returning.
Action	This is desired behavior. Examine the underlying services that did not return in time to determine the cause of the timeout.
ISC.0049.9014E	Scope "{0}" not found or invalid
Explanation	At run time, Integration Server could not resolve the scope of the pipeline in a flow step. The scope resolved to an object that was not an IData.
Action	Make sure that the path in the scope property resolves to an IData object at run time.
ISC.0049.9015E	FlowExit "{0}" - label not found: "{1}"
Explanation	In a flow service, the Exit operation failed because it could not locate the label anywhere in the ancestry of the Exit step.
Action	Make sure that an ancestor flow step has a label that matches the one in the Exit step.
ISC.0049.9016E	Invalid scope path
Explanation	At run time, Integration Server could not resolve the pipeline scope specified for a flow step because the syntax of the scope property is not valid.
Action	Make sure that the path syntax of the scope property is valid.

ISC.0049.9017E	(1) Illegal path from: "{0}"
Explanation	In the pipeline, the map path for the source or destination is empty.
Action	If this error occurs while editing a flow service, save the flow service and then reload it.
ISC.0049.9018E	The path has been used: {0}
Explanation	More than one mapping operation is being performed on a pipeline object.
Action	Only one operation may be performed on a pipeline object in a Map step. Remove all but one of the map operations for the pipeline object, or ensure that only one operation is attempted at run time.
ISC.0049.9019I	More than one copy into the path with different common parent(s).
Explanation	When mapping data in the pipeline, under a single Map step, you tried to map from documents to two different document fields under a common parent. However, the source documents have different dimensions.
Action	Separate the data mapping into two different Map steps.
ISC.0049.9022E	Data type does not match the path.
Explanation	A pipeline mapping operation specifies a target type that does not match the source type at run time.
Action	Ensure that the source type at run time matches the target type specified by the map operation.
ISC.0049.9024E	Cannot make the copy from: {0} to: {1}
Explanation	While executing mapping in a flow step, Integration Server determined that it could not copy one field to another because the elements were of incompatible types.
Action	Make sure that the field types are compatible and have the same dimensions.
ISC.0049.9025E	Invalid source path.
Explanation	While trying to execute a map between fields, Integration Server determined that no source field was specified.
Action	In the pipeline, make sure that a source field is specified.

ISC.0049.9026E	Invalid target path.
Explanation	While trying to execute a map between fields, Integration Server determined that no target path was specified.
Action	In the pipeline, make sure that the map specifies a target destination.
ISC.0049.9027E	Error at {0} - Transformers cannot loop over list elements
Explanation	A Map step includes a link from an array variable in Pipeline In to a scalar input variable for a transformer.
Action	Do one of the following: - Remove the mapping between the array variable in Pipeline in and the scalar input variable for the transformer. - Change the service invoked by the transformer to accept arrays as data. - Create a flow service in which a LOOP step loops over the array variable. Then, (in the same flow service) invoke the service you originally wanted to use as a transformer, and make that Invoke step a child of the Loop. Finally, insert the resulting flow service as a transformer in the Map step.
ISC.0049.9031E	Global Variable {0} does not exist.
Explanation	The global variable that you assigned to a variable in the flow service does not exist in Integration Server.
Action	Ensure that global variable exists in IS, if it does not exist then contact IS Admin to add this Global Variable.
ISC.0050.0002	Invalid pipeline mapping: Cannot map two pipeline variables into the same field.
ISC.0050.0003	Pipeline variable sources have different dimensions.
ISC.0050.0004	Copy failed: {0}; to={1}, from={2}
ISC.0050.0005	Set failed: {0}; field={1}
ISC.0050.0007	Failed size check on path {0}
ISC.0050.0008	No valid value objects for path {0}

ISC.0050.0009	Data check: data type mismatch
ISC.0050.0013	Copy failed: No source data available from {0}
ISC.0050.0014	Field {0} incorrectly declared as array type
ISC.0050.0015	Incomplete path: null value for {0}
ISC.0050.0016	Cannot create object for the class: {0}
ISC.0050.0017E	Error encoding schema in FlowMap {0}
Explanation	While saving a flow service, Integration Server encountered an error trying to encode the input or output of a Map step.
Action	Contact Software AG Global Support.
ISC.0050.0018E	Error decoding schema in FlowMap {0}
Explanation	While loading a flow service, Integration Server encountered an error trying to decode the input or output of a Map step.
Action	Contact Software AG Global Support.
ISC.0050.0019	Copy failed: No source data available: to={0}, from={1}
ISC.0050.0020	Copy failed: Cannot create target data: to={0}, from={1}
ISC.0050.0021	Copy failed: Cannot support the required class name: to={0}, from={1}
ISC.0062.0001	CreateRegions createNsDecls type not supported
ISC.0062.0002E	CreateRegions createRegions type not supported
Explanation	The pub.web:createRegions service failed to execute because the input provided for the "regions" parameter was not an instance of IData[].
Action	Examine the service input make sure the "regions" parameter specifies an instance of IData[].

ISC.0062.0003U	GenerateQueryString {0} setValues {1}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0062.0004E	GenerateQueryStrings createFields type not supported
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0062.0005E	GenerateQueryStrings createNodeIDs type not supported
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0062.0006E	GenerateQueryStrings the bind failed
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0062.0007U	GetDocAsTable nodeTypeToString: {0} unknown type
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0062.0008	MakeRules.makeNSRecordFromDTD root of doc:{0} sig:{1}
ISC.0062.0009	MakeRules.makeNSRecordFromDTD root of doc:null
ISC.0062.0010	MakeRules.findElementDef name {0} not found in DTD:{1}
ISC.0062.0011E	MakeRules.makeRecord ERROR ConnectParticleName:{0}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

- ISC.0062.0012 **MakeRules.generateFlowFromDTD node parameter is null**
- ISC.0062.0013 **MakeRules.generateFlowFromDTD no output signature**
- ISC.0062.0014E **QueryDocWithIdentity createFields type not supported:{0}**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.
- ISC.0062.0015 **QueryDocWithIdentity createNsDecls type not supported:{0}**
- ISC.0062.0016E **queryXMLNode createFields type not supported:{0}**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.
- ISC.0062.0017 **{0} createNsDecls type not supported:{1}**
- ISC.0062.0018U **DocumentToXMLString boundNode argument is null**
Explanation The pub.xml:documentToXMLString service failed to execute because the required "document" parameter was missing. This parameter specifies the name of the document to be converted to XML.
Action Examine the service input and make sure it specifies a value for the "document" parameter.
- ISC.0062.0019 **ERROR unsupported type:{0} !!!!**
- ISC.0062.0022 **Server encountered an unknown error: {0}**
- ISC.0062.0032 **Invalid number format: {0}**
- ISC.0062.0033 **Illegal parameter value. {0} is too many root elements in boundNode. Number attributes:{1}.**

ISC.0062.0034	loadXMLNode called client.http pipe: {0}
ISC.0062.0036	Invalid port number {2} for {3}
ISC.0062.0037	loadXMLNode service encountered unsupported encoding: {0}
ISC.0062.9001U	boundNode parameter is null
Explanation	The pub.xml:documentToXMLString service failed to execute because the required "document" parameter was missing.
Action	Examine the service input and make sure it contains the document to be converted in the form of an IData object.
ISC.0062.9002U	Namespace prefix name "{0}" for uri {1} is not legal XML name
Explanation	The pub.xml:documentToXMLString service failed to execute because it detected illegal characters in the namespace prefix of the document to be converted. Integration Server flags invalid characters in the namespace prefix only if the value for the "enforceLegalXML" parameter is set to "true".
Action	To resolve this error, do one of the following: (1) Set the input for the "enforceLegalXML" parameter to "false". This causes the service to produce an XML fragment. (2) Make sure the input for the "nsDecls" parameter specifies a namespace prefix that starts with a letter or the underscore "_" character. In addition, it can only contain letters, digits, and the period ".", hyphen "-", and underscore "_" characters.
ISC.0062.9003U	Illegal parameter value. {0} is too many root elements in boundNode. Number attributes:{1}
Explanation	The pub.xml:documentToXMLString service failed to execute because the document to be converted contains multiple root elements. Integration Server flags this condition only if the input for the "enforceLegalXML" parameter is set to true.
Action	Examine the service input and make sure the "enforceLegalXML" parameter is set to "false". This will cause the service to produce an XML fragment composed of the multiple elements that were not enclosed within a root element.

- ISC.0062.9004U** **Attribute name "{0}" is not legal XML name**
- Explanation** The pub.xml:documentToXMLString service failed to execute because the prefix that designates the keys that contain attributes contains illegal characters. Integration Server flags this condition only if the input for the "enforceLegalXML" parameter is set to true.
- Action** To resolve this error, do one of the following:
- (1) Set the input for the "enforceLegalXML" parameter to "false" . This will cause the service to produce an XML fragment.
 - (2) Make sure the input for the "attrPrefix" parameter starts with a letter or underscore "_" character. In addition, it can only contain letters, digits, and the period ".", hyphen "-", and underscore "_" characters.
-
- ISC.0062.9005U** **Element name "{0}" is not legal XML name**
- Explanation** The pub.xml:documentToXMLString service failed to execute because the document being converted contains illegal XML tag names. Integration Server flags this condition only if the input for the "enforceLegalXML" parameter is set to true.
- Action** To resolve this error, do one of the following:
- (1) Set the input for the "enforceLegalXML" parameter to "false". This causes the service to produce an XML fragment.
 - (2) Make sure the input for the "document" parameter starts with a letter or underscore "_" character. In addition, it can only contain letters, digits, and the period ".", hyphen "-", and underscore "_" characters.
-
- ISC.0062.9006U** **Illegal parameter value. Document Type "{0}" not found.**
- Explanation** The pub.xml:xmlNodeToDocument service failed to execute because the "documentTypeName" was specified, but the document it represents does not exist on the Integration Server namespace.
- Action** Examine the service input and make sure the "documentTypeName" parameter specifies the fully qualified name of the document type. Remember that namespace element names are case-sensitive.
-
- ISC.0062.9007E** **collect parameter must be null when using recordName parameter**

ISC.0062.9008	MakeArrays parameter must be false when using recordName parameter
ISC.0062.9009	Arrays parameter must be null when using recordName parameter
ISC.0062.9010	Records parameter must be null when using recordName parameter
ISC.0062.9012	Internal error: no record generated by makeNSRecord
ISC.0062.9013	Internal error: no NSName generated
ISC.0062.9014	MakeRules.recursiveCollectRecordRefs found nested ContentParticleSet
ISC.0062.9015	MakeRules.findElementDef no element definitions found
ISC.0062.9016	MakeRules.findElementDef name "{0}" not found in DTD
ISC.0062.9017	XML node parameter is null
ISC.0062.9018	No NSRecord generated for package "{0}" Document Type "{1}"
ISC.0062.9019	XML node is null
ISC.0062.9020	Document Type "{0}" already exists.
ISC.0062.9021U	"object" is null
Explanation	The object to be validated does not exist in the pipeline.
Action	Link an XML node or document variable to the object variable in Service In.

ISC.0062.9022U	"{0}" - object does not exist
Explanation	The document type or schema specified for the "conformsTo" parameter does not exist in the Integration Server namespace.
Action	Change the value of the "conformsTo" parameter to be a document type or schema that exists in the Integration Server namespace.
ISC.0062.9023U	conformsTo parameter is null
Explanation	While executing the pub.schema.validatePipeline service, the Integration Server determined that no value was specified for the "conformsTo" property, which is a required parameter. This parameter specifies the IS document or IS schema against which the Integration Server performs validation.
Action	Specify a value for the "conformsTo" parameter that is an IS document type or schema type that exists in the IS namespace.
ISC.0062.9024U	Integration Server does not support this type of object in validation {0}
Explanation	The object to be validated is not one of the types supported by validation.
Action	Currently, only XML, pipeline, and document (IData object) validation are supported.
ISC.0062.9025	collect parameter must be null when using documentTypeName parameter
ISC.0062.9026	MakeArrays parameter must be false when using documentTypeName parameter
ISC.0062.9027	Arrays parameter must be null when using documentTypeName parameter
ISC.0062.9028	Documents parameter must be null when using documentTypeName parameter
ISC.0062.9029	The schema domain of the conformsTo object must match the schemaDomain parameter
ISC.0063.0006	Generate Transaction Ids {0}

ISC.0063.0017	Retrieve completed job tid={0}
ISC.0063.0020	Error (see job log) tid={0}
ISC.0063.0027	Error loading tid={0}; skipping ...
ISC.0063.0036	Can Still Retry {0}
ISC.0063.0042	Job Manager not initialized.
ISC.0063.0045	Deregister - already 0
ISC.0063.0046	Jobs still active on shutdown
ISC.0063.0049	Start for Nonexistent Tid={0}
ISC.0063.0050	Job Expired for Tid={0}
ISC.0063.0052	Retrieve on Nonexistent Tid={0}
ISC.0063.0053	Retrieve on new job
ISC.0063.0054	Retrieve on heuristic failure
ISC.0063.0055	Retrieve on expired job
ISC.0063.0056	Job Timed Out for Tid={0}

ISC.0063.0058	Restart for Nonexistent Tid={0}
ISC.0063.0059	Restart for Ended Tid={0}
ISC.0063.0060	Restart on active Tid={0}
ISC.0063.0061	Restart on non-pending Tid={0}
ISC.0063.0062	Status for non-existent Tid={0}
ISC.0063.0063	ChainedWait for non-existent Tid={0}
ISC.0063.0064	Get Remote TID for non-existent Tid={0}
ISC.0063.0069	Administrator email is not set.
ISC.0063.0070	Administrator email is {0}.
ISC.0063.0071	Logfile used:{0}. Jobdir used:{1}.
ISC.0063.0072	{0} broke lock for guaranteed job, tid={1}.
ISC.0063.0073E	The IS Internal database pool is not configured properly. Assign a valid database pool for the "ISInternal" functional alias and restart the Integration Server.
Explanation	The ISInternal functional alias on the Settings > JDBC Pools page in the Integration Server Administrator is not properly configured, or the database it refers to is unavailable.
Action	Configure the ISInternal functional alias on the Settings > JDBC Pools page in the Integration Server Administrator and use the "Test" button to verify that it can connect to the database. After configuring the ISInternal functional alias, restart the Integration Server.

ISC.0063.0074	End for Nonexistent Tid={0}
ISC.0063.0075	Failed to obtain repository context : {0}
ISC.0063.0078	Unable to accept requests
ISC.0063.0079	End: Invalid Transaction Id
ISC.0063.0080	Unable to accept requests
ISC.0063.0084	Unable to accept requests
ISC.0063.0086	Unable to accept requests
ISC.0063.0090	No Output Writer specified
ISC.0063.0098	Not a custom stream
ISC.0063.0100	Not a custom Writer
ISC.0063.0101	Don't close user stream
ISC.0063.0103	{0} property is invalid. Using default value of {1}.
ISC.0063.0104	{0};{1} did not create remote tid
ISC.0064.0001E	HttpContext cannot clone self
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

ISC.0064.0011W	Invalid maxRedirects setting {0}
Explanation	The watt.net.maxRedirects property is not valid. It must be an integer.
Action	Change the value of the watt.net.maxRedirects property to an integer.
ISC.0064.0012E	Class not found: {0}
Explanation	Integration Server encountered an internal error because it could not find a class in the namespace.
Action	Contact Software AG Global Support.
ISC.0064.0018E	Unable to instantiate class: {0}
Explanation	Integration Server encountered an internal error because it could not instantiate a class in the namespace.
Action	Contact Software AG Global Support.
ISC.0064.0029D	Could not open Socket connection to proxy={0} Exception:{1}
Explanation	An exception was encountered while making an FTP connection through a proxy server. See the exception for details.
Action	Check that the FTP proxy you are using is correctly configured on the Settings > Proxy Servers page of Integration Server Administrator.
ISC.0064.0030W	The {0} property is not a valid integer: {1}.
Explanation	An invalid value was specified for the property identified in the message. The value for this property must be an integer.
Action	Change the value of the property to an integer.
ISC.0064.9001E	Could not connect to ftp server: {0}
Explanation	FTP server is not accessible.
Action	Ensure that the FTP server and port are valid. If FTP proxy is configured in Integration Server, ensure that the proxy settings are correct.
ISC.0064.9002E	FTP host name or port number is not specified
Explanation	FTP hostname cannot be null and port cannot be zero.
Action	Ensure that you provide valid values for FTP host and port fields.

ISC.0064.9003	Fail to connect to FTP proxy: {0}+ port: {1}
ISC.0064.9004E	Fail to connect to FTP server: {0} port: {1}
Explanation	Integration server is unable to access the FTP server.
Action	Ensure that the FTP host and port fields contain valid values. If FTP host and port fields contain valid values and if Integration Server is still unable to access FTP server, contact Software AG Global Support.
ISC.0064.9005E	{0}
Explanation	Credentials of the FTP user are invalid.
Action	Ensure that the FTP user, password, and account fields have correct and valid values. Set the log level of Network Services component (64) to 'trace' to get more details.
ISC.0064.9006E	{0}
Explanation	FTP proxy server that you have configured does not support the SITE command.
Action	Check the FTP proxy server configuration to ensure that the FTP proxy server supports the SITE command. Set the log level of Network Services component (64) to 'trace' to get more details.
ISC.0064.9007E	{0}
Explanation	FTP proxy server that you have configured does not support the OPEN command.
Action	Check the FTP proxy server configuration to ensure that the FTP proxy server supports the OPEN command. Set the log level of Network Services component (64) to 'trace' to get more details.
ISC.0064.9008E	FTP PORT command failed
Explanation	FTP server encountered an error while sending the PORT command.
Action	The following lists the actions you can take: <ol style="list-style-type: none">1. Ensure that the FTP server implements the PORT command.2. Ensure that the user has the permission to execute the command.3. If the problem still persists, contact Software AG Global Support. Set the log level of Network Services component (64) to 'trace' to get more details.

ISC.0064.9009E	Invalid Data Channel
Explanation	FTP client is not able to create a data port for listening. In FTP Active mode, client creates a port for data connection and FTP server opens a connection to the client data port.
Action	Ensure that the data port specified in the FTP client is available. -OR- Use FTP passive transfer mode. Set the log level of Network Services component (64) to 'trace' to get more details.
ISC.0064.9010E	{0}
Explanation	FTP server is not able to connect to the data port of the client. The possible cause for this is that the data port might be blocked by a firewall on the client side.
Action	The following lists the actions you can take: <ol style="list-style-type: none">1. Check whether the client is behind a firewall. If yes, make sure that the firewall allows the connection from the server.2. Use FTP passive transfer mode.3. Increase the connection timeout of data port using <code>watt.net.ftpClientDataConnTimeout</code> property.
ISC.0064.9012E	Socket close err. {0}
Explanation	FTP server encountered an error while closing the FTP client socket.
Action	Contact Software AG support team.
ISC.0064.9013E	{0}
Explanation	FTP server is not accessible.
Action	Contact Software AG support team. Set the log level of Network Services component(64) to trace to get more details.
ISC.0064.9014E	Content must be of type byte[], String or InputStream
Explanation	The content type of the data sent to the FTP server is not of type byte array, string, or InputStream.
Action	Make sure that the data sent to the FTP server is of type byte array, string, or InputStream.

ISC.0064.9015E	FTP AUTH command failed with error code {0}
Explanation	An FTP client sent an AUTH command to establish an FTPS connection with the Integration Server, but the command failed with the indicated return code.
Action	Check your FTP documentation for the possible causes of the FTP return code. In addition, check the server log and error log for possible causes for the error.
ISC.0064.9016E	FTP AUTH command failed with error {0}
Explanation	An FTP client sent an AUTH command to establish an FTPS connection with the Integration Server, but the command failed.
Action	Check your FTP documentation for the possible causes of the FTP error message. In addition, check the server log and error log for possible causes for the error.
ISC.0064.9017E	FTP PBSZ command failed with error code {0}
Explanation	An FTP client sent a PBSZ command to establish a secure connection between the client and Integration Server, but the command failed with the indicated return code.
Action	Check your FTP documentation for the possible causes of the FTP error message. In addition, check the server log and error log for possible causes for the error.
ISC.0064.9018E	FTP PROT command failed with error code {0}
Explanation	An FTP client sent a PROT command to establish a secure connection between the client and Integration Server, but the command failed with the indicated return code.
Action	Check your FTP documentation for the possible causes of the FTP error message. In addition, check the server log and error log for possible causes for the error.
ISC.0064.9019E	FTP EPRT command failed with error {0}
Explanation	The FTP server returned an error for the EPRT command sent by the Integration Server FTP client.
Action	Ensure that the FTP server implements the EPRT command. Ensure that the user has the permission to execute the command. Set the log level of Network Services facility (facility number 64) to 'trace' to get more details. If the problem persists, contact Software AG Global Support.
ISC.0072.0010	Index {0} out of bounds for key {1}

ISC.0072.0011	value missing name. key={0}
ISC.0072.0014	LoopToken.evalArray unknown array type:{0}
ISC.0072.0016	Exception:{0} executing included template.
ISC.0072.0017	IfVarToken.processArgs value:{0} index:{1} ret:{2}
ISC.0072.9001E	Unknown service: {0}
Explanation	Integration Server encountered an internal error because it could not find a requested service in the namespace.
Action	Contact Software AG Global Support.
ISC.0072.9002E	Reporter died from IOException: {0}
Explanation	The Reporter.createTemplateFromFile() class issued an error because it could not read the template from the supplied file.
Action	Examine the use of the Reporter class in your application and make sure that the application has proper Read access to the template file.
ISC.0076.0001	BinCoder decode error creating IData {0}, using {1} instead. Excpt:{2}
ISC.0076.0002	BinCoder decode error creating IDataCodable {0}, using {1} instead. Excpt:{2}
ISC.0076.0003	BinCoder decode error creating Codable {0}. Excpt:{1}
ISC.0076.0004	BinCoder decode error creating as String {0}, s={1}. Excpt:{2}
ISC.0076.0005E	BinCoder decode error creating Java serialized object. Excpt:{0}
Explanation	The java.io.ObjectInputStream.readObject() service encountered an error while trying to decode a Java serialized object. For a ClassNotFoundException, the most likely cause is that a client performing a remote invoke placed a class definition into the pipeline, but the class definition does not exist on the receiving Integration Server. For an InvalidClassException, the most likely cause is that the class definition on the Integration Server does not match the class definition placed in the pipeline by the client.

Action	Make sure that the originating client and the receiving Integration Server have the same class definitions. For other I/O exceptions, there might be corruption in the input stream; therefore, you should try the request again.
ISC.0076.0006	BinCoder decode error creating array {0}
ISC.0076.0007	XMLCoder decode invalid data type: {0}
ISC.0076.0008E	XMLCoder decode exception: {0}
Explanation	Integration Server threw an exception while decoding an IDataXML encoded document.
Action	The document is corrupt. Contact Software AG Global Support.
ISC.0076.0009E	RPCBinCoder2 decode error for array class: {0}
Explanation	Integration Server encountered an error while trying to decode an array of remote objects. Class definitions might be out of sync.
Action	Contact Software AG Global Support.
ISC.0076.0010E	RPCBinCoder2 decode error for Codable class: {0}
Explanation	Integration Server encountered an error while trying to decode a codable class. Class definitions might be out of synch.
Action	Contact Software AG Global Support.
ISC.0076.0011E	RPCBinCoder2 decode error for as_String class: {0}
Explanation	Integration Server encountered an error while trying to decode an object that was encoded as a String.
Action	Contact Software AG Global Support.
ISC.0076.0012E	SOAP Encoding Registrar cannot register schema type {0}; schema type already exists.
Explanation	The SOAP Encoding Registrar could not register the indicated schema type. This is a serious internal error.
Action	Contact Software AG Global Support.

ISC.0076.0013E **SOAP Message Coder cannot encode output data; pipeline does not match output signature**

Explanation The SOAP message coder could not XML-encode the results of a SOAP remote procedure call because a variable appeared in the pipeline more than once.

Action Examine the target service to determine why it is not producing output values that match the output signature. Correct the service's signature and/or logic after identifying the source of the problem.

ISC.0076.0014U **SOAP Message Coder failure; a RuntimeException was thrown in the SOAP Coder**

Explanation The message coder encountered a serious internal error.

Action Contact Software AG Global Support.

ISC.0076.0015E **SOAP Message Coder cannot encode variable {0}; variable does not have a valid XML name**

Explanation The message coder could not XML-encode the SOAP RPC request or response because the pipeline contained the variable <varName>, whose name is not a valid name for an XML element.

Action This error often occurs because the variable name contains a colon (:). Change the name of <varName> to one that is also valid as an XML element name (or map <varName> to a new variable, and use that variable as your SOAP RPC input or output parameter).

ISC.0076.0016 **Soap Message Coder warning; unregistered coder for variable {0}, using String**

ISC.0076.0017E **SOAP Message Coder error; no coder is registered for encoding style {0}**

Explanation The message coder encountered a serious internal error.

Action Contact Software AG Global Support.

ISC.0076.0018 **Soap Message Coder warning; unregistered coder for variable {0}, using BasicData**

ISC.0076.0019E **SOAP Message Coder cannot decode message; encoding style {0} is not a registered style**

Explanation The message coder could not decode the submitted XML because it does not support the specified encoding style.

Action Check the incoming XML and verify that the encodingStyle attribute is specified correctly and that it specifies a style that Integration Server supports.

ISC.0076.0020E	Soap Message Coder warning; invalid HREF found {0}
Explanation	The message coder could not resolve the href pointing to reference. A null value was produced instead.
Action	Examine the incoming XML and make sure that the specified reference points to an element that exists in the body of the message.
ISC.0076.0021E	SOAP Message Coder cannot decode message; arrayType attribute value {0} is malformed
Explanation	The message coder could not decode an XML-encoded array because it cannot understand the value of the "arrayType" attribute.
Action	Check the incoming XML and make sure that the "arrayType" attribute is using the correct syntax. For example, make sure that it is not missing a "[" symbol.
ISC.0076.0022E	SOAP Message Coder cannot decode message; cannot determine type of element {0}
Explanation	The message coder could not decode the XML-encoded parameters it has received, because the simple element <elementName> has an unknown data type (for example, xsi:type="myDataType").
Action	Check the incoming XML and make sure the data type has been specified correctly. Also make sure that it is using the correct namespace.
ISC.0076.0023E	SOAP Message Coder cannot decode message; unable to create array for arrayType attribute value {0}
Explanation	The message coder could not decode an XML-encoded array because it could not allocate an array of the specified dimensions.
Action	Check the incoming XML and make sure that the arrayType attribute is specified correctly. For example, make sure that it does not specify a negative dimension or an invalid array size (e.g., too many dimensions or dimensions that are unrealistically large). If the array is unusually large or the server is extremely very low on memory, the possibility also exists that this error was the result of an out-of-memory condition.
ISC.0076.0026E	Broker Coder cannot encode document; the document, document type or both are null values
Explanation	While attempting to process a document from the Broker, Integration Server determined that the document, the document type, or both are null values. This is an internal error.
Action	Contact Software AG Global Support.

ISC.0076.0027E	Broker Coder cannot encode document; Broker document type name is missing
Explanation	The subscribing Integration Server received a document from the Broker or a publishing Integration Server, but was unable to encode the document because the document type name was missing from the event subscription. There are three possible reasons: (1) the document to be encoded is corrupted (2) the document type is out of sync with the corresponding document type on the Broker (3) an internal error occurred.
Action	Examine the document to be encoded and synchronize the document type with the Broker. If the error persists after the synchronization, contact Software AG Global Support.
ISC.0076.0028	Broker Coder cannot decode document; byte[] is in wire format version {0}. Latest supported format is version {1}
ISC.0076.0029	Broker Coder warning; multi-reference with sequence id {0} does not exist; using null value
ISC.0076.0030E	Broker Coder warning; cannot parse value {0}; using {1} instead
Explanation	Integration Server was not able to parse the document. There are two possible reasons: (1) the document might be corrupted (2) the document type is out of sync with the corresponding document type on the Broker.
Action	Examine the document and make sure that it is not corrupted. Also, synchronize the document type with the corresponding Broker document type.
ISC.0076.0031E	Broker Coder warning; cannot create an instance of {0}
Explanation	Integration Server could not create an instance of the indicated class. This is an internal error.
Action	Contact Software AG Global Support.
ISC.0076.0032	Broker Coder cannot decode document; the document, document type or both are null values
ISC.0076.0033E	Broker Coder cannot decode document; the document does not conform to the document type, {0}
Explanation	The subscribing Integration Server was not able to decode the incoming document from either the Broker or the publishing Integration Server because the document type on the local Integration Server is out of sync with the corresponding document types on the publishing Integration Server and the Broker.
Action	Synchronize the publishable document type on the subscribing Integration Server with the corresponding Broker document type.

ISC.0076.0034	Priority Classloader could not load the class while decoding.Trying Global classloader.
ISC.0076.9001U	Unsupported RPC type: {0}
Explanation	Integration Server RPC Bin Coder does not support the version specified in the input stream to be decoded. This is an internal error.
Action	Contact Software AG Global Support.
ISC.0076.9002U	incorrect IDataXMLCoder file format: no element 'IDataXMLCoder' found
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0076.9003U	encoding {0}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0076.9004U	decoding: {0} ex:{1}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0076.9005U	decoding: boolean ex:{0}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0076.9006U	decoding: {0}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0076.9007U	decoding: No null-arg create method in class: {0}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.

ISC.0076.9008U	Unsupported RPC type: {0}
Explanation	Integration Server RPC Bin Coder does not support the version specified in the input stream to be decoded. This is an internal error.
Action	Contact Software AG Global Support.
ISC.0076.9009U	Root element is null
Explanation	The flow.xml or node.ndf file is corrupt.
Action	Contact Software AG Global Support.
ISC.0076.9010U	Sibling root element is null rootTag:{0} localName:{1} root:{2}
Explanation	The XMLCoder class issued an error because the supplied XML input stream cannot be decoded.
Action	Examine the use of the XMLCoder class in your application and make sure that the XML input stream has the correct format and it only contains supported object types. If the error still occurs, use the setIgnoreInvalid() class to set the flag to false so that XMLCoder ignores the unsupported object type that it decodes.
ISC.0076.9011U	illegal file format
Explanation	The service pub.flow:restorePipelineFromFile failed to execute because the file containing the saved pipeline was not encoded with XMLCoder or IDataXMLCoder.
Action	Examine the file containing the saved pipeline and make sure it is not corrupt. If the file was saved using the pub.flow:savePipelineToFile service, and it is not corrupt, contact Software AG Global Support.
ISC.0076.9012E	Invalid state. JSON input stream does not start with the "{" character.
Explanation	The input stream does not contain valid JSON content. JSON content must begin with the "{" character.
Action	Add a "{" character to the beginning of the JSON content.
ISC.0076.9013E	Invalid state. JSON Object in the input stream does not end with "}" character.
Explanation	The JSON object in the input stream does not contain valid JSON content. The JSON object content must end with the "\}\" character.
Action	Add a "\}\" character to the end of the JSON object.

ISC.0076.9014E	Invalid state. JSON input stream contains incorrect syntax.
Explanation	The JSON input stream contains incorrect JSON syntax.
Action	Correct the errors in the JSON input stream.
ISC.0076.9015E	Invalid state. JSON Object in the input stream does not start with "{" character.
Explanation	The JSON object in the input stream does not contain valid JSON content. The JSON object content must begin with the "{" character.
Action	Add a "{" character to the beginning of the JSON object in the input stream.
ISC.0076.9016E	Invalid state. Array in the JSON input stream does not end with "]" character.
Explanation	The JSON array in the input stream does not contain valid JSON content. The JSON array must end with the "]" character.
Action	Add the "]" character from the end of the JSON array.
ISC.0076.9017E	Numeric value ({0}) for field {1} is outside the range for integer values. Integers must be within the range of -2147483648 to 2147483647. Error:{2}
Explanation	Integration Server encountered an invalid integer value while parsing a JSON object.
Action	Correct the value before parsing the JSON object.
ISC.0076.9018E	Numeric value ({0}) for field {1} is outside the range for long numbers. Long numbers must be within the range of -9223372036854775808 to 9223372036854775807. Error:{2}
Explanation	Integration Server encountered an invalid long number value while parsing a JSON object.
Action	Correct the value before parsing the JSON object.
ISC.0076.9019E	Numeric value ({0}) for field {1} is outside the range for float values. Error:{2}
Explanation	Integration Server encountered an invalid float value while parsing a JSON object.
Action	Correct the value before parsing the JSON object.
ISC.0076.9020E	Numeric value ({0}) for field {1} is outside of the range for double values. Error:{2}
Explanation	Integration Server encountered an invalid double value while parsing a JSON object.
Action	Correct the value before parsing the JSON object.

ISC.0076.9101E **SOAP Encoding Registrar cannot register encoding style {0}; encoding style already exists.**

Explanation Integration Server cannot register the specified encoding style because the encoding style is already registered.

Action Contact Software AG Global Support.

ISC.0076.9102E **SOAP Encoding Registrar cannot register Java type {0}; Java type already exists.**

Explanation Integration Server cannot register the specified Java type because it already exists in the registry.

Action Contact Software AG Global Support.

ISC.0076.9103E **SOAP Encoding Registrar cannot register Schema type {0}; Schema type already exists.**

Explanation Integration Server cannot register the specified Schema type because it already exists in the registry.

Action Contact Software AG Global Support.

ISC.0076.9104E **SOAP Encoding Registrar cannot unregister Java type {0}; doesn't exist in the registry**

Explanation Integration Server cannot unregister the specified Java type because it does not exist in the registry.

Action Contact Software AG Global Support.

ISC.0076.9105E **SOAP Encoding Registrar cannot unregister Schema type {0}; doesn't exist in the registry**

Explanation Integration Server cannot unregister the specified Schema type because it does not exist in the registry.

Action Contact Software AG Global Support.

ISC.0076.9202E **SOAP Message Coder failure; a RuntimeException was thrown in the SOAP Coder**

Explanation The SOAP message contains an element that does not have a valid QName.

Action Make sure the elements in the SOAP message have valid QNames.

ISC.0076.9203E	SOAP Message Coder cannot decode message; Invalid number {0}
Explanation	The message coder could not decode an XML-encoded array because one of its dimensions is set to a nonnumeric value.
Action	Check the incoming XML and make sure that the arrayType attribute specifies a positive integer. For example, make sure it has not been inadvertently set to a nonnumeric value such as "A".
ISC.0076.9204E	SOAP Message Coder cannot encode output data; pipeline does not match output signature, duplicate variable {0} in pipeline
Explanation	The message coder could not XML-encode the results of a SOAP remote procedure call because the specified variable appeared in the pipeline more than once.
Action	On the Integration Server, examine the target service to determine why it is not producing output values that match the output signature. Correct the service's signature and/or logic after identifying the source of the problem.
ISC.0076.9205E	SOAP Message Coder cannot encode variable {0}; variable does not have a valid XML name
Explanation	The message coder could not XML-encode the SOAP RPC request or response because the pipeline contained the specified variable, whose name is not a valid name for an XML element.
Action	This error often occurs because the variable name contains a colon (:). Change the name of specified variable to one that is also valid as an XML element name (or map the variable to a new variable, and use the target variable as your SOAP RPC input or output parameter).
ISC.0076.9206E	SOAP Message Coder error; no coder is registered for encoding style {0}
Explanation	Integration Server encountered a serious internal error when encoding the SOAP message.
Action	Contact Software AG Global Support.
ISC.0076.9208E	SOAP Message Coder cannot decode message; cannot determine type of element {0}
Explanation	The message coder could not decode the XML-encoded parameters it has received, because the specified element has an unknown data type (for example, xsi:type="myDataType").
Action	Check the incoming XML and make sure the data type has been specified correctly. Also make sure that it is using the correct namespace.

ISC.0076.9209E SOAP Message Coder cannot decode message; unable to create array for arrayType attribute value {0}

Explanation The message coder could not decode an XML-encoded array because it could not allocate an array of the specified dimensions.

Action Check the incoming XML and make sure that the arrayType attribute is specified correctly. For example, make sure that it does not specify a negative dimension or an invalid array size (e.g., too many dimensions or dimensions that are unrealistically large). If the array is unusually large or the server is extremely very low on memory, the possibility also exists that this error was the result of an out-of-memory condition.

ISC.0076.9210E SOAP Message Coder cannot decode message; arrayType attribute value {0} is malformed

Explanation The message coder could not decode an XML-encoded array because it cannot understand the value of the arrayType attribute.

Action Check the incoming XML and make sure that the arrayType attribute is using the correct syntax. For example, make sure that it is not missing a "[" symbol.

ISC.0076.9211E SOAP Message Coder cannot encode output data; pipeline does not match output signature, required variable {0} is missing

Explanation The message coder could not transform the results of a SOAP remote procedure call because the required variable varName was not in the pipeline.

Action On Integration Server, examine the target service to determine why it is not producing the required output variables. Correct the service signature and/or logic after identifying the source of the problem.

ISC.0076.9212E SOAP Message Coder cannot encode output data; pipeline does not match output signature, extra variable {0} in pipeline

Explanation Integration Server encountered an error while processing an RPC/Encoded SOAP message. Either the SOAP message does not match the output signature of the service or the contents of the output pipeline produced by the service do not match the service signature.

Action Do one or more of the following:

- Change the SOAP message response so that it matches the service output signature.
- Change the service output signature so that it matches the expected SOAP message response.
- Ensure that the service produces an output pipeline that matches the service signature.

ISC.0076.9220E	{0} Coder: decoding error; illegal input parameter value(s)
Explanation	One of the input parameters to the encode or decode method is null.
Action	Make sure that the input parameters passed to the encode or decode methods are not null.
ISC.0076.9221E	{0} Coder: decoding error; can't get the SOAP Body from the SOAP Message
Explanation	The SOAP body element cannot be retrieved from the SOAP message.
Action	Make sure that the SOAP message is valid and contains a SOAP body element.
ISC.0076.9222E	{0} Coder: decoding error; can't convert SOAP Message to IS Document
Explanation	Integration Server cannot convert a SOAP message to a document (IData) because of a decoding error.
Action	Contact Software AG Global Support.
ISC.0076.9230E	{0} Coder: encoding error; can't create SOAP Message
Explanation	Integration Server cannot create the SOAP message because an encoding error occurred.
Action	Contact Software AG Global Support.
ISC.0076.9231E	{0} Coder: encoding error; can't add SOAP Body Element to SOAP Message
Explanation	Integration Server cannot add the SOAP body element to the SOAP message because of an encoding error.
Action	Contact Software AG Global Support.
ISC.0076.9234E	{0} Coder: encoding error; can't convert IS Document to XML String
Explanation	Integration Server cannot convert the document (IData) to an XML String because of an encoding error.
Action	Contact Software AG Global Support.
ISC.0076.9236E	SOAP Message Coder cannot decode message; value "{0}" doesn't match expected pattern yyyy-MM-dd
Explanation	The date pattern is invalid.
Action	Make sure that the date value uses the pattern yyyy-MM-dd.

- ISC.0077.0001E** **Config set local host error. Excpt:{0}**
Explanation During startup, Integration Server was not able to set local host information from the values specified on the "watt.net.localhost" property.
Action Examine the value specified for property "watt.net.localhost". The value can either be a machine host name or a string representing the machine's IP address, such as "localhost" or "127.0.0.1".
- ISC.0077.0002** **Unsupported email encoding {0} specified. Defaulting to {1}**
- ISC.0077.0003S** **Cannot initialize password store with null manager**
Explanation Initialization of the code that manages outbound passwords failed. The most likely cause is a problem with the outbound password configuration files.
Action Make sure that the following outbound password configuration files reside on the Integration Server:

 config/txnPassStore.dat

 config/empw.dat

 config/configPassman.cnf

 config/passman.cnf

 See the webMethods Integration Server documentation for information about these files and to determine whether you can restore them. If you cannot determine the source of the problem, contact Software AG Global Support.
- ISC.0077.0004S** **Exception during {0}, type: {1}, msg: {2}**
Explanation A problem occurred when Integration Server tried to store or retrieve an outbound password or retrieve an encryption code from the outbound password store.
Action The outbound password data store, config/txnPassStore.dat, is probably corrupted. See the webMethods Integration Server documentation for information about this file and how to restore it and other outbound password configuration files. If you cannot determine the source of the problem, contact Software AG Global Support.
- ISC.0077.0005** **Unable to {0}, password mgr is null**

ISC.0077.0006E	System property "{0}" equals "{1}". This value is not valid. The default value of "{2}" will be used instead.
Explanation	Integration Server detected an invalid value on the indicated configuration file property.
Action	Refer to the webMethods Integration Server documentation for a description of the property and its required or allowed values.
ISC.0077.9001	Stream is already closed
ISC.0077.9003	Source directory does not exist
ISC.0077.9004	Source File not a directory
ISC.0077.9006E	Could not determine encoding of file {0}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0077.9007E	Invalid encoding, {0}, specified for file {1}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0077.9009	Local name cannot be null
ISC.0077.9010	Local name cannot be an empty string.
ISC.0077.9011	Namespace name cannot be an empty string.
ISC.0077.9012	Invalid value {0} specified for local name.
ISC.0077.9013U	Document to XSD error: Field {0} cannot be represented in XML Schema. The field name contains a prefix but an XML Namespace property is not assigned to the field
Explanation	The document type being used to generate a WSDL document contains a top-level variable whose name includes a prefix (that is, the name is in the format prefix:local name). This variable is not associated with an XML namespace.
Action	Do one of the following:

- (1) Associate the variable with an XML namespace by specifying a value for the variable's XML Namespace property.
- (2) Remove the prefix. Note that some protocols require the use of a prefix. Before removing the prefix, check the service signature's input and output requirements as documented for each protocol in the webMethods Integration Server documentation.

ISC.0077.9014U Document to XSD error: Field {0} cannot be represented in XML Schema. The field name does not conform to the XML NCName definition

Explanation The document type being used to generate a WSDL document contains field names that do not conform to the XML NCName definition.

Action To resolve this error, rename the fields to conform to the QName lexical rules specified in <http://www.w3.org/TR/REC-xml-names/#NT-QName> and the XML namespace and local naming conventions specified in <http://www.w3.org/TR/REC-xml-names/#NT-NCName>.

ISC.0077.9015E The amount of data needed is greater than the amount of data reserved.

Explanation A service needed to write a large amount of data to tspace, but the space the service reserved is not large enough to hold the data.

Action Update your program to reserve more tspace. If your program does not reserve tspace directly, contact Software AG Global Support.

ISC.0077.9016 Provided private key {0} is invalid.

ISC.0077.9017 Unable to read the key/certificate file(s) {0}.

ISC.0077.9018 Provided certificate(s) {0} is/are invalid.

ISC.0077.9022E XOPObjct content cannot be read more than once.

Explanation You attempted to read the contents from an XOPObjct. However, previous logic in either the same service or a previous service has already read the XOPObjct. The XOPObjct instance can only be read one time.

Action Update the service logic so that it reads an XOPObjct only one time.

ISC.0077.9023E	Error while parsing the "{0} {1}" XML string. Parser error: {2}; XML: {3}
Explanation	One of the reference parameters or metadata elements that you specified as message addressing property is not a valid XML string.
Action	Ensure that the XML string that you specify as message addressing reference parameter or metadata element is correct.
ISC.0077.9024E	Error while parsing the "{0} {1}" XML string. The XML that you specify should be namespace qualified. XML: {2}
Explanation	One of the reference parameters that you specified as the message addressing property is not a namespace qualified XML string.
Action	Ensure that the XML string that you specify as message addressing reference parameter element is namespace qualified.
ISC.0081.0002	Error registering universal name {0}, already registered to {1}
ISC.0081.0003	Registered universal name {0} on service {1}
ISC.0081.0004	Duplicate universalName {0} registered to a different service {1}, not this service {2}. Unregister failed.
ISC.0081.0005E	Could not create a unique ID for the trigger from the trigger's name.
Explanation	Integration Server was unable to create a unique identifier for the trigger. This is an internal error.
Action	Try to recreate the trigger. If that fails, contact Software AG Global Support. Be prepared to provide logs and the version number and patch level for Integration Server and your operating system.
ISC.0081.9001E	Node {0} does not exist
Explanation	The node cannot be locked because it has been deleted by another user or otherwise does not exist.
Action	Ensure that the node exists.
ISC.0081.9002E	Cannot perform operation without Write ACL privileges on {0}
Explanation	The user attempting to lock the node does not have write permission.
Action	Ensure that the user has write permission for the file.

ISC.0081.9003E	Unable to lock: {0}. It has been locked by user {1}.
Explanation	The node cannot be locked because it is locked by another user.
Action	Ensure that the node is not already locked by another user.
ISC.0081.9004E	universalName {0} is already registered
Explanation	The specified universal name already exists and is assigned to another element.
Action	Specify a unique universal name that is not already used by another element.
ISC.0081.9005E	Unknown content type: {0}
Explanation	Integration Server cannot create an instance of the specified content type because Integration Server does not recognize or does not support the specified content type.
Action	Specify a content type supported by Integration Server.
ISC.0081.9007E	Node exists
Explanation	An element with this fully qualified name already exists on the Integration Server. Integration Server uses the following format for the fully qualified name: folder.subfolder1.subfolder2:element
Action	Specify an element name whose fully qualified name will be unique to the Integration Server.
ISC.0081.9008E	Node '{0}' does not exist
Explanation	A node (element) in the Integration Server namespace was not specified.
Action	Specify a node (element) in the Integration Server namespace.
ISC.0081.9016E	Search expression {0} is not well-formed. Enter a valid regular expression or element name.
Explanation	The regular expression syntax is not valid.
Action	Ensure that specified regular expression is valid and can be compiled into a valid pattern.
ISC.0081.9164E	Exception occurred during generation of WSDL for service {0}: {1}
Explanation	An error occurred while attempting to validate or generate WSDL for a Web service descriptor. The error text identifies the specific error details.
Action	Use the error details to correct the issue before attempting to save the Web service descriptor or request WSDL for the Web service descriptor.

ISC.0081.9165E	Invalid WSDL. Attribute {0} must appear in element {1} at Operation: {2}, Binding: {3}
Explanation	While creating a Web service descriptor from a WSDL document, Integration Server found an invalid WSDL attribute. Most likely it was a soap:fault definition that was missing the name attribute.
Action	Correct the WSDL document before attempting to create the Web service descriptor.
ISC.0081.9166E	Invalid "use" detected in Operation {0} at Binding {1}
Explanation	While consuming a WSDL document to create a Web service descriptor, Integration Server encountered an invalid value for the use= attribute. The only valid values for the use attribute are "literal" or "encoded".
Action	Correct the use attribute value in the WSDL document and then attempt to create the Web service descriptor.
ISC.0081.9167E	Output signature of an RPC/Literal or a Document/Literal operation cannot have top-level fields that are named "*body" or that begin with the "@" symbol. Operation Name : {0}
Explanation	The output signature of a service used as an operation in an RPC/Literal binder cannot have top-level fields named "*body" or top-level fields that begin with "@".
Action	Change the output signature of the service before attempting to use the service as an operation in an RPC/Literal binder.
ISC.0081.9169e	Input signature of an RPC/Encoded operation cannot have fields named "*body" or that begin with the "@" symbol. Operation Name : {0}
Explanation	A service used as an operation in an RPC/Encoded binder cannot contain fields named "*body" or fields with a name that starts with "@" symbol.
Action	Before using the service as an operation in an RPC/Encoded binder, change the service signature to remove or rename the fields named "*body" or fields with a name that start with "@" symbol.
ISC.0081.9170	Output signature of an RPC/Encoded operation cannot have fields named "*body" or that begin with the "@" symbol. Operation Name : {0}
Explanation	The output signature of a service used as an operation for an RPC/Encoded binder cannot contain a field named "*body" or a field with a name that starts with "@".
Action	Change the output signature of the service before using the service as an operation in an RPC/Encoded binder.

- ISC.0081.9171E Request header of an RPC/Encoded operation cannot have fields named named "*body" or that begin with the "@" symbol. Operation Name : {0}, Header : {1}**
- Explanation** An attempt was made to add a Request Header to an operation used in an RPC/Encoded binder but the document type being added either has a field named "*body" or a field name starting with "@". Neither is allowed in a Header for an operation in an RPC/Encoded binder.
- Action** Remove the fields named "*body" and the fields that start with "a" from the document type. Or use a document type that meets the field name requirements to define the format of the Header.
-
- ISC.0081.9172E Response header of an RPC/Encoded operation cannot have fields named "*body" or that begin with the "@" symbol. Operation Name : {0}, Header : {1}**
- Explanation** An attempt was made to add a Response Header to an operation in an RPC/Encoded binder but the document type being added either has a field named "*body" or a field name starting with "@". Neither is allowed in a Header for an operation in an RPC/Encoded binder.
- Action** Change the document type to meet the field name requirements or use a different document type that meets the requierments to define the format of the Header.
-
- ISC.0081.9173E Fault for an RPC/Encoded operation cannot have fields named "*body" or that begin with the "@" symbol. Operation Name : {0}, Fault : {1}**
- Explanation** An attempt was made to add a Fault to an RPC/Encoded operation but the document type being added either has a field named *body or a field name starting with @. Neither is allowed in a Fault for an RPC/Encoded operation.
- Action** Edit the document type to remove the fields named *body or those that begin with the "@" symbol and then add the Fault to the RPC/Encoded operation. Or, select a different document type to define the format of the Fault.
-
- ISC.0081.9174E Input signature of an RPC/Literal operation cannot have a List field at the top level. Operation Name : {0} Field : {1}**
- Explanation** The input signature of a service used as an operation in a RPC/Literal binder contains a List field at the top level. Services used as operations in RPC/Literal binders cannot have List fields at the top level of the service input signature.
- Action** Remove the List field from the service input signature before attempting to use the service as an operation in a RPC Literal Binder.

ISC.0081.9175E	Output signature of an RPC/Literal operation cannot have a List field at the top level. Operation Name : {0} Field : {1}
Explanation	The output signature of a service used as an operation in an RPC/Literal binder contains a List field at the top level. Services used as operations in RPC/Literal binders cannot have signatures that use List fields at the top level.
Action	Correct the service output signature before attempting to use the service as an operation in a RPC/Literal binder
ISC.0081.9176E	Input signature of an RPC/Literal or a Document/Literal operation cannot have a String Table field. Operation Name : {0} Field : {1}
Explanation	A service with a String table in its service signature cannot be used as an operation for an RPC/Literal or Document/Literal binder.
Action	Change the service signature before attempting to use it as an operation in a an RPC/Literal or Document/Literal binder.
ISC.0081.9177E	Output signature of an RPC/Literal or a Document/Literal operation cannot have a String Table field. Operation Name : {0} Field : {1}
Explanation	The output signature of a service used as an operation in an RPC/Literal or Document/Literal binder cannot contain a a String table.
Action	Change the servie output signature before attempting to use the service as an operation in an RPC/Literal or Document/Literal binder.
ISC.0081.9178E	Input signature of an RPC/Literal operation cannot have identically named fields at the top level. Operation Name : {0} Field : {1}
Explanation	A service used as an operation in a RPC/Literal binder has an input signature containing identically named fileds at the top level. All top-level field names must be unique for services used as operations in an RPC/Literal binder.
Action	Change the service signature before attempting to use the service as an operation in an RPC/Literal binder.
ISC.0081.9179E	Output signature of an RPC/Literal operation cannot have identically named fields at the top level. Operation Name : {0} Field : {1}
Explanation	A service used as an operation in an RPC/Literal binder contains fileds with duplicate names at the top level in the output signature. All top-level field names must be unique for operations in RPC/Literal binders.
Action	Change the output signature of the service before attempting to use the service as an operation in an RPC/Literal binder.

ISC.0081.9180E	Unable to find {0}, needed to generate WSDL for operation {1}
Explanation	A service first provider Web service descriptor uses an IS service as an operation, but that IS service no longer exists in the Integration Server namespace.
Action	Edit the Web service descriptor to use an existing IS service as the operation or recreate the missing IS service.
ISC.0081.9181E	Cannot find document type {0} needed to generate WSDL
Explanation	An internal error has occurred while attempting to validate a Web service descriptor or generate WSDL for the Web service descriptor. The specified document type is used within the definition of the Web service descriptor but it cannot be found in the Integration Server namespace.
Action	If the Web service descriptor was created from WSDL document, for example a consumer Web service descriptor a WSDL first provider Web service descriptor, delete the Web service descriptor and recreate it. If the Web service descriptor is a service first provider Web service descriptor, manually create the missing document type, or correct the references to the document type from the Web service descriptor (for example update the signatures of service used sa operations, update Header definitions, or update Fault definitions).
ISC.0081.9182E	Invalid WSDL schema generated for the service signatures or the document types referred by the WSD "{0}". To view the generated WSDL change the logging level of Namespace(0081) to Trace. Error details: {1}
Explanation	This is a generic message that Integration Server throws for all Xerces parser errors.
Action	If Xerces parser throws "Unique Particle Attribute" error, then a possible workaround for this issue is to set the value of the 'Allow unspecified fields' constraint of the variables in the IS doc type referred by the Web service descriptor to 'False'.
ISC.0081.9194E	The header has a message part "{0}" defined by the type "{1}". Message parts in a header must be defined by the element attribute instead of the type attribute.
Explanation	An attempt was made to set the Pre 8.2 compatibility mode property to false for a Web service descriptor, but the WSDL document used to create the Web service descriptor has Header parts defined using the type attribute. For the Web service descriptor to have the Pre 8.2 compatibility mode property set to false, the Header parts in the WSDL document must use the element attribute.
Action	If you want the Web service descriptor to have a Pre 8.2 compatibility mode property set to false, change the Header parts in WSDL document to use the element attribute and then use Designer recreate the Web service descriptor.

ISC.0081.9195E, W	Invalid message part(s) defined in the wsdl: {0}
Explanation	An invalid Message Part definition was found while consuming WSDL to create a Web service descriptor. The error message lists the specific error details .
Action	Use the error details in the message to correct the WSDL. Then, use the corrected WSDL document to create the Web service descriptor.
ISC.0081.9197E	Cannot find SOAP-JMS trigger "{0}" specified in the provider Web service endpoint alias "{1}" assigned to binder "{2}" in the web service descriptor "{3}".
Explanation	The Web service endpoint alias assigned to the provider Web service descriptor uses a SOAP-JMS trigger that cannot be found. The provider Web service endpoint alias for use with a JMS binder is not valid if the SOAP-JMS trigger specified in the alias cannot be found. The Web service descriptor cannot be saved if a valid Web service endpoint alias is not assigned to a binder that specifies JMS as the transport.
Action	Update the provider Web service endpoint alias to use a different SOAP-JMS trigger. Alternatively, assign a different valid provider Web service endpoint alias to the binder.
ISC.0081.9198E	Cannot find provider Web service endpoint alias "{0}" assigned to binder "{1}" in the web service descriptor "{2}".
Explanation	The Web service endpoint alias assigned to the provider Web service descriptor cannot be found. The Web service descriptor cannot be saved if a Web service endpoint alias is not assigned to a binder that specifies JMS as the transport.
Action	Assign a valid provider Web service endpoint alias to the binder.
ISC.0081.9199W	MEP for operations {0} has changed from In-Only MEP to In-Out MEP. As a result, Integration Server will now execute the corresponding response handlers.
Explanation	Changing the Pre-8.2 compatibility mode property of the Web service descriptor from false to true resulted in a change of the Message Exchange Pattern (MEP) for the specified operations to In-Out. At run time, Integration Server will execute response handler services for the specified operations.
Action	No action required.
ISC.0081.9200W	MEP for operations {0} has changed from In-Out MEP to In-Only MEP. As a result, Integration Server will no longer execute the corresponding response handler services.
Explanation	Because the specified operation has no defined output, changing the Pre-8.2 compatibility mode property of the Web service descriptor from true to false resulted in a change of the Message Exchange Pattern (MEP) for the specified operations to In-Only. At run time, Integration Server will no longer execute the response handler services for the specified operations.
Action	No action required.

- ISC.0081.9201W** **MEP for operations {0} has changed from Robust In-Only MEP to In-Out MEP.**
- Explanation** Changing the Pre-8.2 compatibility mode property of the Web service descriptor from false to true resulted in a change of the Message Exchange Pattern (MEP) for the specified operations to In-Out.
- Action** No action required.
-
- ISC.0081.9203W** **Invoke RefreshConnectors against the Web service descriptor to have the Web service connector's signature updated to reflect the change to the compatibility mode.**
- Explanation** After changing the Pre-8.2 compatibility mode property for a consumer Web service descriptor, the Web service connectors need to be refreshed. If an operation does not have any defined output, refreshing the Web service connectors will update the output signature to reflect the compatibility mode change. If you changed the Pre-8.2 compatibility mode property to false, the Web service connector will no longer have any SOAP message-related output parameters. If you changed the Pre-8.2 compatibility mode property to true, the output signature will include an output parameter for a SOAP fault.
- Action** Refresh the Web service connectors for this Web service descriptor.
-
- ISC.0081.9204E** **Web service descriptor {0} is not available because the WS-Policy file with policy ID {1} attached to the WSD is not present in the policy repository.**
- Explanation** The Web service descriptor is not available because the WS-Policy file attached to the Web service descriptor is deleted or moved from the policy repository.
- Action** The following lists the actions you can take: 1) Ensure that the WS-Policy that is attached to the Web service descriptor resides in the policy repository. -OR- 2) Edit the Web service descriptor so that it no longer uses the deleted or moved WS-Policy file.
-
- ISC.0081.9207E** **Invalid WSDL. wsdl:fault element named {0} must be present in operation {1} of port type {2}**
- Explanation** The WSDL document used to create the WSDL first provider or consumer Web service descriptor does not contain wsdl:fault element in the wsdl:operation of the portType.
- Action** Ensure that the WSDL contains the correct wsdl:fault element in the wsdl:operation of the portType. Contact Software AG Global Support for further assistance.
-
- ISC.0082.0001** **Type {0} exists in schema {1}. Set {1} as owner schema.**

ISC.0082.483E	"fractionDigits"+STR_BASE_FACET_FIXED
Explanation	The fractionDigits facet is fixed for the type and cannot be changed
Action	Do not attempt to change the fractionDigits value for the type.
ISC.0082.90007E	Missing Attribute Information Item
Explanation	The attribute is declared as required but is missing from the instance document.
Action	Correct the instance document.
ISC.0082.9001E	Error while parsing "{0}"
Explanation	An unexpected error occurred while validating the instance document.
Action	Contact Software AG Global Support.
ISC.0082.9002E	Unable to retrieve root element
Explanation	The instance document does not have a root element and cannot be validated.
Action	Correct the instance document.
ISC.0082.9003E	Unable to locate a matching element declaration
Explanation	The element in the instance document does not have an element declaration.
Action	Correct the instance document. Ensure that the element name is correctly spelled.
ISC.0082.9004E	[attributes] property must be empty
Explanation	The element is defined to be of simple type. No attributes may be present.
Action	Remove the attributes from the element in the instance document, or use an element that permits the attribute.
ISC.0082.9005E	EII (s) are not allowed in [children] property
Explanation	The element type does not allow child elements to be present in the content.
Action	Remove the child elements from the instance document, or use a type definition that permits the desired child elements.
ISC.0082.9006E	Unable to locate a matching attribute declaration
Explanation	Integration Server could not locate an attribute declaration for the attribute.
Action	Correct the instance document to reference an attribute for which there is a declaration or remove the attribute from the instance document.

ISC.0082.9008E	Invalid value - does not match fixed value
Explanation	The element declaration has a fixed value. Only that value may be present in the instance document.
Action	Correct the instance document.
ISC.0082.9009E	Child element {0} at position {1} is unexpected
Explanation	The instance document contains an element at the specified location that does not match what is expected.
Action	Correct the instance document.
ISC.0082.9010E	Incomplete content - one or more child elements are expected
Explanation	The instance element does not contain the expected child elements. Content is missing.
Action	Correct the instance document to contain the missing content.
ISC.0082.9011E	Unable to locate attribute declaration
Explanation	Integration Server could not locate a corresponding schema definition for the attribute.
Action	Ensure that a schema for the relevant namespace has been created and that it contains a declaration for the attribute.
ISC.0082.9012E	Unable to locate type definition
Explanation	Integration Server could not locate a corresponding schema definition for the type.
Action	Ensure that a schema for the relevant namespace has been created and that it contains a definition for the type.
ISC.0082.9013E	Unable to locate type definition {0}
Explanation	Integration Server could not locate a corresponding schema definition for the type.
Action	Ensure that a schema for the relevant namespace has been created and that it contains a definition for the type.
ISC.0082.9014E	Unable to locate element declaration
Explanation	Integration Server could not locate a corresponding schema definition for the element.
Action	Ensure that a schema for the relevant namespace has been created and that it contains a declaration for the element.

ISC.0082.9015E	Ambiguous content model in schema - not LL(1)
Explanation	The content model is ambiguous. The given set of particle can validate the same instance with more than one unique set of occurrence counts.
Action	A schema must not be ambiguous. It must be possible to validate an instance without looking ahead in the content model definition. Modify the schema so that the content model is not ambiguous.
ISC.0082.9016E	Unable to resolve QName: {0}
Explanation	The type reference cannot be resolved to a defined type.
Action	Specify a defined type.
ISC.0082.9017E	{0} is not validly derived from {1}
Explanation	The type specified in the instance document is not a valid subtype of the type specified in the schema element declaration.
Action	Correct the instance document by specifying a valid subtype.
ISC.0082.9018E	{0} is an abstract type and cannot be used directly to validate content
Explanation	An abstract type cannot be specified in an instance document.
Action	Specify a concrete type that has been derived from the abstract type.
ISC.0082.9019E	{0} is an abstract element and cannot appear in an instance
Explanation	The instance document contains an element that has been declared abstract in the schema. Abstract elements may not appear in an instance document.
Action	Remove the abstract designation rfrom the schema element definition or use a member of the abstract element's substitution group in the instance document.
ISC.0082.9020E	{0} - xsi:type is used incorrectly (declared type is anonymous)
Explanation	The element declaration does not reference a named type. It is not possible to specify a type in the instance document.
Action	Do not use a type specification for an element that has an anonymous type declaration.
ISC.0082.9022E	The nillable value of {0} is false, hence xsi:nil cannot appear in an instance
Explanation	The element declaration does not have the nillable attribute set to true. The element in the instance document may not have a nil attribute.
Action	Correct the instance document or modify the element declaration to have the nillable attribute set to true.

ISC.0082.9023E	The value of xsi:nil is invalid
Explanation	The instance document element contains a value for the nil attribute that is not valid. The nil attribute must have a value of true or false.
Action	Correct the instance document to specify a valid value for the nil attribute.
ISC.0082.9024E	{0} cannot have content or child elements since xsi:nil is true
Explanation	An element is marked nill in the instance document. The element cannot have any content.
Action	Correct the element in the instance document.
ISC.0082.9026E	Undefined Object found
Explanation	An unexpected object was found in the document.
Action	Correct the instance document by removing the unexpected object.
ISC.0082.9027E	Dimension mismatch, List expected
Explanation	The instance document contains a scalar value where an array is expected.
Action	Correct the input data.
ISC.0082.9028E	Dimension mismatch, Single item expected
Explanation	An array was encountered where a scalar item was expected.
Action	Correct the instance document to specify a scalar item instead of an array.
ISC.0082.9029E	Dimension mismatch, Table expected
Explanation	The instance document contained an object type other than String array of dimension two.
Action	Correct the instance document
ISC.0082.9030E	Type mismatch, String expected
Explanation	The instance document contained an object type other than String.
Action	Correct the instance document.

ISC.0082.9031E	Type mismatch, Document expected
Explanation	The document field was expected to reference another document but instead referenced some other data type.
Action	Correct the instance document.
ISC.0082.9033E	Java type mismatch; expected {0}, got {1}
Explanation	The field is declared to contain one of the supported Java wrapper types but the instance document contains some other data type.
Action	Correct the instance document.
ISC.0082.9034E	Field is absent, field must exist
Explanation	The specified element or attribute is required but is not present in the instance document.
Action	Correct the instance document to contain the required element or attribute.
ISC.0082.9035E	Value cannot be null, allow null value is false
Explanation	The field is declared to not contain nulls, but the instance document contains a null.
Action	Correct the instance document.
ISC.0082.9036E	Duplicate root element {0} found
Explanation	An instance document may contain only one root element.
Action	Correct the instance document so that it has only one root element.
ISC.0082.9037E	Element [{0}] cannot have characters [{1}], because the type's content type is element-only
Explanation	The element's type declaration does not permit text nodes to be present.
Action	Remove the embedded text from the instance document, or use an element type declaration that permits text.
ISC.0082.9038E	Tag occurs too many times
Explanation	The element occurs more times than permitted by the element declaration's maxOccurs attribute.
Action	Correct the instance document.

ISC.0082.9039E	Tag occurs too few time
Explanation	The element occurs fewer times than required by the element declaration's minOccurs attribute.
Action	Correct the instance document.
ISC.0082.9101S	Document Type generation error: {0}
Explanation	An internal failure has occurred.
Action	Contact Software AG Global Support.
ISC.0082.9102S	Integration Server says - {0}
Explanation	An unexpected error has interrupted the conversion process.
Action	Retry the request. If the error recurs contact Software AG Global Support.
ISC.0082.9104S	{0} - unable to locate the root element
Explanation	An internal error has interrupted the conversion process.
Action	Contact Software AG Global Support.
ISC.0082.9105E	Cannot process multi-dimensional array {0}. The maximum supported dimensionality for arrays is 2.
Explanation	Document types may not contain String arrays with dimension greater than two
Action	Do not use String arrays with dimension greater than two.
ISC.0082.9106E	Complex type {0} is recursive. Recursive types are supported only when selecting the option "Generate complex types as document types"
Explanation	It is not possible to expand a type inline if it has a recursive reference. The expansion become infinite.
Action	Use the Generate complex types as document types option.
ISC.0082.9109E	Nested and repeating model groups are not yet supported by strict compliance for the {0} component
Explanation	This version of Integration Server does not support strict conversion of schema content models that have nested or repeating model groups.
Action	Do not use the Strict conversion option. Use the Lax or None option instead.

ISC.0082.9401E	Invalid: length
Explanation	The length facet value must be a non-negative integer.
Action	Specify a valid value for the length facet.
ISC.0082.9402E	Invalid: minLength
Explanation	The minLength facet value must be a non-negative integer.
Action	Specify a valid facet value.
ISC.0082.9403E	Invalid: maxLength
Explanation	The maxLength facet value must be a non-negative integer.
Action	Specify a valid facet value.
ISC.0082.9404E	Invalid: totalDigits
Explanation	The totalDigits facet value must be a positive integer.
Action	Specify a valid facet value.
ISC.0082.9405E	Invalid: fractionDigits
Explanation	The fractionDigits facet value must be a non-negative integer.
Action	Specify a valid value for the fractionDigits facet.
ISC.0082.9408E	maxLength is less than minLength
Explanation	The maxLength facet value is less than the minLength facet value.
Action	Adjust the minLength or maxLength facet so that minLength is less than or equal to maxLength.
ISC.0082.9410E	Invalid enumerated item: {0}. Length of value is not equal to specified length
Explanation	The enumerated item length is not equal to the length required by its type.
Action	Specify a valid value for the type.
ISC.0082.9411E	Invalid enumerated item: {0}. Value is shorter than minimum length
Explanation	The enumerated item is shorter than the required length of its type.
Action	Specify a valid value for the type.

ISC.0082.9412E	Invalid enumerated item: {0}. Value is longer than maximum length
Explanation	The enumerated value is longer than the maximum length allowed by its type.
Action	Specify a valid value for the type.
ISC.0082.9416E	Invalid: minExclusive
Explanation	The minExclusive facet value exceeds the values permitted by the totalDigits or fractionDigits facets.
Action	Specify a valid facet value.
ISC.0082.9417E	Invalid: maxInclusive
Explanation	The maxInclusive facet value exceeds the values permitted by the totalDigits or fractionDigits facet.
Action	Specify a valid value for the maxInclusive facet.
ISC.0082.9418E	Invalid: maxExclusive
Explanation	The maxExclusive facet value exceeds the values permitted by the totalDigits or fractionDigits facets.
Action	Specify a valid value for the maxExclusive facet.
ISC.0082.9425E	maxInclusive is less than minInclusive
Explanation	The maxInclusive facet value is less than the minInclusive facet value.
Action	Change the value of the maxInclusive facet or the minInclusive facet.
ISC.0082.9427E	maxExclusive is less than minExclusive
Explanation	The maxExclusive facet value is less than the minExclusive facet value.
Action	Change the value of the maxExclusive facet or the minExclusive facet.
ISC.0082.9428E	maxExclusive is less than minInclusive
Explanation	The maxExclusive facet value is less than the minInclusive facet value.
Action	Change the value of the maxExclusive facet or the minInclusive facet.

ISC.0082.9436E	maxInclusive is less than minExclusive
Explanation	The maxInclusive facet value is less than the minExclusive facet value.
Action	Change the value of the maxInclusive facet or the minExclusive facet.
ISC.0082.9438E	Invalid enumerated item: {0}
Explanation	The enumeration is empty.
Action	Specify a value for the enumeration facet.
ISC.0082.9440E	Invalid enumerated item (Out of range): {0}
Explanation	The enumeration facet value is outside of the permitted value range of the type.
Action	Correct the enumeration facet value.
ISC.0082.9441E	Invalid enumerated item (Does not match pattern): {0}
Explanation	The enumeration value does not match the pattern facet for the type.
Action	Correct the enumeration value to match the pattern facet.
ISC.0082.9442E	Invalid enumerated item. Length of value is not equal to specified length
Explanation	The length of an enumeration value for a list must be equal to the length facet of the list.
Action	Specify a list enumeration facet with the correct length.
ISC.0082.9443E	Invalid enumerated item. Value is shorter than minimum length
Explanation	The length of an enumeration value for a list must be greater than or equal to the minLength facet of the list.
Action	Specify a list enumeration facet with the correct length.
ISC.0082.9444E	Invalid enumerated item. Value is longer than maximum length
Explanation	The length of an enumeration value for a list must be less than or equal to the maxLength facet of the list.
Action	Specify a list enumeration facet with the correct length.

ISC.0082.9447E	Value does not conform to datatype
Explanation	The value is not a valid instance of the type.
Action	If the error occurs during schema compilation, correct the value specification in the schema. If the error occurs during document validation, it indicates that validation successfully detected an invalid document.
ISC.0082.9449E	"length"+STR_OUT_OF_BOUND
Explanation	The length facet for the list is outside of the permissible range. It must not be less than the minLength facet and it must not be greater than the maxLength facet.
Action	Specify a valid length facet.
ISC.0082.9450E	"minLength"+STR_OUT_OF_BOUND
Explanation	The minLength facet value is either less than the minLength facet value or greater than the maxLength facet value of the base type
Action	Specify a minLength facet value that is within the range allowed by the base type.
ISC.0082.9451E	"maxLength"+STR_OUT_OF_BOUND
Explanation	The maxLength facet value is either greater than the maxLnegth facet value or less than the minLength facet value of the base type.
Action	Specify a maxLength facet value that is within the range allowed by the base type.
ISC.0082.9452E	"minInclusive"+STR_OUT_OF_BOUND
Explanation	The minInclusive facet value is either less than the minInclusive facet value or greater than the maxInclusive facet value of the base type.
Action	Specify a minInclusive facet value that is within the range allowed by the base type.
ISC.0082.9453E	"minExclusive"+STR_OUT_OF_BOUND
Explanation	The minExclusive facet value is either less than the minExclusive facet value or greater than the maxExclusive facet value of the base type.
Action	Specify a minExclsuive facet value that is within the range allowed by the base type.
ISC.0082.9454E	"maxInclusive"+STR_OUT_OF_BOUND
Explanation	The maxInclusive facet value is less than the minInclusive facet value or greater than the maxInclusive facet value of the base type
Action	Specify a correct maxInclusive facet or remove it.

ISC.0082.9455E	"maxExclusive"+STR_OUT_OF_BOUND
Explanation	The maxExclusive facet value is less than the minInclusive facet value or greater than the maxInclusive facet value of the base type.
Action	Specify a correct maxExclusive facet or remove it.
ISC.0082.9457E	"totalDigits"+STR_OUT_OF_BOUND
Explanation	The totalDigits facet value is greater than the totalDigits facet value of the base type.
Action	Specify a totalDigits facet value that is within the range allowed by the base type.
ISC.0082.9458E	"fractionDigits"+STR_OUT_OF_BOUND
Explanation	The fractionDigits facet of a derived type may not exceed the fractionDigits facet of the base type
Action	Correct the fractionDigits facet value so that it does not exceed the fractionDigits facet value of the base type.
ISC.0082.9459E	"whiteSpace"+STR_OUT_OF_BOUND
Explanation	The whiteSpace facet value is incompatible with the whiteSpace facet value of the base type
Action	The whiteSpace facet value must specify white space handling that is more restrictive than the base type facet.
ISC.0082.9460E	No matching enumeration value
Explanation	The element value in the instance document contains a token that is not specified in the element type's enumeration facet.
Action	None. Validation successfully detected an invalid document.
ISC.0082.9463E	Length of value is not equal to specified length
Explanation	The length of the element value in the instance document does not match the length specified by the element type's length facet.
Action	None. Validation successfully detected an invalid document.
ISC.0082.9464E	Value is shorter than minimum length
Explanation	The instance document element value is shorter than the minLength facet for the element type, or the element contains a list with fewer items than the minLength facet of the list type.
Action	None. Validation successfully detected an invalid document.

ISC.0082.9465E	Value is longer than maximum length
Explanation	The instance document element value is longer than the maxLength facet for the element type, or the element contains a list with more items than the maxLength facet of the list type.
Action	None. Validation successfully detected an invalid document.
ISC.0082.9466E	Datatype definition is missing
Explanation	The list specification does not include a type definition for the items of the list.
Action	Specify an item type definition for the list.
ISC.0082.9469E	Value does not match pattern(s)
Explanation	The element value in the instance document does not match the element type's facet pattern.
Action	None. Validation successfully detected an invalid document.
ISC.0082.9471E	The year 0000 is prohibited
Explanation	The facet value may not contain a year value of 0000.
Action	Do not use 0000.
ISC.0082.9472E	totalDigits is less than fractionDigits
Explanation	The fractionDigits facet value must be less than or equal to the totalDigits facet value.
Action	Adjust the fractionDigits or the totalDigits facet value.
ISC.0082.9473E	Invalid facet type
Explanation	An invalid facet is specified.
Action	Specify a valid facet.
ISC.0082.9474E	The input has invalid characters
Explanation	An invalid whitespace character is present in the instance document.
Action	None. Validation successfully detected an invalid document.

ISC.0082.9475E	"length"+STR_BASE_FACET_FIXED
Explanation	The length of the list is fixed and cannot be changed.
Action	Remove the length facet.
ISC.0082.9476E	"minLength"+STR_BASE_FACET_FIXED
Explanation	The minLength facet of the base type is fixed; it cannot be customized.
Action	Remove the minLength facet from the type specification.
ISC.0082.9477E	"maxLength"+STR_BASE_FACET_FIXED
Explanation	The maxLength facet of the base type is fixed; it cannot be customized.
Action	Remove the maxLength facet from the type specification.
ISC.0082.9478E	"minInclusive"+STR_BASE_FACET_FIXED
Explanation	The minInclusive facet of the base type is fixed; it cannot be customized.
Action	Remove the minInclusive facet from the type specification.
ISC.0082.9479E	"minExclusive"+STR_BASE_FACET_FIXED
Explanation	The minExclusive facet of the base type is fixed; it cannot be customized.
Action	Remove the minExclusive facet from the type specification.
ISC.0082.9480E	"maxInclusive"+STR_BASE_FACET_FIXED
Explanation	The maxInclusive facet of the base type is fixed; it cannot be customized.
Action	Remove the maxInclusive facet from the type specification.
ISC.0082.9481E	"maxExclusive"+STR_BASE_FACET_FIXED
Explanation	The maxExclusive facet of the base type is fixed; it cannot be customized.
Action	Remove the maxExclusive facet from the type specification.
ISC.0082.9482E	"totalDigits"+STR_BASE_FACET_FIXED
Explanation	The totalDigits facet of the base type is fixed; it cannot be customized.
Action	Remove the totalDigits facet from the type specification.

ISC.0082.9484E	"whiteSpace"+STR_BASE_FACET_FIXED
Explanation	The whiteSpace facet of the base type is fixed; it cannot be customized.
Action	Remove the whiteSpace facet from the type specification.
ISC.0082.9485E	This datatype cannot have this facet
Explanation	The specified facet is not defined for the type on which it appears.
Action	Remove the facet from the type specification where it appears.
ISC.0082.9486E	Cannot specify length with minLength or maxLength
Explanation	The length facet cannot be specified along with the minLength or maxLength facets.
Action	Remove the length facet or the minLength and maxLength facets.
ISC.0082.9487E	"Invalid enumerated item: {0}. "+STR_EXCEEDS_TOTAL_DIGIT
Explanation	The enumerated item has more total digits than allowed by its type.
Action	Specify a valid value for the type.
ISC.0082.9488E	"Invalid enumerated item: {0}. "+STR_EXCEEDS_FRACTION_DIGIT
Explanation	The enumerated item has more fraction digits than allowed by its type.
Action	Specify a value that is valid for the type.
ISC.0082.9489E	STR_EXCEEDS_TOTAL_DIGIT
Explanation	The total digits in the instance item exceeds the total digits that is valid for the type.
Action	None. Validation has successfully detected an invalid document.
ISC.0082.9490E	STR_EXCEEDS_FRACTION_DIGIT
Explanation	The instance item exceeds the fraction digits allowed for its type
Action	None. Validation successfully detected an invalid document.
ISC.0082.9491E	Value is less than minInclusive
Explanation	The element value in the instance document is less than the minInclusive facet for the element type.
Action	None. Validation successfully detected an invalid document.

ISC.0082.9492E	Value is less than or equal to minExclusive
Explanation	The element value in the instance document is less than or equal to the minExclusive facet for the element type.
Action	None. Validation successfully detected an invalid document.
ISC.0082.9493E	Value is greater than maxInclusive
Explanation	The element value in the instance document exceeds the value of the maxExclusive facet for the element type
Action	None. Validation successfully detected an invalid document.
ISC.0082.9494E	Value is greater than or equal to maxExclusive
Explanation	The element value in the instance document exceeds or equals the value of the maxExclusive facet for the element type
Action	None. Validation successfully detected an invalid document.
ISC.0082.9495E	"Length constraint cannot be customized. "+STR_LENGTH_EXISTS
Explanation	The base type already has a length facet; it is not possible to change the length facet.
Action	Remove the length facet from the type specification.
ISC.0082.9496E	"Cannot specify minLength if length is specified. "+STR_LENGTH_EXISTS
Explanation	The length and minLength facets are mutually exclusive.
Action	Remove one of the facets from the type specification.
ISC.0082.9497E	"Cannot specify maxLength if length is specified. "+STR_LENGTH_EXISTS
Explanation	The maxLnegth and length facets are mutually exclusive.
Action	Remove one of the facets from the type specification.
ISC.0082.9712E	Cannot specify both {0} and {1}
Explanation	The schema properties are mutually exclusive. Only one can be specified.
Action	Decide which property is relevant and remove the other.

ISC.0082.9723E	Xerces Java parser determined that the XML schema definition is invalid
Explanation	<p>The Xerces Java parser determined that an XML schema definition is invalid. This can occur in the following situations:</p> <ul style="list-style-type: none">- When creating an asset (IS schema, document type, or flow service) from an XML Schema definition.- When creating a Web service descriptor from a WSDL document that contains a schema element or references an XML schema definition.- When refreshing Web service connectors- When executing a Web service connector- When changing the IS schemas, document types, or service signatures associated with a Web service descriptor
Action	<p>Use the information returned by the Xerces Java parser to make the schema valid.</p> <p>Alternatively, if you do not want the Xerces Java parser to perform schema validation, do one of the following:</p> <ul style="list-style-type: none">- When creating the asset, clear the Validate schema using Xerces check box- For an existing Web service descriptor, set the Validate schema using Xerces property to False.
ISC.0083.9001E	Requested type not available
Explanation	<p>The pub.xml:queryXMLNode service failed to execute because the Integration Server XQL query engine encountered an internal error.</p>
Action	<p>Contact Software AG Global Support.</p>
ISC.0083.9002E	Tree type not supported
Explanation	<p>The pub.xml:queryXMLNode service failed to execute because the supplied query object supplied was not a valid XML Node object.</p>
Action	<p>Examine the service input and ensure it is a valid XML node object. You can invoke the pub.xml:xmlStringToXMLNode or pub.xml:loadXMLNode service to obtain the document and transform it to an XML node object before performing the query.</p>
ISC.0083.9003E	Expression is empty
Explanation	<p>The pub.xml:queryXMLNode service failed to execute because no query expression was specified.</p>
Action	<p>Examine the logic and make sure that the query expression is not empty.</p>

ISC.0083.9004E	Node parameter is null
Explanation	The pub.xml:queryXMLNode service failed to execute because the XML Node to be queried was empty or missing.
Action	Examine the XML node object submitted for query and make sure it is not null.
ISC.0083.9005E	"{0}" object type not currently supported.
Explanation	The pub.xml:queryXMLNode service failed to execute because the document submitted was not an instance of an XML Node object. This service can obtain information from XML nodes only. Note: An XML node is a special representation of an XML document that can be consumed by the Integration Server. Most webMethods services that operate on XML documents require an XML node as input.
Action	Examine the document submitted and make sure that you have used pub.xml:xmlStringToXMLNode or pub.xml:loadXMLNode service to convert the document to an XML Node object before performing the query.
ISC.0083.9006E	Regions are not supported on IData objects
Explanation	The pub.xml:queryXMLNode service failed to execute because it tried to perform a region query on an IData object; the Integration Server does not support this type of query. Currently only XML node objects are supported for region queries. Note: An XML node is a special representation of an XML document that can be consumed by the Integration Server. Most webMethods services that operate on XML documents require an XML node as input.
Action	Do not attempt to query regions on IData objects.
ISC.0083.9007E	Source not available for IData objects
Explanation	The pub.xml:queryXMLNode service failed to execute because it tried to obtain information from a Document (an IData object) instead of an XML Node. This service can obtain information from XML Nodes only. Note: An XML node is a special representation of an XML document that can be consumed by the Integration Server. Most webMethods services that operate on XML documents require an XML node as input.
Action	Do not attempt to query the source from Documents (IData objects).
ISC.0083.9008E	Recursion detected in IData at {0}; can't have recursion when query contains or //
Explanation	The pub.xml:queryXMLNode service failed to execute because it tried to perform a query on a recursive IData object, but the query contained " " (a union operator) or "/" (a path operator). These operators are not allowed when querying a recursive IData object.
Action	Do not attempt to query a recursive IData object when the query contains " " or "/".

ISC.0083.9009	Illegal typecast in query expression
ISC.0083.9011	'true()' or 'false()' expected
ISC.0083.9012E	(' expected
Explanation	The pub.xml:queryXMLNode service failed to execute because it specified an incorrect syntax. Specifically, the left-hand parenthesis "(" was missing after the "true" or "false" Boolean function.
Action	Examine the query expression and make sure it uses the correct syntax. There must be matching parentheses after any "true" or "false" functions, e.g., true(), false().
ISC.0083.9013E)' expected
Explanation	The pub.xml:queryXMLNode service failed to execute because the right-hand parenthesis ")" was missing after the "true" or "false" Boolean function.
Action	Examine the query expression and make sure it uses the correct syntax. There must be matching parentheses after any "true" or "false" functions, e.g., true(), false().
ISC.0083.9014E	Invalid boolean method: {0}
Explanation	The pub.xml:queryXMLNode service failed to execute because the Integration Server XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0083.9015E	Comparison requires an rvalue
Explanation	The pub.xml:queryXMLNode service failed to execute because the right-hand operand was not present in the query. Left- and right-hand operands are required for a comparison query.
Action	Examine the query expression and make sure that both the left- and right-hand operands are supplied.
ISC.0083.9016E	Comparison righthand operand evaluates to more than one value
Explanation	The pub.xml:queryXMLNode service failed to execute a comparison query because the value of the right-hand operand was not a scalar.
Action	Examine the query expression and make sure the value of the right-hand operand is a scalar or a value that can be cast at runtime to a scalar.

ISC.0083.9017E	Comparison operator is missing.
Explanation	The pub.xml:queryXMLNode service failed to execute a comparison query because the expression contained \$any\$ or \$all\$, but no comparison operator. A comparison operator must be specified in an expression that contains \$any\$ or \$all\$.
Action	Examine the query expression and make sure it contains a comparison operator.
ISC.0083.9018E	Only relative queries allowed inside filters.
Explanation	The XQL query expression contains an absolute path inside the filter. For example, "book[/author]".
Action	Make sure that the XQL query expression contains a relative path inside the filter. For example, "book[author]".
ISC.0083.9019U	'[' is not matched by ']'
Explanation	The pub.xml:queryXMLNode service failed to execute because the left-hand square bracket "[" was specified but the right-hand square "]" bracket was missing. An expression that uses a filter operator or a subscript operator must contain matching parentheses.
Action	Examine the query expression and make sure it contains matching brackets "[]" .
ISC.0083.9020E	Filter brackets may only select nodes or attributes
Explanation	The pub.xml:queryXMLNode service failed to execute because a subquery within the "[]" was not a node or attribute. A subquery must be a node or an attribute when a filter operation is used.
Action	Examine the query expression and make sure that the subquery contained within the "[]" is a node or attribute.
ISC.0083.9021E	Invalid or missing term
Explanation	The pub.xml:queryXMLNode service failed to execute because a query expression using a filter operator specified an invalid term or no terms at all.
Action	Examine the query expression and make sure it specifies a valid term. Valid terms are: dot('.'), left parenthesis('('), at('@'), and wildcard('*').
ISC.0083.9022E	'(' is not matched by ')'. Token "{0}" found.
Explanation	The pub.xml:queryXMLNode service failed to execute because the query expression contained a left parenthesis "(" that was not matched by a right parenthesis ")", but rather by another character. The query expression must specify matching parentheses when a filter operator is used.
Action	Examine the query expression and make sure it contains matching parentheses "()".

ISC.0083.9023E	'(' is not matched by ')'. End of query found.
Explanation	The pub.xml:queryXMLNode service failed to execute because the query expression contained a left parenthesis "(" but no right parenthesis ")". A query expression must specify matching parentheses when a filter operator is used.
Action	Examine the query expression and make sure it contains matching parentheses "()".
ISC.0083.9024E	Invalid or misplaced term "{0}"
Explanation	The pub.xml:queryXMLNode service failed to execute because an invalid character was specified in a query expression that contains a filter operator. Valid characters are dot ".", left and right parentheses "(" and ")", at "@", and wildcard "*".
Action	Examine the query expression and ensure that only valid characters are specified.
ISC.0083.9025E	Invalid attribute name "{0}:"
Explanation	The XQL query expression contains an invalid attribute name. This attribute belongs to a namespace. For example, "//@prefix:123".
Action	Make sure that the XQL query expression contains a valid attribute name. For example, "//@prefix:a123".
ISC.0083.9026E	Invalid or missing attribute name
Explanation	The XQL query expression contains an invalid or undefined attribute name. For example, "//@123" or "//@".
Action	Make sure that the XQL query expression contains a valid attribute name. For example, "//@a123".
ISC.0083.9027E	attribute() takes a quoted string
Explanation	The pub.xml:queryXMLNode service failed to execute because the optional parameter passed to attribute() function was not a quoted string.
Action	Examine the query expression and make sure that it uses the correct syntax and passes a quoted string to the attribute() function.
ISC.0083.9028E	attribute() incorrect attribute name "{0}"
Explanation	The XQL query expression contains an invalid attribute name inside the attribute(). For example, "//book/attribute('123')".
Action	Make sure that the XQL query expression contains a valid attribute name inside the attribute(). For example, "//book/attribute('a')".

ISC.0083.9029	Only nodes have attributes
ISC.0083.9030E	count() takes a query parameter
Explanation	The XQL query expression contains a parameter in the count(), which is not allowed. For example, "//book/count(1)".
Action	Make sure that the XQL query expression does not contain a parameter in the count(). For example, "//book/count()".
ISC.0083.9031E	Type {0} can't be cast to Date
Explanation	The pub.xml:queryXMLNode service failed to execute because the query engine returned a value that could not be cast as a date.
Action	Examine the query expression and make sure it uses the correct syntax and specifies the correct query.
ISC.0083.9032E	date({0}){1}
Explanation	The pub.xml:queryXMLNode service failed to execute because the parameter passed to the XQL date() function was not in a format that could be converted to a date.
Action	Examine the detailed error message and make sure that the string parameter passed to the XQL date() function can be converted to a date.
ISC.0083.9033E	date(){0} Error offset:{1}
Explanation	The pub.xml:queryXMLNode service failed to execute because the parameter passed to the XQL date() function could not be parsed.
Action	Examine the detailed error message and the position provided in it and make sure that the string parameter passed to the date() function in the query expression can be parsed to a date.
ISC.0083.9034E	Invalid element name "{0}:"
Explanation	The XQL query expression contains an invalid element name. This element belongs to a namespace. For example, "//a:1".
Action	Make sure that the XQL query expression contains a valid element name. For example, "//a:b".

ISC.0083.9035	Invalid or missing element name
ISC.0083.9036E	element() takes a quoted string
Explanation	The pub.xml:queryXMLNode service failed to execute because the optional parameter passed to XQL element() function was not a quoted string.
Action	Examine the query expression and make sure it uses the correct syntax and passes a quoted string to the element() function.
ISC.0083.9037E	element() incorrect attribute name "{0}"
Explanation	The XQL query expression contains an invalid parameter in element(). For example, "/book/element("1")".
Action	Make sure that the XQL query expression contains a valid parameter name in element(). For example, "/book/element("a")".
ISC.0083.9038	Only nodes have child elements
ISC.0083.9039E	Type {0} can't be cast to Float
Explanation	The pub.xml:queryXMLNode service failed to execute because it expected a float, but the value it received was not a float.
Action	Examine the query expression. Make sure it uses the correct syntax and specifies the query you intended.
ISC.0083.9040E	id() takes a quoted string
Explanation	The pub.xml:queryXMLNode service failed to execute because the optional parameter passed to XQL id() function was not a quoted string.
Action	Examine the query expression and make sure it uses the correct syntax and passes a quoted string to the XQL id() function.
ISC.0083.9041E	Type {0} can't be cast to Integer
Explanation	The pub.xml:queryXMLNode service failed to execute because it expected an integer, but the value it received could not be cast as an integer.
Action	Examine the query expression. Make sure it uses the correct syntax and specifies the query you intended.

ISC.0083.9042E	name() takes a quoted string
Explanation	The pub.xml:queryXMLNode service failed to execute because the optional parameter passed to XQL name() function was not a quoted string.
Action	Examine the query expression and make sure it uses the correct syntax and passes a quoted string to the XQL name() function.
ISC.0083.9043E	name() requires a non-empty string
Explanation	The pub.xml:queryXMLNode service failed to execute because the parameter passed to the XQL name() function was empty.
Action	Examine the query expression and make sure it uses the correct syntax and passes a non-empty quoted string to the name() function.
ISC.0083.9044E	node() must be used relative to a node
Explanation	The pub.xml:queryXMLNode service failed to execute because it specified an incorrect syntax for the XQL node() function or tried to execute the function against a non-node object.
Action	Examine the query expression and make sure it uses the correct syntax for the node() function and executes the function against a node.
ISC.0083.9045E	region() must be used relative to a node
Explanation	The pub.xml:queryXMLNode service failed to execute because it specified an incorrect syntax for the XQL region() function or tried to execute the function against a non-node object.
Action	Examine the query expression and make sure it uses the correct syntax for the region() function and executes the function against a node.
ISC.0083.9046	Query parameters of region() must return nodes
ISC.0083.9047	region() can't have more than one region start node
ISC.0083.9048	region() can't have more than one region end node
ISC.0083.9049E	textnode() must be used relative to a node
Explanation	The pub.xml:queryXMLNode service failed to execute because it specified an incorrect syntax for the XQL textnode() function or tried to execute the function against a non-node object.
Action	Examine the query expression and make sure it uses the correct syntax for the textnode() function and executes the function against a node.

ISC.0083.9050	Function or method name expected
ISC.0083.9051E	'(' missing after function or method name
Explanation	The pub.xml:queryXMLNode service failed to execute because a left-hand parenthesis "(" was missing after the function or method name. The correct syntax is functionname() or methodname() .
Action	Examine the query expression and make sure that it uses the correct syntax for the function or method.
ISC.0083.9052E	Query contains truncated invocation
Explanation	The pub.xml:queryXMLNode service failed to execute because an incomplete expression was provided for a function call. Specifically, the expression contained a left parenthesis "(" but the invocation parameter or right parenthesis ")" was missing. Examples: function() function(parameter
Action	Examine the query expression and make sure it uses the correct syntax.
ISC.0083.9053E	')' must terminate parameter list
Explanation	The pub.xml:queryXMLNode service failed to execute because the right parenthesis ")" was missing from the parameter list that was passed to the XQL function.
Action	Examine the query expression and make sure it uses the correct syntax and includes the right parenthesis to terminate the parameter/parameter list.
ISC.0083.9054E	missing function parameter
Explanation	The pub.xml:queryXMLNode service failed to execute because the parameter required by the XQL function was not provided.
Action	Examine the query expression and make sure it uses the correct syntax and includes the required parameter.
ISC.0083.9055E	Invalid number of parameters in function or method "{0}"
Explanation	The pub.xml:queryXMLNode service failed to execute because an invalid number of parameters were passed to the XQL function or method.
Action	Examine the query expression and make sure it uses the correct syntax and passes the correct number of parameters to the XQL function. See XQL Query Language at http://www.w3.org/TandS/QL/QL98/pp/xql.html for method or function reference.

ISC.0083.9056E	"{0}" is not a recognized function name
Explanation	The pub.xml:queryXMLNode service failed to execute because an invalid XQL function name was provided.
Action	Examine the query expression and make sure that it only uses the valid XQL functions. Integration Server currently supports the following pre-defined functions: attribute(), Boolean(), comment(), count(), date(), element(), float(), id(), integer(), name(), node(), not(), pi(), region(), textnode(), true(), false().
ISC.0083.9057E	"{0}" is not a recognized method name
Explanation	The pub.xml:queryXMLNode service failed to execute because an invalid XQL method name was provided.
Action	Examine the query expression and make sure that it only uses the valid XQL methods. Integration Server currently supports the following pre-defined methods: basename(), count(), end(), index(), namespace(), nodename(), nodetype(), nodetypestring(), prefix(), regex(), regexinsensitive(), regexinsensitivematch(), regexmatch(), rawtext(), stringmatch(), source(), text(), value().
ISC.0083.9058E	Methods may only be applied to nodes and attributes
Explanation	The pub.xml:queryXMLNode service failed to execute because the Integration Server XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0083.9059	regex() takes a quoted string
ISC.0083.9060	regexinsensitive() takes a quoted string
ISC.0083.9061	regexinsensitivematch() takes a quoted string
ISC.0083.9062	regexmatch() takes a quoted string
ISC.0083.9063	stringmatch() takes a quoted string

ISC.0083.9064E	Query contains extraneous terms
Explanation	The pub.xml:queryXMLNode service failed to execute because there was a syntax error in the expression. Specifically, there were extraneous terms in the expression.
Action	Examine the query expression and make sure it uses the correct syntax.
ISC.0083.9065E	Cannot parse queries of type {0}
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0083.9066E	Left operand of / must be either a node or an attribute
Explanation	The pub.xml:queryXMLNode service failed to execute because the query expression specified the unary child operator "/" but the value specified by the left-hand operand was not a node type or an attribute type.
Action	Examine the query expression and make sure the left-hand operand is a node or attribute.
ISC.0083.9067E	Only relative queries allowed in relative paths.
Explanation	The XQL query expression contains an absolute path inside another absolute path. For example, "/x/(/y)".
Action	Make sure that the XQL query expression does not contain an absolute path embedded inside another absolute path.
ISC.0083.9068E	Left operand of // must be a node
Explanation	The pub.xml:queryXMLNode service failed to execute because the query expression specified the unary child descendant operator "//" but the value specified by the left-hand operand was not a node.
Action	Examine the query expression and make sure the left-hand operand is a node.
ISC.0083.9069E	Invalid subscript argument
Explanation	The pub.xml:queryXMLNode service failed to execute because no argument was supplied for the subscript operator or the argument supplied was not an integer.
Action	Examine the query expression and make sure that a valid integer is provided for the subscript operator.

ISC.0083.9070E	Only values of the same type may be unioned
Explanation	The pub.xml:queryXMLNode service failed to execute a union operation because the left-hand operand is not the same type as the right-hand operand.
Action	Examine the query expression and make sure that both operands are of the same type. Valid types are node, attribute, string, integer, float, and Boolean.
ISC.0083.9071E	{0} and {1} types are not comparable
Explanation	The pub.xml:queryXMLNode service failed to execute a comparison operation because the left-hand operand is not the same type as the right-hand operand.
Action	Examine the query expression and make sure that the left-hand operand and right-hand operand are of the same type. Valid types are node, attribute, string, integer, float, and Boolean.
ISC.0083.9072E	The {0} relation is not defined on {1} types
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0083.9073E	Unrecognized expression type "{0}"
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0083.9074	generateQueryString Node doc is a required parameter. Must not be null.
ISC.0083.9075	generateQueryString String queryType is a required parameter. Must not be null.
ISC.0083.9076E	generateQueryString only supports WQL, XQLVALUES and XQL types. Unsupported type "{0}"
Explanation	The pub.xml:queryXMLNode service failed to execute because an expression attempted to evaluate an unsupported type. Integration Server currently only supports WQL,XQLVALUES and XQL.
Action	Contact Software AG Global Support.

ISC.0083.9077E	Unknown TreeExpression type
Explanation	Integration Server tried to process an unsupported type. This is an internal error. Currently only the WQL, XQLVALUES and XQL types are supported.
Action	Contact Software AG Global Support.
ISC.0083.9078E	Cannot cast "{0}" to boolean
Explanation	The pub.xml:queryXMLNode service failed to execute because it attempted to cast a string value to a Boolean type. The possible causes are: (1) the left-hand and right-hand operands specified with a comparison operator were not of the same type (2) the value returned by the query was of an unexpected type.
Action	Examine the query expression and make sure it specifies the correct syntax and performs the query you expected.
ISC.0083.9079E	Cannot cast "{0}" to a float
Explanation	The pub.xml:queryXMLNode service failed to execute because it attempted to cast a string value to a float. The possible causes are: (1) the left-hand and right-hand operands specified with a comparison operator were not of the same type (2) the value returned by the query was of an unexpected type.
Action	Examine the query expression and make sure it specifies the correct syntax and performs the query you expected.
ISC.0083.9080E	Cannot cast "{0}" to an integer
Explanation	The pub.xml:queryXMLNode service failed to execute because it attempted to cast a string value to an integer. The possible causes are: (1) The left-hand and right-hand operands specified with a comparison operator were not of the same type. (2) The value returned by the query was of an unexpected type.
Action	Examine the query expression and make sure it specifies the correct syntax and performs the query you expected.
ISC.0083.9081E	Cannot cast "{0}" to a long
Explanation	The pub.xml:queryXMLNode service failed to execute because it attempted to cast a string value to a long type. The possible causes are: (1) the left-hand and right-hand operands specified with a comparison operator were not of the same type (2) the value returned by the query was of an unexpected type.
Action	Examine the query expression and make sure it specifies the correct syntax and performs the query you expected.

ISC.0083.9082	IO error occurred while parsing a grove in a VARNAME expression: {0}
ISC.0083.9083E	XqlQuery.getStringWithIdentities: Query "{0}" does not yield strings:{1}
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0083.9084E	XqlQuery.getString: Query "{0}" does not yield strings:{1}
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0083.9085E	XqlQuery: Query yields unknown type
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0083.9086E	XqlQuery.getNodeWithIdentities: Query "{0}" does not yield nodes
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0083.9087E	XqlQuery.getNode: Query "{0}" does not yield nodes
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0083.9088E	XqlQuery.getNodeArrayWithIdentities: Query "{0}" does not yield nodes
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.

- ISC.0083.9089E** **XqlQuery.getNodeArray: Query "{0}" does not yield nodes**
Explanation The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action Contact Software AG Global Support.
- ISC.0083.9090E** **XqlQuery.getIData: Query "{0}" does not yield nodes**
Explanation The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action Contact Software AG Global Support.
- ISC.0083.9091E** **Query does not yield an IData instance as expected**
Explanation The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action Contact Software AG Global Support.
- ISC.0083.9092E** **XqlQuery.getIDataArray: Query "{0}" does not yield nodes**
Explanation The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action Contact Software AG Global Support.
- ISC.0083.9093E** **Query "{0}" does not yield only IData instances as expected**
Explanation The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action Contact Software AG Global Support.
- ISC.0083.9094E** **Floating point numbers must begin with a digit**
Explanation The pub.xml:queryXMLNode service failed to execute because an invalid query expression was provided. Specifically, a floating point number was provided in an incorrect format. A digit must immediately precede and follow the dot "." term. Examples of the correct format are "1.23" and "-0.99.". Examples of incorrect formats are ".99" and "1."
Action Examine the query expression and make sure that it uses the correct format for floating point numbers.

ISC.0083.9095E	Unrecognized operator '{0}'
Explanation	The pub.xml:queryXMLNode service failed to execute because an expression contained an unrecognized operator.
Action	Examine the query expression and make sure it only uses the valid operators specified in the XQL specification. For more information, see XQL Query Language at http://www.w3.org/TandS/QL/QL98/pp/xql.html .
ISC.0083.9096E	Invalid number: "{0}"
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine could not parse a numberString to an integer or a float because the string does not represent an integer or float number.
Action	Examine the query expression and make sure that it uses the correct syntax. See XQL Query Language at http://www.w3.org/TandS/QL/QL98/pp/xql.html for more information.
ISC.0083.9097	Missing terminal quote: {0}{1}
ISC.0083.9098E	"{0}" is not a recognized function or method name
Explanation	The pub.xml:queryXMLNode service failed to execute because an invalid XQL function or method was specified in the query expression.
Action	Examine the query expression and make sure that you only use a set of pre-defined XQL function names or method names in the query. For a list of pre-defined functions and methods in XQL, see The XML Query Language (XQL) at http://www.w3.org/TandS/QL/QL98/pp/xql.html .
ISC.0083.9099E	Method requires Node tree for query "{0}".
Explanation	The pub.xml:queryXMLNode service failed to execute because the XQL query engine encountered an internal error.
Action	Contact Software AG Global Support.
ISC.0083.9100	Queries on attributes are not supported by IData trees.
ISC.0083.9101	nsDecls and namespaces are not supported by IData trees.

ISC.0084.9004E	Access Denied
Explanation	The user does not have permission to access an Integration Server resource. Review the server log to find the resource and the user who was denied access.
Action	If the user should have access to this resource, either add the user to the group that is in the Allowed list of the execute ACL of the resource, or add one of this user's groups to the Allowed list of the execute ACL of the resource.
ISC.0084.9005E	Invalid Session ID or Session Expired
Explanation	Whenever a client presents a Session ID that is no longer valid, Integration Server throws this exception and sets the 401 HTTP response code to force the client to re-authenticate.
Action	No action is necessary.
ISC.0084.9006E	Server is not accepting new requests at this time
Explanation	A client request was submitted during Integration Server shutdown. Integration Server does not accept requests during shutdown.
Action	Resubmit the request after Integration Server becomes available again.
ISC.0084.9007E	Server has reached client limit
Explanation	Integration Server was not able to create a session to service a client request. Integration Server sends this error with HTTP response code 503 to the client.
Action	Review the server log and error log to find possible causes of this error.
ISC.0084.9102E	Resubmit data array cannot be null.
Explanation	webMethods Monitor failed to resubmit the rejected document because the data array for resubmission was not supplied.
Action	Examine the document to be resubmitted and make sure that it is valid and not empty.
ISC.0084.9103E	Resubmit data cannot be null.
Explanation	webMethods Monitor failed to resubmit the rejected document because the data for resubmission was not supplied.
Action	Examine the document to be resubmitted and make sure that it is valid and not empty.

ISC.0084.9104E	Auditcontexts cannot be null or empty.
Explanation	webMethods Monitor failed to resubmit the rejected document because the "auditContexts" field in the data was either null or empty.
Action	Examine the document to be resubmitted and make sure that it is valid and that the "auditContexts " field is not missing.
ISC.0084.9105E	Service name cannot be null or empty.
Explanation	webMethods Monitor failed to resubmit the rejected document because the "serviceName" field in the data was either null or empty.
Action	Examine the document to be resubmitted and make sure that it is valid and that the "serviceName" field is not missing.
ISC.0084.9106U	Service for resubmission does not exist on the server.
Explanation	webMethods Monitor failed to resubmit the rejected document because the service for resubmission does not exist on Integration Server.
Action	Examine the document to be resubmitted and make sure that the name specified in the "serviceName" field is a valid service and exists on Integration Server.
ISC.0084.9107E	Input pipeline cannot be null.
Explanation	webMethods Monitor failed to resubmit the rejected document because the "pipeline" field in the data was either null or empty.
Action	Examine the document to be resubmitted and make sure that it is valid and that the "pipeline" field is not missing.
ISC.0084.9108E	User name cannot be empty or null.
Explanation	webMethods Monitor failed to resubmit the rejected document because the "userName" field in the data was either null or empty.
Action	Examine the document to be resubmitted and make sure that it is valid and that the "userName" field is not missing.
ISC.0084.9109E	Access is denied to the user.
Explanation	The current user does not have permission to invoke the service that is being resubmitted.
Action	To grant permission to the user, add the user to a group that is listed in the Execute ACL assigned to the service.

- ISC.0084.9301E **Not Authorized to use Server**

- ISC.0086.9000 **Recipient certificate at index {0} not in recognizable format**

- ISC.0086.9001 **bytes must be byte[]**

- ISC.0086.9005 **URL must begin with "http:" or "https:"**

- ISC.0086.9006 **HTTP method is null**

- ISC.0086.9007 **only use one of: data.stream, data.bytes or data.mimeStream on a POST**

- ISC.0086.9008 **do not use: data.stream, data.bytes or data.mimeStream on a GET**

- ISC.0086.9009 **{0}: input parameter required**

- ISC.0086.9010 **invalid HTTP method: {0}**

- ISC.0086.9012 **Invalid TO field: {0}**

- ISC.0086.9013 **Invalid CC field: {0}**

- ISC.0086.9014 **Invalid BCC field: {0}**

- ISC.0086.9015 **files must be of type Values[]**

- ISC.0086.9016 **No filename nor content included in the attachment!**

ISC.0086.9017	mimeStream must be an InputStream
ISC.0086.9018	'pattern' is a required input
ISC.0086.9020	{0} does not exist
ISC.0086.9021	{0} cannot be read
ISC.0086.9022	{0} is a directory
ISC.0086.9023	Missing required parameter: '\$name'
ISC.0086.9024	Missing required parameter: 'fileName'
ISC.0086.9025	Saved pipeline {0} does not exist
ISC.0086.9026	Missing required parameter: 'response'
ISC.0086.9028	getLastError invoked outside of a Flow
ISC.0086.9029	parameter 'key' is required when fromList is not null
ISC.0086.9030	input must be an InputStream
ISC.0086.9031	index must be a non-negative integer
ISC.0086.9032	{0} input parameter required

ISC.0086.9033	content input parameter required
ISC.0086.9034	Message content is not empty
ISC.0086.9035	Missing required value: {xmlvalues}
ISC.0086.9036	Missing required value: {record}
ISC.0086.9037	Missing one or more required values: {recordList,name}
ISC.0086.9039	Certificate not in recognizable format
ISC.0086.9040	Certificate at index {0} not in recognizable format
ISC.0086.9041	Invalid certificate input at index {0}
ISC.0086.9042	Could not create certs only SMIME object {0}
ISC.0086.9043	Not a valid InputStream
ISC.0086.9044	InputData not in recognizable format
ISC.0086.9045	Invalid recipient certificates information
ISC.0086.9046	Invalid recipient certificate input at index {0}
ISC.0086.9047	Incorrect keylength specified: {0}

ISC.0086.9048	Unsupported encryption algorithm specified: {0}
ISC.0086.9049	Could not create SMIME Enveloped object {0}
ISC.0086.9050	Invalid private key information
ISC.0086.9052	Invalid signer certificate file information
ISC.0086.9053	Certificate file not in any recognizable format
ISC.0086.9054	Could not create signed SMIME object {0}
ISC.0086.9055	Could not retrieve content from input
ISC.0086.9056	Encrypted Content not in recognizable format
ISC.0086.9057	Recipient certificate not in any recognizable format
ISC.0086.9058	Supplied certificate cannot decrypt content
ISC.0086.9059	Not a valid privateKey
ISC.0086.9060	Unable to decrypt symmetric key
ISC.0086.9061	Certs-Only data not in recognizable format
ISC.0086.9062	Signed Content not in recognizable format

ISC.0086.9064	bytes must be type byte[]
ISC.0086.9065	already in exclusive wait
ISC.0086.9066	cannot obtain exclusive wait
ISC.0086.9068	No string table data supplied
ISC.0086.9069	No column names supplied
ISC.0086.9070	{0} Maybe the wrong number of column names
ISC.0086.9071	No row data supplied
ISC.0086.9072	Deprecated Service: table to documentList conversion is now automatic.
ISC.0086.9074	Cannot process null input
ISC.0086.9075	Input not a byte array
ISC.0086.9076	Input in incorrect format, certificate cannot be loaded
ISC.0086.9077	No algorithm has been specified
ISC.0086.9079	No keys provided to sign the provided data
ISC.0086.9080	Data to sign not in the expected format (byte[])

ISC.0086.9081	An error occurred processing the signer information for {0}, {1}
ISC.0086.9082	An error occurred creating the signature for the data: {0}
ISC.0086.9083	No signature provided to verify
ISC.0086.9084	No data provided to verify detached signature
ISC.0086.9085	An error occurred attempting to reconstruct the signature: {0}
ISC.0086.9086	Signature provided is not PKCS#7 SignedData
ISC.0086.9087	Invalid data encountered when building the certificate chain, either an instance of a certificate or a byte[] expected
ISC.0086.9088	Invalid data provided for certificate entry {0}, expecting a byte[]
ISC.0086.9089	Parameter {0} is missing
ISC.0086.9090	Parameter {0} is of incorrect type
ISC.0086.9091	Parameters {0}, '\$filestream' and '\$filedata' are all missing. One of these must not be null.
ISC.0086.9093	Http Error: {0} - {1}
ISC.0086.9094	No LDAP URL specified
ISC.0086.9095	No connection key provided

- ISC.0086.9096 **Bad connection key: {0}**
- ISC.0086.9097 **No lookup name provided**
- ISC.0086.9098 **No search filter provided**
- ISC.0086.9099 **No target name provided**
- ISC.0086.9102 **No schema information available**
- ISC.0086.9103 **Required parameter 'packageName' is missing**
- ISC.0086.9104 **Required parameter 'publisher' is missing**
- ISC.0086.9105 **The 'fileList' or 'fileNamePattern' parameter is required**
- ISC.0086.9106 **Required parameter 'package' is missing**
- ISC.0086.9107 **Package "{0}" has already been released, select a different name instead**
- ISC.0086.9108 **Required parameter 'package' is missing**
- ISC.0086.9109 **Required parameter 'packageFile' is missing**
- ISC.0086.9113 **No such user present : {0}**
- ISC.0086.9117 **Task being updated is not a one-time task**

ISC.0086.9118	Task being updated is not a repeating task
ISC.0086.9119	Task being updated is not a complex task
ISC.0086.9120	Inputs cannot be null
ISC.0086.9121	Certificate file not found: {0}
ISC.0086.9122	Certificate file {0} not in any recognizable format
ISC.0086.9123	IO Exception encountered while reading file: {0}
ISC.0086.9125	lockMode must be "{0}" or "{1}". Supplied value was {2}.
ISC.0086.9126	key of entry to unlock can not be null
ISC.0086.9127	key of value to add can not be null
ISC.0086.9128	key of entry to insert or update can not be null
ISC.0086.9129	key of entry to get can not be null
ISC.0086.9131	key of entry to remove can not be null
ISC.0086.9132	value to insert or update can not be null
ISC.0086.9133	Cannot obtain entry lock for key

- ISC.0086.9134 **Missing required parameter: tid**

- ISC.0086.9135 **Missing required parameter: alias**

- ISC.0086.9136 **Missing required parameter: service**

- ISC.0086.9138 **Not allowed to activate package "{0}"**

- ISC.0086.9139 **The target name specified by {0} is {1}, not allowed to install package or patch to {1}**

- ISC.0086.9140 **Not allowed to enable package "{0}"**

- ISC.0086.9141 **Not allowed to disable package "{0}"**

- ISC.0086.9142 **Not allowed to recover package "{0}"**

- ISC.0086.9143 **Package file "{0}" does not exist in Inbound directory**

- ISC.0086.9144 **Exception occurred while checking target package name**

- ISC.0086.9145 **Invalid or non-existing package name "{0}" provided**

- ISC.0086.9146 **A required parameter {0} was not supplied**

- ISC.0086.9147 **The Universal Name {0} is unknown**

- ISC.0086.9148 **The Universal Name {0} is already defined for {1} in the registry**

ISC.0086.9149	The Universal Name {0} is already defined as a Service
ISC.0086.9150	The Universal Name {0} is not a valid QName
ISC.0086.9151	Parameter {0} is the wrong data type
ISC.0086.9152	Not allowed to reload package "{0}"
ISC.0086.9153	Unknown package name "{0}" provided
ISC.0086.9154	Package "{0}" is already active
ISC.0086.9155	Package "{0}" is already enabled
ISC.0086.9156	Package "{0}" is already disabled
ISC.0086.9157	Not able to convert headerLines to byte array
ISC.0086.9158	Missing required parameter: 'headerLines'
ISC.0086.9159	Invalid input. 'headerLines' must be an instance of IData
ISC.0086.9160	Missing required parameter: 'body'
ISC.0086.9161	Invalid input. 'bytes' must be an instance of byte array
ISC.0086.9162	Invalid input. 'stream' must be an instance of InputStream

ISC.0086.9163	Invalid input. 'body' must be an instance of IData
ISC.0086.9164	Error reading inputstream: 'stream'
ISC.0086.9165	Both 'bytes' and 'stream' cannot be absent
ISC.0086.9166	bytes is a required field
ISC.0086.9167	stream is a required field
ISC.0086.9168	Could not retrieve raw data from implicitly signed message
ISC.0086.9169	Alias for Enterprise Gateway Proxy not specified
ISC.0086.9170	No of Connections to Enterprise Gateway Proxy not specified
ISC.0086.9171	New threshold for outstanding Requests not specified
ISC.0086.9172	Connection ID not specific
ISC.0086.9173	Listener Type not specified
ISC.0086.9174	Invalid input. "{0}" is a required parameter of type IData
ISC.0086.9175	Invalid input. "{0}" is a required parameter of type String
ISC.0086.9176E	Invalid input. "{0}" must be of type String
Explanation	The specified input parameter must have a value of type String, but does not.
Action	Set the specified input paramater to a value that is of type String.

ISC.0086.9177	Invalid input. "{0}" must be a positive integer
Explanation	The specified input parameter contains an invalid value.
Action	Set the value of the specified input parameter to a positive integer.
ISC.0086.9178	Invalid input. "{0}" must be true or false
Explanation	The specified parameter must be set to true or false.
Action	Set the specified parameter to true or false.
ISC.0086.9179	Missing required parameter: {0}
ISC.0086.9180	Invalid value for parameter: {0}. {0} is not a recognized numeric type
ISC.0086.9181E	Missing required parameter: pattern
Explanation	The pattern input parameter is required, but has not been provided.
Action	Supply a value for the pattern input parameter.
ISC.0086.9182	Missing required value: {document}
ISC.0086.9183	Missing one or more required values: {documentList,name}
ISC.0086.9184	Invalid or non-existing package name "{0}" provided
ISC.0086.9185	Missing required parameter: version
ISC.0086.9186	Missing required parameter: JVMversion
ISC.0086.9187	Missing required parameter: targetPkgVersion
ISC.0086.9189	Invalid date pattern or input

ISC.0086.9193	FTP session key not specified
ISC.0086.9198	Missing content or filename
ISC.0086.9199	{0} is not a valid directory!
ISC.0086.9200	Private key data must be in a byte array (byte[]).
ISC.0086.9201	Certificate chain data must be an array of byte array (byte[][]).
ISC.0086.9202	Certificate at position {0} in array is not in any recognizable format
ISC.0086.9203	Not a valid long number
ISC.0086.9204E	"{0}" is required.
Explanation	A required input value is missing.
Action	Supply the missing input value and re-execute the service.
ISC.0086.9205E	If "{0}" is supplied, it must be zero (0) or greater.
Explanation	The indicated input value is a negative number, but it must be zero or a positive number.
Action	For the specified parameter, enter a value of 0 or a positive integer. Alternatively, if the specified parameter is optional, delete the supplied value.
ISC.0086.9206E	"offset" + "length" cannot exceed the size of "{0}".
Explanation	The values specified for offset and length are invalid because they will cause Integration Server to write data from the stream past the end of the supplied buffer.
Action	Supply valid values for offset and length.
ISC.0086.9207E	The mark method is not supported by the supplied InputStream.
Explanation	A service invoked the pub.io:mark service to mark a location on a stream, but the supplied stream does not implement the mark and reset methods.
Action	If you are invoking a user-written service, either use a different kind of InputStream that implements the mark and reset methods, or do not invoke the pub.io:mark service. Otherwise, contact Software AG Global Support.

ISC.0086.9208E	The reset method is not supported by the supplied InputStream.
Explanation	A service invoked the pub.io:reset service to reset to a location on a stream, but the supplied stream does not implement the mark and reset methods.
Action	If you are invoking a user-written service, either use a different kind of InputStream that implements the mark and reset methods, or do not invoke the pub.io:reset service.
ISC.0086.9209E	"{0}" must be greater than zero (0).
Explanation	The input variable specified is negative or zero, but the value must be a positive number.
Action	Supply a value greater than zero for the indicated input parameter.
ISC.0086.9210	User specified encoding "{0}" does not match content encoding received from remote server.
ISC.0086.9211	No LDAP credentials provided
ISC.0086.9212	{0} is a required input
ISC.0086.9213	Notification for {0} is already registered
ISC.0086.9214	Notification for {0} does not exist
ISC.0086.9215	Invalid private key provided
ISC.0086.9217	Invalid certificate chain provided
ISC.0086.9218	Invalid partner certificate provided
ISC.0086.9220	Access to internal passwords denied

- ISC.0086.9221 Password input is required
- ISC.0086.9222 Password input must be WmSecureString
- ISC.0086.9223 Old password input is required
- ISC.0086.9224 New password input is required
- ISC.0086.9225 Password must be of type WmSecureString
- ISC.0086.9226 Password for key already exists
- ISC.0086.9227 Password for key does not exist. Must add password as new entry
- ISC.0086.9228 Key cannot be null
- ISC.0086.9229 Key cannot be empty
- ISC.0086.9230 Must input string, bytes, or chars
- ISC.0086.9232 XML needs to be provided.
- ISC.0086.9233 A set of values for nodeSelectors must be provided.
- ISC.0086.9234 Either a recipientID or a recipientCert must be provided.
- ISC.0086.9235 The XML could not be parsed.

ISC.0086.9236	Unable to set up the XPath context.
ISC.0086.9237	The keystore or key alias information is incorrect.
ISC.0086.9238	A value for baseURI must be provided for an enveloping signature.
ISC.0086.9239	The reference URI did not provide any content to sign.
ISC.0086.9245	The signatureSelector parameter must contain a value.
ISC.0086.9248	The signature could not be found.
ISC.0086.9250	Parameter [{0}] is not of type: [{1}]
ISC.0086.9251	Column [{0}] is missing for the parameter: [{1}]
ISC.0086.9252	key[{0}] does not exist in the pipeline
ISC.0086.9253	[{0}] could not be converted to a number
ISC.0086.9254	[{0}] could not be converted to a date
ISC.0086.9255	Invalid date pattern[{0}] specified.
ISC.0086.9256	File [{0}] does not exist
ISC.0086.9257	File [{0}] exists, but is a directory

- ISC.0086.9258 **Directory [{0}] cannot be created**

- ISC.0086.9259 **File [{0}] exists, but is read-only**

- ISC.0086.9260 **Directory [{0}] does not exist**

- ISC.0086.9261 **[{0}] is not a directory**

- ISC.0086.9262 **Failed to delete original file [{0}] after copying the [{1}]**

- ISC.0086.9263 **Specified path [{0}] is not on the [{1}] allowed list in the fileAccessControl configuration file**

- ISC.0086.9264 **Error reading properties file: [{0}]**

- ISC.0086.9265 **originalObject parameter does not implement java.io.Serializable interface**

- ISC.0086.9266 **File [{0}] already exists**

- ISC.0086.9268 **PARAM_NUMLIST [{0}]: [{1}] could not be parsed**

- ISC.0086.9270 **No PrivateKey entry found for key alias {0}.**

- ISC.0086.9271 **Invalid index[{0}]. Value should be between {1} and {2}**

- ISC.0086.9272 **{0} cannot be empty**

- ISC.0086.9273 **Invalid holiday date pattern [{0}] specified in the holidays.cnf file**

ISC.0086.9274	Could not parse the holiday date [{0}] specified in the holidays.cnf file using the pattern [{1}]
ISC.0086.9275	Invalid weekend [{0}]. Valid value should be one of the following: 'sunday', 'monday', 'tuesday', 'wednesday', 'thursday', 'friday', 'saturday'
ISC.0086.9276	'itemList' parameter should be an array
ISC.0086.9277	Specified command [{0}] is not on the allowedOSCommands list in the OSCommands.cnf file
ISC.0086.9278	[{0}] may not exist or it may not be a directory
ISC.0086.9279	Specified working directory [{0}] is not on the 'allowedWorkingDirectories' list in the OSCommands.cnf file
ISC.0086.9280	Unable to find the node corresponding to the provided signature node selector xpath {0}.
ISC.0086.9281	Unable to find the encryption certificate for recipient {0}.
ISC.0086.9282	Unable to resolve the certificate to verify the signature.
ISC.0086.9283	An invalid schema location pair was provided
ISC.0086.9284	Folder{0} is not empty Explanation The specified folder must be empty. Action Delete the contents of the specified folder or specify an empty folder.
ISC.0086.9285	Invalid folder name {0}. Error : {1} Explanation The specified folder name is invalid. Action Specify a valid folder name.

ISC.0086.9286	HSM based Keystore is not supported
ISC.0086.9289E	Applications cannot use an HTTP Status-Code of {0}
Explanation	Only valid HTTP Status-Codes may be supplied.
Action	Supply a valid HTTP Status-Code.
ISC.0086.9310E	Could not restore pipeline from file {0}.
Explanation	The pub.flow:restorePipelineFromFile service failed because the specified pipeline file could not be found in the IntegrationServer_directory\pipeline directory.
Action	Make sure the specified pipeline file exists in the IntegrationServer_directory\pipeline directory, and then restore the pipeline.
ISC.0086.9311E	Could not save pipeline to file {0}.
Explanation	The pub.flow:savePipelineToFile service failed because the IntegrationServer_directory\pipeline directory could not be found or does not exist.
Action	Make sure the IntegrationServer_directory\pipeline directory exists, and then save the pipeline.
ISC.0086.9318E	{0} must be "{1}" or "{2}".
Explanation	The service failed because the specified input variable contains an invalid value. The values allowed for the input variable are listed in the message text.
Action	Enter a valid value for the input variable.
ISC.0086.9319E	{0} must be "{1}", "{2}", "{3}" or "{4}".
Explanation	The service failed because the specified input variable contains an invalid value. The values allowed for the input variable are listed in the message text.
Action	Enter a valid value for the input variable.
ISC.0086.9320E	If {0} is supplied, {1} must also be supplied.
Explanation	The service failed because the combination of input variables defined in the service is invalid. The message text lists the required input variable combinations.
Action	Provide a valid combination of input variables.

ISC.0086.9321E	If {0} is "{1}", {2} must be supplied.
Explanation	The service failed because the combination of input variables defined in the service is invalid. The message text lists the required input variable combinations.
Action	Provide a valid combination of input variables.
ISC.0086.9322E	{0} must be "{1}", "{2}", "{3}" or "{4}" or "{5}".
Explanation	The service failed because the specified input variable contains an invalid value. The values allowed for the input variable are listed in the message text.
Action	Enter a valid value for the input variable.
ISC.0086.9323E	{0} must be "{1}", "{2}" or "{3}".
Explanation	The service failed because the specified input variable contains an invalid value. The values allowed for the input variable are listed in the message text.
Action	Enter a valid value for the input variable.
ISC.0086.9324E	If {0} is "{1}", {2} and {3} must be supplied.
Explanation	The service failed because the combination of input variables defined in the service is invalid. The message text lists the required input variable combinations.
Action	Provide a valid combination of input variables.
ISC.0088.0001U	SOAPException: {0}
Explanation	The SOAP message handler could not process the message because an error occurred.
Action	Examine the details element in the SOAP exception message for information about the specific failure that occurred.
ISC.0088.0002E	Failed registering SOAP Processor, missing parameter: {0}
Explanation	Integration Server failed to add the specified SOAP processor to the processor registry using the pub.soap.processor:registerProcessor service.
Action	Examine the service input and make sure that the fully qualified service name is specified correctly for input parameter "svcName".
ISC.0088.0003E	Failed registering SOAP Processor {0} as directive {1}; directive already registered
Explanation	Integration Server failed to add the specified SOAP processor to the processor registry using the pub.soap.processor:registerProcessor service.
Action	Make sure that the "directive" parameter specifies the correct directive. (Directive names are case-sensitive.) In addition, make sure that the specified directive is not already registered in the SOAP Processor registry. Often, this error occurs because the registry already contains a processor registered to the specified directive.

ISC.0088.0004E	Failed registering SOAP Processor {0} as directive {1}; unknown service {0}
Explanation	Integration Server failed to add the specified SOAP processor to the processor registry using the pub.soap.processor:registerProcessor service.
Action	Examine the service input and make sure that the fully qualified service name is specified correctly for input parameter "svcName". (Service names are case-sensitive.) Often, this error occurs because the service does not exist on the Integration Server.
ISC.0088.0005E	Failed unregistering SOAP Processor, missing parameter: {0}
Explanation	The pub.soap.processor:unregisterProcessor service failed to execute because the "directive" parameter was not supplied.
Action	Examine the service input and make sure that the "directive" parameter specifies the correct directive. (Directive names are case-sensitive.) Often, this error occurs because the directive is not specified.
ISC.0088.0006E	Failed unregistering SOAP Processor {0}; no such directive registered
Explanation	Integration Server failed to remove the specified processor from the SOAP Processor registry using the pub.processor:unregisterProcessor service.
Action	Make sure that the "processorName" parameter specifies the correct directive. (Remember that directive names are case-sensitive.) In addition, make sure that the specified directive is currently registered in the SOAP Processor registry. It may have already been removed. Usually, this error occurs because the registry does not contain a processor registered to the specified directive.
ISC.0088.0007E	Failed registering SOAP Processor {0} as directive {1}; invalid character(s) in directive
Explanation	Integration Server failed to add the specified processor to the SOAP Processor registry using the pub.processor:registerProcessor service.
Action	Examine the service input and make sure that the value for the "directive" parameter only contains characters that are part of a Unicode identifier. See the description of the Java standard for the full range of Unicode values. Usually, this error occurs because the specified directive contains characters that are not part of a Unicode identifier.
ISC.0088.0008	Failed registering JAX Handler {0}; Handler already registered
ISC.0088.0009	Failed initializing JAX Handler {0}; error {1}

ISC.0088.0010	Failed destroying JAX Handler {0}; error {1}
ISC.0088.0011	Failed registering JAX Handler {0}, missing parameter {1}
ISC.0088.0012	Failed unregistering JAX Handler {0}; handler not registered
ISC.0088.0013	Failed unregistering JAX Handler {0}, missing parameter {1}
ISC.0088.0014	Failed listing JAX Handlers, missing parameter {0}
ISC.0088.0015	Failed finding JAX Handler {0}, missing parameter {1}
ISC.0088.0016	Failed finding JAX Handler {0}, handler not registered
ISC.0088.0017	Failed finding JAX Handler for header {0}:{1}
ISC.0088.0020	pub.client:soapClient SOAP request sent: {0}
ISC.0088.0022	pub.client:soapClient OutputValidationError - pipeline: {0} result: {1}
ISC.0088.0023	pub.client:soapClient InputValidationError - result: {0}
ISC.0088.0024	Encode input ({0}): {1}
ISC.0088.0026	Decode input ({0}): {1}
ISC.0088.0028E	Service handler {0} could not be registered. A service handler by that name already exists
Explanation	A service handler with the provided name already exists.
Action	Specify a unique name for the service handler.

ISC.0088.0029E	Error initializing handler {0}. Error {1}
Explanation	An error occurred while initializing the JAX-RPC header handler.
Action	The init() method of the JAX-RPC handler threw an error. Correct the error in init() method.
ISC.0088.0030E	Error destroying service handler {0}. Error:{1}
Explanation	An error occurred while destroying the JAX-RPC handler.
Action	The destroy() method of the JAX-RPC Handler has thrown an error. Correct the error in destroy() method.
ISC.0088.0031E	Service handler {0} could not be registered. Missing required parameter {1}
Explanation	A parameter required to register the service handler was not provided.
Action	Provide the missing parameter.
ISC.0088.0032E	Service handler {0} could not be unregistered. A service handler by that name is not registered
Explanation	The specified service handler is not registered.
Action	Provide the name of a registered service handler.
ISC.0088.0033E	Service handler {0} could not be unregistered. Missing required parameter {1}
Explanation	The service handler could not be unregistered because a required parameter is missing.
Action	Provide the missing parameter.
ISC.0088.0034E	Registered service handlers could not be listed. Missing required parameter {0}
Explanation	The list of registered service handlers could not be created because a required input parameter was not provided.
Action	Provide the missing input parameter.
ISC.0088.0035E	Service handler {0} could not be found. Missing required parameter {1}
Explanation	Service handler could not be found because a required input parameter was not provided.
Action	Provide the missing input parameter.

ISC.0088.0036E	Service handler {0} could not be found. Service handler is not registered
Explanation	A service handler with the provided name does not exist.
Action	Register a service handler with the provided name or specify the name of an existing registered service handler.
ISC.0088.0037E	Could not find service handler for header {0}:{1}
Explanation	The QName of the header does not correspond to a registered service handler.
Action	Verify that the QName of the header corresponds to a registered service handler or register a service handler for the provided universal name.
ISC.0088.0038E	Error while processing asynchronous SOAP response received by the consumer Web service descriptor {0}. SOAP Message : {1}
Explanation	Integration Server failed to process the asynchronous SOAP response directed to the consumer web service descriptor specified in the message.
Action	Check the server log and error log to find possible causes of this error and take corrective steps.
ISC.0088.0039E	Error while processing asynchronous SOAP response received by the consumer Web service descriptor {0}.
Explanation	Integration Server failed to process the asynchronous SOAP response directed to the consumer Web service descriptor specified in the message, possibly because the SOAP response is not well formed.
Action	Check the server log and error log to find possible causes of this error and take corrective steps.
ISC.0088.0100	WS Security processing failed : Unable to convert SOAPMessage into a Document : {0}
ISC.0088.0101	WS Security processing failed : Unable to convert Document into a SOAPMessage : {0}
ISC.0088.0102	WS Security processing failed : A valid Document was not specified. Unable to create SOAPMessage

- ISC.0088.0103 **WS Security processing failed : UsernameToken supported only with PasswordType as Text**

- ISC.0088.0104 **WS Security processing failed : Invalid Credentials. User name {0}**

- ISC.0088.0105 **WS Security processing failed : Authentication failed for user : {0}**

- ISC.0088.0106 **WS Security processing failed : X509 Authentication failed with exception : {0}**

- ISC.0088.0107 **WS Security processing failed : Unable to create Keystore**

- ISC.0088.0108 **WS Security processing failed : Unable to create Crypto**

- ISC.0088.0109 **WS Security processing failed : Invalid private key passed in to the Web service connector.**

- ISC.0088.0110 **WS Security processing failed : Invalid certificate chain passed in to the Web service connector.**

- ISC.0088.0111 **WS Security processing failed : Error while reading the private key/certificates from the Web service endpoint**

- ISC.0088.0112 **WS Security processing failed : Error while operating on Keystore**

- ISC.0088.0113 **WS Security processing failed : Unable to resolve partner certificate for encrypting the response**

- ISC.0088.0114 **WS Security processing failed : Untrusted certificate chain**

- ISC.0088.0115 **WS Security processing failed : Error during response encryption while retrieving partner certificate from the certificate mapper.**

ISC.0088.0116	WS Security processing failed : Invalid outbound security policy. Username token assertion not supported in the response
ISC.0088.0117	WS Security processing failed : Invalid outbound security policy. X509Authenticion token assertion not supported in the response
ISC.0088.0118	WS Security processing failed : Unable to resolve private key for signing or decrypting the message
ISC.0088.0119	WS Security processing failed : Unexepected error occurred while accessing the Keystore/Truststore
ISC.0088.0120	WS Security processing failed : Unable to resolve partner certificate for encrypting the request
ISC.0088.0200E	WS Security processing failed: Unable to retrieve {0} provider Web service endpoint alias named "{1}"
Explanation	Integration server could not find the provider Web service endpoint alias with the type and name specified in the message.
Action	Create an appropriate provider Web service endpoint alias.
ISC.0088.0201E	WS Security processing failed: Decryption of encrypted key failed because the key is encrypted with an unknown certificate.
Explanation	Integration Server is unable to find a private key corresponding to the certificate used to encrypt the key.
Action	Configure an appropriate keystore in the WS Security Properties section of the appropriate consumer or provider Web service endpoint alias or by using the Decryption Key option under Security > Certificates in the Integration Server Administrator.
ISC.0088.0202E	WS Security processing failed: Unable to resolve the private key required for signing the SOAP request.
Explanation	Private key required for signing the SOAP request is not configured.
Action	Configure a keystore by adding the values in the WS Security Properties section of the appropriate consumer Web Service endpoint alias or by using the Signing Key option under Security > Certificates in the Integration Server Administrator.

ISC.0088.0203E **WS Security processing failed: Unable to resolve the private key required for signing the SOAP response.**

Explanation Private key required for signing the SOAP response is not configured.

Action Configure a keystore by adding the values in the WS Security Properties section of the appropriate provider Web Service endpoint alias or by using the Signing Key option under Security > Certificates in the Integration Server Administrator.

ISC.0088.0204E **WS Security processing failed: Invalid partner certificate passed into the Web service connector.**

Explanation Value provided for auth/message/partnerCert field while executing the Web service connector is invalid.

Action Provide a valid certificate for auth/message/partnerCert.

ISC.0088.0205E **WS Security processing failed: Invalid partner certificate provided in the endpoint alias "{0}".**

Explanation Partner certificate file provided in the endpoint alias mentioned in the message is invalid.

Action Specify a valid partner certificate file in the endpoint alias mentioned in the message.

ISC.0088.0206E **WS Security processing failed: Unable to resolve the private key required for decrypting the SOAP request.**

Explanation Private key required for decrypting the SOAP request is not configured.

Action Configure a keystore by adding the values in the WS Security Properties section of the appropriate provider Web service endpoint alias or by using the Decryption Key option under Security > Certificates in the Integration Server Administrator.

ISC.0088.0207E **WS Security processing failed: Unable to resolve the private key required for decrypting the SOAP response.**

Explanation Private key required for decrypting the SOAP response is not configured.

Action Configure a keystore by adding the values in the WS Security Properties section of the appropriate consumer Web service endpoint alias or by using the Decryption Key option under Security > Certificates in the Integration Server Administrator.

ISC.0088.0208E **WS Security processing failed: Decryption failed because the SOAP message is encrypted with an unknown certificate.**

Explanation Integration server is unable to find a private key corresponding to the certificate used to encrypt the message.

Action Configure an appropriate keystore in the WS Security Properties section of the appropriate consumer or provider Web service endpoint alias or by using the

	Decryption Key option under Security > Certificates in the Integration Server Administrator.
ISC.0088.0209E	WS Security processing failed: Signature verification failed because the certificate associated with the signing private key is unknown.
Explanation	Integration server is unable to find a certificate corresponding to the private key used to sign the message.
Action	Ensure that the certificate corresponding to the private key used to sign the message is imported into the certificate mapper using Security > Certificates > Configure Client Certificates in the Integration Server Administrator.
ISC.0088.0210E	WS Security processing failed: Error retrieving certificate from certificate mapper.
Explanation	Integration Server failed to retrieve the certificate corresponding to the private key that was used to sign the message. Integration Server encountered an unexpected error when attempting to retrieve the certificate from the certificate mapper.
Action	Probable cause is that the embedded database of Integration Server that is used to store the certificates is corrupted. Contact Software AG Global Support.
ISC.0088.0211W	WS Security processing failed: Binder for the SOAP action "{0}" in the Web service descriptor "{1}" not found. Integration Server will use server private keys and certificates for handling WS-Security.
Explanation	Integration Server cannot find the binder for the specified SOAP action in the Web service descriptor. Integration Server is unable to use the private keys and certificates from the endpoint alias. As a result, Integration Server will use the server private keys and certificates.
Action	Ensure that the correct SOAP action is specified in the incoming SOAP request.
ISC.0088.0212E	WS Security processing failed: HSM keystores are not supported.
Explanation	The Integration Server WS-Security functionality does not support HSM keystores.
Action	Use a supported keystore type, for example, PKCS12 or JKS.
ISC.0088.0213E	WS Security processing failed: Integration server only supports Username token with password type {0}, but received with password type {1}.
Explanation	Incoming SOAP request has an unsupported password type in the Username token. Integration Server supports Username tokens with passwords of type: http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-username-token-profile-1.0/#PasswordText only.
Action	Ensure that the SOAP request the requester/client sends has a valid Username token.

ISC.0088.0214E	WS Security processing failed: Unable to retrieve {0} consumer Web service endpoint alias named "{1}"
Explanation	Integration server could not find the consumer Web service endpoint alias with the type and name specified in the message.
Action	Create an appropriate consumer Web service endpoint alias.
ISC.0088.9129E	Invalid node: XML blocks must be in a container
ISC.0088.9131E	Invalid node: must be well-formed XML
ISC.0088.9142E	Invalid Body Entry. SOAP Body Entries must have a namespace name.
ISC.0088.9143E	Invalid Header Entry. SOAP Header Entries must have a namespace name.
ISC.0088.9165E	Soap Coder not found for a {0} SOAPMessage
ISC.0088.9167E	Service not found for soapAction = {0}
ISC.0088.9168E	SOAP Version Mismatch: SOAP Version "{0}" in request does not match the SOAP version "{1}" of the Web service.
ISC.0088.9169E	External WSDL URL does not exist for {0}, its a service first WSD.
ISC.0088.9170E	SOAP Version Mismatch: SOAP Version "{0}" in response does not match the SOAP version "{1}" of the Web service.
ISC.0088.9256E	Fault returned by invoked service
ISC.0088.9300E	Attachment Processing Failed: Can't get the size of the attachment due to an I/O Error

ISC.0088.9301E	Attachment Processing Failed: Can't retrieve the content due to an I/O Error
ISC.0088.9302E	Attachment Processing Failed: Attachment contains 'null' content
ISC.0088.9303E	Attachment Processing Failed: The value for Data Handler is 'null'
ISC.0088.9304E	Attachment Processing Failed: Data Handler contains 'null' Input Stream
ISC.0088.9320E	MTOM Attachments Processing Failed: Cannot convert SOAP Message to XOP Package; 'null' value for 'Web Service Descriptor'
Explanation	The Web service descriptor identified by the part of request URL (for provider) or passed Web service descriptor name (for consumer) as parameter, does not exist.
Action	Correct the URL or correct the passed Web service descriptor name or create a proper Web service descriptor.
ISC.0088.9321E	MTOM Attachments Processing Failed: Cannot convert SOAP Message to XOP Package; base64Binary encoded data is not in the Canonical Lexical form
Explanation	Base64Binary encoded data is not in Canonical Lexical form; it contains line break characters or tabs.
Action	Convert the Base64Binary data into Canonical Lexical form.
ISC.0088.9322E	MTOM Attachments Processing Failed: Cannot convert SOAP Message to XOP Package; invalid SOAP Message
Explanation	The SOAP Message is invalid; either it is not well formed or it does not contain valid namespace declarations.
Action	Check the structure and content of the SOAP message.
ISC.0088.9323	MTOM Attachments Processing Failed: Cannot convert SOAP Message to XOP Package; I/O Error occurred
Explanation	Converting SOAP Message to XOP Package has been interrupted by another thread.
Action	Retry the action that caused it.

ISC.0088.9324E	MTOM Attachments Processing Failed: Cannot convert XOP Package to SOAP Message; 'Content-Id' header field is missing in some of the attachments
Explanation	One or more attachments does not contain the “Content-Id” field. This field is required to put the content of the attachment back into the SOAP message.
Action	Verify that the serialization of XOP Package to MIME stream had “Content-Id” present in the corresponding MIME part.
ISC.0088.9325E	MTOM Attachments Processing Failed: Cannot serialize the XOP Message; unable to retrieve bytes from SOAP String using the SOAP Message Content Encoding
Explanation	The conversion of SOAP String to byte array using the encoding specified for SOAP message has failed.
Action	Correct the content encoding specified for the SOAP message.
ISC.0088.9326E	MTOM Attachments Processing Failed: Cannot serialize the XOP Message; MIME serialization has failed
Explanation	Serialization of XOP Package to MIME Stream has failed.
Action	Verify the structure of SOAP Message is correct. Particularly the elements which contains base64Binary data.
ISC.0088.9327E	MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; value of the 'Content-Type' header of the MIME message is not equal to 'multipart/related'
Explanation	Value for the “Content-Type” header field of the MIME message is not equal to “multipart/related”.
Action	Verify that you have passed the correct value for “Content-Type” while serializing the MIME message.
ISC.0088.9328E	MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; value of the 'type' parameter of the 'Content-Type' header of the MIME message is not equal to 'application/xop+xml'
Explanation	Value for the “type parameter” of the “Content-type” header field of the MIME message is not equal to “application+xop+xml”.
Action	Verify that you have passed the correct value for “type” parameter while serializing the MIME message.

ISC.0088.9329E	MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; value of the 'start-info' parameter of the 'Content-Type' header of the MIME message is not equal to 'application/soap+xml'
Explanation	Value for the “start-info” parameter of the “Content-Type” header field of the MIME message is not equal to “application/soap+xml”.
Action	Check if you have passed the correct value for “start-info” parameter while serializing the MIME message otherwise pass the correct value for it.
ISC.0088.9330E	MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; 'Content-Type' header of the Root MIME Part is invalid
Explanation	Invalid content type for Root MIME part.
Action	Verify that you have passed the correct value for “Content-Type” header field of the Root MIME Part while serializing the MIME message.
ISC.0088.9331E	MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; 'Content-Type' header of the Root MIME Part does not match with the 'type' parameter of the MIME message
Explanation	The value of the “Content-Type” header of the Root MIME Part is not equal to the value of the “type” parameter of the “Content-Type” header of the MIME message.
Action	Verify that you have passed the correct value for these field(s)/parameter(s) while serializing the MIME message.
ISC.0088.9332E	MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; value of 'type' parameter of the 'Content-Type' header of the Root MIME Part does not match with the value of the 'start-info' parameter of the MIME message
Explanation	The value of the “type” parameter of the “Content-Type” header of the Root MIME Part is not equal to the value of the “start-info” parameter of the “Content-Type” header of the MIME Message.
Action	Verify that you have passed the correct value for these field(s)/parameter(s) while serializing the MIME.
ISC.0088.9333E	MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; SOAP Message in the Root MIME part is not of version 1.2
Explanation	The version of the SOAP Message not equal to 1.2.
Action	Send the SOAP 1.2 message.

ISC.0088.9334E **MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; Root MIME Part contains invalid SOAP Message**

Explanation The SOAP Message in the Root MIME Part is invalid; either it is not well formed or it does not contain valid namespace declarations.

Action Check the structure and content of the SOAP message in the Root MIME Part.

ISC.0088.9335E **MTOM Attachments Processing Failed: Cannot de-serialize the input MIME Stream; input stream is not a valid MIME stream**

Explanation MIME Stream does not contain the valid data as per the MIME specifications.

Action Verify that the MIME stream contains a valid MIME message.

ISC.0088.9336E **Retrieving contents of the XOPObjct failed: "{0}"**

Explanation You attempted to read the contents from an XOPObjct. However, previous logic in either the same service or a previous service has already read the XOPObjct. The XOPObjct instance can only be read one time.

Action Update the service logic so that it reads an XOPObjct only one time.

ISC.0088.9351E **Could not find Web Service Descriptor with name {0}**

ISC.0088.9352E **Handler {1} not associated with Web Service Descriptor {0}**

ISC.0088.9353E **Could not find policy with name {0}**

ISC.0088.9354E **Missing required parameter : {0}**

ISC.0088.9355E **First element of the SOAP-ENV:Body must have a QName**

ISC.0088.9400E **Invalid BOOLEAN value {0} for variable {1}; must be true or false**

ISC.0088.9432E **SOAP Header data does not conform to Header Record: {0}**

ISC.0088.9433E	Access denied to Handler Service {0} in the Handler Chain
ISC.0088.9434E	Provided header data for the header named "{0}" exceeds the number of headers expected by Web Service Descriptor "{1}"
ISC.0088.9500E	Unable to determine SOAP version. Make sure that entry has a valid parent.
ISC.0088.9501E	Invalid namespace: {0}
ISC.0092.9118E	Port "{0}" is not unique within service "{1}"
Explanation	When creating a consumer Web service descriptor from a WSDL with the specified service, the service definition contains multiple ports that all have the same name.
Action	Update the WSDL so that the port name is unique within the service definition.
ISC.0092.9119E	Schema definition not found for imported namespace(s):{0}
Explanation	While creating a consumer Web service descriptor or a WSDL first provider Web service descriptor from a WSDL document, Integration Server determined that the WSDL document contained one or more <code>xsd:import</code> elements that did not specify the <code>schemaLocation</code> attribute. Consequently, the schema processor in Integration Server cannot locate the schema definition for the imported namespace and Web service descriptor creation fails. When this message appears at run time, the {0} in the message is replaced by the list of the imported namespaces for which a <code>schemaLocation</code> attribute is not specified.
Action	Correct the WSDL document by adding a valid <code>schemaLocation</code> attribute for each <code>xsd:import</code> element that did not specify a <code>schemaLocation</code> . The value of the <code>schemaLocation</code> attribute is a URI to the XML Schema definition for the imported namespace. Alternatively, modify the WSDL document by adding in inline schema definition for each namespace with a missing <code>schemaLocation</code> to the <code>wsdl:types</code> element in the WSDL document. Then attempt to create the Web service descriptor from the WSDL document.
ISC.0107.9001E	Cannot create element "{0}"; a document type or schema with this name already exists on the Integration Server.
Explanation	While trying to pull a document from the Broker, Integration Server determined that a record being referenced already existed on the Integration Server. As a result, synchronization could not continue.
Action	When synchronizing document types, clear the "Overwrite existing elements when importing referenced elements" check box.

- ISC.0107.9002 Cannot create field "{0}" in Broker document type for "{1}"; this field name is not valid on the Broker. The Broker will transport the field contents, which will be visible to Integration Server clients only.

- ISC.0107.9003 Cannot retrieve "{0}"; document type with this name does not exist on the Integration Server.

- ISC.0107.9004 Cannot make "{0}" unpublishable; it is not a publishable document type.

- ISC.0107.9005 Cannot make "{0}" publishable; it is already a publishable document type.

- ISC.0107.9006 Cannot create field "{0}" in Broker document type for "{1}"; recursive types cannot be represented on the Broker. The Broker will transport the field contents, which will be visible to Integration Server clients only.

- ISC.0107.9007 Cannot make "{0}" publishable; it contains the field name '_env'.

- ISC.0107.9008 Cannot make document type "{0}" publishable; this name is not valid.

- ISC.0107.9009 Cannot make "{0}" publishable; the referenced document type "{1}" does not exist.

- ISC.0107.9010 Cannot create field "{0}" in Broker document type for "{1}"; field with duplicate names are not permitted on the Broker.

- ISC.0107.9011 SimpleType with the name "{0}" does not exist on the Integration Server.

- ISC.0107.9012 Could not lock node "{0}"{1}

- ISC.0107.9013 Could not create node "{0}". User "{1}" does not have write permission on folder "{2}".

ISC.0124.9017E	Document to XSD error: Field {0} cannot be represented in XML Schema. The field contains an XML Namespace property but the field name does not contain a prefix
Explanation	A service for which a service first provider web service descriptor is being created uses an IS document type that contains a field with an assigned XML namespace property value. However, the field name does not include a prefix to associate with the XML namespace. That is, the field name is not in the format prefix:localName.
Action	Either add a prefix to the field name using the format prefix:localName or remove the value assigned to the XML namespace property. Important! Some protocols require the use of an XML namespace. Review the documentation for service signature requirements for service first provider web service descriptors.
ISC.81.9187W	JAX-RPC handlers are not supported when the Pre-8.2 compatibility mode is false. The following handlers will be ignored at run time: {0}
Explanation	Integration Server only supports JAX-RPC handlers for use with Web service descriptors that run in pre-8.2 compatibility mode (i.e., when the Pre-8.2 compatibility mode property is true).
Action	To continue using the JAX-RPC handler, change the Web service descriptor to run in pre-8.2 compatibility mode. If you do not want to run the Web service descriptor in pre-8.2 compatibility mode, replace the JAX-RPC handler with a service handler that has the same behavior.
ISC.81.9188W	Port type names of all the binders will be changed to "{0}". As a result, all bindings in the generated WSDL will use the same port type.
Explanation	When a Web service descriptor's Pre-8.2 compatibility mode property is set to false, Integration Server generates WSDL with all the bindings referring to same port type. As a result, when you change the Pre-8.2 compatibility mode property from true to false, Integration Server changes the port type names of all the binders to (wsdName)_PortType, where (wsdName) is the Web service descriptor name.
Action	Depending on your web service client framework, you may need to regenerate or recreate existing Web service clients from the WSDL.
ISC.81.9189E	All binders must have the same binding style and use when Pre-8.2 compatibility mode is false.
Explanation	When a Web service descriptor's Pre-8.2 compatibility mode property is set to false, Integration Server does not allow the Web service descriptor to have binders that have different binding styles and use. Integration Server issues this message when either you are attempting to create a new binder for a Web service descriptor and the new binder has a different binding style or use from the existing binders, or when you are trying to consume a WSDL to create a Web service descriptor and WSDL has multiple bindings with different style and use.
Action	If you are trying to create a new binder for a Web service descriptor, use the same binding style and use as the existing binders. If you are trying to consume a WSDL that contains multiple bindings with different style and use, split the WSDL into multiple WSDLs that each use the same style and use.

ISC.81.9190E	Multiple port types are not supported when Pre-8.2 compatibility mode is false.
Explanation	The WSDL document used to create the Web service descriptor consists of multiple port types. When creating a Web service descriptor in Designer, Integration Server does not support multiple port types.
Action	Split the WSDL document that consists of multiple port types into multiple WSDL documents that each use a single port type. Then, create Web service descriptors from each WSDL document.
ISC.81.9196W	MTOM streaming is not supported when the Pre-8.2 compatibility mode is true.
Explanation	When the Pre-8.2 compatibility mode property of a Web service descriptor is set to true, Integration Server does not support MTOM streaming of attachments. Integration Server issues this message when you change the Pre-8.2 compatibility mode property from false to true and when at least one of the operation's input or output signature contains a field of type Object and the java wrapper type is set to com.wm.util.XOPObject.
Action	To continue using MTOM streaming, set the Pre-8.2 compatibility mode property of the Web service descriptor to false. If you want to run the Web service descriptor in pre-8.2 compatibility mode, ensure that the attachment size is not very large to avoid out of memory errors.
ISC.88.9171E	Operation not found for soapAction = {0}
Explanation	Integration Server could not find the operation for the SOAP action specified in the incoming SOAP request.
Action	Ensure that the correct SOAP action is specified in the incoming SOAP request. For a service first provider, if needed, you can edit the SOAP action to operation map present in the binder properties.
ISC.88.9172E	Web service cannot be found for endpoint reference (EPR) = {0}
Explanation	Integration Server could not find the Web service with the specified endpoint reference.
Action	Ensure that the Web service descriptor with the endpoint reference exists in the Integration Server.
ISC.88.9173E	Operation can not be found for endpoint reference (EPR) = {0} and soapAction = {1}
Explanation	Integration server could not find the operation in the Web service identified with the specified endpoint reference and SOAP action.
Action	Ensure that the operation with the specified SOAP action is present in the Web service descriptor identified by the endpoint reference.

ISC.88.9357E	You cannot use this service against the specified Web service descriptor because its Pre-8.2 compatibility mode property is set to false.
Explanation	Either pub.soap.utils.resetWSDEffectivePolicy or pub.soap.utils.setWSDEffectivePolicy services were specified with a Web service descriptor with Pre-8.2 compatibility mode property set to false. These services can only be used with Web service descriptors that are running in pre-8.2 compatibility mode (i.e., the Pre-8.2 compatibility mode property is set to true)
Action	Change the Web service descriptor's Pre-8.2 compatibility mode property to true.
ISE.0093.9902E	Error occurred while invoking a service : {0}
Explanation	The Integration Server encountered an internal error while invoking a service. More information about the error is provided in the error message.
Action	Contact Software AG Global Support.
ISE.0093.9903E	Not implemented
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISE.0093.9904E	Unknown session: {0}
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISE.0093.9908E	Parameter {0} specified for method is invalid
Explanation	The parameter that you specified is not valid.
Action	Specify a valid parameter.
ISE.0093.9924E	FAILED
Explanation	Integration Server is unable to retrieve the status of Repository Server V2.
Action	Ensure that the port and host information that you specified to retrieve the status of Repository Server V2 is correct.
ISE.0093.9934E	Service {0} doesn't exist or was removed.
Explanation	The service that you are trying to execute does not exist in Integration Server.
Action	Ensure that the service exists in Integration Server.

ISE.0093.9935E	Package {0} doesn't exist or was removed.
Explanation	The package that you are trying to access does not exist or is deleted.
Action	Ensure that the package you want to access exists in the IntegrationServer_directory\packages directory.
ISE.0093.9936E	Port {0} doesn't exist or was removed.
Explanation	The e-mail port that you are trying to access is not configured or enabled.
Action	Ensure that the e-mail port you want to access is configured and enabled.
ISE.0093.9952E	Access was denied to resource {0}
Explanation	The Integration Server encountered an internal error due to resource access.
Action	Contact Software AG Global Support.
ISE.0093.9953E	A Java exception occurred {0}
Explanation	Integration Server encountered an unexpected error.
Action	Contact Software AG Global Support.
ISE.0093.9954E	Resource {0} doesn't exist or was removed.
Explanation	The Integration Server encountered an internal error due to resource access.
Action	Contact Software AG Global Support.
ISO.0086.9326E	Unable to find the OSGi service reference for EventEmitter. Make sure the NERV bundles that provides the OSGI service exist in the installation profile for IS.
Explanation	When the pub.event.nerv:send service was invoked, the underlying OSGi services used for sending events were not available.
Action	Check the logs located in the Software_AG_directory/profiles/IS/logs directory and make sure that no errors were encountered during the initialization of Integration Server.
ISO.0086.9327E	Unable to find the OSGi service EventEmitter. Make sure the NERV bundles that provides the OSGI service exist in the installation profile for IS.
Explanation	When the pub.event.nerv:send service was invoked, the underlying OSGi services used for sending events were not available.
Action	Check the logs located in the Software_AG_directory/profiles/IS/logs directory and make sure that no errors were encountered during the initialization of Integration Server.

ISO.0086.9328E	Unable to find the OSGi service reference for MessageCreator. Make sure the NERV bundles that provides the OSGI service exist in the installation profile for IS.
Explanation	When the pub.event.nerv:send service was invoked, the underlying OSGi services used for sending events were not available.
Action	Check the logs located in the Software_AG_directory/profiles/IS/logs directory and make sure that no errors were encountered during the initialization of Integration Server.
ISO.0086.9329E	Unable to find the OSGi service MessageCreator. Make sure the NERV bundles that provides the OSGI service exist in the installation profile for IS.
Explanation	When the pub.event.nerv:send service was invoked, the underlying OSGi services used for sending events were not available.
Action	Check the logs located in the Software_AG_directory/profiles/IS/logs directory and make sure that no errors were encountered during the initialization of Integration Server.
ISP.0000.9101E	Unable to register NTLM Challenge Response Authentication handler
Explanation	A handler was registered and then re-registered without first being unregistered.
Action	Register a handler only once. If you want to re-register a handler, first unregister it.
ISP.0046.0001E	Could not initialize {0} Listener. Invalid port specified: {1}
Explanation	While attempting to initialize a port, Integration Server detected that the port was improperly configured. Specifically, an invalid port number was specified for the port in the server.cnf, ports.cnf, or listeners.cnf file.
Action	Edit the appropriate configuration file and specify a port number from 1 through 65534 that is not already in use.
ISP.0046.0006E	Cannot initialize {0} Listener on port {1}. No socket available.
Explanation	While trying to initialize an HTTP listener, Integration Server determined that the socket associated with the requested port is already in use by another application. As a result, the requested port is unavailable.
Action	Specify a port that is not already in use, or disable the application that is using the requested port.

- ISP.0046.0007W** **{0} Access denied. Connection disallowed {1}**
- ISP.0046.0019S** **Unable to establish connection to Enterprise Gateway Server {0};{1}. Exception: {2}.**
Explanation The Internal Server could not establish a connection to Enterprise Gateway Server for the reason indicated.
Action Ensure that the Enterprise Gateway registration port is enabled.
- ISP.0046.0020S** **Unable to establish connection to Enterprise Gateway Server {0};{1}. Internal Server was not authenticated on the Enterprise Gateway.**
Explanation Internal Server authentication failed on the Enterprise Gateway.
Action Ensure that the registration credentials specified during the creation of the Internal Server port are correct.
- ISP.0047.0001E** **47.1 obsolete**
Explanation While attempting to initialize a port, Integration Server detected that the port was improperly configured. Specifically, an invalid port number was specified for the port in the server.cnf, ports.cnf, or listeners.cnf file.
Action Edit the appropriate configuration file and specify a port number from 1 through 65534 that is not already in use.
- ISP.0047.0002** **Resuming HTTPS Listener on port {0}**
- ISP.0047.0003** **Starting HTTPS Listener on port {0}**
- ISP.0047.0005** **Stopping HTTPS Listener on port {0}**
- ISP.0047.0008** **Could not start HTTPS Listener on port {0}. No SSL support available.**
- ISP.0047.0009** **Error in SSL setup: {0}**
- ISP.0047.0010** **Certificate Authority was recognized**

ISP.0047.0011	Certificate Authority was not recognized {0}
ISP.0047.0012	Client does not have a digital certificate
ISP.0047.0013	Access denied to host {0}
ISP.0047.0014	Error in SSL Setup: {0}
ISP.0047.0015	Error in SSL setup: Not all certificate fingerprints were loaded
ISP.0047.0016	The required client certificate was not provided by {0}
ISP.0047.0017	Could not start HTTPS listener on port {0}
ISP.0047.0018E	Aborting connection from {0}: {1}
Explanation	Integration Server encountered a problem while trying to establish a secure connection with the client at the indicated address.
Action	Make sure the client properly supports SSL connections.
ISP.0047.0019E	SSL listener restricted to 128 bit or better encryption:
Explanation	Integration Server configuration property <code>watt.net.ssl.server.strongcipheronly</code> is set to "true", but the list of ciphers includes weak ciphers. Integration Server displays these weak ciphers in subsequent messages.
Action	Either use only strong ciphers, or set <code>watt.net.ssl.server.strongcipheronly</code> to "false".
ISP.0047.0020E	cipher {0} = {1} ({2} bit)
Explanation	Integration Server configuration property <code>watt.net.ssl.server.strongcipheronly</code> is set to "true", but the list of ciphers includes the weak ciphers displayed by this message.
Action	Either use only strong ciphers, or set <code>watt.net.ssl.server.strongcipheronly</code> to "false".

ISP.0047.0021E	Aborting connection request on {0} port {1}, a certificate map does not exist for {2}
Explanation	A client presented a certificate to Integration Server, but the certificate has not been mapped to a user on Integration Server. For a certificate to be mapped to a user, the certificate must have been previously stored on Integration Server and associated with that user.
Action	Use the Server Administrator interface to import the certificate to Integration Server and map it to the appropriate user.
ISP.0047.0022	Access denied to host : Hostname verification failed
ISP.0047.0023	Aborting connection, Server Certificate purpose verification failed
ISP.0047.9998U	Exception --> {0}
Explanation	Integration Server encountered an error. This message contains the exception produced by the server.
Action	Examine the error message to determine the problem.
ISP.0057.0001I	Delete operation completed
ISP.0061.0001	Access denied to remote server {0} for user {1}
ISP.0061.0002	Expired remote connection to {0} for user {1}
ISP.0061.0003	Established new remote connection to {0} for user {1}
ISP.0061.0004	Established new remote connection to {0}
ISP.0061.0005	Error expiring remote connection: {0}
ISP.0061.0006	Error expiring remote connection for user {0}: {1}

ISP.0061.0007	Expired remote connection to {0}
ISP.0061.0008	Could not create default Remote Server Alias: {0}
ISP.0061.0009	The default Remote Server Alias was created.
ISP.0068.0001	Successfully logged in as user {0} on host {1}
ISP.0068.0002	Login attempt as user {0} on host {1} failed
ISP.0068.0004	Processed {0} new message(s)
ISP.0068.0005	Error processing email message. {0}.
ISP.0068.0006	EMAIL Access denied. Connection disallowed from host {0}
ISP.0068.0007	EMAIL Access denied. Invalid host in senders address: {0}
ISP.0068.0008	EMAIL Access denied. Could not figure out senders email address.
ISP.0068.0009	EMAIL Access denied. User {0} not allowed to run service {1}
ISP.0068.0010	Could not decode body part of email message
ISP.0068.0011	Could not decode message body into input parameters
ISP.0068.0012	Listener key not provided. Not running email listener

- ISP.0068.0013 **Error processing service: {0}**

- ISP.0068.0014 **Could not get message content: {0}**

- ISP.0068.0015 **Could not get body part of message: {0}**

- ISP.0068.0016 **Error parsing message: {0}**

- ISP.0068.0017 **Could not get message UID: {0}**

- ISP.0068.0018 **Could not start listener threads: {0}**

- ISP.0068.0020 **Could not get message with uid {0}**

- ISP.0068.0021 **Could not process message with uid {0}**

- ISP.0068.0022 **Could not send reply message to {0}. Check email address and smtp settings.**

- ISP.0068.0023 **Received reply message. Not processing**

- ISP.0068.0024 **The connection to the IMAP server {0} for user {1} was temporarily lost. Some messages may not have been processed.**

- ISP.0068.0025 **No content handler for content type {0}. Service {1} called without content handler.**

- ISP.0068.0026 **Content type: {0} Subject: {1}**

- ISP.0068.0027 **{0} lost connection to {1} server {2}**

ISP.0068.0028	{0} reconnected to {1} server {2}
ISP.0068.9001E	Skipping processing reply email message
Explanation	The subject line of the e-mail received on the e-mail port starts with "Re:". Hence, it is treated as a reply message and its processing is skipped.
Action	Investigate why the subject line of the e-mail starts with "Re:". Usually, this is an indicator of a reply message.
ISP.0068.9002E	Skipping processing returned email message
Explanation	The subject line of the e-mail received on the e-mail port starts with "Returned". Hence, it is treated as a message that is returned by the recipient and its processing is skipped.
Action	Avoid the error and process the returned messages by setting the extended property "watt.server.email.processReturnedEmails" to true.
ISP.0068.9003E	Invalid service: {0}
Explanation	<p>Integration Server received a message on the e-mail port listener, but the service specified to perform the message processing is invalid. The service that Integration Server selects to execute message processing depends on how the server is configured. Integration Server searches for the value in the locations listed below in order of precedence:</p> <ul style="list-style-type: none">- The Global Service field on the Email Client Configuration screen on the Server Administrator.- The e-mail message from the e-mail client.- The Default Service field on the Email Client Configuration screen on the Server Administrator. <p>The problem is often that the service name is specified in the wrong case (service names are case sensitive). Other causes could be that no service was specified at all or the service is not in its specified location.</p>
Action	Make sure the service name is specified correctly and exists in the location specified.
ISP.0068.9004E	No such service: {0}
Explanation	The Integration Server FTP listener encountered an internal error.
Action	Contact Software AG Global Support.

ISP.0068.9005E	Unknown content type: {0}
Explanation	The Integration Server does not support the MIME type specified.
Action	Only use the MIME types supported by the Integration Server.
ISP.0068.9006E	Server Error: {0}
Explanation	An unexpected error occurred when invoking the service.
Action	If the exception details provided as part of the message does not give any hint, contact Software AG Global Support.
ISP.0068.9101E	Invalid header {0}
Explanation	The header specified is invalid.
Action	Ensure that a valid header is provided. Keep the following points in mind when specifying a header: <ol style="list-style-type: none">1. Header name should not contain spaces.2. Header value should not be empty.3. Header name and value should not be the same.
ISP.0068.9102E	Invalid TO field: {0}
Explanation	Either the recipient e-mail address is not provided in the "to" field or the address provided is invalid.
Action	Enter a valid e-mail address in the "to" field. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.
ISP.0068.9103E	Invalid CC field: {0}
Explanation	The e-mail address entered in the "cc" field is invalid.
Action	Enter a valid e-mail address in the "cc" field. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.
ISP.0068.9104E	Invalid BCC field: {0}
Explanation	The e-mail address entered in the "bcc" field is invalid.
Action	Enter a valid e-mail address in the "bcc" field. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.

ISP.0068.9106E	No filename nor content included in the attachment!
Explanation	Content or filename is not provided in the attachments field.
Action	Provide either the content or the filename in the attachments field. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.
ISP.0068.9108E	charset {0} is not valid
Explanation	Character set encoding specified for the body or attachment is invalid.
Action	Ensure that the Character set encoding specified is valid. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.
ISP.0068.9110E	Invalid MAILHOST field: {0}
Explanation	No value is provided for the mailhost parameter of the pub.client:smtp service.
Action	Provide a valid value for the mailhost parameter of the pub.client:smtp service. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.
ISP.0068.9111E	Invalid Message Recipient: {0}
Explanation	Either the recipient e-mail address is not provided in the "to" field or the address provided is invalid.
Action	Enter a valid e-mail address in the "to" field. Refer to "pub.client:smtp" service in webMethods Integration Server documentation for further details.
ISP.0071.0001	Could not initialize FTP Listener. Invalid port specified: {0}
ISP.0071.0002	Suspending FTP(S) Listener on port {0}
ISP.0071.0003	Can not build data channel, the exception is {0}, the message is {1}
ISP.0071.0004	The port range specified for passive data connections to FTP(S) listeners is invalid: please specify both "watt.net.ftpPassivePort.min" and "watt.net.ftpPassivePort.max" values

ISP.0071.0005 **The port range specified for passive data connections to FTP(S) listeners is invalid: "watt.net.ftpPassivePort.min" value is not a number**

ISP.0071.0006 **The port range specified for passive data connections to FTP(S) listeners is invalid: "watt.net.ftpPassivePort.max" value is not a number**

ISP.0071.0007 **The port range specified for passive data connections to FTP(S) listeners is invalid: "watt.net.ftpPassivePort.min" and "watt.net.ftpPassivePort.max" values are not within 1-65534 range**

ISP.0071.0008 **The port range specified for passive data connections to FTP(S) listeners is invalid: "watt.net.ftpPassivePort.min" value is greater than "watt.net.ftpPassivePort.max" value**

ISP.0071.0009 **All ports within the port range specified for passive data connections to FTP(S) listeners are in use**

ISP.0071.9001E **Cannot build data connection: use PORT or PASV first**

Explanation The Integration Server failed to connect to a port on the FTP client because the FTP client did not provide valid port information.

Action Check the Integration Server configuration and restart the server. If the problem persists, contact Software AG Global Support.

ISP.0071.9002E **{0}: cannot create**

Explanation An FTP client application connected to an FTP port on the Integration Server and tried to create a remote directory on the FTP server, but the "mkdir" command failed.

Action Make sure the directory name was specified correctly. Also, examine the remote file system and make sure that you have permission to create the directory there.

ISP.0071.9003E **{0}: cannot delete**

Explanation An FTP client application connected to an FTP port on the Integration Server and tried to delete a file on the FTP server, but the "delete" command failed.

Action Make sure the file name was specified correctly and that the file exists on the remote server. Also, examine the remote file system and make sure that you have permission to delete the file from the remote file system.

ISP.0071.9004E	Cannot rename File to {0}
Explanation	An FTP client application connected to an FTP port on the Integration Server and tried to rename a file on the FTP server, but the "rename" command failed.
Action	Make sure the old and new file names were specified correctly. Also, examine the remote file system and make sure that you have write permission to both the old and new file names.
ISP.0071.9005U	Unable to make dir {0}
Explanation	An FTP client application connected to an FTP port on the Integration Server and tried to create a remote directory on the FTP server, but the "mkdir" command failed.
Action	Make sure the directory name is specified correctly. Also, examine the remote file system and make sure that you have the appropriate permissions to create the directory there.
ISP.0071.9006U	Unable to delete {0}
Explanation	An FTP client application connected to an FTP port on the Integration Server and tried to delete a file on the FTP server, but the "delete" command failed.
Action	Make sure the file name is specified correctly and that the file exists. Also, examine the remote file system and make sure that you have permission to delete the file.
ISP.0071.9007U	Unable to rename to {0}
Explanation	An FTP client application connected to an FTP port on the Integration Server and tried to rename a file on the FTP server, but the "rename" command failed.
Action	Make sure the old and new file names are specified correctly. Also, examine the remote file system and make sure that you have write permission to both the old and new file names.
ISP.0071.9008E	Cannot write
Explanation	Integration Server failed to put the file in the folder directory. The file must be in the service directory for processing.
Action	Put the file in the service directory.
ISP.0071.9009E	Invalid transaction name. Not in the form 'tid[;mime.type][;encoding]'.
Explanation	The MIME type specified in the FTP request is incorrect. It should be in the form of 'tid[;mime.type][;encoding]'.
Action	Make sure to provide the name in the correct format.

ISP.0071.9010U	Unable to determine mime type
Explanation	Integration Server does not support the MIME type specified.
Action	Only use the MIME types supported by Integration Server. Refer to the webMethods Integration Server documentation for more information.
ISP.0071.9011E	Cannot read
Explanation	Ensure that the specified file exists in the FTP server.
Action	The Integration Server failed to read the specified file from the FTP server.
ISP.0071.9012U	No such service: {0}
Explanation	The Integration Server FTP listener encountered an internal error.
Action	Contact Software AG Global Support.
ISP.0071.9013U	Unknown content type: {0}
Explanation	The Integration Server does not support the MIME type specified.
Action	Only use the MIME types supported by the Integration Server. Refer to the webMethods Integration Server documentation for more information.
ISP.0071.9014U	Server Error: {0}
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISP.0071.9015E	Cannot publish STOR complete event
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISP.0085.9001E	Issuer DN must be provided
Explanation	The certificate is incomplete. It must include an Issuer DN.
Action	Supply a certificate that includes an Issuer DN.
ISP.0085.9002E	Serial number must be provided
Explanation	The certificate is incomplete. It must contain a serial number.
Action	Supply a certificate that includes a serial number.

ISP.0085.9004E	data provided for certificate not in expected format
Explanation	Only X509Certificates may be used to identify Integration Server clients.
Action	Supply a valid X509Certificate.
ISP.0085.9005E	No map entry exists for the specified information
Explanation	Internal error.
Action	Contact Software AG Global Support.
ISP.0085.9006E	Certificate's file name is required
Explanation	Certificate Path is empty.
Action	Supply the fully qualified file name for a certificate file.
ISP.0085.9007E	Specified certificate file does not exist
Explanation	The Certificate Path field refers to a non-existent file.
Action	Supply the fully qualified file name of a certificate file.
ISP.0085.9008E	Specified certificate file is empty
Explanation	The Certificate Path field refers to an empty file.
Action	Supply the fully qualified file name of a certificate file.
ISP.0085.9009E	Attempted to update a non-existent entry
Explanation	Internal error.
Action	Contact Software AG Global Support.
ISP.0085.9010E	{0} is not a valid user
Explanation	The supplied user name does not identify a user on this Integration Server.
Action	Supply a valid user.
ISP.0085.9011E	Missing input for the parameter 'oldName'
Explanation	Internal error.
Action	Contact Software AG Global Support.

ISP.0085.9012E **No service/Document Type exist for: {0}**
Explanation Internal error.
Action Contact Software AG Global Support.

ISP.0085.9013E **Missing input for the parameter 'newName'**
Explanation Internal error.
Action Contact Software AG Global Support.

ISP.0085.9014E **Not a Document Type: {0}**
Explanation Internal error.
Action Contact Software AG Global Support.

ISP.0085.9015E **Not a flow service: {0}**
Explanation Internal error.
Action Contact Software AG Global Support.

ISP.0085.9016E **Missing input parameter: path**
Explanation Internal error.
Action Contact Software AG Global Support.

ISP.0085.9017E **No input for the parameter {0}**
Explanation This is an internal error.
Action Contact Software AG Global Support.

ISP.0085.9018E **Specified node {0} not found**
Explanation Internal error.
Action Contact Software AG Global Support.

ISP.0085.9019 **Missing required parameter: 'fileName'**

ISP.0085.9020	Missing required parameter: 'pipeline'
ISP.0085.9030	No such folder: {0}
ISP.0085.9032	Invalid folder type: {0}
ISP.0085.9033	Provided folder name is null
ISP.0085.9034	Provided source is null
ISP.0085.9035	Provided package name is null
ISP.0085.9038	No such folder: {0}
ISP.0085.9041U	No such service: {0}
Explanation	Integration Server FTP listener encountered an internal error.
Action	Contact Software AG Global Support.
ISP.0085.9043	Must specify either Specification or Signature
ISP.0085.9047	Failed to register {0}
ISP.0085.9050	no such service {0}
ISP.0085.9051	service {0} is not a Java IM
ISP.0085.9052	node is missing a name

ISP.0085.9053E	invalid package
Explanation	An application tried to delete a service, but the package specified does not exist on the Integration Server.
Action	Examine the service input and verify that a valid package name is specified.
ISP.0085.9054	Node name was not provided
ISP.0085.9055	Node {0} does not exist
ISP.0085.9057	Target name was not provided
ISP.0085.9059	Target package does not exist. Create it first
ISP.0085.9060	IOException occurred file={0}: {1}
ISP.0085.9061	Similarly-named node already in use
ISP.0085.9062E	Package name was not provided
Explanation	An application tried to export a package, but the package name was not provided.
Action	Examine the service input make sure it provides a valid package name.
ISP.0085.9063	{0} package does not exist
ISP.0085.9064	Node directory does not exist
ISP.0085.9065	IOException occurred creating zip for {0} node
ISP.0085.9066	{0} package not found

ISP.0085.9067	{0} package directory not found
ISP.0085.9068	IOException occurred creating zip for {0} package
ISP.0085.9074	no such class {0}
ISP.0085.9075	Package {0} is not enabled
ISP.0085.9076	class not in package
ISP.0085.9077	node is not in a package
ISP.0085.9078E	node belongs to invalid package
Explanation	An application tried to create a service, but the package name specified to contain the service was missing or invalid.
Action	Examine the service input and make sure a valid package name is provided.
ISP.0085.9079E	not a valid folder name
Explanation	An application tried to create a new service, but the folder name was missing or invalid.
Action	Examine the service input and verify that a valid folder name is provided.
ISP.0085.9080	node name already in use
ISP.0085.9081	folder node "{0}" in path "{1}" doesn't exist
ISP.0085.9082	folder node "{0}" exists in package
ISP.0085.9083	unsupported node type: {0}

- ISP.0085.9084** **Unable to lock: {0}. It has been locked by user {1}.**
- ISP.0085.9085** **Unable to modify; node {0} is locked by another user.**
- ISP.0085.9086** **Unable to perform the required operation. The destination folder has locked services which share a common Java source file.**
- ISP.0085.9087** **Required parameter 'package' is missing**
- ISP.0085.9088E** **Invalid package version {0}, the accepted format is #.#.#.###**
Explanation The supplied package version is an invalid version number. The correct format is "x.y" or "x.y.z" (x, y, z all must be digits from 0-9, e.g. 2.0, 4.0.1 etc.).
Action Examine the service input and make sure a valid package version is provided.
- ISP.0085.9089E** **Not allowed to add unknown package(s) {0} to dependency list**
Explanation The package that was added to another package's dependency list does not exist on Integration Server.
Action Specify the package name again, this time specifying a package that exists on Integration Server and is enabled.
- ISP.0085.9093** **Port must be numeric**
- ISP.0085.9094E** **Invalid Folder/Service Name**
Explanation The service, folder, or provider Web service descriptor that was added to a port's access list does not exist on Integration Server.
Action Enter the name of the service, folder, or Web service descriptor again, making sure to specify one that exists on Integration Server.
- ISP.0085.9095** **Unable to add service to this port**
- ISP.0085.9100E** **No password specified**
Explanation The alias created for a remote server omitted the remote server's password.
Action Enter a valid password in the password field.

ISP.0085.9101E	Missing one or more required parameters: \$alias, \$service
Explanation	The pub.remote:invoke service failed to execute because one or both of the required "\$alias" or "\$service" parameters were not supplied.
Action	Examine the service input and ensure that both the parameters are specified.
ISP.0085.9102E	No such remote server: {0}
Explanation	The pub.remote:invoke service failed to execute because an invalid server alias was provided.
Action	From the Settings>Remote Servers page of the Server Administrator examine the Remote Servers List and make sure an alias exists for the remote server. If not, create one before invoking the pub.remote:invoke service again.
ISP.0085.9103E	User session required to invoke a protected remote server
Explanation	Integration Server encountered a serious internal error because the user session object that invokes the service on the remote server is null.
Action	Contact Software AG Global Support.
ISP.0085.9104E	Access denied to invoke on remote server {0}
Explanation	The pub.remote:invoke service failed to invoke the service on the remote server because the current user does not have the proper ACL.
Action	Using the Integration Server Administrator, examine the remote server alias properties as well as the service's Execute ACL setting on the remote server. Make sure that the current user has the proper ACL to invoke the service.
ISP.0085.9105E	User session required to invoke a remote server with SESSION scope
Explanation	Integration Server encountered a serious internal error because the user session object that invokes the service on the remote server is null.
Action	Contact Software AG Global Support.
ISP.0085.9106	Missing required parameter: \$jobID
ISP.0085.9108	No such job: {0}

ISP.0085.9110	No such service is currently loaded {0}
ISP.0085.9113E	Invalid Date format.Date must be in YYYY/MM/DD format.
Explanation	When attempting to schedule a one-time task, an invalid date or time format was specified.
Action	Enter the date and/or time again, this time using the correct format.
ISP.0085.9114	You specified a date/time in the past
ISP.0085.9115	Invalid Time format.Time must be in HH:MM:SS format
ISP.0085.9116E	Interval must be a positive integer {0}
Explanation	A repeating task could not be scheduled because the specified interval is not valid.
Action	Specify the interval again, this time specifying a positive integer.
ISP.0085.9117E	Invalid task type: {0}
Explanation	The WmRoot service wm.server.schedule:createUserTask failed to execute because an invalid task type was supplied. Valid task types are: "once", "repeat", and "complex".
Action	Examine the service input and ensure that the "type" parameter specifies a valid task type.
ISP.0085.9118	Unknown service type: {0}
ISP.0085.9119	{0} is missing or package is disabled
ISP.0085.9120	Templates directory for package {0} could not be created
ISP.0085.9121	Template file exists but is not writable
ISP.0085.9123U	nobody to send message to
Explanation	Integration Server failed to invoke a service on the remote server using the e-mail port because the "to" parameter was not supplied.
Action	Examine the logic to make sure that it passes the correct input to the "to" parameter when invoking services remotely using the e-mail listener.

ISP.0085.9124U	no attachment
Explanation	Integration Server failed to invoke a service on the remote server using the e-mail port because the "attachments" parameter was not supplied.
Action	Examine the logic to make sure that it passes the correct input to the "attachments" parameter when invoking services remotely using the e-mail listener.
ISP.0085.9125U	attachments must be of type Values[]
Explanation	Integration Server failed to invoke a service on the remote server using the e-mail port because the input for the "attachments" parameter was not of Values[] type.
Action	Examine the logic to make sure that it passes the correct Values[] input to the "attachments" parameter when invoking services remotely using the e-mail listener.
ISP.0085.9126E	Invalid attachment file {0}
Explanation	Integration Server failed to invoke a service on the remote server using the e-mail port because the file attachment specified in the "filename" parameter does not exist in the system.
Action	Examine the logic to make sure that it passes a valid file to the "filename" parameter and make sure that it exists in the file system.
ISP.0085.9127	No filename nor content included in the attachment!
ISP.0085.9129	An error was encountered removing {0}
ISP.0085.9131E	Not allowed to add empty package version, the accepted format is *.*
Explanation	The package dependency list does not specify a version for the package.
Action	Enter a valid package version in the format "x.y" or "x.y.z" (x, y, z all must be digits from 0-9, e.g. 2.0, 4.0.1 etc.).
ISP.0085.9132	Unable to perform operation. {0} has entities locked by another user. Please unlock these entities before performing this operation
ISP.0085.9133	A required parameter {0} was not supplied

- ISP.0085.9135** **The Universal Name {0} is already defined for {1} in the registry**
- ISP.0085.9136** **The Universal Name {0} is already defined as a Service or Document**
- ISP.0085.9139E** **Cannot {0} changes because the file(s) representing {1} may have been changed to 'Read-Only'. To {0} changes, change the following file(s) from 'Read-Only' to 'Read/Write' either manually or through a source control system: {2}**
- Explanation** Integration Server could not compile the Java or C service, possibly because the files have changed to Read-Only.
- Action** Examine the file permissions and change the file permission from Read-Only to Read/Write, either manually or through a source control system.
- ISP.0085.9140** **Unable to lock: {0}. It might be locked by another user.**
- ISP.0085.9141E** **The Universal Name {0} contains an invalid character**
- Explanation** This is an internal error.
- Action** Contact Software AG Global Support.
- ISP.0085.9145E** **Invalid input**
- Explanation** A WmRoot service failed to execute because the service input is not of the type required by the service.
- Action** Examine the error stack trace to determine the exception that was thrown and the service that threw it. For example, the service may require an IData object, but the supplied input was not an instance of IData.
- ISP.0085.9146** **Cannot schedule service. Input has unsupported datatypes**
- ISP.0085.9147E** **Missing required parameter: 'header'**
- Explanation** Integration Server encountered an internal error.
- Action** Contact wSoftware AG Global Support.
- ISP.0085.9148E** **'header' must be of type IData**
- Explanation** Integration Server encountered an internal error.
- Action** Contact Software AG Global Support.

ISP.0085.9149	Cannot perform operation without Read ACL privileges on {0}
ISP.0085.9150	Cannot perform operation without List ACL on package {0}
ISP.0085.9151	Cannot set Execute ACL {1} on {0}. You do not have permission to access the {1} ACL.
ISP.0085.9152	Cannot set List ACL {1} on {0}. You do not have permission to access the {1} ACL.
ISP.0085.9153	Cannot set Read ACL {1} on {0}. You do not have permission to access the {1} ACL.
ISP.0085.9154	Cannot set Write ACL {1} on {0}. You do not have permission to access the {1} ACL.
ISP.0085.9155	Cannot set List ACL {1} on package {0}. You do not have permission to access the {1} ACL.
ISP.0085.9156E	Cannot perform operation without List ACL privileges on {0}
Explanation	You do not have List access to the element that you tried to lock for editing or the service you attempted to view.
Action	Contact the Administrator of the Integration Server to request List ACL permission for the service or element.
ISP.0085.9157	Cannot perform operation without Write ACL privileges on {0}
ISP.0085.9158	Required parameter "{0}" is missing in invoke of {1}
ISP.0085.9159	Invalid input. "{0}" is a required parameter of type IData
ISP.0085.9160	Invalid input. "{0}" is a required parameter of type String

- ISP.0085.9161** **Invalid input. "{0}" must be of type String**
- ISP.0085.9162** **Invalid input. "{0}" must be a positive integer**
- ISP.0085.9163** **Invalid input. "{0}" must be true or false**
- ISP.0085.9164** **Folder {0} not found**
- ISP.0085.9165** **Unable perform the operation because Broker reports: {0}**
- ISP.0085.9166E** **Not a valid condition type**
Explanation An invalid condition type was provided. The condition type must be "simple" or "join."
Action Examine the service input and ensure that the condition type provided is "simple" or "join."
- ISP.0085.9167E** **Not a valid trigger name. Trigger name must be of type String**
Explanation An invalid trigger name was provided. The trigger name must be of type String.
Action Examine the service input and ensure that the trigger name is of type String.
- ISP.0085.9168** **Specified trigger name does not exist: {0}**
- ISP.0085.9169** **Could not validate data corresponding to publishable document: {0}**
- ISP.0085.9170** **Trigger condition not satisfied by this document: {0}**
- ISP.0085.9171E** **Not a valid condition name. Condition name must be of type String**
Explanation During a trigger test, Integration Server encountered an invalid condition name. The condition name must be of type String.
Action Examine the service input and ensure that the condition name is of type String.

ISP.0085.9172E	Specified condition name does not exist: {0}
ISP.0085.9173	Trigger condition not satisfied. All documents must be submitted incase of "AND" join type
ISP.0085.9174	Package "{0}" does not exist.
ISP.0085.9175	Trigger condition "{0}" does not have a service
ISP.0085.9176	Trigger condition "{0}" does not have a document type; A trigger condition must have at least one document type
Explanation	To be considered valid, a trigger condition must identify at least one document type.
Action	Edit the trigger condition to specify a document type.
ISP.0085.9177	"{0}" does not exist or it is not a service
ISP.0085.9178	Document type "{0}" does not exist
ISP.0085.9179	"{0}" is not a publishable document type.
ISP.0085.9184	Node "{0}" is not writable.
ISP.0085.9185	Invalid filter "{0}" for document type "{1}": {2}
ISP.0085.9186	Multiple join conditions are not allowed in a single trigger.
ISP.0085.9187	Could not copy folder completely: {0}
ISP.0085.9188	Could not delete folder completely: {0}

- ISP.0085.9189** **Could not move folder completely: {0}**

- ISP.0085.9200** **Reference(s) for "{0}" could not be automatically updated, because the element(s) are currently locked.**

- ISP.0085.9201** **Internal reference(s) could not be automatically updated.**

- ISP.0085.9202** **Target node "{0}" already exists.**

- ISP.0085.9203** **Errors occurred while updating remote aliases ({0} of {1} updates failed). See server logs for more details.**

- ISP.0085.9204** **Local update failed: {0} (Note: The cluster synchronization will not run until all local errors are resolved.)**

- ISP.0085.9205** **Password input is required**

- ISP.0085.9206** **Password input must be WmSecureString**

- ISP.0085.9207** **Old password input is required**

- ISP.0085.9208** **New password input is required**

- ISP.0085.9210** **Host Name not specified**

- ISP.0085.9211** **No WSDL specified: wsdlURL or wsdlString input is required**

- ISP.0085.9212** **Provided package name is null**

ISP.0085.9213	Provided name is null
ISP.0085.9215	Invalid SOAPBinding found: {0}
ISP.0085.9216	Cannot schedule service. Error is : {0}
ISP.0085.9217	Cannot schedule service. Please contact your System Administrator
ISP.0085.9218	The Lateness Action option that you have selected is invalid for this Schedule Type
ISP.0085.9219	This One time task was suspended since it was overdue. It cannot be resumed
ISP.0085.9220	The lateness time that you have selected is invalid for this Lateness Action. Overdue time must be 0 minutes for 'Run the task immediately' Overdue option and must be greater than 0 minutes for 'Suspend and wait for administrator action' and 'Skip and run at next scheduled time' Overdue options.
ISP.0085.9232	No such user present: {0}
ISP.0085.9233	Cannot update child task
ISP.0085.9235	Interval time is greater than or equal to the difference between the start time and end time.
ISP.0085.9258	Web Services Descriptor name not specified, or Web Services Descriptor not found
ISP.0085.9259	Web Services Descriptor is not a Consumer, no WSCollectors exist.
ISP.0085.9260	Web Services Connector {0} was not deleted. Reason= {1}.

- ISP.0085.9261** **Implicit and Explicit Universal names of the node are identical. The Universal name is registered for the node {1}**
- ISP.0085.9263E** **Unable to get information for user/certificate mapping: {0}**
Explanation An error was encountered while getting details for a certificate. The error may have occurred while reading from the database or while constructing an X509Certificate object. See the error message for details.
Action If it is a database error, go to the Settings > JDBC Pools page and use the Test button for the ISInternal functional alias to verify that you can still connect to the database. If you can, it may have been a transient error. Try displaying or importing this certificate again. If you cannot, contact your DBA to troubleshoot your database connection problem. If it is not a database error, contact Software AG Global Support.
- ISP.0085.9264** **Cannot resume the task as the User {0} is disabled.**
- ISP.0085.9265** **Cannot resume the task as the User {0} is removed.**
- ISP.0085.9268E** **A positive integer must be provided for the port**
- ISP.0085.9269** **User Name for Transport not specified**
- ISP.0085.9270** **User Name for WS Security not specified**
- ISP.0085.9273** **URL must begin with "http:" or "https:"**
- ISP.0085.9274** **HTTP method is null**
- ISP.0085.9275** **only use one of: data.stream, data.bytes or data.mimeStream on a POST**
- ISP.0085.9276** **do not use: data.stream, data.bytes or data.mimeStream on a GET**

ISP.0085.9277	Invalid private key provided
ISP.0085.9278	Invalid certificate chain provided
ISP.0085.9279	Invalid partner certificate provided
ISP.0085.9280	invalid HTTP method: {0}
ISP.0085.9281	Http Error: {0} - {1}
ISP.0085.9282	Unable to modify; node {0} is system locked.
ISP.0085.9284	Invalid Date or Time.
ISP.0085.9285	Found unresolved dependent services: {0}
ISP.0085.9289	Remote Invoke not licensed.
ISP.0085.9290	Transport Type not specified
ISP.0085.9291	Binding with style="rpc" and use="encoded" is not supported for SOAP version 1.2. Binding {0} ignored.
Explanation	Integration Server does not support RPC/Encoded for SOAP version 1.2. Integration Server ignores bindings that specify this style/use.
Action	No action is required.
ISP.0085.9292	Bindings or operations with mixed "use" are not supported
ISP.0085.9293	Host Name must be ASCII characters

- ISP.0085.9294 **User Name for Transport must be ASCII characters**

- ISP.0085.9295 **Password for Transport must be ASCII characters**

- ISP.0085.9296 **User Name for WS Security must be ASCII characters**

- ISP.0085.9297 **Password for WS Security must be ASCII characters**

- ISP.0085.9299W **Binding with style="document" and use="encoded" is not supported. Binding {0} ignored.**

- ISP.0085.9300 **The HTTP URL alias "{0}" is already registered for the path: {1}**

- ISP.0085.9301 **A required parameter {0} was not supplied**

- ISP.0085.9302 **No valid bindings found in the WSDL.**

- ISP.0085.9303 **No Valid services found in the WSDL. The WsConnector may not work until a valid _url is given as input.**

- ISP.0085.9304 **HSM based Keystore is not supported**

- ISP.0085.9305 **Unsupported ExtensibleElement "{0}" found in Operation "{1}" and SOAPBinding "{2}"**

- ISP.0085.9306 **SOAP Action "{0}" already found in Operation "{1}" and Binding "{2}". SOAP Action must be unique for Operation and or Binding for a specified SOAP Version.**

- ISP.0085.9307 **"{0}" is not a valid HTTP URL Alias name. "{1}" leading character prohibited.**

ISP.0085.9308	"{0}" is not a valid HTTP URL Alias target path. "{1}" leading character prohibited.
ISP.0085.9309	"{0}" is not a valid HTTP URL Alias name. "{1}" character prohibited.
ISP.0085.9310	"{0}" is not a valid HTTP URL Alias target path. "{1}" character prohibited.
ISP.0085.9311	"{0}" is not a valid HTTP URL Alias name. Space character prohibited.
ISP.0085.9312	"{0}" is not a valid HTTP URL Alias target path. Space character prohibited.
ISP.0085.9313	"{0}" is not a valid alias name. HTTP URL Alias must not start with "{1}".
ISP.0085.9314	"{0}" is not a valid HTTP URL Alias target path. URL path must not start with "{1}".
ISP.0085.9343E	Deployment activation for deployment ID {0} failed with an exception. For more information, see the Integration Server logs.
Explanation	The deployment was not activated due to the reason specified in the Integration Server logs.
Action	See the Integration Server logs for more information.
ISP.0085.9344E	Artifact delivery for deployment ID {0} failed with an exception. For more information, see the Integration Server logs.
Explanation	The artifacts relating to the specified deployment ID were not delivered due to the reason specified in the Integration Server logs.
Action	See the Integration Server logs for more information.
ISP.0085.9345E	Deletion of artifacts delivered for deployment ID {0} failed with an exception. For more information, see the Integration Server logs.
Explanation	The artifacts relating to the specified deployment ID were not deleted due to the reason specified in the Integration Server log.
Action	See the Integration Server logs for more information.

- ISP.0085.9346E** **The deletion of artifacts for checkpoint ID {0} failed with an exception. For more information, see the Integration Server logs.**
- Explanation** The artifacts associated with the specified checkpoint ID could not be deleted due to the reason specified in the Integration Server log.
- Action** Check the Integration Server log for details.
-
- ISP.0085.9364I** **There are no assets for the specified checkpoint ID: {0}. Deployer cannot activate checkpoint.**
-
- ISP.0085.9365E** **Extraction of assets for checkpoint ID {0} failed for the composite {1}. For more information, see the Integration Server logs.**
- Explanation** Assets for the specified checkpoint ID could not be extracted due to the reason specified in the Integration Server log.
- Action** Check the Integration Server log for details.
-
- ISP.0085.9370I** **There are no assets for the specified deployment ID: {0}. Deployer cannot activate deployment.**
-
- ISP.0085.9372E** **Checkpoint operation for the checkpoint ID {0} was not successful. For more information, see the Integration Server logs.**
- Explanation** The checkpoint operation failed due to the reason specified in the Integration Server log.
- Action** Check the Integration Server log for details.
-
- ISP.0085.9375E** **Checkpoint activation for the checkpoint ID {0} was not successful. For more information, see the Integration Server logs.**
- Explanation** The checkpoint could not be created due to the reason specified in the Integration Server log.
- Action** Check the Integration Server log for details.
-
- ISP.0085.9376E** **Checkpoint activation for the checkpoint ID {0} failed with an exception. For more information, see the Integration Server logs.**
- Explanation** The checkpoint activation failed due to the reason specified in the Integration Server logs.
- Action** See the Integration Server logs for more information.

ISP.0085.9384E	Missing required parameter: {0}
Explanation	A required parameter was not supplied.
Action	Supply a value for the missing parameter and execute the service again.
ISP.0090.0006	recursive IData reference key:'{0}'
ISP.0090.0007	{0} recursive IDataCordable reference key:'{1}'
ISP.0091.0001	{0} in {1} minutes or as soon as idle
ISP.0091.0002	Pending shutdown/restart request has been canceled
ISP.0091.0003	Grace period has expired. Server is shutting down.
ISP.0091.0004	Grace period has expired. Server is restarting.
ISP.0108.0002W	Old decryption key has been retrieved for this recipient: {0}
Explanation	If the decryption key is not found when processing an encrypted message, the private key is looked up in the decryption key history. If the private key is found in the decryption key history, this warning message is displayed.
Action	Ensure that proper decryption keys are available when processing the encrypted messages.
ISP.0108.0003E	Could not load PKI ProfileFactory : {0}
Explanation	A PKI profile factory cannot be loaded.
Action	Contact Software AG Global Support.
ISP.0108.0004E	Could not load PKI Profile : {0}
Explanation	A PKI profile cannot be loaded.
Action	Contact Software AG Global Support.

ISP.0108.0005E	Could not parse PKI directory port {0}, using default port: {1}
Explanation	When the Profile manager cannot parse a PKI directory port, the default PKI Directory port (389) is used, and this error message is displayed.
Action	Ensure that a proper PKI directory port is provided so that there are no errors when parsing it.
ISP.0108.0006E	Could not parse PKI manager port {0}, using default port: {1}
Explanation	When the Profile manager cannot parse a PKI manager port, the default PKI manager port (829) is used and this Error message is displayed.
Action	Ensure that a proper PKI manager port is provided, so that there are no errors when parsing it.
ISP.0108.0007E	Could not log out PKI Profile: {0}
Explanation	This error is displayed when a PKI profile cannot log out. Logout of a PKI profile is required when deactivating or unregistering a PKI profile.
Action	Contact Software AG Global Support.
ISP.0108.0008W	Encryption and Signing key pairs have been updated: {0}
Explanation	The encryption certificate in the user's profile is not synchronized with the one in the JNDI directory. In this case, the signing and encryption key pairs are updated and this warning message is displayed.
Action	Ensure that the encryption certificates are synchronized with those available in the JNDI directory.
ISP.0108.0009W	Could not check profile "{0}" for key pair update: {1}
Explanation	When the encryption certificates in the user's profile are not synchronized with those available in the JNDI directory, the signing and encryption key pairs are updated. This warning message is displayed when there are errors when accessing the LDAP directory while updating the key value pairs.
Action	Contact Software AG Global Support.
ISP.0147.0006E	Error while closing sftp session: Details: {0}
Explanation	The session key that you specified has expired.
Action	Ensure that the session corresponding to this session key exists and has not expired.

ISP.0147.0007E	Error in sftp session sweeper thread. Details: {0}
Explanation	Integration Server encountered an error in the SFTP session sweeper thread.
Action	Read through the details provided in the error message and take corrective steps.
ISS.0001.0001	All licenses have been consumed.
ISS.0001.0002	{0} License key expired or invalid.
ISS.0001.0003	{0} License will expire in {1} days.
ISS.0001.0004	Integration Server will shutdown in 30 minutes, unless a valid license key is provided.
ISS.0001.0005	Unable to load package {0} due to invalid license for package {1}.
ISS.0001.0006	Could not add {0} as dependent package due to invalid license.
ISS.0001.0007	Could not load {0} because one of the dependent package is not loaded.
ISS.0001.0008	{0} Functionality disabled due to license restrictions.
ISS.0001.0009	License key file is read-only. License settings cannot take effect until you make the file read/write.
ISS.0001.0010	The license key is not valid with this version of Integration Server. License key is version {0} and Integration Server is version {1}.
ISS.0001.0011U	The Integration Server is not licensed by the current license key.
Explanation	Integration Server has reached its client limit. Your license for Integration Server allows only a certain number of sessions to be used at a time. Integration Server issues this message when the number of users trying to use the server exceeds the number specified in the license.
Action	Check the number of licensed sessions specified in your Integration Server license. Consider upgrading the license to obtain more user "seats" if the number of users requiring access to your Integration Server has increased.

ISS.0002.0002E	Error loading LDAP settings: {0}
Explanation	Integration Server encountered an IOException while reading the ldap.cnf file.
Action	Check to make sure that the operating system user that is running Integration Server has permission to read and write to the ldap.cnf file. In addition, make sure that the ldap.cnf file is a valid XML file and has not been corrupted in some way. As a last resort, delete the ldap.cnf file and reconfigure the LDAP settings from the Server Administrator.
ISS.0002.0003E	Error saving LDAP settings: {0}
Explanation	An IOException occurred while Integration Server was writing the ldap.cnf file.
Action	Check to make sure that the operating system user that is running Integration Server has permission to read and write to the ldap.cnf file and to the server config directory. In addition, make sure that there is sufficient disk space and quota space for creating and writing a new file.
ISS.0002.0005W	LDAP User Manager enabled, but no LDAP directories are configured
Explanation	The Integration Server is attempting to perform operations that require a connection to an LDAP server, but the Integration Server is only partially configured to use LDAP. Specifically, the configuration does not include a list of LDAP directories to which the Integration Server can connect.
Action	Use the Integration Server Administrator to configure the Integration Server to connect to one or more LDAP directories. For more information about working with LDAP, refer to the webMethods Integration Server documentation.
ISS.0002.0007W	Query returned multiple DN's for a single user with filter ({0})={1}
Explanation	The values specified in the Query DN field on the LDAP directory settings screen are not sufficient to uniquely identify a user. Integration Server uses this field to build a query to send to the LDAP server so that the LDAP server can authenticate the user.
Action	Make sure that the user root, user property, and user names specified on the Query DN field are not ambiguous.
ISS.0002.0008E	Could not get a connection from the pool in the time allowed
Explanation	Integration Server was unable to connect to the LDAP server because the request to obtain a connection timed out. This error can occur if the LDAP directory server is slow, is under high load, or is experiencing high latency, and there are insufficient connections in the connection pool to meet demand.
Action	This error is probably transient. It is usually sufficient to wait a few seconds and try the operation again (for example logging in, executing a service) when the load has decreased and resources have become available. If the problem persists, then from the LDAP Directory Settings page of the Server Administrator, try increasing the size of the LDAP connection pool. Also check to make sure the LDAP directory server is

properly configured and that the network is able to handle the load being placed on it by the application.

ISS.0002.0009E	Unable to open a connection to {0}
Explanation	The Integration Server was unable to open a connection to the indicated LDAP directory server.
Action	To resolve this issue, do the following: <ul style="list-style-type: none">- Make sure the LDAP server is running and that the Integration Server has permission to connect to it.- Make sure that the connection parameters specified on the LDAP Settings screen of the Server Administrator are properly configured.- If you are using SSL, make sure that the directory URL specified on the LDAP Settings screen specifies an SSL port on the LDAP server and that both the Integration Server and LDAP server support SSL.- If you are specifying credentials, make sure the principal specified on the LDAP Settings screen of the Server Administrator is correct and that the password matches. This error can also occur if the Integration Server cannot establish a connection to the LDAP server within the configured time limit because of a problem such as network latency. For more information about connecting the Integration Server to an LDAP server, see the webMethods Integration Server documentation.
ISS.0002.0010E	Error querying for user {0}: {1}
Explanation	During a user log in, the Integration Server encountered an error while performing a query to obtain the user's Distinguished Name.
Action	In the Server Administrator, on the LDAP Settings screen for the LDAP directory, ensure that the user root and user properties are set correctly.
ISS.0002.0013W	Found group {0}, but it contained no attribute {1}
Explanation	During ACL mapping, Integration Server determined that the value specified in the group attribute field does not match the attribute values of the group that Integration Server found.
Action	Make sure the group name attribute field contains a valid group name attribute.

- ISS.0002.0014E Error querying for groups on {0} with root {1} and filter {2}: {3}**
- Explanation** Integration Server encountered an error when looking for LDAP groups to map to an Integration Server ACL.
- Action** If the text of the exception indicates a connection issue, try performing the mapping later. Otherwise, check the values specified for group name, filter, and group name attribute on the Map Groups to ACLs screen.
-
- ISS.0002.0015E Unable to create ACL mapping: LDAP User Manager not initialized**
- Explanation** An attempt to map an LDAP group to an ACL failed because the LDAP User Manager function of the Integration Server is not running. This error occurs when one user disables LDAP while another user is trying to perform ACL mapping.
- Action** Use the Integration Server Administrator to check the External User Management Configuration screens for possible configuration problems. In addition, try checking the server and error logs for messages about problems with the LDAP manager. For information about using the Integration Server with an external directory, refer to the webMethods Integration Server documentation.
-
- ISS.0002.0016E Unable to create ACL mapping: ACL {0} not found**
- Explanation** An attempt to map an LDAP group to an ACL failed because the ACL specified on the Map Groups to ACLs screen does not exist. This error occurs if one user deletes the ACL in question when another user is trying to map an LDAP group to it.
- Action** Determine why the other user changed the Integration Server configuration then reconfigure the Integration Server to use LDAP, if appropriate. For information about using the Integration Server with an external directory, refer to the webMethods Integration Server documentation.
-
- ISS.0002.0017E Unable to retrieve password for handle {0}: {1}**
- Explanation** The Integration Server is trying to connect to an LDAP server. As part of connecting, the Integration Server needs to send a password to the LDAP server. This error occurs when the Integration Server cannot find the password it stored for this purpose. A likely cause is that the ldap.cnf file was moved from one system to another, but the stored outbound passwords were not.
- Action** Make sure the Outbound Password Manager is properly configured, and that its files are readable by the Integration Server process. If the Outbound Password Manager is set up correctly, and the error still occurs, go to the LDAP Configuration screen of the Server Administrator and reenter the existing password.

ISS.0002.0018E	Unable to store password for handle {0}: {1}
Explanation	The Integration Server was unable to store the password needed to connect to an LDAP server. The Integration Server must supply passwords to many of the applications it connects to. It stores these outbound passwords in encrypted form on the Integration Server. This error occurs when an administrator enters or changes the password, but the Integration Server cannot subsequently store it.
Action	Check to see if the Integration Server is properly configured to handle outbound passwords. Make sure that the following outbound password configuration files reside on the Integration Server and are readable and writable: config/txnPassStore.dat, config/empw.dat, config/configPassman.cnf and config/passman.cnf. Refer to the webMethods Integration Server documentation for more information.
ISS.0002.0019E	Unable to delete password for handle {0}: {1}
Explanation	An administrator updated the Integration Server configuration so that it no longer connects to an LDAP server. As part of this process, the Integration Server tried to delete the password it uses to connect to the LDAP server, but was unable to. The Integration Server deletes the LDAP server from the configuration, but the password remains, in encrypted form, on the Integration Server. The most likely cause is that the files used to store outbound passwords on the Integration Server are read-only.
Action	Refer to the webMethods Integration Server documentation for more information about outbound passwords and the files used to store them. Then try to determine why the files are in read-only mode.
ISS.0002.0020E	Unable to check password: LDAP User Manager not initialized
Explanation	The Integration Server tried to check the password of an LDAP user but could not because the LDAP user manager is not running. This error occurs when one user updates the Integration Server configuration to disable LDAP directory use while another user is trying to perform an LDAP operation.
Action	Determine why the other user changed the Integration Server configuration. Then, reconfigure the Integration Server to use LDAP, if appropriate. For information about using the Integration Server with an external directory, refer to the webMethods Integration Server documentation.
ISS.0002.0021E	Unable to check group membership: LDAP User Manager not initialized
Explanation	The Integration Server tried to find members of an LDAP group but could not because the LDAP user manager is not running. This error occurs when one user updates the Integration Server configuration to disable LDAP directory use while another user is trying to perform an LDAP operation.
Action	Determine why the other user changed the Integration Server configuration. Then, reconfigure the Integration Server to use LDAP, if appropriate. For information about using the Integration Server with an external directory, refer to the webMethods Integration Server documentation.

- ISS.0002.0023E Error initializing a connection to {0}: {1}**
- Explanation** The Integration Server encountered an exception while trying to connect to the indicated LDAP server.
- Action** Check the following:
- Make sure the LDAP directory server is running and that the Integration Server has permission to access it.
 - Make sure the parameters on the External User Management Configuration screens of the Server Administrator have been properly set.
-
- ISS.0002.0024W Error closing connection to {0}: {1}**
- Explanation** Integration Server encountered an exception while trying to connect to the indicated LDAP server. Integration Server will clean up the connection.
- Action** No action is required.
-
- ISS.0002.0030E While attempting automatic LDAP configuration, some invalid settings were found. It is necessary to complete the configuration manually.**
- Explanation** When you upgrade from Integration Server release 6.1 or earlier to Integration Server release 6.5 or later, the upgrade process tries to automatically configure the external user management facilities in your new Integration Server based on these settings in your old Integration Server. To determine the old configuration settings, the upgrade process looks for the following properties:
- watt.server.ldap.server
 - watt.server.ldap.attr.userId
 - watt.server.ldap.attr.member
- This error indicates that the upgrade process was unable to find one of these properties. The automatic configuration does not continue.
- Action** Go to the Security > Users and Groups > External User Management Configuration screen of the Server Administrator and configure the Integration Server to use an external LDAP directory. For additional information, refer to the webMethods Integration Server documentation.
-
- ISS.0002.0034E Invalid credentials connecting to {0} as {1}**
- Explanation** The Integration Server encountered an Authentication Exception because the indicated user could not log in to the indicated LDAP server.
- Action** This error can occur for a number of reasons. Make sure that the DN of the user is valid, the credentials (i.e. password) specified are valid, and the user account is enabled.

ISS.0002.0035E	Invalid credentials connecting to {0} as {1}: {2}
Explanation	The Integration Server encountered an Authentication Exception because the indicated user could not log in to the indicated LDAP server. The last part of the message <errorMessage> includes extra information provided by the LDAP server about the error. You can use this data to audit authentication errors when the Integration Server connects to Microsoft Active Directory.
Action	This error can occur for a number of reasons. Check to make sure that the DN of the user is valid, the credentials (i.e. password) specified are valid, and the user account is enabled. Note: The errorMessage portion of this error displays only if the watt.server.ldap.extendedMessages property in the server.cnf file is set to true. If you do not find the extended message useful, you can disable extended messaging by setting this property to false.
ISS.0002.0040E	Error querying for users : {0}
Explanation	Error while listing users from the LDAP server, a runtime exception occurred while querying users for the provided search criteria.
Action	Ensure that the search criteria is defined properly, the LDAP server is configured properly, and it is running.
ISS.0002.0041E	Error querying for users : {0}
Explanation	Some errors occurred while searching for a particular group, or a search string in the LDAP Server.
Action	Ensure that the search criteria is defined properly, the LDAP server is configured properly, and it is running.
ISS.0002.0042W	Bailing out query as {0} is null or empty.
Explanation	While listing users from the LDAP server, either the directory name suffix or directory name prefix returned from the server is null or empty.
Action	Ensure that the LDAP configuration is correct and the LDAP server is not disconnected.
ISS.0002.0044E	Error querying for user(s) on {0} with search root {2}: {3}
Explanation	Error while listing users from the LDAP server, a runtime exception occurred while querying users for the provided search criteria.
Action	Ensure that the search criteria is defined properly, the LDAP server is configured properly, and it is running.

ISS.0002.0045W	Found No Group on quering on {0} with root {1} and filter {2}
Explanation	No group is found in the LDAP server for the search criteria.
Action	Refine the search query to get the required result.
ISS.0002.0046E	Selected group {0} does not exist.
Explanation	The Integration Server group associated with the LDAP configuration is deleted.
Action	Ensure that the group selected while configuring LDAP exists. If the group does not exist, you can take one of the following actions: 1) Modify the LDAP configuration to specify another group. 2) Add a group with the same name as the deleted group that was associated with the LDAP configuration.
ISS.0002.9001E	LDAP User Manager not initialized
Explanation	A user is trying to execute an operation on the LDAP server but LDAP user manager is not initialized.
Action	Check the LDAP settings.
ISS.0002.9002E	Error saving new ACL Mappings: {0}
Explanation	A runtime exception occurred while adding new mappings to the LDAP Server.
Action	Ensure that the mapping strings are correct (they should be in the following format - name; dn), the LDAP server is configured properly and it is running.
ISS.0003.9001	Transformation: Required argument "{0}" missing.
ISS.0003.9002	Transformation: No XML source provided
ISS.0003.9003	Transformation: No result type specified
ISS.0003.9004	Transformation: No result filename specified

ISS.0003.9005	Transformation: No result system ID specified
ISS.0003.9006	Transformation: PipedInputStreamException - {0}
ISS.0003.9007	Transformation: HTTPS URL error - {0}
ISS.0003.9008	Transformation: HTTPS URL error - Response returned with HTTP protocol error {0}.
ISS.0003.9009	XSLT Samples: No XSLT input paramters provided
ISS.0003.9010	XSLT Service: No valid input provided
ISS.0003.9011	XSLT Service: No associated .xsl file for this service
ISS.0007.0001E	Access Denied. User "{0}" does not have permissions to invoke service: {1}.
Explanation	The user does not have permission to invoke an Integration Server resource. Read through the details provided in the server log to find the user name and the name of the service.
Action	To grant permission to the user, either add the user to a group that is listed in the Execute ACL assigned to the service, or add one of this user's groups to the Execute ACL assigned to the service.
ISS.0007.0002E	Access Denied. No permissions to invoke service ({0}) on port "{1}".
Explanation	The Access Mode for the specified port is configured to Deny by Default. With this configuration, the port only allows the services explicitly listed in the Allow List. The identified service is not in the Allow List of the identified port.
Action	If this service should be allowed on this port, add the service to the Allowed Services list of the port.
ISS.0010.8050	Error while connecting to the remote authorization server using the remote server alias "{0}". Error details: {1}
Explanation	Integration Server cannot connect to the specified remote OAuth authorization server.
Action	Edit the remote server alias and ensure that all the parameters are specified correctly. If needed, run a test of the remote server alias.

- ISS.0012.0014E** **Unable to initialize JAAS login context. JAAS configuration file in use: {0}. Error message: {1}. Stack trace: {2}**
- Explanation** Integration Server uses IntegrationServer/config/is_jaas.cnf file for its JAAS configuration. If there is any problem loading this file, Integration Server throws this exception.
- Action** The entries found in a JAAS configuration file should follow the JAAS syntax. If you made any changes to the IntegrationServer/config/is_jaas.cnf, review your changes and make sure there are no syntax errors in the file.
-
- ISS.0012.0016E** **Initialization of X509ValidatorModule failed with exception: {0}.**
- Explanation** The X509ValidatorModule defined in the IntegrationServer/config/is_jaas.cnf file is incorrect.
- Action** Review the Integration Server error log for the actual exception. Refer to the webMethods Integration Server documentation for information about how to use this module and correct any errors found.
-
- ISS.0012.0017E** **Authentication failed because the X.509 certificate path validation has failed.**
- Explanation** The X509ValidatorModule is enabled in the IntegrationServer/config/is_jaas.cnf file. As a result, Integration Server performed certificate path validation using the information provided, but the client certificates failed the certificate path validation.
- Action** Make sure that the truststore used by the X509ValidatorModule contains the intermediary certificates as well.
-
- ISS.0012.0020E** **Authentication failed because the X.509 certificate has been revoked.**
- Explanation** The X509ValidatorModule is enabled in the IntegrationServer/config/is_jaas.cnf file. As a result, Integration Server checked the client certificate against the Certificate Revocation List (CRL) and the client certificate was found to be revoked.
- Action** Advise the client to resubmit the request using a valid certificate.
-
- ISS.0012.0022E** **Access Denied. Authentication resolved to user "{0}". User is not defined in any of the available user stores.**
- Explanation** Integration Server JAAS authentication modules return the username in the Subject. Integration Server then tries to retrieve the definition of this user either locally in its user store, or in Central Users (if configured), or LDAP (if configured). If Integration Server is not able to find the user anywhere, it rejects the client request with this error.
- Action** If this user should be allowed accessing Integration Server resources, make sure this user is defined in any of the user stores accessible to Integration Server.

ISS.0012.0023E	SAML assertion verification failed. The current time {0} violates the "Not Before" setting {1} specified in the SAML assertion.
Explanation	Integration Server received a SAML assertion that arrived before the "Not Before" setting.
Action	Check the clock time of the issuer. If it is significantly different from the clock time on the Integration Server machine, adjust the Clock Skew value on the Security -> SAML screen.
ISS.0012.0024	SAML assertion verification failed. The current time {0} violates the "Not On Or After" setting {1} specified in the SAML assertion.
Explanation	Integration Server received a SAML assertion that arrived later than the "Not On Or After" setting.
Action	Check the clock time of the issuer. If it is significantly different from the clock time on the Integration Server machine, adjust the Clock Skew value on the Security -> SAML screen.
ISS.0012.0025E	Rejecting SAML assertion from issuer "{0}" because issuer is not configured on the Security > SAML screen.
Explanation	Integration Server received a SAML assertion from an issuer that has not been configured on the Security -> SAML screen.
Action	Configure the issuer on the Security -> SAML screen.
ISS.0012.0027W	{0}% or more of maximum number of concurrent stateful sessions are in use. {1} sessions are available.
Explanation	Integration Server is approaching the threshold for concurrent stateful sessions.
Action	No immediate action is required. Once the limit is reached, all new requests to create stateful sessions will be rejected. You can increase the limit using the Resources screen in the Integration Server Administrator; however, doing so could increase the server's resource requirement.
ISS.0012.0030E	Rejecting SAML assertion because the subject identified in the SAML assertion is not the one who signed the request.
Explanation	For security reasons, Integration Server cannot accept requests that are not signed by the subject identified in the SAML assertion.
Action	Sign the message using the subject identified in the SAML assertion.

- ISS.0013.0001** **Binding XML. Service {0} was unable to bind incoming XML data**
- ISS.0013.0004E** **The syntax for the watt.server.content.type.mappings property is invalid. Accept header fields of HTTP client requests might not be handled correctly. Verify that the correct syntax is used for this parameter.**
- Explanation** The syntax for the watt.server.content.type.mappings parameter is invalid.
- Action** Use the correct syntax for this parameter. See Administering webMethods Integration Server for more information about using watt.server.content.type.mappings.
- ISS.0014.0001E** **Encountered fatal errors while starting License Manager. Shutting down server.**
- Explanation** Integration Server encountered a serious internal error while validating the license.
- Action** Contact Software AG Global Support.
- ISS.0014.0004** **No listening ports were available. Shutting down server.**
- ISS.0014.0009** **Server is unable to determine its own name.**
- ISS.0014.0012** **watt.server.fileEncoding unsupported by JVM. Server may be unable to continue.**
- ISS.0014.0013** **watt.server.netEncoding unsupported by JVM. Text may not process properly.**
- ISS.0014.0014** **watt.server.logEncoding unsupported by JVM. Logging in default encoding.**
- ISS.0014.0017** **Warning: {0} when initializing ACL Manager file {1}**
- ISS.0014.0021E** **Failed to invoke notification callback {0}: {1}**
- Explanation** Integration Server encountered an error while updating ACLs. Specifically, an error occurred when Integration Server invoked a service that is registered as a notification callback.
- Action** Make sure that the service being invoked exists and can be executed.

ISS.0014.0022E	Retrying service {0}. Retry count is {1}
Explanation	Integration Server is retrying a service that was previously unsuccessful.
Action	No action is required.
ISS.0014.0023E	Available Thread Pool Threshold No Longer Exceeded: {0}% available
Explanation	Integration Server is no longer exceeding the specified threshold for thread pool usage.
Action	No action is required.
ISS.0014.0024E	Server Initialization Aborted. See log messages.
Explanation	During start up, Integration Server encountered a serious internal error that caused it to shut down immediately.
Action	Make sure that the machine on which Integration Server runs has sufficient disk space. In addition, make sure the operating system user that is trying to start Integration Server has a sufficient space allowance and has read/write permission to the directory on which Integration Server resides.
ISS.0014.0025	Master password for outbound password encryption has expired. Password was last changed on {0}. The current expiration interval is {1} days
ISS.0014.0026	Master password for outbound password encryption expires in {0} days
ISS.0014.0027	Unable to remove outbound password handle {0}
ISS.0014.0028	Cannot initialize OutboundPasswordManager with null Password Manager
ISS.0014.0029S	Master password failed a sanity check
Explanation	During Integration Server initialization, the sanity check of the master password for outbound passwords failed. Integration Server uses the master password to encrypt outbound passwords, which the Integration Server uses to connect to applications or systems such as remote Integration Servers, proxy servers, or databases. The outbound passwords are stored in files on Integration Server and encrypted for security purposes. During initialization, Integration Server performs a sanity check of the master password by attempting to use it to decrypt a special, internal string that it previously encrypted using the master password. If the decrypted internal string matches the clear text version of the string, Integration Server knows the correct master password was provided. This error is issued when the decrypted and clear text versions of the string do not match.
Action	The sanity check of the master password can fail for a number of reasons: - The outbound password file is corrupted.

- The master password file is corrupted.
- You mistyped the master password when you were prompted for it.

If you suspect you have mistyped the password, shut down the server and restart it, this time entering the correct password. If this does not correct the problem, refer to the webMethods Integration Server documentation.

ISS.0014.0030S	Master password updated
Explanation	The master password, which Integration Server uses to encrypt outbound passwords, has been successfully updated.
Action	No action is required.
ISS.0014.0035S	OutboundPasswordManager configuration directory cannot be null
Explanation	Integration Server cannot locate the configuration directory it uses for managing outbound passwords.
Action	Contact Software AG Global Support.
ISS.0014.0039S	OutboundPasswordManager, {0} caught this: type {1}, msg {2}
Explanation	The code that Integration Server uses to manage outbound passwords encountered a problem while trying to perform the indicated operation.
Action	If the exception message text does not suggest a solution, contact Software AG Global Support.
ISS.0014.0047	com.wm.app.b2b.server.DataStore must be initialized before it can be used.
ISS.0014.0048	The ISInternal functional alias is not configured properly on the JDBC Pools page. Assign a valid database pool and restart the Integration Server.
ISS.0014.0051	Cannot acquire the lock.
ISS.0014.0054	Error occurred while initializing server: {0}

ISS.0014.0055	Cannot acquire an exclusive lock. Another session is holding a shared lock on the requested item.
ISS.0014.0056	Cannot acquire an exclusive lock on the requested context. Another session has locked it.
ISS.0014.0057	Integration Server is quiesced and is not accepting new requests at this time.
ISS.0014.0058	Integration Server has reached the license limit for concurrent sessions.
ISS.0014.9101	User does not exist: {0}
ISS.0014.9102	No package name specified
ISS.0014.9104	A listener must be provided
ISS.0014.9105	A listener factory must be provided
ISS.0014.9106	A listener factory with {0} is already registered in the {1} package
ISS.0014.9107	Attempted to register a factory with an invalid identifying key
ISS.0014.9108	Attempted to register a listener with an invalid identifying key
ISS.0014.9109	A listener is already registered with the key {0}. The existing listener must be unregistered first
ISS.0014.9110	Failed to update listener configuration information

- ISS.0014.9111 Unregistration failed, could not update the configuration**
- ISS.0014.9112 Service {0} unable to bind incoming XML data**
- ISS.0014.9113 No Valid Active Packages**
- ISS.0014.9114 Package directory for {0} does not exist**
- ISS.0014.9115 Package {0} does not exist**
- ISS.0014.9116 Unable to locate or start compiler**
- ISS.0014.9117 Unable to save file {0} for {1}**
- ISS.0014.9118U ServerReferenceManager can't get session to access object cache**
Explanation Integration Server encountered an internal error with the object cache.
Action Contact Software AG Global Support.
- ISS.0014.9119U Unable to allocate a new thread in the time specified**
Explanation Integration Server has reached the configured limit for the number of new threads it can create. After waiting unsuccessfully for resources to become available, Integration Server issued this ISRuntime exception. This exception usually indicates a transient condition in which resources are temporarily unavailable. If this error occurs during execution of a trigger, and retry is enabled, Integration Server will automatically retry the service. If, after a configured amount of time, the resources are still unavailable, Integration Server throws this exception.
Action If the problem persists, use the Resource Settings page of the Server Administrator to specify thread pool settings that are more appropriate for your environment.
- ISS.0014.9120 Can not set thread pool max to zero or less than min, max={0}, min={1}**

ISS.0014.9121	Repository config file repository4.cnf not found.
ISS.0014.9123E	{0} package not reloaded; missing the following assets: {1}
Explanation	An internal error occurred while using the local service development feature in Software AG Designer. An attempt to reload an updated IS asset (flow service, Java service, document type, etc.) failed because the specified IS asset does not exist in the IS namespace. At run time, the {0} in the error message is replaced with the package name and the {1} is replaced with the IS assets that do not exist in the namespace.
Action	Contact Software AG Global Support.
ISS.0014.9124E	{0} package not reloaded. {1} already registered in {2}
Explanation	While using the local service development feature in Software AG Designer, an attempt to reload an updated IS asset (flow service, Java service, document type, etc.) failed because Integration Server determined that another package contains an asset with the same name. At run time, the {0} in the error message is replaced with the package name, the {1} is replaced with the IS asset name for which a reload was attempted, and the {2} is replaced with the name of the package that contains the already loaded, identically named asset.
Action	Ensure that each IS asset uses a name that is unique across the Integration Server namespace. To rename one of the assets, you might need to disable the package that contains the asset whose name you do not want to change. Change the name of the IS asset in the package that you want to change. Then, re-enable both packages.
ISS.0014.9125E	Primary port change failed. The primary port must be a port associated with the WmRoot package.
Explanation	An attempt to change the primary port failed because the chosen port is associated with a package other than WmRoot.
Action	Select a port associated with the WmRoot package as the primary port. Alternatively, change the chosen port to associate it with the WmRoot package and then designate the port as the primary port.
ISS.0014.9126E	Primary port change failed. The primary port must be an enabled port.
Explanation	An attempt to change the primary port failed because the chosen port is not enabled.
Action	Select an enabled port as the primary port. Alternatively, enable the chosen port and then designate the port as the primary port.

ISS.0014.9127E	Primary port change failed. The primary port must be an HTTP or HTTPS port.
Explanation	An attempt to change the primary port failed because the chosen port is not an HTTP or HTTPS port.
Action	Select an HTTP or HTTPS port to use as the primary port.
ISS.0014.9128E	Primary port change failed. The primary port must be a standard port.
Explanation	An attempt to change the primary port failed because the chosen port was not a standard port. Currently, the only non-standard port type is the diagnostic port.
Action	Select a standard HTTP or HTTPS port to use as the primary port. Do not select a diagnostic port to be the primary port.
ISS.0015.0002E	Error {0} initializing Invoke Manager class {1} from {2}
Explanation	Integration Server failed to initialize InvokeManager from the configuration file located at <IntegrationServer_dir>/config/invokemanager.cnf file at startup.
Action	Contact Software AG Global Support.
ISS.0015.0003E	Error {0} initializing Invoke Manager with {2}
Explanation	Integration Server failed to initialize InvokeManager from the configuration file located at <IntegrationServer_dir>/config/invokemanager.cnf file at startup.
Action	Using a text editor, open the <IntegrationServer_dir>/config/invokemanager.cnf file and make sure that the content is not corrupt. If the error still occurs, consider removing the invokemanager.cnf file and restarting Integration Server.
ISS.0015.0004E	Service {0} failed ACL access checking for user {1}
Explanation	The client application failed to invoke the service because the current user did not have the Execute ACL privileges to execute the service.
Action	Using the Integration Server Administrator, examine the ACL settings of the service as well as the ACL group to which the current user belongs. Make sure that the user has the proper ACL settings.
ISS.0017.0001E	An error was encountered parsing {0}: {1}. See the Integration Server error log for the full stack trace.
Explanation	Either the format of XML in the configuration file is invalid, or a specific setting is not allowed.
Action	Read through the details provided in the error message and edit the configuration file to correct the problem.

ISS.0017.0002I	Cache manager {0} created.
ISS.0017.0003E	{0} is required.
Explanation	A value is required for the indicated parameter.
Action	Supply a value for the parameter.
ISS.0017.0004E	There is no cache manager named {0}.
Explanation	There is no cache manager with this name on Integration Server.
Action	Make sure the cache manager name is typed correctly and that it exists on the Integration Server.
ISS.0017.0005E	There is no cache named {0} in the {1} cache manager.
Explanation	Integration Server tried to connect to the indicated cache, but there is no cache with this name associated with the cache manager.
Action	Provide the name of a cache that is managed by the supplied cache manager.
ISS.0017.0006I	Cache {0} created.
ISS.0017.0007E	Cache manager names starting with "SoftwareAG" are reserved.
Explanation	The cache manager could not be created because the name is invalid.
Action	Choose a different name for the cache manager.
ISS.0017.0008I	Successfully deleted cache manager {0}.
ISS.0017.0009I	All elements have been removed from cache {1} of cache manager {0}.
ISS.0017.0010I	Disabled cache {1} of cache manager {0}.
ISS.0017.0011I	Enabled cache {1} of cache manager {0}.

- ISS.0017.0012E** **Cache manager {0} is not started.**
Explanation The service failed to execute because the specified cache manager is not available.
Action Open Integration Server Administrator and go to the Settings > Caching page to verify that the cache manager is started and the cache the service wants to use is enabled.
- ISS.0017.0013E** **Cache {1} for cache manager {0} not enabled.**
Explanation The operation could not be completed because the indicated cache could not be found in the indicated cache manager.
Action Make sure the cache name is typed correctly and that it is contained in the indicated cache manager.
- ISS.0017.0014E** **Cache manager {0} already exists.**
Explanation The cache manager could not be created because a cache manager with the indicated name already exists on the Integration Server. The name you specify must be unique on the Integration Server.
Action Enter a new name for the cache manager that is unique to the Integration Server.
- ISS.0017.0015E** **The {0} cache manager attempted to connect to a Terracotta Server Array, but the Integration Server license does not allow it. This cache manager will not be usable.**
Explanation To use this feature, Integration Server must have a license that allows distributed caching.
Action Obtain the appropriate license from Software AG Global Support and add it to the Integration Server.
- ISS.0017.0016E** **If rejoin is enabled, a Terracotta Server Array URL must be supplied.**
Explanation You selected the Rejoin check box, but did not configure the cache manager to connect to a Terracotta Server Array.
Action Specify a Terracotta Server Array URL or clear the Rejoin check box.
- ISS.0017.0017E** **Cannot use the administrative services to change a system cache manager: {0}.**
Explanation The cache could not be created because a cache with that name already exists in the cache manager. The name you specify must be unique within the cache manager.
Action See Administering webMethods Integration Server for more information about system cache managers.

ISS.0017.0018E	The {0} cache already exists.
Explanation	The cache could not be created because a cache with that name already exists in the cache manager. The name you specify must be unique within the cache manager.
Action	Enter a name for the cache that is unique within the cache manager.
ISS.0017.0019E	Cannot delete a system cache manager: {0}.
Explanation	The cache manager you attempted to delete is a system cache manager and cannot be deleted.
Action	See Administering webMethods Integration Server for more information about system cache managers.
ISS.0017.0020E	Cache manager name cannot contain any of these characters: ? [] / = + < > ; " , * ^ @
Explanation	The cache manager could not be created because the name you specified contains invalid characters.
Action	Specify a new name using valid characters.
ISS.0017.0021E	Cache manager name cannot start with a '.' or end with a space.
Explanation	The cache manager could not be created because the name you specified contains invalid characters.
Action	Specify a new name using valid characters.
ISS.0017.0022E	Cache manager name cannot be an operating system device name.
Explanation	The cache manager could not be created because the name you specified is a reserved word as specified by your operating system.
Action	Specify a new name for the cache manager. Refer to your operating system's documentation for a list of reserved words.
ISS.0017.0023E	An error was encountered updating {0}: {1}. See the Integration Server error log for the full stack trace.
Explanation	While attempting to enable or disable clustering for the Integration Server, an error occurred while updating the Terracotta Cache Manager configuration files.
Action	Review the error details provided in the message and in the Integration Server error log. After correcting the issue that caused the error, use Integration Server Administrator to enable or disable clustering for the Integration Server.

- ISS.0017.0024E** **When a cache is distributed, Overflow to Disk, Overflow to Off-heap and Persist to Disk cannot be selected.**
- Explanation** The Overflow to Disk, Overflow to Off-heap and Persist to Disk options are not allowed with distributed caches.
- Action** If you are creating a distributed cache, remove the values from the Overflow to Disk, Overflow to Off-heap and Persist to Disk fields.
-
- ISS.0017.0026E** **Cache manager name is null in {0}. The cache manager will not be used**
- Explanation** A cache manager configuration file was supplied with a null cache manager name.
- Action** Edit the configuration file and provide a name for the cache manager.
-
- ISS.0017.0027E** **A cache manager named "{0}" has already been loaded from {1}. The name cannot also be used in {2}. The cache manager in {2} will be ignored.**
- Explanation** More than one configuration file in the Integration Server_directory\config\Caching directory contains the specified cache manager. Integration Server cannot load two instances of the same cache manager. The cache manager that is already loaded is being used. The cache manager in the second configuration file will be ignored.
- Action** Either remove one of the configuration files or change the cache manager name in one of the configuration files.
-
- ISS.0017.0028I** **Cache manager {0} successfully shutdown.**
-
- ISS.0017.0029I** **Cache manager {0} successfully started.**
-
- ISS.0017.0030E** **Cache manager {0} successfully reloaded.**
- Explanation** A value is required for the indicated parameter.
- Action** Supply a value for the parameter.
-
- ISS.0017.0031I** **Cache manager {0} is already running.**
-
- ISS.0017.0032I** **Cache manager {0} is not running.**

ISS.0017.0033E	Cannot enable a system cache.
Explanation	The cache you attempted to enable is a system cache. System caches are used by internal processes and cannot be modified.
Action	See Administering webMethods Integration Server for more information about system caches.
ISS.0017.0034E	Cannot disable a system cache.
Explanation	The cache you attempted to disable is a system cache. System caches are used by internal processes and cannot be modified.
Action	See Administering webMethods Integration Server for more information about system caches.
ISS.0017.0035E	Cannot clear the contents of a system cache.
Explanation	The cache you attempted to clear is a system cache. System caches are used by internal processes and cannot be modified.
Action	See Administering webMethods Integration Server for more information about system caches.
ISS.0017.0036E	Cannot start a system cache manager.
Explanation	The cache manager you attempted to start is a system cache manager. System cache managers are used by internal processes and cannot be modified.
Action	See Administering webMethods Integration Server for more information about system cache managers.
ISS.0017.0037E	Cannot shutdown a system cache manager.
Explanation	The cache manager you attempted to shutdown is a system cache manager. System cache managers are used by internal processes and cannot be modified.
Action	See Administering webMethods Integration Server for more information about system cache managers.
ISS.0017.0038E	Cannot reload a system cache manager.
Explanation	The cache manager you attempted to reload is a system cache manager. System cache managers are used by internal processes and cannot be modified.
Action	See Administering webMethods Integration Server for more information about system caches.

- ISS.0017.0039E** **Attempted to create cache manager {0} that connects to a Terracotta Server Array, but the Integration Server license does not allow it. Cannot save cache manager configuration.**
- Explanation** To use this feature, Integration Server must have a license that allows distributed caching.
- Action** Obtain the appropriate license from Software AG Global Support and add it to Integration Server.
-
- ISS.0017.0040I** **Successfully evicted expired elements from the cache {0} contained in cache manager {1}.**
-
- ISS.0017.0041I** **Cleared all caches starting with name {0} contained within the cache manager {1}.**
-
- ISS.0017.0042I** **Cleared all caches contained within the cache manager {0}.**
-
- ISS.0017.0043E** **Error occurred while clearing caches starting with name {0} contained within the cache manager {1}. Details:{2}**
- Explanation** The service cannot remove the element from the cache for the reason indicated in the message.
- Action** Take the appropriate action based on the details shown in the message.
-
- ISS.0017.0044E** **Error occurred while clearing caches contained within the cache manager {0}. Details:{1}**
- Explanation** The service did not clear the caches in the specified cache manager because of the specified error.
- Action** Take the appropriate action based on the details shown in the message.
-
- ISS.0017.0045I** **Added cache {0}.**
-
- ISS.0017.0046I** **Updated cache {0}.**
-
- ISS.0017.0047I** **Deleted cache {0}.**

ISS.0017.0048E	{0} is not a distributed cache. Integration Server cannot synchronize with the Terracotta Server Array.
Explanation	You can only synchronize distributed caches with a Terracotta Server Arrays.
Action	Set the Distributed option on all the caches you want to synchronize with the Terracotta Server Array.
ISS.0017.0049E	The {0} cache manager is not running. Start the cache manager to synchronize the cache with the Terracotta Server Array.
Explanation	You cannot synchronize caches against the Terracotta Server Array when the cache manager is not running.
Action	Start the cache manager and then synchronize the cache with the Terracotta Server Array.
ISS.0017.0050I	The configuration for the {0} cache has been synchronized with the Terracotta Server Array.
ISS.0017.0051I	Integration Server cannot evict expired elements for caches contained in a system cache manager.
ISS.0017.0052I	Integration Server cannot reload the {0} cache manager because it is not running.
ISS.0017.0053E	The {0} cache in {1} has a different local configuration than the configuration on the Terracotta Server Array. Integration Server is using the configuration from the Terracotta Server Array.
Explanation	The configuration of the local cache should match that of the associated Terracotta Server Array. If the local cache configuration does not match the configuration of the Terracotta Server Array, Integration Server ignores the local cache configuration and uses the configuration of the Terracotta Server Array.
Action	Configure the local cache to match the configuration of the Terracotta Server Array.
ISS.0017.0054I	Use Integration Server Administrator to synchronize mismatched cache configurations with the Terracotta Server Array.

ISS.0017.0055E **Integration Server has registered a cache manager, but the configuration file is not in the config/Caching directory. Integration Server cannot manage this configuration.**

Explanation Integration Server saved the configuration for a cache manager, but the configuration file is not in the IntegrationServer/config/Caching directory. If the configuration is valid, you can still use the cache manager, but you cannot use Integration Server Administrator to stop or start the cache manager or edit its configuration.

Action Copy the configuration file to the IntegrationServer/config/Caching directory and restart Integration Server.

ISS.0017.0056E **The {0} cache manager is shut down but there is no configuration file associated with it. Integration Server cannot restart this cache manager.**

Explanation The cache manager configuration file is not in the IntegrationServer/config/Caching directory.

Action Restore the missing configuration file to the IntegrationServer/config/Caching directory.

ISS.0017.0057E **The {0} cache manager is shut down but its corresponding configuration file ({1}) no longer exists. Integration Server cannot restart this cache manager.**

Explanation The cache manager configuration file is not in the IntegrationServer/config/Caching directory.

Action Restore the missing configuration file to the IntegrationServer/config/Caching directory.

ISS.0017.0058E **Integration Server cannot remove the Terracotta Server Array URLs for this cache manager because one or more of its caches are distributed. Clear the Distributed option on all the caches.**

Explanation Integration Server cannot remove Terracotta Server Array URLs if any of the caches contained in the cache manager are distributed.

Action Shut down the cache manager and then change the Terracotta Server Array URLs.

ISS.0017.0059E **Integration Server cannot modify the Terracotta Server Array URLs for a cache manager while it is running. Shut down the cache manager, then change the Terracotta Server Array URLs.**

Explanation Integration Server cannot modify the Terracotta Server Array URLs for a cache manager while it is running.

Action Shut down the cache manager and then change the Terracotta Server Array URLs.

ISS.0017.0060I	Updated cache manager {0}.
ISS.0017.0061I	Added cache manager {0}.
ISS.0017.0062E	Integration Server encountered an error while parsing {0}: {1}.
Explanation	The cache manager configuration file contains invalid syntax.
Action	Manually edit the cache manager configuration file so that it is syntactically correct.
ISS.0017.0063I	The current Terracotta license is not valid for the BigMemory settings configured for the {0} cache manager. To use the cache manager, either remove the BigMemory settings from the configuration file or obtain a valid Terracotta license for BigMemory.
ISS.0017.0064E	Deployment of cache manager {0} failed because of invalid license. Check the Integration Server log for details.
Explanation	Integration Server could not deploy the cache manager because the license for Integration Server or Terracotta is invalid.
Action	Acquire the correct license file for Terracotta, Integration Server, or both and then redeploy the cache manager.
ISS.0017.0065I	Reading cache manager configuration from file {0}.
ISS.0017.0066I	{0} is a system cache manager.
ISS.0017.0067I	Read cache manager {0} from file {1}.
ISS.0017.0068I	Integration Server is running in safe mode. Cache manager {0} not initialized.
ISS.0017.0069I	Initializing cache manager {0}.
ISS.0017.0070I	Cache manager {0} initialized.

- ISS.0017.0072I** **Shutting down cache manager {0}.**
- ISS.0017.0073I** **Cache manager {0} is shut down.**
- ISS.0017.0074I** **Shutting down cache managers.**
- ISS.0017.0075I** **Finished shutting down cache managers.**
- ISS.0017.0076E** **The value specified in the "Maximum Elements in Memory" field must be an integer no larger than 2147483647.**
- Explanation** An invalid value was specified in the Maximum Elements in Memory field.
- Action** Change the value to an integer no larger than 2147483647.
- ISS.0017.0077E** **Field cannot be changed while the cache manager is running: {0}**
- Explanation** The specified field cannot be modified while the cache manager is running.
- Action** Shut down the cache manager, and then update the field. To shut down the cache manager, open Integration Server Administrator and go to the Settings > Caching page, then click the "Shutdown" link for the cache's cache manager.
- ISS.0024.0001** **Could not initialize User Manager.**
- ISS.0024.0002** **Error occurred while initializing User Manager: Class {0} was not found in CLASSPATH.**
- ISS.0024.0003** **Error occurred while initializing User Manager: {0}**
- ISS.0024.0004** **Could not access User Manager**
- ISS.0024.0005E** **Could not read users.cnf (the file may be corrupt)**
- Explanation** Integration Server could not read user and group configuration information from the users.cnf file. The file might be corrupt.
- Action** Examine this file in the Integration Server /config directory. Ensure that the server has read access to it. If the file is corrupted, you might need to set up the users and/or groups again through the Integration Server Administrator.

ISS.0024.0006E	Could not write users.cnf (the file may be corrupt)
Explanation	Integration Server could not write user and group configuration information to the users.cnf file. The file might be corrupt.
Action	Examine this file in the Integration Server /config directory. Ensure that the server has write access to it. If the file is corrupted, you might need to set up the users and/or groups again through the Integration Server Administrator.
ISS.0024.0007	The JDBCPool {0} associated with Central Users JDBC function is not defined so the Central User Manager is not enabled
ISS.0024.0010	Central User Manager initialization failed with error : {0}
ISS.0024.0011	Not able to load the {0} Role/Group.
ISS.0024.0013	Integration Server cannot add group to ACL because the required parameter "{0}" is not supplied.
ISS.0024.0014	Integration Server cannot add group "{0}" to ACL "{1}" because ACL "{1}" is not defined.
ISS.0024.0015	Integration Server cannot add group "{0}" to ACL "{1}" because group "{0}" is not found.
ISS.0024.0018	Integration Server failed to add group "{0}" to ACL "{1}" because of exception: {2}.
ISS.0025.0009E	Integration Server could not initialize the cache manager. Stopping Integration Server initialization. Use the server log and error log to diagnose and correct the problem.
Explanation	This error occurs when Integration Server is configured to be in a cluster and cannot connect to the Terracotta Server Array (TSA). This could happen because the TSA URL in your cluster configuration is incorrect, the TSA is offline, or because there is a network problem.
Action	(1) Verify that the Terracotta Server Array is available and accepting connections. (2) If it is, start the server in safe mode by including the "-safeboot" argument in the command line. On the Settings > Clustering page of Integration Server Administrator, check that the Terracotta Server Array URL value is correct. (3) Make sure the network configuration of the host is correct and there are no problems with your network.

ISS.0025.0034U	Dispatcher could not be shutdown: {0}
Explanation	Integration Server encountered a serious internal error while shutting down.
Action	Contact Software AG Global Support.
ISS.0025.0035	Dispatcher could not be started: {0}
ISS.0025.0040I	FIPS mode initialized
Explanation	Integration Server is operating under Federal Information Processing Standards.
Action	No action is required.
ISS.0025.0041I	FIPS mode not initialized
Explanation	Integration Server is not operating under Federal Information Processing Standards.
Action	No action is required.
ISS.0025.0042S	FIPS mode could not be initialized. Shutting down server: {0}
Explanation	An error was encountered during initialization of FIPS mode operation.
Action	Contact Software AG Global Support. Be prepared to provide configuration information related to security provider and FIPS mode.
ISS.0025.0043S	Integration Server started in Safe Mode
Explanation	Integration Server is operating in safe mode either because it was started using the safeboot switch or because there were problems with the master password. When running in safe mode, Integration Server is not connected to any external resources, except the server's own external repository, and you cannot update any passwords. If it is a master password problem, there will be other messages logged that indicate that there was a master password problem.
Action	If you intended to start the Integration Server in safe mode, then no action is required. If the Integration Server automatically started in safe mode due to a master password problem, see the webMethods Integration Server Administrator documentation.
ISS.0025.0046	Monitoring API could not be initialized. JmsUrl = {0}. Value must be supplied for JmsUrl.

ISS.0025.0047	Monitoring API could not be initialized because of following exception. Check JMS Provider. {0}
ISS.0025.0048	Monitoring API could not be initialized. Check JMS Provider.
ISS.0025.0050	The JCE Unlimited Strength Jurisdiction Policy File was not found. Please install it.
ISS.0025.0053	Error encountered while disabling Monitoring API.
ISS.0025.0054	Fabric Agent initialization failed.
ISS.0025.0056	FIPS could not be initialized because the JCE Unlimited Strength Jurisdiction Policy File was not found. Shutting down Integration Server.
ISS.0025.0058	Error reading system level information: {0}
ISS.0025.0059W	Error initializing cluster node name: {0}
Explanation	The specified cluster node name is an empty node name.
Action	Specify a non-empty cluster node name.
ISS.0025.0060W	Falling back on the fully qualified domain name as the cluster node name, cluster node name is :{0}
Explanation	Integration Server is using the default cluster node name for the machine because the cluster node name is empty or not provided.
Action	No action is required.
ISS.0025.0061E	The logical name for the cluster node is not correct: {0}
Explanation	The name for the cluster node is not valid. The logical host name you specify must be unique within the cluster and cannot contain a semicolon (;).
Action	Specify a unique logical name to identify the Integration Server instance in the cluster.

ISS.0025.0062CC	Web services stack could not be initialized. Shutting down server: {0}
Explanation	Integration Server encountered an error while initializing the Web services stack. Typical reasons are: 1) Loading of axis2.xml file located in Integration Server_directory/config/wss or Integration Server_directory/config/wssClient/conf folders failed because the file has been modified. 2) Integration Server failed to initialize the policy manager for the Web service.
Action	If you have modified the axis2.xml file located in Integration Server_directory/config/wss or Integration Server_directory/config/wssClient/conf folders, make sure that the changes made are correct. For all other reasons, refer to the details listed in the error message and respond accordingly.
ISS.0025.0063E	EDA Manager initialization failed: {0}
Explanation	The EDA Manager did not initialize during Integration Server start up.
Action	Review the exception returned with the error message to determine why the EDA Manager did not initialize.
ISS.0025.0064E	EDA Manager initialized.
Explanation	The EDA Manager initialized successfully.
Action	No action required.
ISS.0025.0065W	Encountered an error while disabling listeners. Proceeding with server shutdown.
Explanation	An error occurred while shutting down Integration Server. If the logging level for logging facility 0025, Initialization, is set to Debug or higher, the server log will include a stack trace with more details about the error.
Action	No action is required. Integration Server will shut down as requested.
ISS.0025.0066W	Encountered an error while suspending triggers. Proceeding with server shutdown.
Explanation	An error occurred while shutting down Integration Server. If the logging level for logging facility "0025 Initialization" is set to Debug or higher, the server log will include a stack trace with more details about the error.
Action	No action is required. Integration Server will shut down as requested.

ISS.0026.0002E	Failure while loading service {0}: {1}
Explanation	Integration Server failed to install, enable, or reload the package because it could not load a service in the package into its namespace.
Action	Examine the error message to determine the problem service. Usually this error occurs when a Java service was not compiled before loading the package.
ISS.0026.0005	Flow service could not be registered with the server: folder.servicename may already exist.
ISS.0026.0006	Warning missing type name while loading service {0}
ISS.0026.0007	Warning missing type name in operation {0} while loading service {1}
ISS.0026.0008E	Error: Exception serializing Flow Service {0}
Explanation	Integration Server encountered an internal error with a flow service.
Action	Contact Software AG Global Support.
ISS.0026.0009E	Error: unknown flow operation type for node:{0} in file:{1}
Explanation	Integration Server encountered an internal error with a flow service.
Action	Contact Software AG Global Support.
ISS.0026.0010	Warning: {0} Operation with no body in service {1}
ISS.0026.0011	Warning: {0} Operation missing service name in {1}
ISS.0026.0012W	Warning: Flow Branch Operation must have switch name or use conditional labels in {0}
ISS.0026.0013	Warning: Flow Branch Operation cannot have switch name and use conditional labels in {0}

- ISS.0026.0014** **Warning: {0} Operation missing target path in {1}**
- ISS.0026.0015** **Warning: {0} Operation missing source path name in {1}**
- ISS.0026.0016** **Warning: Flow Map Delete Operation missing field name in {0}**
- ISS.0026.0017** **The HTTP URL alias could not be registered by the service {0}. "{1}" is already registered as an alias for the path: {2}**
- ISS.0026.9101E** **Missing flow.xml**
Explanation The flow.xml file does not exist. When a flow service is created, Integration Server creates a flow.xml file and a node.ndf file in the IntegrationServer\packages\packageName\ns\folderName directory that corresponds to the package and folder in which the flow service was created.
Action Contact Software AG Global Support.
- ISS.0026.9102E** **Read only {0}**
Explanation The flow.xml file cannot be updated because it is read-only.
Action Navigate to the directory of the flow.xml file and make it a writable file.
- ISS.0026.9103E** **Unable to write to flow.xml**
Explanation An exception occurred while writing to the flow.xml file.
Action Contact Software AG Global Support.
- ISS.0026.9104E** **Missing class {0}**
Explanation The specified Java class cannot be found. This error is returned by the JVM.
Action Contact Software AG Global Support.
- ISS.0026.9105E** **Method {0} is not defined with the proper signature**
Explanation The signature of the Java service does not have a return type of void.
Action Contact Software AG Global Support.

ISS.0026.9106E	No method {0} in class {1}
Explanation	The service is to be supported by a specific method in a class. However, the loaded class does not contain the specified method.
Action	Make sure the class contains the method that you want to use to support the service.
ISS.0026.9107E	Method {0} is unexpectedly null
Explanation	Method defined to support the invoked service is null.
Action	Contact Software AG Global Support.
ISS.0026.9108E	Unable to create service; Service name missing
Explanation	The service cannot be created because the service name is missing. Integration Server can only create and register services that have a name.
Action	Make sure to specify a name for the service.
ISS.0026.9109E	Already registered in {0}
Explanation	An identically named element already exists in another package. The fully qualified element name must be unique across Integration Server. Fully qualified element names use the format: folder.subfolder.subfolder:elementName
Action	Provide a different name for the element.
ISS.0026.9110E	{0} : Name already used by another service type in {1} package
Explanation	Integration Server cannot save or register the service because a service with that name already exists in the package.
Action	Specify a different name for the service.
ISS.0026.9111E	Unable to register service; Package {0} is not enabled
Explanation	An attempt was made to register a service in a disabled package. A service can be registered in an enabled package only.
Action	Enable the package and then attempt to register the service.
ISS.0026.9201E	Unknown service: {0}

ISS.0027.0001W	nCipher Hardware accelerator not available
Explanation	An error occurred while accessing the nCipher hardware.
Action	Turn the "0027 Server Configuration" logging facility up to TRACE on the Settings > Logging > Server Logger page of the Integration Server Administrator and try again. See the details of the error in the server log.
ISS.0028.0002	Packages directory missing or corrupted
ISS.0028.0003	Unable to copy the original package manifest file: {0}
ISS.0028.0006	Unable to load {0} package (possibly due to circular dependencies)
ISS.0028.0007	This package requires {0} package (Version {1}) to load
ISS.0028.0008	Warning! Loading package from backup manifest file
ISS.0028.0009	Unable to read manifest file for {0} package
ISS.0028.0010	Unknown service type ({0}) in {1} package
ISS.0028.0011	Unable to write package manifest file: {0}
ISS.0028.0013	Startup service exited with the following error: {0}
ISS.0028.0014	Startup service {1} was not found in {0} package
ISS.0028.0016	Shutdown service exited with the following error: {0}
ISS.0028.0017	Shutdown service {1} was not found in {0} package

ISS.0028.0018	Server could not update the node definition file. Changes to the package were not saved.
ISS.0028.0020	Unable to read node definition file
ISS.0028.0021	Server could not update the node subdirectory. Changes to the package were not saved.
ISS.0028.0022	Unable to locate class: {0}
ISS.0028.0023	Could not delete service
ISS.0028.0024	Invalid Package License key for Package: {0}
ISS.0028.0025	Unable to save Package Key for Package: {0}
ISS.0028.0026E	Invalid or corrupt namespace plug-in configuration found in {0} package
Explanation	Integration Server could not read plug-in configuration information from the nsplugins.cnf file associated with the indicated package.
Action	Contact Software AG Global Support.
ISS.0028.0027	Namespace plug-in type name {0} in package {1} conflicts with existing type
ISS.0028.0028	Cannot create namespace factory class {0} in package {1}: {2}
ISS.0028.0029	Namespace factory class invalid type {0} in package {1}
ISS.0028.0030	Error: Will not load deprecated service type ({0}) in service {1} in package {2}

- ISS.0028.0035** **Package {0} has failed to load.**
- ISS.0028.0036** **Document type {0} has failed to load. Duplicate Broker document type name {1} is also referenced by {2}**
- ISS.0028.0038** **Error loading {0} : Name already used by another item in package {1}**
- ISS.0028.0039E** **Failure while loading document type {0}: {1}**
Explanation Integration Server failed to load the document type into the namespace because another document type with the same name was already being loaded into the Integration Server namespace.
Action Examine the error message to determine the problem document types. Check both document types to make sure they have different names. If they have the same name and both need to be loaded into the namespace, rename one and try again.
- ISS.0028.0040E** **Failure while loading schema {0}: {1}**
Explanation Integration Server failed to load the schema into the namespace because another schema with the same name was already being loaded into the Integration Server namespace.
Action Examine the error message to determine the problem schemas. Check both schemas to make sure they have different names. If both need to be loaded into the namespace, rename one and try again.
- ISS.0028.0041E** **Failure while loading element {0}: {1}**
Explanation Integration Server failed to load the element into the namespace because another element with the same name was already being loaded into the Integration Server namespace.
Action Examine the error message to determine the problem elements. Check both elements to make sure they have different names. If both need to be loaded into the namespace, rename one and try again.
- ISS.0028.0043** **Error unregistering node {0}: {1}**

ISS.0028.0044W	Invalid classpath entry: {0}
Explanation	An I/O error occurred when Integration Server tried to access the file system to resolve the canonical name of the directory in which the file exists.
Action	Check the file system for errors, such as problems with permissions and cyclical links.
ISS.0028.0045E	Failed to install package {0}. Another package exists with the name {1}
Explanation	Integration Server was unable to install a package because a package with the same name already exists on the Integration Server.
Action	Rename one of the packages, either the existing package or the one you are trying to install. Note that case does not matter; Integration Server considers "ABC" the same name as "abc".
ISS.0028.0046E	Unable to load package replication passwords from {0}
Explanation	Integration Server encountered an error while loading the indicated class.
Action	Check the audit log for messages about the underlying cause of the exception.
ISS.0028.0047E	Unable to save package replication passwords to {0}
Explanation	Integration Server encountered an error while loading the indicated resource.
Action	Check the Audit log for messages about the underlying cause of the exception.
ISS.0028.0048	Failed to read class {0} from input stream
ISS.0028.0049	Unable to locate resource {0}
ISS.0028.0051E	Task Scheduler startup service exited with the following error: {0}
Explanation	Integration Server encountered an error while executing the scheduler startup service task.
Action	Contact Software AG Global Support.
ISS.0028.0052E	Task Scheduler startup service {1} was not found in {0} package
Explanation	The package startup process could not locate the service named in the message.
Action	Contact Software AG Global Support.

- ISS.0028.0055 **Caching of package classes is disabled due to the following error for file [{0}]: {1}**
- ISS.0028.0056 **The post-initialization startup service {0} threw an exception: {1}. See the error log for the full stack trace.**
- ISS.0028.0057 **Failure while registering HTTP URL alias "{0}" for the package {1}. Already registered as an alias for the path: {2}**
- ISS.0028.0058 **Failure while registering HTTP URL alias "{0}" for the package {1}. Already registered by package {2} as an alias for the path: {3}**
- ISS.0028.0059 **Failure while registering HTTP URL alias "{0}". Already registered as an alias for the path: {1}**
- ISS.0028.0060 **Failure while registering HTTP URL alias "{0}". Already registered by package {1} as an alias for the path: {2}**
- ISS.0028.0061E **Unable to load system package {0} due to dependency on non-system packages.**
Explanation Integration Server cannot load the specified system package because it depends on a non-system package. System packages are pre-defined packages that are part of the Integration Server product (for example, WmPublic). A system package can have dependencies on other system package(s) only.
Action Using Designer, edit the package dependencies for the specified system package to remove the dependency on the non-system package.
- ISS.0033.0001 **Inactive server {0} was removed from cluster {1}**
- ISS.0033.0100 **If any multicast setting is supplied (Discovery Address, Discovery Port, Time To Live), they must all be supplied.**
- ISS.0033.0103E **Could not open the session cache. {0}**
Explanation Integration Server encountered an internal error.
Action Contact Software AG Global Support.

ISS.0033.0104E	Could not add server to the cluster. {0}
Explanation	Integration Server failed to add a server to the cluster.
Action	Make sure that the server repository is running and that the connection to other servers is valid.
ISS.0033.0108	Could not remove server from cluster. {0}
ISS.0033.0114E	Failed to add server statistics to the cluster cache. {0}.
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISS.0033.0124E	Local Address
Explanation	Integration Server failed to remove expired sessions from the Repository. This is an internal error.
Action	Contact Software AG Global Support.
ISS.0033.0128	Unable to save settings to the server's configuration file.
ISS.0033.0143	Please restart the server to make the new settings take effect.
ISS.0033.0144	Changes not saved: {0} is required.
ISS.0033.0146	Evaluating host {0} to receive Session Document.
ISS.0033.0147	Register Session Document handler with host {0}.
ISS.0033.0148	Received unknown special document. Body = <<{0}>>.
ISS.0033.0149	Changes not saved. Invalid value. {0} must be an integer.

ISS.0033.0150 **Changes not saved. Invalid Well Known Address. If either host or port is supplied, both must be supplied. host={0}, port={1}.**

ISS.0033.0151U **The cluster is now not operational.**

Explanation During server startup, Integration Server detected a problem with its configuration that will prevent it from being part of a cluster.

Action Check the Clustering and Repository settings for your Integration Server. Refer to the webMethods Integration Server documentation for more information about clustering. If you cannot determine the cause of the problem, contact Software AG Global Support.

ISS.0033.0153E **Could not obtain a handle to ConnectionManager.**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISS.0033.0154E **Could not save session {0} to the session cache. {1}.**

Explanation Integration Server failed to persist the indicated session to the Repository. This is an internal error.

Action Contact Software AG Global Support.

ISS.0033.0155E **Could not create local session {0} from the cached session values. {1}.**

Explanation An Integration Server in a cluster tried to update a session object, but was unable to find it. This in an internal error.

Action Contact Software AG Global Support.

ISS.0033.0156E **Cluster Invoke did not complete successfully. Cluster Synchronization feature is not configured.**

Explanation After a trigger configuration update, Integration Server attempted to apply the change to other Integration Servers in the cluster, but was unable to. The most likely reason is that the Cluster Synchronization feature has not been properly configured.

Action Review the cluster synchronization for rriger management text in the webMethods Integration Server documentation for instructions on configuring your cluster to propagate trigger changes to other Integration Servers in the cluster.

ISS.0033.0159	The TSA URL must be specified on the Settings > Clustering page in order to join a cluster. Clustering has been disabled. This server is running in stand-alone mode.
ISS.0033.0161	CLUSTERING DISABLED: Could not create or join distributed clustering cache "{0}". This server is NOT a member of a cluster.
ISS.0033.0162	The Cluster Name can contain only the following characters: alphanumeric, dashes, underscores, and colons.
ISS.0033.0163	Cache configuration is invalid. Settings were not saved: {0}
ISS.0033.0164	The ISInternal functional alias on the JDBC Pools page must be configured to use an external database in order to enable clustering.
ISS.0033.0167	The ISInternal functional alias on the JDBC Pools page must be configured to use an external database in order to join a cluster. Clustering has been disabled. This server is running in stand-alone mode.
ISS.0033.0169	Logical cluster node name, {0}, is not valid.
Explanation	A cluster node name is either empty or null. Integration Server detects invalid cluster node names at server initialization or when someone attempts to pin a scheduled task to cluster node with an invalid name.
Action	Provide a non-empty cluster node name for the cluster node.
ISS.0033.0181I	Cluster name cannot contain any of these characters: ? [] / = + < > ; " , * ^ @
ISS.0033.0182I	Cluster name cannot start with a '.' or end with a space.
ISS.0033.0183I	Cluster name cannot be an operating system device name.
ISS.0033.0184I	Cluster name cannot be null or empty.

- ISS.0035.0002** **Initial log rotation interval could not be set: {0} ms in not valid**
- ISS.0035.0004** **watt.server.logRotateInterval is invalid ({0}). The default log rotation of {1} minutes will be used.**
- ISS.0036.0002E** **Errors occurred invoking URL {0}**
Explanation A client application using the Java API did one of the following:
- 1) Tried to invoke the indicated folder or service name, but specified the wrong folder/service name.
 - 2) Specified invalid certificates when setting up the SSL connection to the Integration Server.
- Action** Examine the error stack trace to determine which exception was thrown. If it is a MalformedURLException, check the folder/service name provided in the API call and make sure that you specified the fully qualified service name. If it is a CertificateException, an IOException, or an InvalidKeyException, check the certificates provided and make sure that they are valid.
- ISS.0036.0004** **Error occurred while pinging server: {0}**
- ISS.0036.0005** **Error occurred while disconnecting from server: {0}**
- ISS.0036.0009E** **Ping Failed to server: {0}**
Explanation A client application performed a periodic ping of a remote Integration Server. The ping resulted in an exception.
Action Verify that the remote Integration Server is up and running. In addition, verify that there is network connectivity between the two servers.
- ISS.0051.0002E** **Error: {0}**
Explanation Integration Server failed to add a port, remove a port, or edit an existing port because it could not save ports properties to <IntegrationServer_dir>/config/port.cnf.
Action Examine the port.cnf file to make sure that it is not corrupt and not Read-Only. If the file is corrupt, you may need to remove the file and restart Integration Server. After you do this, you can re-add ports to the Integration Server.

ISS.0051.0003	Port {0} already registered
ISS.0051.0005	Unable to unregister port {0}
ISS.0051.0008	Listener {0} was denied access to service {1}
ISS.0053.0002	Access denied for user {0} on port {1} from {2}.
ISS.0053.0003	Dispatch caught exception in run loop: {0}
ISS.0053.0005	Dispatch caught exception while trying to send response: {0}
ISS.0053.0006S	(tid={0}) Enterprise Gateway Server encountered the error "{1}" while handling a request from client "{2}" at request URL "{3}".
Explanation	Enterprise Gateway Server experienced an internal error while handling the request.
Action	If the issue persists, contact the system administrator.
ISS.0053.0008I	(tid={0}) Attempting to forward the request to the Internal Server again because the original attempt failed with exception "{1}". The retry count is {2} and the request URL is "{3}".
Explanation	Enterprise Gateway Server failed to transmit the client request to the Internal Server due to the indicated network exception. The server will automatically try to send the request again. If the retry attempts fail, the server will log a message and fail the client request.
Action	The action you take depends on the exception issued. Look at the exception message for specific information.
ISS.0053.0009W	(tid={0}) Enterprise Gateway Server encountered an I/O error while writing the Internal Server's response back to the client at "{1}". The request URL is "{2}".
Explanation	An input/output error occurred between Enterprise Gateway Server and the Internal Server.
Action	If the issue persists, contact the system administrator.

ISS.0053.0010E (tid={0}) Enterprise Gateway Server encountered error "{1}" while handling the request. The server is unable to retry the request at this time. The retry count is {2}.

Explanation Enterprise Gateway Server experienced an internal error while handling the request.

Action If the issue persists, contact the system administrator.

ISS.0053.0011W (tid={0}) Enterprise Gateway Server is stopping attempts to retry the request because the content length "{1}" of the retry request does not match the content length "{2}" of the original request. The retry count is {3}.

Explanation Enterprise Gateway Server could not complete the request for the reason indicated.

Action If the issue persists, contact the system administrator.

ISS.0053.0012S Access is denied for user "{0}" on port {1} from client "{2}" through Enterprise Gateway "{3}".

Explanation Incorrect credentials were specified while connecting to the Internal Server through the Enterprise Gateway.

Action Supply valid credentials.

ISS.0054.0002E CSRF attack detected. CSRF token is not present in the request URL: {0}

Explanation CSRF secure token is missing in the request URL, possibly due to a CSRF attack.

Action If the request is valid, provide a valid CSRF secure token for the request.

ISS.0055.0001E Critical Java Service error

Explanation Integration Server encountered a serious internal error.

Action Contact Software AG Global Support.

ISS.0055.0002 Service setup {0} uses old-style signature

ISS.0055.0003 Initialization of Java Service {0} failed due to error: {1}

ISS.0056.0001 No SMTP server set. Cannot deliver mail

ISS.0056.0002	No recipient specified. Cannot deliver mail
ISS.0056.0003	Unable to send mail. *{0}*
ISS.0056.0004	Invalid SMTP port specified {0}. SMTP logging turned off
ISS.0059.0001U	Interrupted {0}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISS.0070.0003W	Error encountered creating {0} listener on port {1}
Explanation	An error was encountered while creating a listener.
Action	See the exception message for details about the error.
ISS.0070.0004E	Failed to load configuration information
Explanation	An error occurred while creating a listener from the settings in a package's listeners.cnf file.
Action	Go to the Settings > Logging > Server Log page in the Integration Server Administrator and increase the logging level for the "0070 Listeners" logging facility to TRACE. Reload the package that has the affected port or restart Integration Server. If the problem recurs, capture the exception written to the server log and send it to Software AG Global Support. If you cannot connect to Integration Server because all ports are affected, contact Software AG Global Support and provide them with the listener.cnf file from the WmRoot package.
ISS.0070.0006E	Failed to save configuration information
Explanation	An error occurred while saving listener settings.
Action	Increase the logging level for the "0070 Listeners" logging facility to TRACE and try to save the listener settings again. If the problem recurs, capture the exception written to the server log and send it to Software AG Global Support.
ISS.0070.0008W	Failed to bootstrap listener {0}
Explanation	The listener could not be started from the settings in the listeners.cnf file in a package's config directory. This file may have been manually edited or corrupted.
Action	If you have a backup of the listeners.cnf file, restore it and reload the package or restart Integration Server.

ISS.0070.0013W	Failed to start listener {0}. The following error was encountered: {1}
Explanation	Could not start the listener.
Action	See error details in the message.
ISS.0070.0027E	An I/O or Socket exception has occurred on {0}
Explanation	An error occurred while listening on a port.
Action	See the exception message for details about the error.
ISS.0070.0030W	Duplicate alias {2} encountered creating {0} listener on port {1}
Explanation	When loading a package, Integration Server encountered a port alias that is the same as an existing port alias on Integration Server. The alias for a port must be unique across the Integration Server. Integration Server loads and enables the package but will not create the port with the duplicate alias.
Action	If you do not want the port created, you do not need to do anything. However, if you want the port to be created when the package is loaded, delete the existing port with that alias, create a new port that has the same properties as the just deleted port, and then reload the package containing the duplicate alias. Integration Server creates the port when the package is reloaded.
ISS.0070.9001E	Invalid global service {0}
Explanation	Invalid global service name provided for message processing. An e-mail listener was started. When the Integration Server tried to determine which service to use for message processing for this listener, the Integration Server detected a problem with the name of the service specified as the Global Service. The Global Service overrides the setting for the Default Service or the service specified in the e-mail message from the e-mail client. The problem could be that the service name is specified in the wrong case (service names are case sensitive) or that the specified service does not exist in the Integration Server's namespace.
Action	Examine the Global Service name provided. Make sure the name is in the correct case and that the service exists in the Integration Server's namespace.
ISS.0070.9002E	Invalid default service {0}
Explanation	An e-mail listener was started. When the Integration Server tried to determine which service to use for message processing for this listener, the Integration Server detected a problem with the name of the service specified as the Default Service. The Integration Server executes the Default Service if no service is specified in the e-mail message and no service is specified for the Global Service in the Email Client Configuration screen on the Integration Server Administrator. The problem could be that the service name is specified in the wrong case (service names are case-sensitive) or that the specified service does not exist in the Integration Server's namespace.
Action	Examine the Default Service name provided. Make sure the name is in the correct case and that the service exists in the Integration Server's namespace.

ISS.0070.9003	Enable failed: Could not log into account {0}@{1}
ISS.0070.9005	Must provide Server Host
ISS.0070.9006	Must provide Server Type
ISS.0070.9007	Must provide User Name
ISS.0070.9009	Error starting to listen: {0}
ISS.0070.9010	A number must be provided for the port
ISS.0070.9011E	An invalid port number was provided
Explanation	An administrator entered an invalid port number on a port configuration screen in the Integration Server Administrator.
Action	Specify a positive integer from 1 through 65534 for the port number.
ISS.0070.9012	A port number must be provided
ISS.0070.9013	Private key not specified
ISS.0070.9014	Private key file does not exist
ISS.0070.9015	Listener is not enabled
ISS.0070.9016	A listener must be provided
ISS.0070.9017	Could not process certificate {0}

ISS.0070.9018	Peer certificate chain is not present
ISS.0070.9019	Peer certificate is not in IS Certificate map
ISS.0070.9020	Peer certificate chain is not trusted
ISS.0070.9021	Invalid/unsupported listener type found, {0}
ISS.0070.9022	Invalid value for minimum threads, {0}
ISS.0070.9023	Invalid value for maximum threads, {0}
ISS.0070.9024	Invalid value for thread priority, {0}
ISS.0070.9025	Invalid min/max threads min={0} is greater than max={1}
ISS.0070.9026	Invalid thread priority {0}, minimum priority={1} and maximum priority={2}
ISS.0070.9027	Invalid port backlog queue value={0}
ISS.0070.9028	Invalid keep alive timeout value={0}
ISS.0070.9029	Invalid Enterprise Gateway internal port number {0}
ISS.0070.9030	Invalid port number {0}
ISS.0070.9031	Invalid maximum number of connections value {0}

ISS.0070.9039	Access denied to host : Hostname verification failed
ISS.0070.9040	Aborting connection, Server Certificate purpose verification failed
ISS.0070.9041	Key alias is empty. Specify a key alias for the port or a global SSL key alias on the Security > Certificates > Edit page.
Explanation	The port cannot be enabled because a key alias was not specified and there is not a default SSL key alias for the Integration Server.
Action	Before enabling the port, either define a key alias or specify a default SSL key alias for the Integration Server. The default SSL key alias is the keys alias specified during configuration of the SSL authentication credentials for the Integration Server. To use a defined key alias with the HTTPS port, specify that keystore alias in the create or update operation. To use the Integration Server's default SSL key alias with the HTTPS port, do not supply key alias information for the create or update operations.
ISS.0070.9042	Keystore alias is empty. Specify a keystore alias for the port or a global SSL keystore alias on the Security > Certificates > Edit page.
Explanation	The port cannot be enabled because a keystore alias was not specified and there is not a default SSL keystore alias for the Integration Server.
Action	Before enabling the port, either define a keystore alias or specify a default SSL keystore alias for the Integration Server. The default SSL keystore alias is the keystore alias specified during configuration of the SSL authentication credentials for the Integration Server. To use a defined keystore alias with a port, specify that keystore alias when creating or updating the port. To use the Integration Server's default SSL keystore alias with the port, do not supply keystore alias information when creating or updating the port.
ISS.0070.9043	Invalid keypair specified. Public and private keypair moduli don't match
ISS.0070.9044E	Unsupported key type: {0}. The HTTPS/FTPS listener supports RSA keys only. Specify a key store that contains the appropriate RSA private key.
Explanation	HTTPS or FTPS listener is configured with a keystore having DSA or EC key types. The HTTPS/ FTPS listener currently supports only RSA keys.
Action	Configure the HTTPS or FTPS listener to use a keystore that contains the RSA key.

ISS.0070.9046E	Invalid character/s found in host name, {0}, in IP Access Deny list.
Explanation	The specified host in the deny list contains one or more invalid characters.
Action	Correct the host name to remove the invalid characters. The host names or IP addresses can include upper and lower case alphabetic characters, digits (0-9), hyphens (-), and periods (.) and cannot include spaces. For IPv6, IP addresses can also include colons (:) and brackets ([])
ISS.0081.9183E	All binders must contain the same operations
Explanation	The binders in the Web service descriptor do not contain the same operations. In a service first provider Web service descriptor with multiple binders, the binders must contain the same operations.
Action	Modify the binders to contain the same operations.
ISS.0081.9184W	The web service descriptor does not contain any operations
Explanation	A provider Web service descriptor cannot be saved if it does not contain any operations.
Action	Add operations to the provider Web service descriptor.
ISS.0081.9185E	Cannot resolve operation {0} in binding {1}; operation does not have a unique SOAPAction or a unique first element name.
Explanation	The provider Web service descriptor could not be created because the operation in the specified binding does not have a unique SOAPAction value or the first part element in the operation's input message is not unique. If neither of these values are unique, Integration Server cannot match an incoming web service request with an operation.
Action	Modify the WSDL document so that operations within a binding have unique SOAPAction values or make sure operations with duplicate SOAPAction values have an input message in which the first part element is unique.
ISS.0081.9186W	Web service name will change from: {0} to: {1}
Explanation	Changing the value of the Pre-8.2 compatibility mode property for a provider Web service descriptor results in a change to the value of the name attribute in the wsdl:service element in the associated WSDL document. Web service descriptors that run in pre-8.2 compatibility mode use the local name of the Web service descriptor as the service name. Web service descriptors that do not run in pre-8.2 compatibility mode use the fully qualified name of the Web service descriptor as the service name.
	For example, suppose that a Web service descriptor has the fully qualified name folder.myFolder.myWebService. If the Web service descriptor runs in pre-8.2 compatibility mode, in the WSDL document, the value of the name attribute in the wsdl:service element is "myWebService". If the Web service descriptor does not run in pre-8.2 compatibility mode, in the WSDL document, the value of the name attribute in the wsdl:service element is "folder.myFolder.myWebService".

Action	Existing consumer Web service descriptors and Web service connectors created from an earlier version of the WSDL document are not affected by the service name change and will execute as expected. However, web service clients created on other platforms might be affected. If a web service client is affected by the name change, regenerate the client using the updated WSDL document.
ISS.0081.9191W	The fault has a message part "{0}" defined by the type "{1}". Message parts in a fault must be defined by the element attribute instead of the type attribute.
Explanation	The WSDL for the Web service descriptor contains a fault message part defined by the type attribute. To be deployed to the Web services stack in version 8.2 or later of Integration Server, the fault message part must be defined using the element attribute.
Action	To enable the WSDL for the Web service descriptor to be deployed to the Web services stack, modify the fault message part in the source WSDL used to create the Web service descriptor.
ISS.0081.9192W	WS Security Handler has no effect when the Pre-8.2 compatibility mode property is false. To enforce WS Security attach WS Policies.
Explanation	When a Web service descriptor is not running in pre-8.2 compatibility mode (i.e., the Pre-8.2 compatibility mode property is set to false), Integration Server does not execute the WS Security Handler. As a result, the WS Security Handler has no effect and WS Security will not be enforced.
Action	If you want to enforce WS Security, create the appropriate WS Policies and attach the WS Policies to the Web service descriptor.
ISS.0081.9193W	WS Policies has no effect when the Pre-8.2 compatibility mode property is true.
Explanation	When a Web service descriptor is running in pre-8.2 compatibility mode (i.e., the Pre-8.2 compatibility mode property is set to true), Integration Server does not enforce WS Policies attached to the Web service descriptor.
Action	If you want to enforce WS Policies (including those with WS-Security assertions), set the Pre-8.2 compatibility mode property to false. As an alternative, if you want to keep the Pre-8.2 compatibility mode property is set to true and still enforce WS Security policies, you can use the Integration Server WS Security facility. In this case, remove all WS Policies that you have attached to the Web service descriptor and attach the WS Security Handler. For more information about the WS Security Handler, see the Designer online help.

- ISS.0081.9205E** **JMS Binders are not supported when Pre-8.2 compatibility mode is true.**
- Explanation** One of the following situations occurred: the Pre-8.2 compatibility mode property was changed from false to true for a Web service descriptor that contains a binder with a Transport property set to JMS, a binder that specifies the JMS transport was added to a Web service descriptor that runs in compatibility mode (the Pre-8.2 compatibility mode property is set to true), or the Transport property for an existing binder was changed to JMS for a Web service descriptor that runs in compatibility mode. A Web service descriptor for which the Pre-8.2 compatibility mode property is set to true does not support binders with a JMS transport.
- Action** If you want to keep the JMS binder, change the Pre 8.2 compatibility mode property from true to false. If you want to keep the Web Service descriptor in Pre 8.2 compatibility mode, delete any binders using the JMS transport or change the binder Transport property to a supported transport (HTTP or HTTPS). Then, save the modified Web service descriptor.
-
- ISS.0084.0001E** **Invalid credentials**
- Explanation** Integration Server validates any credentials (username/password or certificates) that are supplied by the client, and if those credentials fail to match any user known to Integration Server, Integration Server will return this exception back to the client.
- Action** Supply the correct credentials.
-
- ISS.0084.9009W** **Warning: CSRF secure token is not present in the request. If you still want to complete this request, click Continue.**
- Explanation** CSRF token is missing in the request URL, possibly due to a CSRF attack.
- Action** If the request is valid, click Continue to complete the request.
-
- ISS.0084.9010E** **CSRF secure token is not present in the request.**
- Explanation** CSRF token is missing in the request URL, possibly due to a CSRF attack.
- Action** If the request is valid, provide a valid CSRF token for the request.
-
- ISS.0084.9101E** **Access Denied**
-
- ISS.0085.9208E** **Service first provider Web service descriptors cannot be refreshed.**
- Explanation** An attempt was made to refresh a service first provider Web service descriptor. Only WSDL first provider Web service descriptors and consumer Web service descriptors can be refreshed.
- Action** None.

ISS.0085.9209E	Cannot refresh Web service descriptor. The Web service descriptor cannot be found in the Integration Server namespace.
Explanation	A Web service descriptor cannot be refreshed because it does not exist in the Integration Server namespace.
Action	None.
ISS.0085.9211E	Cannot roll back Web service descriptor to previously saved version.
Explanation	An attempt to refresh a Web service descriptor failed. However, Integration Server could not roll back to the most recently saved version of the Web service descriptor and its associated assets. This can happen if Integration Server becomes unresponsive when rolling back the Web service descriptor.
Action	Delete the Web service descriptor and recreate it using the updated WSDL document. Note that any changes made to the Web service descriptor, such as new headers or faults, will be lost. Alternatively, if the Web service descriptor was checked into a version control system, check out the last checked in version of the Web service descriptor and then refresh the Web service descriptor
ISS.0085.9212E	Cannot Save the refreshed Web service descriptor. Integration Server will rollback to the most recently saved versions of the Web service descriptor and its associated assets.
Explanation	The WSDL file used to refresh the Web service descriptor contains or references an invalid schema.
Action	Use the information in the server log to determine why the schema is invalid. Correct the WSDL file or the associated XML Schema definition. Then, refresh the Web service descriptor.
ISS.0085.9213E	Cannot refresh Web service descriptor. One or more operations cannot be merged. Integration Server will roll back to the most recently saved versions of the Web service descriptor and its associated assets.
Explanation	As part of refreshing a Web service descriptor, Integration Server merges in changes made to existing services used as operations. One of the following can prevent Integration Server from merging the changes in successfully: - The contents or properties of an existing service could not be merged into the refreshed version of the service. - The ACL information could not be set for the refreshed service. - An existing service could not be locked. Integration Server will roll back to the most recently saved versions of the Web service descriptor and its associated assets.
Action	Contact Software AG Global Support. Obtain a copy of the server log before contacting support.

ISS.0085.9214W **The {0} docTypes folder contained one or more user-defined document types used for headers. These document types were deleted when the Web service descriptor was refreshed.**

Explanation The specified docTypes folder contains a document type used for a header in the Web service descriptor. This document type will be deleted upon refresh. When refreshing a Web service descriptor, Integration Server deletes the WSDName_docTypes folder and all elements contained in that folder and its subfolders. Integration Server will not recreate any assets manually added to the folder or its subfolders.

Action Do not add any assets to any of the folders created automatically by Integration Server for a Web service descriptor including the WSDName_doctypes folder. If you added any assets to the folders, move the assets to another folder before refreshing the Web service descriptor.

ISS.0085.9215W **The {0} docTypes folder contained one or more user-defined document types used for faults. These document types were deleted when the Web service descriptor was refreshed.**

Explanation The specified docTypes folder contained a document type used for a fault in the Web service descriptor. This document type will be deleted upon refresh. When refreshing a Web service descriptor, Integration Server deletes the WSDName_docTypes folder and all elements contained in that folder and its subfolders. Integration Server will not recreate any assets manually added to the folder or its subfolders.

Action Do not add any assets to any of the folders created automatically by Integration Server for a Web service descriptor including the WSDName_doctypes folder. If you added any assets to the folders, move the assets to another folder before refreshing the Web service descriptor.

ISS.0085.9262 **No registered handler found for Header QName:{0}**

Explanation The WSDL you are using to create the Web service connector has a header defined, but a matching header handler is not registered in Integration Server.

Action Add a header handler with a QNAME matching the Document Universal Name to Integration Server, then create the Web service connector. If you do not have the appropriate header handler, you can continue the process and Developer will create the Web service connector without the header information.

ISS.0085.9283 **Unknown ExtensibleElement "{0}" found in SOAPBinding "{1}"**

Explanation The WSDL used to create the Web service descriptor contains a binding element with a child other than SOAP 1.1 or SOAP 1.2. Integration Server does not support extensions to SOAP, such as sdk:binding (Microsoft SOAP-Toolkit extensions). Integration Server will process the valid portions of the SOAP 1.1 or SOAP 1.2 binding, but will skip processing of the unsupported extension.

Action Verify that the WSDL contains a valid SOAP 1.1 or SOAP 1.2 binding, and is usable without the extension.

ISS.0085.9315E	Binding {0} contains duplicate operation names {1}
Explanation	Web service descriptor cannot be generated. A binding in the WSDL document contains more than one operation with the same name.
Action	Modify the WSDL document so that operation names are unique within a binding.
ISS.0085.9317E	Error occurred during export of the package {0}. Details : {1}
Explanation	Integration Server could not export the package because an error occurred during export.
Action	Read through the details provided in the error message and take corrective steps.
ISS.0085.9318E	Invalid parameters passed. Make sure each required parameter is passed as an input to the service.
Explanation	Integration Server cannot export the assets because the required input parameters are not specified.
Action	Specify all the required parameters.
ISS.0085.9319E	Archive name passed "{0}" is invalid
Explanation	The name of the archive contains illegal characters.
Action	Remove all illegal characters from the archive name.
ISS.0085.9320E	Invalid service found; service {0} does not define any ports
Explanation	The WSDL document contains a wsdl:service element that does not define any ports. A Web service descriptor cannot be created.
Action	Modify the WSDL document to include ports in the wsdl:service element.
ISS.0085.9321E	Invalid port found; port {0} does not specify a binding
Explanation	The WSDL document contains a wsdl:port element that does not specify a binding. A Web service descriptor cannot be created.
Action	Modify the WSDL document to include a binding for the port.
ISS.0085.9322E	Invalid SOAP binding found; binding {0} does not contain all operations for corresponding portType {1}
Explanation	The specified binding does not contain all of the operations declared in the specified portType.
Action	Modify the WSDL document so that the binding contains all of the operations declared in the specified portType.

ISS.0085.9323W	Port alias for JMS Binder "{0}" set to "{1}". Ensure that this is the correct port alias.
Explanation	When creating a WSDL first provider Web service descriptor, Integration Server uses the first JMS provider web service endpoint alias listed on the Settings > Web Service Endpoints page in Integration Server Administrator as the port alias.
Action	If you want to use a different JMS provider web service endpoint alias as the port alias, select the JMS binder and assign a different port alias.
ISS.0085.9324E	Unable to create JMS Binder for binding {0}. There is not a defined JMS provider web service endpoint alias.
Explanation	When creating a WSDL first provider Web service descriptor, Integration Server uses the first JMS provider web service endpoint alias listed on the Settings > Web Service Endpoints page in Integration Server Administrator as the port alias. If there is no defined JMS provider web service endpoint alias, Integration Server does not create the Web service descriptor.
Action	Create a JMS provider web service endpoint alias. Then create the WSDL first provider Web service descriptor.
ISS.0085.9325E	Invalid parameter passed. {0} is a required parameter.
Explanation	Integration Server cannot export the assets because the required input parameters are not specified.
Action	Specify all of the required parameters.
ISS.0085.9326E	Error occurred while exporting runtime configurations: {0}. For more information, see the Integration Server logs.
Explanation	Deployer encountered an error while exporting runtime configurations: {0}.
Action	Check Integration Server log for more information.
ISS.0085.9327E,W	Unknown transport found in binding {0}. {1} is not a valid transport value.
Explanation	The WSDL document used as the source for the Web service descriptor contains a binding with an invalid transport attribute. Integration Server will not create a WSDL first provider Web service descriptor when a binding transport is invalid. Integration Server will create a consumer Web service descriptor when a binding transport is invalid if the WSDL document contains other valid bindings.
Action	No action is required.

ISS.0085.9328E,W	No transport found in binding {0}. Valid transport value is required.
Explanation	The WSDL document used as the source for the Web service descriptor contains a binding that does not specify a transport. Integration Server will not create a WSDL first provider Web service descriptor when a binding transport is missing. Integration Server will create a consumer Web service descriptor when a binding transport is missing if the WSDL document contains other valid bindings.
Action	If possible, determine the actual transport type and then edit the WSDL document to specify that transport for the specified binding.
ISS.0085.9329E,W	Unable to create JMS Binder for binding {0}. JMS Binders can be created using Designer only.
Explanation	The source WSDL document for the Web service descriptor contains a SOAP JMS binding. Developer cannot be used to create a WSDL first provider Web service descriptor from a WSDL document with a SOAP JMS binding. Developer can be used create a consumer Web service descriptor from a WSDL document with a SOAP JMS binding if the WSDL document contains other valid SOAP HTTP bindings, but the resulting consumer Web service descriptor will not have a JMS binder.
Action	Use Designer to create the Web service descriptor.
ISS.0085.9331E	Error occurred while deploying the asset: {0}. For more information, see the Integration Server logs.
Explanation	Integration Server encountered an error while deploying the asset. Typical reasons for this error are: 1) Stream is already read. 2) An I/O error occurred. 3) Value for aclData input parameter is not provided. 4) Any other error that occurred during deployment.
Action	Read through the details provided in the error message and take corrective steps.
ISS.0085.9333W	JVM: "{0}" of the target Integration Server for installing package: "{2}" is older than the recommended JVM: "{1}".
Explanation	The target Integration Server is running a JVM version that is older than the version recommended by the source package.
Action	Ensure that the target Integration Server is running the same or a later version of the JVM specified during release creation.
ISS.0085.9334E	The version of target package cannot be null for a patch release.
Explanation	The source package being installed is a patch release, but when the patch release was created, no version was specified for the target package.
Action	Specify a version for the target package when creating the patch release.

ISS.0085.9335W **The target Integration Server version "{2}" and the Integration Server version "{1}" recommended by source package "{0}" are incompatible.**

Explanation The target Integration Server version does not match the Integration Server version recommended by the source package.

Action Ensure that the version of the target and source Integration Servers are the same.

ISS.0085.9336W **Package "{2}" will not be deployed because the source package is a patch release and target package version: "{0}" does not match the required target package version: "{1}".**

Explanation During installation of a patch release, Integration Server detected that the version of the target package is not the version required by the patch release.

Action Install the correct version of the target package before applying the patch.

ISS.0085.9337W **Package "{0}" will not be deployed because the source package is a patch release and the target package does not exist.**

Explanation Integration Server could not install the package because the source package being installed is a patch release and the required package does not exist on the target server.

Action The following lists the actions you can take: 1) Install the package in the target server before applying the patch. -OR- 2) Redefine the source package to a full release before deploying the package on the target server.

ISS.0085.9338W **Package "{2}" will not be deployed because the version of source package: "{0}" is older than the version of target package: "{1}".**

Explanation The package installed in the target server is of a later version than the source package being installed.

Action Ensure that the version of the package on the target server is earlier than or the same as the package being installed.

ISS.0085.9341E **Recursive invoke of wm.server.util:remoteInvoke service on a local server is not allowed.**

Explanation You cannot invoke the wm.server.util:remoteInvoke service using the wm.server.util:remoteInvoke service recursively on a local server. Recursive invoke of wm.server.util:remoteInvoke service on a local server results in reduced thread availability and after sometime, Integration Server stops responding.

Action Make sure that you are not invoking the wm.server.util:remoteInvoke service recursively on a local server.

ISS.0085.9377E	Internal Error - Asset {0} does not exist
Explanation	While using the local service development feature in Software AG Designer, an attempt to move, copy, or rename an IS asset, such as a flow service, java service, document type, or trigger, resulted in an internal error occurred. At run time, the {0} in the message is replaced with the name of the IS asset being moved, copied, or renamed.
Action	Contact Software AG Global Support.
ISS.0085.9380E	Invalid folder name {0}. Error : {1}
Explanation	The specified folder name is invalid.
Action	Specify a valid folder name.
ISS.0085.9381E	Folder {0} is not empty
Explanation	The specified folder must be empty.
Action	Delete the contents of the specified folder or specify an empty folder.
ISS.0085.9382E	Message addressing endpoint alias "{0}" of type "{1}" does not exist.
Explanation	The specified message addressing endpoint alias does not exist.
Action	Ensure that the message addressing endpoint alias name that you specified is correct and that this endpoint alias exists.
ISS.0085.9383E	Cannot delete message addressing endpoint alias "{0}" because it is referred to by the following provider endpoint aliases {1}
Explanation	A Web service endpoint alias for a provider Web service descriptor is using the message addressing endpoint alias that you attempted to delete as a part of the Response Map. Integration Server can only delete a message addressing endpoint alias if it is not in use.
Action	Before deleting a message addressing endpoint alias, ensure that the endpoint alias is not associated with the Response Map of any provider Web service endpoint alias.
ISS.0085.9385E	Reliable messaging sequence {0} not found.
Explanation	No reliable messaging sequence for the specified internal Sequence Id was not found.
Action	Ensure that a valid Internal Sequence Id is specified.

ISS.0086.9063E	Missing required value: string
Explanation	The string parameter is required but is either missing from the pipeline or is null.
Action	Make sure the string parameter is being supplied to the service and that the value of string is not null.
ISS.0086.9287E	Applications cannot set the "{0}" field in the HTTP response header.
Explanation	The input to the pub.flow:setResponseHeader service specifies a header field that cannot be set by an application.
Action	Change the input to the pub.flow:setResponseHeader service so that it does not specify a header field that cannot be set by an application.
ISS.0086.9288E	Either "{0}" or "{1}" must be supplied
Explanation	A value is required for one of the two indicated parameters.
Action	Supply the missing value.
ISS.0086.9290E	Invalid JMS property name "{0}"; property name must contain only Java identifier part characters.
Explanation	The property name specified as input to pub.flow:setResponseHeaders does not meet the syntax requirement for JMS properties as described in the Java Message Service standard.
Action	Modify the property name to meet the syntax requirements for JMS properties. Refer to the Java Message Service standard for information about syntax requirements for message properties.
ISS.0086.9291E	Invalid JMS property name "{0}"; reserved word.
Explanation	The property name specified as input to pub.flow:setResponseHeaders contains a reserved word as described in the Java Message Service standard.
Action	Modify the property name by removing the reserved word. Refer to the Java Message Service standard for information about reserved words for message properties.
ISS.0086.9292E	Applications cannot set the "{0}" field in the JMS response header.
Explanation	The input to the pub.flow:setResponseHeader service specifies a message header field that cannot be set by an application.
Action	Change the input to the pub.flow:setResponseHeader service so that it does not specify a header field that cannot be set by an application.

ISS.0086.9293E	At least one of the parameters, "generateHeaderDocumentTypes", "generateBodyDocumentTypes" or "generateFaultDocumentTypes", must be set to true.
Explanation	The "generateHeaderDocumentTypes", "generateBodyDocumentTypes", and "generateFaultDocumentTypes" parameters are all set to false while executing the pub.soap.handler:generateDocumentTypesFromWSDL service.
Action	Set the value of any one of these parameters to true.
ISS.0086.9294E	If convertAllPackages is set to true, packageNames cannot be specified.
Explanation	When convertAllPackages is set to true, the pub.ws.utils:setCompatibilityModeFalse service sets the Pre-8.2 compatibility mode property to false for each Web service descriptor in an enabled package. It is invalid to specify individual packages in packageNames as well.
Action	Either remove the specified value for packageNames or set convertAllPackages to false.
ISS.0086.9295E	If convertAllPackages is set to false, packageNames must be specified.
Explanation	When convertAllPackages is set to false, the packageNames parameter must specify the names of the packages that contain the Web service descriptors for which to change the Pre-8.2 compatibility mode value.
Action	Either specify packages in packageNames or set convertAllPackages to true.
ISS.0086.9296E	Package {0} not enabled.
Explanation	The specified package is not enabled. The pub.ws.utils:setCompatibilityModeFalse service can change Web service descriptors in enabled packages only.
Action	Enable the package.
ISS.0086.9297E	Package {0} not found.
Explanation	The packageNames parameter specifies a package that does not exist.
Action	Ensure that the package name is spelled correctly. Additionally, verify that package exists on the Integration Server.
ISS.0086.9298E	Unable to lock Web service descriptor for editing.
Explanation	The Pre-8.2 compatibility mode property cannot be changed because an error occurred while attempting to lock the Web service descriptor for editing.
Action	Determine what error prevents locking of the Web service descriptor by examining the lock properties of the Web service descriptor or by attempting to lock (or check out) the Web service descriptor. Either action should provide a detailed error message that you can use to resolve the error. Then either run the pub.utils.ws:setCompatibilityModeFalse service again or lock (check out) the Web

service descriptor and change the value of the Pre-8.2 compatibility mode property manually.

ISS.0086.9299E

Web service descriptor is locked by another user.

Explanation

The Pre-8.2 compatibility mode property cannot be changed because another user has the Web service descriptor checked out or locked for editing.

Action

Review the lock properties of the Web service descriptor to determine which user has it checked out or locked for editing. After the user unlocks (or checks in) the Web service descriptor, either run the `pub.utils.ws:setCompatibilityModeFalse` service again or lock (check out) the Web service descriptor and change the value of the Pre-8.2 compatibility mode property manually.

ISS.0086.9309E

Could not release a lock of type {0} for key {1} in cache {2} contained within the cache manager {3}. Error:{4}

Explanation

The specified lock type for the specified key, cache, and cache manager does not match the actual lock type held. This error also occurs if a release lock is called from a thread that did not lock the key.

Action

Specify the correct lock type or invoke the service from the same thread that acquired the lock.

ISS.0086.9312E

Error while executing command {0}: {1}

Explanation

Integration Server encountered an error while executing the command. Typical reasons are: 1) The session is invalid. 2) The command parameter is invalid. 3) The SFTP server is not reachable.

Action

Read through the details provided in the error message and take corrective steps.

ISS.0086.9313E

Invalid session {0}

Explanation

The session key that you specified is invalid.

Action

Ensure that session key is correct and that the session corresponding to this session key exists.

ISS.0086.9314E

Session {0} expired.

Explanation

The session key that you specified has expired.

Action

Adjust the session timeout value for this SFTP user alias according to your requirements. Once a session expires, you must create a new session.

ISS.0086.9315E	Session {0} is in use. Integration Server does not support parallel command execution on a session.
Explanation	You attempted to execute commands in parallel.
Action	Integration Server does not support parallel command execution on a session. Ensure that you execute the commands sequentially.
ISS.0086.9316E	One or more required values are missing: {0}.
Explanation	You have not provided all the mandatory input parameters that Integration Server requires to execute the SFTP put command.
Action	Ensure that you provide all the input parameters to execute the SFTP put command. For example, to execute the put command, you have the option to provide a combination of contentStream and remote file name. Integration Server throws this error if you do not provide both the input parameters in this combination.
ISS.0086.9317E	Invalid mode: {0}.
Explanation	The mode that you specified to execute an SFTP command is invalid.
Action	Ensure that you specify a valid value for mode. Valid values are "OVERWRITE", "RESUME", and "APPEND".
ISS.0088.9108E	SOAP Handler {0} already registered
Explanation	While executing pub.soap.processor:registerProcessor, Integration Server could not register the custom SOAP message processor because the registry already has a SOAP message processor registered for the supplied directive.
Action	When registering a custom SOAP message processor using pub.soap.processor:registerProcessor, specify a directive for which there is not already a custom SOAP message processor. Alternatively, use pub.soap.processor:unregisterProcessor to unregister the custom SOAP message processor that is currently registered to the specified directive and then register the new SOAP message processor with that directive.
ISS.0088.9109	SOAP is only supported using HTTP POST protocol
Explanation	The SOAP message handler was not able to accept the request because the SOAP message was submitted to Integration Server using the HTTP GET method. The SOAP message handler only accepts requests via the POST method (per W3C specification).
Action	Modify the client to use HTTP POST to submit SOAP messages to Integration Server.

ISS.0088.9110E	Invalid BOOLEAN value {0} for variable {1}; must be 0 or 1
Explanation	The addHeaderEntry service failed because the mustUnderstand attribute was not set correctly.
Action	Check the logic in the process that failed to make sure that it sets the value of the specified variable to either 0 or 1. No other values are permitted when setting the mustUnderstand attribute.
ISS.0088.9111E	Cannot load or execute the SOAP processor {0}
Explanation	The SOAP message handler cannot process the SOAP message because the requested SOAP processor is non-operational.
Action	On the server, check the status of the service that is registered to directiveName. Make sure this service is loaded and operating successfully. (Frequently this error occurs because the processor was modified and then did not recompile successfully.)
ISS.0088.9112E	An Exception was thrown in the server:{0}
Explanation	Integration Server, the SOAP processor, or one of the services processing the message has thrown an exception.
Action	See the detail element in the SOAP fault to determine the exception that was thrown and which process it was thrown by.
ISS.0088.9113E	The SOAP Envelope does not have a Body block
Explanation	The SOAP client was given a soapRequestData that did not contain a body element.
Action	Examine the logic in the client to see whether it uses the stringToSoapData or streamToSoapData service to generate their SOAP objects. If so, determine whether the String or stream from which the SOAP object was generated represented a valid SOAP message. Also check whether the SOAP processor or client used any of the data removal utilities (such as removeHeaderEntry or removeBodyEntry) and might have inadvertently removed the entire Body element.
ISS.0088.9116]E	The server cannot execute the requested SOAP utility; required parameter {0} is missing or invalid
Explanation	The requested SOAP utility service failed to execute because a required parameter was not supplied.
Action	Check the logic in the SOAP processor or client to make sure that it passes the correct parameters to each SOAP utility service that it invokes.

ISS.0088.9117E	One or more header entries were not understood by the SOAP processor
Explanation	The SOAP processor has rejected the SOAP message because it cannot obey a mandatory header entry (a header entry whose mustUnderstand attribute is enabled).
ISS.0088.9118E	Parameter {0} must be a valid soapData
Explanation	The requested SOAP utility service failed to execute because the value supplied to the specified parameter s not a SOAP object.
Action	Examine the logic in the SOAP processor or client and make sure that it passes a SOAP object to the specified parameter.
ISS.0088.9119E	SOAP Processor did NOT return a valid SOAP Response
Explanation	The message handler did not receive a valid SOAP message from the SOAP processor.
Action	Examine the logic in the SOAP processor to make sure that it composes the SOAP response message correctly. For example, check to see whether it the processor uses the stringToSoapData or streamToSoapData services to generate soapResponseData. If so, determine whether the original String or stream represents a valid SOAP message. If the SOAP processor logic seems correct, contact Software AG Global Support. This would indicate a serious internal error.
ISS.0088.9120E	Parameter {0} is not one of the valid data types: {1}
Explanation	The requested SOAP utility failed to execute because the specified parameter did not have the correct data type. The exception message identifies the data type that is expected.
Action	Examine the logic in the SOAP processor or client and make sure that it passes an object of the specified data type to the specified parameter.
ISS.0088.9122E	Service {0} does not exist
Explanation	The SOAP facility could not complete the requested operation because it could not find the specified service. This error is issued by various SOAP processes (e.g., registering a SOAP processor, invoking a SOAP processor, invoking a target service).
Action	Examine the process that failed and make sure that it specifies the name of the requested service correctly. For example, if you receive this error when registering a SOAP processor, check that you have specified the svcName parameter correctly. Remember that service names are case-sensitive.

- ISS.0088.9123E Requested SOAP processor {0} is not registered on this server**
- Explanation** The Integration Server could not process the SOAP message because it does not have the SOAP processor requested by the client.
- Action** On the client side, verify that the correct process directive is specified in the URL (remember that the directive is case-sensitive). If the client has specified the process directive correctly, then use `pub.soap.processor:list` to verify that the requested processor is registered on the Integration Server.
-
- ISS.0088.9124E SOAP Message does not conform to the SOAP message model**
- Explanation** The SOAP message passed to the `validateSoapData` utility failed validation (for example, it is missing the Body element or the Header element follows the body).
- Action** Examine the logic that produced the message and see whether it uses the `stringToSoapData` or `streamToSoapData` service to manually generate a SOAP object instead of using the message composition services (e.g., `createSoapData`, `addHeaderEntry`, `addBodyEntry`). If so, determine whether the String or stream from which the SOAP object is generated represents a valid SOAP message. Also check whether the SOAP processor or client used any of the data removal utilities (such as `removeHeaderEntry` or `removeBodyEntry`) and might have inadvertently removed required portions of the SOAP object (for example, the entire Body element).
-
- ISS.0088.9125E SOAP request does not conform to the SOAP message model**
- Explanation** The SOAP message handler could not process the SOAP request because it violates the SOAP message schema (for example, it is missing the Body element or the Header element follows the body).
- Action** On the client side, correct the logic that builds the message to ensure that it produces a valid SOAP message.
-
- ISS.0088.9126E SOAP response does not conform to the SOAP message model**
- Explanation** The SOAP message handler could not return the SOAP response generated by a SOAP processor on the Integration Server because the message violates the SOAP message schema.
- Action** Examine the logic in the SOAP processor and see whether it uses the `stringToSoapData` or `streamToSoapData` service to generate a SOAP object. If so, determine whether the String or stream from which the SOAP object is generated represents a valid SOAP message. Examine the logic that produced the message and see whether it uses the `stringToSoapData` or `streamToSoapData` service to manually generate a SOAP object instead of using the message composition services (e.g., `createSoapData`, `addHeaderEntry`, `addBodyEntry`). If so, determine whether the String or stream from which the SOAP object is generated represents a valid SOAP message. Also check whether the SOAP processor or client used any of the data removal utilities (such as `removeHeaderEntry` or `removeBodyEntry`) and might have inadvertently removed required portions of the SOAP object (for example, the entire Body element).

ISS.0088.9127E	The server could not load the SOAP XML Validator
Explanation	The SOAP message handler encountered a serious internal error.
Action	Contact Software AG Global Support.
ISS.0088.9128E	Request is from namespace {0}, server requires namespace {1}
Explanation	The SOAP message handler could not process the message because the message is not from a version of SOAP that the Integration Server supports. Integration Server supports the version indicated in the exception message.
Action	From the client side, resubmit the message using a version of SOAP that Integration Server supports.
ISS.0088.9132E	Failed to register SOAP Handler {0}, illegal characters in directive name.
Explanation	Integration Server was not able to successfully register the SOAP processor, because directiveName contains characters that are not allowed in a directive name.
Action	Register the SOAP processor under a name that is composed only of letters, digits, or the characters <code>-_!~*'</code> .
ISS.0088.9133E	Error while encoding RPC output
Explanation	While encoding RPC output, an exception occurred which resulted in an Integration Server error.
Action	Use the underlying exception to help determine what caused the error.
ISS.0088.9134E	Exception occurred while processing the body of the message
Explanation	Integration Server, the SOAP processor, or one of the services processing the SOAP message has thrown an exception.
Action	See the detail element in the SOAP fault to determine the exception that was thrown and by which process it was thrown.
ISS.0088.9135E	A WMDocument Exception was thrown in the server, usually because an XML block was not well-formed
Explanation	The SOAP message handler, the soapHTTP service, or the soapRPC service has received a SOAP message that contains invalid XML.
Action	Check the process that submitted the SOAP message to the Integration Server and make sure that it is producing valid XML. This error usually occurs because of a basic error in the XML document, such as missing tags or overlapping elements.

ISS.0088.9137E	Invalid input parameter; {0} must be a Document (IData)
Explanation	The requested SOAP service failed to execute because the object passed into the specified parameter is not an IData object.
Action	Check the logic in the SOAP processor or client to make sure that it passes an IData into the specified parameter.
ISS.0088.9138E	Input parameters do not conform to targetInputSignature: {0}
Explanation	The pub.client:soapRPC service could not submit the remote procedure call because the input parameters did not pass the data-validation process.
Action	This error is thrown when a client supplies an invalid set of input parameters for a SOAP remote procedure call. Specifically, it indicates that the parameters submitted to pub.client:soapRPC in reqParms do not match the structure and constraints of the document type specified in targetInputSignature. Generally, you will want to code your client to detect this kind of error and take some type of corrective action when it occurs.
ISS.0088.9139E	Output parameters do not conform to targetOutputSignature: {0}
Explanation	The SOAP RPC client could not submit the remote procedure call because the output parameters returned by the remote server did not pass the data-validation process.
Action	This error is thrown when a client receives an invalid set of output parameters (results) from a SOAP remote procedure call. Specifically, it indicates that the parameters returned to pub.client:soapRPC in respParms do not match the structure and constraints of the document type specified in targetOutputSignature. Generally, you will want to code your client to detect this kind of error and take some type of corrective action when it occurs.
ISS.0088.9140E	Invalid target signature {0}, must be a Document Type
Explanation	The SOAP RPC client could not process the remote procedure call because it was not able to validate the input or output parameters associated with the request. The signature it was given for validation is not a document type.
Action	Examine the logic in the SOAP RPC client and make sure that the object it specifies in targetInputSignature and/or targetOutputSignature is a document type. That is, these parameters, if used, specify the fully qualified name of a document type that exists on Integration Server.
ISS.0088.9141E	Invalid target signature {0}, Document Type does not exist
Explanation	The SOAP RPC client could not process the remote procedure call because it was not able to validate the input or output parameters associated with the request. The specified document type does not exist on the Integration Server.
Action	Examine the logic in the SOAP RPC client and make sure that targetOutputSignature and/or targetOutputSignature are correctly specified. (Remember that the names of

document types are case sensitive.). Also verify that the specified document type exists on the server and the package in which it resides is loaded and enabled.

ISS.0088.9144	this SOAPEnvelope object already contains a valid SOAPHeader object
Explanation	An attempt was made to add a SOAPHeader object to the SOAPEnvelope of a SOAPMessage that already contains a SOAPHeader object.
Action	The SOAPEnvelope object may contain a maximum of one SOAP Header.
ISS.0088.9145E	this SOAPEnvelope object does not contain a valid SOAPHeader object
Explanation	An attempt was made to access the SOAPHeader object, but the SOAPEnvelope of the SOAPMessage does not contain a SOAPHeader object.
Action	Add a SOAPHeader object to the SOAPEnvelope before accessing it.
ISS.0088.9147E	this SOAPEnvelope object does not contain a valid SOAPBody object
Explanation	An attempt was made to access the SOAPBody object, but the SOAPEnvelope of the SOAPMessage does not contain a SOAPBody object.
Action	Add a SOAPBody object to the SOAPEnvelope before accessing it.
ISS.0088.9148E	Exception occurred while retrieving SOAPHeader object
Explanation	The specified exception occurred while attempting to access the SOAPHeader object.
Action	Correct the error and retry.
ISS.0088.9149E	Exception occurred while retrieving SOAPBody object
Explanation	The specified exception occurred while attempting to access the SOAPBody object.
Action	Correct the error and retry.
ISS.0088.9150E	Exception occurred while retrieving SOAPHeaderElement objects
Explanation	The specified exception occurred while attempting to access the SOAPHeaderElement object.
Action	Correct the error and retry.

ISS.0088.9151E	Exception occurred while retrieving SOAPBodyElement objects
Explanation	The specified exception occurred while attempting to access the SOAPBodyElement object.
Action	Correct the error and retry.
ISS.0088.9152E	The property {0} is unknown
Explanation	An attempt was made to either get or set a property of the specified SOAPMessage, but the property name is unknown. The only valid SOAPMessage property names are javax.xml.soap.WRITE_XML_DECLARATION and javax.xml.soap.CHARACTER_SET_ENCODING.
Action	Specify the name of a valid property.
ISS.0088.9153E	this SOAPMessage object already contains a valid Detail object
Explanation	An attempt was made to add a Detail object to the SOAPBody of this SOAPMessage, but the SOAPBody already contains a Detail object. The SOAPBody can contain one and only one Detail object.
Action	Remove the existing Detail object before adding the new one.
ISS.0088.9154	this SOAPMessage object already contains a valid Fault object
Explanation	An attempt was made to add a Fault object to the SOAPBody of this SOAPMessage, but the SOAPBody already contains a Fault object. The SOAPBody can contain one and only one Fault object.
Action	Remove the existing Fault object before adding the new one.
ISS.0088.9155E	this SOAPMessage does not contain a valid Envelope object
Explanation	The specified SOAPMessage does not contain a valid SOAPEnvelope object.
Action	Create a new SOAPMessage that contains a valid SOAPEnvelope object.
ISS.0088.9163E	Could not retrieve WSDL for service {0}, WSD not found.
Explanation	Integration Server could not retrieve the WSDL for the specified Web service descriptor because the specified Web service descriptor does not exist on Integration Server.
Action	Ensure that the specified Web service descriptor exists on Integration Server.

ISS.0088.9164E	Access to WSDescriptor {0} denied.
Explanation	The user is not authorized to access the specified Web service descriptor.
Action	Specify a username that is authorized to access the specified Web service descriptor.
ISS.0088.9166E	Binder not found for soapAction = {0}
Explanation	The Web service descriptor has more than one binder, with the same operation name. Developer cannot calculate a default soapAction attribute to identify the correct operation.
Action	Include a unique soapAction attribute in the SOAPAction HTTP Header for every request.
ISS.0088.9251E	JAX-RPC Handler failed to process the message
Explanation	The JAX-RPC handler was invoked to process the message. Either the handleRequest() or handleResponse() method returns false, indicating a failure.
Action	Check the webMethods Integration Server log for error messages generated by the JAX-RPC handler.
ISS.0088.9252E	An Exception has been caught: {0}
Explanation	An exception was caught while attempting to process a SOAP message.
Action	Correct the problem indicated by the exception message.
ISS.0088.9253E	Could not add "Text" element to "Reason" element, locale is null
Explanation	An attempt to add a Text element to the existing Reason element failed because the locale was not specified.
Action	Specify the locale when adding the Text element.
ISS.0088.9255I	This element's QName cannot be changed
Explanation	An attempt to change the QName of a SOAPEnvelope, SOAPBody, or SOAPHeader failed, because the QName cannot be changed.
Action	No action is required.
ISS.0088.9356E	One or more required Headers "{0}" are not present in the SOAP request.
Explanation	The SOAP request received by the provider does not contain one or more required headers. Note that Integration Server considers all headers defined in a Web service descriptor to be required.
Action	Determine why the SOAP request does not contain the required headers, which might involve contacting the client to determine why the client did not include the required headers in the request.

ISS.0088.9420E	Required parameter {0} is missing
Explanation	A required input parameter was not provided.
Action	Provide the required input parameter.
ISS.0088.9421E	The service {0} does not exist
Explanation	The specified service does not exist.
Action	Specify an existing service.
ISS.0088.9422E	Either parameter {0} or {1} must be provided
Explanation	The service requires either one of the specified parameters, but neither was provided.
Action	Provide one of the required parameters.
ISS.0088.9423E	Service handler {0} is already registered
Explanation	A service handler with that name is already registered.
Action	Specify a different name when registering the service handler.
ISS.0088.9425E	Error destroying service handler {0}. Error:{1}
Explanation	An error occurred while destroying the JAX-RPC handler.
Action	The destroy() method of the JAX-RPC Handler has thrown an error. Correct the error in destroy() method.
ISS.0088.9427E	Service handler {0} could not be unregistered. A service handler by that name is not registered
Explanation	A service handler with the provided name is not registered.
Action	Specify the name of a registered service handler.
ISS.0088.9428E	Service handler {0} could not be found. A service handler by that name is not registered
Explanation	The specified service handler could not be found because it is not registered.
Action	Provide the name of a registered service handler.

ISS.0088.9429E	Could not find service handler for header {0}:{1}
Explanation	The header QName does not correspond to a registered service handler.
Action	Verify that the QName of the header corresponds to a registered service handler or register a service handler for the provided QName.
ISS.0088.9430E	Handler processing failed on the provider
Explanation	A handler service failed on the provider.
Action	Examine the handler services for errors and correct any errors that are found.
ISS.0088.9431E	Handler processing failed on the consumer: {0}
Explanation	A handler service failed on the consumer.
Action	Examine the handler services for errors and correct any errors that are found.
ISS.0088.9443E	One or more required Headers "{0}" are not present in the SOAP response.
Explanation	The SOAP response received by the Web service connector does not contain one or more required headers. That is, the SOAP response does not contain a header with a QName that matches the QName of a header defined in the consumer Web service descriptor. Note that Integration Server consider all headers defined in a Web service descriptor to be required.
Action	Determine why the SOAP response does not contain the required headers, which might involve contacting the provider to determine why the provider did not include the required headers in the response.
ISS.0092.9045E	A WS-I compliant Web Service Descriptor cannot contain a header or fault with a different namespace. Source: {0}
ISS.0092.9101E	Cannot specify both 'element' and 'type'.
ISS.0092.9102E	{0}: not a valid web service description document
ISS.0092.9103E	{0}: invalid file, unable to parse root element

- ISS.0092.9105E **Cannot find the specified Document Type or input/output parameter.**
- ISS.0092.9106E **Field {0} is multi-dimensional which cannot be converted to xsd without using SOAP_ARRAY**
- ISS.0092.9107E **Port {0} is missing required extended element.**
- ISS.0092.9108E **SimpleType {0} does not have base type.**
- ISS.0092.9109E **The system cannot find {0}**
- ISS.0092.9111E **Element must be a document type, service, or specification**
- ISS.0092.9112E **The service does not have a valid signature**
- ISS.0092.9113E **Unknown ExtensibleElement "{0}"**
- ISS.0092.9114E **Invalid WSDL; 'arrayType' attribute value {0} is malformed. Invalid QName {1}**
- ISS.0092.9115E **Invalid WSDL; 'arrayType' attribute value {0} is malformed. It should contain characters '[' and ']'**
- ISS.0092.9116E **Invalid WSDL; 'arrayType' attribute value {0} is malformed. Invalid rank size {1}**
- ISS.0094.0001E **Repository Exception: {0}**
- Explanation** During initialization, Integration Server could not initialize the Repository Manager. The most likely reason is that the repository4.cnf file is corrupted.
- Action** Check the directory that contains the repository files. By default, they are located at <IntegrationServer_dir>\WmRepository4\ directory. Try renaming the repository4.cnf file manually (to something like "damagedrepository4.cnf") or deleting it, then try re-initializing Integration Server. If that does not work, contact Software AG Global Support.

ISS.0094.0003E	RepositoryManager detected damaged data files : {0}
Explanation	During initialization, Integration Server detected that some of the data files that make up the repository were corrupted. In a recovery attempt, Integration Server tried to open the files, but was unable to.
Action	Check the directory that contains the data files. By default, the data files are located at <IntegrationServer_dir>\WmRepository4\ directory. You can also look in the repository4.cnf file for the location of the data files. Try manually renaming the files (to something like "damagedFSDData00000000") or deleting them, then try re-initializing Integration Server. If that does not work, contact Software AG Global Support.
ISS.0094.0004E	RepositoryManager Exception renaming damaged data files : {0}
Explanation	During initialization, Integration Server detected that some of the data files that make up the repository were corrupted. In an attempt to correct the problem, Integration Server tried to rename the damaged files before creating new ones but encountered an exception when trying to rename the damaged files.
Action	Check the directory that contains the data files. By default, the data files are located at <IntegrationServer_dir>\WmRepository4\ directory. You can also look in the repository4.cnf file for the location of the data files. Try manually renaming the files (to something like "damagedFSDData00000000") or deleting them, then try re-initializing Integration Server. If that does not work, contact Software AG Global Support.
ISS.0094.0006E	RepositoryManager Exception creating new data files : {0}
Explanation	During initialization, Integration Server detected that some of the data files that make up the repository were corrupted. In an attempt to correct the problem, Integration Server renamed the damaged files and tried to create new ones but encountered an exception when trying to create new files. Possible reasons for the problem are that the file system does not have enough space for the data files or that Integration Server does not have write access to the directory that contains the files.
Action	Check the directory that contains the data files. By default, the data files are located at <IntegrationServer_dir>\WmRepository4\ directory. You can also look in the repository4.cnf file for the location of the data files. Make sure the file system has space for the files and that Integration Server has write access to the directory.
ISS.0095.0006E	AuditLogManager: Exception auditing start of service {0}: {1}
Explanation	An error was encountered while audit logging the start of a service invocation.
Action	Set the logging level of the "0095 Audit Log Manager" logging facility to TRACE on the Settings > Logging > Server Logger page of the Integration Server Administrator. If the error recurs, see the error details in the server log.

- ISS.0095.0007E AuditLogManager: Exception auditing end of service {0}: {1}**
Explanation An error was encountered while audit logging the start of a service invocation.
Action Set the logging level of the "0095 Audit Log Manager" logging facility to TRACE on the Settings > Logging > Server Logger page of the Integration Server Administrator. If the error recurs, see the error details in the server log.
- ISS.0095.0008E AuditLogManager: Exception auditing error for service {0}: {1}**
Explanation An error was encountered while audit logging a service invocation.
Action Set the logging level of the "0095 Audit Log Manager" logging facility to TRACE on the Settings > Logging > Server Logger page of the Integration Server Administrator. If the error recurs, see the error details in the server log.
- ISS.0095.0009E AuditLogManager: Audit runtime interface object cannot be initialized: {0}**
Explanation The Integration Server Audit Log Manager encountered an internal error.
Action Contact Software AG Global Support.
- ISS.0095.0010E AuditLogManager Runtime Exception: {0} publishing log entry {1}. {2}**
Explanation An error was encountered while audit logging a service error.
Action See the detailed error message and stack trace that follow. If audit logging to a database, you may have to work with your DBA to diagnose a database problem.
- ISS.0095.0014E Audit Logging initialized with errors.**
Explanation An error was encountered while starting the audit logging facility.
Action Set the logging level of the "0095 Audit Log Manager" logging facility to TRACE on the Settings > Logging > Server Logger page of the Integration Server Administrator. If the error recurs, contact Software AG Global Support and provide them with the server log.
- ISS.0095.0015W Database at URI {0} is not available.**
Explanation An audit logger is configured to write log messages to a database, but the database is not available.
Action Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the ISCoreAudit functional alias is correct. For process auditing, check the ProcessAudit functional alias. Use the Test button to check that Integration Server can reach the configured database.

ISS.0095.0016W	Changing destination of queue {0} from database {1} to file system {2}.
Explanation	An asynchronous audit logger is configured to write log messages to a database, but the database is not available. The audit logger is being reconfigured to write audit messages to the file system.
Action	Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the ISCoreAudit functional alias is correct. For process auditing, check the ProcessAudit functional alias. Use the Test button to check that Integration Server can reach the configured database.
ISS.0095.0017W	Changing destination of logger {0} from database {1} to file system {2}.
Explanation	A synchronous audit logger is configured to write log messages to a database, but the database is not available. The audit logger is being reconfigured to write audit messages to the file system.
Action	Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the ISCoreAudit functional alias is correct. For process auditing, check the ProcessAudit functional alias. Use the Test button to check that Integration Server can reach the configured database.
ISS.0095.0018W	Cannot change destination of logger {0} to file system.
Explanation	An audit logger is configured to write log messages to a database, but the database is not available. It is not possible to write messages for this audit logger to the file system because the messages contain binary data. This audit logger is being disabled.
Action	Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the ISCoreAudit functional alias is correct. For process auditing, check the ProcessAudit functional alias. Use the Test button to check that Integration Server can reach the configured database.
ISS.0095.0019W	Disabling the logger {0}.
Explanation	The audit logger is being disabled. This is probably happening because the logger's database is not available.
Action	Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the ISCoreAudit functional alias is correct. For process auditing, check the ProcessAudit functional alias. Use the Test button to check that Integration Server can reach the configured database.
ISS.0095.0020W	Audit Logging Initialization: The {0} JDBC Pool Alias was not configured with enough connections. The Maximum Connections have been increased to {1}.
Explanation	The auditing system needed more database connections than were provided in the JDBC Pools configuration. The configuration was changed as needed.
Action	No action is required.

ISS.0095.0021E ERROR: Audit Logging Initialization: The {0} JDBC Pool Alias was not configured with enough connections. Unable to automatically increase the Maximum Connections setting.

Explanation The auditing system needed more database connections than were provided in the JDBC Pools configuration. An attempt was made to automatically increase the number of connections, but it failed.

Action Go to the Settings > JDBC Pools page of the Integration Server Administrator and increase the Max Connections setting for the ISCoreAudit functional alias. Restart Integration Server.

ISS.0095.0022W Audit Logging Initialization: Unable to verify the Max Connections setting for the Audit Logging database.

Explanation Integration Server encountered an error while checking the Max Connection setting for the ISCoreAudit functional alias.

Action If the auditing system is slow or unresponsive, go to the Settings > JDBC Pools page of the Integration Server Administrator and increase the Max Connections setting for the ISCoreAudit functional alias.

ISS.0095.0024W The value for watt.server.audit.logDir has been changed and does not identify an existing directory that Integration Server can write to. File-based audit logs will continue to be written to the {0} directory.

Explanation The audit log directory was not changed because the watt.server.audit.logDir parameter refers to a directory that either does not exist or Integration Server does not have permission to write to. As a result, Integration Server will write file-based audit logs to the last valid directory specified.

Action Go to the Settings > Extended page in the Integration Server Administrator and change the value for the watt.server.audit.logDir parameter. Specify a directory that exists on the server and that Integration Server can write to. You can specify the full path name, or a relative path in relation to the Integration Server.

ISS.0095.9998E AuditLogManager Exception: {0} {1}

Explanation An error was encountered using the audit logging database.

Action Try logging again. It may be a transient error. If the error persists, examine the detailed message and stack trace that follow. You may need to work with your DBA to diagnose a problem with the audit logging database.

ISS.0096.0001E	JDBCConnectionManager: initialization failed for {0} functional alias, check configuration.
Explanation	Unable to initialize the functional alias. Integration Server will not be able to connect to the database for this functional alias.
Action	Go to the Settings > JDBC Pools page of the Integration Server Administrator and verify that the functional alias settings are correct. Use the Test button to check that Integration Server can reach the configured database.
ISS.0096.0002W	JDBCConnectionManager: creating Embedded Pool Alias for {0}.
Explanation	The connection pool for the embedded database is being created.
Action	No action is required.
ISS.0096.0004E	JDBCConnectionManager: embedded database objects not created: {0}
Explanation	Unable to create tables, keys, or other database objects while initializing the embedded database.
Action	Verify that Integration Server has write access to the file system. If the problem persists, contact Software AG Global Support.
ISS.0096.0005E	JDBCConnectionManager: initialization failed with exception {0}
Explanation	Initialization of the JDBC Connection Manager failed.
Action	Contact Software AG Global Support.
ISS.0097.0004E	Failed to lock Repository entry {0}
Explanation	Integration Server encountered an internal error when trying to lock the repository.
Action	If the error continues, contact Software AG Global Support.
ISS.0097.0006I	Messaging synchronizer shutdown
Explanation	The Broker Synchronizer has shut down.
Action	No action is required. This message is displayed when Integration Server is shutting down.
ISS.0097.0012E	Messaging Synchronizer cannot open repository for sync-state storage
Explanation	An error was encountered while trying to open WmRepository4.
Action	Contact Software AG Global Support.

ISS.0097.0013E	Messaging Synchronizer cannot update sync state; cannot remove sync data from repository: {0}
Explanation	An error occurred while removing sync state data from WmRepository4.
Action	Contact Software AG Global Support.
ISS.0097.0014E	Messaging Synchronizer cannot update sync state; document type not specified
Explanation	The document type to be synchronized was not specified; the nsName input variable is null.
Action	Specify a document type name for nsName.
ISS.0097.0015D	Messaging Synchronizer cannot update sync state; document type {0} has no sync state
Explanation	The requested document type has no sync state.
Action	No action is required.
ISS.0097.0016E	Messaging Synchronizer cannot perform sync; Integration Server cannot connect to provider
Explanation	Synchronization cannot occur because Integration Server cannot connect to the message provider.
Action	Make sure the message provider is running and that the message connection alias is enabled in Integration Server Administrator.
ISS.0098.0003U	Exception occurred while decoding Broker Document {0} : {1}
Explanation	Integration Server failed to decode the document received from the Broker. The document may be corrupt.
Action	Check the publisher of the document. Consider redelivering the document from the Broker.
ISS.0098.0010U	Exception initializing Dispatcher configuration from file: {0}
Explanation	Integration Server encountered the indicated exception while trying to initialize the Dispatcher. This is a serious internal error.
Action	Contact Software AG Global Support.

ISS.0098.0023E	Document Router for Consumer Queue:{0} encountered error: {1}
Explanation	Integration Server encountered an error while routing a document to a Broker.
Action	The action to take depends on the exception that occurred. Review the returned exception for more guidance.
ISS.0098.0024U	No Trigger available for incoming Document {0}. Rejecting Document
Explanation	Integration Server failed to deliver the incoming document to the trigger because there is not a trigger that subscribes to the document. The intended trigger may be disabled or deleted.
Action	Examine the existing triggers. If a trigger that subscribes to the document is disabled, enable it and ask the publisher to re-publish or deliver the document.
ISS.0098.0025E	Document {0} from store {1} exceeded Redelivery Count.
ISS.0098.0029U	Exception while doing Request Reply: {0}
Explanation	Integration Server encountered an internal error while executing a request reply.
Action	Contact Software AG Global Support.
ISS.0098.0030E	{0} received duplicate document(s). Error {1}
Explanation	Integration Server determined that it received duplicate documents from a publisher.
Action	If you determine that the Integration Server did receive duplicate messages, check the publishing source to learn the source of the problem. In some cases, Integration Server did not really receive duplicates. For example, two documents might use the same tracking ID but have different content. If Integration Server did not receive a duplicate document, try resubmitting the document using webMethods Monitor.
ISS.0098.0031E	Consumer:{0} unable to persist Document(s) to Document Store. Error: {1}
Explanation	Integration Server failed to write a document to the transient store. A likely cause is that the Integration Server JVM has run out of memory.
Action	Try increasing the heap size. The heap size indicates how much memory is allotted for server processes. To edit the heap size, shut down the server, and open the server.bat or server.sh using a text editor. Set JAVA_MIN_MEM to the minimum heap size and set JAVA_MAX_MEM to the maximum heap size. By default, the minimum heap size is 128MB and the maximum heap is 256MB. Your capacity planning and performance analysis should indicate whether you need to set higher maximum and minimum heap size values.

ISS.0098.0033E **Error while shutting down Dispatcher: {0}**

Explanation Integration Server encountered an internal error.

Action Contact Software AG Global Support.

ISS.0098.0036U **{0} encountered Transport Exception: {1}**

Explanation Integration Server failed to publish the document because of one of the following:

- 1) The Broker is temporarily unavailable.
- 2) The client does not have the canPublish permission for its associate Broker document.
- 3) The document being published does not conform to the Broker document on the Broker. This may be because the document was not synchronized with the one on the Broker.
- 4) An internal error occurred.

Action Do one of the following:

- 1) Check the Broker status. If the Broker or network connection is temporarily down, wait until they are up to re-publish the document.
- 2) Using the Broker administration tool, check the publication permissions of the client group to which the trigger client belongs. Make sure that the client is allowed to publish the document.
- 3) Synchronize the document and make sure that the document being published matches its associate Broker document type.
- 4) If the previous actions fail to correct the problem, contact Software AG Global Support.

ISS.0098.0038E **{0} handling invalid Document. Exception: {1}**

Explanation Integration Server encountered an error while processing a document. Specifically, the document does not have a corresponding publishable document type on the Integration Server or the publishable document type does not have a matching schema.

Action Make sure that the appropriate document types and schemas for the document exist on the Integration Server.

ISS.0098.0041E	Unable to connect to Broker. Starting to poll
ISS.0098.0044U	Exception while interacting with the Document Store name:{0} Problem:{1}
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISS.0098.0045U	Unrecoverable Exception while initializing the Dispatcher: {0}
Explanation	Integration Server encountered the indicated exception while trying to initialize the Dispatcher. This is an internal error.
Action	Contact Software AG Global Support.
ISS.0098.0047E	Connection to Broker unavailable. Unable to create transport for Trigger:{0}.
ISS.0098.0048U	Unable to remove subscription for Publishable Document {0} from transport:{1}. If connected, please remove subscription from {2} manually.
Explanation	Integration Server failed to remove the document type subscription before unregistering the trigger. The Broker may be unavailable.
Action	In the Broker Administrator, check the status of the Broker and the network connection. If one or both are down, then you will need to manually remove the stale subscriptions for the trigger when they are back up.
ISS.0098.0049U	Exception:{0} while executing trigger. {1} Document for TriggerStore:{2}.
Explanation	Integration Server failed to execute the trigger. This indicates an internal error.
Action	Contact Software AG Global Support.
ISS.0098.0055U	Exception during attempt to register Trigger: {0}
Explanation	Integration Server failed to register the trigger. This indicates an internal error.
Action	Contact Software AG Global Support.
ISS.0098.0056U	Unable to acknowledge Document {0} to transport for Trigger {1}. Exception:{2}
Explanation	Integration Server encountered an internal error while acknowledging the document to the transport for the trigger.
Action	Contact Software AG Global Support.

ISS.0098.0057U	Unable to delete Document Store for Trigger:{0}. Exception:{1}
Explanation	Integration Server encountered an internal error while deleting the document store associated with the trigger.
Action	Contact Software AG Global Support.
ISS.0098.0058E	Stopping delivery of {1} to trigger {0} to prevent infinite loop.
ISS.0098.0059U	Exception while shutting down the Document Stores:{0}.
Explanation	Integration Server encountered a serious internal error while shutting down.
Action	Contact Software AG Global Support.
ISS.0098.0060U	Exception while saving Dispatcher configuration :{0}.
Explanation	Integration Server encountered an exception while trying to save Dispatcher configuration information to the dispatch.cnf file in the <IntegrationServer_dir>/config directory.
Action	If the dispatch.cnf file is set to read-only, change it to read/write. If the file is not set to read-only, this error indicates a serious internal error and you should contact Software AG Global Support.
ISS.0098.0062E	{0} encountered Exception: {1}
ISS.0098.0073U	ControlledPublishOnSuccess max exceeded while processing {0}
Explanation	Integration Server failed to publish a document because the maximum concurrent publish-on-success value was exceeded.
Action	Do one of the following: 1) On the Integration Server, increase the "concurrent publish on success" setting by editing the "watt.server.control.maxPublishOnSuccess" property. 2) Decrease the number of concurrent publish operations in the service.
ISS.0098.0074E	Outbound msg store max exceeded, services blocking. Start broker to drain store.

ISS.0098.0075E	Insufficient memory while decoding event:{0} for {1}.
Explanation	Integration Server does not have sufficient memory to decode the documents being retrieved from the Broker. Integration Server will attempt to decode the documents one more time.
Action	Check the size of the documents sent by the Broker and consider increasing the heap size of the Integration Server's JVM. You can view the heap size by editing the <IntegrationServer_dir>\bin\server.bat file (on Windows systems) or <IntegrationServer_dir>\bin\server.sh file (on Unix systems).
ISS.0098.0076U	Unable to decode events for {0}. Please check JVM Heap size and/or size of Documents on the Broker.
Explanation	Integration Server does not have sufficient memory to decode the documents from the Broker.
Action	Check the document size sent by the Broker and consider increasing the heap size of the JVM used by Integration Server. You can view the heap size by editing the <IntegrationServer_dir>\bin\server.bat file (on Windows systems) or <IntegrationServer_dir>\bin\server.sh file (on Unix systems).
ISS.0098.0077E	Dispatcher out of memory. Retrying operation.
Explanation	Integration Server does not have sufficient memory to continue its document publishing operations. Integration Server will attempt to process this message again.
Action	Consider increasing the heap size of the JVM used by Integration Server. You can view the heap size by editing the <IntegrationServer_dir>\bin\server.bat file (on Windows systems) or <IntegrationServer_dir>\bin\server.sh file (on Unix systems).
ISS.0098.0078E	Dispatcher out of memory. Operation failed. Check error log.
Explanation	Integration Server does not have sufficient memory to continue its document publishing operations. Integration Server has exceeded its retry count, and an exception will be thrown.
Action	Consider increasing the heap size of the JVM used by Integration Server. You can view the heap size by editing the <IntegrationServer_dir>\bin\server.bat file (on Windows systems) or <IntegrationServer_dir>\bin\server.sh file (on Unix systems).
ISS.0098.0079E	Dispatcher out of memory. Retry succeeded.
Explanation	Integration Server successfully retried a publishing operation after an OutOfMemory error prevented the operation from working the first time.
Action	If the Integration Server continues to issue this message, check the JVM Heap size and/or size of Documents on the Broker. The Trigger configuration (possibly the acknowledgment queue size) may need to be adjusted.

- ISS.0098.0080U** **Insufficient memory while persisting messages for Trigger: {0}.**
Explanation Integration Server does not have sufficient memory to persist the documents to the document store for the trigger.
Action Check the size of the documents being persisted and consider increasing the heap size of the JVM used by Integration Server. You can view the heap size by editing the <IntegrationServer_dir>\bin\server.bat file (on Windows systems) or <IntegrationServer_dir>\bin\server.sh file (on Unix systems).
- ISS.0098.0081U** **Insufficient memory while persisting message: {1} for Trigger: {0}.**
Explanation Integration Server does not have sufficient memory to persist a single document to the document store for the trigger.
Action Check the size of the document being persisted and consider increasing the heap size of the JVM used by Integration Server. You can view the heap size by editing the <IntegrationServer_dir>\bin\server.bat file (on Windows systems) or <IntegrationServer_dir>\bin\server.sh file (on Unix systems).
- ISS.0098.0082U** **Unable to persist Document: {0} to Document Store: {1}. Exception: {2}**
Explanation Integration Server failed to persist the document to the document store. This indicates a serious internal error.
Action Contact Software AG Global Support.
- ISS.0098.0083U** **Unable to acknowledge Document: {0} for Trigger Store: {1}. Insufficient memory.**
Explanation Integration Server does not have sufficient memory to acknowledge the document to the document store.
Action Check the size of the document being persisted and consider increasing the heap size of the JVM used by Integration Server. You can view the heap size by editing the <IntegrationServer_dir>\bin\server.bat file (on Windows systems) or <IntegrationServer_dir>\bin\server.sh file (on Unix systems).
- ISS.0098.0084U** **Exception:{0} during Trigger dispatching.**
Explanation Integration Server encountered an internal error while which processing a document destined for an individual trigger.
Action Contact Software AG Global Support.

ISS.0098.0085U	Unable to remove all subscriptions for transport:{0} while unregistering trigger. If connected, please remove subscription from {1} manually.
Explanation	Integration Server failed to remove all stale subscriptions before unregistering the trigger. The Broker may be unavailable.
Action	In the Broker Administrator, check the status of the Broker and the network connection. If one or both are down, then you will need to manually remove the stale subscriptions for the trigger when they are back up.
ISS.0098.0086U	Unable to remove all subscriptions for transport:{0} before registering trigger. If connected, please remove stale subscriptions from {1} manually.
Explanation	Integration Server failed to remove all stale subscriptions before registering the trigger. The Broker may be unavailable.
Action	In the Broker Administrator, check the status of the Broker and the network connection. If one or both are down, then you will need to manually remove the stale subscriptions for the trigger when the Broker and network are back up.
ISS.0098.0087E	Duplicate document of type:{0} with Id:{1} received for trigger:{2}.
ISS.0098.0089U	Transaction size (no of documents * size of documents) is too large for Document Store: {0}. Please reduce capacity of Trigger and /or increase initial size of Document Stores.
Explanation	The Integration Server failed to persist documents because the document store did not contain enough space. Documents received from the Broker are persisted in the triggers' persistent stores.
Action	In the Integration Server Administrator, click Settings>Resources>Document Stores. On this page, consider increasing the initial size of the document store. Also, consider reducing the number of triggers that subscribe to the document.
ISS.0098.0090U	Size of Document: {0} for Document Store: {1} is too large. Server is unable to persist. Audit logging the document.
Explanation	Integration Server failed to persist a document because the document store did not contain enough space.
Action	In the Integration Server Administrator, click Settings>Resources>Document Stores. On this page, consider increasing the initial size of the document store.

ISS.0098.0096I **Integration Server is now connected to a Broker that tracks document redelivery counts. Restart the Integration Server to make use of redelivery counts in duplicate detection.**

Explanation Integration Server connects to a version of the Broker that supports redelivery count. Previously it was connected to a Broker that did not support this feature.

Action Restart Integration Server so that it can take advantage of the redelivery count feature supported by the Broker.

ISS.0098.0100 **Copying of documents to trigger store started.**

ISS.0098.0103S **{0} not initialized. Adjust document store settings and restart server.**

Explanation Integration Server was unable to create the Document Store on disk. The Document Store is essential for Integration Server functioning, therefore startup terminates.

Action Check to see if there is enough disk space on the drive where the Document Store is being created (usually under <IS_SERVER_ROOT>\DocumentStore directory). If there is sufficient disk space, then check to see if the dispatch.cnf file under <IS_SERVER_ROOT>\config directory is corrupted. If the problem persists despite a re-start, contact Software AG Global Support.

ISS.0098.0104I **Integration Server is now connected to a Broker that does not track document redelivery counts. Restart the Integration Server so that duplicate detection does not expect document redelivery counts.**

Explanation Integration Server connects to a version of the Broker that does not support the redelivery count. Previously it was connected to a Broker that does support this feature.

Action Restart the Integration Server so that its duplicate detection mechanism does not expect redelivery counts to be present in documents delivered by the Broker.

ISS.0098.0105E **Unable to fully build comparable trigger: {0}**

Explanation During Cluster Synchronization, Integration Server was unable to compare trigger nodes across all the nodes in the cluster. The most likely cause is that one or more triggers are not completely configured. Cluster Synchronization makes sure that changes made to a trigger's configuration on one Integration Server are propagated to other servers in the cluster. If an Integration Server is configured for Cluster Synchronization, this process runs when an administrator makes a trigger configuration change through the Integration Server Administrator or when a user-written service calls one of the pub.trigger:* services.

Action Using the development tool, check the trigger configuration. After correcting the problem, retry the task you were performing when the error occurred.

ISS.0098.0106	Trigger comparison failed: trigger = {0}; parameter = {1}; local value = {2}; remote value = {3}.
ISS.0098.0107E	Error occurred during cluster invoke: Alias = {0}; Service = {1}; Exception = {2}.
Explanation	During Cluster Synchronization, Integration Server threw an exception while invoking a service on a remote node in the cluster. Cluster Synchronization makes sure that changes made to a trigger's configuration on one Integration Server are propagated to other servers in the cluster. If an Integration Server is configured for Cluster Synchronization, this process runs when an administrator makes a trigger configuration change through the Server Administrator or when a user-written service calls one of the pub.trigger:* services.
Action	The action you take depends on the exception issued. Look at the exceptionMessage for specific information.
ISS.0098.0108	Serial trigger {0} has been automatically suspended due to an exception: {1}.
ISS.0098.0109	Unable to establish secure connection to Broker. Password needed for SSL connection to Broker:{0}.
ISS.0098.0112	Trigger Resource Monitor now monitoring resource availability for trigger "{0}".
ISS.0098.0113	Trigger Resource Monitor invoked "{0}". Status of resource is "available".
ISS.0098.0114	Trigger Resource Monitor invoked "{0}". Status of resource is "not available".
ISS.0098.0115	Trigger Resource Monitor has resumed trigger "{0}".
ISS.0098.0116	Trigger Resource Monitor encountered an exception while attempting to resume trigger "{0}": {1}
ISS.0098.0117	The ISInternal functional alias is not configured properly on the JDBC Pools page. It is required in order to create and manage AND and XOR trigger joins. Assign a valid database pool and restart the Integration Server.

- ISS.0098.0118** The ISInternal functional alias on the JDBC Pools page must be configured to use an external database in order to create and manage AND and XOR trigger joins.
- ISS.0098.0119** Trigger Retry Failure occurred for trigger "{0}" : "{1}" . This trigger is being suspended and the message is being rolled back to the Broker because the Audit Logging subsystem also failed: "{2}"
- ISS.0098.0120** The default Broker was detected while initializing the dispatch.cnf file. Broker Settings will automatically be enabled.
- ISS.0098.0121** The default Broker was not detected while initializing the dispatch.cnf file. Broker Settings will automatically be disabled.
- ISS.0098.0122** The subscription for publishable document {0} will not be removed or recreated because the client prefix {1} used by the Broker connection for trigger {2} may be shared by multiple clients. If required, please remove subscription from Broker manually.
- ISS.0098.0123** The subscription for publishable document {0} will not be removed or recreated because the client prefix {1} used by the Broker connection for trigger {2} may be shared by multiple clients. If required, please remove subscription from Broker manually.
- ISS.0098.0124E** **A username and password are required for Username/Password authentication.**
Explanation Authentication credentials were not specified.
Action Provide a username and password.
- ISS.0098.9002U** **Required property missing for creating {0} transport: {1}**
Explanation Integration Server could not read properties from the <IntegrationServer_dir>\config\dispatch.cnf file. The file may be corrupt.
Action Examine the dispatch.cnf file to make sure that it is not corrupt and that the "clientGroupName" and "brokerHost" fields exist. If the file is corrupt, rename it and restart Integration Server. After you do this, you can re-configure the Broker Settings using the Integration Server Administrator.

ISS.0098.9005	Invalid connections properties for creating {0}
ISS.0098.9006U	No matching Document Type exists for {0}
Explanation	A pub.publish* service returned an error because the document specified in the "documentTypeName" parameter does not exist on the Integration Server.
Action	Examine the input for the "documentTypeName" parameter. Make sure that the parameter specifies the fully qualified name of the document type for which you want to publish or deliver an instance. Keep in mind that document type names are case-sensitive. Additionally, ensure that the specified document type exists on Integration Server.
ISS.0098.9007E	Data does not conform to the Publishable Document Type {0} errors: {1}
Explanation	A pub.publish* service issued an error because the IData input for the "document" parameter does not conform to the document type specified in the "documentTypeName" parameter.
Action	Examine the validation error message and the IData object passed to the "document" parameter. Make sure that it conforms to the document type specified in the "documentTypeName" parameter.
ISS.0098.9008U	No registered Transport for the given id: {0}
Explanation	Integration Server failed to create a subscription to the publishable document type specified in a trigger. The transport information does not exist, which indicates an internal error.
Action	Contact Software AG Global Support.
ISS.0098.9009	Certificate file require for using SSL encryption
ISS.0098.9010E	No waiting thread for Document Id: {0}. Requestor might have timed out.
Explanation	Integration Server encountered an internal error while publishing the document and waiting for a reply.
Action	Contact Software AG Global Support.
ISS.0098.9011U	{0} is not a Publishable Document Type.
Explanation	A pub.publish* service returned an error because the document type specified in the "documentTypeName" parameter was not publishable.
Action	Ensure that the Publishable property is set to "true" for the document type."

ISS.0098.9013U	Dispatcher is not initialized
Explanation	Integration Server was not able to publish, deliver, or reply to a document because the dispatcher that is responsible for performing these operations was not initialized.
Action	Log on to the Integration Server Administrator and make sure that you have correctly configured Integration Server for document publishing.
ISS.0098.9014U	BrokerException: {0}
Explanation	Integration Server was unable to publish or retrieve documents from the Broker because the operation failed on the Broker.
Action	Examine the error message provided by the Broker. Refer to the webMethods Broker API documentation for the Java Client for a detailed description of the error.
ISS.0098.9015	Rejected document because Dispatcher was unable to deliver document after {0} attempts
ISS.0098.9016U	Broker Transport unable to subscribe to Publishable Document Type:{0} BrokerEvent Type:{1}
Explanation	Integration Server failed to create a subscription to the publishable document type specified in a trigger. The client is not allowed to subscribe to the Broker document type associated with the publishable document type.
Action	In the Broker Administrator, check the subscription permissions of the client group to which the trigger belongs. Make sure that the client is allowed to subscribe to the Broker document type associated with the publishable document type.
ISS.0098.9017	Rejecting document as there is no enabled Trigger registered:
ISS.0098.9018E	Unrecoverable Error while initializing the webMethods Messaging Subsystem (Dispatcher): {0}. No webMethods Messaging features will be available until this issue is resolved and the server is restarted.
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISS.0098.9019U	Request timed out while waiting for reply
Explanation	Integration Server encountered an internal error while publishing or delivering the document and waiting for a reply.
Action	Contact Software AG Global Support.

ISS.0098.9021U	Received incorrect document as Reply. Expecting {0} and received {1}
Explanation	Integration Server failed to receive the expected reply document while publishing or delivering the document and waiting for a reply.
Action	Check the subscriber of the publisher document. Make sure that the subscriber delivers a correct reply document.
ISS.0098.9022E	Invalid DispatcherMessage {0}
Explanation	Integration Server failed to deliver the document to the subscribing triggers. The document is null, which indicates an internal error.
Action	Contact Software AG Global Support.
ISS.0098.9023U	Transport Factory: {0} not found.
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISS.0098.9024U	{0} Unknown Transport Type specified. Unable to create transport.
Explanation	Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISS.0098.9025U	{0} not configured. {1} operation can only be done after a {0} is configured.
Explanation	The pub.publish:deliver or pub.publish:deliverAndWait service failed to execute because Integration Server is not configured to connect to the Broker.
Action	Use Integration Server Administrator to configure the server to connect to a Broker.
ISS.0098.9027U	Unknown broker version.
Explanation	Integration Server failed to connect to the Broker because the version of the Broker is not supported.
Action	Do not attempt to set up such an environment. See the "Installing webMethods Products" for supported configurations.
ISS.0098.9028	Incompatible Broker version. The minimum Broker version required is 6.0.

ISS.0098.9033E	Duplicate condition name "{1}" in Trigger "{0}"
Explanation	Integration Server could not save the condition settings of a trigger because the trigger has duplicate condition names.
Action	Edit the trigger so that each condition has a unique name.
ISS.0098.9034E	Condition name "{0}" - Cannot have duplicate document types in AND join.
Explanation	Integration Server could not save a trigger because a condition has duplicate document types in an "AND" join.
Action	Edit the trigger condition to make sure that unique document types are specified in the "AND" join.
ISS.0098.9035E	Cannot specify different filters for document type "{0}" within a single trigger
Explanation	Integration Server could not save the condition settings of a trigger because more than one filter is specified for a document type in the trigger.
Action	If multiple conditions in the trigger specify the same document type, make sure that the filter applied to the document type is the same for each condition.
ISS.0098.9036U	Unable to ack
Explanation	Integration Server failed to acknowledge the document to the trigger document store. This indicates an internal error.
Action	Contact Software AG Global Support.
ISS.0098.9050U	Unable to publish volatile Document: {0}. Broker not connected.
Explanation	Integration Server published a volatile document while the Broker was down. A service exception occurred for the publishing service and the volatile document was lost.
Action	Make sure the Broker is available and re-publish the document.
ISS.0098.9051U	No activation specified for Join Document:{0}.
Explanation	The published document cannot be processed in a join because it is missing an activation ID.
Action	The publisher of the document needs to set an activation ID for the document.

ISS.0098.9056U	cmd for msgs all not the same or null
Explanation	A flow service mixed the pub.publish:deliver and pub.publish:publish steps when the "delayUntilServiceSuccess" parameter is set to "true".
Action	Use separate flow services to deliver and publish a message when the "delayUntilServiceSuccess" parameter is set to "true".
ISS.0098.9057U	destination for msgs all not the same or null
Explanation	A flow service contains multiple pub.publish:deliver steps where the "delayUntilServiceSuccess" parameter is set to "true", but the destination IDs are not identical.
Action	Use separate flow services to deliver a message to different destination IDs when the "delayUntilServiceSuccess" parameter is set to "true".
ISS.0098.9058E	publish-on-success is suspended
Explanation	The publish-on-success facility has been programmatically suspended. Therefore, the publish-on-success operation will not work.
Action	Restart the Integration Server.
ISS.0098.9059E	max concurrent publish-on-success is exceeded
Explanation	The watt.server.control.maxPublishOnSuccess parameter was exceeded by a publishing flow. The maxPublishOnSuccess parameter controls the maximum number of documents that Integration Server publishes on success at one time.
Action	Decrease the number of documents published by a flow service that uses publish-on-success, or increase the value of the maxPublishOnSuccess parameter.
ISS.0098.9061	Document store runtime capacity
ISS.0098.9062U	Document store is missing for {2}
Explanation	Integration Server encountered an internal error in the document store.
Action	Contact Software AG Global Support.
ISS.0098.9063	Step size for {2} must be positive and no greater than 100: {3}

ISS.0098.9064	Unable to mark as complete to the Document History
ISS.0098.9065E	Error reply {0} received. adapterType:{1}, errorCategory:{2},errorText:{3},eventId:{4}
Explanation	A client, typically an Integration Server but possibly a Broker client or Adapter, sent a request document to an Integration Server, but received an error reply (a document of type <code>pub.publish.notification:error</code>) in response. This happens when the service executing the request document on the target server encounters an error. Instead of sending the expected reply document type, it sends an error document indicating it could not process the request document correctly.
Action	Check the Error log of the target Integration Server, that is, the Integration Server to which the request document was sent. If the error occurred when a document was being published to a single subscriber, you will know which target server issued the error reply. However, if the error occurred during a publish to multiple Integration Servers, you will have to determine which target server issued the error.
ISS.0098.9066E	Missing required parameter: "{0}".
Explanation	A client tried to invoke a service, but did not specify a required parameter.
Action	Supply the missing required parameter.
ISS.0098.9067E	Trigger not found for triggerName: "{0}".
Explanation	Integration Server tried to suspend or fetch metadata for the indicated trigger, but there is no trigger with this name enabled on Integration Server.
Action	Make sure the trigger name is typed correctly and that the trigger is enabled.
ISS.0098.9068E	Unable to get status for Trigger "{0}": No IControlObject found.
Explanation	Integration Server encountered an error while trying to perform an action against a trigger, but the trigger was not completely configured, and as a result, not fully initialized.
Action	Verify that the trigger is properly configured and is considered to be valid. After correcting the problem, retry the task you were performing when the error occurred.
ISS.0098.9069E	Unable to get status for Trigger "{0}": {1}
Explanation	Integration Server encountered an error while trying to perform an action against a trigger.
	- For trigger retrieval, the status indicates whether the trigger is active or suspended.
	- For trigger processing, the status indicates whether the trigger is active or suspended and shows the current threads being used, the current volatile queue size, and the current persisted queue size.

Action	The action you take depends on the exception issued. Look at the exception message and the server log for additional details.
ISS.0098.9072E	Trigger "{0}" is locked. Change not permitted.
Explanation	A user tried to modify the indicated trigger using the Trigger Management screens in Integration Server Administrator or the built-in services, but the trigger is locked.
Action	Unlock the trigger and try again.
ISS.0098.9073E	Unable to suspend document {0} for Trigger "{1}": No IControlObject found.
Explanation	A request to suspend document processing failed. The most likely cause is that the trigger was not completely configured, and as a result, not fully initialized.
Action	Make sure the trigger is configured properly and is considered to be valid. After correcting the problem, retry the task you were performing when the error occurred.
ISS.0098.9074E	Unable to suspend document {0} for Trigger "{1}": {2}
Explanation	A request to suspend document processing failed due to the indicated exception.
Action	The action you take depends on the exception issued. Look at the exception message value in the message for specific information.
ISS.0098.9075E	Unable to resume document {0} for Trigger "{1}": No IControlObject found.
Explanation	A request to resume document processing failed. The most likely cause is that the trigger was not completely configured, and as a result, not fully initialized.
Action	Make sure the trigger is properly configured and is considered to be valid. After correcting the problem, retry the task you were performing when the error occurred.
ISS.0098.9076E	Unable to resume document {0} for Trigger "{1}": {2}
Explanation	A request to resume document processing failed due to an exception.
Action	The action you take depends on the exception issued. Look at the exception message value in the message for specific information.
ISS.0098.9077E	Unable to persist the change made to Trigger "{0}": {1}
Explanation	The configuration change for a trigger was not saved to file. As a result, the change will revert back to its original value after Integration Server restarts or someone reloads the package.
Action	The action you take depends on the exception issued. Look at the exception message value in the message for specific information.

ISS.0098.9078E	maxExecutionThreads cannot exceed queueCapacity
Explanation	The value specified for the number of maximum execution threads exceeds the queue capacity. This is not permitted because the number of documents the Integration Server can process concurrently (maxExecutionThreads) cannot exceed the maximum number of documents that can be in the trigger's queue (queueCapacity).
Action	Change the maximum execution threads value to be less than or equal to the queue capacity. Alternatively, change the queue capacity value so that it is greater than or equal to the maximum execution threads.
ISS.0098.9079E	queueRefillLevel cannot exceed queueCapacity
Explanation	The value specified for the queue refill level exceeds the queue capacity. The queue refill level is the number of unprocessed documents that must remain in the trigger queue before Integration Server retrieves more documents for the queue from the Broker. This level cannot exceed the maximum number of documents that can be in the trigger's queue (queueCapacity).
Action	Change the queue refill level value so that it is less than or equal to the queue capacity. Alternatively, change the queue capacity value so that it is greater than or equal to the queue refill level.
ISS.0098.9080E	{0} must be a positive number.
Explanation	The value specified for the indicated parameter was zero or a negative number. This value must be positive number.
Action	Supply a positive number for the indicated parameter.
ISS.0098.9081	Unable to publish Document: {0}. Broker not connected.
ISS.0098.9082	Unable to create trigger "{0}": {1}
ISS.0098.9083	Unable to create trigger "{0}". Invalid Trigger Name.
ISS.0098.9084	Unable to create trigger "{0}". Invalid NSName.
ISS.0098.9085	Unable to create trigger "{0}". Package "{1}" does not exist.

ISS.0098.9086	Unable to create trigger "{0}": Insufficient Write ACL privileges.
ISS.0098.9087	Unable to create trigger "{0}". A trigger with this name already exists.
ISS.0098.9088	{0} must me greater than 0 or -1.
ISS.0098.9089	{0} must me greater than or equal to 0.
ISS.0098.9090	Unable to publish to the broker the Document: {0}. Sync the document with the broker.
ISS.0099.0001U	Broker Transport:{0} unable to subscribe to Broker Document {1}. Exception {2}
Explanation	The Integration Server failed to create the subscription for the trigger on the Broker. The Broker may be unavailable.
Action	In the Broker Administrator, check the status of the Broker and the network connection. If all are correct, then this is an internal error. Contact Software AG Global Support.
ISS.0099.0002U	Broker Transport:{0} unable to unsubscribe to Broker Document {1}. Exception {2}
Explanation	The Integration Server failed to cancel the subscription for the trigger from the Broker after removing the trigger from the Integration Server. The Broker might be unavailable.
Action	In the Broker Administrator, check the status of the Broker and the network connection. If all are correct, then this is an internal error. Contact Software AG Global Support.
ISS.0099.0003U	Unable to create Broker Transport {0}. Exception {1}
Explanation	The Integration Server failed to create the Broker transport for the Broker client because the client could not reconnect to the Broker. The Broker might be temporarily unavailable.
Action	In the Broker Administrator, check the status of the Broker and the network connection. If all are correct, then this is an internal error. Contact Software AG Global Support.
ISS.0099.0005E	Creating subscription on Broker without invalid filter: {0}
Explanation	A trigger contains an invalid filter. The subscription was created on the Broker without the invalid filter.
Action	Change the filter in the trigger to a valid trigger.

ISS.0099.0006U	Unable to disconnect Broker Transport. Exception: {0}
Explanation	Integration Server failed to disconnect from the Broker during shutdown. This indicates an internal error.
Action	Contact Software AG Global Support.
ISS.0099.0007U	BrokerTransport:{0} got Exception: {1}
Explanation	The Integration Server encountered an internal error.
Action	Contact Software AG Global Support.
ISS.0099.0008U	Insufficient memory while retrieving events for BrokerTransport:{0}
Explanation	The Integration Server does not have sufficient memory to retrieve even one document from the Broker.
Action	From the Broker, check the size of the document. Consider increasing the heap size of the Integration Server's JVM. You can view and edit the heap size in the IntegrationServer_dir\bin\server.bat file (on Windows systems) or IntegrationServer_dir\bin\server.sh file (on UNIX systems).
ISS.0099.0009U	Unable to retrieve events from the Broker for BrokerTransport:{0}. Insufficient JVM memory. Please check Heap size/ size of Documents on the Broker.
Explanation	The Integration Server does not have sufficient memory to retrieve documents from the Broker.
Action	From the Broker, check the size of the documents. Consider increasing the heap size of the Integration Server's JVM. You can edit the heap size in the IntegrationServer_dir\bin\server.bat file (on Windows systems) or IntegrationServer_dir\bin\server.sh file (on UNIX systems).
ISS.0099.0010U	Broker Transport:{0} failed to unsubscribe to all Broker Documents. Exception {1}
Explanation	The Integration Server failed to cancel the subscriptions from the Broker while removing the trigger from the Integration Server. The Broker might be unavailable.
Action	In the Broker Administrator, check the status of the Broker and the network connection. If all are correct, then this is an internal error. Contact Software AG Global Support.
ISS.0099.0011E	Broker Transport Factory unable to retrieve password for handle {0}
Explanation	An internal error occurred.
Action	Contact Software AG Global Support.

ISS.0099.0012E	{0} failed to retrieve password for handle {1}. Exception {2}
Explanation	An internal error occurred.
Action	Contact Software AG Global Support.
ISS.0099.0013E	{0} failed to save password for handle {1}. Exception {2}
Explanation	An internal error occurred.
Action	Contact Software AG Global Support.
ISS.0099.0014E	{0} failed to refresh broker settings. Exception type {1}, msg {2}
Explanation	An error occurred while saving broker settings to disk.
Action	Read through the details provided in the exception and take corrective steps. If you are not able to resolve the problem, contact Software AG Global Support.
ISS.0099.0015E	BrokerTransport : Broker Timing out repetitively. New subscriptions won't get created and if subscriptions are already existing, this might lead to the client queue growing on the broker
Explanation	An attempt to create a new subscription has timed out multiple times.
Action	Contact Software AG Global Support.
ISS.0100.0005E	Web Container error: {0};{1}
Explanation	The Apache Tomcat server encountered an error.
Action	Examine the error message provided and check Tomcat references at http://jakarta.apache.org/tomcat/resources.html for more information about the exception.
ISS.0100.0019E	ISConnector.invoke: {0}
Explanation	The Integration Server HTTP stack encountered an error while passing control to the WmTomcat connector.
Action	Contact Software AG Global Support.
ISS.0100.0030E	WebContainer.removePackage: {0}
Explanation	Integration Server tried to process a request to delete a package that contains a Web application but could not because there was an internal Tomcat error.
Action	Contact Software AG Global Support.

ISS.0100.0031E	WebContainer.addPackage: {0}
Explanation	Integration Server tried to process a request to deploy or redeploy a Web application but could not because there was an internal Tomcat error.
Action	Contact Software AG Global Support.
ISS.0100.0032E	Invalid URI: {0}
Explanation	WmTomcat tried to process a request but could not because the HTTP request passed an invalid URI. Integration Server logs the HTTP request and response, but does not invoke anything in Tomcat.
Action	Contact Software AG Global Support.
ISS.0100.0036E	{0} getReader() has already been called for this request
Explanation	A servlet or JSP called the ServletRequest.getInputStream() method after it had already called the ServletRequest.getReader() method. The servlet or JSP can call one method or the other, not both.
Action	Check the servlet or JSP and ensure that only one of these methods is called.
ISS.0100.9900U	The {0} action is not enclosed by a {1} action.
Explanation	Integration Server was not able to execute a Web application because there are syntax errors in the JSP file.
Action	Examine the error message to determine which tag name caused the exception to be thrown. Then check the JSP file that contains the tags and look for syntax errors. See the "Web Applications Developer's Guide" for the correct usage. After you fix the problem, re-deploy the Web application on Integration Server.
ISS.0100.9901U	The {0} action is not enclosed by a {1} action at {2}.
Explanation	Integration Server was not able to execute a web application because there was a syntax error in the <webm:ifvar> and <webm:else> tags in the JSP file.
Action	Examine the JSP file that contains the <webm:ifvar> and <webm:else> tags. See the "webMethods Applications Developer's Guide" for the correct usage of these tags. After you fix the problem, re-deploy the Web application on Integration Server.
ISS.0105.0003E	Cannot get canonicalKey: {0}
Explanation	The pub.synchronization.xref:getCanonicalKey service failed to execute because an exception was thrown when Integration Server tried to retrieve the corresponding canonical key for the specified native ID from the repository.
Action	Examine the exception message and stack trace for details. Verify that you have provided correct input for the "appID", "nativeID", and "objectID" parameters. If you cannot find the cause for the problem, contact Software AG Global Support.

ISS.0105.0005E	Cannot insert into database this record, appId="{0}", nativeId="{1}", canonicalKey="{2}", objId="{3}", error: {4}
Explanation	The pub.synchronization.xref:createXReference service or pub.synchronization.xref:insertXReference service failed to execute because an exception was thrown when Integration Server tried to insert or create the cross-reference record in the repository.
Action	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check the webMethods Integration Server documentation to make sure that you have set up your JDBC Pool configurations correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.
ISS.0105.0006E	Cannot close latch: {0}
Explanation	The "pub.synchronization.latch:closeLatch" service failed to execute because an exception was thrown when Integration Server tried to close the latch for a given application ID, canonical Key, and object ID.
Action	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check the webMethods Integration Server documentation to make sure you have set up your JDBC Pool configurations correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.
ISS.0105.0007E	Cannot open latch: {0}
Explanation	The "pub.synchronization.latch:closeLatch" service failed to execute because an exception was thrown when the Integration Server tried to open the latch for a given application ID, canonical Key, and object ID.
Action	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check "Installing webMethods Products" to make sure you have set up your JDBC Pool correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.
ISS.0105.0008E	Cannot get nativeId: {0}
Explanation	The "pub.synchronization.xref:getNativeId" service failed to execute because an exception was thrown when the Integration Server tried to retrieve the native ID for a given canonical key, application ID, and object ID.
Action	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check "Installing webMethods Products" to make sure you have set up your JDBC Pool configurations correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.

- ISS.0105.0009E** **Cannot obtain a JDBC connection: {0}**
Explanation The Integration Server was not able to obtain a connection to the JDBC database where cross-reference keys and echo suppression status are stored. A likely cause is that the pool alias for this database was specified incorrectly on the Settings>JDBC Pools page of the Server Administrator.
Action From the Settings>JDBC Pools page of the Server Administrator, examine the pool alias properties for the Xref and make sure it specifies the correct Database URL, User Id, Password, and Database driver. Then, restart the Integration Server.
- ISS.0105.0010E** **No JDBC connection available**
Explanation The Integration Server was not able to obtain a connection to the JDBC database where the cross-reference keys and echo suppression status are stored. A likely cause is that no JDBC pool connections are available.
Action From the Settings > JDBC Pools page of the Integration Server Administrator, examine the pool alias properties for the Xref and consider increasing the number of connections. Then, restart Integration Server.
- ISS.0105.0011E** **Release JDBC connection error: {0}**
Explanation Integration Server tried to perform a database operation, but the "pub.synchronization*" service failed to release its connection to the database. This indicates an internal error.
Action Contact Software AG Global Support.
- ISS.0105.0012E** **Get preparedStatement error: {0}**
Explanation While trying to perform a database operation, a "pub.synchronization*" service encountered an SQLException.
Action Examine the error stack trace to determine which SQL exception was thrown. Make sure you followed the instructions in the "webMethods Integration Server documentation and set up the Database correctly. If you cannot determine the cause of the error, contact the database vendor.
- ISS.0105.0013E** **Check isLatchClosed error: {0}**
Explanation The pub.synchronization.latch:isLatchClosed service threw an exception when it tried to check the latch status for a given canonical key, application ID, and object ID.
Action Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check "Installing webMethods Products" to make sure you have set up your JDBC Pool correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.

ISS.0105.0014E	Drop all records with objId="{0}", error: {1}
Explanation	The "pub.synchronization.xref:deleteByObjectId" service threw an exception when it tried to remove all cross-reference records associated with a particular process or synchronization.
Action	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check the webMethods Integration Server documentation to make sure that you have set up your JDBC Pool configurations correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.
ISS.0105.0024E	Delete xref record: appId="{0}", canonicalKey="{1}", objId="{2}", error: {3}
Explanation	The pub.synchronization.xref:deleteXReference service threw an exception when it tried to remove all cross-reference records associated with a particular process or synchronization.
Action	Examine the error stack trace to determine which exception was thrown. If it was a SQLException, check the webMethods Integration Server documentation to make sure that you have set up your JDBC Pool configurations correctly. If you cannot determine the cause of the problem, contact Software AG Global Support.
ISS.012.0026E	The certificate in the SAML assertion signature does not match the certificate on file for the issuer; Rejecting SAML assertion.
Explanation	The certificate in the SAML assertion signature does not match the certificate on file for the issuer.
Action	Check the issuer configuration on Security -> SAML screen and make sure that the identified truststore contains the correct certificate for the issuer.
ISS.0128.0001E	Unable to get JDBC connection. Exception:{0}
Explanation	Integration Server was unable to connect to the database defined by the DocumentHistory functional alias. This alias defines the database that the Integration Server uses to detect duplicate documents.
Action	From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. Review the Journal log for messages about the operation being performed. If the problem persists, contact your Database Administrator.

- ISS.0128.0002E** **Exception while {1}: {0}**
- Explanation** An exception occurred when Integration Server tried to perform a task using the In Doubt Resolver component.
- Action** From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. If the problem persists, contact your Database Administrator.
-
- ISS.0128.0003E** **SQLException:{0} while {1}**
- Explanation** An exception occurred when Integration Server tried to perform a SQL operation using the JDBC connection pool for the functional alias DocumentHistory.
- Action** From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. Review the Journal log for messages about the operation being performed. If the problem persists, contact your Database Administrator.
-
- ISS.0128.0004E** **Exception while loading the Decision Tree: {0}**
- Explanation** An exception occurred when Integration Server tried to create the decision tree for resolving duplicate documents. The decision is based on multiple criteria, but Integration Server was not able to load these criteria into memory.
- Action** Contact webMethods Customer Care. Be prepared to provide logs and the version number and patch level for Integration Server and your operating system.
-
- ISS.0128.0005E** **Exception:{0} while resolving Document of type: {1} and Id: {2} for trigger: {3}. Document is being deemed as In Doubt.**
- Explanation** An exception occurred when Integration Server tried to resolve a document it received. The exception might be due to a problem with the database connection for the alias DocumentHistory or with the Resolver Service associated with the trigger.
- Action** Examine the Server log for error messages that indicate the cause of the problem. If the error was a database/SQL exception, check to see if the functional alias DocumentHistory is working properly. If a problem occurred with the Resolver Service, verify that the service is properly coded.

ISS.0128.0006E	Trigger: {0} encountered exception while executing resolver service: {1}. Exception: {2}
Explanation	Integration Server received a document, but the document resolver service associated with the trigger encountered an exception.
Action	Check the Error log to see if the Document Resolver Service associated with the trigger has logged any error messages. If no messages have been logged, change the auditing properties for the service to enable the Log on Error property. In addition, because this is a user-written service, check it to make sure it has been coded properly.
ISS.0128.0007E	In Doubt document of type:{0} with Id:{1} received for trigger:{2}. Document is being Audit Logged.
Explanation	Integration Server received a document, but the document resolver service associated with the trigger could not resolve the document and therefore considers it to be "In Doubt".
Action	Check the document's id to see if it is a duplicate. If there is an document resolver service associated with the trigger, determine why the service was not able to resolve the document. Integration Server records occurrences of In Doubt Documents in the Audit log. You can view In Doubt documents through WmMonitor.
ISS.0128.0008E	Unable to Audit Log document of type:{0} with id:{1} as it can't be decoded. Exception:{2}.
Explanation	An error occurred when Integration Server tried to resolve a document. As part of the resolution process, a document first goes to the In Doubt Resolver component. If that component successfully resolves the document, Integration Server decodes the document and sends it to the trigger. However, if the In Doubt Resolver cannot resolve the document, the Integration Server decodes the document and sends it to the In Doubt Resolver service associated with the trigger. This error is issued if there is an error when decoding the document before sending it to the In Doubt Resolver service associated with the trigger.
Action	Make sure the document type on Integration Server matches the associated Broker document type on the Broker. Re-sync the document types by pushing the IS document type to the Broker ("Push to Broker"). If all the document type fields and data types match and the problem still persists, contact webMethods Customer Care.
ISS.0128.0009E	Unable to get JDBC Connection to the database.
Explanation	As part of storing history for the document being processed, the Integration Server's In Doubt Resolver component add/deletes rows to a database. While performing one of these actions, the connection to the database was lost.
Action	From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a functional alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. If the problem persists, contact your Database Administrator. Review the Journal log for messages

about the operation being performed. If the problem persists, contact your Database Administrator.

ISS.0128.0010 **Detected expired UUID:{0} for trigger:{1}. Deleting all expired UUIDs.**

ISS.0128.0011 **Unable to resolve processing state for UUID:{0} for trigger:{1}. Exception:{2}**

ISS.0128.0012 **Unable to mark UUID:{0} for trigger:{1} as complete in the database. A non-expired UUID already exists.**

ISS.0128.0014E **Unable to insert UUID:{0}. Exception:{1}**

Explanation As part of storing history for the document or message being processed, Integration Server's In Doubt Resolver component stores the UUID (universally unique ID) of the document (message) in a database. An exception occurred during this process.

Action From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. If the problem persists, contact your Database Administrator.

ISS.0128.0015E **Document history initialization failed. Please verify database connection is available.Exception {0}.**

Explanation No valid JDBC connection Pool is available for the In Doubt Resolver Alias "DocumentHistory". Detection of duplicate documents depends on the availability of a database where document history is defined.

Action From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the Test button, then there is a problem with the connection. If the problem persists, contact your Database Administrator.

ISS.0128.9002E **Unable to get Connection**

Explanation No valid JDBC connection Pool is available for the In Doubt Resolver Alias "DocumentHistory".

Action From the Settings>JDBC Pools> page of the Integration Server Administrator, make sure that a Functional Alias called DocumentHistory exists and is associated with a valid Pool Alias. Click the Test button. If the alias exists, but there are errors when you hit the test button, then there is a problem with the connection. Review the Journal log for messages about the operation being performed. If the problem persists, contact your Database Administrator.

ISS.0128.9006E	Invalid argument supplied for:{0}
Explanation	Integration Server stores document history information in a database so that it can detect when duplicate documents are received. This error occurs when a process tries to insert an entry that specifies an invalid argument into the database.
Action	Check to see if the name of the trigger and the UUID of the document satisfy the constraints specified on the columns of the Table WM_IDR_MSG_HST in your database. This error can occur if the Trigger Name or UUID exceeds the column length of the database column.
ISS.0128.9013E	Exception while executing in doubt resolver service:{0}
Explanation	Integration Server received a document, but an exception occurred during execution of the document resolver service associated with the trigger.
Action	Check the Integration Server error log to see if the document resolver service has logged any error messages. If no errors were logged, configure the document resolver service's auditing properties to Log on Error. In addition, verify that the document resolver service has been coded properly.
ISS.0128.9015E	The DocumentHistory functional alias is not configured properly on the JDBC Pools page. Assign a valid database pool and restart the Integration Server.
Explanation	Integration Server stores document history information in a Document History database so that it can detect when duplicate documents are received. Integration Server throws this exception whenever it does not find a JDBC Pool for the Document History functional alias.
Action	Configure a JDBC Pool for Document History functional alias.
ISS.0131.0001E	No threads available. All diagnostic listener threads are in use.
Explanation	Integration Server has detected that all threads allocated to the diagnostic thread pool are in use.
Action	Wait for one or more of these threads to finish. If this problem persists, contact webMethods Customer Care.
ISS.0131.0002	DOMString size error. Details:{0}
ISS.0131.0003	Hierarchy request error. Details:{0}

- ISS.0131.0004 Wrong document error. Details:{0}
- ISS.0131.0005 Invalid character error. Details:{0}
- ISS.0131.0006 No data allowed error. Details:{0}
- ISS.0131.0007 No modification allowed error. Details:{0}
- ISS.0131.0008 Not found error. Details:{0}
- ISS.0131.0009 Not supported error. Details:{0}
- ISS.0131.0010 Inuse attribute error. Details:{0}
- ISS.0131.0011 Invalid state error. Details:{0}
- ISS.0131.0013 Invalid modification error. Details:{0}
- ISS.0131.0015 Invalid access error. Details:{0}
- ISS.0131.0017 Type mismatch error. Details:{0}
- ISS.0131.9998 Cannot set attribute name or value to null
- ISS.0131.9999 Cannot get null attribute
- ISS.0134.0002 JMS Runtime Configuration Internal Error. Unable to set thread pool max: {0}

ISS.0134.0003	An error occurred while loading JMS configuration file: {0}
ISS.0134.0004	Unable to start JMS connection alias "{0}": {1}
ISS.0134.0005E	Unable to start JMS connection alias "{0}". The alias is now disabled: {1}
Explanation	The specified JMS connection alias could not be started because it is disabled. Only enabled JMS connection aliases can be started.
Action	Enable the JMS connection alias.
ISS.0134.0006	JNDI Property "{0}" not found. Setting JMS connection alias "{1}" to disabled.
ISS.0134.0009	JMS configuration file not found: {0}
ISS.0134.0010	JMS subsystem is not configured. The default JMS connection alias is being created.
ISS.0134.0011	Unable to load JMS configuration file "{0}": {1}
ISS.0134.0012	Unable to load JMS configuration file "{0}": File not found.
ISS.0134.0014	"jms.cnf" file contains no configuration data.
ISS.0134.0015	Unable to load configuration for JMS connection alias "{0}": {1}
ISS.0134.0016	JMS Connection Error on connection "{0}": {1}
ISS.0134.0017	Unable to destroy CSQ for connection "{0}": {1}
ISS.0134.0018	Unable to ping JNDI provider "{0}": {1}

- ISS.0134.0019 **Unable to start CSQ Factory. The CSQ feature will not be functional for any JMS connection aliases: {0}**

- ISS.0134.0020 **Exception occured while pinging JMS provider "{0}": {1}**

- ISS.0134.0021 **Error delisting resource from transaction: {0}**

- ISS.0134.0022 **Error closing JMSSESSION: {0}**

- ISS.0134.0023 **Error shutting down CSQ Factory: {0}**

- ISS.0134.0024 **CSQ Dispatcher "{0}" unable to retrieve producer. CSQ Dispatcher is now stopping: {1}**

- ISS.0134.0025 **CSQ Dispatcher "{0}" is stopping because of exception: {1}**

- ISS.0134.0026 **CSQ Dispatcher "{0}" was unable to send message to "{1}" after {2} retries: {3}**

- ISS.0134.0027 **CSQ Dispatcher "{0}" was unable to send message to "{1}": {2}**

- ISS.0134.0028 **Out of memory error while acking message from CSQ "{0}". Attempting two retries**

- ISS.0134.0030 **CSQ Dispatcher "{0}" was unable to acknowledge message: {1}**

- ISS.0134.0031 **Out of memory error while sending message from CSQ. Attempting two retries**

- ISS.0134.0033 **No metadata found for JMS connection alias {0}**

- ISS.0134.0034 **No metadata found for JMS connection alias {0}: {1}**

ISS.0134.0035	The JMS provider and version associated with JMS connection alias {0} is not officially supported.
ISS.0134.0039	IllegalStateException occurred in Consumer {0}: {1}
ISS.0134.0040	OutOfMemoryError occurred in Consumer {0}
ISS.0134.0041	JMS Trigger {0} failed preprocessing: {1}
ISS.0134.0042	JMS Trigger {0} failed: {1}
ISS.0134.0043	JMS Trigger {0} failed post-processing: {1}
ISS.0134.0044	JMS Trigger {0} was unable to set JMS Reply To Context: {1}
ISS.0134.00451	JMS Trigger {0} has acknowledged the message(s).
Explanation	The specified JMS trigger has acknowledged the message(s) to the JMS provider.
Action	No action required.
ISS.0134.0046	JMS Trigger {0} has recovered the message(s).
ISS.0134.0051	Created JMS Trigger Thread Pool with a maximum of {0} threads.
ISS.0134.0053	Unable to start JMS Trigger {0}: {1}
ISS.0134.0056	Error closing Connection Handle: {0}.
ISS.0134.0057	JMS Trigger {0} did not shutdown in the allotted time ({1} seconds). It is now being forced to shutdown.

- ISS.0134.0058 JMS Trigger {0} is shutting down because of exception: {1}

- ISS.0134.0059 Error destroying Consumer Context: {0}.

- ISS.0134.0060 Unable to refill Shared Session Pool after release: {0}

- ISS.0134.0061 Consumer Context Pool shutdown timeout: Freeing up active entries.

- ISS.0134.0062 Internal Error: returning unused object to Consumer Context Pool!

- ISS.0134.0063 JMS transaction failed with \$errorType {0}.

- ISS.0134.0064 Unable to register JMS Trigger {0}: {1}

- ISS.0134.0065 Unable to unregister JMS Trigger {0}: {1}

- ISS.0134.0066 JMSTrigger {0} has started.

- ISS.0134.0072 JMS Trigger Resource Monitor scheduled new system task.

- ISS.0134.0073 JMS Trigger Resource Monitor has resumed the last trigger. Its system task will now be canceled.

- ISS.0134.0074 JMS Trigger Resource Monitor is now monitoring the resource availability of trigger {0}.

- ISS.0134.0075 JMS Trigger Resource Monitor invoked service {0}. Status of resource is "{1}".

- ISS.0134.0076 JMS Trigger Resource Monitor received an exception while invoking service {0}: {1}

ISS.0134.0077	JMSTrigger Resource Monitor has resumed trigger {0}.
ISS.0134.0078	JMS Trigger Resource Monitor received an exception while attempting to resume trigger {0}: {1}
ISS.0134.0081	No suitable data type was found in the message body so an empty Message is being created.
ISS.0134.0082	Not starting JMS connection alias {0} because package {1} is not loaded/enabled yet.
ISS.0134.0083	Trigger {0} cannot receive messages in a batch while using a transacted connection. The "max batch messages" size will be set to 1.
ISS.0134.0084	Unable to acknowledge InDoubtResolver: {0}
ISS.0134.0085	Unable to remove InDoubtResolver entry: {0}
ISS.0134.0086	Trigger Preprocessing Failure occurred for trigger {0}: {1}. The DocumentHistory JDBC alias may not be configured correctly. The trigger will be automatically suspended. You must restart it manually.
ISS.0134.0087	Trigger Preprocessing Failure occurred for trigger {0}: {1}. The trigger will be automatically suspended and IS will monitor the DocumentHistory JDBC resource.
ISS.0134.0088	Rejecting incoming message for trigger: {0}, documentID: {1}. Delivery Count has exceeded {2} attempts.
ISS.0134.0089	JMS Trigger {0} failed decoding: {1}
ISS.0134.0090	Unable to retrieve password from Password Manager with key {0}: {1}

- ISS.0134.0091 Unable to set password in Password Manager with key {0}: {1}
- ISS.0134.0094 Unable to start JMS connection alias "{0}". The server will attempt to reconnect every {1} seconds: {2}
- ISS.0134.0096 Could not create Destination to Ping Connection Alias :{0}.
- ISS.0134.0098 JMS connection alias "{0}" is unable to check the JNDI namespace for updates to the ConnectionFactory "{1}": {2}
- ISS.0134.0099 JMS connection alias "{0}" is updating because of changes made to ConnectionFactory "{1}" in the JNDI namespace.
- ISS.0134.0100 Unable to restart JMS connection alias "{0}" after updating ConnectionFactory "{1}": {2}
- ISS.0134.0102 Unable to register event listener. Update functionality not available for this JNDI provider: {0}
- ISS.0134.0103 The JNDI event listener for JMS connection alias "{0}" has been disconnected. The system will try to reconnect.
- ISS.0134.0104 JMS connection alias "{0}" is dynamically setting polling interval to {1} milliseconds.
- ISS.0134.0105 JMS connection alias "{0}" is unable to retrieve polling interval, so the default value of {1} minutes will be used instead: {2}
- ISS.0134.0106 Starting JMS connection alias with Guaranteed Multisend policy. Broker list = {0}; Multisend Broker count = {1}.
- ISS.0134.0114D Refreshed session for consumer: {0}
- Explanation** Integration Server refreshed the session for the specified message consumer.
- Action** None.

ISS.0134.0115D	Initialized default Session pool for alias "{0}"; max size "{1}"
Explanation	Integration Server created a default Session Pool for the specified JMS connection alias.
Action	No action required.
ISS.0134.0116D	Initialized MessageProducer pool for alias "{0}"; destination "{1}"; max size "{2}"
Explanation	For the specified JMS connection alias, Integration Server created a MessageProducer Pool for the specified destination.
Action	No action required.
ISS.0134.0117E	Unable to initialize MessageProducer pool for alias "{0}"; destination "{1}": {2}
Explanation	An error occurred while initializing the MessageProducer Pool for the specified JMS connection alias and destination. The error most likely occurred because the destination does not exist or cannot be accessed.
Action	Verify that the specified destination exists and that you have sufficient privileges to access the destination. If the JMS connection alias uses a JNDI provider for administered objects, verify that the JNDI provider is available.
ISS.0134.0999	JMS subsystem unexpected error: {0}
ISS.0134.9045E	Unable to create trigger "{0}". Invalid or non-ascii characters in NSName.
Explanation	The WS endpoint trigger could not be created because the Web service endpoint alias name includes characters that are not valid for an element name.
Action	Change the name of the alias so that it does not include any characters that Integration Server considers to be reserved or invalid for element names. Refer to the Designer or webMethods Developer documentation for a list of reserved or invalid characters.
ISS.0134.9082E	The client side queue cannot be used with a send and wait request if the reply destination is a temporary queue.
Explanation	The useCSQ parameter is set to true and the replyToDestinationName is blank or specifies a temporary queue.
Action	If you want Integration Server to route messages to the client side queue when the JMS provider is not available leave useCSQ set to true and specify a queue that is not temporary. That is, specify values for the destinationNameReplyTo and destinationTypeReplyTo input parameters.

ISS.0134.9083E	The pub.jms:sendBatch service is not supported with this provider.
Explanation	The connectionAliasName parameter specifies a JMS connection alias that uses a JMS provider that is not supported with the pub.jms:sendBatch service.
Action	Change the value of the connectionAliasName parameter to specify a JMS connection alias that uses a supported JMS provider.
ISS.0134.9084E	The pub.jms:sendBatch service is not supported with connection factories that use the multisend guaranteed or multisend best effort Broker cluster policies.
Explanation	The connectionAliasName parameter specifies a JMS connection alias that uses a connection factory to which the multisend guaranteed or multisend best effort Broker cluster policy is applied. The pub.jms:sendBatch service cannot be used with connection factories that have these policies.
Action	Change the value of the connectionAliasName parameter to specify a JMS connection alias that does not use a connection factory to which the multisend guaranteed or multisend best effort Broker cluster policy is applied.
ISS.0134.9350E	UM admin operation failed [{0}]: {1}
Explanation	The specified admin operation could not be completed on Universal Messaging due to the listed error. Integration Server will perform admin operations on Universal Messaging when Designer is being used to manage destinations and durable subscribers on Universal Messaging.
Action	Use the provided error message to determine why the admin operation could not be completed.
ISS.0135.0004E	Unable to delete JNDI configuration file: {0}
Explanation	An error occurred while deleting the JNDI properties file.
Action	Ensure that another user is not currently accessing the JNDI properties file.
ISS.0135.9001E	JNDIConfigurationManager was unable to load properties file "{0}": {1}
Explanation	The JNDI Configuration manager cannot load the properties file for a JNDI alias.
Action	Ensure that the JNDI properties file exists in the Integration Server config directory.
ISS.0135.9002E	Unable to load JNDI Properties. Invalid properties file: {0}
Explanation	The JNDI configuration manager cannot load the properties file for a JNDI alias because the JNDI properties file is empty.
Action	Ensure that the JNDI properties file exists in the Integration Server configuration directory and is not empty.

ISS.0135.9003E	JNDI configuration file already exists: {0}
Explanation	Integration Server cannot save the JNDI alias because a JNDI configuration file for the alias already exists.
Action	Specify a different name for the JNDI alias.
ISS.0135.9004E	No properties found for JNDI alias {0}
Explanation	The JNDI properties file for the specified JNDI alias does not exist.
Action	Ensure that the JNDI properties file exists in the Integration Server config directory and is not empty.
ISS.0135.9005E	Unable to load JNDI Properties. File not found: {0}
Explanation	Integration Server cannot load the properties file for the JNDI alias.
Action	Ensure that the JNDI properties file is present in the Integration Server config directory and that the properties file is valid.
ISS.0135.9006E	JNDI configuration file does not exist: {0}
Explanation	An error occurred while deleting the JNDI properties file.
Action	Ensure that the JNDI properties file exists in the Integration Server config directory.
ISS.0137.0002W	Scheduler: Unable to get pool for ISInternal
Explanation	Integration Server was unable to get the ISInternal JDBC connection pool.
Action	Configure the ISInternal functional alias (specified on the Settings > JDBC Pools screen in Integration Server Administrator) and assign a valid JDBC connection pool to it.
ISS.0137.0006E	Scheduler: Error initializing scheduler: {0}
Explanation	Integration Server encountered an error while initializing the database in which information about scheduled jobs is stored.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
ISS.0137.0007E	Scheduler: Unable to get a connection to the database.
Explanation	Integration Server was unable to get a connection from the JDBC connection pool.
Action	Use Integration Server Administrator to increase the maximum number of connections available in the JDBC connection pool that is assigned to the ISInternal functional alias.

ISS.0137.0010E	Scheduler: Resources unavailable: {0}
Explanation	Scheduler thread throttle, which is the percentage of server threads the scheduler function is permitted to use, is reached. Integration Server cannot execute a scheduled task because there are no threads available.
Action	Use Server Administrator to increase the maximum number of connections available in the JDBC pool that is assigned to the ISInternal functional alias.
ISS.0137.0011E	Scheduler: Exception: {0}
Explanation	Integration Server encountered an error while retrieving a scheduled task from the database and executing it.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
ISS.0137.0012E	Scheduler: Error inserting task into database: {0}
Explanation	Integration Server encountered an error while adding a new scheduled task to the database.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
ISS.0137.0013E	Scheduler: Error updating task in database: {0}
Explanation	Integration Server encountered an error while updating the information of a scheduled task in the database.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
ISS.0137.0014E	Scheduler: Error updating status in database: {0}
Explanation	Integration Server encountered an error while updating the status of a scheduled task in the database.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
ISS.0137.0016E	Scheduler: Exception getting task IDs from database: {0}
Explanation	Integration Server encountered an error while retrieving the IDs of scheduled tasks associated with a user.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.

ISS.0137.0017E	Scheduler: Exception getting tasks from database: {0}
Explanation	Integration Server encountered an unexpected SQLException while retrieving the scheduled tasks from the database.
Action	Ensure that the database is available and configured to execute scheduled tasks.
ISS.0137.0018E	Scheduler: Exception while invoking "{0}": {1}
Explanation	Integration Server encountered a runtime exception while invoking a scheduled task.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
ISS.0137.0021E	Invalid database vendor type: {0}
Explanation	The database driver for the ISInternal functional alias is not valid.
Action	Go to the Settings > JDBC Pools page in Integration Server Administrator and set ISInternal's pool alias to use one of the listed database drivers.
ISS.0137.0022E	No ISInternal JDBC Pool
Explanation	The ISInternal functional alias is not configured.
Action	Configure the ISInternal functional alias (specified on the Settings > JDBC Pools screen in Integration Server Administrator) and assign a valid JDBC connection pool to it.
ISS.0137.0023E	Could not get connection
Explanation	Integration Server attempted to acquire a JDBC connection, but no connections are available in the pool assigned to the ISInternal functional alias.
Action	Use Server Administrator to increase the maximum number of connections available in the JDBC pool that is assigned to the ISInternal functional alias.
ISS.0137.0024E	Namespace Dependency Manager is disabled
Explanation	Unable to determine if the service executed by a scheduled task refers to other services that are unavailable.
Action	Contact Software AG Global Support.
ISS.0137.0025E	Found unresolved dependent services: {0}
Explanation	Integration Server was unable to create or run the scheduled task because the service scheduled to run contains a reference to a service that cannot be located.
Action	Update the scheduled task to specify a correct reference to the dependent service. Note: Integration Server performs reference validation for services only when the <code>watt.server.scheduler.ignoreReferenceValidation</code> configuration parameter is set to true. The default is false.

ISS.0137.0026E	User {0} is disabled
Explanation	The user a scheduled task is set to run as is disabled. The task will not run.
Action	Enable the user or modify the task to run as a different user.
ISS.0137.0027E	User {0} is removed
Explanation	The user associated with a scheduled task has been removed.
Action	Add the user or change the scheduled task to execute with an enabled user.
ISS.0137.0028W	Could not complete last run
ISS.0137.0029E	Rolling back due to scheduler thread throttle reached: {0}
Explanation	A scheduled task attempted to use more threads than the maximum number allowed by the Scheduler thread throttle limit. Any scheduled tasks that attempt to execute under these circumstances will fail.
Action	Use Integration Server Administrator to increase the Scheduler thread throttle under Settings > Resources > Edit Resource Settings > Server Thread Pool.
ISS.0137.0030E	...<truncated>
Explanation	Integration Server encountered an error during the execution of a scheduled task.
Action	Read through the contents of the error logs and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
ISS.0137.0031E	Invalid Target {0}
Explanation	A scheduled task is set to run on a host that is not currently a member of the Integration Server cluster.
Action	Modify the scheduled task to run on a member of the cluster.
ISS.0137.0032E	Invalid task ID {0}
Explanation	Internal error.
Action	Contact Software AG Global Support.

ISS.0137.0033E	Errors encountered while initializing Scheduler. Scheduled tasks will not run. Check the logs for more information.
Explanation	Integration Server encountered an error either while initializing the scheduler or while connecting to the database in which information about scheduled jobs is stored. As a result, scheduled tasks will not run.
Action	Read through the contents of the error logs and take corrective steps. After correcting the issue that caused the error, restart the Integration Server.
ISS.0137.0034E	Unknown Service: {0}. Scheduled task will not run.
Explanation	The service configured to execute for a scheduler does not exist in the Integration Server.
Action	Ensure that the service is available in the Integration Server.
ISS.0138.0350E	Test of CentraSite connection failed.
Explanation	Integration Server encountered an exception while connecting to CentraSite.
Action	Ensure the parameters that Integration Server uses to connect to CentraSite are correct. Specifically, check the URL pointing to CentraSite (including the port), the user name, and password.
ISS.0139.0056W	Error: Default keystore alias "DEFAULT_IS_KEYSTORE" cannot be created. Details: {0}
Explanation	Error while creating DEFAULT_IS_KEYSTORE alias at the first startup of Integration Server.
Action	<p><p>The following lists the actions you can take:</p><p>1. Ensure that the keystore file 'keystore.jks' is present in the Integration Server_directory\common\conf directory.</p><p>2. Ensure that the keystore has not expired.</p><p>3. Contact Software AG Global Support.</p></p>
ISS.0139.0057W	Error: Default truststore alias "DEFAULT_IS_TRUSTSTORE" cannot be created. Details: {0}
Explanation	Error while creating DEFAULT_IS_TRUSTSTORE alias at the first start up of Integration Server.
Action	<p><p>The following lists the actions you can take:</p><p>1. Ensure that the truststore file platform_truststore.jks is present in the Integration Server_directory\common\conf\ directory.</p><p>2. Ensure that the truststore has not expired.</p><p>3. Contact Software AG Global Support.</p></p>

ISS.0139.9002E	Error: invalid keystore or truststore configuration file "{0}".
Explanation	Configuration file related to keystore is corrupted.
Action	Create a keystore alias.
ISS.0139.9003I	Keystore alias "{0}" saved successfully.
ISS.0139.9004W	Keystore alias "{0}" saved successfully. Warning: before using the keystore, you must create a password for at least one of its key aliases. Please edit the keystore alias configuration and add one or more valid key alias passwords.
Explanation	The key aliases are not configured. Before using the keystore, you must create a password for at least one of its key aliases.
Action	Edit the keystore alias configuration and add at least one valid key alias passwords.
ISS.0139.9005E	Keystore alias "{0}" saved successfully. An error occurred while loading the keystore in memory, please edit the keystore alias configuration. Details: {1}
Explanation	An error occurred while loading the keystore in memory.
Action	Edit the keystore alias configuration. Make sure that the keystore location is correct and keystore exists on the file system. Then, make sure that the configuration file related to the keystore is valid.
ISS.0139.9006W	Keystore alias "{0}" saved successfully. Warning: the following key aliases "{1}" cannot be used because they do not have passwords. Please edit the keystore alias configuration and add password(s) for the appropriate key alias(es).
Explanation	Some key aliases are not configured.
Action	Edit the keystore alias configuration and add passwords for the corresponding key aliases.
ISS.0139.9007W	Keystore alias "{0}" saved successfully. Warning: the following key aliases "{1}" have been removed from the keystore alias configuration.
Explanation	Few key aliases were removed from the keystore alias configuration.
Action	Refresh the keystore alias.
ISS.0139.9012E	Error: cannot save the keystore alias "{0}".
Explanation	Either the keystore location is invalid, or the key aliases passwords do not consist of ASCII characters.
Action	Make sure that the keystore location is valid and the key aliases passwords consist of valid ASCII characters.

ISS.0139.9013E	Error: keystore "{0}" not found.
Explanation	The configuration file related to keystore alias is unavailable.
Action	Make sure that the configuration file related to the keystore alias exists in the directory ../config/security/keystore.
ISS.0139.9014E	Error: keystore "{0}" not found. Details: {1}.
Explanation	Invalid keystore location.
Action	Make sure that the location of the keystore is correct; the key aliases passwords are valid; and the configuration file exists, and it is not corrupted.
ISS.0139.9016W	Keystore "{0}" was reloaded successfully. Warning: you must provide the password for at least one key alias in the keystore before using it. Please edit the keystore alias configuration and add at least one valid key alias password.
Explanation	Either the keystore does not contain any key aliases, or a key alias password is not provided. You must provide the password for at least one key alias in the keystore before using it.
Action	Check whether the keystore has any key aliases. If not, then add key alias in the keystore. If there are key aliases in the keystore, then edit the keystore alias configuration and add at least one valid key alias password.
ISS.0139.9017W	Keystore "{0}" reloaded successfully. Warning: the following key aliases "{1}" cannot be used because they do not have a password. Please edit the keystore alias configuration and add one or more valid key alias passwords.
Explanation	Key alias must be configured in advance.
Action	Edit the keystore alias configuration and add one or more valid key alias passwords.
ISS.0139.9018W	Keystore "{0}" reloaded successfully. Warning: the following key aliases "{1}" have been removed from the alias configuration.
Explanation	Key alias must be configured in advance.
Action	Edit the keystore alias configuration and add one or more valid key alias passwords.
ISS.0139.9019E	Error: cannot reload keystore "{0}". Details: {1}.
Explanation	Keystore alias does not map to a valid keystore.
Action	Make sure that the keystore location is correct and keystore exists on the file system. Make sure that the configuration file related to the keystore is valid.

ISS.0139.9020E	Error: cannot reload keystore "{0}".
Explanation	Configuration file does not exist.
Action	Make sure that the configuration file, which corresponds to the truststore alias, exists in the directory ../config/security/keystore.
ISS.0139.9022E	Error: unable to delete the keystore alias "{0}".
Explanation	Keystore does not exist.
Action	Make sure that the keystore location is correct and the keystore exists on the file system.
ISS.0139.9023E	Error: invalid keystore alias name "{0}".
Explanation	Keystore alias is null or empty.
Action	Make sure that the keystore alias is not null or empty.
ISS.0139.9024E	Error: cannot load the keystore pointed to by keystore alias "{0}", because of invalid password(s) for key alias(es) "{1}".
Explanation	Invalid key alias password.
Action	Make sure that the key aliases passwords are correct.
ISS.0139.9025E	Error: invalid key alias "{0}".
Explanation	The key alias is invalid.
Action	Make sure that the key alias exists in the keystore.
ISS.0139.9026E	Error: unable to look up the password for the key alias "{1}" in the keystore '{0}'.
Explanation	Invalid key alias password.
Action	Make sure that the key alias password is correct.
ISS.0139.9028E	Truststore alias "{0}" saved successfully. An error occurred while loading the truststore in memory, please edit the truststore alias configuration. Details: {1}.
Explanation	Configuration file is corrupted.
Action	Make sure that the configuration file, which corresponds to the truststore alias is valid.

ISS.0139.9029E	Error: cannot save the truststore alias "{0}".
Explanation	Truststore location is invalid.
Action	Make sure that the truststore location is valid.
ISS.0139.9030E	Error: truststore "{0}" not found.
Explanation	The configuration file related to truststore alias is unavailable.
Action	Make sure that the configuration file related to the truststore alias exists in the directory ../config/security/keystore.
ISS.0139.9031E	Error: truststore "{0}" not found. Error: {1}.
Explanation	Either the truststore location, or the configuration file is invalid.
Action	Make sure that the location of the truststore is correct; the truststore alias password is correct; and the configuration file exists, and it is not corrupted.
ISS.0139.9033E	Error: cannot reload truststore "{0}". Details: {1}.
Explanation	Either the keystore location is invalid, or the key aliases are modified.
Action	Make sure that the keystore location is valid and the key alias is not modified.
ISS.0139.9034E	Error: cannot reload truststore "{0}".
Explanation	Configuration file does not exist.
Action	Make sure that the configuration file, which corresponds to the truststore alias, exists in the directory ../config/security/keystore.
ISS.0139.9036E	Error: unable to delete the truststore alias "{0}".
Explanation	Configuration file does not exist.
Action	Make sure that the configuration file for the truststore alias exists in the directory ../config/security/keystore.
ISS.0139.9037E	Error: invalid truststore alias name "{0}".
Explanation	Invalid truststore name.
Action	Make sure that the truststore name is not null or empty.

ISS.0139.9038E	Error: cannot retrieve data for the truststore "{0}".
Explanation	Keystore is not loaded or initialized properly.
Action	Make sure that keystore is valid and the alias refers to the valid keystore location.
ISS.0139.9039E	Error: cannot retrieve trusted certificates from the truststore pointed to by truststore alias "{0}". Details: {1}.
Explanation	Truststore is not initialized or loaded properly.
Action	Reload the truststore alias and then make sure that the configuration file exists for the truststore alias.
ISS.0139.9041E	Error: cannot retrieve the key for alias "{0}" from the keystore pointed to by keystore alias "{1}". Details: {2}.
Explanation	Key alias entry in the keystore is not valid.
Action	Make sure that the key alias entry in the keystore is valid. For example, the certificate chain is available or the algorithm of the private key matches to the algorithm of the PublicKey in the end entity Certificate (at index 0).
ISS.0139.9043E	Error: cannot retrieve the certificate for alias "{0}" from the truststore pointed to by truststore alias "{1}". Unsupported certificate type "{2}".
Explanation	Invalid certificate type.
Action	Make sure that the certificate configured by the key alias is X509 Certificate.
ISS.0139.9044E	Error: the alias has been modified from "{0}" to "{1}".
Explanation	Keystore alias does not map to a valid keystore.
Action	Make sure that the keystore alias refers to a valid keystore.
ISS.0139.9045E	Error: either the alias name "{0}" or the configuration file name "{1}" is incorrect.
Explanation	Configuration file does not exist.
Action	Make sure that the configuration file exists for the alias in the directory ../config/security/keystore.
ISS.0139.9047E	Password for following key aliases must be ASCII characters: {0}
Explanation	The key alias password consists of non-ASCII characters.
Action	Make sure that the key alias password consists of valid ASCII characters.

ISS.0139.9051E	Error: cannot load the keystore/truststore configuration file "{0}". Details:{1}.
Explanation	Keystore alias does not map to a valid keystore.
Action	Make sure that the keystore alias refers to a valid keystore. In addition, verify that the configuration file related to the keystore alias is valid. Make sure that the security provider is installed and registered with Integration Server if you use a security provider.
ISS.0139.9052E	Error: invalid keystore/truststore configuration file "{0}".
Explanation	Configuration file does not exist.
Action	Make sure that the configuration file, which corresponds to the truststore alias, exists in the directory ../config/security/keystore.
ISS.0139.9053E	Error: ISKeyStoreManager initialization failed. Cannot create the keystore configuration directory "{1}".
Explanation	Keystore directory does not exist.
Action	Keystore location is invalid. Make sure that the keystore directory exists.
ISS.0139.9054E	Error: alias has been modified from "{0}" to "{1}".
Explanation	Keystore alias does not map to a valid keystore .
Action	Make sure that the keystore alias refers to a valid keystore.
ISS.0139.9055E	Error: either the alias name "{0}" or the configuration file name "{1}" is incorrect.
Explanation	Configuration file is corrupted.
Action	Make sure that the configuration file, which corresponds to the truststore alias, exists in the directory ../config/security/keystore.
ISS.0139.9058I	Default keystore alias for Integration Server.
ISS.0139.9059I	Default truststore alias for Integration Server.
ISS.0141.0001E	Unable to create JMS URI for WS Endpoint Alias "{0}": {1}
Explanation	The Web service endpoint alias does not contain the information needed to construct a JMS URI.
Action	Use the information in the exception to update the alias. For example, you may need to make changes to the provider Web service endpoint alias or edit the SOAP-JMS trigger used with the alias.

- ISS.0141.0002E** **Unable to create WS Endpoint Trigger: {0}**
- Explanation** Integration Server could not create a WS endpoint trigger using the information in the provider Web service endpoint alias.
- Action** In Integration Server Administrator, use the information provided in the exception to edit the provider Web service endpoint alias
-
- ISS.0141.0101W** **WS-Policy file {0} with policy ID {1} is invalid. Details: {2}**
- Explanation** The WS-Policy file added to the policy repository is not valid. Integration Server has moved the policy file to the IntegrationServer/config/wss/policies/invalid folder.
- Action** Correct the invalid WS-Policy file in the IntegrationServer/config/wss/policies/invalid folder to make it valid and move it back into the main policy repository directory.
-
- ISS.0141.0103W** **Web service descriptor {0} is not available because the WS-Policy file {1} with policy ID {2} attached to the WSD is deleted.**
- Explanation** The Web service descriptor is not available because the WS-Policy file attached to the Web service descriptor is deleted or moved from the policy repository.
- Action** The following lists the actions you can take:
- 1) Ensure that the WS-Policy that is attached to the Web service descriptor resides in the policy repository.
 - OR-
 - 2) Edit the Web service descriptor so that it no longer uses the deleted WS-Policy file.
-
- ISS.0141.0107W** **Web service descriptor {0} is not available because the policy ID in WS-Policy file {1} is changed from {2} to {3}.**
- Explanation** The Web service descriptor is not available because the policy ID of the WS-Policy file attached to the Web service descriptor has changed.
- Action** The following lists the actions you can take:
- 1) Change the policy id of the WS-Policy that is attached to the Web service descriptor to what it was previously.
 - 2) Edit the Web service descriptor by re-attaching the WS-Policy file with the updated policy ID.

ISS.0141.0108E	Transport header "{0}" is invalid and will not be added to the message. Transport headers must be Strings.
Explanation	In the name/value pair supplied as a transport header, the name and the value must be of type String. If a transport header has a name or value that is not of type String, the header will not be included in the message.
Action	Change the transport header so that the name and value are both of type String.
ISS.0141.0109W	Could not deploy consumer Web service descriptor {0} for handling asynchronous responses. Connectors generated for this consumer Web service descriptor can only be used for handling responses synchronously. Cause: {1}.
Explanation	The consumer Web service descriptor specified in the message could not be deployed to handle asynchronous responses. See the error message for more details about the cause of the failure.
Action	If the error message indicates that the error can be resolved by changing the WSDL, change or correct the WSDL used for creating the consumer Web service descriptor and recreate the consumer. If the error still occurs, contact Software AG Global Support.
ISS.0141.9106E	Received a null response.
Explanation	An internal error occurred while processing the Web service request.
Action	Contact Software AG Global Support.
ISS.0141.9107E	Received unsupported content-encoding: {0}
Explanation	The Web service response used the specified content-encoding, which is not supported.
Action	Ensure that the Web service request specifies a supported content-encoding for the response.
ISS.0141.9108E	An HTTP transport error occurred. Error Code: {0}, Error Message: {1}
Explanation	An error occurred while sending a Web service response. The error code and message portions of the error contain details about the error.
Action	Contact Software AG Global Support.
ISS.0141.9109E	Access Denied
Explanation	A Web service request has arrived over an HTTP or HTTPS port, but the port access check has failed for the Web service descriptor. This means that the provider Web service descriptor name is either missing from the Allow list or is present in the Deny List, depending on how access to the port is defined.
Action	If access to this Web service is to be allowed over this port, ensure that the provider Web service descriptor name is either removed from the port's deny list or added to the port's allow list.

ISS.0141.9208E	Could not deploy the Web service descriptor {0}. Cause: {1}
Explanation	Integration Server could not deploy the Web service descriptor. Typical reasons are: 1) The WS-Policy that is attached to the provider Web service descriptor does not exist. 2) The module required to handle the attached WS-Policy does not exist. 3) The "rampartConfigProperties" parameter, which is in the axis2.xml file, is locked. If it is not one of these reasons, refer to the error message, which lists the cause.
Action	The following lists the actions you can take for one of the typical causes: 1) Ensure the WS-Policy that is attached to the Web service descriptor resides in the policy repository: (webMethods_directory)/IntegrationServer/config/wss 2) Ensure the module required to handle the attached WS-Policy resides in the (webMethods_directory)/IntegrationServer/config/wss/modules subdirectory. 3) Ensure the "rampartConfigProperties" parameter in the axis2.xml file is not locked. The axis2.xml file resides (webMethods_directory)/IntegrationServer/config/wss/modules subdirectory. For all other reasons, refer to the cause listed in the error message and respond accordingly.
ISS.0141.9211E	Received a plain text response: {0}
Explanation	A Web service call expected a SOAP Response but instead received a plain text response. The actual responseText is returned within a SOAP fault.
Action	Determine why the Web service provider did not return a SOAP response. It is possible that an incorrect endpoint address was used or an error occurred on the Web service provider.
ISS.0141.9213E	Unknown web services reliable messaging sequence {0} specified for endpoint URI {1}.
Explanation	A reliable messaging sequence with the specified sequence key corresponding to the specified endpoint URI does not exist.
Action	Specify a valid sequence key for the specified endpoint URI.
ISS.0141.9214E	A duplicate web services reliable messaging sequence {0} specified for endpoint URI {1}.
Explanation	A reliable messaging sequence with the specified sequence key and endpoint URI already exists.
Action	Specify a valid sequence key for the specified endpoint URI.

ISS.0141.9215E	A closed web services reliable messaging sequence {0} specified for endpoint URI {1}.
Explanation	The reliable messaging sequence with the specified sequence key and endpoint URI is closed.
Action	Specify a valid sequence key for the specified endpoint URI.
ISS.0141.9216E	A terminated web services reliable messaging sequence {0} specified for endpoint URI {1}.
Explanation	The reliable messaging sequence with the specified key and endpoint URI is terminated.
Action	Specify a valid sequence key for the specified endpoint URI.
ISS.0141.9217E	Web services reliable messaging is not enabled for consumer web Services Descriptor {0}.
Explanation	Reliable messaging is not enabled for the specified consumer web service descriptor.
Action	Specify a valid consumer web service descriptor for which reliable messaging is enabled or enable reliable messaging for the specified consumer web service descriptor.
ISS.0142.0003W	User {0} issued request to cancel the thread. Thread id - {1}
Explanation	Integration Server received a request to cancel an executing thread.
Action	No action is required.
ISS.0142.0004W	User {0} issued request to kill the thread. Thread id - {1}
Explanation	Integration Server received a request to kill an executing thread.
Action	No action is required.
ISS.0142.0018E	The <code>watt.server.threadKill.timeout.enabled</code> parameter is set to true; however, the property that enables the thread kill facility, <code>watt.server.threadKill.enabled</code>, is set to false.
Explanation	The ability to cancel or kill service threads is controlled by the <code>watt.server.threadKill.enabled</code> property. If you want to be able to cancel or kill threads, this property must be set to true, which is the default setting.
Action	Set <code>watt.server.threadKill.enabled</code> to true so that a flow step will not run beyond its specified timeout period.

ISS.0145.0000E Unable to start Integration Server in quiesce mode. No quiesce port was specified.

Explanation Integration Server cannot be started from the command line with the -quiesce switch unless a quiesce port is specified.

Action Start Integration Server using either the Start menu (on Windows) or the startup.sh script (on UNIX). Then, specify the quiesce port that Integration Server should use to enter and exit quiesce mode.

ISS.0145.0009E Unable to quiesce this Integration Server. Exception: {0}

Explanation An error occurred while switching this server to quiesce mode.

Action Check the Integration Server server and error logs. Take appropriate corrective action for the reported asset type. Then, try switching to quiesce mode again.

ISS.0145.0012W Handler "{0}" cannot disable asset type "{1}". Exception: {2}

Explanation While entering quiesce mode, Integration Server encountered an error when attempting to disable the specified asset type.

Action In the Integration Server Administrator, manually disable the assets of the reported asset type.

ISS.0145.0015E Unable to return Integration Server to active mode. Exception: {0}

Explanation An error occurred while switching this Integration Server to active mode.

Action Check the Integration Server server and error logs. Then, take the appropriate corrective action.

ISS.0145.0018W Handler "{0}" was unable to restore state of "{1}" asset type. Exception: {2}

Explanation While exiting quiesce mode, Integration Server could not restore the state of the specified asset type.

Action In the Integration Server Administrator, manually enable the assets of the reported asset type.

ISS.0145.0020W Unable to shut down the quiesce mode manager. Exception: {0}.

Explanation Integration Server could not save the quiesce properties in the quiesce configuration file. The quiesce.cnf file either does not exist or is corrupt.

Action Delete the quiesce.cnf file from the Integration Server_directory\config directory. Then, restart the server and specify the quiesce port again.

ISS.0145.0022E	Unable to save the configuration after setting quiesce port to {0}. Exception: {1}
Explanation	An error occurred when the quiesce port was changed and Integration Server attempted to save the changes.
Action	Set the quiesce port to a valid port. If the error recurs, contact Software AG Global Support.
ISS.0145.0023E	Unable to validate quiesce port {0}. Port does not exist.
Explanation	The quiesce port has been deleted.
Action	Specify the port alias of an existing valid port.
ISS.0145.0024E	Unable to validate quiesce port {0}. Port is not enabled.
Explanation	The quiesce port is disabled.
Action	Enable the quiesce port.
ISS.0145.0025E	Unable to validate quiesce port {0}. Port is not associated with WmRoot or WmPublic package.
Explanation	The quiesce port does not reside in either the WmRoot or the WmPublic package.
Action	Specify the port alias of a valid quiesce port that resides in either the WmRoot package or the WmPublic package.
ISS.0145.0027E	Unable to validate quiesce port {0}. Port type is incorrect.
Explanation	The specified quiesce port does not belong to the HTTP or HTTPS protocol.
Action	Specify the port alias of a valid quiesce port of type HTTP or HTTPS.
ISS.0145.0028E	Unable to validate quiesce port {0}. Port is suspended.
Explanation	The quiesce port is suspended.
Action	Resume the quiesce port.
ISS.0145.0029E	Unable to validate quiesce port {0}. Port does not have the necessary access mode.
Explanation	The quiesce port's access mode is set to Deny+.
Action	Change the quiesce port's access mode to Allow.

ISS.0145.0302W	Unable to suspend {0}. Reason: {1}
Explanation	While entering quiesce mode, Integration Server could not suspend the specified trigger.
Action	Check the server log for details and manually suspend the trigger.
ISS.0145.0306W	Unable to resume {0}. Reason: {1}
Explanation	While entering quiesce mode, Integration Server could not resume the specified trigger, even though the package containing trigger is enabled.
Action	Check the server log for details and manually enable the trigger.
ISS.0145.0315W	Quiesce timeout limit of {0} minutes has expired. {1} services are running. Proceeding with disabling the packages.
Explanation	Integration Server is proceeding with disabling packages even though some long-running services are still running. One or more of these services might fail.
Action	In the Integration Server Administrator, check which services are still running and make sure those services have completed before attempting to quiesce this server again. Alternatively, increase the quiesce timeout limit.
ISS.0145.0504E	Cannot disable packages. Exception: {0}
Explanation	While entering quiesce mode, Integration Server could not disable packages.
Action	Check the Integration Server server log for details. Then, in the Integration Server Administrator, manually disable the packages.
ISS.0145.0506E	Package "{0}" is not loaded.
Explanation	While starting in quiesce mode, Integration Server could not load the WmRoot or WmPublic package.
Action	Start the server in active mode, and then enter quiesce mode.
ISS.0145.0509E	Unable to restore state of packages. Exception: {0}
Explanation	While exiting quiesce mode, Integration Server could not restore the state of packages.
Action	Check the Integration Server server log for details. Then, in the Integration Server Administrator, manually enable or disable the packages as necessary.

ISS.0145.0511E	Cannot enable package "{0}".
Explanation	While exiting quiesce mode, Integration Server could not enable the specified package.
Action	In the Integration Server Administrator, manually enable the specified package.
ISS.0145.0603E	Cannot enable listener "{0}" in quiesce mode. Exception: {1}
Explanation	Integration Server could not start the quiesce listener.
Action	Ensure that the listener is enabled in the listener.cnf configuration file.
ISS.0145.0604E	Cannot disable listener "{0}" in quiesce mode. Exception: {1}
Explanation	Integration Server could not stop the quiesce listener.
Action	Ensure that the listener is disabled in the listener.cnf configuration file.
ISS.0145.0700E	Unable to process scheduled task. Exception: {0}
Explanation	Integration Server encountered a runtime error of unknown cause while attempting to quiesce a scheduled task.
Action	Check the server log for details and take the appropriate corrective steps.
ISS.0145.0701E	Unable to retrieve scheduled task "{0}" from database. Exception: {1}
Explanation	Either the database server is down or Integration Server is no longer connected to the database.
Action	Make sure the connection between Integration Server and the database is active.
ISS.0145.0702E	Unable to retrieve scheduled task from database. Exception: {0}
Explanation	Either the database server is down or Integration Server is no longer connected to the database.
Action	Make sure the connection between Integration Server and the database is active.
ISS.0145.0705E	Unable to resume scheduled task "{0}" in quiesce mode. Exception: {1}
Explanation	The state of the scheduled task may be inconsistent between the database and Integration Server. This can occur when changes are made to the database outside of Integration Server.
Action	Check the state of the task in the database. In the Integration Server Administrator, change the state of the task to match the state reported in the database.

ISS.0145.0711E	Unable to retrieve host name. Exception: {0}
Explanation	The Integration Server you are attempting to quiesce is part of a cluster, and there is an issue with the cluster's configuration.
Action	Verify your clustering environment and cache configuration according to the guidelines in the webMethods Integration Server documentation.
ISS.0145.0803W	Cannot disable JMS connection alias "{0}". Reason: {1}
Explanation	While entering quiesce mode, Integration Server could not disable the specified JMS connection alias.
Action	In the Integration Server Administrator, manually disable the JMS connection alias.
ISS.0145.0805W	Cannot enable JMS connection alias "{0}". Reason: {1}
Explanation	While exiting quiesce mode, Integration Server could not enable the specified JMS connection alias.
Action	In the Integration Server Administrator, manually enable the JMS connection alias.
ISS.0145.0902E	Unable to shut down the guaranteed delivery outbound Job Manager. Exception: {0}
Explanation	While entering quiesce mode, Integration Server could not shut down the outbound Job Manager.
Action	In the Integration Server Administrator, manually disable the guaranteed delivery outbound Job Manager.
ISS.0145.0905E	Unable to initialize the guaranteed delivery inbound Job Manager. Exception: {0}
Explanation	While exiting quiesce mode, Integration Server could not initialize the guaranteed delivery inbound Job Manager.
Action	In the Integration Server Administrator, manually enable the guaranteed delivery inbound Job Manager.
ISS.0145.0906E	Unable to initialize the guaranteed delivery outbound Job Manager. Exception: {0}
Explanation	While exiting quiesce mode, Integration Server could not initialize the guaranteed delivery outbound Job Manager.
Action	In the Integration Server Administrator, manually enable the guaranteed delivery outbound Job Manager.

ISS.0146.9001E	Key cannot be empty.
Explanation	The Key field must not be empty while adding a global variable.
Action	Provide a valid Key for the global variable.
ISS.0146.9002E	Value cannot be empty.
Explanation	The Value field must not be empty while adding a global variable.
Action	Provide a valid value for global variable.
ISS.0146.9003E	Global variable {0} already exists.
Explanation	Global variable key must be unique.
Action	Provide a unique key for the global variable.
ISS.0146.9004E	Global variable {0} does not exist.
Explanation	You attempted to delete or edit a global variable that does not exist.
Action	Ensure that the global variable exists before attempting to edit or delete it.
ISS.0146.9005	Global Variable key cannot contain any of these characters:{0}
Explanation	The global variable key that you specified contains special characters other than period (.) or underscore(_).
Action	Ensure that the global variable key does not contain any special characters other than period or underscore(_).
ISS.0146.9006E	Global variable key cannot exceed 255 characters.
Explanation	The global variable key that you specified contains more than 255 characters.
Action	Ensure that length of the global variable key is less than or equal to 255.
ISS.0146.9007E	Global variable value cannot exceed 255 characters.
Explanation	The global variable value that you specified contains more than 255 characters.
Action	Ensure that length of the global variable value is less than or equal to 255.
ISS.0147.9001E	SFTP server alias {0} already exists.
Explanation	The SFTP server alias name that you specified already exists in Integration Server.
Action	Specify an SFTP server alias name that does not exist in Integration Server.

ISS.0147.9002E	SFTP server alias {0} does not exist.
Explanation	The specified SFTP server alias does not exist in Integration Server.
Action	Ensure that the SFTP server alias name you specified is correct and that this SFTP server alias exists in Integration Server.
ISS.0147.9003E	Cannot retrieve the host key from location {0}. Details: Corrupt or unknown public key file format.
Explanation	The specified host key file contains the public key of the SFTP server in an unsupported format.
Action	Ensure that the host key file contains the public key in the supported (openssh) format.
ISS.0147.9004E	Cannot find the private key file {0}.
Explanation	Integration Server is unable to find the private key file at specified location.
Action	Ensure that the private key file exists at the specified location.
ISS.0147.9005E	Private key file {0} already exists in Integration Server.
Explanation	The specified private key file already exists in Integration Server.
Action	Specify a different private key file.
ISS.0147.9006E	User alias {0} does not exist.
Explanation	The specified SFTP user alias does not exist in Integration Server.
Action	Ensure that the SFTP user alias name you specified is correct and that this SFTP user alias exists in Integration Server.
ISS.0147.9007E	User alias {0} already exists.
Explanation	The SFTP user alias name that you specified already exists in Integration Server.
Action	Specify an SFTP user alias name that does not exist in Integration Server.
ISS.0147.9008E	Cannot read host key from location {0}.
Explanation	Integration Server is unable to read the host key file from the location you specified.
Action	Specify a valid host key file location to which Integration Server has the required permission for reading.

ISS.0147.9009E	Cannot write the public key to file {0}.
Explanation	Integration Server is unable to write the host key file to the specified location.
Action	Ensure that Integration Server has the required permission and enough disk space to write the host key to the specified location.
ISS.0147.9010E	Cannot get host key from server {0}. Details: {1}
Explanation	Integration Server is unable to retrieve the host key from the specified (arg0) SFTP server.
Action	Ensure that the SFTP server is configured and running on the specified host-port.
ISS.0147.9011E	Test of user alias {0} Fail. Details: {1}
Explanation	Testing of SFTP user alias (arg0) failed due to error (arg1).
Action	Ensure that the SFTP user alias information is correct and that the SFTP server is running on the specified host and port.
ISS.0147.9012E	Cannot delete SFTP server alias {0} because the following SFTP user alias(es) are using it : {1}.
Explanation	Integration Server cannot delete the SFTP server alias (arg0) because the SFTP user alias(es) [arg1] are using it.
Action	Ensure that the SFTP server alias that you want to delete is not included in any SFTP user alias definition.
ISS.0148.9010E	A valid short value must be specified for "{0}".
Explanation	The value of short data type that you entered for field {0} while calling the service is invalid.
Action	Ensure that the value specified for the field {0} is a valid short value.
ISS.0148.9011E	A valid boolean value must be specified for "{0}".
Explanation	The value of boolean data type that you entered for field {0} while calling the service is invalid.
Action	Ensure that the value specified for the field {0} is a valid boolean value.

ISS.0148.9012E	A valid double value must be specified for "{0}".
Explanation	The value of double data type that you entered for field {0} while calling the service is invalid.
Action	Ensure that the value specified for the field {0} is a valid double value.
ISS.0148.9013E	A valid float value must be specified for "{0}".
Explanation	The value of float data type that you entered for field {0} while calling the service is invalid.
Action	Ensure that the value specified for the field {0} is a valid float value.
ISS.0148.9014E	A valid character value must be specified for "{0}".
Explanation	The value of character data type that you entered for field {0} while calling the service is invalid.
Action	Ensure that the value specified for the field {0} is a valid character value.
ISS.0148.9015E	A valid byte value must be specified for "{0}".
Explanation	The value of byte data type that you entered for field {0} while calling the service is invalid.
Action	Ensure that the value specified for the field {0} is a valid byte value.
ISS.0148.9016E	A valid long value must be specified for "{0}".
Explanation	The value of long data type that you entered for field {0} while calling the service is invalid.
Action	Ensure that the value specified for the field {0} is a valid long value.
ISS.0148.9017E	{1} is not a valid value for {0}. Allowed values are {2}
Explanation	The value {1} specified for field {0} while calling a service is not available in the pick list {2}.
Action	Ensure that the value specified for the field {0} is in the pick list {2}.
ISS.0149.0001E	Message size exceeded the limit of {0} MB.
Explanation	Enterprise Gateway Server could not process the request because the message associated with the request is larger than the size allowed in the Enterprise Gateway rule.
Action	Either reduce the message size of the request or increase the message size limit in the filter for the rule.

ISS.0149.0002D	Enterprise Gateway rules processing has started on URL {0} and IP address {1} at time {2}.
Explanation	Enterprise Gateway Server has started processing rules.
Action	No action is needed.
ISS.0149.0003D	Processing Enterprise Gateway rule "{0}".
Explanation	Enterprise Gateway Server has started processing the specified rule.
Action	No action is needed.
ISS.0149.0004D	Processing Enterprise Gateway rule filter "{0}".
Explanation	Enterprise Gateway Server has started processing the specified rule filter.
Action	No action is needed.
ISS.0149.0005E	A rule violation occurred for Enterprise Gateway rule "{0}" for filter "{1}": {2}.
Explanation	Enterprise Gateway Server could not process the request because the request met a filter condition defined in the Enterprise Gateway rule.
Action	Check the filter conditions for the specified rule and either change the conditions or modify the request so a rule violation does not occur.
ISS.0149.0006E	A rule violation occurred for Enterprise Gateway rule "{0}".
Explanation	Enterprise Gateway Server could not process the request because its type did not match the request type configured in the Enterprise Gateway rule.
Action	Modify the request so it matches one of the configured request types.
ISS.0149.0007E	Denial of Service by IP address limit was reached for IP address {0}.
Explanation	Enterprise Gateway Server could not process the request because an Enterprise Gateway Denial of Service limit was reached for this IP address.
Action	Delete the IP address from the Enterprise Gateway deny list.
ISS.0149.0008W	IP address {0} is unblocked.
Explanation	Enterprise Gateway Server is again accepting requests from this IP address because the Enterprise Gateway Denial of Service block interval has elapsed.
Action	No action is needed.

ISS.0149.0009W	IP address {0} is blocked for a duration of {1} minutes.
Explanation	Enterprise Gateway Server has blocked incoming requests from this IP address because the number of requests from this address has exceeded the specified Enterprise Gateway Denial of Service limits.
Action	Wait for the IP address to become unblocked when the block interval elapses. If an IP address is blocked too often, reevaluate the "maximum requests" and "maximum requests in progress" limits.
ISS.0149.0011E	Requests from IP address {0} have exceeded the maximum in-progress limit of {1}.
Explanation	Enterprise Gateway Server will deny or block incoming requests from this IP address because the number of requests from this address has exceeded the specified Enterprise Gateway Denial of Service limit for in-progress requests.
Action	Delete the IP address from the Enterprise Gateway deny list.
ISS.0149.0012D	Denial of Service clean-up task has executed.
Explanation	Periodically, Enterprise Gateway Server starts a task to clear old Denial of Service entries from the queue.
Action	No action is needed.
ISS.0149.0013E	Global Denial of Service limits were reached: {0}.
Explanation	Enterprise Gateway Server will block incoming requests received from all IP addresses because the number of requests has exceeded the specified Enterprise Gateway global Denial of Service limits.
Action	Wait for the block interval to elapse.
ISS.0149.0014E	Requests from IP address {0} have exceeded the maximum request limit of {1} in {2} seconds.
Explanation	Enterprise Gateway Server will deny or block incoming requests from this IP address because the number of requests from this address has exceeded the specified Enterprise Gateway Denial of Service limit for requests allowed in a specified time period.
Action	Delete the IP address from the Enterprise Gateway deny list.
ISS.0149.0015S	Requests from all IP addresses will be blocked for a duration of {0} minutes.
Explanation	Enterprise Gateway Server will block incoming requests received from all IP addresses for the indicated interval because the number of requests has exceeded the specified Enterprise Gateway global Denial of Service limits.
Action	Wait for the block interval to elapse.

ISS.0149.0016E	OAuth token is not present in the request header.
Explanation	Enterprise Gateway Server could not process the request because the OAuth token is not present in the request header.
Action	Either disable the OAuth filter or ensure that the request contains the OAuth token.
ISS.0149.0017E	Maximum in-progress limit of {0} has been exceeded.
Explanation	Enterprise Gateway Server will block incoming requests received from all IP addresses because the number of requests has exceeded the specified Enterprise Gateway global Denial of Service limit for in-progress requests.
Action	Wait for the block interval to elapse.
ISS.0149.0018E	Maximum requests limit of {0} in {1} seconds has been exceeded.
Explanation	Enterprise Gateway Server will block incoming requests received from all IP addresses because the number of requests has exceeded the specified Enterprise Gateway global Denial of Service limit for requests allowed in a specified time period.
Action	Wait for the block interval to elapse.
ISS.0149.0019E	The header "{0}" is not present in the request header.
Explanation	Enterprise Gateway Server could not process the request because the indicated header is not present in the request header.
Action	Either disable the mobile application protection filter or ensure that the request has the required mobile device type, application name, and application version request headers.
ISS.0149.0020E	Mobile application version {0} is {1} {2} for application "{3}" and device type "{4}".
Explanation	Enterprise Gateway Server could not process the request because the request matches the indicated mobile application protection filter condition. As a result, the request is in violation of the Enterprise Gateway rule.
Action	Reevaluate the mobile application protection filter conditions if desired.
ISS.0149.0501CS	Exception occurred while sending a notification for Enterprise Gateway rule "{0}": {1}.
Explanation	Enterprise Gateway Server could not send an alert notification indicating that a rule violation occurred for the reason indicated in the exception.
Action	Check the server error logs and take corrective steps.

ISS.0149.0502CS	Exception occurred while invoking "{0}": {1}.
Explanation	Enterprise Gateway Server could not invoke the flow service to notify users that a rule violation occurred for the reason indicated in the exception.
Action	Check the server error logs and take corrective steps.
ISS.0149.0503W	Alert notification for Enterprise Gateway rule "{0}" was not sent. No alert options were found for the rule.
Explanation	Enterprise Gateway Server could not send an alert notification indicating that a rule violation occurred because no alert options were specified for the rule to indicate how to handle the alert.
Action	Check the server error logs and take corrective steps.
ISS.0149.0504W	Alert notification for Enterprise Gateway rule "{0}" was not sent. SMTP server configuration is not valid.
Explanation	Enterprise Gateway Server could not send an alert notification for the Enterprise Gateway rule because the server is not configured to send emails.
Action	Check the settings on the Settings > Resources screen under Email Notification. If your server is not configured to send emails, use Integration Server Administrator to configure an SMTP port.
ISS.0149.9001E	Enterprise Gateway rule "{0}" already exists.
Explanation	Enterprise Gateway Server could not create the rule because an Enterprise Gateway rule with this name already exists.
Action	Specify a unique name for the Enterprise Gateway rule.
ISS.0149.9002E	Enterprise Gateway rule "{0}" was not found
Explanation	Enterprise Gateway Server could not find the specified Enterprise Gateway rule. Either the rule does not exist on this server or the specified rule name is incorrect.
Action	Ensure that the Enterprise Gateway rule exists on this Enterprise Gateway Server and that the name specified for the rule is correct.
ISS.0149.9003E	Mobile application protection filter conditions were not specified.
Explanation	Enterprise Gateway Server failed to create or update an Enterprise Gateway rule that has a mobile application protection filter enabled because no filter conditions were specified.
Action	Either specify one or more conditions or disable this filter.

ISS.0149.9004E	Mobile application "{0}" was not found.
Explanation	Enterprise Gateway Server did not recognize the application name provided in the mobile application protection filter because the application is not in the Mobile Applications list.
Action	Either specify a different mobile application or use the Mobile Application Protection Options screen in Integration Server Administrator to add the application.
ISS.0149.9005E	Mobile device type "{0}" was not found.
Explanation	Enterprise Gateway Server did not recognize the device type provided in the mobile application protection filter because the device is not in the Device Types list.
Action	Specify a different device type or use the Mobile Application Protection Options screen in Integration Server Administrator to add the device type.
ISS.0149.9006E	Condition "{0}" is not supported.
Explanation	Enterprise Gateway Server failed to apply the condition to this Enterprise Gateway rule because the condition character specified in the mobile application protection filter is not valid.
Action	Ensure that the condition is one of the following characters: =,<,>,<=,>=,<>
ISS.0149.9007E	Mobile application version "{0}" is not valid.
Explanation	Enterprise Gateway Server failed to apply the condition to this Enterprise Gateway rule because the application version specified in the mobile application protection filter is not formatted correctly.
Action	Ensure that the application version is in the following format: <major-version>.<minor-version>.<sub-minor-version>.<patch>
ISS.0149.9008E	Mobile applications list was not updated. The following applications are specified in one or more rules: {0}.
Explanation	Enterprise Gateway Server failed to remove mobile applications from the application list because the applications are specified in a filter condition for one or more rules.
Action	Before you attempt to remove a mobile application from the list, make sure the application is not specified in a filter condition in any rules.
ISS.0149.9009E	Device types list was not updated. The following device types are specified in one or more rules: {0}.
Explanation	Enterprise Gateway Server failed to remove device types from the device types list because the device types are specified in a filter condition for one or more rules.
Action	Before you attempt to remove a device type from the list, make sure the device type is not specified in a filter condition in any rules.

ISS.0149.9010E	Service name "{0}" is not valid.
Explanation	A flow service was specified for Enterprise Gateway Server to invoke when an Enterprise Gateway rule violation occurs, but the service name is not valid.
Action	Specify a valid, fully qualified service name.
ISS.0150.9001	Missing required parameter: "{0}".
Explanation	A required parameter was not supplied.
Action	Supply the specified required parameter.
ISS.0150.9002	Unable to create port: "{0}".
Explanation	Integration Server cannot create the port because an exception occurred.
Action	Use the specified exception to determine why the port could not be created.
ISS.0150.9003	Unable to set the IP access mode for the port: {0}
Explanation	An error occurred during an attempt to set the IP access mode for the port.
Action	Use the exception returned by the error message to determine the cause of the error.
ISS.0150.9004	Unable to set the IP access list for the port: {0}
Explanation	An error occurred while attempting to set the IP access list for the port.
Action	Use the exception returned by the error message to determine the cause of the error.
ISS.0150.9005	Unable to set the URL access mode for the port: {0}
Explanation	An error occurred during an attempt to set the URL access mode for the port.
Action	Use the exception returned by the error message to determine the cause of the error.
ISS.0150.9006	Unable to set the URL access list for the port: {0}
Explanation	An error occurred during an attempt to set the URL access list for the port.
Action	Use the exception returned by the error message to determine the cause of the error.
ISS.0150.9008	The primary port cannot be changed.
Explanation	An update operation attempted to make changes to the primary port of the Integration Server. The primary port cannot be updated.
Action	To make changes to the port that is assigned to be the primary port, specify another port as the primary port. Then make changes to the port that was previously the primary port.

ISS.0150.9009	Invalid protocol. The webMethods Platform Manager subsystem does not support the protocol "{0}".
Explanation	A create or update operation for port settings specified an protocol that is not supported by the webMethods Platform Manager subsystem in Integration Server.
Action	Specify a protocol supported by the webMethods Platform Manager subsystem in Integration Server.
ISS.0150.9010	Cannot change port protocol [from {0} to {1}].
Explanation	An update operation attempted to change the protocol for the port. Once a port is created, the protocol cannot be changed.
Action	To change the protocol used with a particular port, first delete the port. Then, recreate the port with the new protocol.
ISS.0150.9011	Package "{0}" is not loaded or is not enabled.
Explanation	A create or update port operation attempted to create or change a port in a package that either does not exist or is not enabled.
Action	Make sure the package exists and is enabled before performing the create or update port operation.
ISS.0150.9012	Unable to disable port: {0}
Explanation	An exception occurred during an attempt to disable the port
Action	Review the exception to determine why the port could not be disabled.
ISS.0150.9013	No port found with unique ID {0}.
Explanation	A read, update, or delete port operation supplied a port ID that does not exist.
Action	Verify the instance ID that the Software AG Platform Manager associates with the port. To do this, refresh the port list on the Software AG Platform Manager.
ISS.0150.9014	The port was created. However, the access configuration was not set: {0}
Explanation	A create port operation was partially successful. The port was created and some configuration settings were established. However, establishing some or all of the access configuration settings failed. The port will be disabled if it is not already.
Action	Review the exception to determine why the access configuration could not be set.

ISS.0150.9015	The port was partially updated. However, the access configuration was not set: {0}
Explanation	An update port operation was partially successful. Some settings were updated. However, updates to some or all of the access configuration settings failed. The port will be disabled if it is not already.
Action	Review the exception to determine why the access configuration settings could not be updated.
ISS.0150.9020	The diagnostic port must be associated with the WmRoot package. Package {0} is invalid.
Explanation	A create or update operation for the diagnostic port attempted to assign a package other than WmRoot to the diagnostic port. This is not allowed. The diagnostic port must be associated with the WmRoot package.
Action	Specify the WmRoot package when creating or updating the diagnostic port.
ISS.0150.9021	Cannot create diagnostic port. A diagnostic port with port number {0} and ID {1} already exists. Each Integration Server can have one diagnostic port only.
Explanation	An operation attempted to create a diagnostic port. However, the Integration Server already has a diagnostic port. Each Integration Server can have one diagnostic port only.
Action	To create a new diagnostic port, delete the existing diagnostic port first.
ISS.0150.9022	Unable to update port. The diagnostic port cannot be changed to a standard port.
Explanation	An operation attempted to change a diagnostic port to a standard port. A diagnostic port cannot be created in this way because the type of port may not be changed.
Action	To create a standard port on an assigned diagnostic port, first delete the existing diagnostic port and then create a standard port.
ISS.0150.9023	Unable to update port. The standard port cannot be changed to a diagnostic port.
Explanation	An operation attempted to change a standard port to a diagnostic port. A diagnostic port cannot be created in this way because the type of port may not be changed.
Action	To create a diagnostic port on an assigned port, first delete the existing port and then create a diagnostic port.
ISS.0150.9024	Invalid keystore alias {0}
Explanation	A create or update port operation specified a keystore alias that does not exist.
Action	Make sure to specify the name of an existing keystore alias. Verify that the name of the keystore alias is spelled correctly.

ISS.0150.9025	Invalid key alias {0}
Explanation	A create or update port operation specified a key alias that does not exist.
Action	Make sure to specify the name of an existing key alias. Verify that the name of the key alias is spelled correctly
ISS.0150.9026	Invalid truststore alias {0}
Explanation	A create or update port operation specified a truststore alias that does not exist.
Action	Make sure to specify the name of an existing truststore alias. Verify that the name of the truststorealias is spelled correctly.
ISS.0150.9027	Cannot enable port. Keystore alias is empty. Specify a keystore alias for the port or a define a default SSL keystore alias for the Integration Server.
Explanation	A create or update port operation did not specify a keystore alias and there is not a default SSL keystore alias for the Integration Server. An HTTPS port requires a keystore alias.
Action	Either define a keystore alias or specify a default SSL keystore alias for the Integration Server. The default SSL keystore alias is the keystore alias specified during configuration of the SSL authentication credentials for the Integration Server. To use a defined keystore alias with the HTTPS port, specify that keystore alias in the create or update operation. To use the Integration Server's default SSL keystore alias with the HTTPS port, do not supply keystore alias information for the create or update operations.
ISS.0150.9028	Cannot enable port. Keystore alias is empty. Specify a key alias for the port or a define a default SSL key alias for the Integration Server.
Explanation	A create or update port operation did not specify a key alias and there is not a default SSL key alias for the Integration Server. An HTTPS port requires a key alias.
Action	Either define a key alias or specify a default SSL key alias for the Integration Server. The default SSL key alias is the keys alias specified during configuration of the SSL authentication credentials for the Integration Server. To use a defined key alias with the HTTPS port, specify that keystore alias in the create or update operation. To use the Integration Server's default SSL key alias with the HTTPS port, do not supply key alias information for the create or update operations.
ISS.0150.9030	Unable to assign primary port: "{0}".
Explanation	An attempt to change the primary port failed because the selected port does not meet the primary port criteria mentioned in the wrapped exception.
Action	Select a port that meets the primary port requirements. Alternatively, change the chosen port to meet the primary port requirements mentioned in the wrapped exception.

ISS.0150.9037E	Unable to assign quiesce port: "{0}".
Explanation	An attempt to change the quiesce port failed because the selected port does not meet the quiesce port criteria mentioned in the wrapped exception.
Action	Select a port that meets the quiesce port requirements. Alternatively, change the chosen port to meet the quiesce port requirements mentioned in the wrapped exception.
ISS.0150.9999	The webMethods Platform Manager subsystem experienced an unexpected error: {0}
Explanation	An error occurred in the webMethods Platform Manager subsystem that runs in Integration Server.
Action	Contact Software AG Global Support.
ISS.0151.9001	Missing required parameter: "{0}".
Explanation	A required parameter is missing.
Action	Contact Software AG Global Support.
ISS.134.9215E	Connection Count must be a positive integer, and it must not exceed {0}.
Explanation	The value of the Maximum execution threads property is less than the value of the Connection count property. The Maximum execution threads value must be greater than or equal to the Connection count value.
Action	Change the value of the Maximum execution threads property to be greater than or equal to the Connection count property. Alternatively, change the value of the Connection count property to be less than or equal to the Maximum execution threads property.
ISS.134.9216E	The Multiple Connection feature is not supported when using non-durable Topics.
Explanation	Only JMS triggers that subscribe to queues and/or topics (durable subscribers) can use multiple connections to receive messages from the JMS provider. A JMS trigger that subscribes to a topic that is a non-durable subscriber cannot use multiple connections to receive messages from the JMS provider. That is, only a JMS trigger that subscribes to queues and/or topics that are durable subscribers can have a connection count greater than 1.
Action	Set Connection count to 1. Alternatively, remove any topics that are non-durable subscribers from the list of destinations to which the JMS trigger subscribes.

ISS.141.9102E	No transport info in MessageContext
Explanation	An internal error occurred while processing the Web service request.
Action	Contact Software AG Global Support.
ISS.141.9103E	No MessageFormatter in MessageContext
Explanation	An internal error has occurred while processing the Web service request.
Action	Contact Software AG Global Support.
ISS.141.9209E	Could not deploy the Web service descriptor {0} as policy with id {1} is not found.
Explanation	Integration Server was unable to execute the Web service connector because the WS-Policy attached to the Web service connector is either missing or invalid. Valid policies should be in the policy repository, that is, saved in the following directory: (webMethods_directory)/IntegrationServer/config/wss
Action	<p>If you want to secure the Web service with the policy, locate the WS-Policy and add it to the policy repository. You can check the policy repository's invalid subdirectory to see whether the policy was moved because it is invalid. If the policy is in the invalid directory, correct it to make it valid, and move it back into the main policy repository directory.</p> <p>If the WS-Policy does not exist, detach the WS-Policy from the Web service descriptor. If you still need to secure the Web service, create a WS-Policy that provides the security you want, add it to the policy repository, and attach it to the Web service descriptor.</p>
ISS.150.9036E	Port Alias cannot be edited.
Explanation	Once a port is created, the port alias cannot be changed.
Action	None. However, if you want an existing port to use a different port alias, you must delete the port and then recreate it using the new port alias.
ISS.88.9435E	The specified document type {0} does not exist.
Explanation	The document type that you supplied as input to the service does not exist.
Action	Check the name of the document type that you are attempting to use to ensure you have the correct name. Then, specify a document type name that exists and re-invoke the service.

ISS.88.9436E	The structure of the document instance does not match the specified document type, {0}; validation failed.
Explanation	The service validates a document instance using the IS document type you supplied. However, the document instance does not have the structure specified by the IS document type. Validation of the document instance failed.
Action	Check the IS document type you are attempting to use to ensure you specifying the correct one. Then, re-invoke the service specifying the correct IS document type for the document instance.
ISS.88.9437E	Unexpected exception occurred: {0}
Explanation	The Web services stack, which is Integration Server code that performs Web service functionality, encountered an unexpected error.
Action	Read through the contents of the messages, and take corrective steps. If you are unable to resolve the issue, contact Software AG Global Support.
ISS.88.9438E	Unexpected exception occurred while creating a fault message.
Explanation	Integration Server encountered an unexpected error. It was attempting to add a child fault element to a non-existing parent fault element.
Action	Contact Software AG Global Support.
ISS.88.9439E	The query for the fault element failed because its corresponding parent element is absent from the SOAP message.
Explanation	You attempted to query a SOAP message for SOAPFault elements. However, there is no parent element in the SOAP message for the queried item. For example, Integration Server will issue this error if you attempt to query for a fault code when there is no SOAPFault in the SOAP message.
Action	Ensure the SOAP message that you are attempting to process is valid. If the SOAP message is valid, contact Software AG Global Support.
ISS.88.9440E	The structure of the SOAP fault detail Document is not valid, resulting in the invalid attribute name: {0}; validation failed.
Explanation	A document representing the SOAP fault detail was passed to a service that handles SOAP faults, for example, the pub.soap.handler:addFaultBlock. The fault detail Document that was passed to the service has an invalid structure. An example of an invalid structure would be if the name in the Document instance that corresponds to an attribute is "@ns1:", but there is no local name for the attribute. In this example, there should have been additional text after the ":" that corresponds to a valid local name.
Action	Ensure that IS document instance for the SOAP fault detail is a proper representation of valid XML structure. Correct the SOAP fault detail Document and execute the service again.

ISS.88.9441E **Validation requested, but no IS document type specified; validation failed.**
Explanation You specified that you want an input Document to be validated. However, you have not provided the document type that the service should use for validation. As a result, the validation failed.
Action Invoke the service again. This time pass the document type to use for validation in the appropriate input parameter.

ISS.88.9442E **Service executed with invalid input parameter {0} : {1}**
Explanation Execution of the service failed because the specified input parameter was passed an invalid value. The invalid value is displayed in the message.
Action Invoke the service again, this time specifying a valid value for the input parameter.

IS_RUNTIME_EXCEPTION – runtime exception occurred. see error log for details.

JBS.0122.0006 **Package "{0}" has deploy directory contents, but does not have a dependency on 'WmJBoss'**

JNDI_CONTEXT_NOT_INITIALIZED – Cannot perform JNDI operation: JNDI context is not initialized.

JSONCODER_UNSUPPORTED_TOKEN – Invalid state. Unsupported token found in the JSON input stream.

Explanation The input stream does not contain valid JSON content.
Action Provide valid JSON content in the input stream.

LVLCHNG_COMP_CODE_INVALID – Supplied "componentCode" is not valid.

LVLCHNG_COMP_CODE_NULL – Parameter "componentCode" is required and it cannot be null.

LVLCHNG_LISTENER_NULL – Parameter "listener" is required and it cannot be null.

NESTED_TRANS_NOT_SUPPORTED – another tran active. nested tran disabled in settings

NO_LOADERS_FOUND Loader is not configured for the cache {1} contained within the cache manager {0}.

NO_MORE_EVENTS_AVAILABLE – No more xml events available

NO_OUTPUT_SIGNATURE – no output signature

NO_TRANS_FOR_THREAD – current thread not with any transaction

NO_WRITERS_FOUND Writer is not configured for the cache {1} contained within the cache manager {0}.

OAUTH_ONE_PREVENTS_OTHERS – {0} may not be specified if {1} is "{2}".

Explanation The service failed because the specified input variable contains an invalid value combination. The invalid combination is listed in the message text.

Action Enter a valid value combination for the input variable.

OTHER_THAN_SPACE_CHARACTERS_ENCOUNTERED – Other than space characters encountered

PARSER_MUST_BE_ON_START_ELEMENT_TO_READ_NEXT_TEXT – parser must be on START_ELEMENT to read next text

PASSWORDBADOLDPASSWORDS – Invalid user name or password.

Explanation The specified user credentials are not valid.

Action Provide a valid user name and password.

PASSWORD_EMPTY Password is empty. User(s) {0} not added.

Explanation The Password field requires a value.

Action Enter a valid password.

PASSWORD_UPDT_EMPTY – Password is empty. Password was not changed.

Explanation The Password field requires a value.

Action Enter a valid password.

PIECMNE0000	Error initializing ISAttributeValues. ISMonitoringContext cannot be null.
Explanation	The ISAttributeValues cannot be initialized because ISMonitoringContext is null.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0001	Error retrieving AttributeValue. The metaModelTypeID cannot be null or empty.
Explanation	The AttributeValue cannot be retrieved because metaModelTypeID is null or empty.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0002	Error retrieving AttributeValue. The attributeID cannot be null or empty.
Explanation	The AttributeValue cannot be retrieved because metaModelTypeID is null or empty.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0003	Error retrieving AttributeValue. The attributeID cannot be null or empty.
Explanation	The AttributeValue cannot be retrieved because attributeID is null or empty.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0004	Error retrieving attribute values. The attributeQuery object cannot be null.
Explanation	The attribute values cannot be retrieved because the attributeQuery object is null.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0005	Error retrieving attribute values. The modelType is invalid.
Explanation	The attribute values cannot be retrieved because the modelType is invalid.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0006	Error while destroying ISMonitoringContext. The ISMonitoringContext cannot be null.
Explanation	The ISMonitoringContext could not be destroyed because it is null.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0007	Error destroying ISMonitoringContext. Invalid ISMonitoringContext provided.
Explanation	The ISMonitoringContext could not be destroyed because it is not a valid instance of ISMonitoringContext.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0008	Error getting meta model. The metaModelTypeId cannot be null.
Explanation	The meta model could not be retrieved because the metaModelTypeId is null or empty.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0009	Error validating ISMonitoringContext. ISMonitoringContext cannot be null.
Explanation	The ISMonitoringContext could not be validated because it is null.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0010	Error validating ISMonitoring Context. Invalid ISMonitoringContext provided.
Explanation	The ISMonitoringContext could not be validated because it is not an instance of MonitoringContext.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0011	Error validating ISMonitoringContext. ISInputContext object is null.
Explanation	The ISMonitoringContext cannot be validated because the supplied ISInputContext object is null.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0012	Error validating ISMonitoringContext. ISInputContext is invalid.
Explanation	The ISMonitoringContext cannot be validated because the supplied ISInputContext object is invalid.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0013	Error validating ISMonitoringContext. Context host attribute cannot be null or empty.
Explanation	The ISMonitoringContext cannot be validated because the context has a host attribute that is null or empty.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0014	Error validating ISMonitoringContext. Context port attribute is invalid.
Explanation	The ISMonitoringContext cannot be validated because the context has an invalid port attribute.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0015	Error initializing ISModelInstance. ISMonitoringContext is null.
Explanation	An ISModelInstance cannot be initialized because the ISMonitoringContext is null.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0016	Error getting model instances. The metaModelTypeName is null or empty.
Explanation	The model instances cannot be retrieved because a metaModelTypeName is null or empty.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0017	Error getting model instances. Invalid metaModelTypeName.
Explanation	The model instances cannot be retrieved because a valid metaModelTypeName was not supplied.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0018	Error while initializing ISServerModel. ISMonitoringContext is null.
Explanation	The ISServerModel cannot be initialized because ISMonitoringContext is null.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0019	Error getting attributes for Integration Server. The modelInstanceListToQuery cannot be null.
Explanation	Integration Server attributes cannot be retrieved because the modelInstanceListToQuery was null .
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0020	Error getting Integration Server attributes. The attributeListToQuery cannot be null.
Explanation	The Integration Server attributes cannot be retrieved because the attributeListToQuery was null.
Action	This is an internal error. Contact Software AG Global Support.
PIECMNE0021	Error getting attributeID. The attributeID cannot be null.
Explanation	The Integration Server attribute cannot be retrieved because the attributeID was null.
Action	This is an internal error. Contact Software AG Global Support.

PIECMNE0022	Error while pinging Integration Server. Invalid ISMonitoringContext.
Explanation	The ping of Integration Server failed because the provided ISMonitoringContext is invalid.
Action	This is an internal error. Contact Software AG Global Support.
PIESIME0000	Unable to access Integration Server:{0}
Explanation	An error occurred while attempting to access Integration Server. The details of the error will replace the {0} in the message text.
Action	Use the details of the error to resolve the error preventing a connection to Integration Server.
PIESIME0001	Integration Server is unavailable:{0}
Explanation	An error occurred while attempting to access Integration Server. The details of the error will replace the {0} in the message text.
Action	Use the provided error information to correct the issue and try again.
PIESIME0002	An error occurred while invoking a service on Integration Server:{0}
Explanation	An error occurred while invoking a service on Integration Server. The details of the error will replace the {0} in the message text.
Action	Use the supplied error information to correct the condition causing the error. Then, reissue the service request.
PIESIME0004	Port object cannot be null.
Explanation	ISContext cannot be created because the Port object is null.
Action	Provide a valid Port object that is not null.
PIESIME0005	UserCredentials username/password cannot be null.
Explanation	ISContext cannot be created because the username/password is null.
Action	Make sure that the username/password has a valid value and is not null.
PIESIME0006	Missing required ClientAuthType for SSL.
Explanation	ISContext cannot be created because the ClientAuthType required for SSL is null.
Action	Make sure the ClientAuthType has a valid value and is not null.

PIESIME0007	Invalid protocol. The webMethods Platform Manager subsystem does not support the protocol "{0}".
Explanation	A create or update operation for port settings specified a protocol that is not supported by the webMethods Platform Manager subsystem in Integration Server.
Action	Specify a protocol supported by the webMethods Platform Manager subsystem in Integration Server.
PIESIME0008	Unable to connect Integration Server:{0}
Explanation	An error occurred while attempting to connect Integration Server. The details of the error will replace the {0} in the message text.
Action	Use the error details to resolve the error that is preventing a connection to Integration Server.
PIESIME0009E	Port Validation Error :{0}
Explanation	The port configuration is not valid.
Action	Make sure the port configuration is valid.
PIESIME0010	Port Validation Error, Invalid URLAccess Service :{0}
Explanation	The port is not valid because the supplied URLAccess does not have a valid service name.
Action	Specify a valid service name for URLAccess.
PIESIME0011	Port Validation Error, Invalid IPAccess Hostname :{0}
Explanation	The port is not valid because the IPAccess Hostname is not valid.
Action	Specify a valid value for the IPAccess Hostname.
PIESIME0012	Port Validation Error, Port Alias already exists : {0}
Explanation	The port is not valid because the port alias is used by another port on Integration Server.
Action	Specify a port alias that is unique for the Integration Server.
PIESIME0013	Port Validation Error, Primary port may not be disabled in an update.
Explanation	A primary port cannot be disabled as part of an update.
Action	Do not attempt to disable the primary port as part of updating a port. If you want to disable the port acting as the primary port, you must first designate another port as the primary port. Then you can disable the port that was previously the primary port.

PIESIME0014 **Port Validation Error, Primary port package name must be WmRoot. Invalid Package Name : {0}**

Explanation The primary port must be associated with the WmRoot package.

Action Make sure the primary port is associated with the WmRoot package.

PIESIME0015 **Invalid server configuration parameter names: {0}**

Explanation The server configuration parameter names must begin with "watt."

Action Rename the server configuration parameter names so that they begin with "watt."

PIESIME0016 **A required configuration parameter is missing: {0}**

Explanation A required configuration parameter is missing.

Action Check the logs.

PIESIME0017 **Configuration details for COMMON-JDBC cannot be null.**

Explanation While creating a JDBC pool alias, the configuration details for COMMON-JDBC cannot be null.

Action Provide valid JDBC pool alias configuration details.

PIESIME0018 **JDBC pool alias cannot be null or empty.**

Explanation While creating or updating a JDBC pool, the pool alias cannot be null or empty.

Action Provide a valid value for the JDBC pool alias.

PIESIME0019 **Invalid configuration type.**

Explanation The configuration type provided while creating the JDBC pool alias must be of type COMMON-JDBC.

Action Provide a valid configuration of type COMMON-JDBC.

PIESIME0020 **Invalid configuration type.**

Explanation The configuration type provided while updating the JDBC pool alias must be of type COMMON-JDBC.

Action Provide a valid configuration of type COMMON-JDBC.

PIESIME0021	JDBC pool cannot be null.
Explanation	While creating a JDBC pool alias,the pool configuration details cannot be null.
Action	Provide valid configuration details while creating or updating a JDBC pool.
PIESIME0022	{0} cannot be null or empty.
Explanation	The specified value must not be null or empty
Action	Provide a valid value.
PIESIME0023	Enter a positive number for {0}
Explanation	The specified value must not be a negative number.
Action	Specify a positive number.
PIESIME0024	JDBC configuration instance id is missing.
Explanation	JDBC configuration instance id is required and must be specified.
Action	Provide a valid JDBC configuration instance id.
PIESIME0025	MaxSize must be greater than 0.
Explanation	The value provided for MaxSize must be greater than 0.
Action	Ensure that the value provided for MaxSize is greater than 0.
PIESIME0026	Configuration details for COMMON-JDBC cannot be null.
Explanation	While updating a JDBC pool alias, the configuration details for COMMON-JDBC cannot be null.
Action	Provide valid JDBC pool alias configuration details.
PIESIME0027	JDBC pool cannot be null.
Explanation	While updating a JDBC pool alias,the pool configuration details cannot be null.
Action	Provide valid configuration details while creating or updating a JDBC pool.
PIESIME0028	MinSize must be less than or equal to MaxSize.
Explanation	Minimum connections must be less than or equal to maximum connections.
Action	Ensure that the value provided for MinSize is less than or equal to MaxSize.

PIESIME0029	Invalid SMTP port.
Explanation	SMTP port should be greater than 0.
Action	Change the SMTP port to a valid value greater than 0.
PIESIME0030	Unable to retrieve truststores.
Explanation	Integration server is unable to retrieve the truststores.
Action	Ensure that there are truststores installed in Integration server.
PIESIME0031	SMTP settings are already defined.
Explanation	Unable to define new SMTP settings because the SMTP settings are already defined.
Action	To specify new SMTP settings, update the existing SMTP configuration.
PIESIME0032	The truststore {0} does not exist.
Explanation	The specified truststore alias cannot be found.
Action	Ensure that the specified truststore exists in Integration Server.
PIESIME0033	Configuration details for COMMON-DBFUNCTION cannot be null.
Explanation	While updating a functional alias, the configuration details for COMMON-DBFUNCTION cannot be null.
Action	Provide valid functional alias configuration details.
PIESIME0034	Invalid configuration type.
Explanation	The configuration type provided while updating the functional alias must be of type COMMON-DBFUNCTION.
Action	Provide a valid configuration of type COMMON-DBFUNCTION.
PIESIME0035	Functional alias cannot be null
Explanation	While updating a functional alias, the functional alias configuration details cannot be null.
Action	Provide valid configuration details while updating a functional alias.

PIESIME0037	Configuration details for COMMON-JNDI cannot be null.
Explanation	While configuring a JNDI provider alias, the configuration details for COMMON-JNDI cannot be null.
Action	Provide valid JNDI provider alias configuration details.
PIESIME0038	Invalid configuration type.
Explanation	The configuration type provided while configuring a JNDI provider alias must be of type COMMON-JNDI.
Action	Provide a valid configuration of type COMMON-JNDI.
PIESIME0039	SMTP server not configured.
Explanation	SMTP server is not configured in Integration Server.
Action	Configure SMTP server in Integration Server.
PIESIME0040	Functional alias specified is not valid.
Explanation	The functional alias specified in the input must be valid.
Action	Ensure that the functional alias specified in the input is valid.
PIESIME0041	Functional alias description cannot be modified.
Explanation	The functional alias description specified in the input cannot be modified.
Action	Ensure that the functional alias description specified in the input is not modified.
PIESIME0042	The functional alias {0} cannot be associated with the embedded database pool.
Explanation	The embedded database pool can only be used with IS Internal and Cross Reference database components.
Action	Associate the functional alias with any JDBC connection pool other than the embedded database pool.
PIESIME0043	Invalid configuration details for COMMON-JMS. Invalid value for {0}.
Explanation	The value specified for COMMON-JMS configuration {0} is not valid.
Action	Specify valid values for all the mandatory attributes in COMMON-JMS configuration.

PIESIME0045	Configuration details for COMMON-JMS cannot be null.
Explanation	The configuration details for COMMON-JMS cannot be null.
Action	Provide valid JMS configuration details.
PIESIME0046	Invalid configuration provided while updating the COMMON-JMS configuration.
Explanation	The JMS alias configuration provided while updating the COMMON-JMS configuration does not match the existing JMS alias configuration.
Action	Provide a valid JMS configuration that matches the JMS configuration to be updated.
PIESIME0047	An error occurred while invoking a service in Integration Server : {0}
Explanation	An error occurred while invoking a service in Integration Server. Error {0} occurred.
Action	Use the supplied error information to correct the condition causing the error. Then, reissue the service request.
PIESIME0048	JMS alias {0} should be disabled before {1} operation.
Explanation	The JMS alias {0} should be disabled before performing the {1} operation.
Action	Ensure that the JMS alias is disabled.
PIESIME0049	Messaging connection alias {0} should be disabled before {1} operation.
Explanation	The messaging connection alias {0} should be disabled before performing the {1} operation.
Action	Ensure that the messaging connection alias is disabled.
PIESIME0050	Messaging connection alias description cannot be null or empty.
Explanation	While creating a messaging connection alias, the description field cannot be null or empty.
Action	Provide a valid description for messaging connection alias.
PIESIME0051	Messaging connection alias name cannot be updated.
Explanation	You attempted to update the messaging connection alias. Messaging connection alias name is not editable.
Action	To change the name of a messaging connection alias, delete the existing messaging connection alias and create a new alias.

PIESIME0052	Default messaging connection alias cannot be deleted.
Explanation	The messaging connection alias that you attempted to delete is the default messaging connection alias, which cannot be deleted.
Action	To delete a default messaging connection alias, configure another messaging connection alias as the default.
PIESIME0053	Cannot create a new messaging connection alias for Broker.
Explanation	Only one messaging connection aliases for Broker can exist at a time in Integration Server.
Action	Delete the existing messaging connection aliases for Broker before creating a new messaging connection aliases for Broker.
PIESIME0057	Logger name for COMMON-LOGGERS configuration type is invalid.
Explanation	Valid values of logger name for COMMON-LOGGERS configuration type are Server Logger, Error Logger, Guaranteed Delivery Inbound Logger, Guaranteed Delivery Outbound Logger, Security Logger, Service Logger, and Session Logger.
Action	Ensure that you specify a valid logger name when updating the COMMON-LOGGERS configuration type.
PIESIME0058	Server logger cannot be disabled.
Explanation	You attempted to disable the server logger. Server logger cannot be disabled.
Action	Ensure that the server logger is enabled.
PIESIME0059	Destination for server log entries must be a file.
Explanation	The destination for server log entries can only be a file.
Action	Ensure that you specify a file as the destination for server log entries.
PIESIME0060	Mode for writing server log entries must be synchronous.
Explanation	The server logger writes log entries synchronously to the specified destination file. Therefore, the mode for writing server log entries must be specified as synchronous.
Action	Ensure that the mode for writing server log entries is specified as synchronous.

PIESIME0062	The destination for writing Integration Server log entries must be database or file.
Explanation	Integration Server logger writes log entries to database or file only. You attempted to specify a destination other than database or file.
Action	Ensure that you specify database or file as the destination for writing Integration Server log entries.
PIESIME0063	Configuration details for COMMON-VARS cannot be null.
Explanation	While creating a global variable, the configuration details for COMMON-VARS cannot be null.
Action	Provide valid global variable configuration details.
PIESIME0064	Invalid configuration type.
Explanation	The configuration type provided while creating the global variable must be of type COMMON-VARS.
Action	Provide a valid configuration of type COMMON-VARS.
PIESIME0065	Global variable validation error: Variable Setting cannot be empty.
Explanation	The global variable configuration is not valid.
Action	Make sure that Variable Setting is not empty and that the global variable configuration is valid.
PIESIME0066	Global variable validation error: Integration Server accepts only Strings as global variable values.
Explanation	The global variable value specified is not of type String.
Action	Provide a valid value of type String for the global variable.
PIESIME0067	Global variable validation error: Global variable value cannot be empty.
Explanation	The global variable value must not be empty.
Action	Provide a valid value for the global variable.
PIESIME0068	Global variable validation error: Global variable value cannot exceed 255 characters.
Explanation	The global variable value that you specified contains more than 255 characters.
Action	Ensure that length of the global variable value is less than or equal to 255.

PIESIME0069	Global variable validation error: Global variable key cannot be empty.
Explanation	The global variable key must not be empty.
Action	Provide a valid key for the global variable.
PIESIME0070	Global variable validation error: Global variable key cannot exceed 255 characters.
Explanation	The global variable key that you specified contains more than 255 characters.
Action	Ensure that length of the global variable key is less than or equal to 255.
PIESIME0071	Global variable validation error: Global variable key contains special characters other than "." and "_".
Explanation	The global variable key that you specified contains special characters other than period (.) or underscore(_).
Action	Ensure that the global variable key does not contain any special characters other than period or underscore(_).
PIESIME0072	Invalid value for ServiceLogLevel in Service Logger.
Explanation	The value specified for ServiceLogLevel in Service Logger is not valid. Valid values for ServiceLogLevel are perSvc, brief, and verbose.
Action	Ensure that you specify a valid value for ServiceLogLevel in Service Logger.
PIESIME0073	Invalid value for GenerateAuditingDataOnStartup in Security Logger.
Explanation	The value specified for GenerateAuditingDataOnStartup in Security Logger is not valid. The GenerateAuditingDataOnStartup value must be a valid Boolean value (true/false).
Action	Ensure that you specify a valid value for GenerateAuditingDataOnStartup in Security Logger.
PIESIME0074	Invalid value for GenerateAuditingDataOnEvent in Security Logger.
Explanation	The value specified for GenerateAuditingDataOnEvent in Security Logger is not valid. Valid values for GenerateAuditingDataOnEvent are Success or Failure, Success, and Failure.
Action	Ensure that you specify a valid value for GenerateAuditingDataOnEvent in Security Logger.

PIESIME0075	Invalid value for SecurityAreasToAudit in Security Logger.
Explanation	The value specified for SecurityAreasToAudit in Security Logger is not valid. Valid values for SecurityAreasToAudit are Authentication, Authorization, Certificates, Configuration, JDBC Pools, Keystore, Packages, Passwords, Ports, Proxy Servers, Remote Servers, Services, SSL, and Web Services.
Action	Ensure that you specify a valid value for SecurityAreasToAudit in Security Logger.
PIESIME0076	Unable to disable messaging connection alias.
Explanation	An operation to disable messaging connection alias failed.
Action	Check the Integration Server logs for more information.
PIESIMI0061	Resources
PIESIMW0036	Unable to establish a connection using the specified JNDI provider alias.
Explanation	Integration Server is unable to establish a connection using the specified JNDI provider alias. For possible causes, check the server logs.
Action	Ensure that the JNDI provider is running and that the JNDI provider-specific libraries are used in Integration server.
PIESIMW0044	JMS alias {0} created successfully, but an error occurred while enabling the JMS alias.
Explanation	An error occurred while enabling JMS alias {0}. Check logs of integration server. Exception : {1}
Action	Check the Integration Server log to handle the exception manually.
PIESIMW0055	IS Resource settings updated successfully. If Broker is not configured, Broker-related settings will be ignored.
Explanation	IS Resource settings updated successfully. If Broker is not configured on Integration Server, all the Broker-related settings that you specified will be ignored.
Action	Ensure that Broker is configured if you want the Broker-related settings to be updated.
PIESIMW0056	Unable to read listeners.cnf file from package {0}.
Explanation	Unable to read the listeners.cnf configuration file while attempting to locate the port number for the specified port alias.
Action	No action is required. If the issue persists, contact Software AG Global Support.

POOL_NOT_EXISTS Pool alias {0} does not exist.

PROPERTIES_CAN_NOT_BE_NULL – properties can not be null

QUIESCE_MODE_EXCLUDE_LIST_EMPTY – In Quiesce mode, atleast one port should be in the exclude list for Port type assets.

RESOURCE_CAN_NOT_BE_NULL – resource can not be null

RESPONSE_ONE_OF_THREE_REQD – "{0}" or "{1}" or "{2}" must be supplied

REVERSE_GATEWAY_NO_LICENSE – Could not find a valid license for Enterprise Gateway.

Explanation The Enterprise Gateway Server instance does not have a valid license for webMethods Enterprise Gateway.

Action Check the terms of the license file.

ROLLBACK_FAILED_BAD_STATE – Rollback failed due to status

SCC.0121.0004 enlist failed: {0} xid = {1} rxid = {2}

SCC.0121.0007 delist failed: {0} xid = {1} rxid = {2}

SCC.0121.0010E commit failed: {0} xid = {1} resource = {2}

Explanation Integration Server transaction manager was unable to commit a two-phase commit (2PC) transaction to the backend XA resource.

Action Check to see if the backend resource is connected to Integration Server. Then, if necessary, re-initiate the transaction.

SCC.0121.0013 prepare failed: {0} xid = {1} rxid = {2} vote = {3}

SCC.0121.0017E	rollback failed: {0} xid = {1} resource = {2}
Explanation	The Integration Server transaction manager was unable to roll back a two-phase commit (2PC) transaction, most likely due to a resource issue.
Action	Check to see if the backend resource is connected to Integration Server. Then, if necessary, re-initiate the transaction.
SCC.0121.0020	end failed: {0} xid = {1} rxid = {2}
SCC.0121.0026	delisted transaction commit failed: {0} xid = {1}
SCC.0121.0029	one phase commit failed: {0} xid = {1} resource = {2}
SCC.0121.0031	sync beforeCompletion ran: {0} error: {1}
SCC.0121.0033	sync afterCompletion ran: {0} error: {1}
SCC.0121.0034	commit failed: more than 1 local trans enlisted. xid = {1} rxid = {2}
SCC.0121.0035	resource delisted with TMFAIL flag, transaction marked for rollback. xid = {0} rxid = {1}
SCC.0121.0036	transaction timeout. xid = {0}
SCC.0121.0052E	Unable to persist transaction status for xid = {0}: Exception: {1}
Explanation	The transaction recovery manager in Integration Server was unable to write the status of a two-phase commit (2PC) transaction to the disk-based XA recovery store.
Action	Investigate the following possible causes for the problem: 1) The operating system userid under which the Integration Server is running does not have write privileges to the XAStore directory. 2) There is not sufficient disk space for the directory. 3) The XA recovery store is corrupt. If this is the case, archive the files stored in the XA recovery store directory, mail them to Software AG Global Support, move the files in the XA recovery store to a backup directory, and restart Integration Server.

SCC.0121.0055E	Unable to get unrecovered transactions from persistent store. Exception:{0}
Explanation	The transaction recovery manager in Integration Server was unable to obtain a list of incomplete transactions from the XA recovery store. Integration Server uses this store to hold two-phase commit (2PC) transaction states for possible future recovery.
Action	Investigate the following possible causes for the problem: 1) The operating system userid under which Integration Server is running does not have write privileges to the XAStore directory. 2) There is not sufficient disk space for the directory. 3) The XA recovery store is corrupt. If this is the case, archive the files stored in the XA recovery store directory, mail them to Software AG Global Support, move the files in the XA recovery store to a backup directory, and restart the Integration Server.
SCC.0121.0056	RecoveryManager found {0} unrecovered Transactions. Starting recovery.
SCC.0121.0057	Recovery process started for Transaction Xid:{0}, Status: {1}.
SCC.0121.0062E	Unable to rollback Xid:{0} during recovery for resource:{1}, transaction might be heuristically rolled back/committed by resource. Manual intervention might be required. Exception:{2}: Error Code:{3}.
Explanation	The transaction recovery manager in Integration Server detected a transaction whose status in Integration Server is different from the status stored in the back-end resource (for example, a database). This situation occurs when the transaction recovery manager tries to rollback a transaction that the back-end XA resource has already rolled back or committed.
Action	Check to see if the back-end resource administrator (for example a database administrator) manually issued a rollback/commit for the incomplete transaction. If so, ensure that the other back-end XA resources do the same.
SCC.0121.0067E	Unable to commit Xid:{0} during recovery for resource:{1}, transaction might be heuristically rolled back/committed by resource. Manual intervention might be required. Exception:{2}.
Explanation	The transaction recovery manager of the Integration Server detected a transaction whose status in the Integration Server is different from the status stored in the back-end resource (for example, a database). This situation occurs when the transaction recovery manager tries to commit a transaction that the back-end XA resource has already rolled back or committed.
Action	Check to see if the back-end resource administrator (for example a database administrator) manually issued a rollback/commit for the incomplete transaction. If so, ensure that the other back-end XA resources do the same.

SCC.0121.0070 XARecoveryStore: Error during checkDataDevice. Db:{0} Error:{1}

SCC.0121.0071 XARecoveryStore: Resized Data file recovered. Db:{0}

SCC.0121.0072 XARecoveryStore: Error restoring original data file. Db:{0} Error:{1}

SCC.0121.0073 XARecoveryStore: Recoverable Error Skipped - warnonopen = continue. Db:{0} Error:{1}

SCC.0121.0074 XARecoveryStore: Recoverable Error Encountered but warnonopen = fail. Db:{0} Error:{1}

SCC.0121.0075 XARecoveryStore: Damaged data file detected. Db:{0} Error:{1}

SCC.0121.0076 XARecoveryStore: Data file resize required. Db:{0}

SCC.0121.0077 XARecoveryStore: Error cleaning up resized Data file. Db:{0} Error:{1}

SCC.0121.0078 XARecoveryStore: Error creating resized Data file. Db:{0} Error:{1}

SCC.0121.0079 XARecoveryStore: Error closing original Data file. Db:{0} Error:{1}

SCC.0121.0080 XARecoveryStore: Error closing resized data file. Db:{0} Error:{1}

SCC.0121.0081 XARecoveryStore: Error cleaning up copied Data file. Db:{0} Error:{1}

SCC.0121.0082 XARecoveryStore: Error renaming original data file. Db:{0} Error:{1}

SCC.0121.0083 XARecoveryStore: Data file resize completed. Db:{0}

SCC.0121.0084	XARecoveryStore: Error renaming resized data file. Db:{0} Error:{1}
SCC.0121.0086	XARecoveryStore: Error copying resized Data file. Db:{0}
SCC.0121.0087	XARecoveryStore: Damaged data file renamed. Db:{0} renamed:{1}
SCC.0121.0088	XARecoveryStore: Error renaming damaged data file. Db:{0} Error:{1}
SCC.0121.0089	XARecoveryStore: Damaged data file deleted. Db:{0}
SCC.0121.0090	XARecoveryStore: Error deleting damaged data file. Db:{0} Error:{1}
SCC.0121.0091	XARecoveryStore: Error re-creating damaged data file. Db:{0} Error:{1}
SCC.0121.0092	XARecoveryStore: Damaged data file re-created. Db:{0}
SCC.0121.0094S	Unrecoverable Exception while initializing the XA Recovery Store: {0}
Explanation	Integration Server was unable to create a persistent XA recovery store on disk. Integration Server uses this store to hold two-phase commit (2PC) transaction states for possible future recovery.
Action	Investigate the following possible causes for the problem: 1) The operating system userid under which the Integration Server is running does not have write privileges to the XA recovery store directory. 2) There is not sufficient disk space for the directory. 3) The XA recovery store is corrupt. If this is the case, archive the files stored in the XAStore directory, mail them to Software AG Global Support, move the files in the XA recovery store to a backup directory, and restart the Integration Server.
SCC.0121.0095	XA Recovery Store could not be created.

- SCC.0121.0104** **Unable to gain access to resource:{0} Error:{1}. Please verify that the Connection exists and is correctly configured.**
- SCC.0121.0106** **No transaction record found for Xid:{0} in resource:{1}. Transaction might have been committed or erased on resource:{1}. Unable to resolve as transaction might be in mixed state, requires manual intervention.**
- SCC.0121.0107** **Invalid global transaction state for Xid:{0}. Unable to auto-resolve transaction, aborting recovery.**
- SCC.0121.0108** **Transaction Xid:{0} exceeded abandon timeout setting, aborting recovery.**
- SCC.0121.0112E** **Error while shutting down XA Recovery Store:{0}.**
Explanation The Integration Server XA recovery store did not shut down cleanly. Integration Server uses this store to hold two-phase commit (2PC) transaction states for possible future recovery.
Action Restart Integration Server and examine the Server log for any error messages regarding the XARecovery Store. If the problem is a file permission or out of storage issue, correct the problem and restart the Integration Server. If the problem is not a file permission or out of storage issue, archive the contents of the XAStore directory and contact Software AG Global Support.
- SCC.0121.0113E** **Recover call on XAResource:{0} failed. Exception:{1}, Error Code:{2}**
Explanation The transaction recovery manager on Integration Server encountered an error when it tried to obtain a list of all incomplete XIDs known to the back-end resource. The error occurred because the back-end resource threw an exception.
Action Check to see if the back-end resource is available and connected to Integration Server. The name of the resource will be the name of the connection defined in the adapter for the resource.
- SCC.0121.0116** **Active transaction detected while completing service {0}. Rolling back pending operations.**
- SCC.0121.0118** **Active resource detected while cleaning Top Transaction for service {0}. Rolling back pending operations.**

SCC.0121.0120	Active transaction found with the thread after cleanup while completing service {0}. Check the cleanup process.
SCC.0121.0990	XA Transaction Logging: {0}
SCC.0126.0100	An error occurred while attempting to clean up transaction resources on connection {0}
SCC.0126.0101	An error occurred while attempting to release connection {0}
SCC.0126.0102	An error occurred while attempting to close connection pool {0}
SCC.0126.0103E	Assertion error during creation of connection pool {0}
Explanation	An error occurred while allocating the managed connection because either the connection pool does not exist or the connection pool is empty for the managed connection factory.
Action	Ensure that the connection pool settings contain valid values. If the values are valid and if Integration Server is still unable create the connection pool, contact Software AG Global Support.
SCC.0126.0104	Assertion error during reset of connection pool {0}
SCC.0126.0105E	Assertion error during connection request from pool {0}
Explanation	An error occurred while allocating a connection to a request from the connection pool. This can happen if there are no available connections in the pool, if the managed connection factory does not exist, or if the conditions provided by the basic connection pool properties (such as pool size, minimum number of connections or maximum number of connections) are not met.
Action	Ensure the connection pool settings are valid. If the connection pool settings are valid and Integration Server is still unable to allocate a connection from the connection pool, contact Software AG Global Support.
SCC.0126.0106	An error occurred while attempting to retrieve a connection from {0}

SCC.0126.0107	A connection was not available for request in pool {0}
SCC.0126.0110	Failed to retrieve handle for connection {0}
SCC.0126.0111	A duplicate connection returned from managed connection factory {0}
SCC.0126.0112	A data level assertion occurred while managing connections for pool {0}
SCC.0126.0113	Pool {0} cannot be initialized. The pool timeouts must not be negative.
SCC.0126.0115E	Pool {0} cannot be initialized. The minimum pool size must be <= the maximum pool size.
Explanation	An error occurred while initializing the connection pool because the minimum number of connections is greater than the maximum number of connections allowed or the maximum number of connections is set to zero.
Action	Check the adapter connection pool settings to ensure the values for the minimum number of connections and maximum number of connections are valid. If the adapter connection pool settings are valid and the pool is still unable to initialize, contact Software AG Global Support.
SCC.0126.0116E	Pool {0} cannot be initialized. A valid ManagedConnectionFactory was not provided.
Explanation	An error occurred while checking basic properties for a connection pool because the managed connection factory for this pool is null.
Action	Check the connection pool settings to ensure that a valid connection factory is provided. If the settings are valid and the problem still exists, contact Software AG Global Support.
SCC.0126.0117E	An error occurred while attempting to destroy connection {0}
Explanation	An error occurred while closing the database connection from the connection pool.
Action	This is an internal error. Contact Software AG Global Support.
SCC.0126.0118E	Pool state error in {0}. Cannot process request.
Explanation	The next available connection cannot be obtained from the connection pool because the connection pool is disabled.
Action	Check the connection pool settings to ensure that the connection pool is enabled. If the connection pool is enabled and if Integration Server is still unable to obtain the next available connection from the connection pool, contact Software AG Global Support.

SCC.0126.0119E	An error occurred while attempting to create connections for {0}
Explanation	An error occurred while creating a new connection for the connection pool.
Action	Ensure that the resource database is running and the connection pool settings are valid. If the resource database is running and the connection pool settings are valid, contact Software AG Global Support.
SCC.0126.0120E	{0} Threads are already waiting to get connection. The pool {1} doesn't have a connection available for the request.
Explanation	This error occurs when a thread holds a connection and stops responding or is in an infinite loop. In either case, the connection pool management capabilities to grant, release, or close connections do not work. Meanwhile, if the pool is flooded with many connection requests, all of the requesting threads are held in a waiting state. Under a heavy load, Integration Server might stop responding. If there are a large number of threads already waiting for a connection, ResourceAllocationException will be thrown to the new threads.
Action	Check the adapter connection pool settings to ensure the values for the minimum number of connections and maximum number of connections are valid. If the adapter connection pool settings are valid and the pool is still unable to initialize, contact Software AG Global Support.
SS.0088.9424E	Error initializing service handler {0}. Error: {1}
Explanation	An error occurred while initializing the JAX-RPC header handler.
Action	The init() method of JAX-RPC handler threw an error. Correct the error in init() method.
STATUS_ACTIVE	Transaction is active
STATUS_COMMITTED	Transaction is committed
STATUS_COMMITTING	Transaction is committing
STATUS_MARKED_ROLLBACK	Transaction is marked for rollback

STATUS_NO_TRANSACTION – No Transaction

STATUS_PREPARED Transaction is prepared

STATUS_PREPARING Transaction is preparing

STATUS_ROLLEDBACK Transaction is rolled back

STATUS_ROLLING_BACK – Transaction is rolling back

STATUS_TWO_LOCAL_TX – commit failed. more than one local transaction enlisted.

STATUS_UNKNOWN Transaction status is unknown

STRINGSET_NOSUCHELEMENT – StringSetEnumerator

TEST_INVALID_ALIASE – Associated pool alias for the functional alias {0} does not exist.

Explanation Integration Server cannot establish a connection to the pool. A connection pool alias is not associated with the specified functional alias.

Action Make sure a connection pool is associated with the functional alias.

THREAD_ALREADY_WITH_THIS_TX – thread already associated with this transaction

THREAD_WITH_ANOTHER_TX – thread already associated with another transaction

TRAN_NOT_ACTIVE transaction is not active

TRAN_NOT_FOR_THREAD – transaction is not with current thread

TRAN_NOT_WMIRAN transaction not a Tran instance

UNABLE_TO_INIT_XASTORE – Unrecoverable Error while initializing XA Store: {0}

UNEXPECTED_END_OF_DOCUMENT_WHEN_READING_ELEMENT_TEXT_CONTENT – unexpected end of document when reading element text content

UNEXPECTED_EVENT_TYPE – Unexpected event type {0}

URLALIAS_ALREADY_REGISTERED – The HTTP URL alias could not be registered by the service {0}. "{1}" is already registered as an alias for the path: {2}

URLALIAS_ALREADY_REGISTERED2 – HTTP URL alias "{0}" could not be registered. It is already registered as an alias for the path: {1}

URLALIAS_ALREADY_REGISTERED3 – HTTP URL alias "{0}" could not be registered. It is already registered by package {1} as an alias for the path: {2}

VCS.0132.0051 VCS package shutting down

VCS.0132.0052 loading configuration file: {0}

VCS.0132.0054 error loading configuration file: {0}

VCS.0132.0057 loading users file: {0}

VCS.0132.0059 error loading users file: {0}

VCS.0132.0060 saving users file: {0}

VCS.0132.0061	error saving users file: {0}
VCS.0132.0062	retrieving information from VCS server
VCS.0132.0063	no configuration file read for package: {0}; expecting: {1}
VCS.0132.0064	overwriting existing property: {0}; new value: {1}
VCS.0132.0100	file not checked out: {0}
VCS.0132.0101	file checked out: {0}
VCS.0132.0102	file out of date: {0}
VCS.0132.0103	file checked out by another user: {0}
VCS.0132.0150	setting VCS client as {0}
VCS.0132.0151	no current VCS client
VCS.0132.0152	invalid VCS client: {0}
VCS.0132.0153	no VCS client type set
VCS.0132.0202	files to delete: {0}
VCS.0132.0252	Deleted by %value dev_user% on %value is_host% at %value is_time%

VCS.0132.0253	%value usercomment%%nl%dev_user : %value dev_user%%nl%is_host : %value is_host%%nl%dev_host: %value dev_host%%nl%is_time : %value is_time%
VCS.0132.0254	delete failed; attempting to revert from opened list
VCS.0132.0302	not locking in build mode (no package specified)
VCS.0132.0303	not locking in delete mode
VCS.0132.0304	running checkout from VCS
VCS.0132.0353	Checked in by %value dev_user% on %value is_host% at %value is_time%
VCS.0132.0354	%value usercomment%%nl%dev_user : %value dev_user%%nl%is_host : %value is_host%%nl%dev_host: %value dev_host%%nl%is_time : %value is_time%
VCS.0132.0355	running checkin to VCS
VCS.0132.0502	not deleting files during preDelete
VCS.0132.0651	No entries to submit
VCS.0132.0700	loading directories: {0}; version: {1}
VCS.0132.0800	Perforce client not found
VCS.0132.0801	Perforce user not found
VCS.0132.0850	For {0}, command: {1}

VCS.0132.0951 Parent does not exist: {0}

VCS.0132.1000 Node not found for version

WS_ALIAS_EXISTING_MESSAGE_ADDRESSING – Could not add the Web service endpoint alias because the message addressing endpoint alias {0} for transport type {1} already exists. Provide a different alias name.

Explanation The message addressing endpoint alias name you specified already exists for a transport type (HTTP, HTTPS, JMS).

Action Specify a message addressing endpoint alias name that does not already exist.

XID_NOT_FOUND Failed attempt to store global status={0} for xid={1}. XID not found.

XML_SOURCE_SHOULD_BE_OF_CORRECT_TYPE – xmlSource should be of type 'java.io.InputStream', 'java.io.Reader', 'org.w3c.dom.Node', 'javax.xml.stream.XMLStreamReader' or 'java.lang.String'

XML_TARGET_SHOULD_BE_OF_CORRECT_TYPE – xmlTarget should be of type 'java.io.OutputStream', 'java.io.Writer' or 'javax.xml.stream.XMLEventWriter'

XSL.0002.0014E new Object[][{Integer.valueOf(1),Integer.valueOf(2),"JAXP: Error - {0}"},{Integer.valueOf(2),Integer.valueOf(3),"JAXP: Warning - {0}"},{Integer.valueOf(3),Integer.valueOf(5),"JAXP: Properties file is {0}. "},{Integer.valueOf(4),Integer.valueOf(5),"JAXP: DocumentBuilderFactory = {0}"},{Integer.valueOf(5),Integer.valueOf(5),"JAXP: SAXParserFactory = {0}"},{Integer.valueOf(6),Integer.valueOf(5),"JAXP: TransformerFactory = {0}"},{Integer.valueOf(7),Integer.valueOf(5),"JAXP: Stylesheet template {0} cached."},{Integer.valueOf(8),Integer.valueOf(5),"JAXP: Stylesheet templates cache cleared."},{Integer.valueOf(9),Integer.valueOf(3),"JAXP: Required argument 'stylesheet' not specified; no value removed from stylesheet cache."},{Integer.valueOf(10),Integer.valueOf(5),"JAXP: Stylesheet template {0} removed from cache."},{Integer.valueOf(11),Integer.valueOf(3),"JAXP: Stylesheet template {0} was not found in cache."},{Integer.valueOf(12),Integer.valueOf(5),"JAXP: Stylesheet {0} was successfully compiled."},{Integer.valueOf(13),Integer.valueOf(5),"JAXP: Compiling TransformerFactory = {0}"},{Integer.valueOf(14),Integer.valueOf(2),"JAXP: Error - External entity attack detected. Entity name is {0}"}],}

Explanation An external entity was detected in the XML that the pub.xslt.Transformations:transformSerialXML service received or in the XSLT stylesheet the service used to transform the XML.

Action Check the XML file or the XSLT stylesheet for external entities. If the external entity is a trusted entity, add the entity to the server parameter watt.core.xml.allowedExternalEntities.

keyStoreAliasCreationFailed – Keystore alias "{0}" creation failed. Details: {1}

16 Mediator Messages

0010.0715E	Mediator Upgrade, did not complete successfully.
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. This message indicates the upgrade was not successful. There should be a previous error message in the server log that indicates the problem.
Action	See actions for message ID '0010.0702'
0010.0753	Successfully migrated Mediator cache configuration file
0030.0092	PublisherPropsObserver - Unknown sender data type ({})
Explanation	The properties observer received an invalid sender type.
Action	This indicates a coding error. Non-Mediator code should never call this method.
0030.0094	PublisherPropsObserver - Unknown parameters data type ({})
Explanation	The properties observer received an invalid update object type.
Action	This indicates a coding error. Non-Mediator code should never call this method.
0030.0099	PublisherPropsObserver - Unknown wrapper factory data type ({})
Explanation	This message has incorrect text. It should indicate an invalid data type for UDDP publisher bean.
Action	Update the pg configuration file to use a proper UDDI publisher data type.

0030.0100	PublisherPropsObserver - Unable to find wrapper factory
Explanation	There is no UDDI publisher configured, but its properties are being changed.
Action	Update the configuration file. Either configure a UDDI publisher or unregister the UDDI properties observer.
0030.0104	Exception encountered initializing logging resource: {0}
Explanation	A problem was encountered while setting up a logger for Mediator to use. There should be an exception message with more details.
Action	Fix the problem identified by the exception message.
0030.0109	PublisherPropsObserver - Can't convert string ({0}) to integer for publishing interval, ignoring input
Explanation	The value received for performance data reporting interval was not a valid numeric string.
Action	Make sure a numeric value is input.
0030.0113	PublisherPropsObserver - Unknown pg service deployer data type ({0})
Explanation	The data type of the PG Service Deployer bean is invalid.
Action	Update the pg configuration file to use a proper PG Service Deployer data type.
0030.0301	ConsumerApplicationManager.convert - cannot handle null request
Explanation	Unable to create Consumer deployment object for update.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0302	ConsumerApplicationManager.convert - cannot convert consumer with null {0}
Explanation	Invalid Consumer deployment object was found.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0303	VirtualServiceDeployer.{0} - cannot handle null {1}
Explanation	A null reference was found during a deployment activity. The object and activity are identified in the message.
Action	Probably bad SOAP request for deployment, fix request.

0030.0304	VirtualServiceDeployer.deploy - service ({0}) already deployed, undeploying
Action	Info level message, no action required.
0030.0305	VirtualServiceDeployer.undeploy - cannot undeploy service ({0}), not deployed
Explanation	Attempt to undeploy virtual service failed.
Action	Verify that Mediator and CentraSite agree that the service is no longer deployed. If not, try undeploying this service again, or restarting Mediator/IS.
0030.0306	VirtualServiceDeployer.{0} - caught this: type({1}) message({2})
Explanation	Unable to deploy virtual service. See exception message for more details.
Action	Address the problem indicated by exception and try to deploy again.
0030.0309	ClusteredServiceDeployer{0} - cannot handle null {1}
Explanation	Unable to create VS deployment object for update.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0315	ClusteredConsumerManager.updateConsumer - cannot handle null consumer
Explanation	Unable to create Consumer object for update.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0318	ClusteredServiceDeployer - cannot deploy null info to cache
Explanation	A problem occurred while attempting to convert a PGService for deployment to shared cache. There should be another message describing the conversion or deployment issue.
Action	Fix the conversion or deployment problem.
0030.0319	ClusteredServiceDeployer - cannot undeploy null service name from cache
Explanation	Virtual service undeployment requires a non-empty service name. This is problem with undeployment request payload.
Action	Fix the undeployment request payload.

0030.0328	ConsumerApplicationManager.{0} - cannot handle null update request
Explanation	Invalid Consumer deployment request for update.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0330	ConsumerApplicationManager - not updating consumer ({0}), modification date, ({1}), is no more recent
Action	Info level message, no action required.
0030.0333	ConsumerApplicationManager.{0} - caught this: type({1}) message({2})
Explanation	Unable to create and persist Consumer object for update.
Action	Either bad SOAP request to Deployer, fix Request. Or file system problem, check file system permissions. See logged message text for specific error details.
0030.0336	Consumer Application Update Failed; requested update has invalid {0} field
Explanation	Invalid consumer name or key in remove request.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0337	Consumer Application Remove Failed; consumer ({0}) does not exist
Explanation	Attempt to remove consumer failed.
Action	Reply to CentraSite Deployment attemp should indicate error. Try redeploying this consumer or resynchronizing all consumers.
0030.0343	RegisteredConsumerNamesManager.{0} - cannot handle null update request
Explanation	Invalid RegisteredConsumerNames deployment request for update.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0344	Registered Consumer Names Update Failed; requested update has invalid {0} field
Explanation	Invalid service name or consumer names in registered consumer names update request.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0346	RegisteredConsumerNamesManager - not updating consumer names registered to ({0}), modification date, ({1}), is no more recent
Action	Info level message, no action required.

0030.0347	RegisteredConsumerNamesManager.{0} - cannot handle null update request
Explanation	Invalid RegisteredConsumerNames deployment request for remove.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0348	Registered Consumer Names Remove Failed; requested update has invalid {0} field
Explanation	Invalid service consumer name in remove request.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0350	Registered Consumer Names Remove Failed; service ({0}) has no registered consumers
Explanation	Invalid request to remove RegisteredConsumerNames, must include at least one consumer name.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0352	RegisteredConsumerNamesManager.{0} - caught this: type({1}) message({2})
Explanation	Unable to create and persist RegisteredConsumerNames object for update.
Action	Either bad SOAP request to Deployer, fix Request. Or file system problem, check file system permissions. See logged message text for specific error details.
0030.0356	VirtualServiceDeployer - unable to get endpoints for {0}, caught this: type({1}), msg({2})
Explanation	Unable to obtain endpoint for deployed service.
Action	Probably bad SOAP request to Deployer or bad VSD, fix one or both.
0030.0357	ClusteredRegisteredConsumerNamesDeployer.updateConsumerNames - cannot handle null reg names object
Explanation	Unable to create RegisteredConsumerNames object for update.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0358	Consumer Application Remove Failed; requested update has invalid name and key fields, both are empty
Explanation	Consumer remove request must have either name or key to identify consumer; both were null or empty.
Action	Probably bad SOAP request to Deployer, fix request.

0030.0359	ConsumerApplicationManager - Consumer update request has invalid IP range; from {{0}} to {{1}}
Explanation	Consumer update request had invalid IP address range.
Action	Probably bad SOAP request to Deployer, fix request.
0030.0361	VirtualServiceDeployer - redeploying undeployed service {{0}}, deployment failed for newer version
Action	Info level message, no action required.
0030.0362	VirtualServiceDeployer - a problem was encountered during deployment, {{0}} will be undeployed and replaced if necessary
Action	Info level message, no action required.
0030.0363	VirtualServiceDeployer.{{0}} - service{{1}} caught this: type{{2}} message{{3}}
Explanation	Message context encountered an exception while attempting to redeploy or undeploy a virtual service. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0030.0364	Deployment request for service: {{0}}. Registered consumer name element was processed, but the existing modification date is the same as the request. {{1}}
Action	Info level message, no action required.
0030.0366	UddiPropertiesObserver - Password lookup failed; type {{0}}, message {{1}}
Explanation	A problem was encountered by attempting to retrieve stored password. There should be an exception with more specific trouble description.
Action	Fix the problem identified by the exception message.
0030.0367	UddiPropertiesObserver - Unable to activate performance date policies; type {{0}}, message {{1}}
Explanation	The performance data deployer was unable to run. This message should include more details regarding the reason.
Action	Fix the problem identified by the exception message.

0030.0370	UddiPropertiesObserver - Unable to connect to UDDI: ({0}); property updates saved, but data collection is OFF.
Explanation	A problem was encountered during publisher test.
Action	This is probably a bad configuration parameter, fix it.
0030.0371	UddiPropertiesObserver - Unable to convert port string ({0}) to integer, using default port {1}
Explanation	The value input for 'UDDI port' number is non-numeric.
Action	Input an numeric port value.
0050.0001	Unable to find Policy Element in the VSD:{0}
Explanation	An exception was encountered while attempting to extract a policy element from VSD. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0002	Unable to create Rampart properties:{0}
Explanation	An exception was encountered while attempting to assemble Rampart keystore properties. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0003	Unable to replace static Rampart configuration with configured properties:{0}
Explanation	An exception was encountered while attempting to re-configure Rampart keystore properties. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0004	Unable to create Rampart Configuration Element:{0}
Explanation	An exception was encountered while attempting to convert Rampart configuration string to XML. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0005	Unable to create XPath to select first Policy Alternative:{0}
Explanation	An exception was encountered while attempting to create an Xpath object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0006	Error while removing existing RampartConfig elements:{0}
Explanation	An exception was encountered while attempting to remove configuration elements. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0007	Required configuration information to enable WS-Security processing is missing. Unable to process service: {0}. Please ensure Keystore/Truststore information is configured
Explanation	Service could not be initialized due to a problem with keystore/truststore configuration.
Action	Fix the security configuration.
0050.0011	Exception while determining hostname or IP address of the server:{0}
Explanation	An exception was encountered while attempting to resolve a host name or IP address. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0013	Mediator needs the repository location of the SOAP Stack
Explanation	Configuration does not include a valid location for Axis2 repositoryconfiguration.
Action	Fix the axis2 configuration.
0050.0016	ServerManager ready for processing
Action	Info level message, no action required.
0050.0017	Mediator encountered exception while starting ServerManager:{0}
Explanation	An exception was encountered during configuration of Axis2 listeners. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0018	Invalid Port specified. Using default configuration: {0}
Explanation	The 'port' property has a non-numeric string value, the value configured in Axis is used.
Action	Make sure the property value to numeric.
0050.0019	Port {0} is already in use. Trying alternate
Explanation	The port indicated in the message is not available to use with a new socket.
Action	Specify another port value in the system 'port' property or Axis configuration.
0050.0020	Exception while creating "id" selection XPath: {0}
Explanation	Message context encountered an exception while attempting to create an XPath object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0021	Found Element within Resources element with id: {0}
Action	Info level message, no action required.
0050.0022	Exception while selecting element with id:{0} in Resources Element: {1}
Explanation	Message context encountered an exception while attempting to extract the indicated element from XML. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0023	Mediator received a response for the request with message Id :{0} But a callback is not registered (anymore) to process this response
Explanation	No callback was registered at the time this response was processed.
Action	This is probably a VS configuration problem.
0050.0024	Mediator received a response message without a message Id
Explanation	There was a problem relating the native service response to a virtual service request.
Action	Look for previously logged message indicating that message Id was not used.

0050.0025	Mediator encountered an exception: {0}. No error handlers found - [Message Dropped]
Explanation	This could be a configuration problem. An exception was encountered while attempting to handle a fault. The associated exception message should include more details regarding the problem.
Action	Fix the configuration, or other problem identified by the exception message.
0050.0026	Outbound client can't locate policy from the property :{0}
Explanation	The Synapse message context does not contain an entry for the property key identified in the message.
Action	This is a policy configuration problem.
0050.0027	Mediator outbound client encountered error:{0}
Explanation	Client encountered an exception while attempting to send a message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0029	VSD with incorrect Namespace:{0}. Unable to create PGService.
Explanation	The namespace found in the VSD is unknown.
Action	This is a virtual service configuration problem.
0050.0031	The {0} element is required for a Mediator Service
Explanation	Some element used during service deployment was found to be null. The specific element should be identified in the message text.
Action	This is a virtual service configuration problem.
0050.0032	The {0} sequence element is required for a Mediator Service
Explanation	The VSD is missing the sequence element identified in the message.
Action	This is a virtual service configuration problem.
0050.0033	The inSequence for VSD:{0} is invalid.
Explanation	The sequence identified in the message failed validation. Look for recent error message with more validation failure details.
Action	This is a virtual service configuration problem.

0050.0034	The outSequence for VSD:{0} is invalid.
Explanation	The sequence identified in the message failed validation. Look for recent error message with more validation failure details.
Action	This is a virtual service configuration problem.
0050.0035	Exception while parsing Virtual Service String Definition:{0}
Explanation	An exception was encountered while attempting to parse the virtual service description. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0036	Unable to create Virtual Service Definition
Explanation	Unable to create XML object from the VSD string.
Action	This is a virtual service configuration or deployment problem.
0050.0037	PGServiceFactory encountered and exception while creating the PGService: {0}
Explanation	An exception was encountered while attempting to validate input or output sequence or during WSDL URI processing. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0038	Invalid parameter specified for PGService: {0}
Explanation	The attribute named in the message has no value in the VSD.
Action	This is a virtual service configuration problem.
0050.0039	Exception {0} for PGService: {1}
Explanation	An exception was encountered while attempting during service creation. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0040	No PGService found with name: {0}
Explanation	Attempting to undeploy or get endpoints for a service that does not exist.
Action	Make sure the virtual service exists before operating on it.

0050.0041	WSStack exception processing service: {0} Cause: {1}
Explanation	An AxisFault was encountered while attempting to either undeploy or get endpoints for the virtual service named in the message. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.
0050.0042	Unable to locate the WSStack configuration. Can't deploy Virtual Service:{0}
Explanation	The Synapse configuration cannot supply an Axis configuration.
Action	This is an Axis2/Synapse/WS-Stack configuration problem.
0050.0043	A Virtual Service with name:{0} already exists. Unable to deploy.
Explanation	Cannot deploy an Axis service when one already exists with the same name.
Action	Undeploy the existing service before attempting to redeploy or use the same name.
0050.0044	Unable to locate WSStack configuration. Please check if WSStack is enabled/correctly configured.
Explanation	Unable to retrieve the configuration context supplier bean.
Action	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
0050.0045	Invalid parameter passed for Virtual Service creation:{0}
Explanation	An attempt to persist the VSD for a service found a null element. The VSD is not allowed to be null.
Action	This may be the result of invalid deployment payload; fix the VSD.
0050.0046	Unable to persist VSD:{0} to disk. Encountered error:{1}
Explanation	An exception was encountered while attempting to serialize the VSD for the service identified in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0047	Unable to {0} VSD:{1}. Error:{2}
Explanation	This message is used in several different error conditions, as indicated by the object of 'unable to...'
Action	Fix the 'unable to...' problem for the service identified by 'VSD:'.

0050.0048	Error getting endpoints for service:{0}, Cause: {1}
Explanation	An exception was encountered while attempting to get endpoints. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0049	Exception while creating PGService: {0}, Cause: {1}
Explanation	An AxisFault was encountered while checking if deploying service already exists or while attempting to register service with Axis2. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0050	Error while engaging module: {0}
Explanation	An AxisFault was encountered while attempting to engage the Axis2 module indicated in the message. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.
0050.0052	Axis was unable to load module {0}
Explanation	An exception was encountered while attempting to load and engage module identified in message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0053	Loading the WSDL : {0}
Action	Info level message, no action required.
0050.0055	PGService {0} encountered error while converting wsdl element to a StreamSource:{0}
Explanation	An exception was encountered while attempting to read WSDL from manifest. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0057	Unknown WSDL format for PGService:{0}, neither WSDL 1.1 nor WSDL 2.0
Explanation	The current WSDL element has unknown or no namespace associated.
Action	This is a virtual service configuration problem.

0050.0060	Populating SOAP service using WSDL
Action	Info level message, no action required.
0050.0061	Unable to find a WSDL for the PGService:{0}. Assuming a POX or Legacy service
Action	Info level message, no action required.
0050.0062	PGService: {0} is available on transports {1}
Action	Info level message, no action required.
0050.0063	Adding PGService:{0} to the SOAP Stack
Action	Info level message, no action required.
0050.0064	Removing PGService:{0} due to error: axisFault.getMessage()
Action	Info level message, no action required.
0050.0065	Exception while setting policy on PGService:{0}
Explanation	An exception was encountered while attempting to engage WS-Policy module. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0066	Setting Policy with id:{0} on Mediator Service:{1}
Action	Info level message, no action required.
0050.0068	Successfully created service in SOAP Stack for PGService:{0} containing {1} endpoint(s).
Action	Info level message, no action required.
0050.0069	Error{1} on setting parameter :{0} on Mediator Service
Explanation	An exception was encountered while attempting to set a parameter into an Axis service. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0070	creating new Mediator Service: {0}
Action	Info level message, no action required.
0050.0071	Unable to find service directory for service {0}
Explanation	Unable to persist WSDL assets because the virtual service directory does not exist.
Action	Redeploying the virtual service should create the service directory.
0050.0074	Error: {0} while reading from file {1}
Explanation	An exception was encountered while attempting to read the proxy file identified in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0076	Scheduled task[{0}] with startup delay of {1} ms and interval of {2} ms
Action	Info level message, no action required.
0050.0077	Error initializing JMS transport listener. Cause: {0}
Explanation	An exception was encountered while attempting to register JMS listener. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0078	Unable to stop TransportListener called:{0}. Exception:{1}
Explanation	An AxisFault was encountered while attempting to stop the JMS transport listener during bean initialization. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.
0050.0083	Error {0} occurred while updating the load balancer properties
Explanation	An AxisFault was encountered while attempting to add load balancer URL to an Axis transport description. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.

0050.0084	Loadbalanced Endpoint: [{0}] failed!
Explanation	A mediation operation to a load balanced endpoint has failed. The endpoint indicated in the message is not available. This usually indicates a communication problem with the targeted server.
Action	Fix the targeted server.
0050.0086	Unable to get the IS keystore manager - please check your configuration!
Explanation	Unable to retrieve the keystore manager bean.
Action	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
0050.0087	Keystore initialization failed! Please check the server log for more details
Explanation	Unable to load the keystore file.
Action	This is a Mediator security configuration problem.
0050.0088	Truststore initialization failed! Please check the server log for more details
Explanation	Unable to load the truststore file.
Action	This is a Mediator security configuration problem.
0050.0089	Unable to get the Rampart Configuration Handler - please check your configuration!
Explanation	Unable to retrieve the Rampart creation handler bean.
Action	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
0050.0099	VSD proxy loader, Unable to delete file: {0}
Explanation	The file or directory indicated in the message could not be deleted.
Action	Determine why the file or directory could not be deleted and make it deletable.
0050.0100	VSD proxy loader, Unable to delete directory: {0}
Explanation	The directory indicated in the message could not be deleted.
Action	Determine why the directory could not be deleted and make it deletable.
0050.0101	VSD proxy loader, Unable to create directory: {0}
Explanation	The file or directory indicated in the message could not be created.
Action	Delete the directory so that Mediator can create it again.

0050.0105	Unable to determine fault cause. Please check the log file for more information!
Explanation	This error indicates that Mediator could not determine the cause for the error when trying to extract the soap fault message from the response. Additional errors if any would be present in the IS log file (server.log)
0050.0208	Error resolving WSDL URI. Cause {0}
Explanation	An exception was encountered while attempting to resolve URI elements into XML source. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0209	Error initializing virtual service factory. Cause: {0}
Explanation	An exception was encountered while attempting to initialize XPath elements. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0210	Error setting location of virtual service proxies directory. Path: {0} Cause: {1}
Explanation	An exception was encountered while attempting to use the directory identified in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0211	Unable to determine service endpoint URI for this service: {0} No transport listener defined for the virtual service's transport protocol.
Explanation	The configuration context's listener manager cannot find an endpoint for the current service. This may indicate that the hosting IS does not have an appropriate listener registered.
Action	This is a configuration problem, either in IS ports or VSD
0050.0212	Unknown exception deploying virtual service: {0} Cause: {1}
Explanation	An exception was encountered while attempting to get an endpoint reference from the context listener manager. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0214 **Error {0} manifest from external resources associated with virtual service: {1}. Cause: {2}**

Explanation An exception was encountered while attempting to read WSDL from manifest. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0215 **Error initializing virtual service transformation bean with this xslt: {0} Cause: {1}**

Explanation An exception was encountered while attempting to read the transformation file. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0216 **Error transforming raw virtual service string. Cause: {0} virtual service xml: {1}**

Explanation An exception was encountered while attempting to read the Mediator's transformation file. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0221 **Mediator has an internal configuration error. It's deploy-time xslt transformation file path does not exist. Path: {0}**

Explanation An exception was encountered while attempting to read the file identified in the message. The associated exception message should include more details regarding the problem.

Action This is a configuration problem; make sure the file identified in the message exists and contains the transformation.

0050.0235 **URI creation error: {0}**

Explanation An exception was encountered while attempting to resolve an endpoint URI. The associated exception message should include more details regarding the problem.

Action Fix the problem identified by the exception message.

0050.0250 **Could not find user-specified value for HTTP method! Defaulting to inbound request HTTP method {0}**

Explanation The 'routing method' context variable has an invalid value.

Action If the value indicated in the message is acceptable, no action is required. Otherwise virtual service configuration must be changed.

0050.0252	Could not set HTTP method for outgoing request for endpoint: {0}
Explanation	The outgoing request's message context is null.
Action	This is a virtual service/policy configuration problem.
0050.0300	Context variable name "{0}" is already declared. Multiple declarations in the same context is not allowed.
Explanation	Context variable names must be unique for a service.
Action	This is a service configuration problem.
0050.0303	Attempt to reference context variable without providing a message context. Custom context variables may only be declared with a 'session' scope at this time. Other scopes are not supported.
Explanation	Attempting to get context variable or context variable map, but the message context (or session) is null.
Action	Earlier error messages should provide clues to help determine why a valid message context is null.
0050.0306	Context variable name is required for variable declaration.
Explanation	Variable name validation failed, QName is null or is missing a local part.
Action	This is a context variable configuration problem.
0050.0307	Namespace URI and prefix is required for custom variable declaration. varName: {0}
Explanation	Variable name validation failed, Namespace URI and prefix must both be neither null nor empty.
Action	This is a context variable configuration problem.
0050.0308	Context variable name must be a valid identifier (alpha-numeric, \$, or _ permitted) Found: {0}
Explanation	Variable name validation failed, name has invalid characters.
Action	This is a context variable configuration problem.

0050.0309	Core Context variables cannot have a namespace or prefix as part of its declaration. varName: {0}
Explanation	Variable name validation failed, prefix for core variables must be empty.
Action	This is a context variable configuration problem.
0050.0310	Either a Message context or axis service name is required when creating a custom context variable. varName: {0}
Explanation	Both service name and Axis2 message context are null, this is not acceptable. This is probably the result of attempting to deploy a service with no service name.
Action	Verify that service configuration is correct.
0050.0311	Attempt to create a custom variable using a message context with no AxisService. varName: {0}
Explanation	The axis2 message context is corrupted, it should identify a service.
Action	Earlier error messages should provide clues to help determine why a valid message context could not be created.
0050.0312	Unexpected error creating custom Mediator context variable. varName: {0} reason: {1}
Explanation	An exception was encountered while attempting to create a custom context variable. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0313	Unexpected error removing custom Mediator context variable for service: {0} reason: {1}
Explanation	An exception was encountered while attempting to remove or inject a custom context variable. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0314	Unexpected error initializing core Mediator context variables. reason: {0}
Explanation	An exception was encountered while attempting to create a context variable. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0316	Unexpected error getting Mediator context variable value. varName: {0} reason: {1}
Explanation	An exception was encountered while attempting to get the value of the context variable named in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0317	Unexpected error setting Mediator context variable value. varName: {0}, value:{1}, reason: {2}
Explanation	An exception was encountered while attempting to set the context variable value named in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0318	Expected a virtual service name for this method operation, but none was provided.
Explanation	Attempting to get context variable map for a null service name.
Action	Earlier error messages should provide clues to help determine why a valid service name is null.
0050.0321	Mediator context variable adapter unable to locate this type: {0}
Explanation	The context variable type indicated in the message is unknown.
Action	This is a context variable configuration problem.
0050.0322	Unexpected error getting core Mediator context variable value from adapter. type: {0}
Explanation	An exception was encountered while attempting to get the context variable value named in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0323	Only string and int schema types are supported at this time. Type: {0}, declared with "{1}" context variable is not supported.
Explanation	The context variable schema type is not among the accepted types.
Action	This is a service configuration problem.

0050.0324	Context variable name declarations cannot contain \$ sign symbols in the name since that is used as a reference operator. varName: {0}
Explanation	Variable name validation failed, name must include substitution character, (dollar sign).
Action	This is a context variable configuration problem.
0050.0325	Unable to return list of context variables declared for this service: {0} Reason: {1}
Explanation	An AxisFault was encountered while attempting to retrieve a list of context variable names. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.
0050.0326	Unable to return list of context variables declared for this message context: {0} Reason: {1}
Explanation	An AxisFault was encountered while attempting to get a list of context variables or list of variable keys. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.
0050.0327	Context variable name deployed with virtual service {0} references an unknown namespace prefix. name attribute: {1}
Explanation	Context variable identified in message has invalid namespace.
Action	This is a context variable configuration problem.
0050.0328	Exception while copying context variables from request to response message context. Reason: {0}
Explanation	An AxisFault was encountered while attempting to copy context variable names between contexts. The associated fault message should include more details regarding the problem.
Action	Fix the problem identified by the fault message.
0050.0329	Could not create backup directory for failed services! Dir tried = {0}
Explanation	An attempt to create the 'failed services' directory has failed.
Action	Determine why the directory could not be created. Either fix the creation problem or specify a different directory.

0050.0331	Error occurred when getting backup directory for path {0}
Explanation	An exception was encountered while attempting to determine directory for backing up failed services. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0333	Error occurred while resolving URI; message = {0}
Explanation	An exception was encountered during URI resolution. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0337	Previously selected {0} port {1} is no longer enabled or available!
Explanation	The message indicates port number and type. The requested port is not available.
Action	Select a new port number for the indicated port type.
0050.0343	Context variable API expected an IData object for ctx variable, {0}, but received this: {1}
Explanation	The data element from which a context variable is to be extracted has an unknown data type.
Action	This is probably a flow configuration problem; where the pipeline was populated with an invalid value.
0050.0344	Attempt to insert {0} core ctx variable with invalid value type: {1}. Expected a collection of this type: {2}
Explanation	.The allowable data type for a core context variable is restricted, depending on variable type.
Action	.This is a context variable configuration problem.
0050.0345	Unable to access array element [{0}] in SOAP_HEADERS core ctx variable. Cause: {1}
Explanation	The index value indicated in the message must be numeric.
Action	This is a context variable configuration problem.

0050.0346	Invalid array or key reference for core ctx variable. This substitution string has mismatched braces: {0}
Explanation	The context variable substitution string is invalid, mismatched brace characters were found.
Action	This is a context variable configuration problem.
0050.0347	Attempt to create an IData value for a ctx variable from an unsupported class type. CtxVar: {0} Bad type: {1}
Explanation	The context variable to be converted to IData has an unknown data type.
Action	This is a context variable configuration problem.
0050.0348	Unable to append header block to the end of the soap header. Cause: {0}, soapHeader element: {1}
Explanation	An exception was encountered while attempting to add append new SOAP header block. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0349	Unable to prepend header block to the beginning of the soap header. Cause: {0}, soapHeader element: {1}
Explanation	An exception was encountered while attempting to add prepend new SOAP header block. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0350	Unable to remove header block from the soap header. Cause: {0}, soapHeader: {1}
Explanation	An exception was encountered while attempting to remove a SOAP header block. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0351	Unable to set header block at position {0} of the soap header. Cause: {1}, soapHeader element: {2}
Explanation	An exception was encountered while attempting to replace a SOAP header block with a new one. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0355	Could not create STS configuration directory! Dir tried = {0}
Explanation	The file or directory indicated in the message could not be created.
Action	Delete the directory so that Mediator can create it next time it is required.
0050.0357	Error occurred when getting STS configurations directory for path {0}
Explanation	An exception was encountered while attempting to create the directory indicated in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0362	Error occurred when creating STS client
Explanation	An exception was encountered while attempting to create an STS client object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0364	Error occurred when initializing default STS configuration store
Explanation	An exception was encountered while attempting to create JAXB marshaller/unmarshaller pair. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0365	Could not find STS configuration file with path {0}
Explanation	An attempt to delete the file indicated in the message failed because the file does not exist.
Action	Check this directory [IS_INSTALL_DIR\packages\WmMediator\config\resources\security\sts] to make sure there is an xml file with the STS config name being deleted. For e.g. if the STS config being deleted is MySTS, then there should be an XML file called MySTS.xml in the mentioned directory
0050.0366	Could not delete STS configuration file with path {0}
Explanation	An attempt to delete the file indicated in the message returned 'false'. The file was not deleted.
Action	Make sure the STS config file present under [IS_INSTALL_DIR\packages\WmMediator\config\resources\security\sts] is present and not locked by any other application (e.g. opened in an editor like Windows Notepad). Check the log file to see if there is any java IOException related to disk errors.

0050.0367	Error occurred when saving STS configuration to disk
Explanation	An exception was encountered while attempting to marshal configuration object into file. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0368	Error occurred when reading STS configuration from file {0}
Explanation	An exception was encountered while attempting to unmarshal configuration file indicated in the message into JAXB object. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0371	Error getting IS keystore manager instance!
Explanation	An exception was encountered while attempting to get a reference to the keystore manager. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0373	Error occurred when adding rampart configuration to STS policy
Explanation	An exception was encountered while attempting to configure the STS policy. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0379	Error occurred when adding assertion to STS policy
Explanation	An exception was encountered while attempting to add an assertion to a WS-Policy artifact. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0382	Error occurred when adding OnBehalfOf element to WS-Trust request element
Explanation	An exception was encountered while attempting to add the WS-Trust element to a request. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0383	Error occurred when sending WS-Trust request to STS to obtain SAML assertion
Explanation	An exception was encountered while attempting to add SAML assertion to pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0384	Could not find required property {0} for SAML sender-vouches action!
Explanation	The pub.mediator.security.ws.AddSamlSenderVouchesToken ESB service is missing the required 'ConfigName' input value
Action	Make sure that the 'ConfigName' service input has a valid STS config name (must match one of the configured STS names)
0050.0386	Could not find any STS client configuration with name {0}. Check to see if such an STS configuration exists!
Explanation	This error occurs if the configured ESB service that calls the pub.mediator.security.ws.AddSamlSenderVouchesToken specifies the STS config name incorrectly.
Action	Check if the specified STS config name matches one of the configured STSs in Mediator. The "ConfigName" service input value should be the same name (case-sensitive) as the STS name specified in Mediator Admin configuration page
0050.0388	Could not get SAML assertion from STS!
Explanation	A null assertion element was found in the STS client.
Action	Mediator sent a request to the configured STS to obtain a SAML assertion, but no valid assertion was obtained by the client. Please check the log file for any errors related to sending the WS-Trust request to the STS to obtain the token.
0050.0389	Adding OnBehalfOf element in WS-Trust request for IS user {0}
Action	Info level message, no action required.
0050.0390	Could not find base STS policy file: {0} !
Explanation	An exception was encountered while attempting to load a WS-Policy artifact from the file indicated in the message. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0391	Error occurred when getting STS configurations! Check to see if the ISTSClientConfigManager bean is configured!
Explanation	The STS configuration manager bean could not be found.
Action	This is a Spring bean configuration issue, the pg-config.xml file is missing or corrupted.
0050.0392	Could not find any STS configuration with the name {0}
Explanation	The STS client configuration identified in the message to be loaded or deleted could not be found.
Action	Verify that the STS configuration being loaded or deleted has an equivalent configuration file present under [IS_INSTALL_DIR\packages\WmMediator\config\resources\security\sts] directory. E.g. if the configuration being deleted is called MySTS, then there should be a file with name MySTS.xml in the mentioned directory
0050.0394	Error occurred when getting key aliases for keystore {0}: Error: {1}
Explanation	An exception was encountered while attempting to add a list of certificate aliases to the pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0395	Error occurred when getting keystore handles {0}
Explanation	An exception was encountered while attempting to add a list of keystore handles to the pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0396	Error when signing SAML assertion and SOAP request body
Explanation	An exception was encountered while attempting to sign a SAML assertion and request body. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0397	Error occurred when adding ws-addressing headers to outbound soap request; Error: {0}
Explanation	An exception was encountered while attempting to add WS-Addressing headers. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0050.0400	Using default timestamp value of 300s, because input TTL {0} is invalid (-ve or too big)
Explanation	The input value was not valid, a default was used.
Action	If the default is acceptable, no action is required. Otherwise update the configuration.
0050.0404	Response content type was empty! Falling back to original request content-type [{0}]
Explanation	The response message context contained an empty 'ContentType', so the type from the original request was used.
Action	This may be acceptable. If not, then configuration update will be required.
0050.0507	ScaDeploymentPayload.extractParts found no virtual service requests
Action	Info level message, no action required.
0050.0508	Unexpected exception, attempting to {0}, caught: type({1}), msg({2})
Explanation	An exception was encountered while attempting to process a deployment request. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0509	ScaDeploymentPayload.extractParts - Unable to find consumer file {0}, for component {1}
Explanation	The SCA deployment package was expected to contain a file to define the consumer identified in the message. The file was not found.
Action	This is a deployment payload construction problem.
0050.0510	Unexpected exception, attempting to process {0} request, caught: type({1}), msg({2})
Explanation	An exception was encountered while attempting to process a deployment request. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0515	ScaCompositeConfiguration found component with implementation type ({0})
Action	Info level message, no action required.

0050.0516	{0} - unable to convert string ({1}) to XMLGregorianCalendar: exception message ({2})
Explanation	The date element from the deployment payload has an unexpected format.
Action	This is problem with the contents of the deployment payload.
0050.0517	DeploymentPayload.{0} - input pipeline does not contain expected key ({1})
Explanation	The deployment payload must include an element with the key indicated in the message.
Action	This is problem with the contents of the deployment payload.
0050.0519	ScaDeploymentPayload - unable to delete temporary zip file: ({0})
Explanation	The file indicated in the message could not be deleted.
Action	Determine why the file could not be deleted and make it deletable.
0050.0520	DeploymentPayload - invalid request type: {0}
Explanation	The deployment payload type is unknown.
Action	This is a deployment payload construction problem.
0050.0528	DeploymentPayload - found null/empty virtual service descriptor for service {0}
Explanation	The deployment payload must contain a VSD. The VSD for the service identified in the message was not found.
Action	This is a deployment payload construction problem.
0050.0603	Error occurred when adding UsernameToken to SOAP Envelope: {0}
Explanation	An exception was encountered while attempting to add username token to the pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.
0050.0605	Error occurred when adding X.509 token to SOAP Envelope: {0}
Explanation	An exception was encountered while attempting to add X509 token to the pipeline. The associated exception message should include more details regarding the problem.
Action	Fix the problem identified by the exception message.

0070.0081	Removing the Content-Encoding header in response as the Accept-encoding is null
0201.0049	No Certificate was sent over HTTPS transport
MED.0010.0062E	Unable to get password for callback identifier: {0}
Explanation	Error while retrieving cleartext password from encrypted passman file store.
Action	Review Mediator STS configuration; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0010.0083W	Non-fatal Mediator package initialization error. {0}, {1}
Explanation	Mediator encountered an error during an upgrade processing step after the package initialization completed.
Action	Verify the overinstall upgrade steps were followed as defined in the documentation; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0010.0212E	Endpoint connection timeout duration expected as a number but was not a number ({0})
Explanation	A virtual service was deployed with an invalid connection timeout specified for its native provider endpoint.
Action	Review the advanced endpoint configuration in CentraSite and redeploy the service if necessary.
MED.0010.0214E	Both keystore and key alias must be specified or none at all for SSL configuration; KeyStore alias = [{0}]; Key alias = [{0}]
Explanation	A virtual service with a native provider SSL endpoint was deployed with an invalid advanced endpoint configuration. The endpoint must have a valid alias for both the keystore file and the keystore entry aliases as defined in the Integration Server or it can have no aliases defined at all.
Action	Update the advanced endpoint configuration and redeploy the virtual service to Mediator.

MED.0010.0217E	Error occurred when getting the password for handle {0} from passman!
Explanation	An attempt to retrieve a cleartext password from a passman encrypted file store failed.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0010.0218E	Error occurred when storing the password for handle {0} in passman!
Explanation	An attempt to save a password in a passman encrypted file store failed during Mediator STS configuration.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0010.0220E	Error converting given WS-Policy component to string
Explanation	Mediator was unable to parse policy elements used in producing request security tokens (RST) to a configured security token service (STS).
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0010.0702E	Mediator Upgrade, Mediator migration interrupted due to error. Details: {0}
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. It indicates the upgrade was not successful and further actions are required.
Action	Depending on the error message, one of the three options are available. 1) Resolve the issue causing the upgrade to fail, and restart the Integration Server again to see if the upgrade completes successfully. 2) Delete the mediatorUpgrade.xml file from installation path: \${IS_HOME}/packages/WmMediator/ directory. This is the file that causes Mediator to perform its upgrade step. If this action is taken, the Mediator configuration will have to be re-entered manually through the IS admin UI. 3) Contact support. Everytime the Integration Server is restarted, Mediator will attempt to perform an upgrade as long as its mediatorUpgrade.xml file is present in the package directory.

MED.0010.0705E	Mediator Upgrade, mediatorUpgrade.xml file is corrupted. Expected 'properties' root element but none found.
Explanation	This message indicates the mediatorUpgrade.xml file included after the installer completes a Mediator overinstall is corrupted. This file is normally installed into the \${IS_HOME}/packages/WmMediator/ directory path when the overinstall completes. Its presence causes Mediator to run its upgrade tasks during the next Integration Server restart. Once the upgrade task has completed, this file is removed ensuring the upgrade is run only once.
Action	Contact customer support or remove the mediatorUpgrade.xml file. The mediator package should load without error during the next Integration Server restart if this file is removed, but Mediator configuration must be set up manually through the IS admin UI.
MED.0010.0706E	Mediator Upgrade, unable to read required file. {0}
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. This message implies that the OS user running the Integration Server does not have adequate permissions to read the file referenced in the error message.
Action	Review user and file permissions and make necessary adjustments to ensure the file can be read.
MED.0010.0707E	Mediator Upgrade, configuration file is missing a required entry element key attribute. {0}, File path: {1}
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file used to control a Mediator overinstall upgrade is corrupted. It is missing a reference to an attribute containing a path to an archive of the previous Mediator version prior to the overinstall.
Action	Contact support.
MED.0010.0708E	Mediator Upgrade, configuration file entry element key attribute: {0}, expected this value: {1}, but found: {2}, File path: {3}
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file used to control a Mediator overinstall upgrade is corrupted.
Action	Contact support.

MED.0010.0709E	Mediator Upgrade, unable to find the required file. Expected location: {0}
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. The backup file archive containing the Mediator package prior to the overinstall upgrade cannot be found.
Action	Contact support.
MED.0010.0711E	Mediator Upgrade, unable to delete configuration file. Mediator upgrade task will continue to execute after each Integration Server startup until this file is removed. Path: {0}
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. Verify that the OS user account running the Integration Server has the necessary permissions to delete the file.
Action	If the log messages suggest the upgrade ran successfully, this file can be deleted; otherwise, contact support.
MED.0010.0712E	Mediator Upgrade, configuration file is not valid xml. Unable to parse it. {0}, Details: {1}
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file is corrupted.
Action	Contact support.
MED.0010.0717W	Mediator Upgrade, Could not find Default STS configuration file: {0} in archived zip file
Explanation	The default STS configuration file was not found when performing an overinstall upgrade.
Action	No action is necessary if migrating from Mediator 8.0; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0010.0718E	Mediator Upgrade, configuration file has unexpected element key attribute, {0}, with value. {1}, and configuration file path: {2}
Explanation	This log message may occur when the Mediator package loads during the Integration Server restart after an overinstall. The mediatorUpgrade.xml file is corrupted.
Action	Contact support.

MED.0010.0719E	Mediator Upgrade, Could not find Default STS configuration file: {0} following upgrade; Skipping migrating configuration data!
Explanation	Mediator was unable to locate the default STS configuration file during an overinstall upgrade.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0010.0720W	Mediator Upgrade, Could not load Default STS client configuration; Skipping migrating configuration data
Explanation	The default STS configuration file was not found when performing an overinstall upgrade.
Action	No action is necessary if migrating from Mediator 8.0; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0050.0279D	Callback not removed for message id, "{0}". Receiver: {1}, Properties: {2}
Explanation	When a service is invoked, the state for the invocation is stored in a callbackStore map until the response is returned. The callback object was not found in the map for the given message id.
Action	No action is necessary unless memory runs low. In that event, please contact support.
MED.0050.0280D	Message receiver not found for message id: "{0}", Properties: {1}
Explanation	Synapse callback receiver used to process the provider response is not found.
Action	Please contact support.
MED.0050.0281D	Outbound message id not found. "{0}", Properties: {1}
Explanation	The message id used to correlate a native provider request was not found.
Action	Please contact support.
MED.0050.0408E	Authentication failed for user {0}
Explanation	Invalid basic authentication credentials were included in the Authorization header sent to a virtual service that has a "Require HTTP Basic Authentication" runtime security policy.
Action	The web service consumer should include proper credentials and resend the service request.

- MED.0050.0608E** **Error occurred when adding Timestamp to SOAP Envelope: {0}**
Explanation Mediator was unable to insert a WS security timestamp element to the request's security header sent to the native provider.
Action Review the configured ESB "AddTimestamp" service call for virtual service and redeploy if incorrect. Otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
- MED.0070.0010E** **Incoming request does not contain the 'Authorization' header. This service requires the HTTP Basic Authentication token to be present!**
Explanation No Authorization header was sent to a virtual service that has a "Require HTTP Basic Authentication" runtime security policy.
Action The web service consumer should include proper credentials and resend the service request.
- MED.0070.0032E** **Unable to create Schema for this service "{0}" Schema validation may not succeed!**
Explanation Mediator was unable to initialize the schema parser for a virtual service with a "Validate Schema" runtime policy. This error occurs when a consumer sends Mediator a service request.
Action Review the schemas defined in the virtual service, make corrections, and redeploy the virtual service if necessary; otherwise, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
- MED.0070.0071W** **The ESB service name specified for InvokeESB mediator cannot be empty!**
Explanation A virtual service was deployed containing an ESB service invocation step containing an invalid or missing service name.
Action Review all service invocations from the "Processing steps" configuration for the virtual service and redeploy if necessary.
- MED.0070.0072E** **The 'service' attribute is required for the InvokeESB mediator definition**
Explanation The deployed virtual service configuration is corrupted.
Action This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0070.0073W	Did not invoke ESB service, because the service name was either empty or invalid (must be of the form folder1.folder2:service)
Explanation	A virtual service was deployed containing an ESB service invocation step with an invalid or missing service name.
Action	This warning is logged when a virtual service request is executed. See the action defined for MED.0070.0071.
MED.0200.0045E	Error saving EhCache configuration file: {0}
Explanation	Mediator was unable to save its configuration file used for the Terracotta cache component.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0200.0046E	Could not find specified EhCache configuration file: {0}
Explanation	The Terracotta cache configuration file for Mediator's caches could not be found during package startup.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0203.0062E	ControllingNodeLocker.run, thread id({0}), expected Ehcache, found ({1})
Explanation	Unexpected content was returned in the Terracotta cluster status cache.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0203.0065E	ControllingNodeLocker.run, thread id({0}), caught ({1}/{2}) attempting to get a lock, thread dies
Explanation	Mediator encountered an error trying to obtain a lock on the controlling node in a Terracotta cluster.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0203.0070I	ClusterStatusCache - cache manager for {0} returned null CacheCluster reference, not clustered?
Explanation	Mediator was unable to obtain a reference to the configured Terracotta cluster.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0203.0071I	{0} - getCluster(ClusterScheme.TERRACOTTA) threw exception {1}, using schema NONE
Explanation	An attempt to get Terracotta cluster configuration details failed.
Action	If Mediator is configured for a Terracotta cluster, this is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0203.0072E	ClusterStatusCache - thread id({0}) attempts to release {1} lock, but does not hold it
Explanation	An attempt to release the lock on the node controller in a Terracotta cluster failed.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0203.0073E	Error initializing JAXB Context: {0}
Explanation	Initialization for the cached global or registered consumers deployed to Mediator has failed.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0203.0075E	ControllingNodeLocker.run, thread id({0}), caught {1} attempting to ask about lock status, thread dies
Explanation	The thread defining the controlling node in a Mediator cluster encountered an error.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0203.0076E	Unable to get cache named {0} from cache manager {1}
Explanation	Mediator encountered an error accessing one of the Terracotta caches.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0203.0081E	{0}, thread id({1}), caught {2}/{3} attempting to release lock, thread dies
Explanation	Mediator encountered an error releasing the lock on the controlling node in the Terracotta cluster.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0203.0082E	EhcacheClusterStatusCache, thread id({0}), caught {1}/{2} attempting to update controlling lock in cache
Explanation	Mediator encountered an error updating the controlling node in a Terracotta cluster.
Action	This is an internal error. Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.
MED.0203.0100W	Thread interrupted when trying to obtain {0} lock for cache {1}
Explanation	While Mediator was attempting to obtain a lock on a cache entry key, its thread was interrupted.
Action	No action may be necessary if Mediator is functioning normally.
MED.0203.0101E	Unable to {0} lock the {1} cache for key {2} after waiting {3} mSecs
Explanation	Mediator failed to lock a cache key in the expected period of time.
Action	No action may be necessary if Mediator is functioning normally
MED.0203.0103E	{0} task in thread {1} threw this: {2}
Explanation	An error occurred in the controlling node of a Terracotta cluster during Mediator shutdown.
Action	Contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

MED.0205.0062E **UddiPerformanceMetricsSender - unable to publish metrics over UDDI for service: {0}, message: {1}**

Explanation This log message is produced when Mediator is unable to publish performance metrics results to Mediator. When reviewing the content, please be aware that some exception details may have originated from the CentraSite product hosting the UDDI server. Errors can range from improper Mediator configuration, OS resource issues, network connectivity, or issues with the CentraSite installation.

Action Depending on the errors logged in the Mediator UI, one of the following actions may prove more relevant. Verify CentraSite configuration information regarding UDDI is correct for the Mediator UI. Verify the hostname or IP address is reachable from the computer running the Mediator instance. Verify the CentraSite instance and its repository is up and accessible.

MED.0205.0063E **Unable to initialize UddiClientAdapter due to a missing password for username: {0}.**

Explanation This log message is produced when Mediator is unable to publish performance metrics results to Mediator. A password was not found in the encrypted store for the user configured in the CentraSite panel of the Mediator UI.

Action Verify the password is entered and the configuration was successfully saved for the CentraSite configuration screen in the Mediator UI.

MED.0205.0064E **Error connecting to CentraSite UDDI registry running on {0}://{1}:{2}. Error: {3}**

Explanation This log message may be produced under the following situations: During Mediator package startup. CentraSite configuration entered in Mediator UI is saved, but a connection to the UDDI server fails for these settings. Mediator attempts to publish performance metrics but fails during its regularly scheduled interval.

Action Verify the CentraSite configuration values in the Mediator UI are correct and CentraSite is up and running.

MED.0205.0067E **Error disconnecting to CentraSite UDDI registry running on {0}://{1}:{2}. Error: {3}**

Explanation This log message may be produced during the following situations: During Mediator package shutdown. While Mediator is initializing communications with the CentraSite UDDI server after encountering an error during runtime or saving configuration values in the Mediator UI.

Action Please see the Action for 0205.0064

MED.0205.0602E	Missing "{0}" Jdbc destination pool from spring configuration
Explanation	One of the Mediator configuration files is corrupted and a necessary configuration element is missing.
Action	Contact support.
MED.0205.0603E	Jdbc destination sender expected a JdbcEvent object but received: "{0}"
Explanation	The JDBC destination sender event component received an unexpected event type.
Action	Contact Support.
MED.0205.0604E	Jdbc destination sender encountered a Sql Exception while generating "{0}" events. Error Code: {1} Cause: {2}
Explanation	The Mediator Jdbc destination sender component encountered a SQL exception while sending a runtime event.
Action	Verfiy the database is operational and restart the functional alias pool. Verify the MediatorEvents database component tables installed using the Common Database Component are still defined, and the Jdbc pool credentials defined in Integration Server are correct. If all else fails, please contact Support.
MED.0205.0605D	Jdbc destination sender took {0} msecs to get a connection out of data source.
Explanation	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to get a Jdbc connection exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 50 milliseconds.
Action	No action is necessary.
MED.0205.0606D	Jdbc destination sender took {0} msecs to get a prepared statement out of connection with this SQL: {1}.
Explanation	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to get a Jdbc prepared statement exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 50 milliseconds.
Action	No action is necessary.
MED.0205.0609D	Jdbc destination sender took {0} msecs to close the prepared statement and connection.
Explanation	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to close a Jdbc connection exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 50 milliseconds.
Action	No action is necessary.

MED.0205.0610E	Jdbc event requires at least one sql clause to be valid.
Explanation	The Mediator Jdbc component is in an invalid state.
Action	Contact Support.
MED.0205.0611D	Jdbc destination sender took {0} msec to insert a batch of {1} "{2}" events. AutoCommit enabled on driver? {3}, Transaction Isolation level? {4}
Explanation	If the '0205 MEN - Events' Mediator logging component is set to 'DEBUG', then Mediator will issue a log message if the time it takes to execute a batch of runtime event inserts into the database exceeds a pre-defined threshold as defined in Mediator's pg-jdbc.xml file. The current default is 500 milliseconds.
Action	No action is necessary unless the time is extremely large. In that case, consider reducing the 'pg.jdbc.batchSize' property in Mediator's pg-config.properties file. This will cause the Jdbc destination sender to send updates to the database server in smaller batches.
MED.0205.0612E	Jdbc destination sender cannot use a read-only connection object to insert events.
Explanation	The functional alias used by Mediator's Jdbc destination sender is configured for a read-only transaction model in the Integration Server admin.
Action	Change the configured transaction model so it supports updates to the database.
MED.0205.0614E	Jdbc event sql range should be between 0 and {0}, {1} is out of range.
Explanation	Mediator Jdbc component is in an invalid state.
Action	Contact Support.
MED.0205.0615E	Jdbc performance metrics processor expected only one return key, but "{0}" were found.
Explanation	The Mediator Jdbc component is in an invalid state.
Action	Contact Support.
MED.0205.0616E	Jdbc performance metrics processor expected two SQL statements, but "{0}" were found.
Explanation	The Mediator Jdbc component is in an invalid state.
Action	Contact Support.

MED.0205.0617E	Jdbc performance metrics processor is missing returned primary key upon SQL insert
Explanation	Database did not return the 'event_pk' primary key column for the event inserted into the mediator_metrics_event table.
Action	Verify database is functioning properly; otherwise, contact Support.
MED.0205.0618E	Jdbc event is in a bad state. Data type count "{0}" does not equal column value count "{1}"
Explanation	The Jdbc event destination component is in an invalid state.
Action	Contact Support.
MED.0205.0619W	Jdbc driver doesn't support returned named SQL columns from Insert statement. Trying "Statement.RETURN_GENERATED_KEYS" mode.
Explanation	The Jdbc event destination component will attempt to use named columns for returning the database-generated primary key after inserting a row. If the database driver does not support this feature, this log message is raised, and the component will use another method to return the inserted primary key.
Action	No action required unless other SQLException errors are raised.
MED.0206.0035W	MAC cache update {0} operation took {1} milliseconds to complete for {2} SIEs. This could cause lock attempts for tallying metrics statistics in MAC cache to fail.
Explanation	An update to the policy engine metrics data took longer than expected. When the duration of this task is longer than the configured lock request timeout, tasks can be lost when they fail to obtain exclusive locks.
Action	Review Integration Server performance and increase the advanced property for lock timeout pg.PgMenSharedCacheManager.lockTimeOut and restart IS. Otherwise, if this happens very frequently, contact webMethods Customer Care. Please produce a diagnostic zip file by running the mediator.util:mediatorDiagnosticZip service from the WmMediator package's list of services in IS Admin's package management menu if available.

17

My webMethods Server Messages

ClassPathComponentsMapper.folder.cannot.read – Cannot read from folder.

Explanation Cannot read from file. The file was deleted with no read rights.

Action Check to see if the file exists and if you have read rights.

ClassPathComponentsMapper.folder.not.exists – The folder does not exist:

Explanation The provided folder does not exist.

Action You must specify an existing folder.

ClassPathComponentsMapper.folder.not.valid – The specified path is not a valid folder.

Explanation The specified path is not valid folder; it might be a file and not a folder.

Action Specify a valid folder path.

Error.POP.0.0.001 Error sending mail

Explanation When a forum message is retracted, an e-mail notification is sent to the configured forum administrator. This error occurs if there are any problems sending this e-mail to the administrator.

Action Check the My webMethods Server logs for additional information about the specific e-mail failure. It may be caused by the e-mail server not being available, or because of an invalid forum administrator e-mail address. See Check the My webMethods Server logs for more details. See ..\MWS\server\\logs

POP.001.0002E	A "{0}" occurred with the Message "{1}"
Explanation	An unexpected error occurred during deployment.
Action	Examine the install.log, and optionally try again. In the log file, look for any information specific to the deployed component.
POP.002.0004E	Context is in an invalid state.
Explanation	The server attempted to use an invalid context object. This error is the result of attempting to use a context object before it has been initialized or after it has been uninitialized.
Action	Always use the provider <code>com.webmethods.portal.bizPolicy.IContextProvider</code> (available through the <code>com.webmethods.portal.system.PortalSystem</code>) to acquire a context object.
POP.002.0005E	Unable to locate command: {0}
Explanation	The requested command is not deployed on the server.
Action	Log in to My webMethods Server and use the Install Administration portlet to deploy the command to the server.
POP.002.0006E	Unable to locate biz policy for resource: {0}
Explanation	The server cannot resolve the business policy for the specified resource because no policy has been registered for the resource type.
Action	Create and register a business policy for the resource type. Consult the My webMethods Server documentation to learn more about business policies.
POP.002.0007E	Unknown error encountered while trying to resolve business policy for uri {0}
Explanation	The server cannot resolve a business policy for specified resource because of an internal error.
Action	Check the <code>_problems_.log</code> in the <code>..\MWS\server\default\logs</code> directory for more specific error information.
POP.002.0008E	Uri is not a valid thingID: {0}
Explanation	The server cannot invoke the <code>RemoveAccess</code> command on a resource that is not a metadata resource.
Action	Correct the command-invoking source code to specify a metadata resource using either the <code>'resourceURI'</code> parameter or the context's current resource.

POP.002.0009	Invalid arguments to create Alias command
Explanation	You cannot invoke this command without the required arguments: key and target.
Action	If you invoked this command programatically, review the Javadocs and make the required changes to the invoking code.
POP.002.0010	The arguments are not valid
Explanation	When invoking the alias commands you must supply valid arguments.
Action	If you invoked this command programatically, review the Javadocs and make the required changes to the invoking code.
POP.002.0011	You cannot flush another user's cache
Explanation	Only an Administrator can flush another user's cache.
Action	You must log in to My webMethods Server with Administrator credentials to be able to flush another user's cache.
POP.002.0012E	Class group name is not specified
Explanation	You must specify the groupName parameter when invoking the ReloadClasses command.
Action	Correct the command-invoking code to specify the 'groupName' parameter. The parameter value should be the name of the group's class-loader bundle.
POP.002.0014E	Unable to authenticate user: {0}
Explanation	The server cannot authenticate the user either because the user does not exist or because the user's password is incorrect.
Action	Try again with correct username and password. If necessary, log in to My webMethods or My webMethods Server and use the User Management feature to add the user to the server
POP.002.0016E	Error listing directory groups
Explanation	The server cannot list the groups of a particular directory service, most likely because of a problem connecting to the directory service.
Action	If the directory service is a newly configured directory service, log in to the My webMethods Server and double-check the configuration using the Folders > System > Portlets > Administration > Directory Services Administration portlet. If the directory service is an existing directory service for which groups could be listed previously, validate that the LDAP or ADSI server to which the directory service is connected is up and running properly. Also check that the machine which hosts My webMethods Server is able to connect to the LDAP or ADSI server using the hostname and port specified in the directory service's configuration.

POP.002.0017E	Error retrieving template list
Explanation	The server cannot list directory service templates, because an error occurred loading the templates.
Action	Check the ..\MWS\server\default\logs_problems_.log file for more specific error information.
POP.002.0018E	Error listing users
Explanation	The server cannot list the users of a particular directory service, most likely because of a problem connecting to the directory service.
Action	If the directory service is a freshly configured directory service, go back to the Portal Admin Dashboard, and double-check the configuration using the Directory Service Administration portlet (in the Portal Configuration category). If the directory service is an existing directory service for which groups could be listed previously, validate that the LDAP or ADSI server to which the directory service is connected is up and running properly. Also check that the machine which hosts the Portal server is able to connect to the LDAP or ADSI server using the hostname and port specified in the directory service's configuration.
POP.002.0019E	Error updating directory
Explanation	The server cannot update the directory service configuration because an error occurred in validating or storing the configuration settings.
Action	Check the ..\MWS\server\default\logs_problems_.log file for more specific error information.
POP.002.0020	Invalid command ID: {0}
Explanation	The requested command is not found.
Action	Verify that the command has been properly installed. This can be done by logging in to My webMethods Server as sysadmin and viewing the commands in the folder Folders > System > Manager > Commands directory.
POP.002.0021E	Cannot resolve install mechanics for: {0}
Explanation	An error occurred during the installation of a server component.
Action	Look in the ..\MWS\server\default\logs_problems_.log file for the stack trace of the error. The stack trace may not provide enough detail to say why the error was thrown, but it will show where the error originated.

POP.002.0022	Location is not a folder: {0}
Explanation	When the Install Services commands are instructed to deploy all of the components of a folder, the resource must be a folder and cannot be a file.
Action	Ensure that either the Autodeploy folder is properly configured or that the object passed to the InstallComponents command is a folder.
POP.002.0023	Cannot find folder: {0}
Explanation	When the Install Services commands are instructed to deploy all of the components of a folder, the folder must be available.
Action	Ensure that either the Autodeploy folder is properly configured or that the object passed to the InstallComponents command is an available folder.
POP.002.0025E	Command name is not specified
Explanation	The Ant build file does not contain the command name needed to invoke the ExecuteCommand ant task.
Action	Correct the Ant build file to provide the command name with the 'name' attribute of the ExecuteCommand task.
POP.002.0026E	Cannot resolve command [name, type] [{0}, {1}]
Explanation	The server cannot execute the command by means of an Ant task because the specified command has not been deployed to the server.
Action	Deploy the command specified by the error message.
POP.002.0027E	Attribute target is required
Explanation	The target for invoking the ExecuteTargetLoop Ant task has not been specified.
Action	This error can occur if a developer modifies an Ant build file used to deploy components to the server. Correct the Ant build file to add a 'target' attribute to the ExecuteTargetLoop task invocation.
POP.002.0028E	Cannot create IInitializableComponentData from: {0}
Explanation	The component configuration data is not one of the following types: xml (serialized XML document), xmlLocation (URL specifying an XML document), properties (serialized properties map), propertiesLocation (URL specifying a properties file location).
Action	Correct the component configuration in the phaseProvider.xml configuration file to specify component configuration data as either xml, xmlLocation, properties, or propertiesLocation.

POP.002.0029E	Attribute source is required
Explanation	The server cannot execute an Ant task because the task requires a source attribute to be specified.
Action	Correct the Ant build file to add a 'src' attribute to RunJavaScript and RunSQLScript tasks. The 'src' attribute must specify the file path to the script to be run.
POP.002.0030E	Cannot create IInitializableComponentData from {0} for provider {1}
Explanation	The server cannot unregister the specified component. The component's configuration data has become corrupted.
Action	Reinstall the component with the Folders > Administrative Folders > Administration Dashboard > Configuration > Install Administration portlet, and then re-try uninstalling the component.
POP.002.0031	Cannot find IComponent using IComponentData {0} in provider {1}
Explanation	An attempt was made to unregister a component that is not currently registered.
Action	No further action is required.
POP.002.0032E	Cannot get IComponentData for component {0} from provider {1}
Explanation	An error occurred during the unregistration of a server component.
Action	Look in the ..\MWS\server\default\logs_problems_.log file for the stack trace of the error. The stack trace may not provide enough detail to say why the error was thrown, but it will show where the error originated. It is likely that you need to restart the server.
POP.002.0033E	Component Provider not found: {0}
Explanation	The server cannot unregister the component because component data has become corrupted.
Action	Re-install the component with the Folders > Administrative Folders > Administration Dashboard > Configuration > Install Administration portlet, then re-try uninstalling.
POP.002.0034E	Attribute descriptorSrc is required
Explanation	The Ant task does not have skin descriptor content.
Action	Correct the Ant build file to provide skin descriptor content using the 'descriptorSrc' attribute to CreateSkinInstance, GetSkinInfo, and RemoveSkinInstance Ant tasks.

POP.002.0035E	Skin name is empty
Explanation	The server cannot determine the skin name because the skin descriptor does not contain the skin name or because the skin descriptor is improperly structured.
Action	Correct the skin descriptor to include the skin name in the 'name' attribute value of the 'wm_xt_skin' element.
POP.002.0036E	Portlet info is not specified
Explanation	Portlet descriptor content is not included in the GetPortletInfo Ant task.
Action	Correct the Ant build file to provide portlet descriptor content using the 'descriptorSrc' attribute.
POP.002.0037E	Portlet name is empty
Explanation	The server cannot determine the portlet name because the portlet descriptor does not contain the portlet name or because the portlet descriptor is improperly structured.
Action	Correct the portlet descriptor to include the portlet name as the content of the 'name' element.
POP.002.0038E	Portlet is not available: {0}
Explanation	The specified portlet is not deployed on the server.
Action	Use the Folders > Administrative Folders > Administration Dashboard > Configuration > Install Administration portlet to deploy the portlet specified by the error message.
POP.002.0040E	Cannot find system folder for the portlet: {0}
Explanation	An error occurred during installation of a portlet.
Action	Look in the ..\MWS\server\default\logs_problems_.log file for the stack trace of the error. It may be necessary to reinstall the component.
POP.002.0041	Page have to be a folder type
Explanation	When cloning pages, the source of the cloning operation must be of the appropriate type
Action	Ensure that an appropriate source is used for the cloning operation.

POP.002.0042E	Destination container is not a valid thing: {0}
Explanation	The server cannot clone a remote resource; the resource must be cloned to a metadata destination container.
Action	Correct the command-invoking source code to specify a metadata destination container using the 'destContainerURI' parameter.
POP.002.0043E	Source item container is not a valid thing: {0}
Explanation	The server cannot clone the remote resource; only metadata resources can be cloned.
Action	Correct the command-invoking source code to specify a metadata resource using either the 'resourceURI' parameter or the server context's current resource.
POP.002.0044E	Invalid XType: {0}
Explanation	The server cannot resolve the DBO type of the remote item to be cloned. The most likely reason is that the DBO type has been uninstalled from the system.
Action	Normally, a DBO type cannot be uninstalled from the system until all instances of the type have been deleted. This message may also indicate that a damaged instance of the remote item is still present but cannot be cloned or recovered. No further action can be taken.
POP.002.0046E	Item is not a valid thing: {0}
Explanation	The server cannot invoke the metadata command because the command must be invoked against a metadata resource.
Action	Correct the command-invoking source code to specify a metadata resource using either the 'resourceURI' parameter or the server context's current resource.
POP.002.0047	Can not create an item with an empty name
Explanation	When creating a new resource, a 'name' property is required.
Action	When creating the resource, ensure that a name is supplied.
POP.002.0048E	Delete operation failed
Explanation	The container cannot be deleted because at least one of the items in the container cannot be deleted. Refer to the the list of contained items that cannot be deleted, displayed in the user interface along with this message.
Action	Manually delete the specified undeletable contained items individually. This may result in more detailed information as to why the items cannot be deleted.

POP.002.0049E	Error obtaining owned folder
Explanation	The server cannot obtain the owned folder because of an internal server error.
Action	Check the ..\MWS\server\default\logs_problems_.log file for more specific error information.
POP.002.0050E	Cannot get current resource uri
Explanation	Cannot invoke the portlet command because a target portlet for the command is not specified.
Action	Correct the command-invoking code to specify the portlet with the 'resourceURI' parameter or with the server context's current resource.
POP.002.0051E	ResourceURI is not specified
Explanation	The server cannot invoke the portlet command because a target portlet for the command is not specified.
Action	Correct the command-invoking source code to specify the portlet with the 'resourceURI' parameter or with the server context's current resource.
POP.002.0052E	PortletBean is not ICommandBean
Explanation	The command cannot be invoked against the portlet because the portlet's portlet-bean does not implement the com.webmethods.portal.bizPolicy.command.ICommandBean interface.
Action	Modify portlet's portlet-bean source code to make the portlet-bean implement ICommandBean. Rebuild and redeploy the portlet.
POP.002.0053E	UserID is not of type IThingID or String
Explanation	The command was invoked using RMI with an inappropriate userID data type. This error is usually a result of a bug in the command-invoking code.
Action	Correct the command-invoking code to ensure it invokes the command with a userID specified either as a java.lang.String or a com.portal.webmethods.meta2.thing.IThingID object.
POP.002.0054E	Search library not found: {0}.
Explanation	An attempt was made to delete a search library that does not exist.
Action	Log in to My webMethods Server and use the Search Administration portlet to check the name of the search library against the available libraries.

POP.002.0056E	Saved Searches folder not found.
Explanation	The server cannot save a search because the user's saved-searches folder does not exist.
Action	User folders such as the user's saved-searches folder are created automatically for users when they login to My webMethods Server. Try logging out as the user, and then logging in again.
POP.002.0057E	No name parameter found
Explanation	The server cannot invoke the save-search command name; the command does not specify a name parameter.
Action	Correct the command-invoking source code to specify a 'name' parameter.
POP.002.0058E	Not a valid skin: {0}
Explanation	The server cannot invoke the ReloadSkin command; the specified skin identifier does not identify a valid skin.
Action	Correct the command-invoking source code to specify a valid skin resource using the 'skin' parameter.
POP.002.0059E	Default xmlimport requires an IThingID for the parent: {0}
Explanation	The server cannot import a metadata resource using xmlImport unless the parent of the resource is also a metadata resource.
Action	Correct the xmlImport file to move or remove elements contained by the element specified by the error message.
POP.002.0060	Default xmlimport requires the parent to be a container: {0}
Explanation	When executing an XML import script, every new child must be created within a valid container.
Action	Check the script to ensure that each created item has a valid parent.
POP.002.0061E	Unable to locate acl for aclName: {0}
Explanation	The server cannot modify the access control list (ACL) for a resource specified in xmlImport because the access control list was referenced by an alias that does not exist.
Action	Correct the xmlImport file to replace the 'aclName' attribute value specified by the error message with a valid value.

POP.002.0062E	Unable to find value for acl
Explanation	The server cannot create an access control entry using xmlImport because the ACL element requires a value attribute.
Action	Correct the xmlImport file to add a 'value' attribute to the 'acl' elements. The 'value' attribute values must contain one of the following My webMethods Server access right names (comma separated): READ, CREATE_ITEM, CREATE_CONTAINER, MODIFY, DELETE, PORTLET_MODIFY_PROPERTIES_INSTANCE, PORTLET_MODIFY_PROPERTIES_USER, ALL.
POP.002.0063E	Unable to find ace value for: {0}
Explanation	The server cannot create access an control entry using xmlImport because the xmlImport entry references an unknown right value.
Action	Correct the xmlImport file to add a 'value' attribute to the 'acl' elements. The 'value' attribute values must contain one of the following My webMethods Server access right names (comma separated): READ, CREATE_ITEM, CREATE_CONTAINER, MODIFY, DELETE, PORTLET_MODIFY_PROPERTIES_INSTANCE, PORTLET_MODIFY_PROPERTIES_USER, ALL.
POP.002.0064	Unable to find alias name to set the acl
Explanation	The required argument 'value' was not set on this xmlimport element.
Action	Ensure that the ACL element has a 'value' attribute
POP.002.0065E	Alias attribute missing on context node
Explanation	The server cannot establish the resource context during xmlImport because the context element requires an alias attribute.
Action	Correct the xmlImport file to add an 'alias' attribute to 'context' elements. The alias attribute value must contain the name of a valid alias; elements enclosed by the context apply to the resource identified by this alias.
POP.002.0069S	Root users folder not found
Explanation	The server cannot create the user's home folder because the server users folder does not exist.
Action	Create a new server folder, and set its alias to 'folder.users'.

- POP.002.0076E The basic update properties requires a thingID: {0}**
Explanation The server cannot invoke the ImportFiles command because it does not specify a target folder for the import.
Action Correct the command-invoking source code to specify a folder using either the 'resourceURI' parameter or the server context's current resource.
- POP.002.0077E Adding to version control requires a thingID: {0}**
Explanation The server cannot invoke the version-control command without specifying a versionable resource.
Action Correct the command-invoking source code to specify a versionable resource using either the 'resourceURI' parameter or the server context's current resource.
- POP.002.0078E The resource does not support IVersionableMechanics: {0}**
Explanation The server cannot invoke the version-control command on the resource because the resource is not versionable.
Action Do not invoke the AddToVersion command against resources that are not versionable. Only server folders and server content items are versionable.
- POP.002.0079E Command requires a thingID: {0}**
Explanation The server cannot invoke the version-control command without specifying a versionable resource.
Action Correct the command-invoking source code to specify a versionable resource using either the 'resourceURI' parameter or the server context's current resource.
- POP.002.0080E Invalid version Uri: {0}**
Explanation The server cannot display the server version information of an item because the identifier used to specify the version is not a valid version identifier.
Action Correct the source code that invokes the ViewVersion command to provide a valid version identifier.
- POP.002.0081E Invalid thing ID: {0}**
Explanation The server cannot display the server version information of an item because the identifier used to specify the item does not identify a valid resource
Action Correct the command-invoking source code to provide a valid versioned-item identifier for the 'targetURI' parameter.

POP.002.0082	User {0} don't have rights to view {1}
Explanation	The current user failed the permissions check to see a particular version of an item.
Action	Check the permissions on that item.
POP.002.0083E	Could not acquire context, principal data not found on session
Explanation	The server cannot create a server context for the specified javax.servlet.http.HttpSession because the HttpSession has not been initialized with the necessary server session data.
Action	Restart My webMethods Server.
POP.002.0085E	Can't create subscription for non Thing: {0}
Explanation	The server cannot create a subscription from xmlImport data because subscriptions are supported only for metadata resources.
Action	Correct the xmlImport file to remove 'subscription' elements from non-metadata resource contexts. The best way to determine specifically which subscription elements in the xmlImport file are causing this error is the trial-and-error approach: remove each subscription element in the xmlImport file one by one and then try re-importing from the xmlImport file.
POP.002.0086E	Unable to import xml. No uid.
Explanation	An attempt to create an access control entry or subscription using xmlimport did not specify the user ID of the My webMethods Server user or group.
Action	Correct the xmlImport file to add a 'uid' attribute to 'subscription' and 'ace' elements. The 'uid' attribute value must contain the user ID (LDAP user ID) of a valid My webMethods Server user or the cn (LDAP group ID) of a valid My webMethods Server group.
POP.002.0087W	Unable to import xml. Could not acquire uri for uid: {0}
Explanation	The user referenced in the xmlImport file does not exist on My webMethods Server.
Action	Log in to My webMethods or My webMethods Server with appropriate permissions and add the user, or change the xmlImport file.
POP.002.0089E	Unable to import subscription. No value specified for 'deliveryMode'.
Explanation	The server cannot create a subscription from xmlImport data because the subscription element requires a deliveryMode attribute. This error is caused by importing from an improperly constructed xmlImport file.
Action	Correct the xmlImport file by adding a 'deliveryMode' attribute to 'subscription' elements. The valid value for 'deliveryMode' attribute is "email", indicating notifications for this subscription are to be delivered to the user's e-mail address.

POP.002.0090E	Unable to import subscription. No value specified for 'criteria'.
Explanation	The server cannot create the subscription from xmlImport data because the subscription element requires a criteria attribute that contains the name of at least one criterion valid for the type of resource subscribed to.
Action	Correct the 'subscription' elements in the xmlImport file so that they all contain valid 'criteria' attribute values. Valid values are not empty; they must contain a comma-separated list of criterion names. The criterion names for basic folders are: 'added', 'removed', 'modified', 'deleted', and 'moved'. The criterion names for basic links, forms, portlets, and content items are 'modified', 'deleted', and 'moved'. Custom DBO types may have additional criteria.
POP.002.0091E	No matching criteria found for type: {0} and for criteria: {1}.
Explanation	The server cannot create a subscription from xmlImport data because the subscription element requires a criteria attribute that contains the name of at least one criterion valid for the type of resource subscribed to.
Action	Correct the xmlImport file so that 'subscription' elements contained by any element of the type specified by the error message's resource-typeName have valid 'criteria' attribute values. Valid values are not empty; they must contain a comma-separated list of criterion names. The criterion names for basic folders are: 'added', 'removed', 'modified', 'deleted', and 'moved'. The criterion names for basic links, forms, portlets, and content items are 'modified', 'deleted', and 'moved'. Custom DBO types may have additional criteria.
POP.002.0092E	Can't set ace for non Thing: {0}
Explanation	The server cannot modify the access control entry (ACE) for a resource specified in xmlImport because the resource does not support My webMethods Server access control entries.
Action	Correct the xmlImport file to remove the 'ace' element for the resource specified by the error message.
POP.002.0093E	Unable to locate alias for: {0}
Explanation	The server cannot establish the resource context during xmlImport because the alias specified for the context does not exist.
Action	Log in to My webMethods Server and use the Alias Management portlet to create the alias specified by the error ,message or fix the xmlImport file to use an alias that does exist. To fix the xmlImport file, locate the alias attribute with the value specified by the error message and replace that value with the name of an existing alias.

POP.002.0095	Unable to create alias: {0} because it already exists.
Explanation	The command failed because an alias of the same name has already been registered.
Action	Either apply a different name to the new alias or modify the existing alias that uses the same name.
POP.002.0096E	Mechanics is not an IBasicMechanics
Explanation	The server cannot use xmlImport to update the properties of a resource that is not a metadata resource.
Action	Correct the xmlImport file to not update the properties of non-metadata resources. The best way to determine the element in the xmlImport file that is causing this error is the trial-and-error approach: remove each element in the xmlImport file one-by-one and then try re-importing from the xmlImport file.
POP.002.0097E	Unable to complete import because type: {0} doesn't exist.
Explanation	The server cannot import a resource specified in xmlImport because the resource is an instance of a DBO that is not currently deployed in My webMethods Server.
Action	Deploy the DBO specified by the error message and then rerun the xmlImport.
POP.002.0098	Role xmlimport requires attributes of 'roleProvider' and 'name'
Explanation	When creating a new role using an xmlImport script, the attributes must be available.
Action	Modify the xmlimport script to include the required 'roleProvider' and 'name' properties.
POP.002.0099	Role xmlimport unable to locate roleProvider: {0}
Explanation	The type of role is not registered on the current system.
Action	Check the 'roleProvider' attribute to make sure it is correct.
POP.002.0103	Failed to set Alias {0} for resource {1}.
Explanation	The system failed to correctly set an alias during the xmlimport.
Action	Check the server logs at ..\MWS\server\default\logs for any additional exceptions that occurred during the import.

POP.002.0105	Failed to load xml document from {0}
Explanation	The XML file specified for the xmlimport script is either not found or not well-formed.
Action	Verify that the XML file exists in the specified location and that the contents of the file are valid XML.
POP.002.0107	Failed to invoke remote command: {0}. Original error message: {1}
Explanation	A problem occurred when executing a command on a remote server.
Action	Check the logs on the remote server for additional information.
POP.002.0108	User UID can not be found in MWS directories: {0}
POP.002.0109	Unable import CAF Runtime, CAF application does not exist: {0}
POP.002.0110	You have insufficient privileges to impersonate other users.
POP.002.0111	Illegal Argument: Command result may not be serialized.
POP.002.0112	Unable to locate the portlet type for component: {0}
POP.002.0113	The parent of the task is already completed
POP.002.0114	User {0} does not have the functional privilege to delegate task {1}
POP.003.0003S	No access model specified in property "{0}".
Explanation	The framework.access.model system property does not specify an access model.
Action	Update the portal.properties file to specify framework.access.model property value. The choices are permissive or restrictive.
POP.003.0004S	Unable to register principal types: "{0}".
Explanation	The system directory is corrupted.
Action	Restore the underlying system user directory content from a backup or manually restore the user directory. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.

POP.003.0005S	Unable to register search service: "{0}".
Explanation	An error occurred in registering a new search service.
Action	You might need to reinstall My webMethods Server.
POP.003.0006S	Error initializing content service: "{0}".
Explanation	The content service cannot be initialized.
Action	Check the Content Service Administration portlet to verify that the content service is properly configured.
POP.003.0007E	Cannot list roles, directory service "{0}" not found.
Explanation	The directory service cannot be found.
Action	Check the Directory Service Administration portlet to verify that the directory service is properly configured and functional.
POP.003.0008E	Could not locate system directory: "{0}".
Explanation	The server cannot find the system user directory.
Action	Verify that the system directory is present in Directory Services Administration portlet, and that it is configured and functional.
POP.003.0009E	Error setting system directory: "{0}".
Explanation	The command failed to change the system directory service.
Action	Do not attempt to change the system directory.
POP.003.0012W	"{0}" does not have permission to modify the Administrators group.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu to open the Permissions portlet to give the user access rights.
POP.003.0013W	"{0}" does not have permission to modify the directory configuration.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu to open the Permissions portlet to give the user access rights.

- POP.003.0014E** **Cannot update directory config, domain not found: "{0}".**
Explanation An attempt was made to update the config information for a directory service using an invalid domain name.
Action Use a valid domain name.
- POP.003.0015S** **Cannot update directory config, Administrator user not found: "{0}".**
Explanation The system directory or the database is corrupted.
Action Restore the underlying system user directory content from a backup or do so manually. If LDAPd, you can reinstall the LDAPd server using the webMethods Installer.
- POP.003.0016E** **Cannot update directory config, Everyone group not found: "{0}".**
Explanation The system directory does not have an everyone group or the directory is corrupted.
Action Restore the underlying system user directory content from a backup or do so manually. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.
- POP.003.0017S** **Cannot update directory config, Guest user not found: "{0}".**
Explanation The system directory is corrupted.
Action Restore the underlying system user directory content from a backup or do so manually. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.
- POP.003.0018E** **Cannot remove the system directory.**
Explanation The system directory services cannot be removed.
Action Do not try to remove the system directory.
- POP.003.0021E** **System directory does not have Administrator user.**
Explanation The LDAP user store is missing the administrator user.
Action Add a user to the system LDAP user store whose UID matches the Portal Administrator UID. This should only be necessary if the LDAP user store has become corrupted or the PortalAdmin user has been removed.

POP.003.0022S	System directory does not have Everyone group. Everyone group access will not be available.
Explanation	The system directory is corrupted.
Action	Restore or create the everyone group in the system directory. Use the directory's administration UI or tools for that purpose.
POP.003.0023E	System directory does not have Guest user. Guest access will not be available.
Explanation	The system directory does not have a guest user or it is corrupted.
Action	Restore the underlying system user directory content from a backup or do so manually. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.
POP.003.0024W	The type "{0}" is either 'disabled' or not deployed to this MWS cluster node. Please contact the My webMethods Server Administrator.
Explanation	An attempt was made to view a portlet for which the status has been set to disabled.
Action	Use the Manage Components portlet in the Administration Dashboard to change the status of the portlet type.
POP.003.0025W	{0} cannot view the content of {1}.
Explanation	The user is denied access to view a portlet item
Action	Use the Permissions page to set the authentication scheme for the item to one of the installed authentication schemes.
POP.003.0026W	{0} cannot list the shortcuts to {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0027W	{0} cannot list the notes for {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0028W	{0} cannot view the access list for {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0029W	{0} cannot view the authentication scheme for {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0030W	{0} cannot create an item of type {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open up the Permissions portlet to give the user access rights.
POP.003.0031W	{0} cannot update the content of {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0032W	{0} cannot add the note for {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0033W	{0} cannot remove the note for {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0034W	{0} cannot update the properties of {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0035W	{0} cannot delete {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0037W	{0} cannot destroy {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0038	{0} cannot store content {1}.
Explanation	An attempt was made to store a document on a type that does not support document storage
Action	Ensure that content is stored on document types
POP.003.0039W	{0} cannot contain a duplicate reference to {1}.
Explanation	You cannot create items with the same name under the same folder.
Action	When naming items in a folder, make sure each item uses a name that is unique within the folder.
POP.003.0040W	Cannot uninstall "{0}" because it has "{1}" published instances. Please delete them first and try again.
Explanation	The DBO cannot be uninstalled because it has published instances.
Action	Manually delete all published instances of this DBO and try to uninstall it again. You can use Publish History portlet to help you find all published instances.
POP.003.0044W	{0} is checked out.
Explanation	The item cannot be checked out because it is already checked out.
Action	Wait until the item is checked in and try again.
POP.003.0045W	{0} is not versioned.
Explanation	The item is not versioned.
Action	Add the item to version control using the item's local menu.

POP.003.0046	{0} cannot view version number of {1}.
Explanation	An attempt was made to view a version of a document that failed a permissions check
Action	Verify that the current user has sufficient permissions
POP.003.0047W	{0} cannot list the versions of {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0048W	{0} cannot add to versioning {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0049	{0} cannot remove from versioning {1}.
Explanation	An attempt was made to remove a version from version control that failed a permissions check
Action	Verify that the current user has sufficient permissions
POP.003.0050W	{0} is checked out by {1}.
Explanation	The item is already checked out.
Action	Wait until the item is checked in and before trying to check out.
POP.003.0051W	{0} cannot set the current version of {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0052W	{0} cannot publish a version of {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0053W	{0} cannot check out {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0054W	{0} is not checked out.
Explanation	You cannot check the item in because it is not checked out.
Action	Do not attempt to check in an item that was not checked out.
POP.003.0055W	{0} cannot check in {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0056W	{0} cannot undo the check out of {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's 'rmissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0057E	Source branch is not found: "{0}".
Explanation	The server cannot find a source version branch for this object.
Action	Do not try to add this object to version control.
POP.003.0058	Destination branch is not found: "{0}".
Explanation	Version control system was unable to create a new branch required to complete the add to versioning command.
Action	Check the logs for additional information such as out of disk space.
POP.003.0059W	{0} cannot be added to versioning because parent is null.
Explanation	The item is invalid because it does not have a parent.
Action	Use the local item menu to delete the item.

POP.003.0060W	Not initialized: call <code>init(PageData)</code> first.
Explanation	An internal error has occurred.
Action	Try the operation again.
POP.003.0061W	Column must be contained by a row.
Explanation	The page data xml is not valid. The column element must reside inside a row element.
Action	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try editing and then saving the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.
POP.003.0062E	Property must be contained by a portlet.
Explanation	The page data xml is not valid. The property element must be inside portlet element.
Action	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.
POP.003.0063E	Portlet must contain 'uri' attribute.
Explanation	The page data xml file is not valid. The portlet definition does not have an URI attribute.
Action	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.
POP.003.0064W	Property must contain 'name' attribute.
Explanation	The page data xml is not valid. The property element must have a name attribute.
Action	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.
POP.003.0065E	Wiring must be contained by a portlet.
Explanation	The page data xml is not valid. The property element must reside inside the portlet element.
Action	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.

POP.003.0066W	Wiring must contain 'name' attribute.
Explanation	The page data xml is not valid. The wiring element must have a name attribute.
Action	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.
POP.003.0067E	Wiring must contain 'portlet' attribute.
Explanation	The page data xml file is not valid. The wiring definition does not have a portlet attribute.
Action	If you are using My webMethods Server when you got this message, the My webMethods Server page data has been corrupted. Try to edit and then save the page. If you cannot load the page into the page editor you need to delete the page and then recreate it.
POP.003.0069E	The content service "{0}" is not available. Please contact the My webMethods Server Administrator.
Explanation	The server failed to update the contents of a file that was saved to My webMethods Server.
Action	Verify that the location for the My webMethods Server content repository exists.
POP.003.0070	"{0}" is not editable as it does not exist in a sandbox.
Explanation	An invalid attempt to check in a versioned item was made.
Action	Check out a new version and the the item check in.
POP.003.0071E	Cannot lookup install service: "{0}".
Explanation	The server cannot find the install service for this component.
Action	The component is not supported.
POP.003.0072E	ComponentUri is not a thingID: "{0}".
Explanation	The server cannot determine the location of the installed component based on the passed URI.
Action	Correct the calling code to specify a thingID as the componentUri parameter of the uninstallComponent command.

POP.003.0073E	{0} cannot install component.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0074W	{0} cannot read search service.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0075	{0} cannot set access entries on {1}.
Explanation	An attempt was made to set permissions which failed a permissions check
Action	Ensure the current user has sufficient permissions to edit the permissions on the current object
POP.003.0076W	{0} cannot remove access entries from {1}.
Explanation	The specified user cannot remove entries from the access control list of the specified item.
Action	Grant the user the rights to perform the operation, or have the operation performed by a different user with permission to change the access control list of the target item.
POP.003.0077W	{0} cannot set the authentication scheme of {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0078W	{0} cannot set the owner of {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0079E	Internal error. Access right lengths do not match.
Explanation	Internal error. A database API inconsistency exists.
Action	Use the Manage Components portlet to edit permissions for this My webMethods Server object.

POP.003.0080W	No auth scheme for auth Level: "{0}".
Explanation	The authentication scheme might not be installed yet, or the specified authentication level is not valid.
Action	Install the missing authentication scheme <code>wm_<schema>Auth.cdp</code> component or correct the <code>authLevel</code> attribute value of your custom <code>xmlImport.xml</code> file.
POP.003.0081E	No implementation for auth scheme: "{0}".
Explanation	The authentication scheme for the target My webMethods Server item is invalid.
Action	Use the Permissions page to set the authentication scheme for the item to one of the installed authentication schemes.
POP.003.0082W	{0} cannot list the contents of {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0083W	{0} cannot add an item to {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0084W	{0} cannot add a shortcut to {1}.
Explanation	Most likely user does not have appropriate access rights.E145
Action	Give the user access rights.
POP.003.0085W	{0} cannot remove an item from {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open Permissions portlet to give the user access rights.
POP.003.0086W	{0} cannot remove a shortcut from {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0087	You cannot copy this container into a descendant of itself.
Explanation	A paste operation was attempted inside the source container.
Action	Paste the clipboard contents into an external container.
POP.003.0088W	You cannot move this container into a descendant of itself.
Explanation	The folder cannot move into one of its subfolders.
Action	If you need to move the folder, do not attempt to move it into a subfolder of itself.
POP.003.0090W	{0} cannot contain a duplicate name.
Explanation	The folder or page cannot have items with duplicate names.
Action	When naming items in a folder, make sure each item has a name that is unique within the folder.
POP.003.0091E	Unable to create xtype with null name: "{0}".
Explanation	The xtype id passed into the createChild command is not valid.
Action	Pass a valid xtype id parameter value. The valid values are listed in the tblXTypes tables.
POP.003.0092W	{0} is a reserved folder and cannot be modified.
Explanation	The folder is a system folder and cannot be modified.
Action	Do not try to modify a system folder.
POP.003.0093W	You cannot move a reserved item.
Explanation	The item is reserved and cannot be moved.
Action	Do not attempt to move reserved items.
POP.003.0094W	{0} is a reserved folder and can not be versioned.
Explanation	The folder cannot be added to the version control because it is a special folder type.
Action	Do not try to add this folder to version control.
POP.003.0095W	{0} cannot change the columns of {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0096	{0} cannot move portlet {1}.
Explanation	An attempt to move a portlet failed a permissions check
Action	Verify that the current user has sufficient permissions
POP.003.0097W	{0} cannot minimize portlet {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0099W	{0} cannot view this item.
Explanation	The user attempted to view an item but does not have permission to see it.
Action	The My webMethods Server administrator should use the Manage Components portlet to edit permissions for this My webMethods Server object.
POP.003.0102W	Unable to locate: "{0}".
Explanation	The server cannot find the user in the directory.
Action	The user might have been removed from the directory. Determine if this user belongs in the directory.
POP.003.0103W	Unable to locate: "{0}" invalid type.
Explanation	The directory might be corrupted or improperly configured.
Action	Check the Directory Service Administration portlet to verify that the directory service is properly configured and functional.
POP.003.0104W	{0} cannot modify user.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0105W	Cannot modify attribute on principal, {0} not found.
Explanation	The server cannot find the user in the directory.
Action	The user might have been removed from the directory. Determine if this user belongs in the directory.

POP.003.0106W **Cannot set email address on principal, email address attribute not configured properly.**

Explanation The email attribute is not configured for this user directory.

Action Update the directory configuration in Directory Service Administration portlet to specify an email attribute name and try again.

POP.003.0107W **{0} cannot create an alias.**

Explanation The user does not have appropriate access rights.

Action Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0108W **Alias not found: "{0}".**

Explanation An attempt was made to remove an alias that does not exist.

Action Verify that the remove alias call uses an existing alias name.

POP.003.0109W **{0} cannot delete the "{2}" alias.**

Explanation The user does not have appropriate access rights.

Action Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0110E **Internal ScheduleMechanics error.**

Explanation The paging cookie is invalid.

Action Close the browser, then open it again, and retry the action.

POP.003.0111W **{0} cannot view the subscription of {1}.**

Explanation The user does not have appropriate access rights.

Action Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0112W **{0} cannot list the subscriptions to {1}.**

Explanation The user does not have appropriate access rights.

Action Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.

POP.003.0113W	{0} cannot edit the subscription to {1}.
Explanation	The user does not have appropriate access rights.
Action	Use item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0115W	Cannot create cookie for URI: "{0}".
Explanation	The system directory or the database is corrupted.
Action	Restore the underlying system user directory content from a backup or do so manually. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.
POP.003.0116W	User page size must be >= 0 (zero indicates default).
Explanation	The page size cannot be negative.
Action	Correct the calling code to pass the pageSize parameter as a positive number.
POP.003.0117W	Cannot set password on user, user not found: "{0}".
Explanation	The system directory or the database is corrupted.
Action	Restore the underlying system user directory content from a backup or do so manually. In the case of LDAPd, you can reinstall the LDAPd server using the webMethods Installer.
POP.003.0118E	Cannot get roles for user, user not found: "{0}".
Explanation	The server cannot find the user in the directory.
Action	The user might have been removed from the directory. Determine if this user belongs in the directory.
POP.003.0119E	Unable to locate mechanics: "{0}".
Explanation	Mechanics were not found for the given name or URI.
Action	If the error is related to a standard portlet, try to redeploy the portlet using the Install Administration portlet. If you have created a custom portlet, you need to correct the calling code in CAF and redeploy the portlet.

POP.003.0120W	{0} cannot cut {1}.
Explanation	The user does not have appropriate access rights.
Action	Use the item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0121W	{0} cannot cut {1}.
Explanation	The user does not have the appropriate access rights.
Action	Use the item's Permissions local menu item to open the Permissions portlet to give the user access rights.
POP.003.0122W	A datasource named "{0}" already exists.
Explanation	An attempt was made to register a SQL datasource with a datasource name that has already been used for another datasource.
Action	Use a different name for the new datasource.
POP.003.0123W	You cannot copy a reserved item.
Explanation	The item is reserved.
Action	Do not attempt to copy a reserved item.
POP.003.0124	{0} cannot access datasource.
Explanation	An attempt to issue a SQL statement was made with an invalid argument for the datasource
Action	Ensure that the datasource is registered
POP.003.0126W	compression not allowed.
Explanation	The presentation cache content cannot be compressed.
Action	Correct the calling code to not call PresentationCacheContent.setCompressed(true).
POP.003.0129W	Cannot initialize principal, invalid type: "{0}".
Explanation	The directory might be corrupted or improperly configured
Action	Check the Directory Service Administration portlet to verify that the directory service is properly configured and functional.

POP.003.0130E	Error in thread resyncing group properties [domain]: "{0}".
Explanation	The server failed to refresh the metadata for a Group from the LDAP server.
Action	Validate the connectivity to the LDAP server using an LDAP browser tool, the directory native Administration UI, or other tools.
POP.003.0132	"{0}" depends on "{1}".
Explanation	During the wiring resolution phase an error occurred
Action	Check the wiring configuration for the portlets on the current page.
POP.003.0134W	{0}'s account has been disabled.
Explanation	The user account has been disabled.
Action	Enable the user account in the underlying user directory. Use the directory Administration UI or other tools for that purpose.
POP.003.0135W	Unable to find the content location for: "{0}". Content service is not available or out of sync with the database. Please try again. If the problem persists, contact the My webMethods Server Administrator.
Explanation	The content store is corrupted.
Action	Delete the item and try again.
POP.003.0136W	Cannot install component "{0}" because it requires "{1}" to be installed first.
Explanation	The component being installed depends on another component that is not yet installed and not listed in the items to install list.
Action	Install the required components before attempting to install the component that raised the error.
POP.003.0137W	Unable to create with unknown type: "{0}".
Explanation	Cannot create an item because the xtype is invalid.
Action	Pass a valid xtype parameter to createChild command. All valid xtypes are found in the XTypes system folder in the My webMethods Server UI.
POP.003.0139W	Component "{0}" installation failed. System state is recovered by uninstalling the component. Original error: {1}
Explanation	The installation of the component failed.
Action	Uninstall the component to recover the system state. Look at the install.log file for details of why the installation failed.

POP.003.0140E	Component "{0}" installation failed. System state is recovered by reinstalling the previous version of the component. Original error: {1}"
Explanation	The installation of the component failed.
Action	Uninstall the component to recover the system state. Look at the install.log file for details of why the installation failed.
POP.003.0141	Invalid username or credentials for: "{0}".
Explanation	A failed attempt to login occurred.
Action	Verify that the username and the password are correct.
POP.003.0142	Invalid principal type: "{0}".
Explanation	An attempt to modify a group's membership failed.
Action	Verify that the group exists prior to attempting to modify the group.
POP.003.0143	{0} cannot set policy on {1}.
Explanation	An attempt was made to add an item to a Security Realm failed a permissions check.
Action	Verify that the current user has sufficient permissions.
POP.003.0144	{0} cannot remove policy from {1}.
Explanation	An attempt to remove an item from a Security Realm failed a permissions check.
Action	Verify that the current user has sufficient permissions.
POP.003.0146	{0} cannot modify the members of group: {1}
Explanation	An attempt to modify the members of group failed a permissions check.
Action	Verify that the current user has sufficient permissions.
POP.003.0147	{0} cannot modify the membership of principal: {1}
Explanation	An attempt to modify the groups and roles a principal belongs to failed a permissions check.
Action	Verify that the current user has sufficient permissions.

POP.003.0148	Command Error, Parent is not a container. Class= {0}
Explanation	An attempt was made to create a new item inside a parent that is not a valid container.
Action	Ensure that the attempt is made to create a child inside a valid container.
POP.003.0150	{0} cannot create users or groups in the "{1}" directory service."
Explanation	An attempt was made to create a user or group failed a permissions check.
Action	Verify that the current user has sufficient permissions.
POP.003.0151	{0} cannot modify the members of role: {1}
Explanation	An attempt to modify the members of a role failed a permissions check.
Action	Verify that the current user has sufficient permissions.
POP.003.0153	{0} cannot add a {2} to {1}.
Explanation	An attempt to create a new child failed a permissions check.
Action	Verify that the current user has sufficient permissions.
POP.003.0154	{0} cannot remove a {2} from {1}.
Explanation	An attempt to remove a child from a folder failed a permissions check.
Action	Verify that the current user has sufficient permissions.
POP.003.0155	My webMethods Server webspace {0} should have an valid alias
Explanation	Webspaces must have a valid name in order to be created.
Action	Ensure that a valid alias name is supplied.
POP.003.0156	Unclosed skin property: "{1}". Please close with "].
Explanation	During the dynamic skin property resolution, a malformed skin property was referenced.
Action	Ensure that the javaScript file with the dynamic skin property is properly formed.
POP.003.0160E	Failed to resolve wiring for property "{0}"
Explanation	Wiring cannot be resolved for the <propertyName> property of a portlet instance.
Action	Open the Wiring settings for this portlet, make sure the source portlet and its property are still available. Adjust the wiring settings if necessary.

POP.003.0162	A group cannot be a member of itself.
Explanation	A malformed attempt to modify a group was made.
Action	Do not set a group as a member of itself.
POP.003.0163	Invalid username or Password.
POP.003.0164	{0} cannot copy {1}.
POP.003.0165	{0} cannot clone {1}.
POP.003.0166	{0} is a system component. And will not be uninstalled.
POP.003.0167	Too many failed login attempts for: "{0}". You may try to login again in {1} minutes.
POP.003.0168	Password has expired for: "{0}". Please contact an administrator to reset your password.
POP.003.0169	{0} is reserved and cannot be used for an alias.
POP.003.0170	Failed to load thing {0} from parent container {1}, error={2}
POP.004.0001E	The Resource Bundle for "{0}" was not found.
Explanation	The server cannot load the specified resource bundle class. The bundle is a portlet class that has not been deployed or was deployed in a different portlet.
Action	Use the Portlet Developer to add the resource bundle class to the invoking portlet. Redeploy the portlet.
POP.004.0002E	The Message Key "{0}" was not found in the Resource Bundle "{1}".
Explanation	The resource bundle message key is missing.
Action	Correct the resource bundle to include a resource for the key specified by the error message.

POP.004.0003	There was no Object found for Message Key "{0}".
POP.004.0004E	An error occurred while formatting the Message Key "{0}".
Explanation	The resource bundle message key is missing or the message could not be formatted because its content is invalid.
Action	Correct the resource bundle to include the key specified by the error message, or correct the resource content identified by the key.
POP.004.0005S	Error creating search pools "{0}".
Explanation	The server cannot initialize some search service data structures because an internal portal error occurred.
Action	Use the specific error message details to diagnose the problem.
POP.004.0006S	Invalid cache ID: "{0}".
Explanation	The server cannot initialize an invalid cache.
Action	Correct the thing cache configuration in the cache.xml My webMethods Server configuration file. A valid entry is: <code><cache name="Thing Cache" class="com.webmethods.portal.service.cache.impl.TransientCache" maxSize="10000" isClustered="true" ID= "1" enabled="true"/></code>
POP.004.0008E	Unable to initialize content service component: "{0}".
Explanation	Cannot initialize the content service.
Action	If you cannot reconfigure the offending content service. Call Software AG Global Support for a reset directive.
POP.004.0010E	No provider for directory [name, type] : [{0}, {1}]
Explanation	The server cannot initialize the specified directory service because the directory service is an unknown type.
Action	Correct the directoryConfig.xml My webMethods Server configuration file to remove the Service element with the name attribute value specified by the error message.
POP.004.0011E	Invalid XML for directory, no DirectoryConfig element found: "{0}".
Explanation	The server cannot initialize the directory service because its configuration data is corrupt.
Action	Correct the directoryConfig.xml My webMethods Server configuration file to remove the Service element with the name attribute value specified by the error message.

POP.004.0012S	Unable to construct component data for directory: "{0}".
Explanation	The server cannot initialize the directory service.
Action	Use the Directory Services Administration portlet to create a new directory service and then delete the old one.
POP.004.0013S	Alias Cache not found.
Explanation	The server cannot initialize the alias service because the alias cache is not configured.
Action	Add the following entry to the cache.xml My webMethods Server configuration file: <cache name="AliasCache" class="com.webmethods.portal.service.cache.impl.AliasCache" maxSize="5000" isClustered="true" ID="2" enabled="true"/>
POP.004.0014E	Can't create alias cache.
Explanation	The server cannot initialize the metadata service because the required cache was not located.
Action	Correct the thing cache configuration in the cache.xml My webMethods Server configuration file. A valid entry is: <cache name="Thing Cache" class="com.webmethods.portal.service.cache.impl.TransientCache" maxSize="10000" isClustered="true" ID="1" enabled="true"/>
POP.004.0015E	Unable to create MetaContext: "{0}".
Explanation	The server cannot create a connection to metadata datasource because the configuration information for the datasource was not retrieved.
Action	Correct the metaContext.xml My webMethods Server configuration file to remove the Context element with the connection attribute value specified by the error message.
POP.004.0016S	Can't get schedule list: "{0}".
Explanation	The server was unable to list all of the My webMethods Server schedules.
Action	Verify that the database has been properly configured and that the My webMethods Server schema was properly installed by paying close attention to the installation process.
POP.004.0017S	Thing Cache not found.
Explanation	The server cannot initialize the metadata service because the required cache was not located.
Action	Correct the thing cache configuration in the cache.xml My webMethods Server configuration file. A valid entry is: <cache name="Thing Cache" class="com.webmethods.portal.service.cache.impl.TransientCache" maxSize="10000" isClustered="true" ID="1" enabled="true"/>

POP.004.0018S	Can't create thing cache.
Explanation	The server cannot initialize the metadata service because the thing cache configuration is invalid.
Action	Correct the thing cache configuration in the cache.xml My webMethods Server configuration file. A valid entry is: <code><cache name="Thing Cache" class="com.webmethods.portal.service.cache.impl.TransientCache" maxSize="10000" isClustered="true" ID="1" enabled="true"/></code>
POP.004.0019S	No queue specified.
Explanation	The server cannot initialize the e-mail notification deliverer because the notification queue name was not specified in the deliverer's configuration.
Action	Specify the queue name in the queue attribute of the delivery initializers in the phaseProvider.xml My webMethods Server configuration file.
POP.004.0020S	Unexpected exception: "{0}".
Explanation	The server cannot initialize the e-mail notification deliverer because an unexpected error occurred.
Action	Check the _problems_.log in the My webMethods Server current logging directory for more specific error information.
POP.004.0021S	Invalid ConnectionManager config file.
Explanation	The server cannot initialize the datasource connection manager because it cannot acquire its configuration file.
Action	Validate that the portal.properties My webMethods Server configuration file contains the following entry: 'sled.connectionmanager.config=config:/db.xml'.
POP.004.0022E	Could not acquire meta context : version service name: "{0}".
Explanation	The server cannot acquire the metadata datasource by name because the specified name is unrecognized.
Action	Restart the server where My webMethods Server is installed.
POP.004.0023E	Could not find root folder of version services.
Explanation	The root folder of the version service does not exist.
Action	Reinstall the version service using the My webMethods Server Configurator.

POP.004.0024S	Could not create service thing : version service name: "{0}".
Explanation	The server cannot initialize the version service.
Action	Verify that all of the versioning components have been deployed. This includes the version service and version portlet which can be located in the system portal folders.
POP.004.0027E	Ftp login failed for user [{0}] : {1}.
Explanation	The server cannot login to the remote FTP server.
Action	Verify that the credentials are valid for the FTP connection service, and that the network connectivity is valid.
POP.004.0028E	Ftp Connection Error: Access Denied
Explanation	The server cannot connect to the remote FTP server.
Action	Validate that the credentials and configuration are valid for the FTP connection service, using the Content Service Admin portlet. Verify that the network connectivity is valid.
POP.004.0029E	Ftp Connection Error: "{0}".
Explanation	The server cannot connect to the remote FTP server.
Action	Validate that the credentials and configuration are valid for the FTP connection service, using the Content Service Admin portlet. Verify that the network connectivity is valid.
POP.004.0032E	Invalid ID's in createThing.
Explanation	The server was unable to publish a new My webMethods Server object.
Action	Correct the invoking method to pass in a valid owner and parent ID parameters.
POP.004.0033E	Database is busy or unavailable.
Explanation	The server cannot execute the SQL command because the database is not responding to My webMethods Server in a timely fashion. The database could be experiencing too much load preventing it from responding to My webMethods Server and the server might not be able to access the database's server or port. In addition, the database might not be running.
Action	Verify that the database is running, and is not experiencing heavy load. Verify that the database has an adequate number of connection threads available. Verify that the machine on which the My webMethods Server is running can access the datasource's configured host name and port.

POP.004.0034E	Datasource Mismatch, passed {{0}} to API on {{1}}.
Explanation	The metadata datasource cannot operate on a resource from a different datasource.
Action	Correct the invoking source code to use a metadata service to operate on a resource that belongs to the service's datasource. Consult the API documentation for more information.
POP.004.0035E	Invalid URI
Explanation	The server cannot resolve the datasource for a metadata My webMethods Server identifier.
Action	The identifier that caused this error does not identify a resource, do not use it to identify a resource.
POP.004.0036E	Invalid schedule info: interval "{{0}}", timeAt "{{1}}": Unable to parse 'timeAt' and/or 'interval'
Explanation	An attempt to create or modify a schedule has failed because of invalid schedule parameters.
Action	Correct the invoking code to pass valid schedule parameters. Valid interval and timeAt parameter values are the time values formatted according to the ISO 8601 date/time format.
POP.004.0037E	Invalid schedule info: interval "{{0}}", timeAt "{{1}}": 'timeAt' overlaps with 'interval'
Explanation	The server cannot execute the scheduled event because the time to wait (timeAt), after the interval setting but before executing the event, is approximately as long as the interval itself.
Action	Edit the schedule using the Event Administration portlet, in the Portal Configuration category in the My webMethods Server Admin Dashboard, so the interval is longer than the On/At time-to-wait, such that weeks instead of days, hours instead of minutes.
POP.004.0038E	Unknown thing type: {0}
Explanation	The server was unable to identify the base type of the metadata service object.
Action	Verify that the portlet was built using the My webMethods Server.
POP.004.0039E	Unable to unregister XType: {0}
Explanation	The xtype was not registered or there are published instances of that xtype.
Action	Ensure that all instances of that xtype have been deleted prior to unregistering. These types are found by using the Publish History reporting portlet.

POP.004.0040E	Can't convert to xtype of different base type
Explanation	Xtype conversion is unsupported.
Action	Correct the invoking method and do not attempt to modify the xtype parameter.
POP.004.0041E	Invalid Principal.
Explanation	The server cannot modify the access control entry.
Action	Correct the invoking method to specify a principal parameter.
POP.004.0042E	Invalid Ace. Cannot set both granted and denied on the same right.
Explanation	The server cannot set a single access control entry to grant and deny the same access right.
Action	Correct the invoking source code. Consult the API documentation for more information.
POP.004.0043E	Invalid Ace. Unknown right.
Explanation	The server cannot set access control entry with the right bit outside of the defined right bit range, as defined by the access service API.
Action	Correct the invoking source code. Consult the API documentation for more information.
POP.004.0045E	Invalid Ace. Cannot delegate a right not granted.
Explanation	The server cannot modify the access control entry.
Action	Correct the invoking method to include the proper right set parameter.
POP.004.0046	Setting user name is not supported.
Explanation	Internal group and user objects cannot have their name set
Action	Check and correct directory API usage
POP.004.0047E	Cookie is not set in this view.
Explanation	The server cannot display the inbox notifications because a paging cookie was not set.
Action	Log out, log in, and try again.

POP.004.0048E	Unable to load Subscription object. Subscription no longer exists.
Explanation	The server cannot locate the subscription information that triggered the notification.
Action	Delete the notification by locating the offending notification in the My webMethods Server inbox and deleting it.
POP.004.0049E	Unable to load Event.
Explanation	The server cannot load event data because an error occurred in querying the database.
Action	Check the <code>_problems_.log</code> in My webMethods Server current logging directory for more specific error information.
POP.004.0050E	Unable to remove Notification.
Explanation	The server was unable to locate the notification in order to delete it.
Action	Correct the invoking method to specify a valid notification parameter.
POP.004.0051E	Unable to remove Event.
Explanation	The server cannot remove the event item from the database due to a SQL error while executing the stored procedure that performs the removal.
Action	Check the <code>_problems_.log</code> in My webMethods Server current logging directory for more specific error information.
POP.004.0052E	Start index beyond end of list.
Explanation	The server cannot list a page of metadata resources because the specified start index of the page is greater than the total number of resources in the list.
Action	Correct the source code that executes the query. Specify a start index that is less than the total number of resources in the list by modifying the start property of the <code>com.webmethods.portal.service.view.IPagingCookie</code> .
POP.004.0053E	Paged before first item.
Explanation	The server cannot list a page of metadata resources because the specified start or end index of the page is less than one.
Action	Correct the source code that executes the query. Specify a start index that is less than the total number of resources in the list by modifying the start or end properties of the <code>com.webmethods.portal.service.view.IPagingCookie</code> .

POP.004.0054E	Invalid end index.
Explanation	The server cannot execute a paged container query because the page-start index is greater than the page-end index.
Action	Correct the source code that executes the query. Specify a start index that is less than the end index by modifying the start and end properties of the <code>com.webmethods.portal.service.view.IPagingCookie</code> .
POP.004.0055E	Invalid sort order for getTreeView.
Explanation	The server cannot sort the tree view's results with the supplied sort parameter.
Action	Correct the invoking code to pass valid sort parameters.
POP.004.0056E	Error saving subscription. No subscription or source information.
Explanation	The server cannot add the subscription because the subscription information is corrupted.
Action	Correct the invoking method to specify a valid subscription parameter.
POP.004.0057E	Error adding subscription. No subscription or source information.
Explanation	The server cannot add the subscription because the subscription information is corrupted.
Action	Correct the invoking method and ensure that the proper parameters are passed.
POP.004.0059	Can't create an archived thing, use deactivate or delete.
Explanation	The archived thing type cannot be created directly. It is created automatically when object is deleted
Action	Check and correct MWS API used when creating new object instance
POP.004.0060	Unable to save Role.
Explanation	A database error occurred when saving role information
Action	Check logs for additional exception details
POP.004.0061E	Unable to load Role.
Explanation	The server cannot load the metadata information for a registered role.
Action	Using the Role Administration portlet, regenerate and configure the role.

POP.004.0062E	Missing results from the database.
Explanation	The server has received invalid results from a stored procedure.
Action	Verify that the database has been properly configured and that the schema was properly installed by paying close attention to the installation process.
POP.004.0063E	Access model not set.
Explanation	The access service cannot evaluate access rights for a user until its access model has been specified.
Action	Correct the portal.properties file in the My webMethods Server config directory so that it has the following line: framework.access.model=restrictive.
POP.004.0064E	Access model is not valid.
Explanation	The server cannot set the access model because the specified model is unknown. The valid model values are 1 (permissive) and 2 (restrictive).
Action	Correct the portal.properties file in the My webMethods Server config directory so that it has the following line: framework.access.model=restrictive.
POP.004.0065E	Serialized object version is different then current version: [version, currentVersion] [{0},{1}]
Explanation	The server cannot read the alias stored in the database because its serialized object version is out of date.
Action	Revert to the previous version of wm-caf-server.jar, and restart the My webMethods Server.
POP.004.0066E	Unknown type: {0}
Explanation	The server cannot initialize the directory search control because the specified query type is unknown.
Action	Correct the code invoking directory search to specify a type of 1 (users) or 2 (groups).
POP.004.0067E	Attempted to set subkey on primary-key only key.
Explanation	The server cannot create the cache key.
Action	Correct the invoking method to include appropriate cache key parameter.

POP.004.0068E	Can't find or create valid cache.
Explanation	The cache update stored procedure cannot resolve the cache identifier.
Action	Correct the invoking source code to provide a cache-key with a valid cacheID. Consult the API documentation for more information.
POP.004.0069E	Cache error: data is not a serializable object
Explanation	The server attempted to cache an object that is not serializable.
Action	Correct the source code that invokes the <code>com.webmethods.portal.service.cache.impl.DBCache.getBytesFromObject()</code> method to pass serializable object.
POP.004.0070E	Invalid connection parameters.
Explanation	The server cannot connect to the remote FTP server.
Action	Verify that the credentials and configuration are valid for the FTP connection service, using the Content Service Admin portlet. Verify that the network connectivity is valid.
POP.004.0071E	Error persisting directory config.
Explanation	The server cannot store the directory configuration modifications.
Action	Use the Directory Services Administration portlet to create a new directory service and then delete the old one.
POP.004.0072E	Cannot lookup non user or group thing based objects : {0}
Explanation	The server cannot look up directory service resources using metadata identifiers unless the resource is a user, group, or role.
Action	The identifier specified by the error message does not identify a directory resource, do not try to use it to identify a directory resource.
POP.004.0073E	Invalid URI, no directory service specified "{0}"
Explanation	The server cannot locate an invalid directory user.
Action	Verify that the Directory service is still properly configured by using the Directory Service Administration portlet.

POP.004.0074E	Specified domain in URI not found [domain, uri] -- [{0}, {1}]. This can be due to directory service being disabled or removed
Explanation	The server cannot look up the directory service based on a Portal identifier because the identified directory service does not exist.
Action	This error may have happened because the specified directory service configuration was deleted. Try re-adding the directory service using the Directory Services Administration portlet (in the Portal Configuration category of the Portal Admin Dashboard).
POP.004.0075	Cannot add directory service, service already exists: {0}
Explanation	Directory service name must be unique.
Action	Check and correct directory service name being created.
POP.004.0076E	Error adding new directory service: {0}
Explanation	The server cannot add or update a directory service because of an error in validating or storing the directory service configuration.
Action	Check the _problems_.log in the My webMethods Server current logging directory for more specific error information.
POP.004.0077E	Cannot build URI, unknown type 0
Explanation	The server cannot construct a My webMethods Server identifier for the directory service object because the specified type is not one of user, group, or role.
Action	Correct the source code that invokes the <code>com.webmethods.portal.server.directory.impl.DirectoryTools.constructDirectoryURI()</code> method to specify only either user, group, or role.
POP.004.0078E	Invalid escape character in {0} at position {1}
Explanation	The server was unable to normalize the LDAP DN.
Action	Investigate the original DN and try to remove offending characters if possible.
POP.004.0079E	Cannot retrieve most significant attribute; invalid DN: "{0}"
Explanation	The server cannot parse a directory service object DN (the object's LDAP ID), because the DN is invalid.
Action	Supply a valid DN to the <code>com.webmethods.portal.service.directory.impl.jndi.JNDITools</code> class's <code>getMostSignificantAttr()</code> and <code>getMostSignificantAttrSet()</code> methods.

POP.004.0080E	Unable to connect to: {0}
Explanation	The server cannot connect to the remote LDAP directory store.
Action	Verify that the Directory configuration is valid by using the Directory Service Administration portlet.
POP.004.0081E	No user class specified in directory factory config
Explanation	The server cannot store the directory configuration modifications.
Action	Use the Directory Services Administration portlet to create a new directory service and then delete the old one.
POP.004.0082E	No group class specified in directory factory config
Explanation	The server cannot initialize the directory service.
Action	Verify that the Directory service is properly configured by using the Directory Service Administration portlet.
POP.004.0083E	Unable to wrap object. Unkown type: {0}
Explanation	The server was unable to read an LDAP entry.
Action	Use the Directory Services Administration portlet to verify that the Directory configuration is valid.
POP.004.0084	Unable to wrap LDAP object: {0}
Explanation	There was an error fetching LDAP object properties
Action	Check MWS logs for additional exception details
POP.004.0085E	Error setting attribute [name, value, action, message] - [{0}, {1}, {2}, {3}]
Explanation	The server cannot modify the LDAP attribute.
Action	Verify that the connection to the LDAP directory store has adequate privileges to modify LDAP entries. Use your LDAP vendor's administration tool.
POP.004.0086E	No response controls for directory: {0}
Explanation	The server cannot update the directory search control.
Action	Start a new search.

POP.004.0087E	Cannot page backward
Explanation	The server cannot page directory search control backwards because the control is at the first page of results.
Action	Correct the source code invoking the directory search to check if the search has previous results before trying to page back to previous results. You can determine if a search has previous results by inspecting the value of the hasPrevious property of the com.webmethods.portal.service.view.IPagingCookie that you used to perform the search.
POP.004.0088E	Cannot page forward
Explanation	The server cannot page the directory search control forward because the search has no more results.
Action	Correct the source code invoking the directory search to check if the search has more results before trying to page forward. You can determine if a search has more results by inspecting the value of the hasNext property of the com.webmethods.portal.service.view.IPagingCookie that you used to perform the search.
POP.004.0089E	Unable to retrieve user list
Explanation	The server cannot list the users of a directory service, there might be a problem connecting to the directory service.
Action	If the directory service was recently configured directory service, go back to the My webMethods Server Admin Dashboard, and double-check the configuration using the Directory Service Administration portlet. Verify that the LDAP or ADSI server that connects to the directory service is up and running properly. Verify that the server the hosts My webMethods Server is able to connect to the LDAP or ADSI server using the hostname and port specified in the directory service's configuration.
POP.004.0090E	Unable to lookup user {0}
Explanation	The server cannot locate the specified user.
Action	Use the User and Group Management portlet to verify that the group exists in the LDAP directory store.
POP.004.0091E	Invalid username or password
Explanation	You have supplied invalid credentials.
Action	Try authenticating again with proper user name and password.

POP.004.0092E	Could not lookup DN {0}
Explanation	The server cannot look up a user or group by directory DN, the user or group's LDAP ID, because an error occurred while querying the directory store.
Action	Check the <code>_problems_.log</code> in My webMethods Server current logging directory for more specific error information.
POP.004.0093E	Error looking up group {0}
Explanation	The server cannot locate the specified group.
Action	Verify that the Directory service is configured by using the Directory Service Administration portlet.
POP.004.0094E	Unable to perform search : {0}
Explanation	An unknown error occurred while performing an LDAP directory search.
Action	Correct the invoking method to specify a valid query parameter.
POP.004.0095E	Error getting memberships
Explanation	The server cannot get membership information from the LDAP directory store.
Action	Verify that the Directory configuration is valid by using the Directory Service Administration portlet.
POP.004.0096E	Unable to modify password of user {0} because the supplied old password is incorrect.
Explanation	An attempt was made to change a user's password without supplying the user's existing password.
Action	Supply the correct existing password.
POP.004.0097E	INSTALL is not supported operation for: {0}
Explanation	Installation of the deployable object has failed.
Action	The deployable object does not have any installation code associated with its file extension. Do not attempt to deploy an unsupported type to the My webMethods Server.

POP.004.0098E	UNINSTALL is not supported operation for: {0}
Explanation	The server cannot uninstall the specified type of component.
Action	The specified component was not uninstalled; try again.
POP.004.0100E	Component file not found: {0}
Explanation	The server cannot install the component the component was not found at the specified location.
Action	Specify the correct location. If you are installing a component using the Install Administration portlet, select a valid location using the portlet's Browse button.
POP.004.0101E	Cannot set properties for installer: {0}
Explanation	The server cannot set install services because an internal error occurred.
Action	Check the <code>_problems_.log</code> in My webMethods Server current logging directory for more specific error information.
POP.004.0102E	Script file not found: {0}
Explanation	The server cannot execute a portlet deployment script.
Action	Using My webMethods Server, rebuild and redeploy the portlet.
POP.004.0103E	Install script finished with {0} error(s). Please look at the install.log for details
Explanation	An error occurred while installing or uninstalling a deployable component.
Action	Examine the logs, and try again. Look for the information specific to the deployed component in the <code>install.log</code> file.
POP.004.0104E	Error installing/uninstalling component
Explanation	An error occurred while installing or uninstalling a deployable component.
Action	Examine the logs, and optionally try again. Look for the information specific to the deployed component in the <code>install.log</code> file.
POP.004.0105E	Failed to initialize LoggingCollector: {0}
Explanation	The server cannot initialize logging over the JMS provider.
Action	Verify that the JMS server is running and configured.

POP.004.0106E **PortletInfo is not available for uri [{0}]. Probably the portlet is not properly installed. Try to uninstall and then install it again.**

Explanation Portlet is not currently available.

Action Try to uninstall and then re-install the portlet again.

POP.004.0107E **Invalid portlet descriptor. Portlet/DBO name is not defined**

Explanation The server cannot load portlet information from the portlet descriptor because the portlet descriptor does not contain the portlet's name, or the portlet descriptor is incorrectly structured.

Action Using the My webMethods Server to correct the portlet descriptor and redeploy it to the My webMethods Server.

POP.004.0109E **Portlet URI is not published instance of the portlet or type. Unable to persist properties**

Explanation The server cannot persist the properties of a portlet type without a valid portlet or portlet type identifier.

Action Supply a valid portlet or portlet type identifier to the `com.webmethods.portal.service.portlet.impl.PortletType.setProperties()` method.

POP.004.0110E **Portlet bean class is invalid: {0}**

Explanation The server cannot initialize the portlet because the portlet does not implement the required interface.

Action Using My webMethods Server to correct the portlet's deployment descriptor or regenerate the portlet, and then redeploy it.

POP.004.0111E **Portlet bean is not poolable: {0}**

Explanation The server cannot instantiate the portlet bean because the bean does not implement the `com.webmethods.portal.system.pool.IPooledObject` interface.

Action Use My webMethods Server to correct the portlet bean source code to implement `IPooledObject`.

POP.004.0112E **Portlet title bar class is invalid: {0}**

Explanation The server cannot initialize portlet type information because the portlet titlebar class specified by the portlet's descriptor was not found.

Action Using the Portlet Developer, remove the titlebar class specification from the portlet descriptor and then redeploy the portlet.

POP.004.0113E	Invalid URI, no search service specified: {0}
Explanation	The server cannot locate search provider because of an invalid URI.
Action	Correct the invoking code to use a valid URI.
POP.004.0114E	Invalid datasource name: {0}
Explanation	The server cannot execute a SQL statement against an invalid datasource.
Action	Correct the invoking method to pass the correct parameters. One of the critical parameters is the handle of the datasource, which can be obtained from the DataManager's API.
POP.004.0115S	Can't find data service folder: {0}
Explanation	The server cannot locate the system folder.
Action	It is possible that a system administrator has deleted a critical system folder. If so, you might need to reinstall My webMethods Server.
POP.004.0116E	Cannot obtain database connection from pool: {0}
Explanation	The server cannot obtain a database connection because all connections allocated for My webMethods Server are already in use or My webMethods Server cannot connect to the database.
Action	Verify that the database is running and is not experiencing a heavy load. Verify that the database has an adequate number of connection threads available. Verify that the machine on which the My webMethods Server is running can access the datasource's configured host name and port.
POP.004.0117E	Database connection is closed.
Explanation	The server cannot execute the SQL query because the database connection is closed.
Action	Execute the statement again. If problems persist, shut down and restart My webMethods Server.
POP.004.0118E	Error updating Clob field
Explanation	An error occurred while updating an unbounded size database field at the database level.
Action	Try the operation again.

POP.004.0119E	Error updating Blob field
Explanation	An error occurred in updating an unbounded size database field at the database level.
Action	Try the operation again.
POP.004.0120E	Could not find content service for: {0}
Explanation	The server cannot store versioned content for a resource because the content service for the resource was not found.
Action	Delete the resource.
POP.004.0121E	Versioned content uri is null or empty: {0}
Explanation	The server cannot access the versioning information.
Action	The version information is corrupted. Try to obtain a different version and recreate the changes.
POP.004.0122E	Content doesn't exist: {0}
Explanation	The server cannot read a resource's versioned content because the resource has no content.
Action	Delete the resource using the UI.
POP.004.0123E	User ID is invalid: {0}
Explanation	The server cannot locate the user's information about the versioned object.
Action	The version information is corrupted. Use the Publish portlet to publish a new instance of the item, and add the item to versioning. Consult the My webMethods Server documentation.
POP.004.0124E	Could not find user: {0}
Explanation	Cannot locate the user's information about the versioned object.
Action	The version information is corrupt. Publish a new instance of the item, and add the item to versioning.
POP.004.0125E	Could not find thing: {0}
Explanation	Cannot resolve metadata resource identifier from string.
Action	The resource specified by the identifier does not exist; do not use the identifier.

POP.004.0126E	Cookie is not set on the List View
Explanation	The server cannot sort or slice the list without a paging cookie.
Action	Correct the invoking source code to associate the paging cookie with the list by setting the cookie property of the list.
POP.004.0127E	Unable to initialize directory service {0}: {1}
Explanation	The server cannot initialize the directory service due to an error.
Action	Verify the connection information to the directory service using the Directory Service Administration portlet. Verify that the login credentials are accurate. Verify that there is network connectivity to the directory service from My webMethods Server.
POP.004.0128E	Invalid directory Uri: "{0}"
Explanation	The URI is malformed.
Action	Correct the invoking method to specify a valid URI parameter.
POP.004.0129	Uri "{0}" should resolve to principal object, but was found: {1}
Explanation	Attempting to look up a directory principal by a URL that does not resolve to a valid directory object.
Action	Check and correct directory API usage. Verify that the URI value used to look up directory object is valid.
POP.004.0130E	Unidentified Clob implementation class: {0}
Explanation	The server cannot retrieve an unbounded-length field from the database because the database driver is incompatible with My webMethods Server.
Action	Modify the datasource driver settings in the db.xml My webMethods Server configuration file to use approved driver.
POP.004.0131S	Unidentified Blob implementation class: {0}
Explanation	The server cannot retrieve result set data because of an incompatible database implementation.
Action	Verify that the correct version of Oracle is installed and that you are using the My webMethods Server supplied database drivers. You can consult your Oracle installation documentation to verify the version of Oracle and ensure that you have not added any custom Oracle drivers in the class path.

POP.004.0132E	Xtype not found: {0}
Explanation	The server cannot locate the portlet xtype in the metadata store.
Action	Most likely the portlet has been undeployed. Use the Install Administration portlet to redeploy the portlet.
POP.004.0133	XType already registered: {0}
Explanation	Every XType (Portlet Name, Dynamic Business Object) must have a unique name. An attempt was made to install a new portlet or application that contains a portlet or Dynamic Business Object which is already registered in MWS.
Action	Check to see if an application or portlet was renamed. It is also possible that a component un-install was not fully successful, in this case use <code>/component/development/tools/wm_remove_portlet</code> to clean up and delete component registration in MWS.
POP.004.0134E	Error loading class group: {0}
Explanation	The server cannot load all the classes for the specified class loader group.
Action	Check the <code>_problems_.log</code> in My webMethods Server current logging directory for more specific error information.
POP.004.0135E	Error setting config on directory, rolling back to previous config.
Explanation	The server cannot store the directory configuration modifications.
Action	Use the Directory Services Administration portlet to create a new directory service and then delete the old one.
POP.004.0136E	Unable to retrieve group list.
Explanation	The server cannot get group information from the LDAP directory store.
Action	Verify that the directory configuration is valid by using the Directory Service Administration portlet.
POP.004.0141E	No configuration information found for content service, not initializing: {0}.
Explanation	The server cannot initialize the content service.
Action	If you cannot reconfigure the offending content service by using the Content Service Admin portlet call Software AG Global Support for a reset directive.

POP.004.0144I	FTPconnection connect to {0}.
Explanation	A connection was initiated with the remote FTP server.
Action	This is an informative statement. No action is necessary.
POP.004.0152E	No Query Parameters specified.
Explanation	The server cannot execute the search because there is no search query.
Action	Navigate to the Search portlet and try again.
POP.004.0153E	Search Server is unavailable or not properly configured
Explanation	The server cannot access the search service.
Action	Verify that the search service is properly configured by using the Search Admin portlet.
POP.004.0155E	Error adding file to search index: {0}
Explanation	The server was unable to properly index a My webMethods Server component object.
Action	Determine if the document is in an unknown format or is malformed. Examine the Lucene Search Admin portlet for details on formats.
POP.004.0156E	content stream is null
Explanation	The server cannot locate the content file in the content repository.
Action	Verify that the existence of the content repository and network connectivity. The content repository has some configuration information in the storageConfig.xml. If a custom content service has been mounted, then verify that connectivity between the My webMethods Server process and the network file system is intact. Verify that you can browse to the content using My webMethods Server. Purge all items pending deletion with the Manage Deleted Items Admin Portlet.
POP.004.0157E	Error getting resync list for library: {0}
Explanation	The server cannot resynchronize the search library index because an error occurred in querying the database for the list of resources to index.
Action	Restart the My webMethods Server.

POP.004.0158E	Malformed Language Pack: {0}
Explanation	The server cannot use the language pack because its name is malformed. The name should be one of [language], [language]_[country], or [language]_[country]_[variant], where [language] is a language code such as en or ja, [country] is a country code such as US or JP, and [variant] is a variant code.
Action	Correct the language pack name and re-install language pack.
POP.004.0187	Could not lookup URI {0}
Explanation	If the URI points to an invalid directory object (user or group) an error occurs.
Action	Check and correct directory API usage. Check what URI value was used. This error might also occur if the user was deleted immediately before logging in. The error will go away when MWS caches are updated, usually within seconds.
POP.004.0196	Role Modification is not supported for: {0}.
Explanation	Only static roles support modification of role membership. This error is thrown when attempting to modify membership using the directory APIs for non-static roles
Action	Check and correct directory API usage. Check to see if the role being modified is static role
POP.004.0197	Failed to set property "{0}". Reason: {1}
Explanation	Error has occurred when setting the thing object properties. This might happen when attempting to set the property of a specific java type, but passing in an incompatible value.
Action	Check MWS logs for additional error information. Check the values the code attempted to update and determine if the actual property types are valid.
POP.004.0198E	Cannot create a user with a duplicate id: {0}
Explanation	An attempt was made to create a new user with a duplicate ID of an existing user.
Action	Use a unique identifier when creating a new user, group or role.
POP.004.0199E	Cannot create a group with a duplicate id: {0}
Explanation	An attempt was made to create a new user with a duplicate ID of an existing user.
Action	Use a unique identifier when creating a new user, group or role.

POP.004.0200	Cannot create database connection to default MWS datasource.
Explanation	Unable to create database connection to MWS database schema.
Action	Check MWS database connection configuration in MWS/server/default/config/mws.db.xml config file.
POP.004.0201	Cannot initialize MWS, invalid database schema is specified
Explanation	MWS validates if database schema contains correct tables and then throws this error if it is not configured.
Action	Check if MWS database schema was correctly created by dbConfigurator tool. You might need to drop and re-create MWS schema.
POP.004.0202	Cannot create database connection to default MWS datasource. Please verify database connection parameters in the MWS/server/default/config/mws.db.xml configuration file
Explanation	Something is wrong with the database connection configuration file such as malformed xml or incorrect JDBC driver name.
Action	Verify the database connection parameters in the MWS/server/default/config/mws.db.xml configuration file.
POP.004.0203	User {0} can not set access on {1}
Explanation	User does not have access rights to set or update permissions.
Action	See if the user or groups and roles, the user is a member of has access rights to set permissions on a given object.
POP.004.0204	Failed to search business data with the "taskTypeID" query term specified.
POP.004.0205	Unable to locate whitelist storage object
POP.004.0206	Failed to connect to database at {0}. Verify hostname/port and connection credentials.
POP.004.0207	Unable to update whitelist storage object

POP.005.0002E	Can Not Re-initialize CDS library
Explanation	An attempt was made to initialize the system twice.
Action	After My webMethods Server is initialized, do not attempt to do so again.
POP.005.0003E	Error parsing segment urls: "{0}"
Explanation	One of the My webMethods Servers in the cluster has an incorrect URL.
Action	Determine the correct URL for the My webMethods Server, then log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to correct the error.
POP.005.0004E	Unable to register component: "{0}" due to "{1}"
Explanation	My webMethods Server could not register the specified component.
Action	Look in the <code>_problems_.log</code> file for the stack trace of the error. It might be necessary to reinstall the component.
POP.005.0005	Unable to reload component: "{0}" due to "{1}"
Explanation	During dynamic reloading of a component (for example, a portlet), an error occurred.
Action	Check the logs to investigate what component failed to be reloaded. If the component is a portlet, then try uninstalling the portlet and reinstalling it, or try to revert to a previous version of the portlet.
POP.005.0006E	This server node is not defined in the MWS cluster configuration: "{0}"
Explanation	The specified My webMethods Server is not included in the cluster configuration.
Action	Log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to add the specified My webMethods Server to the cluster.
POP.005.0007	Front End URL is not specified in the MWS cluster configuration
Explanation	The cluster doesn't have a valid configuration.
Action	Log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to check the cluster configuration.
POP.005.0008E	internal cache error
Explanation	An internal error occurred while removing an item from a cache.
Action	Inspect the <code>_problems_.log</code> for details of the failure. This error could indicate that there is invalid data in a cache. Restart My webMethods Server to address the problem.

POP.005.0009E	Unable to loadComponent: "{0}"
Explanation	A failure occurred while loading a My webMethods Server component.
Action	Look in the _problems_.log file for the stack trace of the error. It may be necessary to reinstall the component.
POP.005.0010E	Unknown object: "{0}"
Explanation	The ComponentData object for a component is of an unknown type.
Action	The componentData must be one of the handled object types. This error means that a My webMethods Server component could not initialize because it is invalid. Check the component for a valid configuration.
POP.005.0013	Command not found: "{0}"
Explanation	A request to obtain a registered command failed. The command does not exist.
Action	Check the custom portlet invoking the command and ensure that it is specifying a deployed command.
POP.005.0014	Unbalanced "{1}" in value expression: "{0}"
Explanation	A legacy portlet has created an illegal dynamic expression.
Action	Review the custom portlet for proper syntax of any dynamic expressions.
POP.005.0021	Attempting to use non empty My webMethods Server database for fresh deployment. Please make sure to create new empty My webMethods Server database
Explanation	A first time startup check determined that the configured database is not a new database. A new database is required for a new installation.
Action	You must create new (empty) My webMethods Server database and configure My webMethods Server to connect to it. Please refer to the Software AG documentation for installing webMethods products.
POP.005.0022	Wrong version of My webMethods Server database: {0} but expected: {1}
Explanation	A first time startup check determined that the configured database does not match the schema required by My webMethods Server.
Action	Verify that the specified database is properly configured. The database is likely configured with an old or incomplete schema. Please refer to the Software AG documentation for installing webMethods products.

POP.005.0026	Must have at least one server node defined
Explanation	The cluster does not have a valid configuration. No server nodes are defined.
Action	Log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to check the cluster configuration.
POP.005.0028	"{0}" server node must have at least one web stack listener enabled
Explanation	Each node in the cluster is required to have at least one port enabled for accepting web requests.
Action	Log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to check the cluster configuration.
POP.005.0029	server node name must not be empty
Explanation	The cluster does not have a valid configuration. A server node name is not defined.
Action	Log in to My webMethods Server as sysadmin and use the Cluster Administration portlet to check the cluster configuration.
POP.005.0030	Credentials required.
Explanation	Credentials of a valid My webMethods Server user are required.
Action	Provide the user name and password of a valid My webMethods Server user account.
POP.005.0031	Credentials should be String[].
Explanation	Credentials must be supplied in a string array format.
Action	Configure the JMX client to provide credentials in a string array format.
POP.005.0032	Credentials should have 2 elements.
Explanation	Two credential elements (user name and password) were expected, but a non-matching number of elements were provided.
Action	Provide only the user name and password.
POP.005.0033	JMX Authentication failed!
Explanation	The user cannot be authenticated within My webMethods Server.
Action	Provide a valid My webMethods Server user.

POP.005.0034	JMX Authorization failed!
Explanation	The provided user does not have sufficient privileges for connecting via JMX.
Action	Provide a user with the "Connect to JMX" privilege.
POP.005.0035	Insufficient privileges for establishing JMX communication!
Explanation	The provided user does not have sufficient privileges for connecting via JMX.
Action	Provide a user with the "Connect to JMX" privilege.
POP.005.0036	JMX Server Port number cannot be parsed. Port parameter value "{0}".
Explanation	The provided JMX port number is not an available port number.
Action	Change the JMX port configuration property to an available port number.
POP.005.0037	JDK 1.6 or higher is required to run JMX over SSL.
Explanation	My webMethods Server is currently started with JDK 1.5.
Action	Update the My webMethods Server JDK to JDK 1.6.
POP.005.0038	MWS is currently initializing.
POP.005.0039	Can not start CDS library because MWS did not initialize yet
POP.005.0040	Can not start CDS library because MWS upgrade did not complete yet
POP.005.0041	Unable to start. Required port number {0} on host {1} (for: {2}) is already in use. Perhaps another MWS process is already running?
POP.005.0042	Unable to start. The server name {0} could not be found in the cluster definition
POP.006.0003E	portlet bean URI not specified
Explanation	The portlet:bean JSP tag does not contain a uri attribute to identify a valid portlet instance.
Action	Ensure that all instances of the 'portlet:bean' JSP tag include a 'uri' attribute. The attribute value must identify a valid portlet instance. Also, ensure that the portlet type referenced by the 'uri' attribute has been deployed and that all instances referenced by the attribute exist.

POP.006.0004E	cannot create portlet bean for the URI "{0}"
Explanation	The portlet:bean JSP tag does not contain a uri attribute that identifies a valid portlet instance.
Action	Ensure that all instances of the 'portlet:bean' JSP tag include a 'uri' attribute. The attribute value must identify a valid portlet instance. Also, ensure that the portlet type referenced by the 'uri' attribute has been deployed, and that all instances referenced by the attribute exist.
POP.006.0005	parent "{0}" not found
Explanation	The JSP page is invalid, because a JSP tag that is only valid when it is inside of a parent JSP tag is not inside the expected parent.
Action	Locate the error in the JSP page and correct the problem.
POP.006.0006E	cannot find portlet bean named "{0}" in the current page context
Explanation	The portlet:portletController JSP tag does not contain a portlet attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.portal.service.portlet.IPortletBean object is stored.
Action	Ensure that all instances of the 'portlet:portletController' JSP tag include a 'portlet' attribute that references a valid IPortletBean.
POP.006.0007E	cannot obtain portlet info
Explanation	The portlet:info JSP tag does not contain an info attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.portal.service.portlet.info.IPortletInfo object is stored.
Action	Ensure that all instances of the 'portlet:info' JSP tag include an 'info' attribute that references a valid IPortletInfo object.
POP.006.0008E	cannot find portlet info named "{0}" in the current page context
Explanation	The portlet:propertyGroups, portlet:propertyGroup, or portlet:propertyLine JSP tag does not contain an info attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.portal.service.portlet.info.IPortletInfo object is stored.
Action	Ensure that all instances of the 'portlet:propertyGroups', 'portlet:propertyGroup', and 'portlet:propertyLine' JSP tags include an 'info' attribute that references a valid IPortletInfo object.

POP.006.0015	cannot obtain portlet property info
Explanation	The portlet configuration information could not be found. This problem could result from an invalid JSP page or a portlet installation that has been corrupted.
Action	Review the JSP page and ensure the portlet:propertyLine JSP tag is contained within a portlet:bean tag. If the JSP is correct and the problem persists, try re-installing the broken portlet.
POP.006.0016E	cannot find portlet property info named "{0}" in the current page context
Explanation	The portlet:propertyLine JSP tag does not contain a propertyInfo attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.portal.service.portlet.info.IPortletPropertyInfo object is stored.
Action	Ensure that all instances of the 'portlet:propertyLine' JSP tag include a 'propertyInfo' attribute that references a valid IPortletPropertyInfo.
POP.006.0017	portlet property name not specified
Explanation	The JSP page contains a portlet:propertyLine tag that is missing the required "name" property.
Action	Review the JSP page and correct any missing "name" properties.
POP.006.0018E	cannot obtain portlet property bag
Explanation	The portlet:propertyLine JSP tag does not contain a propertyInfo attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.rtl.util.obj.IPropertyBag object is stored.
Action	Ensure that all instances of the 'portlet:bean' JSP tag include a 'propertyInfo' attribute that references a valid IPropertyBag.
POP.006.0019E	cannot find portlet property bag named "{0}" in the current page context
Explanation	The portlet:propertyLine JSP tag does not contain a propertyInfo attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.rtl.util.obj.IPropertyBag object is stored.
Action	Ensure that all instances of the 'portlet:bean' JSP tag include a 'propertyInfo' attribute that references a valid IPropertyBag.
POP.006.0020E	object named "{0}" in the current page context is not a portlet property bag
Explanation	The portlet:propertyLine JSP tag does not contain a propertyInfo attribute. The value of this attribute is the key to the pageContext entry in which a com.webmethods.rtl.util.obj.IPropertyBag object is stored.
Action	Ensure that all instances of the 'portlet:bean' JSP tag include a 'propertyInfo' attribute that references a valid IPropertyBag.

POP.006.0021	"{0}" requires body content
Explanation	A JSP page contains an sql:query tag with missing SQL query text in the tag body.
Action	The JSP page must be edited to either remove the tag or add the SQL query text as the tag body.
POP.006.0022	skin property not found
Explanation	In a JSP page, the ui:img tag is trying to render an image from the skin, but the image was not defined in the skin.
Action	Edit the skin to add the missing image, or change the JSP page to reference an image that does exist.
POP.006.0024E	'IterateTag' container is null
Explanation	The util:iterate JSP tag does not contain a container attribute. The value of this attribute is the key to the pageContext entry in which a java.util.Collection, java.util.Iterator, or java.lang.Object[] object is stored.
Action	Ensure that all instances of the 'util:iterate' JSP tag include a 'container' attribute that references a valid container object.
POP.006.0025	"{0}" class not supported as an 'IterateTag' container
Explanation	A JSP page uses the util:iterate tag, but the value of the 'container' property is not one of the supported data types.
Action	The JSP page must be edited to correct the problem.
POP.006.0026	"{0}" requires "{1}" attribute
Explanation	A JSP page uses the util:iterate tag, but the "indexVar" tag attribute was not supplied.
Action	The JSP page must be edited to add the missing tag attribute.
POP.006.0027	cannot find 'PerfStartTag' token named "{0}"
Explanation	A JSP page uses the util:perfEnd tag, but the perf token supplied in the "name" tag attribute does not exist.
Action	This problem most likely results from a malformed JSP page. The JSP developer should review the JSP page for any mismatched util:perfStart/util:perfEnd pairs.

POP.006.0028E	cannot find XML DOM node named "{0}" in the current page context
Explanation	Use of the xml:valueOf JSP tag causes this exception.
Action	Remove all instances of the 'xml:valueOf' JSP tag.
POP.006.0029E	cannot create XML DOM document from given XML stream
Explanation	The XML stream specified for the xml:xml JSP tag does not contain well-formed XML.
Action	Check the _problems_.log in the Portal's current logging directory for more specific error information.
POP.006.0030E	cannot load XML DOM document for the specified location "{0}"
Explanation	The xml:xml JSP tag could not load a file from the location specified by the 'location' attribute.
Action	Edit instances of the 'xml:xml' JSP tag to include a 'location' attribute that correctly specifies the url to an XML document.
POP.006.0031	Required Property Editor parameter "{0}" not specified.
Explanation	A JSP page is rendering a property editor, but a required parameter has not been supplied.
Action	The JSP developer should edit the JSP page to supply the missing required parameter.
POP.006.0032	Property Editor "{0}" not deployed.
Explanation	A JSP page is trying to render a property editor that is not deployed to My webMethods Server.
Action	Deploy the missing property editor to My webMethods Server, or change the JSP page to use a property editor that is deployed to My webMethods Server.
POP.006.0033	invalid portlet bean URI: {0}
Explanation	A JSP page is using either the portlet:bean or the portlet:controller tag in which the supplied portlet URI does not match an existing portlet instance.
Action	Deploy the missing portlet instance. Or, edit the JSP page to change the URI to match an existing portlet instance.

POP.007.0002	Error getting directory mechanics: "{0}"
Explanation	The My webMethods Server instance was not properly installed.
Action	Re-create the My webMethods Server database schema and the My webMethods Server server instance.
POP.007.0003	Error rendering layout "{0}" due to "{1}"
Explanation	There was an error either compiling or executing the application *.JSP page.
Action	You may need to run My webMethods Server with a full JDK which includes the Java compiler. Or, if you have modified any system JSP or NBSB pages, there may have been a syntax error.
POP.007.0006	Requested content was not found: "{0}"
Explanation	An error occurred when attempting to browse to a page or file; the page or file does not exist in My webMethods Server.
Action	Verify that the URL being browsed to is correctly formed and specifies a valid URL.
POP.007.0007E	Command not Found: "{0}"
Explanation	An attempt was made to execute a server command that is not deployed.
Action	Log in to My webMethods Server and use the Install Administration portlet to deploy the missing portlet.
POP.007.0008	The requested resource is not a webservice: "{0}"
Explanation	An attempt was made to obtain a WSDL for a resource that is not a web service.
Action	Modify the request to specify a resource that is a web service.
POP.007.0009	You are not authorized to view the resource.
Explanation	The current user does not have permission to view the specified object or page.
Action	Check the permissions for the object or page to ensure that the user has read rights
POP.007.0010E	This renderer is unable to render: "{0}"
Explanation	An attempt was made to use the FolderRenderer to render an item that is not a folder.
Action	You cannot use the FolderRenderer for non-folders; specify a valid folder.

POP.007.0011E	Unknown response: "{0}"
Explanation	The dispatch handler returned an unknown return code.
Action	Correct the dispatch handler to return a valid return code.
POP.007.0012	Cannot redirect to an invalid data type: "{0}"
Explanation	An incorrect API was called when redirecting to new URL. This error is most likely to occur with a custom portlet.
Action	Verify that the portlet specifies the correct API for redirection.
POP.007.0013	Unable to find adequate authentication information to instantiate an http session
Explanation	My webMethods Server is unable to authenticate an HTTP session.
Action	This error can occur because of incorrect implementation of custom authentication (such as, agent based authentication). Review the custom authentication scheme and verify that it is correctly implemented.
POP.007.0023	getWriter() has already been called on this response.
Explanation	This error indicates an incorrect usage of the <code>HttpResponse.getWriter()</code> API and most likely occurred in a custom CAF application.
Action	Review the CAF application and check the implementation of the <code>HttpResponse</code> APIs.
POP.007.0024	getOutputStream() has already been called on this response.
Explanation	This error indicates an incorrect usage of the <code>HttpResponse.getOutputStream()</code> API and most likely occurred in a custom CAF application.
Action	Review the CAF application and check the implementation of the <code>HttpResponse</code> APIs.
POP.007.0026	Response body content already written.
Explanation	This error occurs when attempting to set the <code>HttpResponse</code> header when the response has been already partially or fully committed. This most likely occurred in a custom CAF application.
Action	Review the CAF application and check the implementation of the <code>HttpResponse</code> APIs.
POP.007.0027	Internal Error! Portlet Controller Bean is null.
Explanation	The system cannot serve as the internal controller bean for the portlet.
Action	This error occurs only for non-CAF portlets. Log out and log back in to resolve this problem.

POP.007.0028	User not found: "{0}"
Explanation	This error occurs when a user ID passed into My webMethods Server by a custom authentication handler cannot be matched.
Action	Verify that the specified user exists in the My webMethods Server directories, and check the custom authentication handler logic.
POP.007.0029	No authentication information was found.
Explanation	No user name was supplied to My webMethods Server when authenticating a user. This error can occur with a custom authentication handler.
Action	Check the implementation of the custom authentication handler. Verify the proper operation of any custom login forms.
POP.007.0033	No portlet found to render "{0}" view.
Explanation	This error can occur if there is a registered portlet renderer, but the portlet defined in the renderer is not found.
Action	Renderers are used internally by My webMethods Server to define certain system pages. If this error occurs, check to see if any of the My webMethods Server system components have been un-installed.
POP.007.0035	The value {0} can not be changed
Explanation	An attempt has been made to change the value of an invalid portlet preference.
Action	Verify that the correct portlet preference name is used.
POP.007.0036	The store() method can not be called from a render method
Explanation	An attempt was made to change and persist portlet preferences from the render() method.
Action	Portlet preferences can be changed only with the portlet action method. Correct the code which updates portlet preferences to use the proper method.
POP.007.0037	The state of the portlet can not be changed
Explanation	Portlet preferences can be updated only during the action() request.
Action	Correct the usage of the portlet preferences APIs to change preferences during the action() request.

POP.007.0038	The key given is null.
Explanation	An attempt was made to use the portlet preferences API with a NULL preference name.
Action	Correct the portlet preferences API implementation to specify a valid preference name.
POP.007.0044	The map given is null
Explanation	This error indicates an incorrect usage of the portlet URL APIs; the parameter map setting is NULL.
Action	Correct the portlet URL APIs implementation to specify a valid parameter map.
POP.007.0045	The map given contains a null key
Explanation	This error indicates an incorrect usage of the portlet URL APIs; the parameters map setting contains a NULL key.
Action	Correct the portlet URL APIs implementation to specify a valid parameter map key.
POP.007.0046	The map contains a non String key
Explanation	This error indicates an incorrect usage of the portlet URL APIs; the parameters map setting contains non-String values.
Action	Correct the portlet URL APIs implementation to pass in only String type parameters.
POP.007.0047	Namespace prefix defined more than once for {0}
Explanation	An incorrect URL was passed into My webMethods Server; more than one namespace prefix is provided.
Action	Check that the URL passed into My webMethods Server contains only one single value for the namespace prefix.
POP.007.0048	Namespace prefix is not defined for {0} and the prefix id is not a valid thingID
Explanation	An incorrect URL was passed into My webMethods Server; no namespace prefix is provided.
Action	Modify the URL passed into My webMethods Server to define the missing namespace prefix.

- POP.007.0049** **The portlet mode {0} is not supported for the {1} markup language.**
Explanation The requested mode is not implemented in the portlet or is not supported.
Action Check the portlet URL API usage if attempting to set the mode with APIs. If this is a custom portlet, check to see if the portlet implements this mode.
- POP.007.0051** **Output generated because of an exception**
Explanation An exception occurred while rendering portlet content.
Action Refer to the server logs at ..\MWS\server\default\logs for additional exception details.
- POP.007.0052** **sendRedirect was already called**
Explanation An attempt was made to change the portlet window state, mode, or parameters after a redirect request was sent.
Action Examine and correct the usage of the redirect request in the portlet code.
- POP.007.0053** **The portlet mode is null**
Explanation An attempt was made to set a NULL portlet mode.
Action Examine and correct the usage of the Portlet URL API.
- POP.007.0054** **The window state {0} is not supported by the portlet container**
Explanation An attempt was made to set an invalid window state.
Action Examine and correct the window state being set by the Portlet URL APIs.
- POP.007.0055** **The window state is null**
Explanation An attempt was made to set a NULL window state.
Action Examine and correct the window state being set by the Portlet URL APIs.
- POP.007.0056** **The portlet mode {0} is not supported by the portlet container**
Explanation An attempt was made to set an invalid portlet mode.
Action Examine and correct the portlet mode being set by the Portlet URL APIs.

POP.007.0057	The map contains a non String[] value
Explanation	An attempt was made to set a parameter with a value that is not of the type String[].
Action	Examine and correct parameters being by the Portlet URL API; these values must be String or String[] types only.
POP.007.0058	The key given is null
Explanation	An attempt was made to pass in a NULL key value.
Action	Examine and correct the key value that is being passed in by the Portlet URL API.
POP.007.0059	The value given is null
Explanation	An attempt was made to pass in a NULL value.
Action	Examine and correct the value being passed in by the Portlet URL API.
POP.007.0060	The sendRedirect method can not be invoked after any of the following methods of the ActionResponse interface has been called: setPortletMode, setWindowState, setRenderParameter, setRenderParameters
Explanation	The sendRedirect method can not be invoked after any of the following methods of the ActionResponse interface has been called: setPortletMode, setWindowState, setRenderParameter, setRenderParameters
Action	Correct the code to ensure that the sendRedirect() method does not occur after these calls during the same action request.
POP.007.0061	A relative or incorrect path URL is given
Explanation	An attempt was made to redirect to an invalid URL.
Action	Check the URL that is the target of the redirect. It must start with "http://", "https://", or "/".
POP.007.0062	You cannot have null as a parameter
Explanation	An attempt was made to pass in a NULL parameter name.
Action	Examine and correct the parameter name used in the PortletContext and PortletRequest APIs.

POP.007.0063	Content type cannot be application/x-www-form-urlencoded
Explanation	Incorrect API usage. The ServletRequest.getReader() and getInputStream() methods are not available for requests where a form is submitted.
Action	Examine and correct the ServletRequest.getReader() and getInputStream() API usage.
POP.007.0064	This method cannot be called, when getReader() method has been called
Explanation	The ServletResponse method cannot be used when the getReader() method has been called.
Action	Examine and correct the ServletResponse API usage.
POP.007.0065	The attribute name cannot be null
Explanation	An attempt was made to get or set an attribute using a NULL name.
Action	Examine and correct the attribute name being passed to the API.
POP.007.0066	Path must start with /
Explanation	An attempt was made to get a resource using an invalid path. The path of the resource must start with "/".
Action	Examine and correct the path name set by the PortletContext API.
POP.007.0069	The content type {0} is not supported.
Explanation	An attempt was made to set an invalid content type.
Action	Check and correct the content type being set by the PortletResponse API.
POP.007.0070	The content type has not been set before calling the getPortletOutputStream() method.
Explanation	The response content type must be set before obtaining the output stream.
Action	Examine and correct the API calls.
POP.007.0071	the output stream has already been called
Explanation	A Writer cannot be obtained for the response after obtaining the output stream.
Action	Examine and correct the API usage.

POP.007.0072	the PrintWriter object has already been called
Explanation	A Writer cannot be obtained for the response because the output stream has already been obtained.
Action	Examine and correct the API usage.
POP.007.0073	Can not serialize Portlet Preferences
Explanation	There was error when serializing portlet preferences. Portlet preferences cannot contain non-serializable objects.
Action	Check the server log for more details. Examine and correct any portlet preferences being set to ensure only serializable objects are used.
POP.007.0074	Portlet Application "{0}" is not properly installed or unavailable.
Explanation	The system cannot load the specified portlet application. It is either not installed or is disabled in the cluster partition.
Action	Re-install the portlet application. Check the server logs for errors during installation. Verify that the application is enabled in the cluster partition.
POP.007.0075	Portlet "{0}" is not found
Explanation	The specified portlet is not installed or is disabled in the cluster partition.
Action	Verify that the portlet application is installed; install if necessary. Check the server logs for any installation errors. Verify that the portlet is enabled in the cluster partition.
POP.007.0076	PortletContainer Servlet "{0}" is not found. Check default web application configuration file (defaultPortletAppWeb.xml)
Explanation	System servlet is not found.
Action	Determine if any changes were made to system configuration files in ../MWS/server/default/deploy/portal.war. Re-install My webMethods Server.
POP.007.0077	You are not authorized to view the resource. {0}
Explanation	The current user does not have permission to read the specified object or resource.
Action	Examine and correct the user account permissions.

POP.007.0078	This action requires an anti-cross-site-request-forgery token.
Explanation	The executed command or action did not specify an anti-cross-site-request-forgery token.
Action	Check if the given command or action does require an AXRF token. If it does require a token, the token must be explicitly generated and passed in as a URL parameter. For example, when calling a CAF action from a portlet URL, the action must either be configured to not require a token (which lessens security), or a token must be generated when calling this action from a direct URL.
POP.007.0101	Illegal Property Editor name: "{0}".
Explanation	A legacy portlet property uses an invalid property-editor name.
Action	Examine and correct the property-editor name in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).
POP.007.0102	Illegal Property Editor parameter value for "{0}": "{1}".
Explanation	An incorrect parameter value was passed to the property editor.
Action	Check the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).
POP.007.0103	Property Editor requires DHTML.
Explanation	The property editor "dhtml" property configuration is invalid. The property editor requires DHTML to be enabled.
Action	Examine the property editor configuration in the wm-portlet.xml file. Set dhtml=true (this applies only to legacy non-CAF portlets).
POP.007.0105	Property editor "{0}" parameter "{1}" of type "choice" defined without choices.
Explanation	An invalid 'choice' parameter value was supplied to the property editor.
Action	Examine the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).
POP.007.0106	Illegal property editor "{0}" attribute: "{1}" value: "{2}".
Explanation	An invalid property editor attribute was encountered.
Action	Examine the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).

POP.007.0107	Illegal property editor "{0}" parameter "{1}" attribute "{2}" value: "{3}".
Explanation	An invalid property editor attribute was encountered.
Action	Examine the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).
POP.007.0108	Illegal property editor "{0}" parameter "{1}" choice "{2}" attribute "{3}" value: "{4}".
Explanation	An invalid property editor attribute was encountered.
Action	Examine the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).
POP.007.0109	Property Editor not deployed: "{0}".
Explanation	An incorrect property editor was specified for use
Action	Examine the property editor configuration in the wm-portlet.xml file (this applies only to legacy non-CAF portlets).
POP.007.0110	Illegal Redirect URL: "{0}".
Explanation	An invalid redirect URL was provided.
Action	Check and correct the redirect URL used in the API calls.
POP.009.0001	WebService invocation is disabled for the requested command
Explanation	An attempt was made to invoke a My webMethods Server command as a web service, but the command does not allow invocation as a web service.
Action	1. Enable the command if it is disabled. 2. For some commands it is not possible to execute them with a web service. If this is one of those commands, no other action can be taken.
POP.009.0002	No WebService type mapping found for java class: {0}
Explanation	For a My webMethods Server command being invoked as a web service, one or more of the command bean (input) fields to the command does not have a SOAP serializer (or deserializer) defined. Therefore, the My webMethods Server framework cannot convert the data to a SOAP message.
Action	The command developer must either mark the command as not enabled for web service invocation, or write the custom serializer/deserializer code for the data type and register it in the type mapping registry by overriding the "initializeSOAPMappingRegistry" method of the command Java class.

POP.009.0003	The CommandBean must implement ISoapComplexTypeBean to be used as a WebService
Explanation	For a My webMethods Server command being invoked as a web service, the command bean Java class does not implement the interface that is required to be used as a web service.
Action	The command developer must either mark the command as not enabled for web service invocation, or change the command bean Java class to have it implement the interface.
POP.009.0004	Error initializing ServiceDesc for WebService: {0}
Explanation	An unexpected exception was detected while preparing a My webMethods Server command to be invoked as a web service.
Action	Inspect the stack trace in the My webMethods Server server log files to determine the cause of the exception.
POP.009.0005	No WebService marshalling factories are defined for type {0}, and the type can not be treated as a javabean because it does not contain a public no-arg constructor
Explanation	For a My webMethods Server command being invoked as web service, one of the inputs or outputs is a complex Java class that does not have a no-arg constructor. Therefore, it cannot be automatically marshalled into a SOAP message.
Action	The command developer must either mark the command as not enabled for web service invocation, or add a no-arg constructor to the Java class.
POP.009.0006	SAML or Hybrid authentication can not be used. Please deploy SAML Security Service component or use Basic authentication instead
POP.009.0007	Could not find a user context.
POP.009.0008	The SAML service you are trying to access is not available right now.
POP.009.0102	{0}: {1} is not a IThingIDList
Explanation	The SOAP serializer that is intended to marshal a IThingIDList object into a SOAP message was passed the wrong type of object.
Action	This is most likely a defect in the way the type mapping registry was initialized. Examine the related code to determine the problem and correct as required.

POP.011.0001	The method "{0}" has not been implemented.
Explanation	An attempt was made to improperly invoke a Dynamic API.
Action	Examine the logs for an indication of what component and user action caused this error.
POP.011.0002	must specify both 'prefix' and 'uri' parameters for 'taglib' directive
Explanation	A syntax error occurred while parsing a JSP page.
Action	Correct the syntax error on the JSP page.
POP.011.0003	expected "{0}" end tag but found "{1}" end tag
Explanation	A syntax error occurred while parsing a JSP page.
Action	Correct the syntax error on the JSP page.
POP.011.0005	"{0}" tag declared invalid by TagExtraInfo
Explanation	A syntax error occurred while parsing a JSP page.
Action	Correct the syntax error on the JSP page.
POP.011.0006	"{0}" tag requires "{1}" attribute
Explanation	A syntax error occurred while parsing a JSP page.
Action	Correct the syntax error on the JSP page.
POP.011.0007	specified attribute "{0}" for "{1}" tag not declared in tld
Explanation	A syntax error occurred while parsing a JSP page.
Action	Correct the syntax error on the JSP page.
POP.011.0008	specified attribute "{0}" value for "{1}" tag cannot be request-time expression
Explanation	A syntax error occurred while parsing a JSP page.
Action	Correct the syntax error on the JSP page.
POP.011.0009	request cannot be null
Explanation	An error occurred while uploading a file.
Action	Check the logs for additional information.

POP.011.0010	saveDirectory cannot be null
Explanation	An error occurred while uploading a file.
Action	Use the Content Service page to ensure that a directory is configured to store the uploaded files.
POP.011.0011	maxPostSize must be positive
Explanation	An error occurred while uploading a file.
Action	Use the Content Service page to ensure that a maximum size for uploaded files is configured.
POP.011.0012E	"{0}" is not a directory.
Explanation	The temporary location for saving a file upload is not valid.
Action	Delete all files in the Portal/server/default/temp folder.
POP.011.0013W	"{0}" is not writable directory.
Explanation	The temporary location for saving a file upload is not writable.
Action	Make sure My webMethods Server was started by a user who has rights to the portal temp folder.
POP.011.0014E	Posted content type "{0}" isn't multipart/form-data.
Explanation	My webMethods Server expects to upload a multipart portlet, but the specified content type does not match.
Action	Check the source file for corruption. If the file is valid and correct, try uploading it again.
POP.011.0015E	Posted content length of "{0}" MB exceeds limit of "{1}" MB.
Explanation	An uploaded file is larger than the size allowed by the system administrator.
Action	Upload a smaller file or have the system administrator use the Content Service Administration portlet to increase the maximum allowed file size.
POP.011.0016E	Separation boundary was not specified.
Explanation	The specified file was corrupted before or during the upload process.
Action	Check the source file for corruption. If the file is valid and correct, try uploading it again.

POP.011.0017E	Corrupt form data. No leading boundary was found.
Explanation	The specified file was corrupted before or during the upload process.
Action	Check the source file for corruption. If the file is valid and correct, try uploading it again.
POP.011.0018E	Malformed line after disposition "{0}"
Explanation	The specified file was corrupted before or during the upload process.
Action	Check the source file for corruption. If the file is valid and correct, try uploading it again.
POP.011.0019E	The published file was empty or invalid.
Explanation	The specified file was corrupted before or during the upload process.
Action	Check the source file for corruption. If the file is valid and correct, try uploading it again.
POP.011.0020E	Content disposition "{0}" is corrupt.
Explanation	The specified file was corrupted before or during the upload process.
Action	Check the source file for corruption. If the file is valid and correct, try uploading it again.
POP.011.0021	Invalid content disposition "{0}".
Explanation	An error occurred while processing the uploaded file.
Action	Investigate the contents of the HTTP POST to see if the data was corrupted.
POP.011.0022E	Content type corrupt "{0}".
Explanation	The specified file was corrupted before or during the upload process.
Action	Check the source file for corruption. If the file is valid and correct, try uploading it again.
POP.011.0023E	Malformed line after disposition "{0}".
Explanation	The specified file was corrupted before or during the upload process.
Action	Check the source file for corruption. If the file is valid and correct, try uploading it again.

POP.011.0024	No file name available.
Explanation	An error occurred while uploading a file.
Action	Examine the contents of the HTTP POST to see if the data was corrupted.
POP.011.0025E	Failed to create a DocumentBuilderFactory.
Explanation	The XML parser appears to be missing.
Action	Check for the xercesImpl.jar file in the portal class path. If the file is missing, reinstall My webMethods Server.
POP.011.0026E	Failed to create a TransformerFactory.
Explanation	The Xalan XSTL processor could not be loaded.
Action	Check for the xalan.jar file in the portal classpath. If the file is missing, reinstall My webMethods Server.
POP.011.0027	JMS already initialized with "{0}".
Explanation	An error occurred during startup.
Action	Ensure that startup routines are invoked only once.
POP.011.0028E	JMSProvider: failed to get configuration file.
Explanation	The JMS provider appears to be disconnected.
Action	Verify that the Broker is running and that My webMethods Server can connect to the computer on which the Broker is running.
POP.011.0029E	JMSProvider: failed to get configuration file "{0}", due to "{1}".
Explanation	The JMS provider appears to be disconnected.
Action	Verify that the Broker is running and that My webMethods Server can connect to the computer on which the Broker is running.
POP.011.0030E	JNDI name not found: "{0}".
Explanation	The JMS provider appears to be disconnected.
Action	Verify that the Broker is running and that My webMethods Server can connect to the computer on which the Broker is running.

POP.011.0031	Can't initialize perf service: "{0}".
Explanation	The specified Performance Service failed to initialize.
Action	Check the perfUtils.properties configuration file for spelling errors.
POP.011.0032	Perf Service Not Initialized.
Explanation	An attempt was made to use the Performance Service before it was initialized.
Action	The Performance Service might be disabled. Check the contents of the perfUtils.properties configuration file.
POP.011.0033	Cannot open stream. Location: "{0}".
Explanation	An attempt to access a file failed.
Action	Ensure that the file exists at the specified location.
POP.011.0034E	Size read mismatch "{0}" vs "{1}"
Explanation	An InputStream corruption error occurred.
Action	Examine the _problems_.log file for the stack trace of the error. The stack trace may not provide enough detail to explain why the error was thrown, but it will show where the error originated.
POP.011.0035	Cannot create temporary folder: "{0}"
Explanation	Folder creation failed.
Action	Most likely, the current process lacks Write access to the configured temporary folder.
POP.011.0036E	Unable to delete file: "{0}"
Explanation	An error occurred while removing a temporary file.
Action	Find the specified file and remove it manually.
POP.011.0037E	Unable to delete directory: "{0}"
Explanation	An error occurred while cleaning up temporary files.
Action	Find the specified directory and manually remove the temporary files.

POP.011.0039E	ObjectUtil: illegal arguments.
Explanation	An error occurred while setting a property on an object, because the target object is null or the property name is null or empty.
Action	Examine the <code>_problems_.log</code> file for the stack trace of the error. The stack trace may not provide enough detail to explain why the error was thrown, but it will show where the error originated.
POP.011.0044E	Error obtaining JMS topic for name: "{0}"
Explanation	The requested JMS topic is not available.
Action	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.
POP.011.0045E	no JMS provider, requesting topic name: "{0}"
Explanation	The JMS provider appears to be disconnected.
Action	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.
POP.011.0046E	JMSTopic.createTopicSession(), no JMS provider.
Explanation	The JMS provider appears to be disconnected.
Action	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.
POP.011.0047E	Unable to connect to registry.
Explanation	The My webMethods Server configuration registry is unavailable.
Action	In a cluster deployment, make sure the Master server is started before starting the other cluster nodes.
POP.011.0048	no protocol defined for: "{0}"
Explanation	The system tried to load a file from an unknown protocol.
Action	Check the protocol string spelling.
POP.011.0053E	Error obtaining JMS queue for name: "{0}"
Explanation	The requested JMS queue is unavailable.
Action	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.

POP.011.0054E	no JMS provider, requesting queue name: "{0}"
Explanation	The JMS provider appears to be disconnected.
Action	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.
POP.011.0055E	JMSTopic.createQueueSession(), no JMS provider.
Explanation	The JMS provider appears to be disconnected.
Action	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.
POP.011.0056E	Invalid line: "{0}"
Explanation	An error occurred in parsing a .properties file.
Action	Look in the _problems_.log file for the stack trace of the error. The stack trace may not provide enough detail to explain why the error was thrown, but it will show where the error originated.
POP.011.0057E	JMSDestination.Subscriber, unable to create consumer on: "{0}"
Explanation	The JMS provider appears to be disconnected.
Action	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.
POP.011.0058E	JMSDestination.Subscriber, unable to create session for: "{0}"
Explanation	The JMS provider appears to be disconnected.
Action	Verify that Broker is running and that My webMethods Server can connect to the computer on which Broker is running.
POP.011.0062E	Stream exhausted.
Explanation	An error occurred in decoding a BASE64 String.
Action	Examine the _problems_.log file for the error stack trace. The stack trace may not provide enough detail to explain why the error was thrown, but it will show where the error originated.

- POP.011.0063E** **BASE64Encoder: Bad Padding byte.**
Explanation An error occurred in decoding a BASE64 String.
Action Examine the _problems_.log file for the error stack trace. The stack trace may not provide enough detail to explain why the error was thrown, but it will show where the error originated.
- POP.011.0065** **There must be a default entry --> default=icon_def.gif.**
Explanation The iconMap.properties file is corrupted.
Action Revert any changes made to this file.
- POP.011.0068** **Output stream not set for: "{0}"**
Explanation An error occurred during page rendering.
Action Check the logs for problems that result in this situation.
- POP.011.0076** **Unable to convert data type "{0}" to "{1}"**
Explanation The system failed in the attempted type coercion.
Action If possible, check the input value to ensure that it can be properly coerced to the target data type.
- POP.012.0001.tagname_error** – **Not a valid value!Tag Name cannot contain spaces.**
- POP.012.0001.wm_axsrftconfig** – **This action requires a custom anti-cross-site-request-forgery token.**
- POP.012.0001.wm_caf_task** – **Cannot upload this file as it is empty.Uploading empty files is not allowed.**
Explanation Content cannot contain an empty file, therefore uploading is not allowed
Action Make sure that the file contains content.
- POP.012.0001.wm_calendar** – **Illegal "{0}" parameter value: "{1}".**
Explanation The starting date of an entry in Calendar.
Action Please sepecify the start date of an entry in Calendar.

POP.012.0001.wm_cforms_layout – Recursive use of Composite Form for "{0}".

POP.012.0001.wm_commonsearchbar – Search Context Portlet URI is not valid: {0}

Explanation Search Context Portlet URI is not valid
Action Please specify a valid search context portlet

POP.012.0001.wm_commonsearchresults – Search Context Portlet URI is not valid: {0}

Explanation Search Context Portlet URI is not valid
Action Please specify a valid search context portlet

POP.012.0001.wm_contentrendererE – Unable to parse regexps: {0}

Explanation The My webMethods Server installation is missing RegEx support jars.
Action Reinstall My webMethods Server.

POP.012.0001.wm_dirsearchcontext – This portlet is not intended to be viewed standalone

Explanation This portlet is not intended to be viewed standalone. This error is displayed on UI when it's viewed standalone.
Action Don't view this portlet as standalone portlet.

POP.012.0001.wm_discotres_forumview – Forum or category not specified.

POP.012.0001.wm_discotres_forumwizard – Must specify "parent" property.

POP.012.0001.wm_discotres_messageview – Forum message not specified.

POP.012.0001.wm_discotres_topicview – Forum topic not specified.

POP.012.0001.wm_emaildeliverer – Nondisclosed Portal Event Subscribers

POP.012.0001.wm_fabric_addtostart – You already have an instance of this portlet on the target page.

Explanation You already have an instance of this portlet on the target page.
Action Please choose another portlet to add

POP.012.0001.wm_formattedxml – No content available for {0}.

Explanation No content can be retrieved from that specified style sheet

Action Make sure that style sheet does have content

POP.012.0001.wm_httpheaderauth – In order to properly configure webMethods Portal to accept External Http authentication credentials. These credentials are case sensitive and depending on platform and web server will most likely be either: `sm_user` or `SM_USER`

POP.012.0001.wm_inlinecontent – No content available for {0}.

Explanation No content can be retrieved

Action Please make sure the resource does have content

POP.012.0001.wm_jazzy – Not a valid dictionary identifier: "{0}".

POP.012.0001.wm_login – No current servlet request.

POP.012.0001.wm_mws_diagnostics – No Performance Service is currently available. To enable the Service, please go to the properties page of this portlet.

Explanation No performance service is currently enabled.

Action To enable a service, go to the properties page of the Performance Analysis portlet.

POP.012.0001.wm_noodle – Cannot load page content.

POP.012.0001.wm_noodle_context_wiring – This portlet has no UI.

POP.012.0001.wm_ntlmv2authadmin – NTLM authentication failed because login has been disabled for the {0} user.

Explanation The Directory Service reports that the 'Diisabled' attribute for the user record is set to true. This user cannot authenticate with My webMethods Server.

Action To enable this user to authenticate with My webMethods Server, set the 'Diisabled' attribute to false in the appropriate directory server.

POP.012.0001.wm_portaldca.Cache.CacheSizeDesc – Current number of entries

POP.012.0001.wm_portaldca.Cache.Entries_w_DependenciesDesc – Number of entries that have dependencies

POP.012.0001.wm_portaldca.Cache.ExpirableEntriesDesc – Current number of entries that can expire

POP.012.0001.wm_portaldca.Cache.ExpiredEntriesDesc – Number of entries that have expired during the current interval

POP.012.0001.wm_portaldca.Cache.InvalidEntriesDesc – Number of entries that are no longer considered to be valid

POP.012.0001.wm_portaldca.Cache.MaximumSizeDesc – Maximum number of entries allowed

POP.012.0001.wm_portaldca.Cache.TotalDependenciesDesc – Total number of dependencies for all entries

POP.012.0001.wm_portaldca.Cache.UniqueKeysDesc – Number of entries with unique keys

POP.012.0001.wm_portaldca.Cache.ValidEntriesDesc – Number of entries that are considered to be valid

POP.012.0001.wm_portaldca.DataCollectionAgentSettings – Data Collection Agent Settings

POP.012.0001.wm_portaldca.EnableJVMMemoryMonitor – Enable JVM Memory Monitor

POP.012.0001.wm_portaldca.EnableMonitor – Enable Optimize webService satellite to monitor Portal

POP.012.0001.wm_portaldca.Event.Desc.IAddEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IAddNoteEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IAddReferenceEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IAutoClassificationEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.ICopyEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.ICopyReferenceEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.ICreateEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IDeleteEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IGetEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IModifyEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IMoveEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IMoveReferenceEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IPermissionsEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IPortal2ThingsEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IPortal3ThingsEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IPurgeEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IPurgeRequestEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IRemoveEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IRemoveReferenceEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.ISetAcesEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.ISetAnonymousEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.ISetAuthSchemeEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.ISetOwnerEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.ISetPolicyEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.ITransferEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IUpdateEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.Desc.IWorkspaceUpdateEvent – Number of events during the collection interval

POP.012.0001.wm_portaldca.Event.FirstLoginDesc – Number of times that users has logged in for the first time in a day

POP.012.0001.wm_portaldca.Event.LoginDesc – Number of logins during the day

POP.012.0001.wm_portaldca.Event.LoginFailedDesc – Number of failed logins during the day

POP.012.0001.wm_portaldca.Event.LogoutDesc – Number of logouts during the day

POP.012.0001.wm_portaldca.Event.MissingResource – portaldca is missing a resource for event: {0}

POP.012.0001.wm_portaldca.Event.UnknownDesc – Number of undefined or unknown login events

POP.012.0001.wm_portaldca.Memory.FreeMemoryDesc – The amount free in the JVM

POP.012.0001.wm_portaldca.Memory.MaxAllowedMemoryDesc – The max amount the JVM will attempt to use

POP.012.0001.wm_portaldca.Memory.TotalMemoryDesc – The total amount available in the JVM

POP.012.0001.wm_portaldca.OptimizeAddressAndPort – Optimize Server Address and Port:

POP.012.0001.wm_portaldca.OptimizeAddressAndPortInstructions – (use colon to separate IE HostName:12005)

POP.012.0001.wm_portaldca.SystemName – Portal System Name used by Optimize:

POP.012.0001.wm_portaldca.UpdateTimerValue – Update Timer Value (in seconds):

POP.012.0001.wm_portletinportletE – Recursive use of Portlet-in-Portlet for "{0}".

Explanation Portlet-in-Portlet is attempting to display an item that displays the same Portlet-in-Portlet (for instance, the Portlet-in-Portlet is displaying a portal page containing the same Portlet-in-Portlet).

Action Change the Portlet-in-Portlet's "Portal Page" property to a different item.

POP.012.0001.wm_principalprofileadmin – You don't have rights to modify the properties of this item.

Explanation The current user does not have sufficient privileges to make changes to this portlet

Action Contact a My webMethods Server system administrator to modify the current user's permissions.

POP.012.0001.wm_propertiesE – {0} is not specified.

Explanation The Properties portlet could not locate the object to show its properties.

Action Close and reopen the internet browser window.

POP.012.0001.wm_publish.NotLicensed – The "Publish" feature is disabled because this deployment is not licensed.

POP.012.0001.wm_publish.ToEnable – To enable the "Publish" feature please contact webMethods to obtain a Portal license.

POP.012.0001.wm_securityrealm – {0} Policy Provider Config

POP.012.0001.wm_sessionmonitor – The view "{0}" is not available.

POP.012.0001.wm_shelladmin – A shell with the system name "{0}" already exists.

POP.012.0001.wm_shelleditorE – Cannot clone parent's shell section because it is not a Portal Page.

Explanation Some legacy shells created before Portal 6.2 or customer-created shells may have a raw JSP page assigned to a shell section. Such shells cannot be cloned.

Action Rework the legacy shell to use portal pages instead of JSP pages.

POP.012.0001.wm_skinadmin – A skin with the system name "{0}" already exists.

POP.012.0001.wm_skineditorE – {0} is not a valid skin.

Explanation The specified skin object is not a valid portal skin.

Action Log off from My webMethods and log back in.

POP.012.0001.wm_subscriptionadmin – Please select a user.

POP.012.0001.wm_sysdirsvc – Unable to locate principal: {0}

POP.012.0001.wm_table – Illegal "{0}" property value: "{1}".

POP.012.0001.wm_tabs – Illegal "{0}" property value: "{1}".

POP.012.0001.wm_thumbnailagentE – Error executing external process

Explanation The Thumbnail agent has failed to execute an external process to prepare thumbnails.

Action Use the Install Administration portlet to reinstall the wm_thumbnailagent portlet.

POP.012.0001.wm_tree – Illegal "{0}" property value: "{1}".

POP.012.0001.wm_universalpicker – Cannot resolve portlet ID for "{0}".

POP.012.0001.wm_userhomefolderE – Empty "{0}" property.

Explanation The user ID is either invalid or was not found.

Action Use the User Home folder portlet to refresh the page.

POP.012.0001.wm_userprofilewiring – This portlet has no UI.

POP.012.0001.wm_versionE – Unable to acquire publish portlet controller bean.

Explanation An internal portlet error has occurred.
Action Log off from My webMethods and log back in.

POP.012.0001.wm_webclipE – Cannot clip from "{0}" because it is not an HTTP resource.

Explanation The Webclip portlet has failed to connect to the specified URL and get its HTML content.
Action Check the URL specified for the Webclip portlet.

POP.012.0001.wm_wiringE – Can only wire portlets

Explanation An attempt was made to wire a non-portlet.
Action You can only wire portlets.

POP.012.0001.wm_wsrpproduceradmin – WARNING: Some portlets you have selected do not support WSRP Producer capabilities and cannot be offered. These portlets are not added to the WSRP Producer offered portlets list.

POP.012.0001.wm_xt_dbdirsvc – Directory could not authenticate this user

Explanation The user can't be authentication with given user name and credential.
Action Please make sure the user name and credential provided are valid.

POP.012.0001.wm_xt_dbrole – An error occured executing the SQL query: "{0}". Please type a valid query and try again.

Explanation SQL query is invalid.
Action The log should display the invalid SQL query. Please make sure use a valid SQL query.

POP.012.0001.wm_xt_ldapdirsvc – This directory service does not support creating Users or Groups

Explanation LDAP directory service does not support creating Users or Groups
Action Please contact Administrator if you want to create users or groups.

POP.012.0001.wm_xt_portalrules – Unknown rule thing: {0}

POP.012.0001.wm_xt_rssfeed – age not found: {0}

POP.012.0001.wm_xt_ruleE – The current IDirectoryUser is null.

Explanation Rule matching has failed to load the user.
Action Log off from My webMethods and log back in.

POP.012.0001.wm_xt_samlsecurityservice – The input document contains no elements.

POP.012.0001.wm_xt_shell – Cannot delete "{0}" because it is the default system shell.

POP.012.0001.wm_xt_shortcutE – Unhandled object type found for the wm_xt_shortcut URL property: {0}

Explanation An invalid object type was referenced by a shortcut.
Action Delete the specified object and start over.

POP.012.0001.wm_xt_skinE – Cannot delete "{0}" because it is the default system skin.

Explanation The portal skin specified as the default skin cannot be deleted.
Action Before deleting the skin, use the Skin Administration portlet to specify another skin as the default.

POP.012.0001.wm_xt_ssolink – Failed to generate SAML artifact, artifact is null

POP.012.0001.wm_xtypeviewE – You have not specified an object to display in this portlet.

Explanation The Xtype View portlet does not have a valid target object to display.
Action Update the Xtype View portlet properties and specify a valid DBO to display.

POP.012.0002.wm_caf_task – Cannot connect to webMethods Content Service Platform Server on {0}: {1}. Please make sure the server is available.

Explanation webMethods Content Service Platform is either not running, disconnected, or the environment configuration defined in My webMethods is incorrect.
Action Make sure the CSP server is running; ensure that network connectivity is available; check the CSP environment configuration in My webMethods and verify the connection values.

POP.012.0002.wm_commonsearchbar – Search Context Portlet does not implement ISearchContext interface

Explanation Search Context Portlet does not implement ISearchContext interface
Action Please make sure search context portlet does implement ISearchContext interface

POP.012.0002.wm_commonsearchresults – Search Context Portlet does not implement ISearchContext interface

Explanation Search Context Portlet does not implement ISearchContext interface
Action Please make sure search context portlet does implement ISearchContext interface

POP.012.0002.wm_contentrenderere – Requested content was not found: "{0}"

Explanation The server attempted to download invalid content.
Action Verify that valid content is present at the source location and can be downloaded.

POP.012.0002.wm_dirsearchcontext – Failed to move to next principal in directory services, service={0}, error={1}

Explanation Directory search cannot continue because an exception was thrown when tried to go to next page search. No search result will be return in this case.
Action The log should display which directory service was used for the search, and what kind exception was thrown. Please contact Administrator with those detail log info.

POP.012.0002.wm_discotres_forumview – Can display listing for forum or category only.

POP.012.0002.wm_discotres_forumwizard – Must specify "target" property.

POP.012.0002.wm_discotres_messageview – Can display forum message only.

POP.012.0002.wm_discotres_topicview – Can display listing for forum topic only.

POP.012.0002.wm_jazzy – Not a valid dictionary: "{0}".

POP.012.0002.wm_publish – Please select a type to publish.

POP.012.0002.wm_sessionmonitor – Use this portlet to monitor real-time user activity and send status messages to user(s) via e-mail. Click the appropriate column heading to sort by User Name, Location (Host ID), or Administrator status.

POP.012.0002.wm_shelladmin – A shell with the display name "{0}" already exists.

POP.012.0002.wm_skinadmin – A skin with the display name "{0}" already exists.

POP.012.0002.wm_skineditor – feature not recognized: {0}

POP.012.0002.wm_sysdirsvc – Password attribute is missing

POP.012.0002.wm_systemcontent – <div class="portlet-msg-error"><h3>Attempted redirect to a restricted host. </h3></div>

Explanation My webMethods Server does not allow redirects to arbitrary URLs. In this case the URL was not configured as an acceptable redirect host.

Action Ask the My webMethods Server administrator to modify the Server Redirect WhiteList to allow redirects to this foreign URL.

POP.012.0002.wm_table – One of the following properties must be specified: "{0}"

POP.012.0002.wm_tabs – One of the following properties must be specified: "{0}"

POP.012.0002.wm_tree – One of the following properties must be specified: "{0}"

POP.012.0002.wm_userhomefolder – This user does not have a home folder. Note that the Portal typically does not create a home folder for a user until the user logs in for the first time.

Explanation This user doesn't have a home folder.

Action Note that the Portal typically does not create a home folder for a user until the user logs in for the first time. Please contact Administrator if this problem doesn't go away after that user logged in.

POP.012.0002.wm_versionE – Unable to acquire target resource: {0}

Explanation An internal portlet error has occurred.
Action Log off from My webMethods and log back in.

POP.012.0002.wm_wiki_createnew – Please enter wiki tag name**POP.012.0002.wm_wiringE – {0} is not a normal thing**

Explanation An attempt was made to wire an invalid portlet instance.
Action Delete the specified portlet and locate the correct portlet.

POP.012.0002.wm_xt_dbdirsvc – This directory service does not support creating Users or Groups

Explanation Database directory service does not support creating Users or Groups
Action Please contact Administrator if you want to create users or groups.

POP.012.0002.wm_xt_ldapdirsvc – This directory service does not support deleting Users or Groups

Explanation LDAP directory service does not support creating Users or Groups
Action Please contact Administrator if you want to delete users or groups.

POP.012.0002.wm_xt_portalrules – Unable to resolve user id: {0}**POP.012.0002.wm_xt_rssfeed – refresh interval not found: {0}****POP.012.0002.wm_xt_samlsecurityservice – The SAML artifact is invalid or has expired.****POP.012.0002.wm_xt_shell – Cannot delete "{0}" because it is the base system shell.****POP.012.0002.wm_xt_skinE – Cannot delete "{0}" because it is the base system skin.**

Explanation The portal skin specified as the base system skin cannot be deleted.
Action The base portal skin cannot be deleted because it is used as a parent for all other portal skins.

POP.012.0002.wm_xt_wikiobject – Wiki with such name already exists

POP.012.0003.wm_commonsearchbar – None of the portlet tabs are visible

Explanation This error message is displayed on UI if none of the portlet tabs are visible for search bar

Action Please make sure search options is set.

POP.012.0003.wm_commonsearchresultsE – Failed to parse the max search results setting of "{0}", using default of "{1}"

Explanation The common search code is attempting to build a search query object from a query string that was passed into it. The query string supplied contains an invalid value for the 'maxResults' setting. The warning message is written to the logs and the process continues with the default maxResults value.

Action Make sure the portlet that invokes the API supplies a valid number for the 'maxResults' setting in the search query string. Typically, the end user would not cause this scenario because the wm_commonsearchbar portlet that usually builds the query string validates the maxResults field before allowing the submission of the search form.

POP.012.0003.wm_contentseviceadmin – Cannot start a new content import process because another content import process is currently running.

POP.012.0003.wm_dirsearchcontext – Failed to convert short move to next principal in directory services, service={0}, error={1}

Explanation The internal ID is not a valid integer.

Action The log should display which directory service was used for the search, and what kind exception was thrown. Please contact Administrator with those detail log info.

POP.012.0003.wm_discotres_topicview – Must specify "target" property.

POP.012.0003.wm_jazzy – Cannot load dictionary "{0}" because an I/O error occured.

POP.012.0003.wm_noodle – Cannot load portlet content.

POP.012.0003.wm_ntlmv2authadmin – Field [{0}] is required.

Explanation A necessary form field was not provided.

Action Review the form and fill out all required fields, then resubmit.

POP.012.0003.wm_sessionmonitor – No sessions are available for this Portal Node.

POP.012.0003.wm_shelladminE – The URI "{0}" does not identify a valid shell.

Explanation The shell instance is not a valid portal shell object type.

Action Restart the My webMethods Server to flush the internal caches.

POP.012.0003.wm_skinadminE – The URI "{0}" does not identify a valid skin.

Explanation The skin instance is not a valid portal skin type.

Action Restart My webMethods Server to flush the internal caches.

POP.012.0003.wm_skineditor – property not recognized: {0}

POP.012.0003.wm_subscriptionadmin – Please select a resource.

POP.012.0003.wm_tree – The "{0}" property value must begin with a '{' character.

POP.012.0003.wm_userhomefolder – Use this portlet to locate and browse to a user's personal folder. This can be especially helpful when items become unavailable to the user because of permissions changes and for cleaning house when a user is no longer active.

Explanation This instruction is displayed on UI to explain how this portlet can be used.

Action This is an explanation, not an error message.

POP.012.0003.wm_version – Are you sure you want to set the version as current one?

POP.012.0003.wm_wiki_createnew – Please enter wiki name

POP.012.0003.wm_wiring – You don't have rights to modify the wiring of this item.

Explanation The current user does not have sufficient permissions to modify the wiring properties of this portlet.

Action Contact your My webMethods Server administrator to modify your user permissions.

POP.012.0003.wm_xt_dbdirsvc – This directory service does not support deleting Users or Groups

Explanation Database directory service does not support deleting Users or Groups.

Action Please contact Administrator if you want to delete users or groups.

POP.012.0003.wm_xt_ldapdirsvc – This directory service does not support modifying User or Group memberships

Explanation LDAP directory service does not support modifying Users or Groups

Action Please contact Administrator if you want to create users or groups.

POP.012.0003.wm_xt_portalrules – Deprecated method {0} is not valid on wm_xt_portalrules

POP.012.0003.wm_xt_rssfeedE – Unable to find suitable factory for: {0}

Explanation An RSS feed has failed to parse RSS content.

Action Choose another RSS feed.

POP.012.0003.wm_xt_samlsecurityservice – Unable to locate principal "{0}".

POP.012.0003.wm_xt_shortcut – The Shortcut target resource may not use another Shortcut. URL property: {0}

POP.012.0003.wm_xt_skin – This skin is not available for export.

POP.012.0004.wm_commonsearchbar – Saved Search Name has already been used.

Explanation Saved Search Name has already been used.

Action Please specify a different search name

POP.012.0004.wm_contentserviceadminE – Content service not found: "{0}".

Explanation The content service is no longer valid.

Action If you cannot reconfigure the offending content service by using the Content Service Admin portlet, contact Software AG Global Support for a reset directive.

POP.012.0004.wm_dirsearchcontext – Failed to evaluate expression for object, exp={0}, obj={1}, error={2}

Explanation The expression can't be evaluated.

Action The log should display which expression can't be evaluated, what kind exception was thrown. Please contact Administrator with those detail log info.

POP.012.0004.wm_mws_diagnostics – Performance Service does not support serialization.

Explanation The currently running performance service does not support data serialization, therefore a snapshot cannot be exported.

Action Switch to a performance service that supports serialization.

POP.012.0004.wm_ntlmv2authadmin – Jespa library is required.

Explanation NTLMV2 will not function without the Jespa library.

Action Contact Software AG Global Support for information about downloading the Jespa library from jespa.org.

POP.012.0004.wm_portalaliassearchcontext – One or more of the requested aliases can not be removed**POP.012.0004.wm_shelladminE – Cannot delete "{0}" because it is the default system shell.**

Explanation The default portal shell cannot be deleted.

Action Use the Shell Administration portlet to specify another shell as the default, and then delete the first shell.

POP.012.0004.wm_skineditor – can't resolve input source: {0}**POP.012.0004.wm_tree – Cannot render resource as tree fragment.**

POP.012.0004.wm_wiki_createnew – Please provide the container for wiki

POP.012.0004.wm_xt_dbdirsvc – This directory service does not support modifying User or Group memberships

Explanation Database directory service does not support modifying Users or Groups

Action Please contact Administrator if you want to modify users or groups.

POP.012.0004.wm_xt_ldapdirsvc – No valid "{0}" found for the principal "{1}" from "{2}" directory service. Please check if ID attribute is valid in the Directory Services Configuration

Explanation No principal is found in the LDAP directory service using given name.

Action Please make sure a valid name has been used when searching the principal in the LDAP directory service.

POP.012.0004.wm_xt_portalrules – Web application is not deployed or available {0}. Cannot evaluate {1}

POP.012.0004.wm_xt_samlsecurityservice – Artifact component is longer than maximum length limit, string="{0}", limit={1}

POP.012.0005.wm_contentseviceadminE – Cannot remove default content service.

Explanation The default content service cannot be deleted.

Action My webMethods Server disallows the deletion of the default content service.

POP.012.0005.wm_dirsearchcontext – Failed to create a directory service iterator, dirService={0}, error={1}

Explanation A problem has been encountered while trying to iterate through a directory service.

Action The log should display which which directory service has problem, what kind exception was thrown. Please contact Administrator with those detail log info.

POP.012.0005.wm_jazzy – Please specify text to check.

POP.012.0005.wm_mws_diagnostics – Wrong Import File format.

Explanation The file you are trying to import was exported from a performance service that is different from the one currently running.

Action Check the portlet preferences and make sure the correct performance service is running.

POP.012.0005.wm_ntlmv2authadmin – Configuration test failed. Please double check all the required parameters.

Explanation The specified configuration is not valid. NTLMv2 authentication will not succeed until the parameters are corrected.

Action Review the NTLMv2 configuration and modify parameters as required.

POP.012.0005.wm_portalaliassearchcontext – Unable to add alias "{0}" because an alias with that name already exists.

POP.012.0005.wm_shelladminE – Cannot delete "{0}" because it is the base system shell.

Explanation The shell could not be deleted because it is a parent shell for other deployed shells.

Action My webMethods Server explicitly disallows deletion of the base shell.

POP.012.0005.wm_skineditor – cannot rename "{0}" to "{1}"

POP.012.0005.wm_xt_dbdirsvc – Directory could not load principal data, "{0}" attribute is missing

Explanation The principal data can't be loaded because the specified attribute is missing.

Action The log file should display which attribute is missing. Please contact Administrator to make sure the specific principal is valid and does have the specified attribute.

POP.012.0005.wm_xt_ldapdirsvc – Unable to locate "{0}" directory service. It might have been disabled.

Explanation Can't locate the LDAP directory service.

Action Please make sure the LDAP directory service is enabled.

POP.012.0005.wm_xt_samlsecurityservice – Processing an artifact that was not issued by a cluster but this server is part of a cluster

POP.012.0006.wm_contentseviceadmin – You do not have sufficient rights to modify content service "{1}".

POP.012.0006.wm_dirsearchcontext – Not a valid attribute filter string, string={0}

Explanation The attribute filter string specified is not valid.

Action Please make sure a valid attribute filter string has been provided. The log file should display the invalid value with this error message.

POP.012.0006.wm_portalaliassearchcontext – Unable to update alias "{0}" because an existing alias with that name could not be found.

POP.012.0006.wm_shelladmin – "{0}" does not identify a legacy shell.

POP.012.0006.wm_subscriptionadmin – Please select an owner.

POP.012.0006.wm_xt_dbdirsvc – An error occurred executing the SQL query: "{0}". Please type a valid query and try again.

Explanation The SQL query is invalid.

Action Please make sure the SQL query is valid. Please contact Administrator if you're sure your SQL is valid.

POP.012.0006.wm_xt_samlsecurityservice – Unable to locate server within cluster to validate the SAML artifact, index={0}

POP.012.0007.wm_contentseviceadmin – A content service with a name of "{0}" already exists.

POP.012.0007.wm_dirsearchcontext – Not a valid attribute filter string, missing separator, string={0}

Explanation The specified string doesn't have a valid attribute filter separator.

Action Please make sure a valid attribute filter string has been provided. The log file should display the invalid value with this error message.

POP.012.0007.wm_migration – Congratulations! The Export was successful.

POP.012.0007.wm_mws_diagnostics – Performance Service is not running. No data is available.

Explanation No performance service currently is running, so there is no data to display.

Action Enable a performance service and allow time for it to collect some data, then retry.

POP.012.0007.wm_portalaliassearchcontext – This portlet is not intended to be viewed standalone

POP.012.0007.wm_shelladmin – Cannot convert legacy shell because it uses JSP pages instead of Portal pages.

POP.012.0007.wm_xt_dbdirsvc – {0} is required

Explanation Invalid SQL query because required property is missing.

Action Please make sure SQL query does include the specified required property.

POP.012.0007.wm_xt_samlsecurityservice – The cluster server index contained in the SAML artifact is invalidate for this cluster configuration, index={0}

POP.012.0008.wm_contentseviceadmin – A content service with a root of "{0}" already exists.

POP.012.0008.wm_dirsearchcontext – Unable to locate the attribute provider for URI={0}

Explanation Can't find the principal attribute provider for the specific dir service.

Action The log should display which dir service doesn't have the pricipal attribute provider. Please contact Administrator with those detail log info.

POP.012.0008.wm_migration – Your download should begin shortly.

POP.012.0008.wm_portalaliassearchcontext – Unable to remove alias "{0}" because it is a system alias

POP.012.0008.wm_subscriptionadmin – Please select a group.

POP.012.0008.wm_xt_dbdirsvc – {0} "{1}" is invalid. It is missing required field "{2}"

Explanation Invalid SQL query because required property is missing.

Action Please make sure SQL query does include the specified required property.

POP.012.0009.wm_emailadmin – Use this portlet to configure the mail server settings used by the system when processing e-mail. Specify the mail server (the hostname of the SMTP server) used to route e-mail messages, the SMTP port, the sender name and the sender address (the reply-to address attached to any outgoing notifications).

POP.012.0009.wm_migration – If it does not, click

POP.012.0009.wm_portalaliassearchcontext – Unable to remove alias "{0}" because it does not exist

POP.012.0009.wm_xt_dbdirsvc – {0} "{1}" is invalid. It does not implement case-insensitive lookup for uid attribute

Explanation	The database directory service doesn't support case-insensitive lookup for UID attribute.
Action	The log should display the uid attribute and query info. Please contact Administrator to make sure the database directory service does support case-insensitive lookup for UID attribute.

POP.012.0010.wm_xt_dbdirsvc – Directory could not load principal "{0}"

Explanation	No principal is found in the database directory service using given name.
Action	Please make sure a valid name has been used when searching the principal in the database directory service.

POP.012.0011.wm_migration – Please Note: Internet Explorer might append a '.zip' to the file name. Please remove that '.zip'.

POP.012.0012.wm_migration – Congratulations! The Import was successful.

POP.012.0012.wm_skineditor – You can not set skin parent to itself

POP.012.0014.wm_migration – to see the imported items.

POP.012.0015.wm_migration – May not export resource which does not have a parent

POP.012.0017.wm_securityrealmadmin – Add Resource to Security Realm

POP.012.0019.wm_migration – Export failed : Calender Id/Name Invalid

POP.012.0020.wm_migration – Export failed : Shell Id/Name Invalid

POP.012.0020.wm_securityrealmadmin – Warning: Selecting 'OK' will permanently remove the SecurityRealm from the system.

POP.012.0021.wm_migration – Export failed : Skin Id/Name Invalid

POP.012.0021.wm_securityrealmadmin – Warning: Selecting 'OK' will permanently remove this Container and all its contents from the system.

POP.012.0021.wm_table – Cannot render resource as table.

POP.012.0022.wm_migration – Export failed : Security Realm Id/Name Invalid

POP.012.0023.wm_migration – Exception Closing Stream continuing with processing

POP.012.0024.wm_migration – Export failed : Certificate Id/Name Invalid

POP.012.0025.wm_migration – Export failed : Invalid depth specified {0}

POP.012.0026.wm_migration – Export failed : Invalid URI/alias specified for Export

POP.012.0027.wm_migration – Export did not containing any DLS Objects

POP.012.0028.wm_migration – Export failed : Invalid ID/URI/alias/Name specified for Task Definition Export

POP.012.0029.wm_migration – Export failed : Unable to get the skin archive content for {0}

POP.012.0032.wm_migration – The Descriptor file specified is Invalid

POP.012.0033.wm_migration – Please specify valid target folder path

POP.012.0034.wm_migration – Import Failed for entry :--> {0}

POP.012.0035.wm_migration – No Task Instances found for Task application name {0} and task_type_id {1}

POP.012.0036.wm_migration – Export failed : Invalid ID/URI/alias/Name specified for Task Rules Export

POP.012.0037.wm_migration – Export successful for :--> {0}

POP.012.0038.wm_migration – Failed to get bizPolicy for :--> {0}

POP.012.0039.wm_migration – Failed to get view details for thingID:--> {0}

POP.012.0041.wm_migration – Import functionality is not supported.

POP.012.0055.wm_migration – Import info file {0} is invalid

Explanation The migration portlet was unable to find the control file that lists the My webMethods Server assets to be imported.

Action The user has specified an invalid path and file for the import control file. Check that the specified file exists and has read permission for the current user.

POP.012.0056.wm_migration – Failed to list principals from directory service {0}

Explanation My webMethods Server failed to build a list of principals from the specified directory service. This can happen if the directory service is non-functional and cannot access the underlying directory provider, such as an LDAP server or database.

Action Check the Directory Services Administration portlet to verify that the directory service provider is correctly configured and is enabled. Also check the error logs for directory service provider connection failures.

POP.012.0058.wm_migration – WARNING:Command not found: {0}

Explanation My webMethods Server was unable to locate an internal command by name.
Action This is an internal failure and cannot be remedied by the end-user.

POP.012.0059.wm_migration – Error applying ACL for {0}

Explanation A general error occurred applying an import ACL to a principal.
Action This is a system error that cannot be remedied by the end-user.

POP.012.0060.wm_migration – WARNING: Profile Attribute Import failed: {0}

Explanation A general error occurred when applying the profile attributes to a user during import. The details of the failure will be appended to the error message.
Action This is a system error that cannot be remedied by the end-user.

POP.012.0061.wm_migration – Error importing skin {0}

Explanation A general error occurred when importing a skin. The details of the failure are appended to this message.
Action This is a general message meant to capture any errors that occur during skin import. Refer to the My webMethods Server logs or the additional error text to troubleshoot the specific problem.

POP.012.0062.wm_migration – Error occurred post-processing ACLs

Explanation A general error occurred applying ACLs to imported users, groups, or roles.
Action This is a general message meant to capture any errors that occur when applying ACLs. Refer to the My webMethods Server logs or the additional error text to troubleshoot the specific problem.

POP.012.0063.wm_migration – Rule target not found for {0}.

Explanation The target of a My webMethods Server rule could not be resolved to a specific My webMethods Server object. For example, a shell rule would display this error if it referenced a shell that did not exist.
Action Examine the rule that is reporting the warning to determine the rule target, then confirm that the rule target exists.

POP.012.0065.wm_migration – Unable to register datasource {0}

- Explanation** A general failure occurred importing a datasource.
- Action** This is a general message meant to capture any errors that occur during datasource import. Refer to the My webMethods Server logs or the additional error text to troubleshoot the specific problem.

POP.012.0067.wm_migration – Unable to import saved search for {0}

- Explanation** A general error occurred when importing a set of saved searches for the specified resource (for example, Task List Management or My Inbox).
- Action** This is a general message meant to capture any errors that occur during a saved search import. Refer to the My webMethods Server logs or the additional error text to troubleshoot the specific problem.

POP.012.0068.wm_migration – Unable to locate principal for applying saved searches to {0}

- Explanation** The import includes private saved searches for a user that does not exist in the target My webMethods Server.
- Action** Import or create the missing user and then import the saved searches. Otherwise, this error can be ignored, and the private saved searches will not be imported.

POP.012.0069.wm_migration – Unable to locate principal for {0}

- Explanation** A general warning message that the import references a user, group, or role that could not be located in the target My webMethods Server.
- Action** Make sure any users, groups, or roles used by the asset that generates this warning are imported or created prior to the import.

POP.012.0070.wm_migration – Unable to apply members to {0}

- Explanation** A general error occurred importing the role or group membership.
- Action** This is a general message meant to capture any errors that occur during import. Refer to the My webMethods Server logs or the additional error text to troubleshoot the specific problem.

POP.012.0073.wm_migration – Attempting to import deprecated XType {0}

- Explanation** The import contained a My webMethods Server asset that is no longer supported in My webMethods Server. For example, older versions of wm_xt_savedsearch are no longer supported in 8.0 and generate this warning.
- Action** Because the My webMethods Server asset that generated this error is no longer supported, the message is for informational purposes only.

POP.012.0107.wm_portalcontent – This is not meant to be viewed**POP.012.1001.wm_mws_diagnostics – Cannot find file to parse.**

Explanation Unable to load the file for analysis.

Action Select a file to upload for analysis.

POP.012.1002.wm_mws_diagnostics – Unable to parse the log file; possible wrong log file format.

Explanation The selected log file cannot be parsed. It is possible that the log file is in an incorrect format.

Action Make sure the selected log file is in the appropriate format.

POP.012.1003.wm_mws_diagnostics – Error during XML marshalling. Possible wrong log file format.

Explanation My webMethods Server was unable to parse the xml log file.

Action Select a log file generated by My webMethods Server and upload again.

POP.012.1004.wm_mws_diagnostics – Unable to locate default {0}

Explanation Unable to locate default {0}

Action Check the My webMethods Server instance configuration.

POP.012.1005.wm_mws_diagnostics – The given host: {0} does not exist

Explanation My webMethods Server was not able to reach the remote host.

Action Check the connection settings for the remote host, verify that My webMethods Server has network access to the host, then try again.

POP.012.1006.wm_mws_diagnostics – An error has occurred while downloading the file: {0}

Explanation There was a problem when parsing the file.

Action Check the My webMethods Server logs for more details. See
..\MWS\server\<serverName>\logs

POP.012.1007.wm_mws_diagnostics – An error has occurred while processing the downloaded file: {0}

Explanation There was a problem processing the file.

Action Check the My webMethods Server logs for more details. See
..\MWS\server\<serverName>\logs

POP.012.9000.wm_portal dca – JAX-RPC ServiceException caught: {0}

POP.012.9001.wm_portal dca – Web Service Endpoint URL is Malformed: {0}

POP.012.9002.wm_portal dca – Remote Exception caught: {0}

POP.013.0005E **This item is either inactive or deleted and can not be viewed.**
Explanation The item is deleted but has not yet been purged.
Action Use the Deleted Items Administration portlet to remove the deleted items completely from the user interface.

POP.013.0096 **This was not meant to be viewed**
Explanation An attempt was made to view a My webMethods DBO that does not have a user interface.
Action Do not attempt to view the resource directly. If the resource must be viewed, you must create a renderer that is capable of displaying a user interface for the object.

POP.013.0097 **Datasource {0} not found**
Explanation A portlet is attempting to open a database connection to a data source that is not available on the My webMethods Server.
Action The My webMethods Server administrator should add the missing database connection information using the "Data Sources" portlet.

POP.013.0099 **Unable to construct a secure URL because the MWS secure front end URL is not available**

POP.013.0100 **You must enable JavaScript to use this site.**

POP.015.0001 **No constant was specified for {0}.**
Explanation When the system attempted to parse a My webMethods Server rule, the syntax expected a number and none was found.
Action Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0002	Incorrect number of children. Expected {0} and found {1}.
Explanation	When the system attempted to parse a My webMethods Server rule, the parser expected to find another term and none was found. For instance, the rule might have been a comparison, and only one term was found to compare.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.
POP.015.0003	Both child terms must be numbers.
Explanation	When the system attempted to parse a My webMethods Server rule, the parser expected to find a numeric value or a value that can be converted into a number. None was found.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.
POP.015.0006	Unknown types for comparison: {0} and {1}.
Explanation	When the system attempted to parse a My webMethods Server rule, the parser expected to find valid terms that can be compared to each other but was unable to do so.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.
POP.015.0007	Unable to find object Reference: {0}.
Explanation	When the system attempted to evaluate a My webMethods Server rule, the rule referred to an object reference which could not be located.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.
POP.015.0008	No object Reference name is set.
Explanation	When the system attempted to parse a My webMethods Server rule, the parser expected to find an object identifier and none was found.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.
POP.015.0009	Incorrect number of children. Expected 0 or 1 and found {0}.
Explanation	When the system attempted to parse a My webMethods Server rule, the parser found an unexpected term in the sequence.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0010	Incorrect number of children. Expected 2 or more and found {0}.
Explanation	When the system attempted to parse a My webMethods Server rule, the parser expected to find additional terms and no more were found. For instance, the rule might have been a comparison, and only one term was found to compare.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.
POP.015.0011	Unable to find method to invoke: {0}.
Explanation	When the system attempted to evaluate a My webMethods Server rule, it was unable to invoke the specified method.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.
POP.015.0012	Incorrect number of children. Expected 1 or more and found {0}.
Explanation	When the system attempted to parse a My webMethods Server rule, the parser expected to find additional terms and no more were found. For instance, the rule might have been a comparison, and only one term was found to compare.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.
POP.015.0013	XML Parse Exception. Expected {0} tag and found {1} tag.
Explanation	When the system attempted to parse a My webMethods Server rule, the parser was unable to find the correct XML schema.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.
POP.015.0014	XML Parse Exception while parsing tag {0}.
Explanation	When the system attempted to parse a My webMethods Server rule, the parser was unable to find the correct XML schema.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.
POP.015.0015	Parse Exception at char: {0} {1}.
Explanation	When the system attempted to parse a My webMethods Server rule, the parser encountered a syntax error at the specified position.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.

POP.015.0029	Expected to find matching char "{0}"
Explanation	When the system attempted to parse a My webMethods Server rule, the parser encountered a syntax error at the specified position.
Action	Review the recently modified or uploaded rule to ensure that the syntax is valid.
POP.016.0001	unbalanced end element: expected "{0}" but was "{1}"
Explanation	The optional PrettyPrintingResponseWriter that was enabled manually by the developer to tidy up the rendered html for a page in the web.xml of the webapp, has detected html that was not well-formed.
Action	This should never happen. If this happens a defect in one of the JSF component renderers has not properly closed one of the html tags that was written to the response writer.
POP.016.0002	Portlet Preferences are only available inside the Portlet Context
Explanation	This error message is not used in the current trunk code anymore.
Action	N/A
POP.016.0003	Else control must be preceded directly by If control
Explanation	The CAF view contains an "Else" control without a sibling "If" control.
Action	The developer should change the "Else" control to an "If" control or remove it from the CAF view.
POP.016.0004	Duplicate component ID: {0} (IDs must be unique within naming-container)
Explanation	In a CAF view two controls have the same ID value.
Action	The developer must change the ID of all the controls that are using the same ID to make the control's ID unique.
POP.016.0005	Resource bundle is not available: {0}
Explanation	The specified resource bundle could not be loaded.
Action	The developer should check the resource bundle name to make sure it is correct and make sure the resource bundle file is included in the war file.

- POP.016.0006** **View source is not found: {0}**
Explanation When attempting to load a CAF .view file, the file was not found.
Action The developer should inspect the deployed war file to make sure the missing view file exists.
- POP.016.0007** **Can only switch portlet modes within an action request**
Explanation A portlet attempted to change the portlet mode outside of an action request which is not allowed per the JSR-168 specification.
Action The developer should change the portlet source code and not attempt to change the portlet mode from a code path that does not originate in a portlet action handler.
- POP.016.0008** **Unable to locate control ID {0} in view: {1}**
Explanation There was no control in the view that had the specified control id.
Action The developer should review their application code to make sure the correct control ID is used for the lookup.
- POP.016.0009** **Connection failed to datasource {0}. Caused by: {1}**
Explanation A SQLException was caught while retrieving the data for a RowSetTableContentProvider.
Action Review the server log file to inspect the stack trace of the exception to try to determine the cause of the error.
- POP.016.0010** **Search Results Table Control could not be located**
Explanation The Export Table Button control could not find the table control to use for exporting data.
Action The developer should check the Export For property of the Export Table Button control to make sure it matches the ID of the table control.
- POP.016.0011** **DateInput component value must be a java.util.Date instance**
Explanation The value bound to a Date Input control is not the expected data type.
Action The developer should review the binding expression of the Date Input control to make sure it resolves to a java.util.Date object.

POP.016.0012	DateRangeInput component value must be a com.webmethods.caf.faces.data.object.DateRange instance
Explanation	The value bound to a Date Range Input control is not the expected data type.
Action	The developer should review the binding expression of the Date Range Input control to make sure it resolves to a com.webmethods.caf.faces.data.object.DateRange object.
POP.016.0013	managed-bean-scope value "pageflow" should be changed to "session" for managed-bean "{0}" in application "{1}".
Explanation	A managed-bean declaration in the faces-config.xml is using the deprecated pageflow managed-bean-scope.
Action	The application developer should change the managed-bean-scope value pageflow to session for the managed-bean and then rebuild and redeploy the application.
POP.016.0014	ScheduleInput component value must be a com.webmethods.caf.faces.data.object.Schedule instance
Explanation	The value bound to a Schedule Input control is not the expected data type.
Action	The developer should review the binding expression of the Schedule Input control to make sure it resolves to a com.webmethods.caf.faces.data.object.Schedule object.
POP.016.0015	Interval must be set to calculate previous or next date
Explanation	The Schedule.nextDate(..) or Schedule.previousDate(..) api was called but the schedule does not have an interval configured.
Action	Set the interval on the Schedule object before attempting to calculate the next or previous date.
POP.016.0016	Source table provider does not expose currentRow data and thus cannot be used with PageableTableContentProvider.
Explanation	Source table provider does not expose currentRow data and cannot be used with the PageableTableContentProvider.
Action	Review the configuration of the table content provider to ensure that it is configured properly.
POP.016.0017	Cannot find value for script parameter: {0}
Explanation	The value of a script parameter is null.
Action	The developer should review the source of the script parameter value to determine why it has no value.

POP.016.0018	Cannot find control with id "{1}" for script parameter: {0}
Explanation	The control id specified as the value of a script parameter did not match a control in the view.
Action	The developer should review the script parameter value to ensure it matches an existing control in the view.
POP.016.0019	Cannot create null method binding.
Explanation	An attempt was made to create a method binding object without supplying an expression string.
Action	The developer should review the application code to determine why the expression is null.
POP.016.0020	Cannot create null value binding.
Explanation	An attempt was made to create a value binding object without supplying an expression string.
Action	The developer should review the application code to determine why the expression is null.
POP.016.0021	Cannot convert null locale string.
Explanation	The com.webmethods.caf.faces.convert.ConvertUtils.getLocalFromToString API was called with a null string.
Action	The developer should review the application code to determine why the supplied locale string is null.
POP.016.0022	Portlet control can only be used within a portlet request
Explanation	The Portlet Include control is used in a non-portlet environment.
Action	Do not use the Portlet Include control in a standalone CAF web application.
POP.016.0023	Cannot export from this context or phase
Explanation	An attempt was made to export a file, but a compatible export handler was not found.
Action	You should not get this error.

POP.016.0024	Cannot export control of specified type (id={0},type={1})
Explanation	An attempt was made to export a control but the control specified was not an UIData based control so it cannot be exported.
Action	The developer should review the configuration of the export button to make sure the correct control is being exported.
POP.016.0027	Cannot parse string "{0}" as date (using pattern "{1}").
Explanation	A Date Import control value was a string but it could not be converted to a Date object.
Action	The developer should verify that the value pattern matches the format of the string bound to the control.
POP.016.0029	The "rowVariable" property must be set to use BoundPropertiesSelectedItemGroupProvider.
Explanation	The rowVariable property must be set to use BoundPropertiesSelectedItemGroupProvider.
Action	The developer should review the application code to ensure that the rowVariable property was set.
POP.016.0030	The "rowType" property must be set to use as an IUpdateableTableContentProvider.
Explanation	An attempt was made to add a new row to an updatable table content provider but the row type was not specified.
Action	The developer should review the application code to ensure that the rowType property was set.
POP.016.0031	Cannot create response for {0}.
Explanation	The CAF view handler was unable to get a response writer to render the output.
Action	This should not occur. If this error occurred, there is a catastrophic problem with the server instance. Other errors in the server logs might provide some guidance.
POP.016.0032	AutoRefresh is not supported
Explanation	An attempt was made to autorefresh a LazyNodeTreeContentProvider instance that does not support autorefresh.
Action	The developer should review the application code to remove any calls to the autorefresh API.

POP.016.0033	NeedRefresh is not supported
Explanation	An attempt was made to mark a LazyNodeTreeContentProvider instance as needing a refresh that does not support autorefresh.
Action	The developer should review the application code to remove any calls to the setNeedRefresh API.
POP.016.0034	Child not in parent's children list
Explanation	There is a problem building the structure of a LazyNodeTreeContentProvider instance.
Action	The developer should review the application code that is providing the values to the tree content provider to make sure that the parent/child relationships of the tree data are correct.
POP.016.0035	The "rowIdBinding" property must be set to add or remove rows to or from a SelectableListTableContentProvider. If the table does not need to be selectable, try using a ListTableContentProvider instead.
Explanation	The rowIdBinding property must be set to add or remove rows to or from a SelectableListTableContentProvider. If the table does not need to be selectable, try using a ListTableContentProvider instead.
Action	Set the rowIdBinding property for a SelectableListTableContentProvider. If the table does not need to be selectable, try using a ListTableContentProvider instead.
POP.016.0036	The "rowIdBinding" property must be set to move rows within a SelectableListTableContentProvider.
Explanation	The rowIdBinding property must be set to move rows within a SelectableListTableContentProvider.
Action	This error message is no longer used.
POP.016.0037	Saved Search Not Found: {0}
Explanation	An attempt was made to change the active saved search for a SearchBar control but the target saved search no longer exists.
Action	The end user should refresh the page and select a saved search.
POP.016.0039	cannot load external resource: {0}
Explanation	When loading an app-nav.xml file, there was a reference to an external resource which is not allowed.
Action	The developer should review the app-nav.xml and remove the references to external resources.

POP.016.0040	cannot have more than one root page
Explanation	When loading an app-nav.xml file more than one root page element was detected.
Action	The developer should review the app-nav.xml file to ensure that there is only one root page declared.
POP.016.0042	Error updating control value ("{1}" property of "{0}" control).
Explanation	An error was detected updating a control value. The cause of the error is contain within the message details displayed to the user.
Action	Review the error message details displayed to the user to determine the cause of the error.
POP.016.0043	Toggle target control "{0}" could not be located.
Explanation	The For property in a Toggle control does not resolve to a control.
Action	The application developer should review the application code to ensure that the For property of the toggle control matches the expected target control.
POP.016.0043.details – Check the configuration of the control with this id: {0}	
Explanation	Provides additional details for the "POP.016.0043" error.
Action	See action for the "POP.016.0043" error.
POP.016.0044	Calendar StartDay is not set
Explanation	A calendar control is being rendered but the start day has not been set.
Action	The developer should review the application code to ensure that the calendar has a start day.
POP.016.0045	Invalid value for height property of the "{0}" control.
Explanation	The value of the height property of a Static Row or Static Cell control is not a valid height.
Action	The developer should review the application code to ensure that the height value is a valid unit of measure.
POP.016.0046	Invalid value for width property of the "{0}" control.
Explanation	The value of the width property of a Static Row or Static Cell control is not a valid width.
Action	The developer should review the application code to ensure that the width value is a valid unit of unit of measure.

POP.016.0047 **Can only reset portlet navigation state within an action request**
Explanation Portlet navigation state such as if portlet maximized or minimized can only be changed from an ActionRequest
Action Do not attempt to change the portlet navigate state from the RenderRequest. Use ActionRequest.

POP.016.0048 **The target action was invalid**
Explanation Request portlet action in PortletUrl is invalid and cannot be found
Action Check the name action being requested and determine if it is defined in the portlet Java code

POP.016.0048.detail – The target action was: {0}
Explanation The request portlet action in PortletUrl is invalid and cannot be found
Action Check the name action being request and determine if it is defined in the portlet Java code

POP.016.0049 **The target action was invalid**
Explanation It is possible to invoke actions on the designated portlet via PortletURL. To prevent a malicious user from invoking an arbitrarily action on the portlet, each action defined must be annotated in Java code with @PortletAction annotation which instructs MWS runtime that a given action code is allowed when invoked from a url.
Action Check portlet action definition code, and determine if it has the @PortletAction annotation defined.

POP.016.0049.detail – The target action requires a @PortletAction annotation: {0}
Explanation It is possible to invoke actions on the designated portlet via PortletURL. To prevent malicious user to invoke an arbitrarily action on the portlet, each action defined must be annotated in Java code with @PortletAction annotation which instructs MWS runtime that a given action code is allowed from a url.
Action Check portlet action definition code if it has @PortletAction annotation defined

POP.016.0050 **The target action was invalid**
Explanation To prevent cross-site scripting attacks when malicious script might invoke a porlet action using a URL, the URL used to call a portlet action must obtain and use AXSRF token.
Action When producing a Portlet URL, make sure that the AXSRF token is included in the URL using com.webmethods.caf.portlet.IPortletUrl.setAXSRFT(true) API.

POP.016.0050.detail – The target action "{0}" requires an anti-xsrftoken.

Explanation To prevent cross-site scripting attacks when malicious script might invoke a portlet action using an URL, the URL used to call a portlet action must obtain and use an AXSRF token.

Action When producing a Portlet URL, make sure that an AXSRF token is included in the URL using `com.webmethods.caf.portlet.IPortletUrl.setAXSRFT(true)` API.

POP.016.0051 The target action was invalid

Explanation To prevent cross-site scripting attacks when malicious script might invoke a portlet action using an URL, the URL used to call a portlet action must obtain and use a valid AXSRF token.

Action When producing a Portlet Url, make sure that AXSRF token is included in the URL using `com.webmethods.caf.portlet.IPortletUrl.setAXSRFT(true)` API.

POP.016.0052 The target action was invalid

Explanation The Portlet Url can invoke portlet actions from a URL. If the CAF application does not force use of Annotated Portlet Actions, see CAF documentation for more details, then it is possible to use a JSF binding expression to specify the action to invoke. This error is thrown if binding expression does not resolve to a valid method.

Action Check and correct the binding expression used for portlet action because it does not resolve to a valid action method.

POP.016.0052.detail – The target action was: {0}

Explanation The Portlet Url can invoke portlet actions from a URL. If the CAF application does not force the use of Annotated Portlet Actions, see the CAF documentation for more details, then it is possible to use a JSF binding expression to specify the action to invoke. This error is thrown if binding expression does not resolve to a valid action method.

Action Check and correct binding expression used for portlet action because it does not resolve to a valid action method.

POP.016.0053 The uploaded file type is not allowed as an attachment

Explanation A file uploaded to an Attachment Panel control was a file type that is not allowed.

Action The user should upload a file using one of the file types allowed for attachments.

POP.016.0054 **The uploaded file type is not allowed as an attachment. The allowed file extensions are: {0}**

Explanation A user tried to upload a file to an Attachment Panel that has a file extension that is not allowed as an attachment.

Action The user should only upload files that are allowed as attachments.

POP.016.0055 **The uploaded file is too large. The maximum file size is: {0}**

Explanation A user tried to upload a file to an Attachment Panel that is larger than the allowed size of an attachment.

Action The user should upload a smaller file.

POP.017.0001 **Task is locked and you may not update it at this time. Please wait till task is unlocked**

Explanation Task instance is locked in following cases: when a task is being updated, or when task events and assignments are being processed. To ensure state consistency when a task is locked, no other updates to the task are possible (though the task can still be read and searched on). Typically lock time is very short (similar to database transaction).

Action Enable MWS "task" logging category Debug logging and investigate timing and duration of task locks.

POP.017.0003 **Task auditing level is not sufficient to rollback task state**

Explanation Task state should be kept in task audit in order for task rollback to function. If task state is not present in the audit, rollback is not possible

Action Make sure to audit full task state. Task audit options can be controlled as properties on task definition object. You must login as sysadmin, browse to /task.storage, navigate to "Task Definitions" and open properties of task type, then change audit settings.

POP.017.0004 **You don't have permissions to queue new task**

Explanation User does not have a task functional privilege to queue task of specific task type.

Action Configure Permissions on the user to enable "Queue Task" functional privilege.

POP.017.0007 **You don't have permissions to view this task**

Explanation The current user does not have permission to view task information.

Prior to MWS_7.1.3_Fix9, the mechanism to determine if a user had permission to view a task required the user to hold "view task data" permission. With the introduction of MWS_7.1.3_Fix9, the user/role must have this permission and also must be present in the "assigned to" or "delegated to" lists. Under these conditions, if the user holds only "view task data" permission, permission to view the task is denied and this error occurs.

A task client option, `task.base.permission`, is available to apply the simpler "view task data" permission even if `MWS_7.1.3_Fix9` is applied. For more information, see the Task Engine Optional Settings section in the PDF publication, Task Engine User's Guide.

Action If your system does not have `MWS_7.1.3_Fix9` applied, make sure that the user holds "view task data" permission.

If your system has `MWS_7.1.3_Fix9` applied, make sure the user holds "view task data" permission and is also present on the "assigned to" or "delegated to" lists. Also, see the explanatory text above concerning the `task.base.permission` option.

POP.017.0008 You don't have permissions to view task data

Explanation Current User does not have permissions to view task business data.

Action Configure Permissions on the user to enable "View Task Data" functional privilege.

POP.017.0009 You don't have permissions to view audit log

Explanation Current user does not have permissions to view task audit.

Action Configure Permissions on the user to enable "View Task Audit" functional privilege.

POP.017.0010 You don't have permissions to accept this task

Explanation Current user does not have permissions to accept task instance.

Action Configure Permissions on the user to enable "Accept Task" functional privilege.

POP.017.0011 You don't have permissions to accept other users on this task

Explanation Current user does not have permissions to accept task instance.

Action Configure Permissions on the user to enable "Accept Task" functional privilege.

POP.017.0012 You don't have permissions to assign this task

Explanation Current user does not have permissions to assign task instance.

Action Configure Permissions on the user to enable "Assign Task" functional privilege.

POP.017.0013 You don't have permissions to rollback this task

Explanation Current user does not have permissions to rollback task instance.

Action Configure Permissions on the user to enable "Rollback Task" functional privilege.

POP.017.0014	You don't have permissions to modify task data
Explanation	Current user does not have permissions to update task business data.
Action	Configure Permissions on the user to enable "Modify Task Data" functional privilege.
POP.017.0015	You don't have permissions to modify task info
Explanation	Current user does not have permissions to update generic task info properties.
Action	Configure Permissions on the user to enable "Modify Task Info" functional privilege.
POP.017.0016	Task Type ID is not valid {0}
Explanation	This error is reported when attempting to queue a task and specifying an invalid task type ID (from APIs).
Action	Check if the specified Task Type is deployed to MWS.
POP.017.0017	Task ID is not valid {0}
Explanation	This error is reported when attempting to operate on invalid task.
Action	Check if the specified task is still available in MWS, it may already be deleted.
POP.017.0018	Unable to find task client bean: {0}
Explanation	During task searches, assignments and events evaluation, Task Engine needs access to task generated beans which are part of task application. This error is reported when it fails to instantiate these beans.
Action	Check if task application was deployed properly, and if there are any errors in the install.log, re-install task application.
POP.017.0020	Cannot obtain FacesContext for Task application: {0}
Explanation	Indicates that task application was not properly deployed.
Action	Investigate any possible errors during task application installation. Re-install task application.
POP.017.0022	You don't have permissions to delegate this task
Explanation	Current user does not have permissions to delegate task instance.
Action	Configure Permissions on the user to enable "Delegate Task" functional privilege.

POP.017.0024	You don't have permissions to complete this task
Explanation	Current user does not have permissions to complete task instance.
Action	Configure Permissions on the user to enable "Complete Task" functional privilege.
POP.017.0025	You don't have permissions to cancel this task
Explanation	Current user does not have permissions to cancel task instance.
Action	Configure Permissions on the user to enable "Cancel Task" functional privilege.
POP.017.0026	You don't have permissions to suspend this task
Explanation	Current user does not have permissions to suspend task instance.
Action	Configure Permissions on the user to enable "Suspend Task" functional privilege.
POP.017.0027	You don't have permissions to resume this task
Explanation	Current user does not have permissions to resume task instance.
Action	Configure Permissions on the user to enable "Resume Task" functional privilege.
POP.017.0028	User {0} not found
Explanation	This error is reported when using Task Engine API from WmTaskClient IS package and "impersonated" user name is not valid.
Action	Check the name of the "impersonated" user in the Task Engine API calls.
POP.017.0029	You can not rollback non-Active task
Explanation	Only tasks in "Active" state can be rolled back.
Action	Set the status of the task to "Active".
POP.017.0030	You can not queue new task. Task type is not enabled
Explanation	Task Type, which the task is about to be queued for, is disabled.
Action	Enable the Task Type from the Task Engine Administration.
POP.017.0032	Connecting user does not have Impersonate Users privilege
Explanation	When using remote Task Engine API (from WmTaskClient IS package or web services), the API allows to impersonate user so task operations are performed on behalf of a different user. This is useful because typically passwords of end user are not known, so 'sysadmin' account should be used for remote APIs invocation. It is possible to connect to remote API using a non-sysadmin account, but in this case the user account needs to have "Impersonate Users for Remote Clients" Task Engine privilege.
Action	Grant the user the "Impersonate Users for Remote Clients" Task Engine privilege.

POP.017.0033	You can not update non-Active task: {1}
Explanation	Tasks whose status is "Completed", "Cancelled" or "Expired" cannot be updated.
Action	Administrator can set task status back to "Active".
POP.017.0034	You can not rollback non-Active task
Explanation	Tasks whose status is "Completed", "Cancelled" or "Expired" cannot be rolled back.
Action	Administrator can set task status back to "Active".
POP.017.0037	Task is out of date, please refresh
Explanation	Task Engine updates from UI or API implement "optimistic locking" to ensure that data being updated is up-to-date. This error is reported if task data being passed in from UI or API call is not the latest.
Action	UI needs to be refreshed to reload up-to-date task data. When using Task Engine APIs task data needs to be re-loaded.
POP.017.0039	You don't have permissions to add task comments
Explanation	Current user does not have permissions to add comments to task instance.
Action	Configure Permissions on the user to enable "Add Comment" functional privilege.
POP.017.0040	You don't have permissions to delete task comments
Explanation	Current user does not have permissions to delete comments from task instance.
Action	Configure Permissions on the user to enable "Delete Comments" functional privilege.
POP.017.0041	You don't have permissions to delete other user's task comments
Explanation	Current user does not have permissions to delete comments from task instance which were created by other people.
Action	Configure Permissions on the user to enable "Delete Other People's Comment" functional privilege.
POP.017.0042	You don't have permissions to create new collaboration tasks
Explanation	Current user does not have permissions to queue collaboration task of another task.
Action	Configure Permissions on the user to enable "Queue Collaboration Tasks" functional privilege.

POP.017.0045	You can not update suspended task
Explanation	If current task status is "Suspended", it can only be updated back to "Active" status. No other updates are allowed.
Action	Administrator can set task status back to "Active".
POP.017.0051	You can not set the parent task ID using the self task ID
Explanation	This error is reported when attempting to update an existing task via APIs and set its "parentTaskID" property to the ID of the task itself.
Action	Check "parentTaskID" being set.
POP.017.0052	You can not set the parent task ID using non integer value
Explanation	This error is reported when updating or queuing a new task via API and "parentTaskID" property is not a valid task ID value.
Action	Check value of "parentTaskID" being used.
POP.017.0053	You can not set the parent task ID using invalid task ID
Explanation	This error is reported when updating or queuing a new task via API and "parentTaskID" property is not a valid task ID value.
Action	Check "parentTaskID" value used.
POP.017.0061	You can not set the delegated to or delegated from list if their size does not match
Explanation	When updating task delegation via APIs both "delegatedFromList" and "delegatedToList" list values should contain the same number of items.
Action	Check "delegatedFromList" and "delegatedToList" values used.
POP.017.0071	Task indexTableDis is null or emptys
Explanation	Invalid task index configuration is provided from taskDefinition.xml file.
Action	Re-create task index configuration by re-configuring task index fields in Designer.
POP.017.0072	Task indexTableDis format is invalid: {0}
Explanation	Invalid task index configuration is supplied in taskDefinition.xml file.
Action	Re-create task index configuration by re-configuring task index fields in Designer.

POP.017.0090	Failed to invoke IS service: {0}
Explanation	Failed to invoke IS service when executing task decision table assignment. The reason could be that related rule project is not deployed on the corresponding IS server, or that IS service parameters, such as project name, rule set name, etc. are invalid.
Action	Please make sure the related rule project is deployed and correct IS service parameters are used when configuring task decision table assignment.
POP.017.0100	You cannot accept this task because it was already accepted by another user.
POP.017.0101	You must accept a task before updating it.
POP.017.0102	Unhandled Exception during task change processing
POP.017.0103	Unable to deliver task completion to Process runtime (PRT)
POP.017.0104	Process runtime (PRT) task step failed
POP.017.0105	Process runtime (PRT) task step was cancelled
POP.017.0106	Indexed task searches are not available in Preview Server. Please use standalone MWS server instead
POP.017.0107	Cannot process rule [{0}] for Task [{1}] due to [{2}]
POP.017.0200	{0} ({1})
POP.018.0001	IView object does not support indexed properties
Explanation	A binding expression attempted to resolve a property of an IView object by index. This operation is not supported.
Action	The ViewPropertyResolver does not support lookup of a property by index. Change the application code so that it does not attempt an unsupported operation.

POP.018.0002	IView object is readonly
Explanation	A binding expression attempted to update a property of an IView object which is not supported.
Action	The ViewPropertyResolver does not support update of an IView property. Change the application code so that it does not attempt an unsupported operation.
POP.018.0003.DirSearchProvider – Failed to move to next principal in directory services, service={0}, error={1}	
Explanation	An unexpected exception occurred during the directory service search API call.
Action	Review the server log files for the stack trace of the cause.
POP.018.0004.DirSearchProvider – Failed to evaluate expression for object, exp={0}, obj={1}, error={2}	
Explanation	An unexpected error was caught while evaluating the value of the property used to sort the principal.
Action	Review the server log files for the stack trace of the cause.
POP.018.0005.DirSearchProvider – Failed to create a directory service iterator, dirService={0}, error={1}	
Explanation	An unexpected error was caught while creating a directory service iterator.
Action	Review the server log files for the stack trace of the cause.
POP.018.0006.DirSearchProvider – Unable to locate the attribute provider for URI={0}	
Explanation	While filtering a principal by an attribute, the provider of the attribute was not located.
Action	Check the server to make sure the logged provider URI resolves to a attribute provider.
POP.018.0007.AttachmentsProvider – Attachments container id is not valid: {0}	
Explanation	The attachments provider for an Attachment Panel control does not have a valid container id for read/write of attachment files.
Action	The developer should review the application code to ensure the attachment provider container id is a valid folder id or alias.
POP.018.0008.AttachmentsProvider – Specified attachments container id is not a container: {0}	
Explanation	The attachments provider for an Attachment Panel control does not have a valid container id for read/write of attachment files.
Action	The developer should review the application code to verify that the attachment provider container id is a valid folder id or alias.

POP.018.0009.AttachmentsProvider – Attachment id has not been specified

Explanation The attachments provider updateAttachment or removeAttachment API was called but the attachment id parameter was null.

Action The developer should review the application code to verify that the API calls are passing an attachment id value that is not null.

POP.018.0010.AttachmentsProvider – FileItem has not been specified

Explanation The attachments provider addAttachment or updateAttachment API was called but the fileItem parameter was null.

Action The developer should review the application code to verify that the API calls are passing a fileItem value that is not null.

POP.018.0011.AttachmentsProvider – The specified attachment id is not a child of the attachment container: {0}

Explanation The attachments provider updateAttachment or removeAttachment API was called with an attachment id that is not a child of the attachments container.

Action The developer should review the application code to verify that the API calls are passing an attachment id value that is a child of the attachments folder.

POP.019.0001 Unable to convert data type "{0}" to "{1}"

Explanation The system failed to convert an object from the source data type to the destination data type.

Action Review the error stack trace in the My webMethods Server server logs to determine the cause.

POP.019.0002 Cannot load "{0}" because it is not an HTTP resource

Explanation The html parser failed to load the resource.

Action Inspect the error stack trace in the My webMethods Server server logs to determine the cause.

POP.101.0001.com.softwareag.caf.shared.diagnostics – The directory does not exist

Explanation The specified directory is not found.

Action Provide a valid directory location as a parameter.

POP.101.0002.com.softwareag.caf.shared.diagnostics – The specified path is not a valid directory

Explanation The specified location is not a directory.
Action Provide a valid directory location as a parameter.

POP.101.0006.com.softwareag.caf.shared.diagnostics – Unsupported report type

Explanation A report was generated by an AeventProcessor which is not supported.
Action Use an existing report or add the new one to the list of supported reports in LogAnalyzer.java

POP.101.0007.com.softwareag.caf.shared.diagnostics – An error occurs while adding a root element to the analyzed log file

Explanation A root element cannot be added to the analyzed log file.
Action Check the log file for any discrepancies.

POP.101.0010.com.softwareag.caf.shared.diagnostics – Either one or both of the provided documents are null

Explanation The method load() was not invoked beforehand or it was invoked using incorrect parameters.
Action You need to call the load() method before you continue using EnvDiff API.

POP.101.0011.com.softwareag.caf.shared.diagnostics – At least one argument has to differ from null

Explanation This invocation is not supported.
Action Contact Software AG Global Support.

POP.101.0012.com.softwareag.caf.shared.diagnostics – Cannot read the following file: {0}

Explanation The file cannot be read.
Action Check file and directory permissions; if the file is accessed over a network, check network connectivity.

POP.101.0013.com.softwareag.caf.shared.diagnostics – No output channel found

Explanation This behavior is not supported.
Action Contact Software AG Global Support.

POP.101.0014.com.softwareag.caf.shared.diagnostics – Input directory or file does not exist: {0}

Explanation The specified directory or file does not exist.
Action Specify an existing directory or file.

POP.101.0015.com.softwareag.caf.shared.diagnostics – The system variable %1\$s and the %2\$s parameter are not set

Explanation The required system properties are incorrect or are not set.
Action Set the system variables using proper values. For more information, see the product documentation.

POP.101.0016.com.softwareag.caf.shared.diagnostics – Similarity level must be in the following range: 0-100

Explanation Similarity level is not set to a valid value.
Action Set a similarity level between 0 and 100.

POP.101.0017.com.softwareag.caf.shared.diagnostics – Java artifact mapping file does not exist in: {0}; cannot generate {1} report.

Explanation A Java artifact mapping file cannot be found. The report cannot be generated.
Action Specify a valid Java artifact mapping XML file. Use the --java-artifact-mapping parameter to specify the path.

POP.101.0018.com.softwareag.caf.shared.diagnostics – File not found in: {0}

Explanation The specified file does not exist.
Action Specify an existing file.

POP.101.0019.com.softwareag.caf.shared.diagnostics – File name is null

Explanation The name of the file was not set in java artifact mapping XML file and this is a unsupported scenario.
Action Contact Software AG Global Support.

POP.101.0020.com.softwareag.caf.shared.diagnostics – Product ID is null.

Explanation The product ID was not set in a Java artifact mapping XML file; this is a unsupported scenario.
Action Contact Software AG Global Support.

POP.101.0021.com.softwareag.caf.shared.diagnostics – Database configuration is not specified

Explanation This error occurs when the file mws.db.xml is not specified or cannot be found.
Action Specify a valid mws.db.xml file.

POP.102.0001.com.webmethods.caf.shared.bpm.common – This configuration is missing important parameters! Session and node id are mandatory!

Explanation This error occurs: 1) when a node id is not provided when trying to search for a content type, or 2) when a session is not opened.
Action For 1), select a node that the searched content is associated with. For 2), verify that the CSP server is running, properly configured, and connected.

POP.102.0002.com.webmethods.caf.shared.bpm.common – Illegal connection parameters

Explanation An attempt has been made to connect to the CSP server without providing username/password values.
Action In My webMethods, check the Environment entries for the "wm_csp_task" portlet. If they are empty, next check the Global Environment entries. If no values are provided, specify a value for "csp/default/username" and "csp/default/password" entries. In general, the user name and password are specified in the Global Environment entries, except in cases when you have multiple CSP servers and want different portlets to connect to different servers. Otherwise, the Global Environment values are inherited by all portlets.

POP.102.0003.com.webmethods.caf.shared.bpm.common – The provided session is null!

Explanation The session which is the client primary access point to the CSP server is not instantiated.
Action Verify that the username and password are correct in the CSP configuration in My webMethods Server.

POP.102.0005.com.webmethods.caf.shared.bpm.common – Error while marshalling!

Explanation This error indicates that a low-level communication problem exists between Task Engine and webMethods Content Service Platform.
Action Stop and restart the Task Engine and the CSP server and try again. If the problem persists, contact Software AG Global Support.

POP.102.0006.com.webmethods.caf.shared.bpm.common – Error while unmarshaling result!

Explanation This error indicates that a low-level communication problem exists between Task Engine and webMethods Content Service Platform.

Action Stop and restart the Task Engine and the CSP server and try again. If the problem persists, contact Software AG Global Support.

POP.102.0008.com.webmethods.caf.shared.bpm.common – This configuration is missing important parameters! Content id is mandatory!

Explanation The Content ID value is not set.

Action Verify that a Content ID is set for this provider; ensure that the binding expression is correctly configured.

POP.102.0009.com.webmethods.caf.shared.bpm.common – No retrieval module initiated! Please set proper session!

Explanation The CSP session is not set for the provider; the retrieval module cannot be initiated.

Action Verify that a session is set for this provider; ensure that the binding expression is correctly configured.

PerformanceMonitorDefaultviewView.errorMessage.unsupportedPerfServiceImpl – Currently enabled performance service implementation {0} does not support analysis. Cannot proceed.

WSC.001.0002 Failed to bind to endPoint: {0} and interface: {1}

WSC.001.0004 Context instance does not allow access of inbound SOAP request interceptors

WSC.001.0005 Context instance does not allow access of outbound SOAP request interceptors

WSC.001.0006 Exception occurred while invoking webservice: {0}. Details: {1}

WSC.001.0007 Unable to connect to web service at {0}

WSC.002.0002	SAML artifact not found in request
WSC.002.0006	Invalid SAML assertion issue instant.
WSC.002.0009	SAML Assertion is missing the subject name
WSC.002.0010	SAML Assertion has an invalid authentication method, method: {0}
WSC.002.0011	SAML authentication statement was not found.
WSC.002.0012	SAML Assertion has an invalid statement format
WSC.002.0013	SAML Assertion has an invalid assertion id.
WSC.002.0014	The credential type is not supported: {0}
WSC.002.0015	User failed to authenticate with basic auth: {0}
WSC.002.0016	There was an error connecting to webMethods Integration Server. The connection might be automatically restored.
error.exception	Exception
error.msg.noDebug	The requested URL {0} resulted in an error.
error.msg.withDebug	– The requested URL {0} resulted in an error in {1}.
error.unknown	Unknown

form.user.passwordexpire.title – Password Expires At

http.status.400	Bad Request
http.status.401	Unauthorized
http.status.402	Payment Required
http.status.403	Forbidden
http.status.404	Not Found
http.status.405	Method Not Allowed
http.status.406	Not Acceptable
http.status.407	Proxy Authentication Required
http.status.408	Request Time-out
http.status.409	Conflict
http.status.410	Gone
http.status.411	Length Required
http.status.412	Precondition Failed

http.status.413	Request Entity Too Large
http.status.414	Request-URI Too Large
http.status.415	Unsupported Media Type
http.status.416	Requested range not satisfiable
http.status.417	Expectation Failed
http.status.422	Unprocessable Entity (WebDAV)
http.status.423	Locked (WebDAV)
http.status.424	Failed Dependency (WebDAV)
http.status.500	Internal Server Error
http.status.501	Not Implemented
http.status.502	Bad Gateway
http.status.503	Service Unavailable
http.status.504	Gateway Time-out
http.status.505	HTTP Version not supported

- http.status.507 Insufficient Storage (WebDAV)

- http.status.510 Not Extended

- install.fixes.1 Installing update XML component {0}

- install.fixes.2 Failed to install update XML component {0}

- install.fixes.3 Failed to delete update XML component {0}

- install.fixes.4 Failed to process all update XML components

- install.fixes.5 Completed processing of update XML components

password.complexity.description – Password must contain at least 6 characters, contain upper and lower case characters and at least one number or special character.

password.mix.case Your password must contain upper and lower case characters

password.special.char – Your password must contain at least one number or special character

password.too.short Your password must contain at least 6 characters

task.update.nochange – Task {0} does not have any changes to update.

text.copyright.custom.year –

Software AG Copyright
Copyright © {0} - {1} Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors. </p></td></tr><tr><td> The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners. Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at http://documentation.softwareag.com/legal/. </td></tr><tr><td> </td></tr><tr><td> This software may include portions of third-party products. For third-party copyright notices and license terms, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". This document is part of the product documentation, located at <a

<http://documentation.softwareag.com/legal> and/or in the root installation directory of the licensed product(s).

text.copyright.default –

Software AG Copyright
<p>Copyright © 2006 - 2014 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.</p> <p>The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners. Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at http://documentation.softwareag.com/legal.</p> <p>This software may include portions of third-party products. For third-party copyright notices and license terms, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". This document is part of the product documentation, located at http://documentation.softwareag.com/legal and/or in the root installation directory of the licensed product(s).</p>

18

OSGi Messages

OGICRE0003	Expected String [2] but its length is "{0}"
Explanation	There is a problem with the user-defined credentials that are passed to the server in order to authenticate the user before creating MBeanServerConnection.
Action	The expected user-defined credentials are a username and password. Provide these security credentials only.
OGICRE0004	Authentication fails with user "{0}"
Explanation	There is a problem with authentication of the current user.
Action	Check the provided username and password.
OGICRE0015	"{0}" property is not set, cannot proceed.
Explanation	JMX authentication configuration property " <code>com.softwareag.platform.startup.jmx.auth.config</code> " is not set, cannot proceed.
Action	Set the JMX authentication configuration property " <code>com.softwareag.platform.startup.jmx.auth.config</code> " and provide a valid value to it.
OGICRE0016	JAAS login configuration property "{0}" is not set, cannot proceed.
Explanation	During the startup routine, the OSGi platform attempts to prepare JAAS configuration. The platform expects that the " <code>com.softwareag.platform.startup.jaas.login.config</code> " property is set and points to a valid JAAS configuration file. The error message is displayed when the property is not available at platform startup.
Action	Ensure that the " <code>com.softwareag.platform.startup.jaas.login.config</code> " is set and points to a valid JAAS configuration file.

OGICRE0019	System property "java.io.tmpdir" is not set or empty, cannot ensure that the directory exists.
Explanation	The 'java.io.tmpdir' property is expected to be set by the JVM. The platform startup cannot ensure that the directory pointed by this property is available if the property is empty or undefined.
Action	If you want to use a temporary file directory, make sure that it exists and is set to the JVM.
OGICRE0021	Java temporary directory pointed by "java.io.tmpdir" system property: "{0}" does not exist and cannot be created.
Explanation	The java temporary directory pointed by the "java.io.tmpdir" JVM property does not exist and automatic creation of this directory failed.
Action	Ensure that the directory pointed by the "java.io.tmpdir" JVM property exists.
OGICRI0008	Standard JMX Management is used.
Explanation	Custom authentication is not enabled. The standard JMX Management is used.
Action	If you want to enable custom authentication, set a System property with name "com.softwareag.jmx.noCustomAuthentication" and set it to "false".
OGICRI0013	Using JMX authentication configuration: "{0}"
Explanation	Information about the value of "com.softwareag.platform.startup.jmx.auth.config" JMX authentication configuration parameter.
Action	None.
OGICRI0014	Using JAAS login configuration: "{0}".
Explanation	Information about the value of "java.security.auth.login.config" JAAS configuration parameter.
Action	None.
OGICRI0022	Successfully created Java temporary directory: {0}
Explanation	Directory pointed by "java.io.tmpdir" system property did not exist and the OSGi platform startup bundle created it automatically.
Action	None.

OGICRW0017	Configured JMX RMI Agent port: "{0}" is not valid; default port "{1}" will be used instead.
Explanation	The platform startup routine is attempting to initialize the JMX RMI Agent using the port configured in the "com.softwareag.platform.startup.jmx.rmi.agent.port" key. The property is not a valid number.
Action	Set a valid port number in the "com.softwareag.platform.startup.jmx.rmi.agent.port" key.
OGICRW0020	The parent directory of the Java temporary directory ({0}) is not write enabled.
Explanation	Cannot write into the parent directory of the temporary directory pointed by the "java.io.tmpdir" system property. Automatic creation of the temporary directory will fail.
Action	Ensure that the user who started the platform has permissions to write into the parent directory of the temporary files directory.
OGICRW0023	The parent directory of the Java temporary directory pointed by "java.io.tmpdir" system property: "{0}" does not exist and cannot be created.
Explanation	When the OSGi platform is started it attempts to ensure that the temporary files directory (denoted by the "java.io.tmpdir" system property) exists. If the directory does not exist on the file system, the OSGi platform startup bundle attempts to create it. This message is displayed when the OSGi platform startup bundle fails to create the parent directory of the temporary files directory.
Action	Ensure that the directory pointed by the "java.io.tmpdir" JVM property exists.
OGIMIGE0002	ERROR: Missing file in source installation - {0}
Explanation	This message is displayed when no source file is found.
Action	Check if the file exists and is readable for the user.
OGIMIGE0003	ERROR: Missing file in destination installation - {0}
Explanation	This message is displayed when no destination file is found under path: <installdir_new_version>/profiles<some_profile>/configuration/com.softwareag.platform.config.propsloader/
Action	Check if the file exists and is readable for the user.
OGIMIGE0004	ERROR: Backup failed for destination file - {0}
Explanation	The file is backed up before merging . Losing this file might be crucial.
Action	Make sure that the file can be written in the parent directory.

OGIMIGE0006	ERROR: Error while opening file - {0}
Explanation	In order to migrate a file its content should be read. This error occurs because the file could not be opened properly.
Action	Make sure the file is not locked (for example, the file may be already opened by another program).
OGIMIGE0007	ERROR: Result configuration file in destination installation was not found - {0}
Explanation	After merging, the result is either a new file, or an updated overwritten destination file.
Action	Please make sure the file exists and is readable for the user.
OGIMIGE0010	ERROR: More than one in the destination installation - {0} were found under {1}
Explanation	This message is displayed when more than one destination file is found. This is not expected if a clean destination installation is done.
Action	Check the log file to see where are the files. Remove the unneeded files and leave only one file - the default one.
OGIMIGE0013	ERROR: Loading source properties layout configuration failed. The source file is: from file {0}
Explanation	When we load our properties we also load the comments and blank lines the file contains.
Action	Make sure that you source file is a valid java poprerty file and it is not corrupted.
OGIMIGE0014	ERROR: Cannot identify version of product {0}. Cannot find any locally installed products in the specified installation directory: {1}
Explanation	The migration application attempted to identify the version of a locally installed product with the given product prop file name (without the .prop suffix), but no locally installed products were found in the specified installation directory.
Action	Specify the source version of the product when prompted to.
OGIMIGE0015	ERROR: Cannot identify version of product {0}. Cannot find this product in the list of locally installed products in the specified installation directory: {1}
Explanation	The migration application attempted to identify the version of a locally installed product with the given product prop file name (without the .prop suffix), but such locally installed product was not found in the specified installation directory.
Action	Specify the source version of the product when prompted to.

OGIMIGE0018	ERROR: Storing result properties configuration layout failed.
Explanation	The property file with all the properties and their comments failed on the saving step.
Action	Check the file access permissions of your target installation.
OGIMIGE0019	ERROR: JAAS configuration {0} does not exist.
Explanation	The JAAS configuration file is missing and the migration cannot proceed.
Action	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0020	ERROR: JAAS configuration {0} is not a file.
Explanation	The JAAS configuration file is not a valid file and the migration cannot proceed.
Action	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0021	ERROR: Destination JAAS configuration {0} does not exist.
Explanation	The JAAS configuration file is missing and the migration cannot proceed.
Action	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0022	ERROR: Destination JAAS configuration {0} is not a file.
Explanation	The destination JAAS configuration file is not a valid file and the migration cannot proceed.
Action	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0023	ERROR: Backup failed for destination JAAS configuration file.
Explanation	Creating a backup of the original file was not successful and it is unsafe for the migration to continue.
Action	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0024	ERROR: Error parsing source JAAS configuration
Explanation	An error is found in the source JAAS configuration and the migration cannot proceed.
Action	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0025	ERROR: Error parsing destination JAAS configuration
Explanation	Migration of the JAAS configuration was not successful. An error was found in the destination JAAS configuration and the migration cannot proceed.
Action	Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0026	ERROR: Error saving destination JAAS configuration.
Explanation	An error occurred while storing the migrated JAAS configuration and the migration cannot proceed.
Action	Migration for JAAS configuration was not successful. Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0028	ERROR: Source server.xml configuration {0} does not exist.
Explanation	The server.xml file could not be migrated because the file does not exist.
Action	Check if the source server.xml file exists and is readable for the user.
OGIMIGE0029	ERROR: Source server.xml configuration {0} is not a file.
Explanation	The server.xml is not a proper file.
Action	Check the server.xml file.
OGIMIGE0030	ERROR: Parsing server.xml file {0}.
Explanation	The server.xml file is not a valid XML file.
Action	Check the server.xml file.
OGIMIGE0031	ERROR: Reading server.xml file {0}.
Explanation	The server.xml file could not be read properly.
Action	Check the server.xml file.
OGIMIGE0032	ERROR: Parser Configuration server.xml file {0}.
Explanation	Parser error occurs when parsing the server.xml file.
Action	Check the server.xml file.

OGIMIGE0033	ERROR: Backup file {0}.
Explanation	The file could not be backed up successfully.
Action	Check the source location and target location paths and files.
OGIMIGE0034	ERROR: Reading file {0}.
Explanation	The error occurs because the file could not be read properly.
Action	Check the source location and target location paths,files, and permissions.
OGIMIGE0035	ERROR: Writing file {0}.
Explanation	The error occurs because the file could not be written properly.
Action	Check the source location and target location paths,files, and permissions.
OGIMIGE0036	ERROR: Create/Update file {0}.
Explanation	The error occurs because the file could not be created or updated properly.
Action	Check the source location and target location paths,files, and permissions.
OGIMIGE0042	ERROR: Configuration migration finished with failure(s).
Explanation	Migration failed for the server.xml, web.xml, and config.xml, *.jks files.
Action	Check the detailed error messages displayed by the migration tool.
OGIMIGE0048	ERROR: Cannot identify version of product {0}. The product installation under {1} does not contain any build modules for the current installer platform: {0}
Explanation	The migration application attempted to identify the version of a locally installed product, but the local product is targeting a different installer platform (operating system and architecture) and the product information could not be loaded.
Action	Specify the source version of the product when prompted to.
OGIMIGE0049	ERROR: Cannot parse version of product {0}. The product version of {1} does not have valid syntax. Expecting a version in the format <major>.<minor>.<micro>.<fixnum>.<buildnum>.
Explanation	The migration application attempted to identify the source version of a locally installed product but the product version did not have the expected format.
Action	Specify the source version of the product when prompted to.

OGIMIGE0052	ERROR: User repository file does not exist in the expected location: {0}
Explanation	Migration for common/conf entries was not successful. The users.txt file was not found in the expected location.
Action	Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0053	ERROR: Error reading user repository file: {0}
Explanation	Migration for common/conf entries was not successful. The users.txt file could not be read from the expected location.
Action	Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0054	ERROR: User repository file version cannot be retrieved: {0}
Explanation	Migration for common/conf entries was not successful. The users.txt file was not migrated. An unexpected error occurred during the retrieval of the users.txt file version.
Action	Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0055	ERROR: User repository version is not compatible. Required minimal version is: {0}, found version is: {1}. Manual steps are required.
Explanation	Migration for common/conf entries was not successful. The users.txt file cannot be migrated if the files in both locations are not with compatible versions.
Action	Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0056	ERROR: User repository version could not be retrieved: {0}
Explanation	Migration for common/conf entries was not successful. An unexpected error occurred during the compatibility check of the users.txt file. The users.txt file must be migrated manually.
Action	Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0058	ERROR: Source user repository file does not exist: {0}
Explanation	Migration for common/conf entries was not successful. The source user repository file users.txt cannot be found in the specified location.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0059	ERROR: Destination user repository file does not exist: {0}
Explanation	Migration for common/conf entries was not successful. The destination user repository file users.txt cannot be found in the specified location.
Action	Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0060	ERROR: Source user repository file could not be copied to destination.
Explanation	Migration for common/conf entries was not successful. The source user repository file users.txt cannot be copied to destination due to an unexpected error.
Action	Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0066	ERROR: Missing source SSH configuration file {0}
Explanation	Migration of the SSH configuration was not successful. The source file with the SSH configuration is not found and the migration cannot proceed.
Action	Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0067	ERROR: Error reading source SSH configuration file {0}
Explanation	Migration of the SSH configuration was not successful. An error occurred while reading the source SSH configuration file and the migration cannot proceed.
Action	Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0068	ERROR: Missing destination SSH configuration file {0}
Explanation	Migration for SSH configuration was not successful. The destination configuration file for the SSH configuration cannot be found and the migration cannot proceed.
Action	Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0069	ERROR: Error backing up destination SSH configuration file {0}
Explanation	Migration of the SSH configuration was not successful. An error occurred while trying to backup the original destination SSH configuration file and the migration cannot proceed.
Action	Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0071	ERROR: Destination SSH config file not found {0}
Explanation	Migration for the SSH configuration was not successful. The destination SSH config file was not found and the migration cannot proceed.
Action	Refer to the upgrade documentation and execute the required manual steps.

OGIMIGE0072	ERROR: Error storing migrated SSH configuration {0}
Explanation	Migration of the SSH configuration was not successful. An error occurred while storing the migrated SSH configuration and the migration cannot proceed.
Action	Refer to the upgrade documentation and execute the required manual steps.
OGIMIGE0073	Invalid source installation directory specified: {0}. No {1} subdirectory is present, this directory is required for the {2} migration to proceed.
Explanation	The migration application requires the specified product subdirectory to be available in the source installation in order to proceed, but the directory was not found. This can happen if the product, for which the migration is executed is not available in the source installation directory.
Action	Make sure that the specified source installation contains the product that is being migrated.
OGIMIGE0081	In file {0} Keystore/Truststore file referenced from HTTPS Connector in attribute {1} that can not be found, creating a valid HTTPS configuration not possible.
Explanation	The server.xml file contains a Keystore/Truststore configuration (keystoreFile=truststoreFile=), pointing to a file that cannot be found. Migrating this would lead in an unusable HTTPS configuration.
Action	In your profile check the file /tomcat/conf/server.xml and the properties keystoreFile="TheKeystoreFilename" truststoreFile="TheTrustStoreFileName". Also check that the file(s) TheKeystoreFilename/TheTrustStoreFileName are existing and valid keystore/truststore files or reference the delivered default one: keystoreFile='C:\SAG32\profiles\CIP\configuration\tomcat\conf\localhost_dont_use_in_production.jks' and start the migration again.
OGIMIGE0083	ERROR: Backup file cannot be created - invalid value for destination file passed.
Explanation	While trying to create a backup of the original file, an invalid original file was passed.
Action	Check the log for more details.
OGIMIGE0084	Cannot identify installer platform for specified installation directory: {0}. Reason: Cannot read installation metadata file: {1}
Explanation	The migration application needs to verify that the source installation is created for the same operating system and architecture as the destination installation. This is done by inspecting the installation metadata located under install/products directory in the installation. If the installation metadata is missing or corrupt, or the process does not have read permissions for the specified file, the platform identification will fail and the migration cannot proceed.
Action	Make sure that the specified installation directory contains proper installation metadata (install/products directory containing installer property files for installed products) and the process has the correct privileges to read it.

OGIMIGE0086	Failed to read file "{0}".
Explanation	The platform migration utility could not read the specified file.
Action	Make sure the file exists and the user executing the migration is authorized to read it.
OGIMIGE0087	Failed to close file stream "{0}".
Explanation	An I/O error occurred while closing the file stream.
Action	Make sure the file exists and the user executing the migration is authorized to read it.
OGIMIGE0089	An invalid path property "{0}" was found in file "{1}". Path should not be null or empty.
Explanation	A path property sent for transformation has a null or empty value. Transformation cannot proceed with an invalid argument.
Action	Ensure that the property referenced in the given file has a valid path value.
OGIMIGE0092	The path "{0}" is referenced in file "{1}"; it should be available as "{2}", but could not be found. Hence the path cannot be migrated.
Explanation	The path transformer has discovered that a path referenced in a file in the source installation points to a file inside the source installation. The file does not exist and the configuration is invalid.
Action	Ensure that the path referenced in the specified file points to a valid file on the file system.
OGIMIGE0095	The absolute path "{0}" referenced in file "{1}" does not exist on the file system.
Explanation	The path transformer has discovered that a path referenced in a file in the source installation points to a file outside the source installation. The file does not exist and the configuration is invalid.
Action	Ensure that the path referenced in the specified file points to a valid file on the file system.
OGIMIGE0097	Could not determine original installation location for "{0}".
Explanation	The path transformer failed to determine the original source installation root directory, which is required in order for the transformer to function properly.
Action	Make sure the migration source directory contains a "profiles" folder with at least one valid profile inside.

OGIMIGE0098 **The original source directory "{0}" exists on this file system but the current migration is using "{1}" as a source. Path transformation is not supported.**

Explanation Path transformer determined that the migration source directory is different from the original source installation root directory (which could be the case when you are migrating from a zip file or from a mapped/mounted directory). However, the original source installation root directory exists on this file system but it is not used as a migration source directory. This is not a supported path transformation scenario as the system may not reliably validate the transformed paths.

Action If the original source installation directory is available on the same file system it should be used directly as a migration source directory.

OGIMIGE0099 **The target directory "{0}" must be the same as the installation root directory "{1}".**

Explanation The target directory in the migrated profile config.ini file is different from the migration target directory. The target installation is corrupted.

Action Make sure that the migration target directory is not moved or tampered with.

OGIMIGE0102 **Failed to copy transformed file path from "{0}" to "{1}".**

Explanation Path transformer transformed a file path from the migration source directory to the migration target directory. The file copy operation failed.

Action Make sure that the user executing the migration is able to physically copy the source file to the destination.

OGIMIGE0103 **An invalid URL property "{0}" was found in file "{1}". URL should not be null or empty.**

Explanation A URL property sent for transformation has a null or empty value. Transformation cannot proceed with an invalid argument.

Action Ensure that the property referenced in the given file has a valid URL value.

OGIMIGE0107 **Source installation directory ({0}) uses "{1}" platform, while destination installation directory ({2}) uses "{3}".**

Explanation The migration cannot proceed if the source and destination installation platforms are different.

Action Make sure the source and destination directories contain installations of one and the same platform.

OGIMIGW0005	WARNING: File could not be deleted - {0}.
Explanation	An error occurred while deleting incompatible destination file. This is a warning message because deleting this file should not be crucial for the functionality of the application.
Action	Delete this file manually as it may cause future conflicts.
OGIMIGW0008	WARNING: Referenced file was found in the source installation but was not found in the destination installation: "{0}" . Check if the file was migrated and if not migrate it manually.
Explanation	Configurations could have properties with values that contain paths to files. During migration these paths could become invalid. To prevent the migration of such paths that make the configurations unusable, a check is done if the file exists in the new installation. This warning shows that the file was successfully located in the source installation, but was missing from the destination.
Action	Check if the path from the configuration is valid after the migration. If the path is not valid, migrate the file manually and edit the path if needed.
OGIMIGW0009	WARNING: Referenced file was not found in the destination system: "{0}"
Explanation	Configurations could have properties with values that contain paths to files. During migration these paths could become invalid. To prevent the migration of such paths that make the configurations unusable, a check is done if the file exists in the new installation.
Action	Check if the path from the configuration is valid after the migration. If the path is not valid, migrate the file manually and edit the path if needed.
OGIMIGW0011	WARNING: Property value could not be transformed properly.
Explanation	When a migration is done, some properties require special transformation for their values. For this reason special transformer classes are used. This message is shown when there is a problem with finding the class, the class could not be instantiated or the class is not a valid Transformer class. This could lead to invalid property values.
Action	Check the value of the migrated property.
OGIMIGW0012	WARNING: Installer client jar not available, falling back on custom installer metadata parser.
Explanation	Migration framework did not find a required jar for reading the installation metadata, it will attempt to read the metadata by parsing the prop file instead.
Action	No action is required.

OGIMIGW0016 **WARNING: Properties for transformation were not loaded.This might make your configuration unusable.**

Explanation We are using special files that map properties which need some kind of transformation for their value or key. In order to use them we have to load them from a file. This step has failed.

Action Contact Software AG global support.

OGIMIGW0017 **WARNING: Transformer class was not found for the following property:**

Explanation We allow custom property transformation which is done via a class. The loading of this class has failed. One or more properties were not transformed correctly.

Action Contact Software AG global support.

OGIMIGW0027 **WARNING: Some runtime componets were not enabled in the source configuration - {0}. Migration exits successfully.**

Explanation Some runtime componets like JMX, SSH are not enabled in the source configuration. The migartion will not migrate any data from these source configurations.

Action If you want to disable the component explicitly please do so by changing the port property in the connector in the destination installation.

OGIMIGW0037 **WARNING: Error on read file {0}.**

Explanation The error occurs because the file could not be read properly.

Action Check the source location and target location paths,files, and permissions.

OGIMIGW0038 **WARNING: Error on write file {0}.**

Explanation The error occurs because the file could not be written properly.

Action Check the source location and target location paths,files, and permissions.

OGIMIGW0051 **WARNING: Using the default 'localhost_dont_use_in_production.jks' file in file {0} property name {1}, because the file referenced in the older version could not be found. Change the file specified in the property.**

Explanation The specified property in the specified properties file points to the default .jks keystore file, because the keystore file referenced in the older version could not be found.

Action Change the property to point to a valid existing production .jks keystore file.

OGIMIGW0065	WARNING: SSH port is not set in source configuration {0}. Migration exits successfully.
Explanation	SSH port is not set in source configuration so there is nothing to migrate.
Action	SSH port is not set in configuration and nothing is done. If this is not the case, refer to the upgrade documentation and execute the required manual steps.
OGIMIGW0104	Value for JAAS configuration in config.ini could not be processed.
Explanation	The JAAS configuration modifications will be made to the original JAAS configuration located in the profile folder.
Action	Define an absolute path to the current location of the JAAS configuration to be migrated or move it in the profile configuration folder.

19 Platform Manager Messages

SPMCFCE0012	Properties serializer supports only instances of java.util.Properties
Explanation	The user is trying to use a Properties serializer on an inappropriate object type.
Action	Use proper serializer for your object.
SPMCFCE0023	There is no registered ConfigurationSerializer under runtimeComponentId {0} and configurationTypeId {1}
Explanation	No registered ConfigurationSerializer exists under the entered runtimeComponentId and configurationTypeId.
Action	Register a ConfigurationSerializer under the entered runtimeComponentId and configurationTypeId.
SPMCFCE0026	ConfigurationManager should be registered with the runtimeComponentId and configurationTypeId properties.
Explanation	ConfigurationManager should be registered with the runtimeComponentId and configurationTypeId properties. They cannot be null.
Action	Register ConfigurationManager and set values for the runtimeComponentId and configurationTypeId properties.
SPMCFCE0030	Error occurred during serialization/deserialization.
Explanation	Error occurred during serialization/deserialization.
Action	Check for user permissions and hardware failures and try again.

SPMCFCE0048	ConfigurationSerializer SPI could not be found for RuntimeComponentId "{0}" and ConfigurationTypeId "{1}" .
Explanation	Platform Manager could not find a registered ConfigurationSerializer that can handle ConfigurationInstances with these properties.
Action	Register a ConfigurationSerializer SPI implementation that can handle ConfigurationInstances with these properties.
SPMCFCE0049	Configuration is not available for this component.
Explanation	The component requires a configuration to function properly.
Action	Set the configuration for this component.
SPMCFCI0000	Port Settings
Explanation	PortSettingsConfigurationType Display Name
Action	None.
SPMCFCI0001	Listener ports configuration
Explanation	PortSettingsConfigurationType description.
Action	None.
SPMCFCI0019	The keystore truststore settings cannot be null.
Explanation	The keystore truststore settings cannot be set to null.
Action	Provide a valid keystore truststore setting.
SPMCFCI0028	There can be only one primary pool defined in the JDBC configuration.
Explanation	There can be only one primary pool defined in the JDBC configuration.
Action	Specify only one pool with the primary as true.
SPMCFGE0000	The configuration type argument is not set.
Explanation	The configuration type argument is not set.
Action	Set the configuration type argument.

SPMCFGE0001	The configuration ID doesn't exist.
Explanation	The configuration ID doesn't exist.
Action	Provide a configuration.
SPMCFGE0002	A Configuration instance with ID = {0} does not exist.
Explanation	A Configuration instance with the provided ID does not exist.
Action	Use the ID of an existing Configuration instance.
SPMCFGE0003	Loaded configuration cannot be null.
Explanation	The requested configuration cannot be null.
Action	Provide valid runtimeComponent, configurationInstance, and configurationStatus.
SPMCFGE0004	The Configuration Manager Service is not set.
Explanation	The Configuration Manager Service is not set.
Action	Set the Configuration Manager Service.
SPMCFGE0005	The component ID or configurationType ID is wrong.
Explanation	The component ID or configurationType argument ID is wrong.
Action	Use an appropriate component ID or configurationType ID.
SPMCFGE0006	Configuration is not available for this component.
Explanation	This component needs configuration in order to function.
Action	Set the configuration for this component.
SPMCFGE0007	ConfigurationSerializer SPI could not be found for RuntimeComponentId "{0}" and ConfigurationTypeId "{1}" .
Explanation	Platform Manager did not find registered ConfigurationSerializer that can handle ConfigurationInstances with these properties.
Action	Register ConfigurationSerializer SPI implementation that can handle ConfigurationInstances with these properties.

SPMCFGE0008	Id cannot be null.
Explanation	When creating a configuration instance, the id argument cannot be null.
Action	Provide a non-null id argument.
SPMCFGE0009	ConfigurationTypeId cannot be null.
Explanation	When creating a configuration instance, the ConfigurationTypeId argument cannot be null.
Action	Provide a non-null id argument.
SPMCFGE0010	DisplayName cannot be null.
Explanation	When creating a configuration instance, the displayName argument cannot be null.
Action	Provide a non-null id argument.
SPMCFGE0011	The component to be updated is null.
Explanation	The runtime component to be updated cannot be null.
Action	Provide a non-null runtime component.
SPMCFGE0012	Protocol value cannot be changed.
Explanation	The protocol value for an existing port configuration cannot be changed.
Action	Retry the operation without changing the protocol.
SPMCFGE0013	Create command is not supported.
Explanation	Create configuration command is not supported by this configuration manager.
Action	Check the logs.
SPMCFGE0020	ConfigurationService is not set.
Explanation	ConfigurationService is not set.
Action	Register a ConfigurationService.
SPMCFGE0021	New configuration is null.
Explanation	The configuration sent for validation is null.
Action	Send a valid configuration that is not null.

SPMCFGE0022	Delete command is not supported
Explanation	Delete configuration command is not supported by this configuration manager.
Action	Check the logs.
SPMCFGE0023	The new configuration to be validated can not be null.
Explanation	The new configuration to be validated can not be null.
Action	Send a valid configuration that is not null for validation.
SPMCFGE0024	Duplicate truststore aliases in the existing instances.
Explanation	Duplicate truststore aliases are present in the existing instances.
Action	Use a unique truststore alias.
SPMCFGE0025	Duplicate truststore aliases are present in the existing instances.
Explanation	Duplicate truststore aliases are present in the existing instances.
Action	Use a unique truststore alias.
SPMCFGE0026	Duplicate keystore aliases in existing instances.
Explanation	Duplicate keystore alias is present in the existing instances.
Action	Use a unique keystore alias.
SPMCFGE0027	Duplicate keystore alias is present in existing instances.
Explanation	Duplicate keystore alias is present in the existing instances.
Action	Use a unique keystore alias.
SPMCFGE0028	The file location provided in the keystore could not be found.
Explanation	The file location provided in the keystore could not be found.
Action	The file location provided in the keystore configuration must point to an existing file. Use an existing file location.
SPMCFGE0040	The keystore location information is missing.
Explanation	The keystore location information is missing in the new configuration.
Action	Use a valid keystore location that points to an existing file.

SPMCFGE0041	The keystore location information is either null or empty. It should point to an existing file.
Explanation	The keystore location information is either null or empty. It should point to an existing file.
Action	The keystore location should point to an existing file.
SPMCFGE0042	An exception occurred when trying to get the existing aliases.
Explanation	The PlatformManagerException exception occurred when trying to get the existing aliases.
Action	You need to correct the existing configuration instances with valid aliases.
SPMCFGE0043	An exception occurred when trying to get the existing aliases.
Explanation	The IOException exception occurred when trying to get the existing aliases.
Action	Provide a valid runtime ID and configuration type ID to the validator.
SPMCFGE0049	Configuration of type Common-JDBC is null.
Explanation	Configuration object for Common-JDBC is null.
Action	Specify the valid configuration object for Common-JDBC.
SPMCFGE0051	Duplicate alias for Jdbc Pool is found.
Explanation	Alias for Jdbc Pool is not unique. This is not a valid configuration.
Action	Specify a unique Jdbc Pool alias.
SPMCFGE0053	There can be only one pool with primary as true.
Explanation	There is more than one pool defined as primary. This is not valid.
Action	Specify only one pool with primary as true.
SPMCFGE0055	JDBC Pool information is not available. Specify valid JDBC Pool Settings.
Explanation	JDBC Pool information is not available in the JDBC Settings Configuration Object. This is not valid.
Action	Specify valid JDBC Pool Settings.

SPMCFGE0058	An exception occurred when trying to get the existing aliases.
Explanation	The PlatformManagerException exception occurred when trying to get the existing aliases.
Action	You need to correct the existing configuration instances with valid JDBC pool aliases.
SPMCFGE0059	The JDBC connection failed.
Explanation	The JDBC connection failed because it was invalid.
Action	Specify valid JDBC connection data.
SPMCFGE0060	Failed to close a valid JDBC connection.
Explanation	Failed to close a valid JDBC connection.
Action	Contact your system administrator.
SPMCFGE0061	Password verification failed.
Explanation	The password provided to load the certificate is incorrect.
Action	You need to provide a valid password and try again.
SPMCFGE0065	Configuration Instance "{0}" does not exist.
Explanation	Configuration Instances should be backed up by existing source.
Action	Make sure this particular Configuration Instance is declared correctly.
SPMCFGE0066	Configuration Instance "{0}" is not a valid URL.
Explanation	Configuration Instance "{0}" should be backed up by valid URL source.
Action	Make sure this particular Configuration Instance is declared correctly.
SPMCFGE0067	Unknown property name "{0}".
Explanation	The property is not recognized.
Action	Make sure this particular Configuration Instance is declared correctly.
SPMCFGE0068	The specified port number is already in use. The port number is bound to an application outside the current installation of Software AG Suite of products.
Explanation	The specified port number is already in use. The port number is bound to an application outside the current installation of Software AG Suite of products.
Action	Specify a different port number or shut down the component that is running on this port.

SPMCFGE0071	The value {0} cannot be used. A non-negative number is expected.
Explanation	The specified value must not be a negative number.
Action	Specify a non-negative number.
SPMCFGE0073	The value of the Threadpool Min parameter cannot be equal to or more than the value for the Threadpool Max parameter.
Explanation	The value of the Threadpool Min parameter cannot be equal to or more than the value of the Threadpool Max parameter.
Action	Change the configuration to make the value of the Threadpool Max parameter more than the value of the Threadpool Min parameter.
SPMCFGE0078	The configuration contains duplicate log file name entries.
Explanation	Duplicate log file names exist in the log configuration appendices.
Action	Make sure each log file name in the log configuration is unique.
SPMCFGE0079	Log file name {0} already exists.
Explanation	The specified log file name exists in another runtime component's log configuration.
Action	Make sure each file name is unique across runtime components.
SPMCFGE0080	Not enough disk space.
Explanation	The disk partition free space is less than 10Mb.
Action	Make sure the disk partition has enough free space.
SPMCFGE0081	The user does not have privileges to perform file operations. Check the current security policy.
Explanation	The user performing the file operation does not have the proper privileges necessary to create or write to a log file.
Action	Make sure the user has adequate privileges to perform the operation.
SPMCFGE0082	Error creating temp file in {0}. Make sure the specified directory is valid.
Explanation	The log configuration validation failed because the specified log directory is not valid or does not exist.
Action	Make sure the specified log directory is valid.

SPMCFGE0084	The "from" or "to" email address is not correct.
Explanation	In Platform Manager, during validation of sending a test email, if the "from" or "to" email address is not correct, this error is thrown.
Action	Ensure that the "from" or "to" email address is correct, and try again.
SPMCFGE0086	Not able to connect to the SMTP server {0}.
Explanation	In Platform Manager, the socket connection is not able to connect to the SMTP server with the given credentials.
Action	Ensure the server is running and the specified credentials are correct.
SPMCFGE0088	Unable to send a test mail to the recipient {1} using the SMTP server {0}.
Explanation	In Platform Manager, an error occurs when sending an email to the recipient.
Action	The email ID is non-existent. Enter a valid email ID and try again.
SPMCFGE0090	An exception occurred when trying to get the existing aliases.
Explanation	The IOException exception occurred when trying to get the existing aliases.
Action	Provide a valid runtime ID and configuration type ID to the validator.
SPMCFGE0091	An exception occurred when trying to get the existing JDBC pools defined as primary.
Explanation	The PlatformManagerException exception occurred when trying to get the existing JDBC pools defined as primary.
Action	You need to correct the existing configuration instances with only one JDBC pool as primary.
SPMCFGE0092	An exception occurred when trying to get the existing JDBC pools defined as primary.
Explanation	The IOException exception occurred when trying to get the existing JDBC pools defined as primary.
Action	Provide a valid runtime ID and configuration type ID to the validator.
SPMCFGE0093	No value was specified for the Protocol parameter.
Explanation	No value was specified for the Protocol parameter.
Action	Specify a value for the Protocol parameter.

SPMCFGE0094	The keystore truststore setting is empty.
Explanation	The keystore truststore setting does not contain any fields.
Action	Provide either the keystore, truststore or extended properties.
SPMCFGE0095	The keystore truststore setting does not contain any element.
Explanation	The keystore truststore setting should either have the keystore, the truststore, or the extended properties, which is missing.
Action	Add the keystore, the truststore, or the extended properties to the keystore truststore setting.
SPMCFGE0096	There can be only one primary pool defined in the JDBC configuration.
Explanation	There can be only one primary pool defined in the JDBC configuration.
Action	Specify only one pool with the primary as true.
SPMCFGE0097	The JDBC Pool name is not unique.
Explanation	The JDBC Pool name is not unique.
Action	Specify a unique JDBC Pool name.
SPMCFGE0098	The JDBC driver class should not be null when the database server type is Custom.
Explanation	The JDBC driver class should not be null when the database server type is Custom.
Action	Specify the JDBC Driver class if the database server type is Custom.
SPMCFGE0099	The database server host should not be null when the database server type is non-custom and the URL is not specified.
Explanation	The database server host should not be null when the database server type is non-custom and the URL is not specified.
Action	Specify the hostname for the database server when the server type is non-custom and the database URL is not specified.
SPMCFGE0100	The database server port number should not be null when the database server type is non-custom and the URL is not specified.
Explanation	The database server port number should not be null when the database server type is non-custom and the URL is not specified.
Action	Specify the port number for the database server when the server type is non-custom and the database URL is not specified.

SPMCFGE0101	The database server SID should not be null when the database server type is Oracle and the URL is not specified.
Explanation	The database server SID should not be null when the database server type is Oracle and the URL is not specified.
Action	Specify the Oracle SID when the database server type is Oracle and the database URL is not specified.
SPMCFGE0102	The database server's database name should not be null when the database server type is non-Oracle and the URL is not specified.
Explanation	The database server's database name should not be null when the database server type is non-Oracle and the URL is not specified.
Action	Specify the database name when the database server type is non-Oracle and the URL is not specified.
SPMCFGE0103	An error occurred while getting either the runtime components or configuration instances using the configuration or inventory service.
Explanation	An error occurred while getting either the runtime components or configuration instances using the configuration or inventory service.
Action	Retry the action.
SPMCFGE0105	Configuration instance and its configuration manager must have the same configuration type.
Explanation	Configuration instance and its configuration manager must have the same configuration type.
Action	Check the type of the provided configuration instance.
SPMCFGE0106	Not able to connect to the SMTP server(s) {0} with the given credentials and also not able to send a test mail to the recipient using the SMTP server(s) {1}.
Explanation	In Platform Manager, the socket connection is not able to connect to the SMTP server with the given credentials (if provided). Also, a test mail to the recipient using the SMTP server is also not sent.
Action	Ensure the server is running and the server credentials entered are correct. Also, enter the correct email address and try again.

SPMCFGE0109	The license file can not be empty.
Explanation	In Platform Manager, when an empty license file is uploaded, this message is seen.
Action	You need to ensure to upload a license file that is not empty.
SPMCFGE0110	The truststore location information is missing.
Explanation	The truststore location information is missing in the new configuration.
Action	Use a valid truststore location that points to an existing file.
SPMCFGE0111	The truststore location information is either null or empty. It should point to an existing file.
Explanation	The truststore location information is either null or empty. It should point to an existing file.
Action	The truststore location should point to an existing file.
SPMCFGE0112	The specified port is already bound by configuration instance {0} of runtime {1} and is enabled.
Explanation	The specified port is already bound by configuration instance {0} of runtime {1} and is enabled.
Action	Change the port number and retry.
SPMCFGE0114	The specified Bind Address value of {0} is invalid.
Explanation	The value of {0} is invalid for Bind Address.
Action	Specify a valid bind address and retry.
SPMCFGE0115	The specified port {0} is already in use by another configuration instance.
Explanation	The specified port {0} is already in use by configuration instance {1} of runtime {2}.
Action	Change the port number and retry.
SPMCFGE0117	The specified port number {0} is already in use.
Explanation	The specified port number {0} is already in use. The port number is bound to an application outside the current installation of Software AG Suite of products.
Action	Specify a different port number or shut down the component that is running on this port.

SPMCFGE0120	License file location is not specified in License Location Manager.
Explanation	The location of the license file is not specified in the License Location Manager.
Action	Specify a valid license file location in License Location Manger before loading the License instance.
SPMCFGE0121	The configured license is not valid for this product : {0}
Explanation	The product code in the license file does not match with the product installed.
Action	Contact your system administrator or Software AG Global Support.
SPMCFGE0122	The configured license is not valid for this version : {0}
Explanation	The product version in the license file does not match with the product installed version.
Action	Contact your system administrator or Software AG Support.
SPMCFGE0125	The provided port alias {0} already exists.
Explanation	The provided port alias {0} already exists for this runtime component.
Action	Provide a unique port alias for the runtime component.
SPMCFGE0126	The specified port alias {0} differs from the existing port alias {1}
Explanation	The specified port alias {0} differs from the existing port alias {1}
Action	Do not change the port alias when you execute an update operation.
SPMCFGE0127	The JDBC Pool alias cannot be changed once it is created.
Explanation	While updating a JDBC Pool, the alias was modified. The alias for the JDBC Pool must not change after creating the pool.
Action	Specify the same JDBC Pool alias in the request, or remove it.
SPMCFGE0128	Configuration of type COMMON-JNDI is null.
Explanation	The configuration object for COMMON-JNDI is null.
Action	Specify the valid configuration object for COMMON-JNDI.

SPMCFGE0129	Configuration of type COMMON-JNDI should have one JNDI element.
Explanation	A configuration of type COMMON-JNDI should have one JNDI element.
Action	Provide one JNDI element for this configuration.
SPMCFGE0130	Configuration of type COMMON-JNDI should have JNDI element with valid alias.
Explanation	A configuration of type COMMON-JNDI should have a JNDI element with a valid alias.
Action	Provide URL friendly alias for the JNDI element.
SPMCFGE0131	Configuration of type COMMON-JNDI should have JNDI element with unique alias.
Explanation	A configuration of type COMMON-JNDI should have a JNDI element with a unique alias.
Action	Provide a unique alias for the JNDI element.
SPMCFGE0132	Error occurred while retrieving the JNDI configuration instances.
Explanation	An error occurred while retrieving the JNDI configuration instances.
SPMCFGE0133	Provide a URL for the specified JNDI provider type.
Explanation	The URL for the specified JNDI provider type is missing.
Action	Specify the URL for the specified JNDI provider type.
SPMCFGE0134	Provide Initial Context Factory for the specified JNDI provider type.
Explanation	The specified JNDI provider type does not have an Initial Context Factory.
Action	Specify the Initial Context Factory for the specified JNDI provider type.
SPMCFGE0135	DbFunctional alias was not found.
Explanation	A DbFunctional alias with the specified alias value could not be found.
Action	Check if a DbFunctional alias with the provided alias value is available.
SPMCFGE0136	Element value is not set.
Explanation	The value of an integral element has not been set.
Action	Ensure that the specified data contains valid values for all required elements.

SPMCFGE0137	Invalid DbFunctional alias.
Explanation	The provided DbFunctional alias is invalid.
Action	Check the provided DbFunctional alias for invalid characters.
SPMCFGE0138	Duplicate DbFunctional alias.
Explanation	The provided alias already exists.
Action	Provide a new alias.
SPMCFGE0139	Invalid Pool alias.
Explanation	The provided Pool alias is invalid.
Action	Provide a new Pool alias.
SPMCFGE0140	Problem detected while trying to read/write DbFunctional alias data.
Explanation	The read/write operation failed.
Action	Check if the DbFunctional alias data file is available.
SPMCFGE0141	Configuration of type COMMON-JMS should have JMS element with valid alias.
Explanation	A configuration of type COMMON-JMS should have a JMS element with a valid alias.
Action	Specify a URL friendly alias for the JMS element.
SPMCFGE0142	Configuration of type COMMON-JMS is null.
Explanation	Configuration object for COMMON-JMS is null.
Action	Specify the valid configuration object for COMMON-JMS.
SPMCFGE0143	Configuration of type COMMON-JMS should have a JMS element.
Explanation	A configuration of type COMMON-JMS should have a JMS element.
Action	Specify a JMS element for this configuration.
SPMCFGE0144	Provide URL for the specified JMS provider type.
Explanation	The URL for the specified JMS provider type is missing.
Action	Provide a URL for the specified JMS provider type.

SPMCFGE0145	Provide an existing JNDI alias for the specified JMS provider type.
Explanation	The JNDI alias provided for the specified JMS provider type does not exist.
Action	Provide an existing JNDI alias for the specified JMS provider type.
SPMCFGE0146	The provided JNDI alias does not exist. Provide an existing JNDI alias for the specified JMS provider type.
Explanation	The JNDI alias provided for the specified JMS provider type does not exist.
Action	Provide an existing JNDI alias for the specified JMS provider type.
SPMCFGE0147	Configuration of type COMMON-JMS should have JMS element with unique alias.
Explanation	A configuration of type COMMON-JMS should have a JMS element with a unique alias.
Action	Provide unique alias for the JMS element.
SPMCFGE0148	Error occurred while retrieving the JMS configuration instances.
Explanation	An error occurred while retrieving the JMS configuration instances.
SPMCFGE0149	ConfigurationUiBindingService is not set.
Explanation	The ConfigurationUiBindingService is not set.
Action	Register the ConfigurationUiBindingService.
SPMCFGE0150	Configuration ui binding for {0} runtimeComponent and {1} configurationType cannot be retrieved.
Explanation	The configuration user interface binding cannot be retrieved because of incorrect search parameters or incorrect SPI implementation.
Action	Provide a valid runtimeComponent ID and configurationType ID or check the SPI implementation.
SPMCFGE0151	Error occurred while trying to unmarshal ui binding XML data.
Explanation	An error occurred while trying to unmarshall the user interface binding XML data.
Action	Check if the XML file is well-formed and valid.

SPMCFGE0152	Error occurred while trying to parse XSD Schema.
Explanation	An error occurred while trying to parse the XSD Schema.
Action	Check if the XSD schema is valid.
SPMCFGE0153	Client group for webMethods Messaging alias is invalid or not specified.
Explanation	While configuring webMethods Messaging alias, if provider type is Broker, Client Group cannot be empty.
Action	Provide a valid Client Group while configuring webMethods Messaging alias.
SPMCFGE0154	Broker messaging alias must have valid authentication configuration.
Explanation	If the webMethods Messaging alias provider is Broker, you must specify valid authentication configuration.
Action	Provide a valid authentication while configuring webMethods Messaging alias.
SPMCFGE0155	Broker Messaging alias must have a valid user.
Explanation	While configuring webMethods Messaging alias, if provider type is Broker, you must specify a valid user.
Action	Provide a valid user while configuring webMethods Messaging alias.
SPMCFGE0156	Broker Messaging alias must have a valid password.
Explanation	When the messaging alias provider is Broker, the alias should have a valid password.
Action	Provide a valid password for a messaging alias with provider type Broker.
SPMCFGE0157	Broker Messaging alias must have a valid keystore definition.
Explanation	When the messaging alias provider is Broker, it should have valid keystore definition.
Action	Provide a valid keystore for a messaging alias with provider type Broker.
SPMCFGE0158	Broker Messaging alias must have a valid encryption definition.
Explanation	When the messaging alias provider is Broker, the alias should have a valid encryption definition.
Action	Provide a valid encryption definition for a messaging alias with provider type Broker.

SPMCFG0159	Specify at least one server log facility to be updated.
Explanation	When updating the server logger, you must specify at least one server log facility.
Action	Ensure that you specify a server log facility.
SPMCFG0160	While updating a global variable, you can modify only the value for the global variable.
Explanation	You attempted to modify the key while updating a global variable. You can modify only the value for the global variable.
Action	Ensure that you modify only the value for the global variable.
SPMCFG1018	No primary or HTTPS ports are found for {0} component and its parent/child relations.
Explanation	No primary or HTTPS ports were found for {0} component and its parent/child relations.
Action	Check configured and available ports for availability and collisions.
SPMCFGW0029	The validator with the given type is not able to instantiate a KeyStore.
Explanation	The validator with the given type is not able to instantiate a KeyStore.
Action	Provide the correct certificate information.
SPMCFGW0030	An exception occurred when trying to load the keystore certificate.
Explanation	The NoSuchAlgorithmException exception occurred when trying to load the keystore certificate.
Action	Provide the correct certificate information.
SPMCFGW0031	An exception occurred while trying to load the keystore certificate.
Explanation	The CertificateException exception occurred while trying to load the keystore certificate.
Action	Provide the correct certificate information.
SPMCFGW0032	An exception occurred when trying to load the keystore certificate.
Explanation	The IOException exception occurred when trying to load the keystore certificate.
Action	Provide the correct certificate information.

SPMCFGW0033	An exception occurred when trying to load the keystore certificate.
Explanation	The URISyntaxException exception occurred when trying to load the keystore certificate.
Action	Provide the correct certificate information.
SPMCFGW0034	The file location provided in the truststore could not be found.
Explanation	The file location provided in the truststore could not be found.
Action	Provide the correct certificate information.
SPMCFGW0035	An exception occurred when trying to load the truststore certificate.
Explanation	The KeyStoreException exception occurred when trying to load the truststore certificate.
Action	Provide the correct certificate information.
SPMCFGW0036	An exception occurred when trying to load the certificate.
Explanation	The NoSuchAlgorithmException exception occurred when trying to load the certificate.
Action	Provide the correct certificate information.
SPMCFGW0037	An exception occurred when trying to load the certificate.
Explanation	The CertificateException exception occurred when trying to load the certificate.
Action	Provide the correct certificate information.
SPMCFGW0038	The validator could not load the certificate because of an exception.
Explanation	The validator could not load the certificate when trying to load the certificate because of the IOException exception.
Action	Provide the correct certificate information.
SPMCFGW0039	URI syntax provided is incorrect.
Explanation	The URISyntaxException occurred when trying to load the certificate.
Action	Provide the correct certificate information.

SPMCFGW0057	Platform Manager is unable to load JDBC driver class.
Explanation	Platform Manager is unable to load JDBC driver class because the driver class is not specified in the classpath.
Action	Specify the driver class in the classpath.
SPMCFGW0083	The path of the log file {0} is not fully qualified.
Explanation	The specified log file path is not fully qualified.
Action	Provide the absolute path for the log file.
SPMCFGW0104	Could not perform configuration validation for {0} because {1} error was encountered.
Explanation	Could not perform configuration validation for {0} because {1} error was encountered.
Action	Retry the action.
SPMCFGW0113	The specified port is already bound by configuration instance {0} of runtime {1} and is not enabled.
Explanation	The specified port is already bound by configuration instance {0} of runtime {1} and is not enabled.
Action	Change the port number and retry.
SPMCFGW0116	The specified port {0} is already in use by another configuration instance.
Explanation	The specified port {0} is already in use by configuration instance {1} of runtime {2}, but is not enabled.
Action	Specify a different port number.
SPMCFRE0000	The content of the response is not acceptable according to the accept headers
Explanation	The content of the response is not acceptable according to the accept headers.
Action	Check the response and the accept headers.
SPMCFRE0001	Unexpected exception occurred.
Explanation	Unexpected exception occurred.
Action	Check the logs.

SPMCFRE0002	Configuration partial failure for runtime component: {0}, instance: {1} with type {2} - with linked exception:
Explanation	Configuration partial failure for runtime component: {0}, instance: {1} with type {2} - with linked exception:
Action	Check the logs.
SPMCFRE0003	ConfigurationSerializersRegistry is not available.
Explanation	ConfigurationSerializersRegistry is not available.
SPMCFRE0004	ConfigurationSerializer SPI could not be found for RuntimeComponentId "{0}" and ConfigurationTypeId "{1}" .
Explanation	Platform Manager could not find a registered ConfigurationSerializer that can handle ConfigurationInstances with these properties.
Action	Register a ConfigurationSerializer SPI implementation that can handle ConfigurationInstances with these properties.
SPMCFRE0005	A ConfigurationTypeId "{0}" doesn't exist for RuntimeComponentId "{1}" .
Explanation	There is not registered ConfigurationType with the provided ID for the required RuntimeComponent.
Action	Provide valid ConfigurationTypeId for the required RuntimeComponent.
SPMCLTE0014	ConfigurationSerializer SPI could not be found for RuntimeComponentId "{0}" and ConfigurationTypeId "{1}" .
Explanation	Platform Manager could not find a registered ConfigurationSerializer that can handle ConfigurationInstances with these properties.
Action	Register a ConfigurationSerializer SPI implementation that can handle ConfigurationInstances with these properties.
SPMCLTE0015	Authentication call to SPM failed to execute.
Explanation	Authentication call to SPM failed to execute.
Action	Make sure that the user has valid access rights to the service.
SPMCLTE0016	Cannot retrieve the delegated assertion for the current user.
Explanation	Cannot retrieve the delegated assertion for the current user.
Action	Check if the user has valid delegated rights.

SPMCLTE0017	Internal Error processing Platform Manager request
Explanation	The server encountered an error and it cannot complete the request.
Action	Contact your system administrator.
SPMCLTE0018	The specified runtime component {0} could not be found on node {1}.
Explanation	There is no component called {0} registered for node {1}. The data could not be retrieved.
Action	Check the components for Platform Manager node {1}.
SPMCLTE0020	{0} is not a valid type for the runscript request
Explanation	The type for the runscript request is not valid. Valid types are fix or product.
Action	Resubmit the request with a valid type.
SPMCLTE0021	No artifacts specified in uninstall request
Explanation	The unistall request does not specify any products or fixes.
Action	Resubmit the request with a valid list of products and fixes.
SPMCLTE0022	Invalid artifact type for {0}
Explanation	The artifacts are nov valid. Valid artifacts are either Product or Fix.
Action	Specify valid artifacts in the request.
SPMCLTE0023	Invalid repository type: {0}
Explanation	The specified repository type is not supported.
Action	Use fix or product as the repository type.
SPMCLTE0024	No such repository: {0}
Explanation	The repository does not exist.
Action	Specify a valid repository.
SPMCLTE0025	Unsupported repository type: {0}
Explanation	Fix and product are the only supported repository types.
Action	Use fix or product as the repository type.

SPMCLTE0026	Unsupported repository type: {0}
Explanation	Fix and product are the only supported repository types.
Action	Specify a valid repository type.
SPMCLTE0027	The response cannot be converted to java.util.Properties: {0}
Explanation	The response does not comply with the java.util.Properties text or XML format.
Action	Make sure the format is correct or contact Software AG Global Support.
SPMCLTI0009	Internal Server Error
Explanation	Internal server error.
Action	Make sure that the required services are running, communication channels are accessible, and parameters are valid.
SPMCLTI0010	Unknown Error
Explanation	An unspecified error occurred during communication.
Action	Make sure that the required services are running, communication channels are accessible, and parameters are valid.
SPMCLTI0011	Error occurred during execution of the command!
Explanation	An error occurred during communication.
Action	Make sure that the required services are running, communication channels are accessible, and parameters are valid.
SPMCLTW0001	An exception has occurred while retrieving remotely RuntimeStatus from: {0}
Explanation	This might be happening due to a number of reasons, such as missing monitoring implementation in the product plugin, network interference, and others.
Action	See detailed stack trace in order to define the actual reason for this exception.
SPMCOME0000	{0} is unknown runtime component.
Explanation	This component ID does not exist.
Action	Use runtimeComponentId that already exists.

SPMCOME0001	{0} is an unknown product.
Explanation	The required productId does not exist in the list of InventoryService.getInstalledProducts()
Action	Use a productId of a product that is already installed.
SPMCOME0002	No available implementation for {0}.
Explanation	Displayed status of a product plug-in after calling a specific operation that is not available.
Action	Use an available operation.
SPMCOME0003	The PortSettings XML cannot be empty.
Explanation	The PortSettings XML response cannot be empty.
Action	Add data in the PortSettings XML response.
SPMCOME0004	PortSettings contains property keys that do not match properties in the config.ini file.
Explanation	PortSettings contains property keys that do not match properties in the config.ini file.
Action	Check the property keys and try to find the matching one or fix the config.ini file.
SPMCOME0005	Load configuration error.
Explanation	Indicates issues with reading/writing a configuration.
Action	Fix any issues related to reading or writing the configuration.
SPMCOME0006	Unexpected exception.
Explanation	An unexpected exception occurred while reading/writing a configuration.
Action	Fix the unexpected exception.
SPMCOME0007	An exception occurred.
Explanation	A PlatformManagerException occurred.
Action	Resolve the exception.

SPMCOME0010	Error:
Explanation	This is most likely an error that is not expected.
Action	None.
SPMCOME0017	Provided configuration is not valid.
Explanation	The provided configuration does not conform with the rules for the specified configuration type.
Action	Check the provided configuration for errors and rule breaches.
SPMCOME0018	Unexpected component status.
Explanation	The expected component status is one of the following: {0} but the actual one is {1}
Action	Try to correct the situation. Retry the operation.
SPMCOME0020	A Configuration instance with ID = {0} does not exist.
Explanation	A Configuration instance with the provided ID does not exist.
Action	Use the ID of an existing Configuration instance.
SPMCOME0029	Server did not find anything matching the request URI.
Explanation	There is no resource for this URI.
Action	Check if the URI is correct. Check if the resource IDs are valid.
SPMCOME0030	The request cannot be understood by the server.
Explanation	Inconsistent or empty body.
Action	Do not retry without modifications of the request.
SPMCOME0031	The request is not acceptable as stated in the accept headers.
Explanation	Platform Manager cannot return the response in the desired format.
Action	Either change the accept headers, or the data format of the response.
SPMCOME0033	The KPI '{0}' contains invalid data and cannot be created.
Explanation	The error occurs when the RuntimeStateZone can not be calculated. This could happen if the given values for max, marginal, and normal are null or in the wrong format.
Action	Check the content of the KPI and provide proper data.

SPMCOMI0008	The command is disabled.
Explanation	Most probably an important OSGi service is not registered.
Action	None.
SPMCOMI0009	No help available.
Explanation	This command does not provide a help message.
Action	None.
SPMCOMI0011	[DISABLED]
Explanation	A command with this info line prefix cannot be executed.
Action	None.
SPMCOMI0032	Unsupported operation.
Explanation	The attempted operation is currently not supported by the Platform Manager server.
Action	Contact you administrator.
SPMCOMI0037	Messaging
SPMCOMI0039	Loggers
SPMCONE0001	Error while loading configuration.
Explanation	An error occurred while loading configuration.
Action	Provide valid arguments.
SPMCONE0006	Error while getting a configuration type.
Explanation	An error occurred while getting a configuration type.
Action	Resubmit the request.
SPMCONE0007	Error during serialization
Explanation	An error occurred during the serialization step.
Action	Resubmit the serialization step.

SPMCONE0013	Error while updating configuration.
Explanation	An error occurred while updating the configuration.
Action	Resubmit the configuration.
SPMCONE0015	Error while getting configuration status.
Explanation	Error while getting configuration status.
Action	Get the configuration status correctly.
SPMCONE0024	Error while getting configuration instances.
Explanation	An error occurred while getting configuration instances.
Action	Resubmit the configuration instances get operation.
SPMCONI0000	The command is not recognized. Type {0} for help.
Explanation	The typed command is not recognized.
Action	Type spm for help.
SPMCONI0002	{0} - get configuration values for the given configuration type
Explanation	Missing configuration values for the given configuration type.
Action	Get configuration values for the given configuration type.
SPMCONI0003	Configuration (JavaModel): {0}
Explanation	Configuration (JavaModel) information.
Action	None.
SPMCONI0004	Configuration (Text): {0}
Explanation	Configuration (Text) information.
Action	None.
SPMCONI0005	No load configuration.
Explanation	No load configuration.
Action	None.

SPMCONI0008	Configuration status: {0}
Explanation	Information about the configuration status.
Action	None.
SPMCONI0009	No configuration status.
Explanation	No configuration status.
Action	None.
SPMCONI0010	The specified resource doesn't exist.
Explanation	The specified resource doesn't exist.
Action	None.
SPMCONI0011	There is no configuration type found for this runtime component.
Explanation	There is no configuration type found for this runtime component.
Action	None.
SPMCONI0012	{0} - Submit configuration and get the configuration status
Explanation	The configuration status is missing or the configuration is not submitted.
Action	Submit the configuration and get the configuration status.
SPMCONI0014	Bad URI - {0}
Explanation	Bad URI is submitted.
Action	None.
SPMCONI0016	Configuration status: {0}
Explanation	Information about the configuration status.
Action	None.
SPMCONI0017	No configuration status.
Explanation	No configuration status.
Action	None.

SPMCONI0018	{0} - query for the current configuration status.
Explanation	A query for the current configuration status.
Action	None.
SPMCONI0019	No configuration instance.
Explanation	No configuration instance.
Action	None.
SPMCONI0020	No configuration instances.
Explanation	No configuration instances.
Action	None.
SPMCONI0021	Configuration Instance description: {0}
Explanation	Configuration Instance description.
Action	None.
SPMCONI0022	Configuration Instance ID: {0}
Explanation	Information about the Configuration Instance ID.
Action	None.
SPMCONI0023	Configuration Instance name: {0}
Explanation	Information about the Configuration Instance name.
Action	None.
SPMCONI0025	{0} - list of the configuration instances for a given runtime component
Explanation	List of the configuration instances for a given runtime component.
Action	None.
SPMCONI0026	JobManagerService is not available.
Explanation	JobManagerService is not available.
Action	None.

SPMCONI0027	Invalid job ID: {0}
Explanation	Information about an invalid job ID.
Action	None.
SPMCONI0028	Number of jobs: {0}
Explanation	Information about the number of jobs.
Action	None.
SPMCONI0029	Job ID: {0}
Explanation	Information about the job ID.
Action	None.
SPMCONI0030	The status of the job with ID ({0}) is {1}.
Explanation	Information about the job status.
Action	None.
SPMCONI0031	The job started at {0}.
Explanation	Information about when the job started.
Action	None.
SPMCONI0032	The job ended at {0}.
Explanation	Information about when the job ended.
Action	None.
SPMCONI0033	The job is still running.
Explanation	The job is still running.
Action	None.
SPMCONI0034	The duration of the job so far is {0} seconds.
Explanation	Information about the duration of the job.
Action	None.

SPMCONI0035	{0} - lists all (not done) jobs or status of a specific job
Explanation	Lists all (not done) jobs or status of a specific job.
Action	None.
SPMCONI0036	{0} - runtime status of the component identified by this ID.
Explanation	Runtime status of the component identified by this ID.
Action	None.
SPMCONI0037	No RuntimeState found for {0}.
Explanation	No RuntimeState found.
Action	None.
SPMCONI0038	{0} - list of the runtime components
Explanation	List of the runtime components.
Action	None.
SPMCONI0039	{0} - list of the installed products
Explanation	List of the installed products.
Action	None.
SPMCONI0040	{0} - starts the runtime component with this ID with safe mode enabled.
Explanation	Starts the runtime component with this ID with safe mode enabled.
Action	None.
SPMCONI0041	{0} - starts the runtime component with this ID with debug mode enabled.
Explanation	Starts the runtime component with this ID with debug mode enabled.
Action	None.
SPMCONI0042	{0} - stops the runtime component with this ID.
Explanation	Stops the runtime component with this ID.
Action	None.

SPMCONI0043	{0} - starts the runtime component with this ID.
Explanation	Starts the runtime component with this ID.
Action	None.
SPMCONI0044	{0} - resumes the runtime component with this ID.
Explanation	Resumes the runtime component with this ID.
Action	None.
SPMCONI0045	{0} - restarts the runtime component with this ID.
Explanation	Restarts the runtime component with this ID.
Action	None.
SPMCONI0046	{0} - pauses the runtime component with this ID.
Explanation	Pauses the runtime component with this ID.
Action	None.
SPMCONI0047	{0} - creates a new configuration instance for a given runtime component and a given configuration type.
Explanation	Creates a new configuration instance for a given runtime component and a given configuration type.
Action	None.
SPMCONI0048	Error during creating configuration
Explanation	Error during creating configuration
Action	None.
SPMCONI0049	{0} - Delete configuration and get the configuration status.
Explanation	Delete configuration and get the configuration status.
Action	Delete configuration and get the configuration status.
SPMCONI0050	ConfigurationSerializer is not found for runtimeComponent with ID: {0} and configurationType with ID: {1}
Explanation	ConfigurationSerializer is not found for runtimeComponent with ID: {0} and configurationType with ID: {1}.
Action	None.

SPMCONI0051	{0} - runtime state of the comonent identified by this ID
Explanation	Runtime state of the comonent identified by this ID
Action	None
SPMCORI0000	TestMessage
Explanation	Test message to be removed.
Action	None.
SPMDIAE0000	Log source not found: {0}
Explanation	The requested log source does not exist.
Action	Use getLogSources() prior to retrieveLog().
SPMDIAE0001	{0} does not exist or is not a directory.
Explanation	The specified location does not exist or is not a directory.
Action	Provide a location that exists and is a directory.
SPMDIAW0002	Missing 'logDirs' configuration property for DefaultLogAccess service component configuration.
Explanation	An SPM bundle has a LogAccess service component that is missing its 'logDirs' configuraiton property.
Action	The OSGI service configuration must include this property if log files are to be collected.
SPMDIRE0000	{0} not found!
Explanation	A runtime component or a log was not found.
Action	Verify the requested item is really present in the system.
SPMIMGE0000	Product {0} does not support instance management.
Explanation	The Platform Manager plugin for product {0} does not support instance management.
Action	See the Software AG Platform Manager documentation to double check if product {0} supports instance management. If the product supports instance management, contact Software AG Global Support.

SPMIMGE0002	Properties for {0} cannot be returned.
Explanation	A server error occurred during properties extraction.
Action	Contact Software AG Global Support.
SPMIMGE0003	{0} cannot be matched against {1}
Explanation	The specified regular expression in the component definition does not match the run-time component ID.
Action	Revise the regular expression in the component definition or contact Software AG Global Support.
SPMIMGE0004	Mandatory property {0} is not specified.
Explanation	A required property in the component definition is missing.
Action	Specify the required property in the component definition.
SPMIMGE0005	Instance management script {0} cannot be resolved.
Explanation	The instance management script was not found on the file system or there is another I\O error.
Action	Make sure the instance management script has the correct name and is in the correct location.
SPMIMGE0007	This instance management command cannot be performed because the following input properties are missing: {0}
Explanation	The input properties are insufficient for performing the requested instance management operation.
Action	Provide the input properties that are missing or contact Software AG Global Support.
SPMIMPE0000	Unable to locate configuration source property for persistent ID: {0}; configuration properties for this PID are: {1}.
Explanation	Most probably the persistent ID configuration is not provided by Dynamic Configurator.
Action	Provide the persistent ID using Dynamic Configurator.

SPMIMPE0001	The configuration source location for the persistent ID {0} is not a valid URL: {1}
Explanation	The configuration source location is not a valid URL.
Action	Dynamic Configurator should point to a valid URL for the given persistent ID.
SPMINRI0000	Nothing found for ID = {0}
Explanation	Nothing found for this ID.
Action	None.
SPMINRI0001	Inventory Service is not set.
Explanation	Inventory Service is not set.
Action	None.
SPMINVI0000	Product cannot be null.
Explanation	Product cannot be null.
Action	None.
SPMINVI0001	Category cannot be null.
Explanation	Category cannot be null.
Action	None.
SPMINVI0002	ID must start with productId.
Explanation	ID must start with productId.
Action	None.
SPMINVW0003	Unable to obtain the node's platform code and description from installer service for getSupportedPlatforms. Details: {0}
Explanation	The Installer service is used to retrieve some of the operating system details provided for the platform description.
Action	None.
SPMINVW0004	Unable to obtain the platform details for getSupportedPlatforms. Details: {0}
Explanation	License management details are not available for this node.
Action	None.

SPMJBRE0000	A job with ID {0} cannot be found.
Explanation	A job with the specified ID may have never existed or it may have completed long before this request.
Action	Use the following URI to list all jobs that are running or recently completed: /spm/jobmanager/jobs
SPMJOB0001	Maximum number of non-done jobs reached. Try again later or increase {2}. Current jobs: {0} max jobs: {1}.
Explanation	The job manager queue is full and new jobs cannot be scheduled.
Action	Wait a few moments or increase com.softwareag.platform.management.jobmanager.impl.Configuration.SYS_PROP_MAX_JOBS.
SPMJOB0002	Job sequence exhausted. Try again later or set a bigger {0}
Explanation	All job sequence IDs have been consumed.
Action	Wait a few moments or set a bigger com.softwareag.platform.management.jobmanager.impl.Configuration.SYS_PROP_JOB_SEQUENCE_MAX_SIZE
SPMJOB0000	This job is done or not available due to a problem.
Explanation	The Null Job status.
Action	None.
SPMLCCE0000	runtimeComponentId for productId {0} is null.
Explanation	The AdvancedLifecycleOperations service is registered in with productId that does not contain the given runtimeComponentId.
Action	Make sure that your product plugin has correct productId and runtimeComponentId IDs.
SPMLCCE0001	Runtime component "{0}" does not support life cycle operation "{1}".
Explanation	This Runtime component does not support the specified life cycle operation.
Action	Make sure you execute life cycle operations supported by this run-time component.
SPMLCRE0000	The lifecycle operation to execute is unknown.
Explanation	The operation is not a part of the predefined list of lifecycle operations that can be executed: start, stop, restart, pause, resume, start in debug, and start in safe mode.
Action	Specify an operation from the predefined list.

SPMMONE0000	Could not get JMXConnector for runtime component with id {0} because JMX port configuration was not found.
Explanation	This particular run-time component does not have a configured JMX port or there was a problem obtaining the configuration.
Action	Check if the run-time component is online and that at least one enabled JMX port configuration is available.
SPMOGIE0000	Could not obtain the runtime component id from "cplm" file: {0}
Explanation	There was a problem obtaining metadata information about a specific profile.
Action	Check the profile folder structure and if cplm.xml contains any errors.
SPMOGIE0002	Following exception occurred "{0}" while parsing "{1}".
Explanation	One of the profiles contains wrong metadata.
Action	Check listed file for errors.
SPMOGIE0003	The Common Platform Lifecycle Management (cplm-v.xml) file is malformed.
Explanation	The profile metadata file contains errors.
Action	Try to check cplm.xml file for errors in the specific profile.
SPMOGIE0005	Operation "{0}" is not defined in the "cplm" file.
Explanation	There was lifecycle operation for the specific component that is not defined inside cplm.xml.
Action	Try to repair cplm.xml file in the component profile folder.
SPMOGIE0008	Common Platform Lifecycle Management (cplm-v.xml) file not found!
Explanation	A file called cplm.xml is expected inside the profile folder.
Action	Try to create cplm.xml file for the component.
SPMOGIE0009	Configuration with version "{0}" was not found in the metadata file.
Explanation	No configuration with the specified version exists inside the cplm.xml file.
Action	Check the profile folder for cplm.xml and make sure it is up to date.

SPMOGIE0010	Recursive actions not allowed.
Explanation	A recursive action exists inside cplm.xml file.
Action	Check the cplm.xml file in the profile and remove any recursive actions.
SPMOGIE0011	Malformed action "{0}".
Explanation	Wrong metadata information exists inside the profile cplm.xml file.
Action	Check the cplm.xml file for the profile and correct errors.
SPMOGIE0012	Action "{0}" not found.
Explanation	Unknown action defined inside cplm.xml.
Action	Correct the cplm.xml file for the profile.
SPMOGIE0013	Script "{0}" does not exist.
Explanation	The specified script cannot be found in cplm.xml.
Action	Specify valid script/path inside the profile cplm.xml file.
SPMOGIE0014	Failed executing: {0}
Explanation	A problem occurred while executing the specified script.
Action	Check the specified script for errors.
SPMOGIE0015	Missing value data for element "argument".
Explanation	Wrong data format inside the profile cplm.xml file.
Action	Provide valid data inside cplm.xml.
SPMOGIE0016	More than one "action" element with the same name exist.
Explanation	A naming conflict exists inside cplm.xml.
Action	Provide different action names.
SPMOGIE0017	Two "configuration" elements have the same version.
Explanation	A conflict exists inside cplm.xml file.
Action	Provide different versions for "configuration" elements.

SPMOGIE0018	Missing attribue "path" or "actionReference" for element "execute".
Explanation	Wrong data exists inside the profile cplm.xml.
Action	Provide the missing data.
SPMOGIE0019	Cannot specify both "path" and "actionReference" attributes in one "execute" element.
Explanation	Wrong data exists inside cplm.xml.
Action	Correct cplm.xml file inside the profile folder.
SPMOGIE0026	Unable to find configuration instances for the runtime component with ID: "{0}". The "{1}" system property is not set.
Explanation	Such a property should be available in the config.ini file located under the configuration folder of this runtime component.
Action	Add the property by hand. The value must be the absolute path to the folder that contains the configuration properties files.
SPMOGIE0027	Unable to find configuration instances for the runtime component with ID: "{0}". "{1}" is either not existing or is not a directory.
Explanation	This folder should contain the configuration properties files.
Action	Check if the location is configured properly in the config.ini file.
SPMOGIE0029	Unable to load the configuration instance with ID "{0}" for the "{1}" runtime component.
Explanation	None of the available configuration handlers can load the configuration instance. The configuration instance type might not be supported.
Action	Check the supported configuration instance types.
SPMOGIE0030	Unable to update the configuration instance with ID "{0}" for the "{1}" runtime component.
Explanation	None of the available configuration handlers can update the configuration instance. The configuration instance type might not be supported.
Action	Check the supported configuration instance types.

SPMOGIE0031	Unable to load the configuration instance with ID: "{0}" for the "{1}" runtime component. The "{2}" property is not available but is required.
Explanation	Unable to load the instance because of invalid set of configuration properties. The required properties must be available.
Action	Add the required property and report the invalid configuration instance.
SPMOGIE0032	Unsupported protocol for configuration instance {0}.
Explanation	Unknown protocol for the specified configuration instance.
Action	Check documentation for supported protocols.
SPMOGIE0033	The update of the "{0}" configuration instance for the "{1}" runtime component failed. The port settings are empty.
Explanation	The incoming configuration is empty. No port settings data is available.
Action	Port settings data should be present inside incoming configuration.
SPMOGIE0034	No port available in configuration instance {0}.
Explanation	Port number cannot be found inside the configuration instance.
Action	Provide port number inside the configuration instance.
SPMOGIE0035	The update of the "{0}" configuration instance for the "{1}" runtime component failed. The available port configurations are more than one.
Explanation	The configuration instance should contain only one port configuration.
Action	Remove obsolete port configurations.
SPMOGIE0036	The update of the "{0}" configuration instance for the "{1}" runtime component failed. The port is null.
Explanation	The port settings do not contain any port configuration.
Action	Provide port configuration.
SPMOGIE0037	Invalid port number: "{0}"
Explanation	The validation of the port number failed. The port number should be greater than 1024 and less than 65535.
Action	Check the source of the port number and provide a value in the specified range.

SPMOGIE0038	Error writing the new configuration. An attempt was made to overwrite an existing configuration file "{0}" with the new configuration.
Explanation	The port number is a part of the configuration file name. Therefore, if the user sets a port that is already used in another configuration, a collision in the file names occurs. In such case the write operation is aborted because configuration data might be lost.
Action	Check if the port number set in the configuration that is being written is not used in another configuration of the same type.
SPMOGIE0039	The new configuration could not be written. Unable to delete the original configuration instance file: "{0}"
Explanation	A problem occurred while deleting the configuration instance file.
Action	For more details, check the I/O exceptions in the log file.
SPMOGIE0040	ConfigurationService not found!
Explanation	Most probably spm configuration bundle was not started.
Action	Try to start spm the configuration bundle.
SPMOGIE0042	No connector configurations or connector port found for component: {0}
Explanation	Expected data is missing for the specified component.
Action	Provide configuration for the specified component.
SPMOGIE0045	Cannot start "{0}" profile in debug mode without debug port configuration.
Explanation	It is possible that wrong data exists inside the cplm.xml file.
Action	Escape single quote with another single quote.
SPMOGIE0046	Cannot start "{0}" profile in debug mode because the debug port configuration is disabled.
Explanation	It is possible that wrong data exists inside the cplm.xml file.
Action	Escape single quote with another single quote.
SPMOGIE0048	Exception occurred while obtaining port configurations for profile "{0}".
Explanation	A problem occurred while reading profile port configurations.
Action	Check profile port configurations for errors.

SPMOGIE0050	{0} cannot be null.
Explanation	{0} cannot be null.
Action	Make sure the parameter is not null.
SPMOGIE0051	{0} must begin with {1}
Explanation	{0} must begin with {1}
Action	Make sure {0} begins with {1}.
SPMOGIE0055	A log configuration not found: {0}
Explanation	A log configuration was not found.
Action	Check your configuration instance path.
SPMOGIE0056	Could not retrieve parent runtime component with id {0} for child runtime component with id {1}.
Explanation	An error occurred while obtaining information for the runtime component.
Action	Check if the runtime component is online and at least one enabled JMX port configuration is available.
SPMOGIE0057	Could not get JMXConnector for a runtime component of category {0}. Runtime component id is {1}.
Explanation	An error occurred while obtaining information for the runtime component.
Action	Check if the runtime component is online and at least one enabled JMX port configuration is available.
SPMOGIE0058	Could not get JMXConnector because no JMX port configuration is available for runtime component with id {0}.
Explanation	An error occurred while obtaining information for the runtime component.
Action	Check if the runtime component is online and at least one enabled JMX port configuration is available.
SPMOGIE0059	Could not get JMXConnector for runtime component with id {0} because none of the configured JMX ports is open.
Explanation	An error occurred while obtaining information for the runtime component.
Action	Check if the runtime component is online and at least one enabled JMX port configuration is available.

SPMOGIE0060	Could not get SubsystemMBean for a runtime component of a type different than ENGINE. Category : {0}, runtime component id : {1}
Explanation	An error occurred while obtaining information for the runtime component.
Action	Check if the runtime component is online and at least one enabled JMX port configuration is available.
SPMOGIE0061	No subsystem with id {0} is found for runtime component with id {1}.
Explanation	An error occurred while obtaining information for the runtime component.
Action	Check if the runtime component is online and at least one enabled JMX port configuration is available.
SPMOGIE0062	Exactly one subsystem is expected for runtime component with id {0}.
Explanation	Exactly one subsystem is expected for the given runtime component.
Action	Make sure there is exactly one subsystem specified for runtime component.
SPMOGIE0064	Executing the script for '{0}' lifecycle operation returned unexpected result code : {1}.
Explanation	Script execution return code was different than expected.
Action	Make sure the correct script corresponds to this lifecycle operation inside cplm.xml.
SPMOGIE0065	Cannot start "{0}" profile in debug mode because the configured debug port is already in use.
Explanation	Another application is started using the same port number.
Action	Stop the other product using the same port for debug mode.
SPMOGIE0066	Platform Manager is unable to find configuration instances for the runtime component with ID: "{0}". "{1}" is either not existing or is not a directory.
Explanation	No configuration instances were found in the listed location.
Action	Check if the location is configured correctly in the config.ini file.
SPMOGIE0067	Platform Manager is unable to find configuration instances for the runtime component with ID: "{0}". "{1}" is empty.
Explanation	Platform Manager is unable to find configuration instances for the runtime component. This folder should contain the profile-related folders and files for the specified runtime component. The path is configured in the config.ini file.
Action	Check if this folder is empty.

SPMOGIE0070	Error while getting runtime status.
Explanation	A problem occurred while obtaining data from an Engine.
Action	Check if the connection and credentials are OK.
SPMOGIE0081	"{0}" operation failed for runtime component with id {1}. Reason:{2}
Explanation	Executing operation against engine failed.
Action	Check JMX credentials and properties for this engine.
SPMOGIE0090	No alias provided for the port configuration.
Explanation	Providing a value for the alias during the creation of the port configuration is required.
Action	Specify an alias for the port configuration.
SPMOGIE0091	The provided port alias is not URL friendly.
Explanation	The provided port alias contains symbols that are not URL friendly.
Action	Provide only URL friendly symbols for the port alias.
SPMOGIE0092	Failed to construct the Configuration Instance ID.
Explanation	Platform Manager failed to construct the Configuration Instance ID.
Action	Check the configuration file for this instance.
SPMOGIE0093	Missing common port alias. This configuration will be ignored.
Explanation	The common port alias is missing and the configuration will be ignored.
Action	Provide an alias for this port configuration.
SPMOGIE0094	Failed to construct the configuration instance.
Explanation	Platform Manager failed to construct the configuration instance.
Action	Provide valid configuration data.
SPMOGIE0096	Cannot read config.ini file for RuntimeComponent with ID {0}. Fall back on default product: {1}.
Explanation	Cannot retrieve the parent product for the specified run-time component because an error occurred while reading the corresponding config.ini file. The default product will be used instead.
Action	Check if the config.ini is a valid properties file.

SPMOGIW0001	Could not pass the validating schema. The "cplm" file will not be validated.
Explanation	File called cplm.xml does not contain expected metadata.
Action	Check profile folder files called cplm.xml for errors.
SPMOGIW0028	Unable to find configuration instances for the runtime component with ID: "{0}". "{1}" is empty.
Explanation	This folder should contain the configuration properties files for the specified runtime component. The path is configured in the config.ini file.
Action	Check if this folder should be empty.
SPMOGIW0054	Could not retrieve engines for runtime component with id : {0}. Reason : {1}
Explanation	Most probably the component with the given ID was offline.
Action	Check if the runtime component is online and at least one enabled JMX port configuration is available.
SPMPROE0003	Script failed with status {0}
Explanation	A fix script job failed with indicated status.
Action	Refer to the Software AG Update Manager log for more information.
SPMPROE0004	Install fixes is not supported.
Explanation	The requested feature is not supported yet.
Action	Use the runscript method to install fixes.
SPMPROE0005	Nothing to install.
Explanation	None of the artifacts exist in the specified repository.
Action	Use different artifacts or install from a different repository.
SPMPROE0006	Install from local repository not supported.
Explanation	The feature is not yet supported.
Action	Export artifacts from the repository into an image archive and install from the archive.

SPMPROE0007	No repository found for {0}
Explanation	The specified repository does not exist.
Action	Create the repository or use a different one.
SPMPROE0008	Install from remote repository is not supported.
Explanation	Installing from a remote repository is not supported.
Action	Create an image archive using installer client, and install from the archive.
SPMPROE0009	Unable to process fix script.
Explanation	Failures occurred processing a fix script.
Action	See the Software AG Update Manager logs and exception for failure details.
SPMPROE0010	Invalid Type: {0}
Explanation	The type of script is unrecognized. Valid types are either product, or fix.
Action	Use product or fix as the script type.
SPMPROE0011	Uninstall of fixes is not supported by the uninstall method.
Explanation	The operation is not supported.
Action	Use runscript to remove fixes.
SPMPROE0012	Invalid artifact type: {0}
Explanation	The artifact was not a product or fix artifact.
Action	Use a valid artifact.
SPMPROE0013	Script failed with exit code {0}. See log at {1} for more information.
Explanation	An installation script failed.
Action	Refer to the log for more details on the failure.
SPMPROE0014	The provided configuration does not include the com.softwareag.plm.spm.provisioning.pathtosum property.
Explanation	The property must be specified in the configuration.
Action	Include a com.softwareag.plm.spm.provisioning.pathtosum property setting that references the Software AG Update Manager installation directory.

SPMPROE0016	The com.softwareag.plm.spm.provisioning.pathtosum property does not reference an existing directory.
Explanation	The property must reference the installation directory of Software AG Update Manager.
Action	Specify a valid directory.
SPMPROE0018	Removal of ProvisioningService configuration is not supported.
Explanation	The ProvisioningService requires a configuration.
Action	None required.
SPMPROE0020	No such repository, {0}
Explanation	The install request specified a nonexistant repository.
Action	Specify a valid repository ID.
SPMPROE0021	No matching products to uninstall.
Explanation	The uninstall request specified products that are not installed.
Action	Ensure that the correct product list or managed node is included in the request.
SPMPROE0022	{0} is not in repository {1}
Explanation	The fix cannot be installed because it does not reside in the source repository.
Action	Specify a different fix or repository.
SPMPROE0023	Multiple fixes with id, {0}, reside in the repository {1}
Explanation	Platform Manager cannot determine which fix version to install.
Action	Specify a complete version number for the fix (<fixname>_<version>).
SPMPROE0024	Script failed with exit code {0};{1}. See log at {2} for more details.
Explanation	The execution of the script failed.
Action	Rerun script after resolving the errors listed in the log.
SPMPROE0025	Script failed with status {0}: {1}
Explanation	The execution of the fix script failed.
Action	Rerun the script after resolving the errors.

SPMPROI0000	Fix installation completed with exit code: {0}
Explanation	The fix script has completed with the indicated exit status.
Action	If status is nonzero, review the Software AG Update Manager logs for possible problems.
SPMPROI0001	Launching: {0}
Explanation	A fix script is being started in a separate process. The specific shell command is included in the message.
Action	None required.
SPMPROI0002	Failed to launch fix script: {0}
Explanation	A script could not be launched. The associated job will be given an error status.
Action	Refer to the exception included in the message to resolve the problem.
SPMPROI0015	The configuration for the ProvisioningService must include a com.softwareag.plm.spm.provisioning.pathtosum property setting
SPMPROI0017	The com.softwareag.plm.spm.provisioning.pathtosum property in the configuration must reference the installation directory of an UpdateManager
SPMPROI0019	Unsupported operation
SPMREPE0000	Unsupported operation.
Explanation	The getContent operation is not supported for fix images.
Action	Use UpdateManager to view fixes.
SPMREPE0001	Unsupported operation.
Explanation	The import operation is only supported on local product repositories.
Action	None required.
SPMREPE0002	Invalid configuration detected for repository, {0}
Explanation	The location property of the repository is invalid. The configuration refers to a fix image, which must be a local file.
Action	Delete the configuration.

SPMREPE0003	Repository not found at {0} for configuration, {1}
Explanation	A configuration was found for a fix image repository that does not exist.
Action	Remove the configuration.
SPMREPE0004	Unsupported operation.
Explanation	The export operation is not supported for this artifact type or repository.
Action	None required.
SPMREPE0005	Unsupported operation.
Explanation	The repository type does not support dependencies.
Action	None required.
SPMREPE0006	Unsupported operations.
Explanation	Publishing is not supported for this repository type.
Action	None required.
SPMREPE0007	Unable to parse canonical in {1}: {0}
Explanation	The product properties could not be processed. The file is not a valid image archive.
Action	Use a valid image archive.
SPMREPE0008	Importing of artifacts into an image archive is not supported.
Explanation	Importing artifacts into an image archive is not supported.
Action	To create an image archive, use the export feature.
SPMREPE0009	URI scheme for image archive repository, {0}, must be file
Explanation	The repository configuration is invalid.
Action	Specify a local file as the archive location.
SPMREPE0010	Repository not found at {0}
Explanation	There is no archive at the specified location.
Action	Specify a valid location for the archive.

SPMREPE0011	Exporting from images is not supported.
Explanation	The function is not supported.
Action	None required.
SPMREPE0012	Dependencies not available for image archives.
Explanation	The function is not supported.
Action	Non required.
SPMREPE0013	Publish feature is not supported for image archives.
Explanation	Only local repositories may be published.
Action	None required.
SPMREPE0016	Unable to list content of sandboxes.
Explanation	The function is not supported.
Action	Use the installer client to view sandbox content.
SPMREPE0017	Sandboxes are not modifiable.
Explanation	Importing into sandboxes is not supported.
Action	None required.
SPMREPE0018	Exporting from sandboxes is not supported.
Explanation	The function is not supported.
Action	Use the installer client to export images from legacy sandboxes.
SPMREPE0019	Dependencies not available for sandboxes.
Explanation	The function is not supported.
Action	Use installer client to interact with legacy sandboxes.
SPMREPE0020	Only local repositories can be published.
Explanation	Sandboxes cannot be published.
Action	None required.

SPMREPE0021	Unable to load/create repository at {0}
Explanation	Platform Manager was not able to read the repository content.
Action	See to logs for more information. The repository may have been corrupted.
SPMREPE0024	Unable to verify archive: {0} due to {1}
Explanation	The file could not be verified as a ZIP archive.
Action	Ensure the path to the archive is correct.
SPMREPE0025	Unable to verify archive: {0} due to {1}
Explanation	The file could not be verified as a ZIP archive.
Action	Ensure the path to the archive is correct.
SPMREPE0026	Local repository, {0}, has an invalid location: {1}
Explanation	The repository configuration is invalid.
Action	Delete the configuration.
SPMREPE0027	Unable to create repository at {0}
Explanation	The repository could not be created.
Action	See the logs for more information.
SPMREPE0028	Exporting of fixes is not supported.
Explanation	The function is not supported.
Action	Use Software AG Update Manager to export fixes.
SPMREPE0037	Unsupported operation.
Explanation	getContent is not supported for remote fix repositories.
Action	Use Software AG Update Manager to view repository content.
SPMREPE0038	Unsupported operation.
Explanation	Import is not supported for remote fix repositories.
Action	Use Software AG Update Manager to manage fix repositories.

SPMREPE0039	Unsupported operation.
Explanation	Export is not supported for remote fix repositories.
Action	Use Software AG Update Manager to manage fix repositories.
SPMREPE0040	Unsupported operation.
Explanation	Dependencies not supported for remote fix repositories.
Action	Use Software AG Update Manager to manage fix repositories.
SPMREPE0041	Unsupported operation.
Explanation	Publish is not supported for remote fix repositories.
Action	Use Software AG Update Manager to manage fix repositories.
SPMREPE0042	Unable to access SD Security Service.
Explanation	The security service used to access remote repositories is not available.
Action	Try to restart the security service.
SPMREPE0043	Unable to obtain security token for user, {0}, for the {1} repository.
Explanation	The attempt to login to the SD security service failed.
Action	Ensure correct credentials are set for the repository.
SPMREPE0044	Unable to load remote repository, {0}, due to {1}
Explanation	A failure was detected attempting to access the repository.
Action	See the logs for more information.
SPMREPE0045	Unsupported operation.
Explanation	Importing into a remote repository is not supported.
Action	None required.
SPMREPE0047	Unsupported operation.
Explanation	Exporting from a remote repository is not supported.
Action	Import the artifacts into a local repository, then export from the local repository.

SPMREPE0048	Unsupported operation.
Explanation	Publish is not supported for remote repositories. They are already published.
Action	None required.
SPMREPE0049	{0} not found in repository.
Explanation	The specified artifact does not exist in the repository.
Action	Verify that the correct artifact is used.
SPMREPE0050	Unable to list repositories due to {0}
Explanation	Failures occurred while reading repository configuration.
Action	Ensure read access is provided for repositories defined in the SPM profile.
SPMREPE0051	Unable to list repositories due to {0}
Explanation	Failures occurred while reading repository configuration.
Action	Ensure read access is provided for the repositories defined in the SPM profile.
SPMREPE0053	Location can not be null.
Explanation	When adding a new repository configuration, the location property must be provided.
Action	Provide a location for the repository being configured.
SPMREPE0054	Invalid content type: {0}
Explanation	The type of a repository must be either product or fix.
Action	Provide a valid repository type.
SPMREPE0055	Repository already configured for {0}
Explanation	A repository at this location is already configured.
Action	None required.
SPMREPE0057	{0} is an invalid path.
Explanation	The location cannot be represented as a valid URI.
Action	Use a valid path.

SPMREPE0058	Location does not exist: {0}
Explanation	There is no fix image archive at the specified location.
Action	Provide the location of an existing fix image archive.
SPMREPE0062	Unable to delete configuration properties: {0}
Explanation	The configuration properties for a repository could not be deleted.
Action	Manually delete the property file.
SPMREPE0064	Must specify repository type.
Explanation	The type argument for listing repositories cannot be null.
Action	Specify the repository type, either product or fix.
SPMREPE0065	No such repository - {0}
Explanation	There is no repository with the given ID.
Action	Use a known repository configuration.
SPMREPE0066	Source and destination arguments cannot be null.
Explanation	Both source and destination arguments must be specified for the import operation.
Action	Provide valid source and destination repository arguments.
SPMREPE0067	No such repository registered, {0}
Explanation	The source repository for the import operation does not exist.
Action	Provide a valid source repository argument.
SPMREPE0068	No such repository registered, {0}
Explanation	The destination repository for the import operation does not exist.
Action	Provide a valide destination repository.
SPMREPE0069	Incompatable repositories.
Explanation	The source and destination repositories must have the same content type.
Action	Ensure that both repositories are either product, or fix repositories.

SPMREPE0070	Cannot import into remote repository, {0}
Explanation	Importing into remote repositories is not supported.
Action	Specify a local repository as the destination.
SPMREPE0071	Unable to create path to provisioning configuration: {0}
Explanation	Unable to create provisioning configuration directory.
Action	Ensure that the Platform Manager configuration directory is writable.
SPMREPE0072	Invalid repository type: {0}
Explanation	The repository type must be product or fix.
Action	Specify a valid repository type.
SPMREPE0073	No repository name provided.
Explanation	A repository name must be provided for discovering fix repositories.
Action	Provide the repository name.
SPMREPE0074	Invalid server or repository name: {0}
Explanation	The server or name arguments contain invalid characters for a URL.
Action	Specify valid server and names for the fix repository.
SPMREPE0075	Repository discovery failed: No ProductRepositoryManagementService available
Explanation	Unable to discover product repositories as the necessary services are not active.
Action	See the logs to determine why the repository manager service is inactive.
SPMREPE0076	Repository discovery failed: {0}
Explanation	The repository manager service reported errors during discovery.
Action	See the logs for more information.
SPMREPE0077	Source repository cannot be null.
Explanation	A source repository must be specified for the export operation.
Action	Specify the local repository to use for export.

SPMREPE0078	Path cannot be null.
Explanation	The path to the destination archive must be specified for the export operation.
Action	Provide a path where the archive should be created.
SPMREPE0079	No such repository registered, {0}
Explanation	There is no repository with the given ID.
Action	Specify a valid source repository.
SPMREPE0080	Unsupported operation.
Explanation	Platform Manager cannot export from archive.
Action	Specify a local repository from which to export.
SPMREPE0081	Cannot export into existing file: {0}
Explanation	Exporting cannot be used to add to an existing archive.
Action	Specify the location to create a new archive.
SPMREPE0082	Artifact must be specified.
Explanation	An artifact argument for get dependencies was null.
Action	Specify the artifact for its list of dependencies.
SPMREPE0083	Source repository cannot be null.
Explanation	The source repository for get dependencies cannot be null.
Action	Specify a valid repository in which to search for dependencies.
SPMREPE0084	No such repository registered, {0}
Explanation	The specified repository does not exist.
Action	Specify a valid repository in which to search for dependencies.
SPMREPE0085	No such repository: {0}
Explanation	The specified repository does not exist.
Action	Specify a valid local repository to publish.

SPMREPE0086	Source and destination repositories are the same.
Explanation	The source and destination repositories must refer to different repositories.
Action	Specify valid repositories.
SPMREPE0087	{0} not found in repository.
Explanation	The specified artifact does not exist in the repository.
Action	Verify that the correct artifact is used.
SPMREPE0088	Unsupported operation.
Explanation	The publishing of local repositories is not supported in this release.
Action	None required.
SPMREPE0089	Unsupported operation.
Explanation	The unpublish operation is not supported for repository type.
Action	None required.
SPMREPE0090	No such repository registered, {0}
Explanation	The specified repository is not registered.
Action	Specify a valid repository, or add the repository.
SPMREPE0091	Failures occurred attempting to publish a repository: {0}
Explanation	Internal errors prevented the publish operation from completing.
Action	Depends on the specific error. Check the logs for the error details.
SPMREPE0092	The repository, {0}, is already published with context, {1}
Explanation	Specify the correct repository or republish to use a different context.
Action	To change context, unpublish, then republish with new context.
SPMREPE0093	Web publishing service is unavailable.
Explanation	The necessary service to publish repositories is not active.
Action	None required.

SPMREPE0094	Invalid context: {0}
Explanation	The context in the publish request may not be null and must start with /
SPMREPE0095	Invalid context: {0}
Explanation	The context must not be null and start with /
Action	Use a valid context.
SPMREPE0096	Repository {0}, is not published.
Explanation	The request assumes the repository has been published.
Action	None required.
SPMREPE0097	Failures detected while unpublishing repository: {0}
Explanation	The unpublishing operation failed.
Action	Depends on the type of failure. Check the logs for the error details.
SPMREPE0098	No credentials for accessing the remote fix repository, {0}, have been configured.
Explanation	You must provide user credentials to access remote repositories.
Action	Specify the user and password properties for the repository.
SPMREPE0099	The location of a repository is invalid: {0}
Explanation	The URI of a repository does not have a valid path.
Action	Specify a valid location when registering repositories.
SPMREPE0100	No repository found at the specified location: {0}
Explanation	The location specified did not match any known repository.
Action	Specify a valid location.
SPMREPE0101	No fix service available.
Explanation	A required service for managing fix repositories is unavailable.
Action	Review the Platform Manager logs for indications of fix service failures.

SPMREPE0103	{0} is an invalid path. It must be relative.
Explanation	To create a new local repository, you must use only relative paths.
Action	Specify a relative path.
SPMREPE0104	Login to repository, {1}, failed for user, {0},
Explanation	Repository configured with incorrect credentials.
Action	Reconfigure the repository credentials.
SPMREPE0105	Only one platform may be specified in the provided filter .
Explanation	The repository operation included a filter with multiple platforms.
Action	Specify only one platform in the filter and retry the operation.
SPMREPE0106	The repository, {0}, is currently in use.
Explanation	The operation cannot be processed until the specified repository becomes available.
Action	Retry when all provisioning operations are completed.
SPMREPE0107	Failed to load repository, {0}
Explanation	An error occurred while attempting to access the repository.
Action	Check the logs for the error details.
SPMREPE0108	Publish with non-default realm or roles is not supported.
Explanation	The requested operation is not supported.
Action	Retry the request without specifying a realm or roles.
SPMREPE0109	{0} is not in repository {1}
Explanation	Unable to export the specified fix into the archive because the fix does not reside in the source repository.
Action	Specify a different fix or repository.
SPMREPE0110	Invalid SDC installer properties
Explanation	The servers/production/versions property in the server.properties file is missing.
Action	This is an internal error and should be reported

SPMREPI0014	Importing into {0}
Explanation	Importing of artifacts is starting.
Action	None required.
SPMREPI0015	Import failed: {0}
Explanation	An import operation failed.
Action	See the installation log for more information.
SPMREPI0023	Creating local repository at {0}
Explanation	A new local repository is being created.
Action	None required.
SPMREPI0029	No matching products found in {0} repository
Explanation	The request to mirror a repository is ignored as none of the specified artifacts reside in the repository.
Action	None required.
SPMREPI0030	Import from {0} to {1} failed due to {2}
Explanation	The import operation failed.
Action	See the logs for more information.
SPMREPI0031	Importing all products from {0} to {1}
Explanation	All products in the source repository will be imported.
Action	None required.
SPMREPI0032	Importing products fro {0} to {1}
Explanation	A subset of products is being imported. The specific products are listed as subsequent log entries.
Action	None required.
SPMREPI0033	{0}
Explanation	The id of a product being imported.
Action	None required.

SPMREPI0034	Import from {0} to {1} was successful.
Explanation	The import operation completed successfully..
Action	None required.
SPMREPI0035	Exporting artifacts from {0} to {1}
Explanation	An export operation is starting.
Action	None required.
SPMREPI0036	Export from {0} to {1} failed due to {2}
Explanation	The export operation failed.
Action	See the logs for more information.
SPMREPI0056	The configuration of repository {0} has an invalid location property: {0}
Explanation	The location property is not a valid URL.
Action	Remove the repository.
SPMREPI0059	Unable to add repository, {0}, due to {1}
Explanation	The location is an invalid URL.
Action	Noe required.
SPMREPI0060	Unable to add repoistor, {0}, due to {1}
Explanation	The attempt to configure the remote repository failed.
Action	See the logs for more information.
SPMREPI0061	Failures occurred during removal of repository, {0}: {1}
Explanation	The repository configuration may not have been completely removed.
Action	See the logs for further information.
SPMREPI0063	Removed repository configuration, {0}
Explanation	The repository was successfully removed.
Action	None required.

SPMREPW0022	Unable to delete {0}
Explanation	The directory of the local repository to be created was not empty.
Action	None required.
SPMREPW0046	Failed to remove password handle for repository, {0}
Explanation	Cleanup of passman data was incomplete while removing the repository.
Action	None required.
SPMREPW0052	Unable to initialize repository, {0}, due to {1}
Explanation	The repository could not be validated.
Action	Remove the repository configuration.
SPMREPW0102	Failed to remove password handle for repository, {0}
Explanation	The passman cleanup was incomplete.
Action	None required.
SPMRMCE0001	Invalid input data.
Explanation	The submitted data failed to un-marshall or validate against the schema.
Action	Correct the reported problem in the input data and retry the request.
SPMRMCE0002	Internal Error processing the request.
Explanation	The server encountered an error and cannot execute the request.
Action	Contact your system administrator.
SPMRMCE0003	Invalid client request.
Explanation	The submitted client request is rejected by the server.
Action	Check the status code for more details or consult the Software AG Platform Manager documentation. Correct the problem and resubmit the request.
SPMRMCE0005	The requested functionality is not supported.
Explanation	Platform Manager does not support the requested functionality.
Action	See the Software AG Platform Manager documentation for the supported requests for this resource.

SPMRMCI0000	Configuration partial failure for runtime component: {0}, instance: {1} with type {2} - with linked exception:
Explanation	The configuration operation for the specified run-time component, instance, and type failed with the specified exception.
Action	Check the logs for the error details.
SPMRPIE0000	Use RepositoryService to create new repository configurations.
Explanation	The ConfigurationService cannot be used to add repository configurations.
Action	Use the RepositoryService to configure new repositories.
SPMTEME0000	Error occurred while reading the configuration instances for {0}
Explanation	The error occurred while creating a template that includes configuration information.
Action	Check whether the configuration instances for the specified runtime component are available by querying them explicitly. Check the logs for errors if the query fails.
SPMTEME0001	Error occurred while applying template {0}
Explanation	The error occurred when applying the specified template.
Action	Check the logs for more details.
SPMTEME0006	Error occurred during template creation {0}
Explanation	The error occurred when creating a template.
Action	Check the logs for more details about the error.
SPMTEME0012	Error occurred while executing a task with id: {0} and status: {1}
Explanation	Executing the specified task failed.
Action	Check the Platform Manager logs for more information.
SPMTEME0014	Deleting configuration instance with type {0} is not supported operation.
Explanation	Platform Manager does not support deleting the configuration instance with the specified type.
Action	Check the warning to determine if any damage to the system will occur.

SPMTEME0015	Skipping deleting configuration instance ({0}) for runtime component - {1}. Reason: {2}
Explanation	The error occurred because either the runtime component, or a configuration manager for the configuration instance is missing in the Platform Manager.
Action	Check if the specified runtime component is present or that the appropriate SPM plugin is installed. Check the warning to determine if any damage to the system will occur.
SPMTEME0016	Skipping deleting configuration instance ({0}) for the missing runtime component - {1}
Explanation	The specified runtime component is missing in the Platform Manager.
Action	Check if the specified runtime component is present in the Platform Manager. Check the warning to determine if any damage to the system will occur.
SPMTEME0017	Task with id: {0} and status {1} did not finish in the expected period of time.
Explanation	The timeout period, configured through a system property, is not sufficient to complete the task.
Action	Try to execute the operation again or increase the timeout value.
SPMTEME0018	Task with id: {0} and status: {1} was canceled.
Explanation	The execution of the operation is interrupted.
Action	Try to execute the operation again.
SPMTEME0019	Error occurred during execution of operation {0} on template {1}
Explanation	The error occurred when executing the specified operation.
Action	Check the logs for more details about the error.
SPMTEMW0002	Applying the template completed with the following warnings: {0}
Explanation	When applying a template, unexpected events occurred, but they did not prevent the process from executing.
Action	Check the warnings with extra caution to determine whether any damage to the system will occur.

SPMTEMW0003	Skipping creating configuration instance ({0}) for the missing runtime component - {1}
Explanation	The specified runtime component is missing in the specified Platform Manager.
Action	Check if the specified runtime component is present. Check the warning to determine if any damage to the system will occur.
SPMTEMW0004	Skipping creating configuration instance ({0}) for runtime component - {1}. Reason: {2}
Explanation	The error occurred because either the runtime component, or a configuration manager for the configuration instance is missing in the specified Platform Manager.
Action	Check if the specified runtime component is present and that the appropriate Platform Manager plugin is installed. Check the warning to determine if any damage to the system will occur.
SPMTEMW0005	Creating configuration instance with type {0} is not supported operation.
Explanation	Platform Manager does not support the create operation for the configuration instance with the specified type.
Action	Check the warning to determine if any damage to the system will occur.
SPMTEMW0007	Skipping updating configuration instance ({0}) for the missing runtime component - {1}
Explanation	The specified runtime component is missing in the Platform Manager.
Action	Check if the specified runtime component is present. Check the warning to determine if any damage to the system will occur.
SPMTEMW0008	Template operation "{1}" completed with the following warnings: {0}
Explanation	During template operation "{1}" unexpected events occurred but they did not prevent the operation from completing.
Action	Check the warnings to figure out what was successfully processed as part of operation "{1}".
SPMTEMW0009	Skipping updating configuration instance ({0}) for runtime component - {1}. Reason: {2}
Explanation	The error occurred because either the runtime component, or a configuration manager for the configuration instance is missing in the Platform Manager.
Action	Check if the specified runtime component is present or that the appropriate Platform Manager plugin is installed. Check the warning to determine if any damage to the system will occur.

SPMTEMW0010	Skipping storage of item with id : {0} . Reason : {1}
Explanation	The issue occurred during item serialization.
Action	Check the Platform Manager logs for more information about the error.
SPMTEMW0011	Updating configuration instance with type {0} is not supported operation.
Explanation	Platform Manager does not support updating the configuration instance with the specified type.
Action	Check the warning to determine if any damage to the system will occur.
SPMTEMW0013	Skipping storage of configuration instance ({0}) for runtime component - {1}. Reason: {2}
Explanation	An error occurred while loading the configuration instance and it will not be included in the template that will be created.
Action	Check the logs for more details about the error.
SPMTERE0000	Template log file not available.
Explanation	The Platform Manager log access service was unable to locate the template log file.
Action	Contact Software AG Global Support.
SPMTERE0001	Installer and Update Manager logs unavailable.
Explanation	The Installer or Update Manager logs cannot be located.
Action	Contact Software AG Global Support.
SPMUTLE0000	Invalid URL.
Explanation	The URL does not fit the specification.
Action	Specify a valid URL.
SPMUTLE0001	URL string cannot be parsed as a URI reference
Explanation	The URL does not fit the specification.
Action	Specify a valid URL.

SPMUTLE0004	Unable to collect NetworkInterface details; caught this: type({0}), msg({1})
Explanation	An attempt to use java.lang.NetworkInterface to collect MAC address information failed.
Action	Determine whether the current user has permission to collect this information.
SPMUTLE0005	Collected {0} MAC addresses before failure.
Explanation	This message will always be logged with SPMULTLE0004
Action	No action required.

20 Process Engine Messages

JL.execution(PRTMessageConstants.AL_ERRPUB_OPTIMIZE) – {1}: exception publishing Optimize log event {2}: {0}

JL.execution(PRTMessageConstants.AL_ERRPUB_OPTIMIZE_STEP) – {1}, {2}: exception publishing Optimize log event {3}: {0}

JL.execution(PRTMessageConstants.AL_ERR_GET_AUDIT_RUNTIME) – {1}: exception getting audit runtime: {0}

JL.execution(PRTMessageConstants.AL_ERR_GET_STACK) – {1}, {2}: exception retrieving process stack: {0}

JL.execution(PRTMessageConstants.AL_NO_MID_FOR_PID) – {1}: exception getting model identifier: {0}

JL.execution(PRTMessageConstants.AL_PIPEERR_STEP0) – {1}, {2}: exception trying to encode step pipeline: {0}

JL.execution(PRTMessageConstants.EP_ERRPUB_EDA) – {1}, {2}: exception publishing EDA Event: {0}

JL.execution(PRTMessageConstants.EP_PIPEERR0) – {1}, {2}: exception encoding transition pipeline to {3}: {0}

JL.execution(PRTMessageConstants.EP_SENDDTX0) – {0}, {1}: sending live transition to {2}

JL.execution(PRTMessageConstants.EP_SENDDTX0_DEADPATH) – {0}, {1}: sending dead transition to {2}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_CHANGE) – {0}: sending process instance change EDA Event: {1}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_ERROR) – {0}: sending process error EDA Event: {1}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_LOG_CUSTOM_ID) – {0}: sending process log custom id EDA Event: {1}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_LOG_MESSAGE) – {0}: sending process log message EDA Event: {1}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_STEP_CHANGE) – {0}, {1}: sending process step instance change EDA Event: {2}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_STEP_ERROR) – {0}, {1}: sending process step error EDA Event: {2}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_STEP_LOOP_CHANGE) – {0}, {1}: sending process step loop instance change EDA Event: {2}

JL.execution(PRTMessageConstants.EP_SEND_PROCESS_STEP_TRANSITION) – {0}, {1}: sending process step instance transition EDA Event: {2}

JL.execution(PRTMessageConstants.IL_ERR_CREATE_LOGGER) – {1}: exception creating instance logger: {0}

JL.execution(PRTMessageConstants.IM_CANCELLEDOK) – {0}, MID={1}, MVer={2}: process cancelled

JL.execution(PRTMessageConstants.IM_CREATEOK) – {0}, MID={1}, MVer={2}: process started

JL.execution(PRTMessageConstants.IM_FAILEDOK) – {0}, MID={1}, MVer={2}: process failed

JL.execution(PRTMessageConstants.IM_FINISHOK) – {0}, MID={1}, MVer={2}: process completed

JL.execution(PRTMessageConstants.IM_RECREATE) – {0}, MID={1}, MVer={2}: process restarting

JL.execution(PRTMessageConstants.IM_SVC_CANCEL_TX) – {0}, {1}: transitioning to cancel step

JL.execution(PRTMessageConstants.IM_TRYCREATE0) – {0}, {1}: new process instance created on {2}

JL.execution(PRTMessageConstants.IM_TRYCREATE2) – {0}, {1}: using existing pid on {2}

JL.execution(PRTMessageConstants.IM_UPDATE_TRACK) – {0}: updated track count by {1} to {2}

JL.execution(PRTMessageConstants.IS_RETRYLIMIT) – {0}, {1}: step level retry count exceeded for service: {2}

JL.execution(PRTMessageConstants.IS_SVC_RETRY) – {1}, {2}: step level retry {3} of {4} in {5} ms: {0}

JL.execution(PRTMessageConstants.IS_THRESHOLD) – {0}, {1}: thread threshold detected; retry abandoned

JL.execution(PRTMessageConstants.PRT_EXCEPTION) – Exception: {0}

JL.execution(PRTMessageConstants.SDA_AFTER_STEP_PIPE) – {0}, {1}: after step pipeline: {2}

JL.execution(PRTMessageConstants.SDA_BEFORE_STEP_PIPE) – {0}, {1}: before step pipeline: {2}

JL.execution(PRTMessageConstants.SDA_BEFORE_STEP_PIPE)...0 – {0}, {1}: before step pipeline: {2}

JL.execution(PRTMessageConstants.SDA_CHANGE_VERSION) – {0}, {1}: process version changed from {2} to {3}

JL.execution(PRTMessageConstants.SDA_DEAD_INGORED) – {0}, {1}: synchronization point ignoring dead path from {2}

JL.execution(PRTMessageConstants.SDA_ERR_GENERAL) – {1}, {2}: exception executing step: {0}

JL.execution(PRTMessageConstants.SDA_ERR_HANDLEEVT_CHANGE) – {1}: exception failing the process: {0}

JL.execution(PRTMessageConstants.SDA_ERR_OUT) – {1}, {2}: exception sending output {3} of {4}: {0}

JL.execution(PRTMessageConstants.SDA_ERR_SAVECTX) – {1}, {2}: exception saving step context: {0}

JL.execution(PRTMessageConstants.SDA_ERR_TX) – {1}, {2}: exception updating track count: {0}

JL.execution(PRTMessageConstants.SDA_EVAL0) – {0}, {1}: transition condition {2} evaluated to {3}

JL.execution(PRTMessageConstants.SDA_EVALF) – {0}, {1}: transition condition {2} is False

JL.execution(PRTMessageConstants.SDA_EVALT) – {0}, {1}: transition condition {2} is True

JL.execution(PRTMessageConstants.SDA_EXC_SEND_DEAD_PATH) – {1}, {2}: unable to send dead path transition with the following exception: {0}

JL.execution(PRTMessageConstants.SDA_INVALID_STEP) – {1}, {2}: deprecated step found: {0}

JL.execution(PRTMessageConstants.SDA_LOGCUST) – {0}, {1}: logging custom audit data

JL.execution(PRTMessageConstants.SDA_LOG_STEP_INPUT_DATA) – {0}, {1}: logging step input data

JL.execution(PRTMessageConstants.SDA_LOG_STEP_LOOP_INPUT_DATA) – {0}, {1}: logging step loop input data

JL.execution(PRTMessageConstants.SDA_LOG_STEP_LOOP_OUTPUT_DATA) – {0}, {1}: logging step loop output data

JL.execution(PRTMessageConstants.SDA_LOG_STEP_OUTPUT_DATA) – {0}, {1}: logging step output data

JL.execution(PRTMessageConstants.SDA_NOPIPE) – {0}, {1}: step not executed, enqueueing event

JL.execution(PRTMessageConstants.SDA_PROCSTATS) – {0}, {1}: pushing step on suspended list

JL.execution(PRTMessageConstants.SDA_PUBLISH1) – {0}, {1}: published output document {2}

JL.execution(PRTMessageConstants.SDA_RETRIES) – {0}, {1}: step iteration count exceeded

JL.execution(PRTMessageConstants.SDA_SVC) – {0}, {1}: executing {2} in package {3}

JL.execution(PRTMessageConstants.SDA_SVC_ERR_MSG) – {1}, {2}: exception invoking service {3}: {0}

JL.execution(PRTMessageConstants.SDA_SVC_ERR_TX) – {0}, {1}: transitioning to error step {2}

JL.execution(PRTMessageConstants.SDA_SVC_SENDOUT) – {0}, {1}: sent {2} output events

JL.execution(PRTMessageConstants.SDA_SYNCBEG) – {0}, {1}: start step execution

JL.execution(PRTMessageConstants.SDA_SYNCEND) – {0}, {1}: end step execution

JL.execution(PRTMessageConstants.SDA_TDELTA0) – {0}, {1}: no track count change

JL.execution(PRTMessageConstants.SDA_TXASYNCH) – {0}, {1}: publishing transition to {2} on {3}

JL.execution(PRTMessageConstants.SDA_TXASYNCH_DEADPATH) – {0}, {1}: sending Dead Path PTE to {2} on {3}

JL.execution(PRTMessageConstants.SDA_TXNOCOND) – {0}, {1}: sending dead transition to {2}

JL.execution(PRTMessageConstants.SDA_TXSEND) – {0}, {1}: sending live transition to {2}

JL.execution(PRTMessageConstants.SDA_UNABLE_INVOKE_ERROR_STEP_LOCALLY) – {1}, {2}: unable to invoke error step locally with the following exception: {0}

JL.execution(PRTMessageConstants.SDA_UNSATISFIED_JOIN) – {0}, {1}: taking unsatisfied join transition {2}

JL.execution(PRTMessageConstants.SDC_ABSOLUTE_TIME_INVALID) – {0}, {1}: absolute timeout type is invalid

JL.execution(PRTMessageConstants.SDC_DROPQ0) – {0}, {1}: dropping {2} events

JL.execution(PRTMessageConstants.SDC_HANDLEJOINTIMER) – {0}, {1}: handling join timeout

JL.execution(PRTMessageConstants.SDC_HANDLEPROCTIMER) – {0}: handling process timeout

JL.execution(PRTMessageConstants.SDC_HANDLESTEPTIMER) – {0}, {1}: handling step timeout

JL.execution(PRTMessageConstants.SDC_JOINTIME) – {0}, {1}: starting join timeout

JL.execution(PRTMessageConstants.SDC_JOIN_RSLT) – {0}, {1}: join evaluates to {2}

JL.execution(PRTMessageConstants.SDC_PROCTIME) – {0}: starting process timeout

JL.execution(PRTMessageConstants.SDC_QUEUE_SZ) – {0}, {1}: {2} events in the queue. Event names: {3}. Join string: {4}. Join state: {5}

JL.execution(PRTMessageConstants.SDC_STEPTIME) – {0}, {1}: starting step timeout

JL.execution(PRTMessageConstants.SDC_TOHANDLE) – {0}, {1}: transitioning to timeout handler

JL.execution(PRTMessageConstants.SDC_TOPIPEERR) – {1}, {2}: exception assembling pipeline: {0}

JL.execution(PRTMessageConstants.SD_ACTIVITY_NOT_RUNNING) – {0}, {1}: boundary event {2} ignored because activity is not running

JL.execution(PRTMessageConstants.SD_CORRELATE) – {0}, {1}: using correlation service {2}

JL.execution(PRTMessageConstants.SD_CORRELATE_DISABLED) – {0}, {1}: correlated to disabled model {2} version {3}

JL.execution(PRTMessageConstants.SD_CORRELATE_ERR) – {1}, {2}: exception invoking correlation svc {3}: {0}

JL.execution(PRTMessageConstants.SD_CORRELATE_FIELD) – {0}, {1}: using correlation field {2}

JL.execution(PRTMessageConstants.SD_CORRELATE_NEW) – {0}, {1}: correlated to process id

JL.execution(PRTMessageConstants.SD_CORRELATE_TN) – {0}, {1}: correlating to TN conversation id

JL.execution(PRTMessageConstants.SD_CORRELBADMID) – {0}, {1}: correlated to {2}, expected {3}

JL.execution(PRTMessageConstants.SD_ERR_DISPATCH) – {1}, {2}: exception dispatching step: {0}

JL.execution(PRTMessageConstants.SD_ERR_HANDLEEVT) – {1}, {2}: exception handling transition event: {0}

JL.execution(PRTMessageConstants.SD_INPUTMATCH) – {0}, {1}, document {3} is a valid published input

JL.execution(PRTMessageConstants.SD_INVOKEDISPATCH) – {0}, {1}: dispatching step on new execution thread

JL.execution(PRTMessageConstants.SD_NOINPUT1) – {0}, {1}: document {3} is NOT a valid published input

JL.execution(PRTMessageConstants.SD_NOSTEPDEF) – {0}, {1}: no process fragment contains this step

JL.execution(PRTMessageConstants.SD_PTE) – {0}, {1}: handling transition event from {2}

JL.execution(PRTMessageConstants.SD_PUBLISH) – {0}, {1}: handling native document {3} on {2}

JL.execution(PRTMessageConstants.SD_STARTSTEP) – {0}, {1}: starting step execution

JL.execution(PRTMessageConstants.SD_STEPSYNCH) – {0}, {1}: running step on same execution thread

JL.execution(PRTMessageConstants.SM_ACTDONE) – {0}: process status changed to {1}

JL.execution(PRTMessageConstants.SM_RESTARTPROC) – {0}: restarting process at step {1}

JL.execution(PRTMessageConstants.SM_RESUMEPROC) – {0}: resuming process at {1}

JL.execution(PRTMessageConstants.SM_START) – {0}: processing {1} request

JL.execution(PRTMessageConstants.ST_DB_CONNECT_ERR1) – {1}: exception connecting to database: {0}

JL.execution(PRTMessageConstants.ST_DB_CONNECT_ERR2) – {1}, {2}: exception connecting to database: {0}

JL.execution(PRTMessageConstants.ST_LOCK_FAIL) – {0}, {1}: step lock FAILED

JL.execution(PRTMessageConstants.ST_LOCK_SUCCESS) – {0}, {1}: step locked

JL.execution(PRTMessageConstants.ST_LOCK_TRY) – {0}, {1}: attempting step lock

JL.execution(PRTMessageConstants.TC_INVOKE_CONTROL_TASKS) – {0}: invoking wm.task.taskclient:controlTasks with control "{1}"

JL.execution(PRTMessageConstants.TC_INVOKE_CONTROL_TASKS_ERR) – {1}: exception invoking wm.task.taskclient:controlTasks service: {0}

JL.execution(PRTMessageConstants.TN_ERR_PROFIELD) – {1}: exception fetching data for field {2}: {0}

JL.execution(PRTMessageConstants.TN_ERR_PROSTORE) – {1}: exception fetching data from TN profile store: {0}

JL.execution(PRTMessageConstants.TO_CANCEL_JOIN) – {0}, {1}: cancelling join timeout

JL.execution(PRTMessageConstants.TO_CANCEL_PROCESS) – {0}: cancelling process timeout

JL.execution(PRTMessageConstants.TO_CANCEL_STEP) – {0}, {1}: cancelling step timeout

JL.execution(PRTMessageConstants.TO_ERR_INVOKE) – {1}, {2}: exception invoking timeout: {0}

JL.execution(PRTMessageConstants.TO_KILLSTEPTHR) – {0}, {1}: killing step execution thread

JL.execution(PRTMessageConstants.TO_MISSING_JOIN_TIMER_TYPE) – {0}, {1}: cannot start Join timeout -- type not specified

JL.execution(PRTMessageConstants.TO_MISSING_PROCESS_TIMER_TYPE) – {0}: cannot start Process timeout -- type not specified

JL.execution(PRTMessageConstants.TO_MISSING_STEP_TIMER_TYPE) – {0}, {1}: cannot start Step timeout -- type not specified

JL.execution(PRTMessageConstants.TO_NO_TRANSITION) – {1}, {2}: no transition to handle timeout: {0}

JL.execution(PRTMessageConstants.TO_STRT_NO_DURATION) – {0}, {1}: did not start timer, no end time specified.

JL.execution(PRTMessageConstants.TO_STRT_TIMER) – {0}, {1}: starting timeout: {2}

JL.execution(PRTMessageConstants.TO_TIMEOUT_JOIN) – {0}, {1}: join timer has expired

JL.execution(PRTMessageConstants.TO_TIMEOUT_PROCESS) – {0}: process timer has expired

JL.execution(PRTMessageConstants.TO_TIMEOUT_STEP) – {0}, {1}: step timer has expired

JL.general(PRTMessageConstants.ADM_MWS_INIT_ERROR) – Unable to initialize MWS library. Business calendar based timeouts will not be able to be evaluated.

JL.general(PRTMessageConstants.ADM_MWS_INIT_ERROR2) – Exception trying to initialize MWS library: {0}

JL.general(PRTMessageConstants.ADM_MWS_INIT_ERROR_GET_POOL) – Error trying to get JDBC pool configuration using functional alias {0}. Business calendar based timeouts will not be able to be evaluated.

JL.general(PRTMessageConstants.ADM_MWS_INIT_ERROR_GET_POOL2) – Exception trying to get JDBC pool configuration: {0}

JL.general(PRTMessageConstants.AL_CANTPOP) – Exception trying to pop audit log context: {0}

JL.general(PRTMessageConstants.AL_CANTPUSH) – Exception trying to push audit log context: {0}

JL.general(PRTMessageConstants.AL_CUSTNOT) – Custom logging: cannot convert {0} to logging type {1} (value {2})

JL.general(PRTMessageConstants.AL_CUSTNOU0) – Custom logging: cannot find value for {0}.{1} on path {2}

JL.general(PRTMessageConstants.AL_ERRPUB1) – Exception publishing Audit Log Event {1}: {0}

JL.general(PRTMessageConstants.AL_ERRPUB_OPTIMIZE) – Exception publishing Optimize Log Event {1}: {0}

JL.general(PRTMessageConstants.AL_ERR_GET_AUDIT_RUNTIME2) – Exception getting audit runtime: {0}

JL.general(PRTMessageConstants.AL_ERR_REG_LOGGER) – Exception registering Process Logger: {0}

JL.general(PRTMessageConstants.AL_NO_MID_FOR_PID) – {1}: exception getting model identifier: {0}

JL.general(PRTMessageConstants.AL_PIPEERR_STEP0) – Exception trying to encode step pipeline for {1}: {0}

JL.general(PRTMessageConstants.BT_CFG_ERROR) – [MID={1}] Problem reading BrainTribe config file: "{2}". {0}

JL.general(PRTMessageConstants.DASHBOARD) – Dashboard

JL.general(PRTMessageConstants.DASHBOARD_DIAGNOSTIC) – Diagnostic

JL.general(PRTMessageConstants.DASHBOARD_ENVIRONMENT) – Environment

JL.general(PRTMessageConstants.DASHBOARD_ENV_AUDIT_SETTINGS) – Audit Logging Settings

JL.general(PRTMessageConstants.DASHBOARD_ENV_CONTROL_TRIGGER) – Standard Control Triggers

JL.general(PRTMessageConstants.DASHBOARD_ENV_CR) – Content Repository View

JL.general(PRTMessageConstants.DASHBOARD_ENV_JDBC) – JDBC Connections

JL.general(PRTMessageConstants.DASHBOARD_ENV_JMS_TRIGGER) – JMS Control Trigger

JL.general(PRTMessageConstants.DASHBOARD_ENV_SETTINGS) – Process Engine Settings

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_AUDITLOG) – Audit Logging Status

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_AUDIT_LOGGING) – Audit Logging

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_BROKER_PUSH) – Broker Push

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_BUSINESS_CALENDAR) – Business Calendars

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_BUSINESS_CALENDARS) – Business Calendars

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_CHECK) – Health Check

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_CONTROL) – Control Triggers

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_DBMS) – DBMS Status

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_DB_SCHEMA) – Database Schema Compatibility

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_EFORM_LISTENER) – E-form Listener

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_JMS) – JMS Control Status

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_JMS_MSG) – JMS

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_OPTIMIZE) – Optimize Subsystem

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_OPTIMIZE_MSG) – Optimize Logging

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_PA_DB) – Process Audit Database

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_PE_DB) – Process Engine Database

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_RESTART_TIMERS) – Restart Timers

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_STARTUP_MESSAGES) – Startup Messages

JL.general(PRTMessageConstants.DASHBOARD_HEALTH_STORAGE) – Storage

JL.general(PRTMessageConstants.DASHBOARD_PROCESS) – Process

JL.general(PRTMessageConstants.DASHBOARD_PROCESS)...0 – Process Engine

JL.general(PRTMessageConstants.DASHBOARD_PROCESSLOG_ALL_EVENTS) – 5 - Process and All Events and Activities

JL.general(PRTMessageConstants.DASHBOARD_PROCESSLOG_ERRORS) – 2 - Errors only

JL.general(PRTMessageConstants.DASHBOARD_PROCESSLOG_NONE) – 1 - None

JL.general(PRTMessageConstants.DASHBOARD_PROCESSLOG_PROCESS) – 3 - Process only

JL.general(PRTMessageConstants.DASHBOARD_PROCESSLOG_START) – 4 - Process and Start Events

JL.general(PRTMessageConstants.DASHBOARD_PROCESSLOG_UNKNOWN) – Unknown

JL.general(PRTMessageConstants.DASHBOARD_PROCESS_AUDIT_ASYNC) – Asynchronous

JL.general(PRTMessageConstants.DASHBOARD_PROCESS_AUDIT_DB) – Database

JL.general(PRTMessageConstants.DASHBOARD_PROCESS_AUDIT_FILE) – File

JL.general(PRTMessageConstants.DASHBOARD_PROCESS_AUDIT_SYNC) – Synchronous

JL.general(PRTMessageConstants.DASHBOARD_PROCESS_SETTINGS) – Settings

JL.general(PRTMessageConstants.DASHBOARD_RESTART_EFORM_FAIL) – Failed to restart e-form listener for {0}.

JL.general(PRTMessageConstants.DASHBOARD_RESTART_EFORM_SUCCESS) – Restart of e-form listener: {0} successful.

JL.general(PRTMessageConstants.DASHBOARD_STATUS_NO) – No

JL.general(PRTMessageConstants.DASHBOARD_STATUS_SUSPENDED) – Suspended

JL.general(PRTMessageConstants.DASHBOARD_STATUS_YES) – Yes

JL.general(PRTMessageConstants.DUP_CHK_BEGIN) – CheckDuplicates processing {0}, uuid, {1}

JL.general(PRTMessageConstants.DUP_CHK_END) – CheckDuplicates processed {0}, uuid, {1}, status, {2}

JL.general(PRTMessageConstants.DUP_CHK_ISEXP) – CheckDuplicates throwing ISRuntimeException {0}, uuid, {1}

JL.general(PRTMessageConstants.EF_CFG_ERROR) – [MID={1}] Problem reading E-form config file: "{2}". {0}

JL.general(PRTMessageConstants.EF_LISTENER_ADDED) – [MID={0}] Now listening to path: "{1}" for e-Forms on jcr "{2}"

JL.general(PRTMessageConstants.EF_LISTENER_ADD_ERROR) – [MID={1}] Error adding listener to Content Repository "{2}". {0}

JL.general(PRTMessageConstants.EF_LISTENER_ALREADY_EXISTS) – [MID={0}] Content Repository currently has a listener listening in that location. No new listener added to listening path: "{1}" for e-Forms on jcr "{2}".

JL.general(PRTMessageConstants.EF_LISTENER_CHANGE_NOTALLOWED) – [MID={0}] Unable to change listener please disable all other models currently using this listener: "{1}"

JL.general(PRTMessageConstants.EF_LISTENER_DOCNOTFOUND) – [MID={0}] Cannot start e-form process because doc type: "{1}" does not exist. For e-form instance at: "{2}". Please recreate the e-form doc or rebuild the model(s).

JL.general(PRTMessageConstants.EF_LISTENER_ERROR) – [MID={1}] Error with Content Repository "{2}". Check if the repo is running, login credentials and repo connection information is correct. {0}

JL.general(PRTMessageConstants.EF_LISTENER FIRED) – [MID={0}] Trying to publish E-form instance "{1}" for template "{2}". With doc type of "{3}". If process does not start please check error log for any pub.publish errors. IData:{4}

JL.general(PRTMessageConstants.EF_LISTENER_FIRED)...0 – [MID={0}] Trying to publish E-form instance "{1}" for template "{2}". With doc type of "{3}". If process does not start please check error log for any pub.publish errors. IData:{4}

JL.general(PRTMessageConstants.EF_LISTENER_NOTCONFIGURED) – [MID={0}] Content Repository "{1}" not configured.

JL.general(PRTMessageConstants.EF_LISTENER_NO_DOCS) – Content Repository currently has no models associated to it. No reason to restart the repository at this time.

JL.general(PRTMessageConstants.EF_LISTENER_PORTS_NOTADDED) – [MID={0}] Cannot edit access for PORT 15006. Please ensure to manually add access for "wm.prt.eforms:update" "wm.server:connect" "wm.server:disconnect" "wm.server:ping".

JL.general(PRTMessageConstants.EF_LISTENER_REMOVED) – [MID={0}] Listener for e-Forms at path: "{1}" has been disabled from jcr "{2}"

JL.general(PRTMessageConstants.EF_LISTENER_REMOVE_ERROR) – [MID={1}] Error disabling/removing listener from Content Repository "{2}". {0}

JL.general(PRTMessageConstants.EF_LISTENER_RESTART_ERROR) – [MID={1}] Error restarting listener(s) to Content Repository "{2}". {0}

JL.general(PRTMessageConstants.EF_LISTENER_RESTART_MODEL_NOTENABLED) – No model(s) enabled using this listener "{0}". Listener will not be restarted.

JL.general(PRTMessageConstants.EF_METHOD_SUCCEEDED) – The method succeeded.

JL.general(PRTMessageConstants.EF_PASS_ERROR) – [MID={1}] Cannot retrieve password: "{2}". {0}

JL.general(PRTMessageConstants.EF_PUBLISH_COULD_NOT_CREATE_DOC) – Could not create the IS document type "{0}" from e-form instance "{1}"; make sure the e-form instance contents matches the IS document type.

JL.general(PRTMessageConstants.EF_PUBLISH_DOCNOTFOUND) – Cannot publish the e-form as an IS document because the IS document type "{0}" does not exist. Please create the IS document type from your e-form template.

JL.general(PRTMessageConstants.EF_PUBLISH_DOC_PUBLISH_FAILED) – Error publishing e-form instance: {0}

JL.general(PRTMessageConstants.EF_PUBLISH_FILENOTFOUND) – Cannot publish the e-form as an IS document because the e-form instance file "{0}" does not exist.

JL.general(PRTMessageConstants.EF_PUBLISH_INPUTS_NOT_PROVIDED) – The required input values were not provided; for this service though some inputs are optional you must provide either (instanceName and instanceByteStream) or (instanceFilePath). If both sets are provided, then (instanceName and instanceByteStream), takes precedence.

JL.general(PRTMessageConstants.EF_PUBLISH_PUBLISH_ATTEMPT) – Trying to publish e-form instance "{0}" as IS document type "{1}". If any associated processes do not start, then please check the error log for any pub.publish:publish errors.

JL.general(PRTMessageConstants.EF_PUBLISH_TEMPLATE_NOT_PROVIDED) – The required input value, templateName, was not provided.

JL.general(PRTMessageConstants.EP_PIPEERR0) – Exception encoding transition pipeline: {0}

JL.general(PRTMessageConstants.EP_SENDERR) – Exception during send: {0}

JL.general(PRTMessageConstants.HEALTHCHECK_AUDITLOG_DB_RED) – Process audit database could not be accessed

JL.general(PRTMessageConstants.HEALTHCHECK_AUDITLOG_INIT_RED) – Error initializing audit logging

JL.general(PRTMessageConstants.HEALTHCHECK_AUDITLOG_RED) – Process Logger is either not enabled or not configured for the database

JL.general(PRTMessageConstants.HEALTHCHECK_BC_RED) – MWS library is not initialized

JL.general(PRTMessageConstants.HEALTHCHECK_BC_YELLOW) – JDBC pool functional alias "CentralUsers" is not configured

JL.general(PRTMessageConstants.HEALTHCHECK_BROKER_RED) – ControlTrigger is not enabled

JL.general(PRTMessageConstants.HEALTHCHECK_BROKER_YELLOW) – Broker is not configured

JL.general(PRTMessageConstants.HEALTHCHECK_JMS_RED) – JMSControlTrigger is not enabled

JL.general(PRTMessageConstants.HEALTHCHECK_OPTIMIZE_NOT_CONFIGURED) – JMS Server URL is not configured

JL.general(PRTMessageConstants.HEALTHCHECK_OPTIMIZE_NOT_INIT) – Unable to initialize Optimize interface

JL.general(PRTMessageConstants.HEALTHCHECK_PADB_RED) – Process audit database could not be accessed

JL.general(PRTMessageConstants.HEALTHCHECK_PADB_VERSION_RED) – Process audit database schema version is incorrect. Minimum version expected is {0}, actual version is {1}.

JL.general(PRTMessageConstants.HEALTHCHECK_PEDB_RED) – Process engine database could not be accessed

JL.general(PRTMessageConstants.HEALTHCHECK_PEDB_VERSION_RED) – Process engine database schema version is incorrect. Minimum version expected is {0}, actual version is {1}.

JL.general(PRTMessageConstants.HEALTHCHECK_TRIGGER_RED) – Trigger {0} is not enabled.

JL.general(PRTMessageConstants.IL_ERR_CREATE_LOGGER) – Exception creating instance logger: {0}

JL.general(PRTMessageConstants.IL_ERR_LOG_ENABLED) – Exception determining if model is enabled for instance logging: {0}

JL.general(PRTMessageConstants.IM_CLEANUPEVERY) – Cache cleanup running every {0} seconds and every {1} instances

JL.general(PRTMessageConstants.IM_MODINACTIVE0) – Warning. Process model {0} is inactive

JL.general(PRTMessageConstants.IM_NOCLEANUP) – Instance cleanup disabled.

JL.general(PRTMessageConstants.IS_RETRYLIMIT) – Step Level Retry count exceeded for service: {0}

JL.general(PRTMessageConstants.IS_SVC_RETRY) – Exception: {0}. Step Level Retry configured for service: {1}. Retry {2} of {3} in {4} ms

JL.general(PRTMessageConstants.IS_THRESHOLD) – Thread Threshold detected. Retry abandoned for {0}.

JL.general(PRTMessageConstants.JMS_ALIAS_ERROR) – JMS Connection Alias for PE 'PE_NONTRANSACTIONAL_ALIAS' has not been configured.

JL.general(PRTMessageConstants.JMS_CREATE_CONNECTION_ERROR) – Error creating JMS connection alias: {0}

JL.general(PRTMessageConstants.JMS_CREATE_TOPIC_ERROR) – Error creating PE internal JMS topic: {0}

JL.general(PRTMessageConstants.JMS_UPDATE_CG_PERMISSIONS_ERROR) – Error updating client group permissions: {0}

JL.general(PRTMessageConstants.MM_BADFRAGERR) – Exception loading model fragment {1}: {0}

JL.general(PRTMessageConstants.MM_CANTMAKEDIR) – Unable to create directory: {0}

JL.general(PRTMessageConstants.MM_DELETING) – Deleting {0} old fragments from {1}

JL.general(PRTMessageConstants.MM_DELFILE) – Deleting XML file {0}

JL.general(PRTMessageConstants.MM_DELFRAG) – Deleting model fragment: {0}

JL.general(PRTMessageConstants.MM_FILEERR) – Exception reading fragment file {1}: {0}

JL.general(PRTMessageConstants.MM_NEWFRAG) – Adding new process fragment (pkg={0}, file={1})

JL.general(PRTMessageConstants.MM_READMOD) – Loading model fragment {0}

JL.general(PRTMessageConstants.MM_READPKG) – Loading process models in package {0}

JL.general(PRTMessageConstants.MON_INVALID_ENABLE_RESUBMISSION) – Enable Resubmission value must be either "True" or "False"

JL.general(PRTMessageConstants.MON_INVALID_LOGGING_LEVEL) – Invalid Logging Level

JL.general(PRTMessageConstants.MON_INVALID_LOG_TRANSITIONS) – Log Transitions value must be either "True" or "False"

JL.general(PRTMessageConstants.MON_INVALID_MODEL) – [MID={0}, MVers={1}] Model does not exist.

JL.general(PRTMessageConstants.MON_INVALID_PID) – Process instance {0} does not exist.

JL.general(PRTMessageConstants.MON_LOGGING_LEVEL_TOO_LOW) – [MID={0}] Logging level for Model cannot be set below minimum value of {1}.

JL.general(PRTMessageConstants.MON_OLD_MODEL_VERSION) – [MID={0}] QoS cannot be changed because it was generated from a pre-7.0 version of Modeler.

JL.general(PRTMessageConstants.OL_OPTIMIZE_INIT_ERROR) – Unable to get Optimize process data collector. Tracking enabled models will not be logged to Optimize.

JL.general(PRTMessageConstants.OL_OPTIMIZE_INIT_ERROR2) – Exception trying to get Optimize process data collector: {0}

JL.general(PRTMessageConstants.OL_OPTIMIZE_SHUTDOWN_ERROR) – Exception trying to shut down Optimize data collector: {0}

JL.general(PRTMessageConstants.PRT_EXCEPTION) – Exception: {0}

JL.general(PRTMessageConstants.PRT_MESSAGE) – {0}

JL.general(PRTMessageConstants.REPO_DEFAULT_ROOT_PATH) – (optional)

JL.general(PRTMessageConstants.REPO_EXE) – A RepositoryException occurred while trying to read data from the Content Repository: "{0}"

JL.general(PRTMessageConstants.REPO_FILE_DOES_NOT_EXIST) – File does not exist in repository

JL.general(PRTMessageConstants.REPO_IO_EXE) – An IOException occurred while trying to read data from the Content Repository: "{0}"

JL.general(PRTMessageConstants.REPO_PATH_NOT_FOUND_EXE) – A PathNotFoundException occurred while trying to read data from the Content Repository: "{0}"

JL.general(PRTMessageConstants.REPO_READ_NODE_ERROR) – An exception occurred while trying to read data from the Content Repository at: "{0}". Please check log for details.

JL.general(PRTMessageConstants.SDA_ERR_GENERAL) – Exception executing step {1}, {2}: {0}

JL.general(PRTMessageConstants.SDA_ERR_HANDLEVT_CHANGE) – Exception trying to fail the process *{1}: {0}

JL.general(PRTMessageConstants.SDA_ERR_OUT) – Exception sending output {1} of {2} for PID {3} SID {4}: {0}

JL.general(PRTMessageConstants.SDA_ERR_SAVECTX) – Exception saving step context {1}, {2}: {0}

JL.general(PRTMessageConstants.SDA_ERR_TX) – Exception updating track count {1}, {2}: {0}

JL.general(PRTMessageConstants.SDA_INVALID_STEP) – Exception: Deprecated step found {1}, {2}: {0}

JL.general(PRTMessageConstants.SDA_SVC_ERR_MSG) – Exception invoking service {1}, {2}, Svc={3}: {0}

JL.general(PRTMessageConstants.SDC_TOPIPEERR) – Exception assembling pipeline {1}, {2}: {0}

JL.general(PRTMessageConstants.SD_CORRELATE_ERR) – Error invoking correlation svc {1}: {0}

JL.general(PRTMessageConstants.SD_ERR_DISPATCH) – Exception dispatching step: {0}

JL.general(PRTMessageConstants.SD_ERR_HANDLEEVT) – Exception handling transition event: {0}

JL.general(PRTMessageConstants.SD_INPUTMATCH) – Document {0} is a valid published input

JL.general(PRTMessageConstants.SD_NOINPUT1) – Document {0} is NOT a valid published input

JL.general(PRTMessageConstants.SD_NOSTEP1) – Document {2} does not match to any step in process {0} on {1}

JL.general(PRTMessageConstants.SD_PUBLISH) – Handling native document {0} on {1}

JL.general(PRTMessageConstants.SD_STEPMATCH) – Document {2} matches step in process {0} on {1}

JL.general(PRTMessageConstants.ST_CACHE_CONNECT_ERR) – Exception: Unable to connect to cache!

JL.general(PRTMessageConstants.ST_CACHE_MGR_NOT_INITIALIZED) – Could not initialize cache manager

JL.general(PRTMessageConstants.ST_CACHE_NOT_INITIALIZED) – Could not initialize cache: {0}

JL.general(PRTMessageConstants.ST_CLEAN_DURATION) – Storage cleaner: Duration {0} ms

JL.general(PRTMessageConstants.ST_CLEAN_EVERY) – Storage cleaner: will run every {0} seconds

JL.general(PRTMessageConstants.ST_CLEAN_JDBC) – Storage cleaner: executing embedded SQL

JL.general(PRTMessageConstants.ST_CLEAN_PROC) – Storage cleaner: executing stored procedure

JL.general(PRTMessageConstants.ST_DB_CONNECT_ERR) – Exception: Unable to connect to database!

JL.general(PRTMessageConstants.ST_DB_ERR) – Storage exception: {0}

JL.general(PRTMessageConstants.ST_FAILED_PROC_EXPIRE) – Storage cleaner: expiration for failed processes: {0} seconds

JL.general(PRTMessageConstants.ST_LOCK_INSERT_FAIL) – Failed to insert Lock ID: {0} -- attempt {1} of {2}

JL.general(PRTMessageConstants.ST_NO_CLEAN) – Storage cleaner: Disabled

JL.general(PRTMessageConstants.ST_NO_CLEAN_FAILED_PROC) – Storage cleaner: clean up for completed processes is disabled

JL.general(PRTMessageConstants.ST_NO_LOCK) – Storage cleaner: cannot acquire lock. Exception: {0}

JL.general(PRTMessageConstants.ST_PROC_EXPIRE) – Storage cleaner: expiration for completed processes: {0} seconds

JL.general(PRTMessageConstants.TM_DFLTSPORT) – Default PE transport is {0}

JL.general(PRTMessageConstants.TM_DFLTSPORT_DEF) – Default PE transport is {0}; deferred

JL.general(PRTMessageConstants.TM_PUSH_ATTEMPT) – Pushing doctypes to Broker

JL.general(PRTMessageConstants.TM_PUSH_ERROR) – Broker push error: {0}

JL.general(PRTMessageConstants.TM_PUSH_NOCONN) – Not performing Broker push (not connected)

JL.general(PRTMessageConstants.TM_SEND) – Sending {2} over {0} to {1}

JL.general(PRTMessageConstants.TM_SENDABBR) – Sending {1} over {0}

JL.general(PRTMessageConstants.TN_DISPATCH0) – DocID={0}, DocType={1}, ConvId={2}: processing incoming TN document

JL.general(PRTMessageConstants.TN_ERR_BADFILTER) – Exception evaluating TN document filter: {0}

JL.general(PRTMessageConstants.TN_ERR_PROFIELD) – Exception fetching data for field {1}: {0}

JL.general(PRTMessageConstants.TN_ERR_PROSTORE) – Exception fetching data from TN profile store: {0}

JL.general(PRTMessageConstants.TN_NOMATCH) – DocID={0}, DocType={1}, ConvId={2}: no Model match for TN document

JL.general(PRTMessageConstants.TN_NOSTEPMATCH) – DocID={0}, DocType={1}, ConvId={2}, MID={3}: no Step match for TN document

JL.general(PRTMessageConstants.TN_STARTORJOIN) – ConvId={0}, PID={1}: starting/joining TN process

JL.general(PRTMessageConstants.TOU_INVALID_BIZ_CAL_ALIAS) – Business calendar alias {0} does not exist

JL.general(PRTMessageConstants.TOU_INVALID_BIZ_CAL_EVALUATOR) – Business calendar evaluator does not exist

JL.general(PRTMessageConstants.TOU_INVALID_BIZ_TIMEOUT) – Business timeout is invalid: {0}

JL.general(PRTMessageConstants.TO_ERR_INVOKE) – Exception invoking timeout for {1}, {2}: {0}

JL.general(PRTMessageConstants.TO_TIMER_THREAD_INTERRUPTED) – Timer thread interrupted: {0}

JL.string(PRTMessageConstants.BT_CFG_ERROR) – [MID={1}] Problem reading BrainTribe config file: "{2}": {0}

JL.string(PRTMessageConstants.DASHBOARD_PROCESSLOG_ALL_EVENTS) – 5 - Process and All Events and Activities

JL.string(PRTMessageConstants.EF_METHOD_SUCCEEDED) – The method succeeded.

JL.string(PRTMessageConstants.EF_PUBLISH_COULD_NOT_CREATE_DOC) – Could not create the IS document type "{0}" from e-form instance "{1}"; make sure the e-form instance contents matches the IS document type.

JL.string(PRTMessageConstants.EF_PUBLISH_DOCNOTFOUND) – Cannot publish the e-form as an IS document because the IS document type "{0}" does not exist. Please create the IS document type from your e-form template.

JL.string(PRTMessageConstants.EF_PUBLISH_DOC_PUBLISH_FAILED) – Error publishing e-form instance: {0}

JL.string(PRTMessageConstants.EF_PUBLISH_FILENOTFOUND) – Cannot publish the e-form as an IS document because the e-form instance file "{0}" does not exist.

JL.string(PRTMessageConstants.EF_PUBLISH_INPUTS_NOT_PROVIDED) – The required input values were not provided; for this service though some inputs are optional you must provide either (instanceName and instanceByteStream) or (instanceFilePath). If both sets are provided, then (instanceName and instanceByteStream), takes precedence.

JL.string(PRTMessageConstants.EF_PUBLISH_PUBLISH_ATTEMPT) – Trying to publish e-form instance "{0}" as IS document type "{1}". If any associated processes do not start, then please check the error log for any pub.publish:publish errors.

JL.string(PRTMessageConstants.EF_PUBLISH_TEMPLATE_NOT_PROVIDED) – The required input value, templateName, was not provided.

JL.string(PRTMessageConstants.HEALTHCHECK_PADB_VERSION_RED) – Process audit database schema version is incorrect. Minimum version expected is {0}, actual version is {1}.

JL.string(PRTMessageConstants.HEALTHCHECK_PEDB_VERSION_RED) – Process engine database schema version is incorrect. Minimum version expected is {0}, actual version is {1}.

JL.string(PRTMessageConstants.IM_CANCELLEDOK) – *PID={0}, MID={1}, MVer={2}: process cancelled

JL.string(PRTMessageConstants.IM_FAILEDOK) – *PID={0}, MID={1}, MVer={2}: process failed

JL.string(PRTMessageConstants.IM_UPDATE_TRACK) – *{0}, {1}: updated track count by {2} to {3}

JL.string(PRTMessageConstants.REPO_DEFAULT_ROOT_PATH) – (optional)

JL.string(PRTMessageConstants.REPO_EXE) – A RepositoryException occurred while trying to read data from the Content Repository: "{0}"

JL.string(PRTMessageConstants.REPO_FILE_DOES_NOT_EXIST) – File does not exist in repository

JL.string(PRTMessageConstants.REPO_IO_EXE) – An IOException occurred while trying to read data from the Content Repository: "{0}"

JL.string(PRTMessageConstants.REPO_PATH_NOT_FOUND_EXE) – A PathNotFoundException occurred while trying to read data from the Content Repository: "{0}"

JL.string(PRTMessageConstants.REPO_READ_NODE_ERROR) – An exception occurred while trying to read data from the Content Repository at: "{0}". Please check log for details.

JL.string(PRTMessageConstants.RULE_SVC_PIPEI) – Prepared pipeline to invoke Rule as: "{0}"

JL.string(PRTMessageConstants.SDA_BEFORE_STEP_PIPE) – *{0}, {1}: after step pipeline: {2}

JL.string(PRTMessageConstants.SDA_BEFORE_STEP_PIPE)...0 – *{0}, {1}: before step pipeline: {2}

JL.string(PRTMessageConstants.SDA_DEAD_INGORED) – *{0}, {1}: synchronization point ignoring dead path from {2}

JL.string(PRTMessageConstants.SD_ACTIVITY_IN_DEBUG) – Boundary event ignored because process was started in Debugger [PID={0}, ACTIVITY_SID={1}, BOUNDARY_SID={2}]

JL.string(PRTMessageConstants.SD_ACTIVITY_NOT_RUNNING) – *{0}, {1}: boundary event {2} ignored because activity is not running

JL.string(PRTMessageConstants.ST_CACHE_CONNECT_ERR) – Exception: Unable to connect to cache!

JL.string(PRTMessageConstants.ST_CACHE_MGR_NOT_INITIALIZED) – Could not initialize cache manager

JL.string(PRTMessageConstants.ST_CACHE_NOT_CONFIGURED) – Could not configure Shared Cache for Join locks

JL.string(PRTMessageConstants.ST_CACHE_NOT_INITIALIZED) – Could not initialize cache: {0}

JL.string(PRTMessageConstants.ST_LOCK_INSERT_FAIL) – Failed to insert Lock ID: {0} -- attempt {1} of {2}

JL.string(PRTMessageConstants.TU_DELTHR_CACHE) – Deleting thread from cluster cache, thread id={0}

JL.string(PRTMessageConstants.TU_SETTHR_CACHE_ALIVE) – Marking thread alive in cluster cache, thread id={0}

JL.string(PRTMessageConstants.TU_SETTHR_CACHE_KILLED) – Marking thread killed in cluster cache, thread id={0}

PRT.0101.0024E Exception trying to encode step pipeline for {1}: {0}

Explanation Unable to encode the pipeline for audit logging.

Action Check the exception message for details.

PRT.0101.0025 Failed to encode pipeline for step {0}: {1}

PRT.0101.0026E Custom logging: cannot find value for {0}.{1} on path {2}

Explanation Unable to get the field value using the specified path.

Action Make sure the field name and the path are correct.

PRT.0101.0028E Custom logging: cannot convert {0} to logging type {1} (value {2})

Explanation Failed to execute custom fields logging because the type of the field value cannot be determined.

Action Verify that the custom field value is the correct field type.

PRT.0101.0029E Exception trying to push audit log context: {0}

Explanation Unable to add audit log context.

Action Check the exception message for details.

PRT.0101.0030E Exception trying to pop audit log context: {0}

Explanation Unable to remove audit log context.

Action Check the exception message for details.

PRT.0101.0031E	Exception publishing Audit Log Event {1}: {0}
Explanation	Unable to publish the log document for audit logging.
Action	Check the exception message for details.
PRT.0101.0034E	Exception publishing Optimize Log Event {1}: {0}
Explanation	Unable to perform the task because an audit runtime storage is not found.
Action	Make sure the audit runtime storage is properly set up and running.
PRT.0101.0035	Exception registering Process Logger: {0}
PRT.0101.0055	*{0}, {1}: sending live transition to {2}
PRT.0101.0057E	Exception encoding transition pipeline: {0}
Explanation	Unable to send an output transition using the specified transport.
Action	Check the exception message for details.
PRT.0101.0059E	Exception during send: {0}
Explanation	Cannot publish the document over the transport.
Action	Check the exception message in the Integration Server error logs for details.
PRT.0101.0060	*{0}, {1}: sending dead transition to {2}
PRT.0101.0080	Loading process models in package {0}
PRT.0101.0082	Found PE model files in {0}
PRT.0101.0083	Loading model fragment {0}
PRT.0101.0084E	Exception loading model fragment {1}: {0}
Explanation	Error while reading process model file.
Action	Check the exception message for details.

PRT.0101.0085	Skipping model fragment {0}
PRT.0101.0086	Deleting {0} old fragments from {1}
PRT.0101.0087E	Exception reading fragment file {1}: {0}
Explanation	Error while reading process model file.
Action	Check the process exception message in the Integration Server error logs for details.
PRT.0101.0088	Deleting model fragment: {0}
PRT.0101.0089	Deleting XML file {0}
PRT.0101.0090	Adding new process fragment (pkg={0}, file={1})
PRT.0101.0091	Unable to create directory: {0}
PRT.0101.0118	[MID={0}, MVers={1}] has timed out
PRT.0101.0122E	Exception invoking timeout for {1}, {2}: {0}
Explanation	Failed to invoke timeout.
Action	Check the exception message for details.
PRT.0101.0124E	*{0}, {1}: starting timeout: {2}
Explanation	Starting absolute timeout.
Action	Informative message only: indicates that an absolute timeout is being started for the process and step with the displayed IDs.
PRT.0101.0140E	*{0}, {1}: killing step execution thread
Explanation	Error while saving the process model file.
Action	Make sure you have write permission to the file system.

PRT.0101.0143I	{0} session
Explanation	Timeout accessed an Integration Server service session to get the service thread.
Action	Informative message only: indicates that an IS service session has been accessed to get the service thread.
PRT.0101.0145	[SID={0}] Creating timer entry for join timeout
PRT.0101.0147	*{0} cannot start Process timeout -- type not specified
PRT.0101.0148	*{0}, {1}: cannot start Join timeout -- type not specified
PRT.0101.0149	*{0}, {1}: cannot start Step timeout -- type not specified
PRT.0101.0150E	Registering PE transport {0}
Explanation	Unable to sync documents with the Broker.
Action	Check the error message for details.
PRT.0101.0151	Using new PE transport {0} as default
PRT.0101.0152	Removing PE transport {0}
PRT.0101.0153	Default PE transport is {0}
PRT.0101.0154	Default PE transport is {0}; deferred
PRT.0101.0155	Not performing Broker push (not connected)
PRT.0101.0156	Pushing doctypes to Broker

- PRT.0101.0157 **Broker push error: {0}**

- PRT.0101.0158 **Sending {2} over {0} to {1}**

- PRT.0101.0160 **Broadcasting {1} over {0}**

- PRT.0101.0162 **Sending {1} over {0}**

- PRT.0101.0175 ***{0}, {1}: new process instance created on {2}**

- PRT.0101.0178 **Warning. Process model {0} is inactive**

- PRT.0101.0180 **NON-START STEP. Step {1} of model {0} is a non-start step**

- PRT.0101.0182 **[MID={0}, MVer={1}, fragment={2}] using newly-created pid**

- PRT.0101.0183 **checking out process stack**

- PRT.0101.0184 **using pre-existing stack. Parent process ID = {0}**

- PRT.0101.0186 **creating brand new process stack**

- PRT.0101.0195 **setting process status to RUNNING**

- PRT.0101.0196 ***PID={0}, MID={1}, MVer={2}: process started**

- PRT.0101.0197 ***{0}, MID={1}, MVer={2}: process restarting**

PRT.0101.0199	[PID={0}, Delta={1}] updating Track Count
PRT.0101.0202	*PID={0}, MID={1}, MVer={2}: process completed
PRT.0101.0206	Cache cleanup running every {0} seconds and every {1} instances
PRT.0101.0207	*{0}, {1}: transitioning to cancel step
PRT.0101.0223	looking for PID for CID {0}
PRT.0101.0224	[MID={1}] matching bizdoc to model. Type name = {0}. Require start = {2}
PRT.0101.0228	{0} index entries found for doctype {1}
PRT.0101.0229	entry({0}) ==> {1}@{2}, filter={3}
PRT.0101.0230	evaluateFilter(): filter = {0}
PRT.0101.0231	evaluateFilter(): pipe = {0}
PRT.0101.0235	DocID={0}, DocType={1}, ConvId={2}: processing incoming TN document
PRT.0101.0236	{{0}} doc internal ID: {1}
PRT.0101.0237	{{0}} doctype name: {1}
PRT.0101.0238	{{0}} conversation ID: {1}

PRT.0101.0240	joining existing conversation {1}
PRT.0101.0241	using model ID {0}
PRT.0101.0242E	DocID={0}, DocType={1}, ConvId={2}: no Model match for TN document
Explanation	Not starting a process instance because no process model is found that matches the business document (bizdoc).
Action	Make sure there is a process model that subscribes to this business document (bizdoc).
PRT.0101.0243E	DocID={0}, DocType={1}, ConvId={2}, MID={3}: no Step match for TN document
Explanation	Unable to match a step to the business document (bizdoc).
Action	Make sure at least one step in the process model subscribes to this business document (bizdoc).
PRT.0101.0244	ConvId={0}, PID={1}: starting/joining TN process
PRT.0101.0247	joining process (status {0})
PRT.0101.0248	PROCESS DONE, CANNOT JOIN
PRT.0101.0249	joining at step {1} (frag {0})
PRT.0101.0251E	IM failed: model is disabled or non-start step
Explanation	Unable to create a process instance because it is a non-start step or the process model is inactive.
Action	If joining a running process, make sure it has the correct conversation ID. Otherwise, make sure the process model is enabled in webMethods Monitor.
PRT.0101.0252	Attribute {0} = {1}

PRT.0101.0253	BizDocAttribute {0} is required in a process, but no definition is available on this server
PRT.0101.0254E	Exception fetching data from TN profile store: {0}
Explanation	Unable to get the Trading Networks partner profile summary.
Action	Check the Trading Networks partner profile.
PRT.0101.0255	Profile Field {0} = {1}
PRT.0101.0256E	Extended profile field {0} is required in a process, but no definition is available on this server
Explanation	Unable to get the extended profile field.
Action	Make sure the extended profile field is populated.
PRT.0101.0257E	Exception fetching data for field {1}: {0}
Explanation	Unable to get the Trading Networks extended profile field.
Action	Check the Trading Networks extended profile field.
PRT.0101.0258	Duplicate document: {0}. Document rejected
PRT.0101.0278	*{0}, {1}: handling transition event to {2}
PRT.0101.0284	*{0}, {1}: handling native document {3} on {2}
PRT.0101.0289E	NO MATCHING STEP
Explanation	Unable to find the step that subscribes to this document.
Action	Make sure a step in the process model subscribes to this document.
PRT.0101.0290E	Document {2} does not match to any step in process {0} on {1}
Explanation	Unable to find the step that subscribes to this document.
Action	Make sure a step in the process model subscribes to this document.

PRT.0101.0292	Document {2} matches step in process {0} on {1}
PRT.0101.0294E	NO MATCHING INPUT for pid
Explanation	Unable to get the input definition for this document.
Action	Make sure the document exists and is synced to the Broker.
PRT.0101.0295E	*{0}, {1}: document {3} is NOT a valid published input
Explanation	Unable to get the input definition for this document.
Action	Make sure the document exists and is synced to the Broker.
PRT.0101.0297	*{0}, {1}, document {3} is a valid published input
PRT.0101.0300E	*{0}, {1}: using correlation service {2}
Explanation	An error occurred while accessing the ProcessAudit database.
Action	Make sure that the ProcessAudit pool alias is configured and functional, and that there are no connectivity problems.
PRT.0101.0301E	pipe: {0}
Explanation	An error occurred while accessing the ProcessAudit database.
Action	Make sure that the ProcessAudit pool alias is configured and functional, and that there are no connectivity problems.
PRT.0101.0303	*{0}, {1}: correlating to TN conversation id
PRT.0101.0305E	*{0}, {1}: correlated to process id
Explanation	An error occurred while accessing the ProcessAudit database.
Action	Make sure that the ProcessAudit pool alias is configured and functional, and that there are no connectivity problems.
PRT.0101.0306	correlation ID mapped to existing PID

PRT.0101.0307E	Error invoking correlation svc {1}: {0}
Explanation	Failed to invoke the specified correlation service.
Action	Check the process exception in the Integration Server error logs for details.
PRT.0101.0309	dispatching event : {0}
PRT.0101.0310	*{0}, {1}: starting step execution
PRT.0101.0311E	*{0}, {1}: no process fragment contains this step
Explanation	Unable to find the step in the process model fragment file.
Action	Make sure generated model fragment file contains this step.
PRT.0101.0314	Exception dispatching step: {0}
PRT.0101.0315E	Exception handling transition event: {0}
Explanation	Failed to handle a process transition document.
Action	Check the exception message for details.
PRT.0101.0317W	Error joining because it is terminated already
Explanation	Cannot join a process that is not running.
Action	Check the exception message for details.
PRT.0101.0318	*{0}, {1}: using correlation field {2}
PRT.0101.0319	*{0}, {1}: correlated to disabled model {2} version {3}
PRT.0101.0320	*{0}, {1}: correlated to {2}, expected {3}
PRT.0101.0335	*{0}, {1}: start step execution

PRT.0101.0336	*{0}, {1}: end step execution
PRT.0101.0337	continuing synchronous execution at step {0}
PRT.0101.0341	*{0}, {1}: executing step
PRT.0101.0343	fragment and step validated
PRT.0101.0347	*{0}, {1}: pushing step on suspended list
PRT.0101.0349	step iteration = {0}
PRT.0101.0356	*{0}, {1}: step not executed, enqueueing event
PRT.0101.0357	*{0}, {1}: step iteration count exceeded
PRT.0101.0358	*{0}, {1}: setting try count to {2}
PRT.0101.0359E	Exception executing step {1}, {2}: {0}
Explanation	The XPath expression cannot be parsed.
Action	Verify that the XPath expression is valid.
PRT.0101.0360E	Exception saving step context {1}, {2}: {0}
Explanation	Failed to save the context of the step.
Action	Check the exception message in the Integration Server error logs for details.
PRT.0101.0361	done preparing step for execution
PRT.0101.0362	*{0}, {1}: logging custom audit data

PRT.0101.0366	no service to execute
PRT.0101.0370	merging pre-defined service inputs
PRT.0101.0372	service executed OK. After step invoke outPipe={0}
PRT.0101.0373	*{0}, {1}: sent {2} output events
PRT.0101.0374E	SERVICE EXECUTION FAILED ({0}) {1}
Explanation	Caught a service exception. If an error handler is defined, the appropriate error action will be taken. Otherwise, the process will be marked as failed.
Action	Check webMethods Monitor for details about the failure.
PRT.0101.0376E	Exception invoking service {1}, {2}, Svc={3}: {0}
Explanation	Failed while executing the step. Service throws an error.
Action	If an error handler is defined, the appropriate error action will be taken. Otherwise, the process will be marked as failed.
PRT.0101.0377	*{0}, {1}: transitioning to error step {2}
PRT.0101.0378E	*{0}, {1}: terminated abnormally
Explanation	Failure during process execution. No error handler defined for the step.
Action	Define an error handler for the failed step so that appropriate error action can be taken.
PRT.0101.0383	considering published output {0} (doctype {1})
PRT.0101.0385	document: {0}. Publishing with stack {1}
PRT.0101.0387E	missing content for document {0}
Explanation	Unable to get the document from the publish output because of a missing or corrupted document object.
Action	Make sure the document is in the publish output pipeline.

PRT.0101.0388	*{0}, {1}: published output document {2}
PRT.0101.0389	considering bizdoc output {0}
PRT.0101.0390	done with bizdoc output {0}
PRT.0101.0391E	Exception sending output {1} of {2} for PID {3} SID {4}: {0}
Explanation	Error while sending output documents.
Action	Check the exception message for details.
PRT.0101.0392	ERROR on output {0} of {1}. Output isa {2}. Output: {3}
PRT.0101.0395	considering transition to step {0} on {1}
PRT.0101.0396	*{0}, {1}: adding dead transition to {2}
PRT.0101.0397	*{0}, {1}: adding live transition to {2}
PRT.0101.0398	synchronously following transition to {0}
PRT.0101.0399	*{0}, {1}: publishing transition to {2} on {3}
PRT.0101.0400E	Exception updating track count {1}, {2}: {0}
Explanation	Failed to evaluate the condition associated with this output, possibly because of an invalid condition parameter.
Action	Check the process exception message in the Integration Server error logs for details.
PRT.0101.0401	*{0}, {1}: no track count change

PRT.0101.0402	*{0}, {1}: updated track count by {2} to {3}
PRT.0101.0403	*{0}, {1}: transition condition {2} evaluated to {3}
PRT.0101.0412W	Cannot execute step {0} because the process was terminated already
Explanation	Cannot execute a step because the process was terminated.
Action	Check for incorrect use of the correlation service.
PRT.0101.0428E	PE queue processing for step {0}
Explanation	An error occurred while executing a step.
Action	See the detailed error message for specific information.
PRT.0101.0430	event queue empty, nothing to do
PRT.0101.0432	*{0}, {1}: transitioning to timeout handler
PRT.0101.0434E	Exception assembling pipeline {1}, {2}: {0}
Explanation	Cannot create a transition pipeline for the specified step.
Action	Check the exception in the Integration Server error logs for details.
PRT.0101.0435	*{0}, {1}: {2} events in the queue. Join state: {3}
PRT.0101.0441	dropping {0} (id {1})
PRT.0101.0442	update track count ({0}) as a result of dropping events after the join
PRT.0101.0444	returning positive join result
PRT.0101.0445	these events will be in the pipeline:

PRT.0101.0447	applying thread count DELTA of {0}
PRT.0101.0448I	*{0}, {1}: starting join timeout
Explanation	Starting join timeout.
Action	Informative message only: indicates that a join timeout has been started.
PRT.0101.0449I	*{0}, {1}: starting step timeout
Explanation	Starting step timeout.
Action	Informative message only: indicates that a step timeout has been started.
PRT.0101.0451	*{0}, {1}: absolute timeout type is invalid
PRT.0101.0452	Exception: Deprecated step found {1}, {2}: {0}
PRT.0101.0455	Error cloning IData {0}.
PRT.0101.0468E	Something just tried to dequeue an event with a null ID
Explanation	Unable to remove metadata from the queue.
Action	Check the IllegalArgumentException message in the Integration Server error logs for details.
PRT.0101.0469E	Document with duplicate correlation ID submitted.
Explanation	An error occurred when a document with a duplicate correlation ID was found.
Action	Make sure each correlation ID is unique.
PRT.0101.0489	PRTX: INSERT {0}.{1} --> p.{2}
PRT.0101.0494	PRTX: mapping {0}.{1} (insert={2})
PRT.0101.0509	Using Shared Cache for Join locks

PRT.0101.0511E	Can not initialize jdbc runtime storage for PE. Make sure ProcessAudit or ProcessEngine runtime pool is configured properly
Explanation	Failed to establish a database for Process Engine storage; using repository instead.
Action	Check the Process Audit and PRT Associated Pool Alias configurations.
PRT.0101.0512E	Storage exception: {0}
Explanation	Exception executing an SQL statement.
Action	Check for incorrect database configuration.
PRT.0101.0513	Storage cleaner: will run every {0} seconds
PRT.0101.0514E	Storage cleaner: executing stored procedure
Explanation	An error occurred while saving the Web service binding file. The user may not have the correct access to the directory.
Action	Make sure that the user has proper read/write access to the directory.
PRT.0101.0515E	Storage cleaner: executing embedded SQL
Explanation	An error occurred while saving the Web service binding file. The user may not have the correct access to the directory.
Action	Make sure that the user has proper read/write access to the directory.
PRT.0101.0517E	Storage cleaner: Duration {0} ms
Explanation	An error occurred while saving the Web service binding file. The user may not have the correct access to the directory.
Action	Make sure that the user has proper read/write access to the directory.
PRT.0101.0518E	Exception: Unable to connect to database!
Explanation	The Web service binding file does not exist. The user may not have the correct access to the directory.
Action	Make sure that the user has proper read/write access to the directory.

PRT.0101.0519	Storage cleaner: expiration for completed processes: {0} seconds
PRT.0101.0521	Storage cleaner: cannot acquire lock. Exception: {0}
PRT.0101.0522	Storage cleaner: expiration for failed processes: {0} seconds
PRT.0101.0523E	Storage cleaner: clean up for completed processes is disabled
Explanation	The WSDL file for the Web service could not be accessed. The file may not exist or it may be in the wrong directory location.
Action	Make sure that this file exists and has been deployed to the correct directory location.
PRT.0101.0531	Exception: {0}. Step Level Retry configured for service: {1}. Retry {2} of {3} in {4} ms
PRT.0101.0532E	No Step Level Retry configured for step service: {0}
Explanation	The WSDL file for the Web service could not be accessed.
Action	Make sure that the WSDL file exists and has been deployed to the generated package.
PRT.0101.0533E	Step Level Retry count exceeded for service: {0}
Explanation	An error occurred while accessing the process model package.
Action	Make sure that the process model has been generated and the corresponding namespace package has been created.
PRT.0101.0534	Thread Threshold detected. Retry abandoned for {0}.
PRT.0101.0535	Error querying process {0} version {1} from {2}. Make sure the process is deployed for monitoring.
PRT.0101.0550	[MID={0}] StatusManager processing {1} request
PRT.0101.0551	*{0}: process status changed to {1}

PRT.0101.0552	*{0}: resuming process at {1}
PRT.0101.0553	*{0}: restarting process at step {0}
PRT.0101.0554	Running process at step {0}
PRT.0101.0601I	web service request/reply {0}
Explanation	Performing Web service request/reply.
Action	Informative message only: indicates that the PRT dispatcher is processing a Web service request/reply.
PRT.0101.0700I	Adding thread to thread table, thread id={0}
Explanation	Added a thread with the following thread ID to the Process Engine's internal thread table.
Action	Informative message only: indicates the thread ID for a thread added to the Process Engine's internal table.
PRT.0101.0701I	Getting thread from thread table, thread id={0}
Explanation	Retrieved a thread with the following thread ID from the Process Engine's internal thread table.
Action	Informative message only: indicates the thread ID for a thread retrieved from the Process Engine's internal table.
PRT.0101.0702	Deleting thread from thread table, thread id={0}
PRT.0101.0830	JMS Connection Alias for PE 'PE_NONTRANSACTIONAL_ALIAS' has not been configured.
PRT.0101.0831	Error creating JMS internal topic: {0}
PRT.0101.0832	Error updating client group permissions: {0}

PRT.0101.0833	Error creating JMS connection alias: {0}
PRT.0101.0850E	[MID={0}] Now listening to path: "{1}" for e-Forms on jcr "{2}"
Explanation	This is an informative message. The e-form configuration is now listening for events.
Action	To generate an event, place an e-form into the My webMethods Server folder location that the listener is monitoring.
PRT.0101.0851	[MID={1}] Error with Content Repository "{2}". Check if the repo is running, login credentials and repo connection information is correct. {0}
PRT.0101.0852E	[MID={1}] Error disabling/removing listener from Content Repository "{2}". {0}
Explanation	Listener cannot be removed because the repository is down or does not exist.
Action	Make sure the repository is still running and connected, and that the listener is valid.
PRT.0101.0853	[MID={0}] Content Repository "{1}" not configured.
PRT.0101.0854	[MID={0}] Listener for e-Forms at path: "{1}" has been disabled from jcr "{2}"
PRT.0101.0855	[MID={1}] Error adding listener to Content Repository "{2}". {0}
PRT.0101.0856E	[MID={1}] Problem reading E-form config file: "{2}". {0}
Explanation	An invalid e-form configuration file or unknown file type using the CSP or JCR file name extension was found in WmPRT\config\.
Action	Log in to My webMethods and delete and then re-create the e-form configuration in the Define Environments application page.
PRT.0101.0857E	[MID={0}] Unable to change listener please disable all other models currently using this listener: "{1}"
Explanation	The SOAP processor aborted processing of the SOAP message because of a problem with the message header.
Action	Make sure the header entries of the SOAP message are valid.

PRT.0101.0858E	[MID={0}] Cannot edit access for PORT 15006. Please ensure to manually add access for "wm.prt.eforms:update" "wm.server:connect" "wm.server:disconnect" "wm.server:ping".
Explanation	E-forms requires the specified port to be open.
Action	Make sure that that port 15006 is open and has access for "wm.prt.eforms:update", "wm.server:connect", "wm.server:disconnect", and "wm.server:ping".
PRT.0101.0859E	[MID={0}] Cannot start e-form process because doc type: "{1}" does not exist. For e-form instance at: "{2}". Please recreate the e-form doc or rebuild the model(s).
Explanation	The document type related to this listener does not exist on the Integration Server.
Action	Re-create the e-form document type and rebuild the affected process model(s).
PRT.0101.0860	[MID={0}] Trying to publish E-form instance "{1}" for template "{2}". With doc type of "{3}". If process does not start please check error log for any pub.publish errors. IData:{4}
PRT.0101.0861	[MID={1}] Error restarting listener(s) to Content Repository "{2}". {0}
PRT.0101.0862	Content Repository currently has no models associated to it. No reason to restart the repository at this time.
PRT.0101.0863	[MID={1}] Cannot retrieve password: "{2}". {0}
PRT.0101.0864	No model(s) enabled using this listener "{0}". Listener will not be restarted.
PRT.0101.0865	[MID={0}] Content Repository currently has a listener listening in that location. No new listener added to listening path: "{1}" for e-Forms on jcr "{2}".
PRT.0101.0900E	Monitor: {0}
Explanation	Type mismatch in BPEL assign.
Action	Check that the mapping performed in the assign step is valid. Mapping is not typesafe.

PRT.0101.0902E	Invalid Logging Level
Explanation	Unable to find type of the field for the record using the specified part and XPath query.
Action	Check that the type used in the part and XPath query is defined in your Integration Server instance. This can occur when the field or record are not defined in the Integration Server instance to which the corresponding process has been deployed.
PRT.0101.0903E	Log Transitions value must be either "True" or "False"
Explanation	Unable to find type of the field for the record using the specified part and XPath query.
Action	Check that the type used in the part and XPath query is defined in your Integration Server instance. This can occur when the field or record are not defined in the Integration Server instance to which the corresponding process has been deployed.
PRT.0101.0907	Enable Resubmission value must be either "True" or "False"
PRT.0101.0908	[MID={0}, MVers={1}] Model does not exist.
PRT.0101.0909	[MID={0}] QoS cannot be changed because it was generated from a pre-7.0 version of Modeler.
PRT.0101.0910	[MID={0}] Logging level for Model cannot be set below minimum value of {1}.
PRT.0101.1001	CheckDuplicates processing {0}, uuid, {1}
PRT.0101.1002	CheckDuplicates processed {0}, uuid, {1}, status, {2}
PRT.0101.1003	CheckDuplicates throwing ISRuntimeException {0}, uuid, {1}
PRT.0101.1100	Error trying to get JDBC pool configuration using functional alias {0}. Business calendar based timeouts will not be able to be evaluated.
PRT.0101.1101	Exception trying to get JDBC pool configuration: {0}

PRT.0101.1102	Unable to initialize MWS library. Business calendar based timeouts will not be able to be evaluated.
PRT.0101.1103	Exception trying to initialize MWS library: {0}
PRT.0101.1200	Business timeout is invalid: {0}
PRT.0101.1201	Business calendar alias {0} does not exist
PRT.0101.1202	Business calendar evaluator does not exist
PRT.0101.1300	*{0}, {1}: did not start timer, no end time specified.
PRT.0101.1301	*{0}: executing Process Timeout
PRT.0101.1302	*{0}, {1}: executing Step Timeout
PRT.0101.1303	*{0}, {1}: executing Join Timeout
PRT.0101.1304	[MID={0}, SID={1}] Error killing step thread
PRT.0101.1305	[MID={0}] Constructing process timeout
PRT.0101.1306	[MID={0}, SID={1}] Constructing step timeout
PRT.0101.1307	[MID={0}, SID={1}] Constructing join timeout
PRT.0101.1309	*{0}, {1}: cancelling step timeout

- PRT.0101.1310 *{0}, {1}: cancelling join timeout
- PRT.0101.1400 Exception trying to fail the process *{1}: {0}
- PRT.0101.1401 *{0}, {1}: sending Dead Path PTE to {2} on {3}
- PRT.0101.1402 *{0}, {1}: process version changed from {2} to {3}
- PRT.0101.1403 *{0}, {1}: taking unsatisfied join transition {2}
- PRT.0101.1500 made input pipe from {0} events
- PRT.0101.1600 Unable to get Optimize process data collector. Tracking enabled models will not be logged to Optimize.
- PRT.0101.1601 Exception trying to get Optimize process data collector: {0}
- PRT.0101.1602 Exception trying to shut down Optimize data collector: {0}
- PRT.0101.1742 Failed to restart e-form listener for {0}.
- PRT.0101.1743 Restart of e-form listener: {0} successful.
- PRT.0101.9123E **No value was supplied for the required parameter {0}.**
Explanation A parameter is missing or corrupted.
Action Make sure that the parameter object exists.
- PRT.0101.9124E **An invalid value was supplied for the required parameter {0}. The bad value was {1}.**
Explanation The value of the specified key is invalid.
Action Make sure the value is the specified type.

PRT.0101.9125E	Service {0} failed.
Explanation	Caught a service exception.
Action	Check the service exception message in the Integration Server error logs for details.
PRT.0101.9135E	Cannot read frag file {0}; the file does not exist.
Explanation	An error occurred while reading the process model file: the file does not exist.
Action	Make sure the model has been generated correctly.
PRT.0101.9136E	Cannot read frag file {0}; the file is not readable.
Explanation	An error occurred while reading the process model file: the file is not readable.
Action	Check the file permissions.
PRT.0101.9137E	Malformed frag file {0}; the file does not contain the 'fragment' key.
Explanation	Unable to read the process model file; the file may be corrupted.
Action	Regenerate the process model.
PRT.0101.9138E	IOException reading frag file {0}
Explanation	An error occurred while reading the process model file.
Action	Refer to the process exception in the Integration Server error logs for details.
PRT.0101.9139E	Cannot write frag file {0}; the file already exists and is not writeable.
Explanation	An error occurred while saving the process model file: the file already exists.
Action	Check the file permissions.
PRT.0101.9151E	Cannot rebind role {0} from partner ID {1} to partner ID {2}
Explanation	Unable to add a TN sender or receiver role because the current public role information indicates a different partner ID.
Action	Make sure the sender or receiver matches the partner ID, then restart the process.
PRT.0101.9195E	Could not enable model "{0}" version "{1}" for {2}
Explanation	Cannot get a lock for global data.
Action	Determine whether another step in the process currently has a lock on global data.

PRT.0101.9196E	Could not disable model "{0}" version "{1}" for {2}
Explanation	Cannot get a lock for global data.
Action	Determine whether another step in the process currently has a lock on global data.
PRT.0101.9197E	Could not acquire lock "{0}"
Explanation	A field is not present in global data when using BPEL assign.
Action	Make sure the data exists.
PRT.0101.9201	Correlated process ID {0} is incorrect; a process already exists with that process ID and a different model ID
PRT.0101.9204E	The CID returned from {0} is too long. CID length is {1}; maximum allowed is {2}
Explanation	The conversation ID has exceeded the maximum allowed length.
Action	Shorten the conversation ID and rerun the process.
PRT.0101.9205E	Correlation ID joins to a process instance that is no longer running. PID: {0}
Explanation	Joins are not allowed on process instances that are not in running status.
Action	Change the state to running or start a new process instance.
PRT.0101.9206	Intermediate Receive Step {2} of model {0} version {1} does not correlate to existing Process ID
PRT.0101.9215E	Cannot start process {0}; unable to determine the appropriate model
Explanation	The process model ID has not been properly stored in the Process Engine DB.
Action	Check that the DB is working properly and rerun the process.
PRT.0101.9216E	Cannot start process {0} with model {1} at step {2}: there is no fragment defined that contains that step
Explanation	The process model fragment file does not contain the definition for the specified step.
Action	Check that the step is properly generated in the fragment file. If not, regenerate the process.

PRT.0101.9217E	Cannot start process {0} at step {1}: there is no such step defined in fragment {2}
Explanation	The process model fragment file does not contain the definition for the specified step.
Action	Check that the step is properly generated in the fragment file. If not, regenerate the process.
PRT.0101.9218	Error changing version for process {0} with model {1} at step {2} from version {3} to {4}: there is no fragment defined that contains that step
PRT.0101.9228E	Missing ConversationID for call to getInstanceId()
Explanation	Cannot start a process because a conversation ID was not present in the Trading Networks document envelope.
Action	Make sure that the conversation ID is properly defined and extracted.
PRT.0101.9229E	Model {0} was specified, but there is no step in this model for a bizdoc of type {1}
Explanation	Cannot find any step in the model that subscribes to this document.
Action	Make sure the model has a step that subscribes to this document.
PRT.0101.9230E	Couldn't start process. Either the model is disabled or this document targets a non-start step.
Explanation	The process cannot be started either because the model is disabled or the step subscribing to this document is not a start step.
Action	Make sure the model is enabled and that the step that subscribes to this document is a start step.
PRT.0101.9231E	No ConversationID available; PE bizdoc processing fails
Explanation	Cannot start a new process or join an existing process because a conversation ID was not present in the TN document envelope.
Action	Make sure that conversation ID is properly defined and extracted.
PRT.0101.9244E	PID {0}: Cannot {1} process; status is {2}
Explanation	The process instance has one of the following statuses: STAT_UNKNOWN, STAT_RUNNING, STAT_SUSPENDED, STAT_FAILED, STAT_CANCELLED, or STAT_DONE. Because the process instance is in one of these states, it cannot run the requested action. The requested action will be one of the following: START, SUSPEND, RESUME, CANCEL, FAIL, RESTART, QUIET, or DONE.
Action	Make sure the action is allowed on processes with the specified status.

PRT.0101.9245E	PID {0}: Bad command RESTART; target step is missing
Explanation	Unable to restart the process because of a missing or corrupted target step ID in the pipeline.
Action	Check the pipeline then restart the process.
PRT.0101.9246E	PID {0}: Bad command RESTART; pipeline is missing
Explanation	Unable to restart the process because of a missing or corrupted pipeline.
Action	Check the pipeline then restart the process.
PRT.0101.9248E	PID {0}: Bad command RESTART; pipeline is missing /ProcessData
Explanation	Unable to restart the process because of a missing or corrupted ProcessData object in pipeline.
Action	Check the pipeline then restart the process.
PRT.0101.9249E	PID {0}: Bad command RESTART; pipeline is missing /ProcessData/LastEvents
Explanation	The process instance was not restarted because the pipeline is missing.
Action	Make sure that the pipeline is properly logged.
PRT.0101.9250E	PID {0}: Bad command RESTART; RestartParameters is missing
Explanation	Cannot restart the process instance because some or all of the restart parameters are missing.
Action	Make sure that all of the restart parameters are present in the pipeline.
PRT.0101.9251E	PID {0}: restart failed because the supplied pipeline contains an invalid ProcessInstanceID {1}
Explanation	Unable to restart due to a invalid process instance ID.
Action	Check the pipeline then restart the process.
PRT.0101.9253E	MID {0}: Cannot restart process; frag {1} step {2} does not define bizdoc {3} as input
Explanation	Process cannot be restarted because the target step does not define the document as an input.
Action	Make sure that the target step specifies the document as an input.

PRT.0101.9254E	PID {0}: failed to restart at step {1} because at least one valid event is needed in path /ProcessData/LastEvents/ of the supplied pipeline {2}
Explanation	The process cannot be restarted because all documents in the pipeline have been removed.
Action	Start a new instance of the process.
PRT.0101.9255E	MID {0} Failed to restart the process because Model {0} is not enabled
Explanation	The process cannot be restarted because the model is disabled.
Action	Enable the model and restart again.
PRT.0101.9256	PID {0} Failed to execute process instance status change
PRT.0101.9262E	PID {0}: Could not get a connection in {1}
Explanation	An error occurred while trying to connect to Process Engine DB storage.
Action	Make sure that Process Engine DB storage is properly configured and running.
PRT.0101.9263E	PID {0}: Update thread count failed
Explanation	An error occurred while communicating with the Process Engine DB.
Action	Make sure that the Process Engine DB is properly configured and running.
PRT.0101.9264	Cannot create new instance of model {0} version {1}, it is not enabled
PRT.0101.9265	Step {2} of model {0} version {1} is not a start step
PRT.0101.9285E	Could not create TN facade
Explanation	Unable to create a Trading Networks implementation.
Action	Check the process exception message in the Integration Server error logs for details.
PRT.0101.9286E	Could not handle doc output
Explanation	Error while handling the output of a business document (bizdoc).
Action	Check the process exception message in the Integration Server error logs for details.

PRT.0101.9287E	bizdoc_output() failed because pipeline object {0} is not a TN bizdoc object
Explanation	The specified document is the wrong type.
Action	Make sure the document is a Trading Networks document.
PRT.0101.9301E	Exception occurred during correlation or cross-reference operation
Explanation	Unable to perform ID correlation because an error occurred while connecting to PRT DB storage.
Action	Refer to the process exception in the Integration Server error logs for details.
PRT.0101.9306	Correlation field {0} does not exist in published document {1}
Explanation	A correlation field is specified for the document starting this step, but the correlation field does not exist in the document at run time.
Action	Ensure that the correlation field is specified in the published document to establish correlation.
PRT.0101.9316	Could not get process ID from conversation ID
PRT.0101.9321	Thread sleep wait interrupted: {0}
PRT.0101.9322	Variable "{0}" does not exist in the pipeline
PRT.0101.9340E	Bad join expression; invalid character {0}
Explanation	The specified character is not allowed in the join expression.
Action	Verify that the join expression is valid.
PRT.0101.9341E	Bad XOR join specification {0}; id required
Explanation	The XOR join expression does not contain an unique ID.
Action	Make sure that a unique ID is present for the XOR join expression.
PRT.0101.9342E	Bad XOR join specification; unparseable timeout {0}
Explanation	The timeout value of the XOR join expression is not in a valid format.
Action	Make sure the timeout value for the XOR join expression is in milliseconds.

PRT.0101.9343E	Bad join expression; one or more unmatched)
Explanation	Missing parenthesis in a join expression.
Action	Make sure the join expression is valid.
PRT.0101.9344E	Bad join expression; one or more unmatched (
Explanation	Missing parenthesis in a join expression.
Action	Make sure the join expression is valid.
PRT.0101.9345E	Bad join expression; bad standalone join spec {0}
Explanation	Invalid standalone in a join expression.
Action	Make sure the join expression is valid.
PRT.0101.9346	Global data is no longer supported. Model {0} : SID {1}
PRT.0101.9356E	Can not set track count to {0}; only 1 allowed for TransitionMetaData
Explanation	The track count is not 0 or 1.
Action	Make sure the track count is 0 or 1.
PRT.0101.9358E	Exception while executing SQL statement
Explanation	The SQL processor failed to execute this statement because there is an error in the statement itself - a reference to a non-existent table, a non-existent (misspelled) field, or an incorrect SQL keyword.
Action	Check the process exception message in the Integration Server error logs for details.
PRT.0101.9360	XPath data is no longer supported. Model {0} : SID {1}
PRT.0101.9412	PID {0}: Cannot execute step {1} because the process was terminated already
PRT.0101.9417E	Cannot publish {0}. Document is not in pipeline.
Explanation	Cannot publish document; the document is not in the pipeline.
Action	Check for improper or missing mapping in the Integration Server flow service.

PRT.0101.9467 Cannot enqueue an event with a null ID

PRT.0101.9469 Error encountered: Document with duplicate correlation ID submitted.

PRT.0101.9613 There are no enabled Processes matching this trigger: {0}

Explanation A document has arrived on a subscriptionTrigger but there are no enabled processes associated with this trigger. Therefore, the document is ignored.

Action In most cases this means your process is not enabled. Log in to My webMethods and use webMethods Monitor to select the process and enable it for execution, then try again.

PRT.0101.9862 This service has been deprecated and is no longer supported.

Explanation The service executed is no longer supported in the current release.

Action Consult the release readme file and the Process Engine Administrator's guide for deprecated and removed services to determine if there is a replacement service.

PRTEExceptionConstants.EXC_EFORM_DUP_FRIENDLYNAME – Friendly name: {0} already in use please choose another.

PRTEExceptionConstants.EXC_PT_JOINTIMEOUT – The step "{2}" of model "{0}" with process id of "{1}" has join timed out, with no timeout step or error step to process.

PRTEExceptionConstants.EXC_TRANSITION_NOT_FOUND – Transition Key {0} could not be found for Process ID {1}.

21 Realtime Monitoring Messages

WEPRME0001	The user name must not be null.
WEPRME0002	The SQL statement must not be null.
WEPRME0003	The temporal validity approach must not be null.
WEPRME0004	The user-defined function must not be null.
WEPRME0005	The class of the user-defined function must not be null.
WEPRME0006	Persistency for user-defined functions is currently not supported.
WEPRME0007	The database source builder must not be null.
WEPRME0008	Persistency for a database source is currently not supported.
WEPRME0009	The class of the database source builder must not be null.

- WEPRME0010** **Persistency for tables is currently not supported.**

- WEPRME0011** **The source adapter must not be null.**

- WEPRME0012** **The authorization module does not currently support persistency.**

- WEPRME0013** **The source adapter class must not be null.**

- WEPRME0014** **The subscription mode must not be null.**

- WEPRME0015** **The sink adapter must not be null.**

- WEPRME0016** **The unsubscription mode must not be null.**

- WEPRME0017** **The sink adapter class must not be null.**

- WEPRME0018** **The authorization privilege must not be null.**

- WEPRME0019** **{0} because the connection has already been closed.**

- WEPRME0020** **{0} because the connection has been shut down by the server.**

- WEPRME0021** **Unable to close the connection; it has already been shut down by the server.**

- WEPRME0022** **The batch job cannot be started because the connection has been already closed.**

- WEPRME0023** **The batch job is already active.**

WEPRME0024	The temporal validity approach {0} requires the use of an instance of SourceAdapter.
WEPRME0025	Unsupported approach: {0}.
WEPRME0026	The temporal validity approach {0} requires the use of an instance of SinkAdapter.
WEPRME0027	The temporal validity approach {0} requires the use of an instance of PnSinkAdapter.
WEPRME0028	The temporal validity approach {0} requires the use of a subclass of SourceAdapter.
WEPRME0029	The temporal validity approach {0} requires the use of a subclass of PnSourceAdapter.
WEPRME0030	The temporal validity approach {0} requires the use of a subclass of SinkAdapter.
WEPRME0031	The temporal validity approach {0} requires the use of a subclass of PnSinkAdapter.
WEPRME0032	The user {0} does not have the privilege to add the query.
WEPRME0033	A user can only add a query to his/her own schema.
WEPRME0034	The user {0} does not have the privilege to use the query.
WEPRME0035	The user {0} does not have the privilege to add the user-defined function.
WEPRME0036	Current system configuration does not support persistency.
WEPRME0037	The user {0} does not have the privilege to remove the user-defined function.

- WEPRME0038** **The user {0} does not have the privilege to add the database source.**

- WEPRME0039** **The user {0} does not have the privilege to remove the database source.**

- WEPRME0040** **The user {0} does not have the privilege to use the database source.**

- WEPRME0041** **The user {0} does not have the privilege to add the table.**

- WEPRME0042** **The user {0} does not have the privilege to remove the table.**

- WEPRME0043** **A user can only add a source to his/her own schema.**

- WEPRME0044** **A user can only add a source to his/her own schema.**

- WEPRME0045** **The user {0} does not have the privilege to remove the query.**

- WEPRME0046** **The user {0} does not have the privilege to add the subscription.**

- WEPRME0047** **A user can only add a subscription to his/her own schema.**

- WEPRME0048** **The user {0} does not have the privilege to remove the subscription.**

- WEPRME0049** **The user {0} does not have the privilege to use the subscription.**

- WEPRME0050** **The user {0} does not have the privilege to grant the privilege.**

- WEPRME0051** **The user {0} does not have the privilege to revoke the privilege.**

WEPRME0052	The user {0} does not have the privilege to check the privilege.
WEPRME0053	The batch job cannot be executed because the connection has been closed.
WEPRME0054	The batch job cannot be executed because the connection has been shut down by the server.
WEPRME0055	No active batch job to execute.
WEPRME0056	The event engine has already been shut down.
WEPRME0057	An unexpected interrupt has occurred.
WEPRME0058	The response type is missing.
WEPRME0059	Calling the push method is not allowed after calling the done method.
WEPRME0060	Calling the heartBeat method is not allowed after calling the done method.
WEPRME0061	The handshake has failed.
WEPRME0062	Unable to establish connection.
WEPRME0063	A user-defined function cannot be registered using a remote connection - use computeRegisterServerFunction.
WEPRME0064	A database source cannot be registered using a remote connection - use computeRegisterServerDataSource.

- WEPRME0065** **A table cannot be registered using a remote connection - use computeRegisterServerTable.**

- WEPRME0066** **The connection has been lost: {0}.**

- WEPRME0067** **Init must be called before opening the adapter.**

- WEPRME0068** **The following command is unknown: {0}.**

- WEPRME0069** **The temporal validity approach {0} requires the use of an instance of PnSourceAdapter.**

- WEPRME0070** **A user can only add a source to his/her own schema.**

- WEPRME0071** **The artefact must not be null.**

- WEPRME0072** **The query identifiers cannot be delivered.**

- WEPRME0073** **The query cannot be prepared.**

- WEPRME0074** **The query cannot be checked.**

- WEPRME0075** **The query properties cannot be retrieved.**

- WEPRME0076** **The server function cannot be registered.**

- WEPRME0077** **The function cannot be deregistered.**

- WEPRME0078** **The server data source cannot be registered.**

WEPRME0079	The data source cannot be deregistered.
WEPRME0080	The server table cannot be registered.
WEPRME0081	The table cannot be deregistered.
WEPRME0082	The source cannot be prepared.
WEPRME0083	The query cannot be started.
WEPRME0084	The query cannot be stopped.
WEPRME0085	The sink cannot be subscribed.
WEPRME0086	The sink cannot be unsubscribed.
WEPRME0087	The earliest possible subscription time cannot be determined.
WEPRME0088	The earliest possible unsubscription time cannot be determined.
WEPRME0089	The server sink cannot be subscribed.
WEPRME0090	The server sink cannot be unsubscribed.
WEPRME0091	The privilege cannot be granted.
WEPRME0092	The privilege cannot be revoked.

- WEPRME0093** **The privilege cannot be checked.**
- WEPRME0094** **The identifiers cannot be retrieved.**
- WEPRME0095** **The registration cannot be checked.**
- WEPRME0096** **The query metadata cannot be delivered.**
- WEPRME0097** **Version mismatch between client and server. Cannot connect to server version {0} using client version {1}. Use a client version between {2} and {3} instead. Your current client version can only connect to server versions between {4} and {5}.**
- WEPRME0098** **Unable to connect to any of the provided servers: {0}.**
- WEPRME0099** **This operation is currently not supported in high availability mode.**
- WEPRME0100** **The query head cannot be retrieved.**
- WEPRME0101** **In high availability mode, this operation is currently only supported using a remote connection.**
- WEPRME0102** **The SQL statement contains syntactical errors.**
- WEPRME0104** **Unrecognized semantic exception. Please report the SQL statement to your software supplier.**
- WEPRME0105** **The {0} argument of the {1} aggregation must be numeric.**
- WEPRME0106** **The types of the arguments of the aggregation do not match the required argument types.**

WEPRME0107	The field {0} is unknown or not visible.
WEPRME0108	The argument of the ABS function must be numeric.
WEPRME0109	In the case function, the type of the {0} result expression does not match the types of the previous result expressions ({1}, {2}).
WEPRME0110	The signature of the user-defined function {0} does not match the specified types ({1}).
WEPRME0111	The user-defined function {0} is unknown or not visible.
WEPRME0112	The {0} argument of the {1} must be numeric.
WEPRME0113	The {0} argument of the {1} must be of character/string type.
WEPRME0114	The types of the arguments of the operation do not match the required argument types.
WEPRME0115	The arguments of the {0} comparison cannot be compared ({1}, {2}).
WEPRME0116	The expression list contains constants of different types.
WEPRME0117	The types of the expression and the constants in the expression list cannot be compared ({0}, {1}).
WEPRME0118	Only expressions and star selections are permitted in a selection list.
WEPRME0119	An aggregate is not allowed inside a WHERE clause.

WEPRME0120	Only expressions are permitted in a GROUP BY clause.
Explanation	The GROUP BY clause contains an entry that is not an expression.
Action	Replace the entry by a valid expression.
WEPRME0121	The {0} constant listed in the set condition must have the same size as the specified field list.
WEPRME0122	The types of the field and the constants in the constant list cannot be compared ({0}, {1}).
WEPRME0123	The source {0} is unknown or not visible.
WEPRME0124	The size of a count-based window must be greater than zero.
Explanation	The query contains an invalid size. This refers to the ROWS argument in an SQL query, or the size attribute of a window element in an XML query.
Action	Specify a valid size.
WEPRME0125	The sliding size specification of a count-based window must be greater than zero.
Explanation	The query contains an invalid sliding size. This refers to the SLIDE argument in an SQL query, or the increment attribute of a window element in an XML query.
Action	Specify a valid sliding size.
WEPRME0126	The duration of a time-based window must be greater than zero.
Explanation	The query contains an invalid duration. This refers to the RANGE argument in an SQL query, or the size attribute of a window element in an XML query.
Action	Specify a valid duration.
WEPRME0127	The sliding size specification of a time-based window must be greater than zero.
Explanation	The query contains an invalid sliding size. This refers to the SLIDE argument in an SQL query, or the increment attribute of a window element in an XML query.
Action	Specify a valid sliding size.

WEPRME0128	The DURATION argument of a MATCHING clause must be greater than zero.
WEPRME0129	The WITHIN argument of a MATCHING clause must be greater than zero.
WEPRME0130	Duplicate definition for the pattern state "{0}".
WEPRME0131	The DEFINE clause does not define all the pattern states required by the specified pattern.
WEPRME0132	The field {0} is already defined by the input query.
WEPRME0133	The type of the defined field and the type of its default value do not match ({0}, {1}).
WEPRME0134	The type of the defined field and the type of the assigned value do not match ({0}, {1}).
WEPRME0135	The field names "START_TIMESTAMP" and "END_TIMESTAMP" are reserved for additional information provided by pattern matching.
WEPRME0136	The identifier for a pattern state must be a single character.
WEPRME0137	An aggregate is not allowed inside the condition in an action definition.
WEPRME0138	The condition of an action definition must be a predicate.
WEPRME0139	An aggregate is not allowed inside an action definition in a MATCHING clause.
WEPRME0140	The right-hand side of an action definition must be an expression.

- WEPRME0141** **Outer joins are currently not supported.**

- WEPRME0142** **Union joins are currently not supported.**

- WEPRME0143** **Only predicates are permitted in the ON clause of a join.**

- WEPRME0144** **Only predicates are permitted in a WHERE clause.**

- WEPRME0145** **The {0} operation requires identical output format of the involved subqueries.**

- WEPRME0146** **Only predicates are permitted in a disjunction.**

- WEPRME0147** **Only predicates are permitted in a conjunction.**

- WEPRME0148** **Only predicates are permitted in a negation.**

- WEPRME0149** **The EXISTS clause is currently not supported.**

- WEPRME0150** **An SQL expression list in a relational expression is currently not supported.**

- WEPRME0151** **A subquery in an operator expression is currently not supported.**

- WEPRME0152** **Only an expression is permitted as the first argument of a comparison.**

- WEPRME0153** **Only an expression is permitted as the second argument of a comparison.**

- WEPRME0154** **Only constants are allowed in the set of an IN clause.**

WEPRME0155	A subquery in an IN clause is currently not supported.
WEPRME0156	Only expressions are permitted as the first argument of a BETWEEN clause.
WEPRME0157	Only expressions are permitted as the second argument of a BETWEEN clause.
WEPRME0158	The arguments of the BETWEEN clause cannot be compared ({0}, {1}).
WEPRME0159	The first argument of the BETWEEN clause is greater than the second argument.
WEPRME0160	Only expressions are permitted in the IS NULL clause.
WEPRME0161	Only expressions are permitted in {0}.
WEPRME0162	Only expressions are permitted in an exponentiation.
WEPRME0163	Only expressions are permitted in a unary operation.
WEPRME0164	Only expressions are permitted in the WHEN clause of a simple CASE statement.
WEPRME0165	Only expressions are permitted in the THEN clause of a simple CASE statement.
WEPRME0166	Only expressions are permitted in the ELSE clause of a simple CASE statement.
WEPRME0167	Only predicates are permitted in the WHEN clause of a boolean CASE statement.
WEPRME0168	Only expressions are permitted in the THEN clause of a boolean CASE statement.

- WEPRME0169** **Only expressions are permitted in the ELSE clause of a boolean CASE statement.**

- WEPRME0170** **Duplicate field definition in recursive query.**

- WEPRME0171** **The number of defined fields in the recursive query does not match the number of fields in the subquery.**

- WEPRME0172** **The defined field name does not match the field name in the subquery.**

- WEPRME0173** **The defined field type does not match the field type in the subquery.**

- WEPRME0174** **Check the specified aggregation.**

- WEPRME0175** **Check the specified SELECT item.**

- WEPRME0176** **Check the specified DEFINE condition.**

- WEPRME0177** **Check the specified action.**

- WEPRME0178** **Check the specified part of the join predicate.**

- WEPRME0179** **Check the specified part of the WHERE clause.**

- WEPRME0180** **The operator type {0} is currently not allowed within a recursive query.**

- WEPRME0181** **The operator type {0} is not allowed within a recursive query.**

- WEPRME0182** **The type {0} is unexpected.**

WEPRME0183	The defined field is not null but the field in the subquery is nullable.
WEPRME0184	The input of a window has to be a chronon stream.
WEPRME0185	The pattern of a MATCHING clause must not be empty.
WEPRME0186	Only constant shifts, i.e., MILLISECONDS, SECONDS, MINUTES or HOURS, are allowed in the SHIFT clause.
WEPRME0187	Only constant DURATION arguments, i.e., MILLISECONDS, SECONDS, MINUTES or HOURS, are allowed in the MATCHING clause.
WEPRME0188	Only constant WITHIN arguments, i.e., MILLISECONDS, SECONDS, MINUTES or HOURS, are allowed in the MATCHING clause.
WEPRME0189	The base time specification does not represent a valid date/time.
Explanation	The query contains an invalid base time. This refers to the RELATIVE TO clause in an SQL query, or the relative-to attribute of a window element in an XML query.
Action	Specify a valid base time.
WEPRME0190	Distinct aggregates are currently not supported.
WEPRME0191	The LIKE clause requires a constant string pattern.
WEPRME0192	Only predicates are permitted in a HAVING clause.
WEPRME0193	Check the specified part of the HAVING clause.
WEPRME0194	Arrays of type {0} are currently not supported.

- WEPRME0195** **Only expressions of type BOOLEAN are allowed in this context but the present type is {0}.**

- WEPRME0196** **The {0} function only supports FLOAT and DOUBLE values as arguments.**

- WEPRME0197** **The argument of the CHAR_LENGTH function must be of string type.**

- WEPRME0198** **Casting from {0} to {1} is currently not supported.**

- WEPRME0199** **The argument of the {0} function must be numeric.**

- WEPRME0200** **The {0} argument of the {1} function must be numeric.**

- WEPRME0201** **Windows can only be applied to input streams or (sub)queries.**

- WEPRME0202** **Tried to configure DataSource with unknown connection type {0} in RTM system.**

- WEPRME0203** **Tried to configure unknown database table {0} in RTM system.**

- WEPRME0204** **Cannot find builder class for DataSource configured in RTM system.**

- WEPRME0205** **Cannot call builder class constructor for DataSource configured in RTM system.**

- WEPRME0206** **Cannot access specified database table for DataSource configured in RTM system.**

- WEPRME0207** **Initialization of CONNECT right failed.**

- WEPRME0208** **Unable to initialize privileges for super user.**

WEPRME0209	Unable to initialize privileges for monitoring user.
WEPRME0210	Unable to retrieve high availability partner host name.
WEPRME0211	Unable to initialize privileges for pre-loaded data sources.
WEPRME0212	Unable to retrieve localhost name.
WEPRME0213	The system is already started.
WEPRME0214	Unable to prepare communication servers.
WEPRME0215	The user cannot be connected as direct connections to this system are currently not allowed.
WEPRME0216	The user cannot be connected as the system is not started.
WEPRME0217	The user cannot be connected as the system is already shut down.
WEPRME0218	The user cannot be connected as the username is unknown or the password is wrong.
WEPRME0219	The user cannot be connected as the connect right is missing.
WEPRME0220	The connection cannot be removed from the system as it is unknown.
WEPRME0221	The system was already shut down.
WEPRME0222	Setting the class loader is only allowed before system start.

- WEPRME0223** **System is not running in high availability mode.**

- WEPRME0224** **The system does not allow remote connections.**

- WEPRME0225** **Create database allowed only before the system start.**

- WEPRME0226** **Drop database allowed only after system is already shut down.**

- WEPRME0227** **No high availability port given.**

- WEPRME0228** **Unable to send synchronous command.**

- WEPRME0229** **Internal error: Callback of class {0} provided to {1} is not an instance of {2}.**

- WEPRME0230** **Status of health check monitor of local system is not OK; shutting down!**

- WEPRME0231** **Unexpected exception in HA ServerConnectionHandler.**

- WEPRME0232** **Unexpected error occurred when master was driving recovery of slave.**

- WEPRME0233** **Unexpected error occurred when handling recovery request from master.**

- WEPRME0234** **Failed to close channel.**

- WEPRME0235** **NullPointerException occurred while accepting new connection.**

- WEPRME0236** **CommunicationException occurred while accepting new connection.**

WEPRME0237	Exception occurred while accepting new connection.
WEPRME0238	Error occurred while accepting new connection.
WEPRME0239	Exception when aborting connection process.
WEPRME0240	Unsupported protocol.
WEPRME0241	No handler registered for protocol {0}.
WEPRME0242	Handshake failed due to an exception.
WEPRME0243	Missing basic properties ({0}) needed to compute composed property.
WEPRME0244	Unable to start communication server.
WEPRME0245	Unable to start connect due to incompatible protocol versions.
WEPRME0246	Unexpected role {0}.
WEPRME0247	Received unknown command {0}.
WEPRME0248	The adapter must not be null.
WEPRME0249	The query {0} cannot be stopped as it is still in use by a subquery.
WEPRME0250	The query {0} cannot be stopped as it is still in use by a subscriber.

- WEPRME0251** **The subscription identifier {0} is already in use for user {1}.**

- WEPRME0252** **The approach ({0}) does not match approach of the query ({1}).**

- WEPRME0253** **The sink cannot be subscribed as the query {0} has not been started.**

- WEPRME0254** **Unable to compute starting point for snapshot-reducible results.**

- WEPRME0255** **Unable to start subscription {0} from {1}.**

- WEPRME0256** **The connection to all servers has been lost.**

- WEPRME0257** **At least one server address has to be provided.**

- WEPRME0258** **Unexpected interrupt when waiting for connection.**

- WEPRME0259** **Unable to connect to {0} due to incompatible server version.**

- WEPRME0260** **Authentication with remote system failed.**

- WEPRME0261** **Inconsistent high availability mode of servers.**

- WEPRME0262** **The source cannot be prepared as the query identifier {0}.{1} is already in use.**

- WEPRME0263** **Unable to parse the given SQL statement: {0}.**

- WEPRME0264** **Unable to compute property: {0}.**

WEPRME0265	The query cannot be prepared as the query identifier {0} is already in use.
WEPRME0266	The query {0} cannot be started as it is already closed.
WEPRME0267	The query {0} cannot be started as it is not yet initialized.
WEPRME0268	The mode {0} is not allowed for server subscriptions.
WEPRME0269	Persistent server subscriptions are only allowed with start time Long.MIN_VALUE.
WEPRME0270	Client subscription may not be unsubscribed using serverUnsubscribe - use unsubscribe.
WEPRME0271	Server subscription may not be unsubscribed using unsubscribe - use serverUnsubscribe.
WEPRME0272	Unable to stop subscription {0} from {1}.
WEPRME0273	A user-defined function factory is already registered for {0}.{1}.
WEPRME0274	No user-defined function is registered for {0}.{1}.
WEPRME0275	A data source is already registered for {0}.{1}.
WEPRME0276	A table is already registered for {0}.{1}.
WEPRME0277	No data source is registered for {0}.{1}.
WEPRME0278	No table is registered for {0}.{1}.

- WEPRME0279** **Subscription start point may only be computed for running queries.**

- WEPRME0280** **The query identifier {0} is unknown.**

- WEPRME0281** **Only numeric, string and date/time values can be used with {0} aggregation.**

- WEPRME0282** **Only numeric values can be used with {0} aggregation.**

- WEPRME0283** **Number of parameters for user-defined aggregation function {0} is {1}, but has to be {2}.**

- WEPRME0284** **Incompatible parameter type for user-defined aggregation function {0} (expected {1}, found {2}).**

- WEPRME0285** **Unknown aggregation type {0}.**

- WEPRME0286** **A {0} aggregate must have exactly one sub-expression.**

- WEPRME0287** **A {0} aggregate must not have more than one sub-expression.**

- WEPRME0288** **Only numeric, string and date/time values can be used with maximum/minimum aggregation.**

- WEPRME0289** **Only numeric values can be used with sum aggregation.**

- WEPRME0290** **The aggregate expression type {0} is currently not supported for approach {1}.**

- WEPRME0291** **Expected parameter type and actual input type do not match.**

WEPRME0292	An exception occurred during batch execution.
WEPRME0293	Client did not provide valid number of supported stream protocols.
WEPRME0294	No stream protocol requested by the client is supported.
WEPRME0295	None of the proposed stream protocols is supported by the server.
WEPRME0296	The stream protocol requested by the server is not supported.
WEPRME0297	An exception occurred while sending a command.
WEPRME0298	Registration of new protocol mappings is only allowed before starting.
WEPRME0299	Starting may be done only once.
WEPRME0300	A yet unknown version.
WEPRME0301	An error occurred while parsing {0} and converting it to the target date format.
WEPRME0302	Unable to determine own address.
WEPRME0303	The protocol {0} requires a serializer for complex {1} which is not available at the server.
WEPRME0304	The protocol {0} requires a serializer for complex {1} which is not available at the client.
WEPRME0305	Unknown protocol {0}.

- WEPRME0306** **There is no handler registered under identifier {0} for protocol {1}.**

- WEPRME0307** **A subscription to query {0} cannot be established as it has been configured to be non-subscribable.**

- WEPRME0308** **The query with identifier {0}.{1} is not a connectable source.**

- WEPRME0309** **Wrong approach: {0} (expected {1}).**

- WEPRME0310** **Unknown command for system operation:{0}.**

- WEPRME0311** **Unable to execute lock command on slave.**

- WEPRME0312** **Execution of command on slave causes exception.**

- WEPRME0313** **Unable to sync command with slave.**

- WEPRME0314** **Only the owner of a source may disconnect from it.**

- WEPRME0315** **Only the owner of a source may connect to it.**

- WEPRME0316** **The dynamic protocol handler could not be connected.**

- WEPRME0317** **The dynamic protocol adapter must not be null.**

- WEPRME0318** **Master result to slave communicators may only be added before the system is started.**

- WEPRME0319** **Unable to grant rights to subscribe to HA difference to user.**

WEPRME0320	Unable to execute recover command on slave.
WEPRME0321	Unable to retrieve health information from master.
WEPRME0322	Unable to retrieve health information from client.
WEPRME0323	Connection to HA partner system timed out.
WEPRME0324	There is already a class {0} bound.
WEPRME0325	This callback is already disconnected.
WEPRME0326	Unable to store entry of class {0} in repository.
WEPRME0327	The repository already contains an artefact of type {0} for {1}.{2}.
WEPRME0328	Repository error: the entry to retrieve is unknown.
WEPRME0329	Repository error: the entry to remove is unknown.
WEPRME0330	Repository error: unknown subscription.
WEPRME0331	Repository does not contain an artefact of type {0} with owner {1} and identifier {2} or it might not be accessed.
WEPRME0332	Loading repository from database failed.
WEPRME0333	Unable to access notification dispatcher of underlying local connection as remote connection is not yet authenticated.

- WEPRME0334** **The user-defined aggregation function must not be null.**

- WEPRME0335** **The class of the user-defined aggregation function must not be null.**

- WEPRME0336** **Persistency for user-defined aggregation functions is currently not supported.**

- WEPRME0337** **The server user-defined aggregation function cannot be registered.**

- WEPRME0338** **The user-defined aggregation function cannot be registered.**

- WEPRME0339** **The user-defined aggregation function cannot be deregistered.**

- WEPRME0340** **The user-defined operator adapter factory must not be null.**

- WEPRME0341** **The class of the user-defined operator adapter factory must not be null.**

- WEPRME0342** **Persistency for user-defined operators is currently not supported.**

- WEPRME0343** **The server user-defined operator cannot be registered.**

- WEPRME0344** **The user-defined operator cannot be registered.**

- WEPRME0345** **The user-defined operator cannot be deregistered.**

- WEPRME0346** **The user {0} does not have the privilege to add the user-defined aggregation function.**

- WEPRME0347** **The user {0} does not have the privilege to remove the user-defined aggregation function.**

WEPRME0348	The user {0} does not have the privilege to add the user-defined operator.
WEPRME0349	The user {0} does not have the privilege to remove the user-defined operator.
WEPRME0350	An user-defined aggregation function is already registered for {0}.{1}.
WEPRME0351	No user-defined aggregation function is registered for {0}.{1}.
WEPRME0352	A user-defined operator is already registered for {0}.{1}.
WEPRME0353	No user-defined operator is registered for {0}.{1}.
WEPRME0354	Only expressions are permitted as argument of {0} functions.
WEPRME0355	Only expressions are permitted as {0} argument of {1} functions.
WEPRME0356	The connected system does not support the registration of user-defined aggregation functions.
WEPRME0357	The connected system does not support the deregistration of user-defined aggregation functions.
WEPRME0358	The connected system does not support the registration of user-defined operators.
WEPRME0359	The connected system does not support the deregistration of user-defined operators.
WEPRME0360	The operator adapter factory class for the user-defined operator adapter factory must not be null.

- WEPRME0361** **Unable to create instance of {0}.**

- WEPRME0362** **{0} does not provide a constructor with signature String[], which is obligatory.**

- WEPRME0363** **Class not found.**

- WEPRME0364** **The user-defined operator factory already exists in the database.**

- WEPRME0365** **The saving of the user-defined operator factory to the database failed.**

- WEPRME0366** **The removal of the user-defined operator factory from the database failed.**

- WEPRME0367** **The parameter type number {0} of a user-defined operator adapter factory for {1}.{2} must not be null.**

- WEPRME0368** **User-defined operator adapter must not be null.**

- WEPRME0369** **Wrong parameters - use class name and method name.**

- WEPRME0370** **Unable to find class {0}.**

- WEPRME0371** **The method name {0} is not unique in class {1}.**

- WEPRME0372** **The method {0} is not declared in class {1}.**

- WEPRME0373** **Methods using varargs are not supported.**

- WEPRME0374** **The method {0} is not static.**

WEPRME0375	The method {0} is not public.
WEPRME0376	The return type {0} of method {1} is not supported.
WEPRME0377	The parameter type {0} of method {1} is not supported.
WEPRME0378	The method has been called with wrong parameters.
WEPRME0379	The method is not accessible.
WEPRME0380	The method cannot be invoked.
WEPRME0381	Wrong number of parameters.
WEPRME0382	No such class found: {0}.
WEPRME0383	Unable to invoke {0}.
WEPRME0384	Unable to determine number of inputs.
WEPRME0385	Unable to determine parameter types.
WEPRME0386	Unable to determine output metadata.
WEPRME0387	Unable to access {0}.
WEPRME0388	No such method available: {0}.

- WEPRME0389** **Return type of method {0} must be StreamMetaData.**

- WEPRME0390** **Return type of method {0} must be JavaTypes.Type.**

- WEPRME0391** **Unable to access constructor.**

- WEPRME0392** **No valid constructor available.**

- WEPRME0393** **Wrong parameters: use class name and method names.**

- WEPRME0394** **The {0} method must have at least two parameters.**

- WEPRME0395** **The state parameter type and the return type of {0} have to be the same.**

- WEPRME0396** **The {0} method must have one parameter.**

- WEPRME0397** **The state parameter type of {0} must be the same as the state parameter type of {1}.**

- WEPRME0398** **The method {0} must not have any parameters.**

- WEPRME0399** **The return type of {0} must be the same as state parameter type of {1}.**

- WEPRME0400** **The user-defined operator {0},{1} is unknown or not visible.**

- WEPRME0401** **The parameter type {0} must be the same as value parameter type of {1}.**

- WEPRME0402** **The state parameter type {0} and return type of {1} have to be the same.**

WEPRME0403	The method {0} must have one parameter.
WEPRME0404	The state parameter type of {0} must be the same as state parameter type of {1}.
WEPRME0405	The return type of {0} must be boolean.
WEPRME0406	The statements are not initialized.
WEPRME0407	The statements have to be initialized first.
WEPRME0408	This statement is not available.
WEPRME0409	The operation removeAll is not supported.
WEPRME0410	The operation removeAndReturn is currently not supported.
WEPRME0411	Elements are already removed by next.
WEPRME0412	{0} is not contained.
WEPRME0413	Calling the method getMinTimeStamp only supported in ordered remove mode.
WEPRME0414	Structure is empty.
WEPRME0415	The only supported key is key 0.
WEPRME0416	Not possible as heap is consuming.

- WEPRME0417** **Remove is always done.**

- WEPRME0418** **The initial list has to be empty.**

- WEPRME0419** **The length of the specified byte array does not match the length of the serialized byte array.**

- WEPRME0420** **The given text node does not contain a single character.**

- WEPRME0421** **The given node cannot be read.**

- WEPRME0422** **The end of file has been reached before record metadata could be read completely.**

- WEPRME0423** **The number of column names and column types differ.**

- WEPRME0424** **The value contains more than one character.**

- WEPRME0425** **The value is not in JDBC time escape format or null.**

- WEPRME0426** **The value is not in JDBC date escape format or null.**

- WEPRME0427** **The character encoding {0} is not supported.**

- WEPRME0428** **The class of the serialized object was not found.**

- WEPRME0429** **The class used by serialization is invalid.**

- WEPRME0430** **The input stream is corrupt.**

WEPRME0431	The input stream consists of primitive data instead of objects.
WEPRME0432	An input/output error has occurred.
WEPRME0433	Writing a serializable object to a string failed due to I/O error.
WEPRME0434	Writing a serializable object to a string failed due to security problems.
WEPRME0435	Writing a serializable object to a string failed due to output stream being null.
WEPRME0436	NULL as null code is not allowed.
WEPRME0437	The end of file has been reached before record could be read completely.
WEPRME0438	The number of values differs from record metadata definition (expecting {0} but found {1}).
WEPRME0439	The index referring to the local error array is out of bounds.
WEPRME0440	The value for column {0} ({1}) must not be null.
WEPRME0441	Error converting value "{0}" to type {1}. {2}.
WEPRME0442	No error at index {0} in the local error array.
WEPRME0443	The length of the specified byte array does not match the length of the serialized double array.
WEPRME0444	The length of the specified byte array does not match the length of the serialized long array.

- WEPRME0445** **The class of the object to be read cannot be found ({0}).**

- WEPRME0446** **The length of the specified byte array does not match the length of the serialized String array.**

- WEPRME0447** **This serializer does not support the restoring of objects.**

- WEPRME0448** **Unsupported type code: {0}.**

- WEPRME0449** **Unsupported type name: {0}.**

- WEPRME0450** **Unsupported type: {0}.**

- WEPRME0451** **Types may not be null.**

- WEPRME0452** **Unsupported Java type: {0} ({1}).**

- WEPRME0453** **Unsupported SQL type: {0}.**

- WEPRME0454** **Negative iterator only supported if negative counts are not.**

- WEPRME0455** **Call to next while not hasNext.**

- WEPRME0456** **The distinctIterator is not supported if negative counts are allowed.**

- WEPRME0457** **Queue is empty.**

- WEPRME0458** **Pos={0}, size={1}.**

WEPRME0459	Operation results in negative value.
WEPRME0460	Negative value.
WEPRME0461	The argument is not an array.
WEPRME0462	The argument is not a wrapper array.
WEPRME0463	SingleObjectList already contains an object.
WEPRME0464	SingleObjectList only supports index 0.
WEPRME0465	SingleObjectList already may only contain one object.
WEPRME0466	This list is empty.
WEPRME0467	SingleObjectList does not support subList.
WEPRME0468	A time period with non-constant time unit (day, week, month and year) must not be greater than {0}.
WEPRME0469	The size in milliseconds of the time period can only be calculated for constant time periods.
WEPRME0470	Composite metadata already contains specified metadata fragment "{0}".
WEPRME0471	Some metadata fragments cannot be added to composite metadata:{0}.
WEPRME0472	Composite metadata does not contain specified metadata "{0}".

- WEPRME0473** **User {0} is already subscribed to {1}.**

- WEPRME0474** **Identifier {0} is not supported.**

- WEPRME0475** **Unable to subscribe to {0} due to failed subscription to dependent metadata: {1}.**

- WEPRME0476** **User {0} is not subscribed to {1}.**

- WEPRME0477** **Unexpected parameter {0}=>{1}.**

- WEPRME0478** **Illegal parameter type! Expected {0}, found {1}.**

- WEPRME0479** **Missing parameter(s): {0}.**

- WEPRME0480** **Double metadata update - this should not appear in current update mechanism.**

- WEPRME0481** **Transparent composite metadata does not contain specified metadata "{0}" as a direct fragment, hence it cannot be removed.**

- WEPRME0482** **Requested point is not part of the domain.**

- WEPRME0483** **Empty domain.**

- WEPRME0484** **New domain ({0},{1}) has to be contained in old one ({2},{3}).**

- WEPRME0485** **Range out of domain.**

- WEPRME0486** **From==to but fromFactor != toFactor.**

WEPRME0487	New domain has to be contained in old one.
WEPRME0488	Bound out of domain.
WEPRME0489	A weight has to be given for each function.
WEPRME0490	Functions do not have a common domain.
WEPRME0491	Parse error at position {0}, cause: {1}.
WEPRME0492	Syntax not supported.
WEPRME0493	Unexpected end of regular expression.
WEPRME0494	Missing number in count expression.
WEPRME0495	Non-digit in count expression.
WEPRME0496	Empty (sub) expression.
WEPRME0497	Range error.
WEPRME0498	Count value is 0.
WEPRME0499	Right parenthesis without matching left parenthesis.
WEPRME0500	Left parenthesis without matching right parenthesis.

- WEPRME0501** **Negative call on empty state.**

- WEPRME0502** **Wrong number of parameters.**

- WEPRME0503** **Empty state.**

- WEPRME0504** **The switch function does not contain a function for the given identifier and no default function is specified.**

- WEPRME0505** **Too many parameters fixed.**

- WEPRME0506** **Inconsistent length of arguments.**

- WEPRME0507** **Indices have to be in ascending order.**

- WEPRME0508** **{0} cannot be used as result type for conversion.**

- WEPRME0509** **This UserDefinedOperator has too many inputs. Maximum expected: {0}. Found: {1},{2}**

- WEPRME0510** **This UserDefinedOperator is missing inputs. Minimum expected: {0}. Found: {1},{2}**

- WEPRME0511** **TableName has to be provided.**

- WEPRME0512** **Map has to be provided.**

- WEPRME0513** **Error reading file.**

- WEPRME0514** **Read line does not match the expected format (check number of rows and row delimiter).**

WEPRME0515	A method responsible for updating a structure was called in a class which does not support updates.
WEPRME0516	ResultSet does not provide row {0}.
WEPRME0517	File {0} cannot be written.
WEPRME0518	Row names must not be null.
WEPRME0519	Error parsing date {0}.
WEPRME0520	No update necessary after delete.
WEPRME0521	At least one row has to be mapped.
WEPRME0522	A required value is missing in the given line.
WEPRME0523	Between line {0} and {1} : {2}.
WEPRME0524	Line {0} : {1}.
WEPRME0525	Number of successful commands must not be negative.
WEPRME0526	At least one supported stream protocol has to be provided.
WEPRME0527	CreateArray only works for complex array types, not for {0}.
WEPRME0528	Unsupported type {0}.

- WEPRME0529** **[This Error replaces a {0} which is not available to the class loader.] {1}.**

- WEPRME0530** **[This RuntimeException replaces a {0} which is not available to the class loader.] {1}.**

- WEPRME0531** **Unable to serialize Object.**

- WEPRME0532** **Unsupported modifier.**

- WEPRME0533** **Unable to deserialize Object.**

- WEPRME0534** **Channel is already closed!**

- WEPRME0535** **The null communication type should not be sent.**

- WEPRME0536** **Java serialization is not supported. Use ObjectOutputStreamCommunication if needed.**

- WEPRME0537** **Unsupported type {0}.**

- WEPRME0538** **Unsupported type.**

- WEPRME0539** **Exception while receiving {0}.**

- WEPRME0540** **Communication type must not be null.**

- WEPRME0541** **Factory parameters must not be null.**

- WEPRME0542** **Unable to create server on address other than local address.**

WEPRME0543	Unable to resolve {0}.
WEPRME0544	Unsupported CommunicationType: {0}.
WEPRME0545	Could not receive answer as receiving was interrupted.
WEPRME0546	Could not receive answer as connection was closed due to an exception.
WEPRME0547	Requests must not use ResponseStatus.
WEPRME0548	Exception while handling async command ({0}).
WEPRME0549	More than one ID is not supported yet.
WEPRME0550	No command handler registered for ID {0}.
WEPRME0551	Command {0} sent by wrong side of communication.
WEPRME0552	Command {0} is asynchronous.
WEPRME0553	Command {0} is synchronous.
WEPRME0554	Wrong protocol, expected {0} but received unknown protocol ID {1}.
WEPRME0555	Wrong protocol, expected {0} but received {1}.
WEPRME0556	Wrong magic value for protocol {0}.

- WEPRME0557** **Protocol must not be null.**

- WEPRME0558** **Uninitialized composite serializer for {0}.**

- WEPRME0559** **Registration not possible after shutdown.**

- WEPRME0560** **There is no address registered for handling protocol {0}.**

- WEPRME0561** **There is already a handler registered for protocol {0}.**

- WEPRME0562** **There is no handler registered for protocol {0}.**

- WEPRME0563** **Unable to shut down server at {0}.**

- WEPRME0564** **Unable to shut down {0} communication servers.**

- WEPRME0565** **Compatibility matrix has to be provided.**

- WEPRME0566** **Duplicate ID{0}.**

- WEPRME0567** **No request types provided for {0}.**

- WEPRME0568** **No respond types provided for {0}.**

- WEPRME0569** **Unknown command ID: {0}.**

- WEPRME0570** **Missing serializer for complex {0}.**

WEPRME0571	Parameter has to specify a directory.
WEPRME0572	Channel is already closed!
WEPRME0573	Unable to read communication server index file {0}.
WEPRME0574	Unable to start communication server on directory {0}.
WEPRME0575	Unable to create communication server index file {0}.
WEPRME0576	The stream protocol requested by the client is not supported.
WEPRME0577	The stream protocol {0} requested by the client is not supported.
WEPRME0578	Exception while closing streams.
WEPRME0579	Unable to accept a new connection in the specified time.
WEPRME0580	No server present at {0} .
WEPRME0581	File instead of directory found at server address {0}.
WEPRME0582	Unknown stream protocol: {0}.
WEPRME0583	Unable to connect to {0}.
WEPRME0584	Unable to close socket.

- WEPRME0585** **Protocol handler must not be null.**

- WEPRME0586** **There was already a handler registered for protocol {0}.**

- WEPRME0587** **There was already a handler registered.**

- WEPRME0588** **The handler to register does not handle the correct protocol {0}.**

- WEPRME0589** **This server does not support protocol type {0}.**

- WEPRME0590** **Unable to start communication server on port {0}.**

- WEPRME0591** **Unable to close server socket.**

- WEPRME0592** **Unable to connect to {0};{1}.**

- WEPRME0593** **Unable to initialize cache.**

- WEPRME0594** **Cache already exists but with another end timestamp.**

- WEPRME0595** **Unable to remove the specified cache.**

- WEPRME0596** **New SerialBlob(..) threw SerialException.**

- WEPRME0597** **New SerialBlob(..) threw SQLException.**

- WEPRME0598** **Write(Element,Node) needs operator, expression or predicate.**

WEPRME0599	Node conversion not implemented for type {0} and sub-type {1}.
WEPRME0600	Unsupported constant type: {0}.
WEPRME0601	Outer semi join.
WEPRME0602	Non-constant unit in time shift.
WEPRME0603	Expression wrapped by this predicate is not of type BOOLEAN.
WEPRME0604	Only expressions can be used as boolean expressions.
WEPRME0605	A boolean expression must not have any sub-predicates.
WEPRME0606	Argument types cannot be compared with {0}.
WEPRME0607	Only expressions can be used as arguments of a comparison predicate.
WEPRME0608	Second parameter of LIKE has to be a constant.
WEPRME0609	Second parameter of LIKE has to be a String.
WEPRME0610	Invalid operator [{0}].
WEPRME0611	A comparison predicate must not have any sub-predicates.
WEPRME0612	The comparison predicate's arguments are not comparable.

- WEPRME0613** **Incomparable Java type {0}.**

- WEPRME0614** **The state of the logical constant is unknown.**

- WEPRME0615** **A logical constant must not have any sub-predicates.**

- WEPRME0616** **Unknown logical constant type {0}.**

- WEPRME0617** **The logical operation type {0} is currently not supported.**

- WEPRME0618** **Illegal member specification.**

- WEPRME0619** **Illegal set specification.**

- WEPRME0620** **Types of member and set are not comparable.**

- WEPRME0621** **Illegal subpredicate.**

- WEPRME0622** **Unknown logical operation type {0}.**

- WEPRME0623** **Only predicates can be used as child nodes of a logical operation predicate.**

- WEPRME0624** **Only operators can be used as sets of an exists predicate.**

- WEPRME0625** **Only expressions can be used as expression of an in predicate.**

- WEPRME0626** **Only operators can be used as sets of an in predicate.**

WEPRME0627	A logical (boolean) IN operator must not have any sub-predicates.
WEPRME0628	A logical (boolean) IN operator does not yet support subqueries.
WEPRME0629	A logical (boolean) NOT must have exactly one sub-predicate.
WEPRME0630	A logical (boolean) NOT must not have more than one sub-predicate.
WEPRME0631	Unknown logical operation type {0}.
WEPRME0632	Unknown aggregation operator mode {0}.
WEPRME0633	Only predicates can be used as filter predicate nodes of an aggregation operator.
WEPRME0634	Only operators can be used as child nodes of an aggregation operator.
WEPRME0635	An aggregation operator must have exactly one input operator.
WEPRME0636	An aggregation operator must not have more than one input operator.
WEPRME0637	Aggregation is currently not supported within recursive PN queries.
WEPRME0638	Unsupported target approach: {0}.
WEPRME0639	Filter predicates are currently not supported in passive aggregation operators.
WEPRME0640	Unknown aggregation operator mode {0}.

- WEPRME0641** **A distinct operator must have exactly one operator.**

- WEPRME0642** **A distinct operator must not have more than one input operator.**

- WEPRME0643** **Unknown distinct operator mode {0}.**

- WEPRME0644** **Empty enumeration.**

- WEPRME0645** **Enumeration contains constants of different types.**

- WEPRME0646** **An enumeration operator must not have any input operators.**

- WEPRME0647** **An enumeration operator provides a set of constants as subquery-replacement for the use in IN-predicates, hence no active enumeration operators are possible.**

- WEPRME0648** **Unknown enumeration operator mode {0}.**

- WEPRME0649** **The specified object is not of the expected type; {0}.**

- WEPRME0650** **ActionMapFormat.parseActionMap(String) failed.**

- WEPRME0651** **Only operators can be used as child nodes of an equivalence operator.**

- WEPRME0652** **The chosen query plan (operator at index {0}) does not exist.**

- WEPRME0653** **The relational metadata of the operator node's children does not fit.**

- WEPRME0654** **The operator node has no children.**

WEPRME0655	Only operators can be used as child nodes of an except/minus operator.
Explanation	An except/minus operator must have exactly two input operators, which provide the input events for the except operator. The except/minus operator returns all events of the first input stream that are not in the second input stream. This means that only the events that are different are returned.
Action	Connect exactly two operators as input of the except/minus operator.
WEPRME0656	An except/minus operator must have exactly two input operators.
Explanation	An except/minus operator must have exactly two input operators, which provide the input events for the except operator. The except/minus operator returns all events of the first input stream that are not in the second input stream. This means that only the events that are different are returned.
Action	Connect exactly two operators as input of the except/minus operator.
WEPRME0657	An except/minus operator must not have more than two input operators.
Explanation	An except/minus operator must have exactly two input operators, which provide the input events for the except operator. The except/minus operator returns all events of the first input stream that are not in the second input stream. This means that only the events that are different are returned.
Action	Connect exactly two operators as input of the except/minus operator.
WEPRME0658	Unknown except/minus operator mode {0}.
WEPRME0659	Passive operators does not have chronon stream properties.
WEPRME0660	I/O exception occurred during metadata construction: "{0}".
WEPRME0661	Only column expressions specified by a single column name can be used as timestamp columns of a file operator.
WEPRME0662	Only operators can be used as child nodes of an output file operator.

- WEPRME0663** **An input-file operator must not have any input operators.**

- WEPRME0664** **File not found.**

- WEPRME0665** **Unable to read file header.**

- WEPRME0666** **Time information must have a reference timestamp.**

- WEPRME0667** **Time information must not have any additional timestamps.**

- WEPRME0668** **Unknown file operator mode {0}.**

- WEPRME0669** **An output-file operator must have exactly one input operator.**

- WEPRME0670** **An output-file operator must not have more than one input operator.**

- WEPRME0671** **For storing time intervals the names of the columns storing the start and an end timestamp are required.**

- WEPRME0672** **File writing currently unsupported.**

- WEPRME0673** **Unknown file operator type {0}.**

- WEPRME0674** **Only operators can be used as child nodes of a selection operator.**

- WEPRME0675** **A selection operator must have exactly one input operator.**

- WEPRME0676** **A selection operator must not have more than one input operator.**

WEPRME0677	Unknown identity operator mode {0}.
WEPRME0678	Only operators can be used as child nodes of an intersection operator.
WEPRME0679	An intersect operator must have exactly two input operators.
WEPRME0680	An intersect operator must not have more than two input operators.
WEPRME0681	Unknown target approach {0}.
WEPRME0682	Unknown intersect operator mode {0}.
WEPRME0683	Only operators can be used as child nodes of a join operator.
WEPRME0684	Only predicates can be used as condition of a theta join operator.
WEPRME0685	A join operator must have at least two input operators.
WEPRME0686	Implementations of multiway join are currently not supported, i.e., they must be transformed to join plans of binary joins using the query optimizer.
WEPRME0687	Implementations of outer joins are currently not supported.
WEPRME0688	Implementations of semi joins are currently not supported.
WEPRME0689	Implementations of joins between active and passive source are currently not supported.
WEPRME0690	Unknown join type {0}.

- WEPRME0691** **Implementations of joins between active and passive sources in PN algebra are currently not supported.**

- WEPRME0692** **Unknown approach {0}.**

- WEPRME0693** **Unknown join mode {0}.**

- WEPRME0694** **Implementations of natural joins without common attributes between active and passive sources are currently not supported.**

- WEPRME0695** **Columns named by {0} cannot be unified because of different types.**

- WEPRME0696** **Column failure.**

- WEPRME0697** **Only operators can be used as child nodes of a mapping operator.**

- WEPRME0698** **A mapping operator must have exactly one input operator.**

- WEPRME0699** **A mapping operator must not have more than one input operator.**

- WEPRME0700** **Unknown mapping operator mode {0}.**

- WEPRME0701** **Some pattern variables are undefined.**

- WEPRME0702** **Only constants can be used as initial values of a matching operator's MEASURE clause.**

- WEPRME0703** **Only columns can be used in a matching operator's PARTITION BY part.**

WEPRME0704	Only predicates can be used in the AS part of a matching operator's DEFINE clause.
WEPRME0705	Only columns can be used on the left side of a DO part of a matching operator's DEFINE clause.
WEPRME0706	Only expressions can be used on the right side of a DO part of a matching operator's DEFINE clause.
WEPRME0707	Only operators can be used as child nodes of a matching operator.
WEPRME0708	A pattern matcher must have exactly one input operator.
WEPRME0709	A pattern matcher must have a synthetic input representing the underlying NFA's state.
WEPRME0710	A pattern matcher must not have more than two input operators.
WEPRME0711	Pattern matching is currently not supported for target approach: {0}.
WEPRME0712	{0} mode not supported.
WEPRME0713	Unknown selection operator mode {0}.
WEPRME0714	The relational metadata of the operator node's children does not fit.
WEPRME0715	The operator node has no children.
WEPRME0716	Only operators can be used as child nodes of a projection operator.

- WEPRME0717** **A projection operator must have exactly one input operator.**
- WEPRME0718** **A projection operator must not have more than one input operator.**
- WEPRME0719** **Unknown projection operator mode {0}.**
- WEPRME0720** **Unsupported data type.**
- WEPRME0721** **A random operator must not have any input operators.**
- WEPRME0722** **Random sources are currently not supported for target approach: {0}.**
- WEPRME0723** **Unknown random operator mode {0}.**
- WEPRME0724** **Unknown content.**
- WEPRME0725** **Ambiguous content.**
- WEPRME0726** **Only operators can be used as child nodes of a recursion operator.**
- WEPRME0727** **A recursion operator must have exactly one input operator.**
- WEPRME0728** **A recursion operator must not have more than one input operator.**
- WEPRME0729** **The use of recursion operators inside the cursor algebra is currently not supported.**
- WEPRME0730** **Unknown recursion operator mode {0}.**

WEPRME0731	Only operators can be used as child nodes of a renaming operator.
WEPRME0732	A renaming operator must have exactly one input operator.
WEPRME0733	A renaming operator must not have more than one input operator.
WEPRME0734	Unknown renaming operator mode {0}.
WEPRME0735	A repository entry operator must not have any input operators.
WEPRME0736	A repository entry operator with name {0} for user {1} is unknown.
WEPRME0737	A subquery using the approach {0} cannot be used in a query compiled for the approach {1}.
WEPRME0738	Only predicates can be used as condition of a selection operator.
WEPRME0739	Only operators can be used as child nodes of a selection operator.
WEPRME0740	A selection operator must have exactly one input operator.
WEPRME0741	A selection operator must not have more than one input operator.
WEPRME0742	Unknown selection operator mode {0}.
WEPRME0743	No value columns specified.
WEPRME0744	Wrong number of fields in value {0} (expected {1}, found {2}).

- WEPRME0745** For exact matches exactly one count argument must be specified.
- WEPRME0746** For maximum matches exactly one count argument must be specified.
- WEPRME0747** For minimum matches exactly one count argument must be specified.
- WEPRME0748** For range matches exactly two count arguments must be specified.
- WEPRME0749** Only operators can be used as child nodes of a set operator.
- WEPRME0750** A set operator must have exactly one input operator.
- WEPRME0751** A set operator must not have more than one input operator.
- WEPRME0752** The defined field list and the specified values are not comparable.
- WEPRME0753** Unknown mode {0}.
- WEPRME0754** Sets are currently not supported for target approach: {0}.
- WEPRME0755** Unknown selection operator mode {0}.
- WEPRME0756** Only operators can be used as child nodes of an output socket operator.
- WEPRME0757** A input-socket operator must not have any input operators.
- WEPRME0758** At this point a source reading its data from a socket channel to {0}@{1}:{2} should be returned.

WEPRME0759	An output-socket operator must have exactly one input operator.
WEPRME0760	An output-socket operator must not have more than one input operator.
WEPRME0761	At this point a sink writing the data received from {0} to a socket channel available at {1}@{2}:{3} should be returned.
WEPRME0762	Unknown socket type {0}.
WEPRME0763	The use of sockets inside the cursor algebra is currently not supported.
WEPRME0764	Unknown socket operator mode {0}.
WEPRME0765	Local metadata fragment identified by {0} cannot be created because of multiple fields matching the field name pattern.
WEPRME0766	Local metadata fragment identified by {0} cannot be created because no available field matches the field name pattern.
WEPRME0767	This exception is thrown to avoid the creation of a new metadata fragment.
WEPRME0768	Initialization is only available for source operators.
WEPRME0769	Recursive query not contained.
WEPRME0770	Source operators are internally used for identifying data sources, hence the occurrence of this exception is a signal of a misuse of a source operator.
WEPRME0771	Only operators can be used as child nodes of a stream operator.

- WEPRME0772** **A stream operator must have exactly one input operator.**

- WEPRME0773** **A stream operator must not have more than one input operator.**

- WEPRME0774** **The use of stream operators inside the pipes algebra is currently not supported.**

- WEPRME0775** **The target of a stream operator is to transform a passive query into an active one, hence no passive stream operators are possible.**

- WEPRME0776** **Unknown stream operator mode {0}.**

- WEPRME0777** **Only operators can be used as child nodes of a time shift.**

- WEPRME0778** **A time shifter must have exactly one input operator.**

- WEPRME0779** **A time shifter must not have more than one input operator.**

- WEPRME0780** **A time shifter must have a constant time shift.**

- WEPRME0781** **Unknown selection operator mode {0}.**

- WEPRME0782** **{0} mode not supported.**

- WEPRME0783** **Only operators can be used as child nodes of an union operator.**

- WEPRME0784** **A union operator must have at least two input operators.**

- WEPRME0785** **A union operator must have at least two input operators.**

WEPRME0786	Unknown union operator mode {0}.
WEPRME0787	Only an operator can be used as child node of a window operator.
WEPRME0788	A window operator must have exactly one input operator.
WEPRME0789	A window operator must not have more than one input operator.
WEPRME0790	A window operator on a non-chronon stream is currently not supported.
WEPRME0791	Unknown window operator type {0}.
WEPRME0792	The use of a window operator inside the cursor algebra is currently not supported.
WEPRME0793	Unknown window operator mode: {0}.
WEPRME0794	Only expressions can be used as child nodes of an aggregate expression.
WEPRME0795	Initialization is only available for user-defined aggregation functions.
WEPRME0796	User-defined aggregation function does not support PN approach.
WEPRME0797	A constant expression must not have any sub-expressions.
WEPRME0798	Local metadata fragment identified by {0} cannot be created.
WEPRME0799	Local metadata fragment identified by {0} cannot be created because of multiple fields matching the field name pattern.

- WEPRME0800** **Local metadata fragment identified by {0} cannot be created because no available field matches the field name pattern.**

- WEPRME0801** **A column expression must not have any sub-expressions.**

- WEPRME0802** **Unable to identify field {0}.**

- WEPRME0803** **Only numeric values can be used with ABS function.**

- WEPRME0804** **The decimal place parameter has to be of type Integer.**

- WEPRME0805** **Illegal condition.**

- WEPRME0806** **Case does not provide FieldMetaData.**

- WEPRME0807** **Inconsistent types in case.**

- WEPRME0808** **Wrong number of parameters for user-defined function {0}(expected {1}, found {2}).**

- WEPRME0809** **Incompatible parameter type for user-defined function {0}(expected {1}, found {2}).**

- WEPRME0810** **Only String values can be used with CHAR_LENGTH function.**

- WEPRME0811** **Casting from {0} to {1} is currently not supported.**

- WEPRME0812** **Unknown function type {0}.**

- WEPRME0813** **Only expressions can be used as child nodes of a function expression.**

WEPRME0814	Initialization is only available for user-defined functions.
WEPRME0815	A {0} operation must have exactly two sub-expressions.
WEPRME0816	A {0} operation must not have more than two sub-expressions.
WEPRME0817	Only numeric values can be used with ABS function.
WEPRME0818	FLOOR function only supports Double and Float values.
WEPRME0819	CEILING function only supports Double and Float values.
WEPRME0820	The result type of a CHAR_LENGTH function has to be Integer.
WEPRME0821	ROUND function only supports numeric values.
WEPRME0822	TRUNCATE function only supports numeric values.
WEPRME0823	Currently casting between these types is not allowed.
WEPRME0824	Currently only casting between numeric types and casting to String type is supported.
WEPRME0825	A {0} function must not have any sub-expressions.
WEPRME0826	Unexpected undefined case.
WEPRME0827	Parameters missing for user-defined function {0}.

- WEPRME0828** **Too many parameters for user-defined function {0}.**

- WEPRME0829** **Unknown function expression type {0}.**

- WEPRME0830** **Only numeric values can be negated.**

- WEPRME0831** **Only numeric values can be mathematically subsumed.**

- WEPRME0832** **Exponentiation with base type {0} is only allowed for exponent types {1}, {2} and {3}.**

- WEPRME0833** **Exponent type cannot be {0}.**

- WEPRME0834** **Only textual values can be concatenated.**

- WEPRME0835** **Unknown operation type {0}.**

- WEPRME0836** **Recognized a numeric constant without a numeric data type.**

- WEPRME0837** **Only expressions can be used as child nodes of an operation expression.**

- WEPRME0838** **A {0} operation must have exactly one sub-expression.**

- WEPRME0839** **A {0} operation must not have more than one sub-expression.**

- WEPRME0840** **A {0} operation must have exactly two sub-expressions.**

- WEPRME0841** **A {0} operation must not have more than two sub-expressions.**

WEPRME0842	Unknown operation expression type {0}.
WEPRME0843	Only numeric values can be negated.
WEPRME0844	Only numeric values can be mathematically subsumed.
WEPRME0845	Unknown operation expression type {0}.
WEPRME0846	The instantiation parameter types of a user-defined operator adapter factory for {0},{1} must not be null.
WEPRME0847	Only expressions can be used as child nodes of a renamed field expression.
WEPRME0848	A renamed field expression must have exactly one sub-expression.
WEPRME0849	A renamed field expression must not have more than one sub-expression.
WEPRME0850	Child at index {0} cannot be accessed because the given index is not assigned so far.
WEPRME0851	Index {0} cannot be accessed ({1} children are allowed).
WEPRME0852	Index {0} cannot be accessed ({1} parents are allowed).
WEPRME0853	New child has reached its maximum number of parents (number of allowed parents: {0}).
WEPRME0854	New parent has reached its maximum number of children (number of allowed children: {0}).

- WEPRME0855** Node has reached its maximum number of children (number of allowed children: {0}).
- WEPRME0856** Node has reached its maximum number of parents (number of allowed parents: {0}).
- WEPRME0857** Only use this method on nodes without a fixed number of children.
- WEPRME0858** Only use this method on nodes without a fixed number of parents.
- WEPRME0859** Parent at index {0} cannot be accessed because the given index is not assigned so far.
- WEPRME0860** A node of the specified iteration cannot be added to the given node's global metadata because it does not hold the specified precondition.
- WEPRME0861** This exception is thrown to avoid the creation of a new metadata fragment after resetting.
- WEPRME0862** Not contained.
- WEPRME0863** Entry already contained.
- WEPRME0864** Entry not contained.
- WEPRME0865** SpeedUp <0 is not allowed.
- WEPRME0866** Unsupported SQL data type.
- WEPRME0867** Period has to be equal to or greater than 0.

WEPRME0868	This period worker thread cannot be woken up, because wait time is zero.
WEPRME0869	The parameter type number {0} of a user-defined function adapter for {1}.{2} must not be null.
WEPRME0870	The return type of a user-defined function adapter for {0}.{1} must not be null.
WEPRME0871	User-defined function adapter must not be null.
WEPRME0872	Class not found.
WEPRME0873	The function adapter class for the user-defined function must not be null.
WEPRME0874	The removal of user-defined function from DB failed.
WEPRME0875	The saving of user-defined function to the database failed.
WEPRME0876	The user-defined function already exists in the database.
WEPRME0877	Unable to create instance of {0}.
WEPRME0878	{0} does not provide a constructor with signature String[], which is obligatory.
WEPRME0879	The parameter types of a user-defined aggregation function adapter for {0}.{1} must not be null.
WEPRME0880	The function adapter class for the user-defined aggregation function must not be null.

- WEPRME0881** **The removal of user-defined aggregation function from the database failed.**

- WEPRME0882** **The saving of user-defined aggregation function to the database failed.**

- WEPRME0883** **The user-defined aggregation function already exists in the database.**

- WEPRME0884** **Query already reconstructed.**

- WEPRME0885** **Could not instantiate adapter class of sink adapter.**

- WEPRME0886** **The {0} already exists in the database.**

- WEPRME0887** **The removal of {0} from the database failed.**

- WEPRME0888** **The saving of query to the database failed.**

- WEPRME0889** **Repository error: The query graph to be sorted must have at least one node without an input.**

- WEPRME0890** **The input queries differ from the sorted output queries.**

- WEPRME0891** **Query properties may only be retrieved after the query is built.**

- WEPRME0892** **Unsupported approach.**

- WEPRME0893** **Could not instantiate adapter class of source adapter.**

- WEPRME0894** **The query already exists in the database.**

WEPRME0895	The removal of query from the database failed.
WEPRME0896	Unable to access class {0}.
WEPRME0897	Unable to create instance of {0}.
WEPRME0898	Update in the database failed.
WEPRME0899	The given SQL statement {0} does not provide streaming data.
WEPRME0900	Unable to parse the given SQL statement: {0}.
WEPRME0901	Unable to translate the given SQL statement ({0}): {1}.
WEPRME0902	Unable to translate the given SQL statement (problem with at least one specified column name): {0}.
WEPRME0903	Configuration could not been loaded, check XML config URL.
WEPRME0904	Could not locate resource!
WEPRME0905	Provided class not found!
WEPRME0906	Unable to read configuration file.
WEPRME0907	XML parsing problem.
WEPRME0908	BOT failed.

- WEPRME0909** **Check whether the persistent ID of the object is null!**

- WEPRME0910** **COMMIT failed.**

- WEPRME0911** **Initializing transaction failed.**

- WEPRME0912** **Obtaining entity manager failed.**

- WEPRME0913** **Persistence factory shutdown failed.**

- WEPRME0914** **ROLLBACK failed.**

- WEPRME0915** **The removal of {0} query from the database failed.**

- WEPRME0916** **The saving of {0} to the database failed.**

- WEPRME0917** **No handler given.**

- WEPRME0918** **Unknown approach.**

- WEPRME0919** **Unknown step.**

- WEPRME0920** **Unsupported approach {0}.**

- WEPRME0921** **Unable to access database with given data source specification.**

- WEPRME0922** **Data source entry already reconstructed.**

WEPRME0923	Unable to access database with given data source and table specification.
WEPRME0924	Unable to reconstruct refresh time.
WEPRME0925	Please provide connection URL property "rtmsystem.datasource.connection_url" in order to connect to database.
WEPRME0926	Please provide JDBC driver name property "rtmsystem.datasource.jdbc_drivename" in order to initialize the data source.
WEPRME0927	Problem with basic data source configuration.
WEPRME0928	Problem with JDBC driver, please verify that the library is attached, library classpath is correct and driver name is correct.
WEPRME0929	The classpath of the JDBC driver is malformed.
WEPRME0930	Obtaining Connection to JDBC Source {0} has failed!
WEPRME0931	This method is not supported by this version.
WEPRME0932	Could not instantiate builder class of ServerDataSourceEntry.
WEPRME0933	Load of tables failed!
WEPRME0934	The builder class for the data source must not be null.
WEPRME0935	Unable to add the specified table.

- WEPRME0936** **Unable to remove the specified table.**

- WEPRME0937** **A server table can only be serialized if its data source entry is of type ServerDataSourceEntry.**

- WEPRME0938** **Illegal HA state - slaves ({0}) are already locked before starting command execution.**

- WEPRME0939** **Setting the remote ID is only allowed if the local connection is a remote stub.**

- WEPRME0940** **Using High Availability, commands may only be given to the master.**

- WEPRME0941** **An unexpected exception occurred while executing a remote command from the client.**

- WEPRME0942** **No async commands supported yet.**

- WEPRME0943** **No sync commands expected by {0}.**

- WEPRME0944** **Only master can deliver list of active servers in HA cluster.**

- WEPRME0945** **Only the master may broadcast update of cluster topology.**

- WEPRME0946** **Remote connection handler is already removed or unknown.**

- WEPRME0947** **Sink currently does not have to handle any commands.**

- WEPRME0948** **System already shut down.**

- WEPRME0949** **The class {0} cannot be instantiated on the server.**

WEPRME0950	The system is already shut down.
WEPRME0951	This API is only to be used in HA mode.
WEPRME0952	Unable to close channel {0}.
WEPRME0953	Unexpected command {0}.
WEPRME0954	Unexpected command: {0}.
WEPRME0955	Unknown command: {0}.
WEPRME0956	Unsupported approach.
WEPRME0957	An exception occurred while connecting.
WEPRME0958	Connection cannot be closed as it was already lost.
WEPRME0959	Connection to server has been lost.
WEPRME0960	Slave trying to initialize metadata after master failed to do so.
WEPRME0961	Unexpected approach {0}.
WEPRME0962	{0} does not provide a constructor with signature <code>String[]</code>, which is obligatory when passing a non-empty <code>String</code> array with parameters.
WEPRME0963	Builder class constructor not usable.

- WEPRME0964** **Builder class for DataSource not found.**

- WEPRME0965** **Builder properties should contain at least one property e.g. connection URL.**

- WEPRME0966** **Check if the schema file available.**

- WEPRME0967** **Specified database table cannot be accessed.**

- WEPRME0968** **System could not be configured, check XML config URL.**

- WEPRME0969** **Unable to configure JPA Provider.**

- WEPRME0970** **Unable to read configuration file.**

- WEPRME0971** **Unable to read configuration file.**

- WEPRME0972** **Unable to validate configuration file.**

- WEPRME0973** **Unknown connection type purpose {0}.**

- WEPRME0974** **Unknown database table {0}.**

- WEPRME0975** **Unknown LoginModuleControlFlag: {0}.**

- WEPRME0976** **Provided resource name is null!**

- WEPRME0977** **Resource could not be located, please verify resource name ({0})!**

WEPRME0978	Inconsistent stream metadata.
WEPRME0979	Unable to connect communication client.
WEPRME0980	Unable to connect due to incompatible protocols.
WEPRME0981	Unknown command.
WEPRME0982	Unsupported approach {0}.
WEPRME0983	Wrong command for being handled here: {0}.
WEPRME0984	Connection lost while not expecting a valid connection.
WEPRME0985	Disaster case, as other server has role {0}.
WEPRME0986	Inconsistent number of master result to slave communicators.
WEPRME0987	Master result to slave communicator which claims to support punctuations does not.
WEPRME0988	Multiple high availability partners are registered in cluster status ({0}).
WEPRME0989	No connection to slave which should be recovered.
WEPRME0990	No responsible master result sender found for query {0}.{1}.
WEPRME0991	Only the master can provide a list of active slaves.

- WEPRME0992** **Other server in unexpected role {0}.**

- WEPRME0993** **PN approach currently not supported here.**

- WEPRME0994** **Setting the cluster status provider is only allowed before start of high availability!**

- WEPRME0995** **Setting the health check provider is only allowed before start of high availability!**

- WEPRME0996** **Setting the system shutdown manager is only allowed before start of high availability!**

- WEPRME0997** **Status of health check monitor of local system is not OK; shutting down!**

- WEPRME0998** **Unable to connect to high availability partner due to incompatible versions.**

- WEPRME0999** **Unable to create client connection handler because cluster status provider is not yet set.**

- WEPRME1000** **Unable to do handshake with HA partner.**

- WEPRME1001** **Unable to grant all artefact privileges to HA user.**

- WEPRME1002** **Unable to initialize master mode because the cluster's master lock could not be acquired.**

- WEPRME1003** **Unable to request communication parameters of master.**

- WEPRME1004** **Unable to request role of HA partner.**

WEPRME1005	Unable to retrieve high availability partner from cluster status.
WEPRME1006	Unable to shut down HA communication client of master.
WEPRME1007	Unable to take over master mode because the cluster's master lock could not be acquired.
WEPRME1008	Unsupported approach: {0}.
WEPRME1009	The specified HA server address {0} is not yet registered.
WEPRME1010	This command should not be used by the HA protocol.
WEPRME1011	Unable to grant rights to subscribe to HA difference to user.
WEPRME1012	No sync commands expected.
WEPRME1013	Break-off of input stream must only occur on input 1.
WEPRME1014	Action must not be null.
WEPRME1015	Add privilege on concrete and already existing artefact makes no sense.
WEPRME1016	Artefact must not be null.
WEPRME1017	Identifier must not be null.
WEPRME1018	Null argument.

- WEPRME1019** **Owner must not be null.**

- WEPRME1020** **Wrong privilege type.**

- WEPRME1021** **Grants load failed.**

- WEPRME1022** **Grants remove failed.**

- WEPRME1023** **No actual artefact known.**

- WEPRME1024** **Privilege {0} for user {1} granted by {2} not found.**

- WEPRME1025** **Privilege {0} for user {1} not found.**

- WEPRME1026** **Privilege cannot be persistent as the referenced artefact is not persistent.**

- WEPRME1027** **The user {0} does not have the privilege {1}.**

- WEPRME1028** **The user {0} does not have the privilege to grant the privilege {1}.**

- WEPRME1029** **Privilege must not be null.**

- WEPRME1030** **The delete failed.**

- WEPRME1031** **The granted privilege to be serialized has no grants specified.**

- WEPRME1032** **The remove of granter {0} to the database failed.**

WEPRME1033	The saving of granter {0} to the database failed.
WEPRME1034	User must not be null.
WEPRME1035	Unsupported privilege type in serialization.
WEPRME1036	Unsupported privilege type.
WEPRME1037	Wrong privilege type.
WEPRME1038	Granting privileges is not supported by this authorization module.
WEPRME1039	Persistence is not supported by this authorization module.
WEPRME1040	Revoking privileges is not supported by this authorization module.
WEPRME1041	Check argument, xmlConfig path is wrong, file could not be located.
WEPRME1042	Check argument, xmlSchema path is wrong, file could not be located.
WEPRME1043	Check arguments, either xmlConfig path or xmlSchema path is wrong, files could not be located.
WEPRME1044	Check arguments, either xmlConfig path or xmlSchema were null.
WEPRME1045	Clearing the system is only allowed before calling createSystem.
WEPRME1046	System could not be configured, check XML config URL.

- WEPRME1047** **Class for schema manager not found.**

- WEPRME1048** **Current system configuration does not support persistence.**

- WEPRME1049** **No schema manager provided!**

- WEPRME1050** **Object of the schema manager cannot be instantiated!**

- WEPRME1051** **Only client commands can be sent using this callback.**

- WEPRME1052** **Problem with access to class of schema manager.**

- WEPRME1053** **Registering protocol handlers is only allowed before system start!**

- WEPRME1054** **Registering protocols is only allowed before system start!**

- WEPRME1055** **Setting the cache provider is only allowed before system start!**

- WEPRME1056** **The protocol handler must not be null.**

- WEPRME1057** **The protocol must not be null.**

- WEPRME1058** **There is already a protocol handler registered using identifier {0}.**

- WEPRME1059** **There is already a protocol registered using identifier {0}.**

- WEPRME1060** **Unknown protocol {0}.**

WEPRME1061	The identifier "{0}" is not allowed for a {1}.
WEPRME1062	The identifier "{0}" is too long (maximum of {1} characters allowed).
WEPRME1063	The identifier of type {0} must not be null.
WEPRME1064	Unsupported artefact {0}.
WEPRME1065	Minimum supported client version must not be greater than maximum one.
WEPRME1066	Server must not support older maximum client versions than the previous one.
WEPRME1067	Server must not support older minimum client versions than the previous one.
WEPRME1068	Server must support clients with same version.
WEPRME1069	Server versions have to be provided in ascending order.
WEPRME1070	The operator is not processing.
WEPRME1071	The timestamps have to be provided in ascending order.
WEPRME1072	Sources must not have inputs.
WEPRME1073	The method (compute)Done must not be called on sources.
WEPRME1074	The method (compute)HeartBeat must not be called on sources.

- WEPRME1075** **The method (compute)Punctuate must not be called on sources.**

- WEPRME1076** **The method (compute)Push must not be called on sources.**

- WEPRME1077** **No additional outputs allowed.**

- WEPRME1078** **A SourceAdapter providing a chronon stream must not use end timestamps other than start timestamp +1.**

- WEPRME1079** **The operator is not processing ({0}).**

- WEPRME1080** **The timestamps have to be provided in ascending order.**

- WEPRME1081** **Source has to have at least one output.**

- WEPRME1082** **Extra start time must be smaller than start time.**

- WEPRME1083** **No extra work function specified for this source.**

- WEPRME1084** **Sequence may not start before the logical start time.**

- WEPRME1085** **Sequence produced wrong start timestamp.**

- WEPRME1086** **HeartBeatPeriod has to be a divisor of elementPeriod.**

- WEPRME1087** **Time {0} already past ({1}).**

- WEPRME1088** **The specified label must not be null.**

WEPRME1089	Lower bound of 1st range does not match with specified minimum.
WEPRME1090	Number of ranges and colors differ.
WEPRME1091	Upper bound of {0} range does not match with lower bound of {1} range.
WEPRME1092	Upper bound of last range does not match with specified maximum.
WEPRME1093	Legend for time series number {0} is not specified!
WEPRME1094	Sinks may not have outputs.
WEPRME1095	An ID has to be provided for each source.
WEPRME1096	Unable to provide metadata.
WEPRME1097	Illegal input index {0}.
WEPRME1098	Input data validity may not overlap more than one day.
WEPRME1099	Output already exists.
WEPRME1100	Output creation must take place before init.
WEPRME1101	Missing negative element for group {0}.
WEPRME1102	The length of minimal splits cannot be less than one millisecond.

- WEPRME1103** **An ID has to be provided for each cache input.**

- WEPRME1104** **An ID has to be provided for each input.**

- WEPRME1105** **Unexpected number of cache inputs!**

- WEPRME1106** **Unexpected number of stream inputs!**

- WEPRME1107** **Duplicate scope limited heartbeat for input {0}.**

- WEPRME1108** **Scope limited heartbeats with different timestamps.**

- WEPRME1109** **Window advance ≤ 0 not allowed.**

- WEPRME1110** **Window size ≤ 0 not allowed.**

- WEPRME1111** **Missing negative input elements.**

- WEPRME1112** **Not all positive elements matched.**

- WEPRME1113** **Negative call on empty state.**

- WEPRME1114** **The window size must not be smaller than or equal to 0.**

- WEPRME1115** **The window advance must not be smaller than or equal to 0.**

- WEPRME1116** **Negative element not matching any previous positive one.**

WEPRME1117	An ID has to be provided for each input.
WEPRME1118	Not all positive elements were matched by a negative one.
WEPRME1119	Adding status is only allowed before open.
WEPRME1120	Additional status elements have to be consecutive.
WEPRME1121	The length of minimal splits cannot be less one millisecond.
WEPRME1122	Adding status is only allowed before open.
WEPRME1123	Double split during processing a scope limited heartbeat.
WEPRME1124	Wrong split settings found during processing of a scope limited heartbeat.
WEPRME1125	Error on both streams !
WEPRME1126	Inconsistent streams.
WEPRME1127	No additional outputs allowed.
WEPRME1128	Minimum split length ≤ 0 not allowed.
WEPRME1129	Ambiguous next edge.
WEPRME1130	Graph has to be packed before sequences can be generated.

- WEPRME1131** **Graph is already packed.**

- WEPRME1132** **No node with ID {0}.**

- WEPRME1133** **Reserved ID.**

- WEPRME1134** **Wrong temporal event order.**

- WEPRME1135** **The checked graph has the following errors:**

- WEPRME1136** **Duplicate scope limited heartbeat for input {0} (old: {1}, new: {2}).**

- WEPRME1137** **Scope limited heartbeats with different timestamps.**

- WEPRME1138** **Maximum size must only be given if blockIfFull is set.**

- WEPRME1139** **Duplicate scope limited heartbeat for input {0}.**

- WEPRME1140** **Start timestamp series is not monotonous.**

- WEPRME1141** **Scope limited heartbeat for recursive input {0} was not processed within the whole recursive query plan.**

- WEPRME1142** **Scope limited heartbeats are not supported for non-recursive inputs of recursion base.**

- WEPRME1143** **The window advance must not be smaller than or equal to 0.**

- WEPRME1144** **The window size must not be smaller than or equal to 0.**

WEPRME1145	Execution has already been assigned.
WEPRME1146	Sink has to belong to this graph.
WEPRME1147	Source has to belong to this graph.
WEPRME1148	No corresponding connection found.
WEPRME1149	Punctuation type {0} is not supported by default serializer.
WEPRME1150	Data must not be null.
WEPRME1151	Invalid element (empty time interval).
WEPRME1152	Check internal queue resources/state.
WEPRME1153	Operator won't produce any result in this state: {0}.
WEPRME1154	Method must not be called inside a connection's batch run.
WEPRME1155	Input record does not comply with the schema: expected {0}, but received {1}.
WEPRME1156	The record size ({0}) of {1} does not comply with metadata {2}.
WEPRME1157	The row {0} does not support null values.
WEPRME1158	RequiredDatabaseSources must not be null.

- WEPRME1159** **RequiredQueries must not be null.**

- WEPRME1160** **RequiredUserDefinedFunctions must not be null.**

- WEPRME1161** **Null properties are not allowed.**

- WEPRME1162** **Property {0} has to be of type {1}.**

- WEPRME1163** **RecordMetaData must not be null.**

- WEPRME1164** **Subscriptions must not be null.**

- WEPRME1165** **The given notification callback is already registered.**

- WEPRME1166** **The given notification callback is not registered.**

- WEPRME1167** **A timestamp for each input has to be specified.**

- WEPRME1168** **All inputs have to be provided before init.**

- WEPRME1169** **An operator may not publish elements in state {0}.**

- WEPRME1170** **An operator may not publish punctuations in state {0}.**

- WEPRME1171** **Cannot determine periodically updated metadata fragments! Execution is unavailable!**

- WEPRME1172** **Cannot determine periodically updated metadata fragments!
PeriodicMetaDataUpdateWorkerThread is unavailable!**

WEPRME1173	Complete from is already set for output ID {0}.
WEPRME1174	Complete from must not change (Was {0} for output {1} and tried to change to {2}).
WEPRME1175	Graph must not be null!
WEPRME1176	Graph Wlock needed.
WEPRME1177	Identifier {0} is not supported.
WEPRME1178	Illegal Operator State: {0} (State.INITIALIZED or State.PROCESSING expected).
WEPRME1179	Index out of bounds.
WEPRME1180	Input {0} already set.
WEPRME1181	Input {0} not set.
WEPRME1182	Input {0} was not set.
WEPRME1183	MetaData-object must not be null!
WEPRME1184	Minimum heartbeat distance must not be smaller than one.
WEPRME1185	Not enough inputs provided.
WEPRME1186	Operator already closed.

WEPRME1187	Operator already closed.
WEPRME1188	Operator is already initialized.
WEPRME1189	Operator is already opened.
WEPRME1190	Operator is working.
WEPRME1191	Operator may not publish punctuations in state {0}.
WEPRME1192	Operator may not use tellDone method in state {0}.
Explanation	The tellDone method of an operator announces to downstream operators that the operator will no longer send events. Calling this method is restricted to certain states of the lifecycle of the operator.
Action	Restrict the use of this method to the permitted lifecycle states.
WEPRME1193	Operator was already closed.
WEPRME1194	Operator was already closed - use reset.
WEPRME1195	Output already exists.
WEPRME1196	Output already set.
WEPRME1197	Output creation must take place before init.
WEPRME1198	Output ID out of bounds.
WEPRME1199	Output not found.

WEPRME1200	Output not set.
WEPRME1201	Punctuations of type {0} are not supported by operator {1}.
WEPRME1202	Setting complete from for operators with optional inputs is only possible if no inputs present.
WEPRME1203	Setting complete from for operators with optional inputs is only possible when initialized.
WEPRME1204	Setting complete from is only possible for sources.
WEPRME1205	Too many inputs provided.
WEPRME1206	Nullary operators have no sources.
WEPRME1207	Input not set.
WEPRME1208	Unable to read from input.
WEPRME1209	From must not be null.
WEPRME1210	Unable to close input stream.
WEPRME1211	Unable to read file.
WEPRME1212	Reset is not supported for a queue while it is consuming.
WEPRME1213	Min must not be greater than max.

WEPRME1214	Only positive numbers of elements are supported.
WEPRME1215	Times must not be negative.
WEPRME1216	Right input has to support reset.
WEPRME1217	Not enough sources provided.
WEPRME1218	Sources not yet provided.
WEPRME1219	Wrong input type.
WEPRME1220	Cannot determine supportsReset before init.
WEPRME1221	No source provided.
WEPRME1222	Source not yet provided.
WEPRME1223	Wrong input type.
WEPRME1224	Initially empty map required.
WEPRME1225	This queue is limited.
WEPRME1226	Buffer must have a capacity of at least one element.
WEPRME1227	No additional run can be obtained before consuming the last one.

WEPRME1228	No new cursors can be requested after all previously requested cursors were closed.
WEPRME1229	Only one additional cursor supported due to consuming TeeBuffer.
WEPRME1230	This is a consuming TeeBuffer.
WEPRME1231	This is not a consuming TeeBuffer.
WEPRME1232	Iterator is empty.
WEPRME1233	Underlying iterator has to support remove.
WEPRME1234	Init not allowed after open{0}{1}.
WEPRME1235	Iterator is already closed.
WEPRME1236	Iterator is already initialized.
WEPRME1237	Iterator is already open.
WEPRME1238	Iterator is not initialized.
WEPRME1239	Iterator was already closed - use reset.
WEPRME1240	Iterator was not opened.
WEPRME1241	No more elements left.

- WEPRME1242** **Remove is not supported by this iterator.**

- WEPRME1243** **Reset is only allowed after open and before close.**

- WEPRME1244** **Update may only be used after next().**

- WEPRME1245** **Not all required sources set.**

- WEPRME1246** **Operator was already initialized.**

- WEPRME1247** **Operators do not supported remove.**

- WEPRME1248** **Sources {0} not set.**

- WEPRME1249** **Update may only be used after next().**

- WEPRME1250** **Exception during close.**

- WEPRME1251** **Exception during init.**

- WEPRME1252** **Exception during query processing.**

- WEPRME1253** **Unable to handle {0} due to {1}.**

- WEPRME1254** **Unknown device.**

- WEPRME1255** **Wrong data format: missing header element.**

WEPRME1256	Wrong data format: missing header end.
WEPRME1257	Wrong data format: missing header start.
WEPRME1258	Wrong data format: missing packet end.
WEPRME1259	Wrong data format: unable to parse parameter.
WEPRME1260	Wrong data format: unable to parse parameter count.
WEPRME1261	Wrong data format: unable to parse timestamp.
WEPRME1262	Wrong data format: wrong number of parameters.
WEPRME1263	Wrong data format: wrong parameter format.
WEPRME1264	Bytes message cannot be read because of the following reason: {0}.
WEPRME1265	Bytes messages do not support reading lines of data.
WEPRME1266	Bytes message cannot be written because of the following reason: {0}.
WEPRME1267	Connection cannot be created. Check associated properties (e.g. authentication properties)! {0}.
WEPRME1268	Connection cannot be listened to because of the following reason: {0}.
WEPRME1269	Connection factory cannot be retrieved via JNDI. Check associated ID! {0}.

- WEPRME1270** **Destination cannot be retrieved via JNDI. Check associated ID! {0}.**

- WEPRME1271** **JNDI context cannot be created. Check connection properties! {0}.**

- WEPRME1272** **Message cannot be sent because of the following reason: {0}.**

- WEPRME1273** **Receiver cannot be created because of the following reason: {0}.**

- WEPRME1274** **Sender cannot be created because of the following reason: {0}.**

- WEPRME1275** **Session cannot be created because of the following reason: {0}.**

- WEPRME1276** **Connection cannot be created because of the following reason: {0}.**

- WEPRME1277** **Input has to support reset.**

- WEPRME1278** **This class must not be reinitialized.**

- WEPRME1279** **Unexpected reinitialization.**

- WEPRME1280** **Only operators can be used as child nodes of a distinct operator.**

- WEPRME1281** **Database sources using direct access cannot be used in user-defined operators.**

- WEPRME1282** **Incompatible parameter type for user-defined operator {0} (expected {1}, found {2}).**

- WEPRME1283** **Initialization is only available for user-defined operators.**

WEPRME1284	Input of user-defined operator has unknown mode {0}.
WEPRME1285	Inputs of a user-defined operator have to be ordered (first input streams, second database sources).
WEPRME1286	Only user-defined operators and sources can be used as child nodes of a user-defined operator (found {0}).
WEPRME1287	Only user-defined operators and sources can be used as child nodes of a user-defined operator.
WEPRME1288	Unable to compute stream metadata for user-defined operator.
WEPRME1289	Unable to retrieve specified source input.
WEPRME1290	Unknown user-defined operator mode {0}.
WEPRME1291	Wrong number of instantiation parameters for user-defined operator {0} (expected {1}, found {2}).
WEPRME1292	List caches cannot be indexed!
WEPRME1293	Missing key indices!
WEPRME1294	Missing key!
WEPRME1295	Unsupported communication type.
WEPRME1296	Attempt to inconsistently initialize serializers for complex {0}.

- WEPRME1297** **Wrong serialization initialization - Missing: {0}, unused: {1}.**

- WEPRME1298** **Wrong alternative.**

- WEPRME1299** **File has to be empty.**

- WEPRME1300** **Update ist not permitted.**

- WEPRME1301** **Iterator always removes elements.**

- WEPRME1302** **Remove is currently not supported.**

- WEPRME1303** **Unsupported type code: {0}.**

- WEPRME1304** **Unsupported RTM exception type.**

- WEPRME1305** **Inputs of an user-defined operator have to be ordered (first input streams, second database sources).**

- WEPRME1306** **Only user-defined operators and sources can be used as child nodes of an user-defined operator (found {0}).**

- WEPRME1307** **Wrong number of instantiation parameters for user-defined operator {0} (expected {1}, found {2}).**

- WEPRME1308** **Incompatible parameter type for user-defined operator {0} (expected {1}, found {2}).**

- WEPRME1309** **Input metadata mismatch for user-defined operator {0}. {1}**

WEPRME1310	Missing inputs for user-defined operator {0}. {1}
WEPRME1311	Too many inputs for user-defined operator {0}. {1}
WEPRME1312	Unable to use user-defined operator {0}. {1}.
WEPRME1313	RequiredUserDefinedOperators must not be null.
WEPRME1314	An input stream is to be connected to an operator at index {0}, but the index must not be negative or exceed the maximum allowed number of inputs, which is {1}.
WEPRME1315	Inconsistent output stream metadata.
WEPRME1316	Unexpected exception at operator instantiation.
WEPRME1317	The entry to insert does not provide the list of required entries.
WEPRME1318	A list of required repository entries has to be provided.
WEPRME1319	An initialization reason has to be provided. Use other constructor if no reinitialization takes place.
WEPRME1320	JPA initialization is only allowed using the parameterless constructor.
WEPRME1321	The entry is not correctly initialized.
WEPRME1322	The entry is not yet initialized.
WEPRME1323	The timestamps have to be provided in increasing order.

- WEPRME1324** **The end timestamp has to be greater than the start timestamp.**

- WEPRME1325** **First snapshot-reducible event has been sent for the following query: Owner: {0}
Identifier: {1} Event: {2}**

- WEPRME1326** **The entry {0} required by {1} is not in the repository.**

- WEPRME1327** **The entry {0} can not be removed as it is still in use.**

- WEPRME1328** **The left-hand side of an action must be a field declared in the measure clause.**

- WEPRME1335** **This UserDefinedOperator is missing cache inputs. Minimum expected: {0}. Found:
{1},{2}**

- WEPRME1336** **This UserDefinedOperator is missing stream inputs. Minimum expected: {0}. Found:
{1},{2}**

- WEPRME1337** **This UserDefinedOperator has too many cache inputs. Maximum expected: {0}.
Found: {1},{2}**

- WEPRME1338** **This UserDefinedOperator has too many stream inputs. Maximum expected: {0}.
Found: {1},{2}**

- WEPRME1339** **Error evaluating user defined Function.**

- WEPRME1340** **Invalid range of exponent.**

- WEPRME1341** **Error occurred when evaluating function {0}. {1}**

- WEPRME1342** **Error occurred when evaluating operation {0}. {1}**

WEPRME1343	Cast to {0} is illegal due to precision loss.
WEPRME1344	Illegal real exponent for negative base. Integer required.
WEPRME1345	Invalid negative exponent for base zero.
WEPRME1346	Undefined for $x \leq 0$.
WEPRME1347	Undefined for negative values.
WEPRME1348	The query {0} cannot be stopped as it is still in use.
WEPRME1349	Unexpected problem caused by usage of a subscription.
WEPRME1350	The user-defined function {0}.{1} cannot be deregistered as it is still in use.
WEPRME1351	The user-defined aggregation function {0}.{1} cannot be deregistered as it is still in use.
WEPRME1352	The user-defined operator {0}.{1} cannot be deregistered as it is still in use.
WEPRME1353	The data source {0}.{1} cannot be deregistered as it is still in use.
WEPRME1354	The table {0}.{1} cannot be deregistered as it is still in use.
WEPRME1355	The number of inputs returned by the user-defined operator adapter's <code>getNumberOfInputs()</code> method ({0}) is not consistent with the the number of inputs the user-defined operator adapter factory is called with ({1}).

- WEPRME1356** **The number of cache inputs returned by the user-defined operator adapter's getNumberOfInputs() method ({0}) is not consistent with the the number of cache inputs the user-defined operator adapter factory is called with ({1}).**

- WEPRME1357** **Division by zero.**

- WEPRME1358** **Column "{0}" not found in metadata object.**

- WEPRME1359** **Unexpected number of field metadata entries. Found {0}, expected {1}.**

- WEPRME1360** **Objects of type {0} do not match. {1} <> {2}.**

- WEPRME1361** **Unexpected number of columns. Found {0}, expected {1}.**

- WEPRME1362** **Argument may not be null!**

- WEPRME1363** **Column {0} has an unexpected type. Found {1}, expected {2}.**

- WEPRME1364** **Column is not expected to be nullable: {1}.**

- WEPRME1365** **Column is expected to be nullable: {1}.**

- WEPRME1366** **Column is expected to be case sensitive: {0}.**

- WEPRME1367** **Column is not expected to be case sensitive: {0}.**

- WEPRME1368** **Parameter is not within range [{0}, {1}]: {2}.**

- WEPRME1369** **Stream is expected to be a chronon stream!**

WEPRME1370	Stream is not expected to be a chronon stream!
WEPRME1371	Parameter does not match expected value. Found {0}, expected {1}.
WEPRME1372	The address given in config parameter {0} must not be empty.
WEPRME1373	The deprecated property {0} is used although the new property {1} is present.
WEPRME1374	Wrong number of factory parameters (was {0} but expected {1}).
WEPRME1375	Invalid port number: {0}.
WEPRME1378	Error evaluating aggregate function {0}. {1}
WEPRME1379	Error occurred in method {0}.
WEPRME1380	The signature of the user-defined aggregation function {0} does not match the specified types ({1}).
WEPRME1381	The user-defined aggregation function {0} is unknown or not visible.
WEPRME1382	Unspecified error.
WEPRME1383	Error occurred when evaluating function {0}.
WEPRME1384	Error occurred when evaluating operation {0}.
WEPRME1385	The field {0} is ambiguous. Check if fields and sources are properly renamed and no duplicate aliases are introduced.

WEPRME1386	The provided source parameters should not be null.
Explanation	The input parameter source parameters is null. A valid source parameters object should be provided.
WEPRME1387	The provided server source parameters should not be null.
Explanation	The input parameter server source parameters is null. A valid server source parameters object should be provided.
WEPRME1388	The provided query parameters should not be null.
Explanation	The input parameter query parameters is null. A valid query parameters object should be provided.
WEPRME1389	The provided query language should not be null.
Explanation	The input parameter query language is null. A valid query language object should be provided.
WEPRME1390	The provided query string should not be null.
Explanation	The input parameter query string is null. A valid query string object should be provided.
WEPRME1391	The command prepareQuery2 is not supported by the server.
Explanation	The client tried to send the command prepareQuery2 to the server. The current server version does not support handling of this command. There is a mismatch between client version and server version.
WEPRME1392	The query {0} cannot be subscribed to using subscription mode {1} as subscriptions to this query were restricted to times when no element is valid.
Explanation	The query was prepared using the query parameter 'isSubscribableOnlyWhenNoElementValid'. Subscriptions to such queries may not use other subscription modes than 'ALL'.
Action	Use subscription mode 'ALL'.
WEPRME1393	The query {0} can currently not be subscribed to as subscriptions to this query were restricted to times when no element is valid.

WEPRME1394	The query {0} cannot be unsubscribed from using subscription mode {1} as subscriptions to this query were restricted to times when no element is valid.
Explanation	The query was prepared using the query parameter 'isSubscribableOnlyWhenNoElementValid'. Unsubscriptions to such queries may not use other subscription modes than 'ALL'.
Action	Use subscription mode 'ALL'.
WEPRME1395	An exception related to {0} occurred in the underlying connection.
WEPRME1396	Creation of empty arrays is not supported.
WEPRME1397	All values in an array value construction must have the same type.
WEPRME1398	Only field expressions can be used as child nodes of an array element reference expression.
WEPRME1399	Limiting subscriptions to times when no element is valid is currently not supported in HA mode.
WEPRME1400	The field {0} is not of type ARRAY.
WEPRME1401	The method {0} is not yet supported in class {1}.
WEPRME1402	The XML query is not a valid XML document.
WEPRME1403	The XML query contains syntactical errors.
WEPRME1404	The XML query contains semantical errors.
WEPRME1405	An operator providing a chronon stream must not use end timestamps other than start timestamp +1.

- WEPRME1406** **Unknown timezone: {0}.**
- WEPRME1407** **The time unit "{0}" is unknown.**
- WEPRME1408** **Connection to {0} system lost.**
- WEPRME1409** **Client lost connection to server with address {0}.**
- WEPRME1425** **The Positive-Negative approach is currently not supported when running in high availability mode.**
- WEPRME1427** **NullPointerException occurred while accepting new connection on address {0}.**
- WEPRME1428** **CommunicationException occurred while accepting new connection on address {0}.**
- WEPRME1429** **Exception occurred while accepting new connection on address {0}.**
- WEPRME1431** **The pattern contains illegal characters. Supported characters are letters and the meta characters '*', '+', '?', '.', '|', '(', ')', '[,]', '^', '{, }', " and digits.**
- WEPRME1432** **An aggregate is not allowed in this context.**
Explanation The query contains an aggregate, but in a context that does not permit aggregates. Aggregates are only allowed in the SELECT and HAVING clauses of an SQL query, or inside an aggregate operator of an XML query.
Action Correct the query and resubmit.
- WEPRME1433** **An Ehcache with the name {0} already exists.**
Explanation The system has tried to create a new Ehcache but it already existed in the CacheManager.
Action Make sure the existing Ehcache is removed from the CacheManager.

WEPRME1434	Ehcache configuration error: {0}.
Explanation	The provided ehcache configuration file is not valid.
Action	Make sure the provided ehcache configuration file is valid.
WEPRME1435	Problem creating new Ehcache: {0}.
Explanation	The system tried to create a new Ehcache but encountered problems.
Action	See detailed message for further information.
WEPRME1436	Invalid value of join attribute "{0}".
Explanation	Join attributes refer to the input operators of a join by specifying their 0-based index. They are thus composed of a list of indexes, where only 0 and 1 are valid indexes. As an additional constraint, the list must not contain duplicates.
Action	Correct the specified join attribute.
WEPRME1437	The child nodes with the UIDs "{0}" and "{1}" are not equivalent in the equivalence node.
Explanation	Two of the child nodes in the equivalence node have different record metadata. All direct children of an equivalence node in a query graph must have the same record metadata (resulting schema).
Action	Adapt the equivalence node so that all child nodes have the same record metadata.
WEPRME1438	Regular expression is invalid at offset {0}.
Explanation	The query contains a PATTERN clause, but its regular expression has invalid syntax. The offset contained in the message is the 0-based offset within the regular expression where the failure was detected.
Action	Correct the regular expression syntax and resubmit the query.
WEPRME1439	Barrier can only await one single set of connections.
WEPRME1440	The connection barrier has not been passed yet.
WEPRME1441	Connection for ID {0} could not be used as it connected too late.

WEPRME1442	Unexpected incoming recovery connection for ID {0}.
WEPRME1443	Duplicate incoming recovery connection for ID {0}.
WEPRME1444	Wrong user or password for recovery connection for ID {0}.
WEPRME1445	The connection is already authenticated.
WEPRME1447	Unable to cast the {0} value {1} to {2}.
Explanation	The specified CAST function tries to cast the specified value to the shown type, but this is not possible.
Action	Either change the value in a way that it can be casted to the specified type or change the type accordingly.
WEPRME1448	Records following the given metadata cannot be serialized using this serializer.
Explanation	The given metadata specifies at least one attribute that cannot be serialized using a serializer based on data input and output.
Action	Use the class RecordStreamSerializer instead.
WEPRME1449	Unable to read the given event.
WEPRME1450	Unable to write the given event.
WEPRME1451	Percentage of delays must be in [0,1].
Explanation	Percentage of delays must be in [0,1].
Action	Configure delay to be in [0,1].
WEPRME1452	Exclusion threshold for delays must be greater than or equal zero.
Explanation	Exclusion threshold for delays must be greater than or equal zero.
Action	Set exclusion threshold for delays to be greater than or equal zero.

WEPRME1453	The weighting factor alpha must be in [0,1].
Explanation	The weighting factor alpha must be in [0,1].
Action	Set the weighting factor alpha to be in [0,1].
WEPRME1454	Size for the queue must be greater 1.
Explanation	Size for the queue must be greater 1.
Action	Set size for the queue to be greater 1.
WEPRME1455	Missing Ehcache configuration.
Explanation	The useEhcache query parameter was set, but there was no Ehcache configuration present in the RTM system configuration.
Action	Either remove the useEhcache query parameter, or extend the RTM system configuration to include an Ehcache configuration.
WEPRME1456	Element must not be null.
Explanation	Element must not be null.
Action	Insert only elements not being null.
WEPRME1457	The system is in overload as the SynchronousSource can not publish as fast as intended.
Explanation	The SynchronousSource tries to send events at physical timestamps according to the specified logical timestamps. In case of permanent delays between intended send time and actual send time, the system seems to be in an overload state. As a consequence event sending is stopped.
Action	Reduce the event rates until the system is in a stable state again.
WEPRME1458	Only one overload detector can be registered at a time.
Explanation	Only one overload detector can be registered at a time.
Action	Register only one overload detector.
WEPRME1459	The DURATION expression of a MATCHING clause must be evaluable to a numeric type.
Explanation	The specified DURATION expression evaluates to a type that is not numeric, e.g., STRING. But DURATION expressions must be numeric.
Action	Change the DURATION expression such that it evaluates to a numeric type.

WEPRME1460 **The WITHIN expression of a MATCHING clause must be evaluable to a numeric type.**

Explanation The specified WITHIN expression evaluates to a type that is not numeric, e.g., STRING. But WITHIN expressions must be numeric.

Action Change the WITHIN expression such taht is evaluates to a numeric type.

WEPRME1461 **Check the DURATION expression.**

Explanation The DURATION expression contains an unspecific error.

Action Check the DURATION expression.

WEPRME1462 **Check the WITHIN expression.**

Explanation The WITHIN expression contains an unspecific error.

Action Check the WITHIN expression.

WEPRME1469 **The maximum window size must not be smaller than or equal to 0.**

Explanation The maximum windo size specifies the maximum validity an event can get applied by the window operator. As validities are always greater than zero the maximum window size also has to be.

Action Specify a maximum window size that is greater than 0.

WEPRME1471 **The size of a count-based window can only be specified using a numeric constant.**

Explanation Count-based windows does not support window size specification using numeric expressions.

Action Replace the window size expression by a numeric constant.

WEPRME1472 **Check the window size expression.**

Explanation The window size expression contains an unspecific error.

Action Check the window size expression.

WEPRME1473 **Only constant maximum windows sizes, i.e., milliseconds, seconds, minutes or hours, are allowed for time-based windows.**

Explanation The maximum window size must be evaluable to a constant amount of milliseconds. For this reason only constant time units are supported.

Action Use a constant unit, i.e., millisecond, second, minute or hour, when specifying a maximum window size.

WEPRME1474	The size of a time-based window can't be specified using a non-numeric constant.
Explanation	The window size is specified by a non-numeric constant.
Action	Replace the non-numeric constant window size specification by a numeric constant or an expression that can be evaluated to a numeric type.
WEPRME1475	The window size must not be greater than the specified maximum window size.
Explanation	The computed window size was greater than the specified maximum window size.
Action	Check the window size expression if it could be limited to results that are less than or equal to the specified maximum window size or adapt (or remove) the specified maximum window size.
WEPRME1476	The user {0} does not have the privilege to refresh the table.
WEPRME1477	The table {0} does not support triggered cache refresh!
Explanation	The table is configured with no support for a a-periodic, triggered cached refreshed.
Action	Change the AccessProperties of the table and enable supportsTriggeredRefresh option to enable a-periodic triggering of table refreshes.
WEPRME1479	The required complete-from timestamp cannot be guaranteed by the source.
Explanation	The source operator cannot guarantee the semantic subscription time requested when preparing the query.
Action	Change or remove the requested semantic subscription time when preparing the query.
WEPRME1480	The required complete-from timestamp cannot be guaranteed by the source adapter (not an intra source adapter).
Explanation	Only intra source adapters are able to guarantee semantic subscription time requests when preparing a query.
Action	Use registered intra source adapters or remove the requested semantic subscription time when preparing the query.
WEPRME1481	The required complete-from timestamp cannot be guaranteed by the source adapter (intra source adapter does not support requesting semantic subscription times).
Explanation	The used intra source adapter does not support guaranteed semantic subscription time requests when preparing a query.
Action	Use intra source adapters supporting this feature or remove the requested semantic subscription time when preparing the query.

WEPRME1482	The required complete-from timestamp cannot be guaranteed by the source adapter (intra source adapter is not able to provide the requested semantic subscription time).
Explanation	The used intra source adapter is not able to guarantee the semantic subscription time requested when preparing the query.
Action	Change or remove the semantic subscription time requested when preparing the query.
WEPRME1483	The required complete-from timestamp cannot be guaranteed by the operator.
Explanation	The operator is already opened and the requested semantic subscription time cannot be guaranteed anymore.
Action	Modify or remove the semantic subscription time requested when preparing the query.
WEPRME1484	The required complete-from timestamp cannot be guaranteed by the count-based window.
Explanation	Count-based windows does not support requesting semantic subscription times when preparing a query.
Action	Remove the count-based window from the query or remove the semantic subscription time request when preparing the query.
WEPRME1485	The duration must not be NULL.
Explanation	The duration expression was evaluated to NULL.
Action	The duration expression must not return NULL as it cannot be interpreted as a duration value. Modify the expression in such a way that it cannot return NULL when being evaluated using the incoming data.
WEPRME1486	The within must not be NULL.
Explanation	The within expression was evaluated to NULL.
Action	The within expression must not return NULL as it cannot be interpreted as a within value. Modify the expression in such a way that it cannot return NULL when being evaluated using the incoming data.
WEPRME1487	The window size must not be NULL.
Explanation	The window size expression was evaluated to NULL.
Action	The window size expression must not return NULL as it cannot be interpreted as a window size value. Modify the expression in such a way that it cannot return NULL when being evaluated using the incoming data.

WEPRME1488	Execution is already started.
WEPRME1489	Execution is already stopped and may not be restarted.
WEPRME1490	Execution is not started, yet.
WEPRME1491	Execution is already stopped.
WEPRME1492	Error unregistering mBean '{0}'.
WEPRME1493	Failed to invoke setter on class '{0}'.
WEPRME1494	Failed to invoke action '{0}' on class '{1}'.
WEPRME1495	Failed to invoke getter '{0}' on class '{1}'.
WEPRME1496	Attribute name cannot be null.
WEPRME1497	Attribute names cannot be null.
WEPRME1498	Getter must not be invoked as long as metadata is not activated.
WEPRME1499	Attribute '{0}' not found in class '{1}'.
WEPRME1500	Setters is not supported.
WEPRME1501	Action name cannot be null.

WEPRME1502	No parameters allowed.
WEPRME1503	No Signature allowed.
WEPRME1504	Action name has to start with either {0}, {1} or {2}.
WEPRME1505	No such metaDataIdentifier found: {0}.
WEPRME1506	Unsupported parameter type: {0}.
WEPRME1507	RAQL syntax not supported.
Explanation	An SQL query was found to support RAQL syntax, which is not (or not yet) supported.
Action	Replace by valid syntax.
WEPRME1508	Aggregates are not allowed in the GROUP BY clause.
Explanation	As the grouping is applied before the aggregates are computed on the groups it is not allowed to use aggregates in the GROUP BY clause.
Action	Remove the aggregate from the GROUP BY clause.
WEPRME1509	Check the specified group expression.
Explanation	The group expression contains an unspecific error.
Action	Check the group expression for errors.
WEPRME1510	Check the specified predicate (having clause).
Explanation	The predicate contains an unspecific error.
Action	Check the predicate for errors.
WEPRME1511	Only operators can be used as child nodes of a limit operator.
Explanation	A non-operator node was passed as the input node of a limit operator, where only an operator node is allowed.
Action	Supply an operator node as the child of a limit operator.

WEPRME1512	Only operators can be used as child nodes of an order operator.
Explanation	A non-operator node was passed as the input node of an order operator, where only an operator node is allowed.
Action	Supply an operator node as the child of an order operator.
WEPRME1513	Translation mode does not support operators of type {0}.
Explanation	An unsupported operator was found during the translation of an SQL statement. The operator may be invalid for the current mode , but valid in other translation mode.
Action	Avoid SQL statements using the offending operator, or use a translation mode that supports it.
WEPRME1514	Invalid aggregate in ORDER BY clause.
Explanation	An ORDER BY clause was found to contain an aggregate function, which was not specified earlier in the same query. This is not allowed, an ORDER BY clause must not introduce new aggregate functions.
Action	Correct SQL statement, e.g. by adding the aggregate in question to the SELECT list.
WEPRME1515	Check the specified part of the ORDER BY clause.
Explanation	The ORDER BY clause was found to contain some invalid construct.
Action	Inspect ORDER BY clause and remove any invalid expressions.
WEPRME1516	Subquery not allowed in this context.
Explanation	A subquery was found in a context, where it is not supported.
Action	Correct statement according to the language specification.
WEPRME1517	Subquery results in more than one column, where it must be a single column.
Explanation	A subquery in a comparison of the where clause must result in a single column.
Action	Correct SQL statement.
WEPRME1518	Invalid frame bound.
Explanation	A window definition contained an invalid frame bound. A frame bound of UNBOUNDED FOLLOWING is not allowed on the left hand side of a window frame BETWEEN definition, and a frame bound of UNBOUNDED PRECEDING is not allowed on the right hand side.
Action	Correct SQL statement.

WEPRME1519	Window function not allowed in this context.
Explanation	A window function was found in a context, where it is not supported.
Action	Correct statement according to the language specification.
WEPRME1520	Check the specified part of the window specification.
Explanation	A window specification was found to contain some invalid construct.
Action	Inspect window specification and remove any invalid expressions.
WEPRME1521	Only operators can be used as child nodes of a window aggregation operator.
Explanation	A non-operator node was passed as the input node of a window aggregation operator, where only an operator node is allowed.
Action	Supply an operator node as the child of a window aggregation operator.
WEPRME1523	ORDER BY should have at least one ordering criteria specified.
Explanation	The query does not specify an order criteria in the ORDER BY clause.
Action	Insert an ordering criteria in the ORDER BY clause.
WEPRME1524	Invalid nested aggregate function reference.
Explanation	The argument of a set function invocation cannot be another set function.
Action	Correct SQL statement.
WEPRME1525	DISTINCT or ALL can only be specified with aggregate functions.
Explanation	An SQL query contained the keywords DISTINCT or ALL in a function call, but the function was not an aggregate function. This is not supported.
Action	Correct SQL statement.
WEPRME1535	The 2nd argument of the ROUND function must be of type integer.
Explanation	The 2nd argument of the given ROUND function call is not of type integer which is mandatory.
Action	Change the expression specifying the 2nd argument of ROUND function such that it is of type integer.

WEPRME1536	Unable to parse long value due to wrong number format. {0}
Explanation	The given literal does not comply with the structure of an integral number, i.e. it contains characters other than 0-9,+,-.
Action	Please remove any invalid characters from your integer literal.
WEPRME1537	Unable to parse integer value due to wrong number format. {0}
Explanation	The given literal does not comply with the structure of an integral number, i.e. it contains characters other than 0-9,+,-.
Action	Please remove any invalid characters from your integer literal.
WEPRME1538	If FROM is specified in the TRIM function, either the trim specification (LEADING, TRAILING, or BOTH) or the trim character or both have to be specified.
Explanation	If FROM is specified in the TRIM function, either the trim specification (LEADING, TRAILING, or BOTH) or the trim character or both have to be specified.
Action	Either add the trim specification, the trim character or both. Alternatively remove the FROM clause.
WEPRME1539	Only expressions are permitted for the trim source argument of the TRIM function.
Explanation	Only expressions are permitted for the trim source argument of the TRIM function.
Action	Use an expression for the trim source argument.
WEPRME1540	Only expressions are permitted for the trim character argument of the TRIM function.
Explanation	Only expressions are permitted for the trim character argument of the TRIM function.
Action	Use an expression for the trim character argument.
WEPRME1541	The {1} function only supports STRING values as argument for the substring source.
Explanation	The {1} function only supports STRING values as argument for the substring source.
Action	Use a STRING value as argument for the substring source.
WEPRME1542	The {1} function only supports INTEGER values as argument for the start position.
Explanation	The {1} function only supports INTEGER values as argument for the start position.
Action	Use an INTEGER value as argument for the start position.

WEPRME1543	The {1} function only supports INTEGER values as argument for the string length.
Explanation	The {1} function only supports INTEGER values as argument for the string length.
Action	Use and INTEGER value as argument for the string length.
WEPRME1544	The {1} function only supports STRING values as argument for the trim character.
Explanation	The {1} function only supports STRING values as argument for the trim character.
Action	Use a STRING value as argument for the trim character.
WEPRME1545	The {1} function only supports STRING values as argument for the trim source.
Explanation	The {1} function only supports STRING values as argument for the trim source.
Action	Use a STRING value as argument for the trim source.
WEPRME1546	The argument of the LOWER and the UPPER function must be of type STRING or CHARACTER.
Explanation	The argument of the LOWER and the UPPER function must be of type STRING or CHARACTER..
Action	Use a STRING or CHARACTER value as argument for the LOWER and the UPPER function.
WEPRME1547	For the SUBSTRING function the substring source must be of type STRING and the start position and string length must be of type INTEGER.
Explanation	For the SUBSTRING function the substring source must be of type STRING and the start position and string length must be of type INTEGER.
Action	Use a STRING value for the substring source and an INTEGER value for the start position and the string length.
WEPRME1548	For the TRIM function the trim source must be of type STRING and the trim character must be of type STRING or CHARACTER.
Explanation	For the TRIM function the trim source must be of type STRING and the trim character must be of type STRING or CHARACTER.
Action	Use a STRING value for the trim source and a STRING or CHARACTER value for the trim character.

WEPRME1549	A {0} operation must have exactly three sub-expressions.
Explanation	A {0} operation must have exactly three sub-expressions.
Action	Ensure that the {0} operation has exactly three sub-expressions.
WEPRME1550	The LOWER and the UPPER function only support STRING and CHARACTER values.
Explanation	The LOWER and the UPPER function only support STRING and CHARACTER values.
Action	Ensure that only STRING and CHARACTER values are used.
WEPRME1551	The trim character for the TRIM function must have exactly one character.
Explanation	The trim character for the TRIM function must have exactly one character.
Action	Use a single character as trim character for the TRIM function.
WEPRME1552	The values for start position and start length of the SUBSTRING function are not valid.
Explanation	The values for start position and start length of the SUBSTRING function are not valid.
Action	Use correct values for start position and start length of the SUBSTRING function.
WEPRME1553	Failed to instantiate user defined aggregation function adapter for given parameter types {0}.
Explanation	The given parameter set is not compatible to any adapter this factory can create.
Action	Check the number of parameters and their types. Add explicit casts where necessary.
WEPRME1554	Failed to instantiate user defined function adapter for given parameter types {0}.
Explanation	The given parameter set is not compatible to any adapter this factory can create.
Action	Check the number of parameters and their types. Add explicit casts where necessary.
WEPRME1555	The return type of method {0} needs to be assignable to {1}. Found: {2}.
WEPRME1556	The first parameter of method {0} needs to be the same class or a super-class of {1}. Found: {2}.

- WEPRME1557** **Mmethod {0} is expected to have return type {1}. Found: {2}.**

- WEPRME1558** **Method {0} is expected to have {1,choice,0#no parameters| 1#exactly one parameter| 1<exactly {1,number} parameters}.**

- WEPRME1559** **The function cannot be registered.**

- WEPRME1560** **The function factory cannot be registered.**

- WEPRME1561** **The class of the user-defined function adapter factory must not be null.**

- WEPRME1562** **The class of the user-defined aggregation function adapter factory must not be null.**

- WEPRME1563** **"Failed to instantiate UDAF adapter for given parameter types. Check getSignature() first!"**

- WEPRME1564** **Receiver version is to old to handle serialized user defined function adapter factory.**

- WEPRME1565** **Receiver version is to old to handle serialized user defined aggregation function adapter factory.**

- WEPRME1566** **The user-defined aggregation function adapter must not be null.**

- WEPRME1567** **Incompatible adapter signatures for {0}.{1}: Expected {2} input parameters, got {3}.**

- WEPRME1568** **Incompatible adapter signatures for {0}.{1}: Expected parameter type compatible to {2}, got {3}.**

- WEPRME1569** **Failed to instantiate user defined aggregation function for argument types: {0}.**

WEPRME1570	The parameter type number {0} of a user-defined aggregation function adapter for {1},{2} must not be null.
WEPRME1571	The parameter types of a user-defined function adapter for {0},{1} must not be null.
WEPRME1572	The aggregate type of a user defined aggregation function adapter must not be null.
WEPRME1573	Failed to instantiate user defined function for argument types: {0}.
WEPRME1574	Parameter number {0} of method {1} is expected to be serializable.
WEPRME1575	The mask "{0}" defining the temporal format is not valid.
Explanation	The mask "{0}" defining the temporal format is not valid.
Action	Select a valid temporal format.
WEPRME1576	Date conversion error for value "{0}".
Explanation	Date conversion error for value "{0}".
Action	Enter a valid date.
WEPRME1577	Unsupported date field "{0}".
Explanation	Unsupported date field "{0}".
Action	Select a valid date field.
WEPRME1578	Conversion to date failed for input string "{0}".
Explanation	Conversion to date failed for input string "{0}".
Action	Enter a valid input string.
WEPRME1579	Adapter return type differs from signature's return type. Expected {0}, got {1}.
WEPRME1580	Number of adapter parameter types differs from the number of the signature's parameter types. Expected {0}, got {1}.

- WEPRME1581** Adapter parameter type {0} differs from the signature's parameter type {0}. Expected {1}, got {2}.

- WEPRMI0001** Initializing RTM system.

- WEPRMI0002** Configuring persistent RTM system.

- WEPRMI0003** Initialization of RTM system finished.

- WEPRMI0004** Starting RTM system.

- WEPRMI0005** Start of RTM system finished.

- WEPRMI0006** Shutting down RTM system.

- WEPRMI0007** Shutdown of RTM system is finished.

- WEPRMI0008** User {0} trying to locally connect to RTM system.

- WEPRMI0009** User {0} connected to RTM system.

- WEPRMI0010** Current HA role is {0}.

- WEPRMI0011** Status of local system is not OK; shutting down!

- WEPRMI0012** Status of cluster is not OK; shutting down!

- WEPRMI0013** HA role has been set to {0}.

WEPRMI0014	Connection to slave system lost.
WEPRMI0015	Slave is preparing recovery.
WEPRMI0016	Slave requesting recovery from master.
WEPRMI0017	Master has started sending recovery data to slave.
WEPRMI0018	Master finished sending recovery data to slave.
WEPRMI0019	Slave has started processing recovery request from master.
WEPRMI0020	Slave successfully finished processing recovery request from master.
WEPRMI0021	Server with newer build number {0} connected as slave.
WEPRMI0022	Aborting authentication with remote RTM system.
WEPRMI0023	Starting to accept new connections.
WEPRMI0024	Stopped accepting new connections.
WEPRMI0025	Aborted handshake due to shutdown.
WEPRMI0026	Handshake with remote RTM system successfully finished.
WEPRMI0027	Snapshot reducibility has been determined for the following query; Owner:{0}; Identifier:{1}; SQL:{2}; Snapshot reducible from:{3};

- WEPRMI0028** **Could not connect to a running high-availability peer, now attempting to acquire master lock.**

- WEPRMI1376** **Properties of RTM system:**

- WEPRMI1377** **Properties of JPA :**

- WEPRMI1412** **Remote connection server is shutting down.**

- WEPRMI1413** **Client starts close procedure.**

- WEPRMI1414** **Client finishes close procedure.**

- WEPRMI1415** **Client marks connection as broken for address {0}.**

- WEPRMI1416** **Client shuts down broken connection to address {0}.**

- WEPRMI1417** **Local connection is closed due to {0}.**

- WEPRMI1418** **Telling slave with address {0} to close remote connection with remoteId {1} due to {2}.**

- WEPRMI1419** **Closing HA result transmission query {0}.**

- WEPRMI1420** **Shutting down remote connection handler with remote connection id {0}.**

- WEPRMI1426** **Starting to accept new connections on address {0}.**

- WEPRMI1430** **Stopped accepting new connections on address {0}.**

WEPRMI1446	Re-authentication at remote RTM system finished successfully.
WEPRMW0001	Unable to shut down RTM system's persistence manager.
WEPRMW0002	Unable to shut down communication servers.
WEPRMW0003	Unable to stop communication server.
WEPRMW0004	Unable to stop communication client.
WEPRMW0005	Unable to shut down client connection handler.
WEPRMW0006	Unable to shut down server connection handler.
WEPRMW0007	Unable to connect to high availability partner.
WEPRMW0008	Unable to shut down master connection handler.
WEPRMW0009	Unable to send for slave health request.
WEPRMW0010	Server with older build number {0} connected as slave.
WEPRMW0011	Unable to shut down slave connection handler.
WEPRMW0012	Unable to send for master health request.
WEPRMW0013	Connection lost.

- WEPRMW0014** **Connection lost due to exception on receiving command.**

- WEPRMW0015** **Connection lost due to unexpected interrupt on command queue.**

- WEPRMW0016** **Connection lost due to unexpected exception during command handling.**

- WEPRMW0017** **Unable to call a task on the decoupled sink adapter.**

- WEPRMW0018** **Authentication with remote RTM system contains illegal commands.**

- WEPRMW1329** **Caught exception during operator initialization.**

- WEPRMW1330** **Caught exception during heartbeat processing from input {0}.**

- WEPRMW1331** **Caught exception while closing operator.**

- WEPRMW1332** **Caught exception processing done signal from input {0}.**

- WEPRMW1333** **Error processing element of index {0}.**

- WEPRMW1334** **Caught exception while opening operator.**

- WEPRMW1410** **Status of local system is not OK; shutting down!**

- WEPRMW1411** **Status of cluster is not OK; shutting down!**

- WEPRMW1421** **Received a shutdown notification from HA {0} with HA communication address {1}.**

WEPRMW1422 **Server ({0}) lost connection to HA partner system.**

WEPRMW1423 **Server is shutting down broken connection for address {0} as communication to master has been lost.**

Explanation This message appears in the log of an HA slave when it loses its connection to a master that supports remote connections. It indicates why clients will lose their connection to that address.

Action Check other messages to see if the reason for the lost connection can be found.

WEPRMW1522 **Aborting authentication with remote RTM system.**

22 Security Messages

SINAZE0000	FileBasedAuthzStoreImpl: Storage cannot be loaded: {0}
Explanation	Role storage (roles.txt) can not be loaded.
Action	Check the existance of the roles.txt file or the relevant storage.
SINAZE0001	FileBasedAuthzStoreImpl: Storage location {0} is missing.
Explanation	Role storage (roles.txt) is missing.
Action	The location passed to the service does not point to the existing file/storage. Check the availablity to the file.
SINAZE0002	Cannot open storage file {0}
Explanation	Role storage (roles.txt) cannot be opened.
Action	Check if the storage (file) is available and accessible.
SINAZE0003	{0} is not readable!
Explanation	Role storage (roles.txt) cannot be read.
Action	Check if the storage (file) has proper access rights, and whether it is not locked.
SINAZE0004	Invalid entry in storage file. Invalid line in the storage file.
Explanation	Role storage (roles.txt) syntax is not correct. Invalide entry is found.
Action	Check the storage (file) and validate the syntax.

SINAZE0005	cannot open {0}
Explanation	Role storage (roles.txt) cannot be opened/accessed.
Action	Check the storage (file).
SINAZE0006	Cannot write to storage file {0}. File does not exist.
Explanation	Cannot write to storage file. File does not exist.
Action	Check the availability of the storage/file.
SINAZE0007	{0} is not writable!
Explanation	Role storage (roles.txt) is not editable.
Action	Check access rights for the storage file.
SINLDE0048	Authentication failed
Explanation	LDAPLoginModule - authentication against LDAP failed. User name or password are wrong.
Action	Re-enter the user name and password. Check if their values are correct.
SINLME0012	Initialize: failed to create X509CRL from the CRL URL: {0} {1}
Explanation	CRLException was thrown during the initialization of the CRL. Possible reasons: the CRL file is broken or it is not in CRL format - http://docs.oracle.com/javase/7/docs/api/java/security/cert/X509CRL.html .
Action	Double check in the JAAS configuration the value of the "crl_url" property and verify if the defined CRL file is a valid CRL file.
SINLME0013	Initialize: failed to create URL or InputStream from the CRL URL: {0} {1}
Explanation	IOException exception during initialization of the CRL. Possible reasons: the URL is broken or the file is not found.
Action	Double check in the JAAS configuration the value of the "crl_url" property and verify if this is a valid URL. If the CRL is on the file system, make sure the value for the "crl_url" begins with "file://".
SINLME0014	Initialize: failed to create CRL - CRL location: {0} {1}
Explanation	Unknown exception during initialization of the CRL.
Action	Double check the log files about the exception type and the explanation.

SINLME0015	Initialize: CRL location is not specified.
Explanation	The "check_crl_status" property is set to true but the "crl_url" property is not set up.
Action	1. Disable CRL check by setting up the "check_crl_status" property to false or by removing it; 2. Specify the "crl_url" property correctly.
SINLME0190	login: unsupported callback {0}
Explanation	Supplied Callback is not supported. Software AG Security Infrastructure supports only SagCredentialCallback, PasswordCallback and NameCallback.
Action	Check which Callback is used.
SINLME0191	Engine failed to load with options: {0}
Explanation	Authentication failed in RoleLoginModule. Storage is not loaded properly.
Action	Check logs for more details about the reasons.
SINLME0192	Provider class cannot be found {0}
Explanation	Role storage implementation provider is not found.
Action	Check the value of the "provider_class" property in the JAAS configuration file.
SINLME0193	Provider class cannot be instantiated {0}
Explanation	Role storage implementation provider cannot be instantiated.
Action	Check the value of the "provider_class" property in the JAAS configuration file.
SINLME0194	Provider class cannot be accessible {0}
Explanation	Role storage implementation provider class is not accessible.
Action	Check the value of the "provider_class" property in JAAS configuration file. Check classloaders, if the requested provider class is available.
SINRME0139	Wrong password format.
Explanation	Password entry for the user is not correct. It must start with "\$6a\$" or "\$6\$".
Action	Check users.txt file.

SINRME0140	Duplicates in user name.
Explanation	User names are duplicated in the users.txt.
Action	Check the users.txt file that is used.
SINRME0141	Duplicates in user name.
Explanation	User names are duplicated in the users.txt.
Action	Check the users.txt file that is used.
SINSSE0022	SSOS properties could not be updated after sso properties file creation. Restart may be needed.
Explanation	SSO Service properties could not be updated after sso properties file creation.
Action	Restart of the SSO service may be needed.
SINSSE0023	CacheManager cannot be instantiated. {0}
Explanation	CacheManager cannot be instantiated. The service will work without cache. This could cause some performance degradation.
Action	Check the value of the "com.softwareag.security.idp.ehcache.location" property in the com.softwareag.sso.pid.properties dynamic configuration file.
SINSSE0024	Ehcache cannot be initialized. cacheManager = {0}
Explanation	Ehcache cannot be initialized. The cachemanager in not available.
Action	Switch logging to debug and check the log file for more details.
SINSSE0025	Ehcache in null
Explanation	Ehcache in null.
Action	Switch logging to debug and check the log file for more details.
SINSSE0026	Return NULL. Missing user ID in the assertion.
Explanation	Wrong SAML assertion format. The required ID attribute is missing.
Action	Check the SAML assertion syntax.

SINSSE0027	parseAssertion(String) throws SAMLException {0}
Explanation	Parsing of the SAML assertion failed.
Action	Activate debug logging and check log file for more details.
SINSSE0028	Return NULL. Missing user ID in the assertion.
Explanation	Wrong SAML assertion format. The required ID attribute is missing.
Action	Check the SAML assertion syntax.
SINSSE0029	{0}
Explanation	Parsing of the SAML assertion failed.
Action	Activate debug logging and check log file for more details.
SINSSE0030	generateAssertion() throws GeneralSecurityException {0}
Explanation	Generation of the SAML assertion failed with GeneralSecurityException.
Action	Activate debug logging and check log file for more details.
SINSSE0031	generateAssertion() throws XMLSignatureException {0}
Explanation	Generation of the SAML assertion failed with XMLSignatureException.
Action	Activate debug logging and check log file for more details.
SINSSE0032	generateAssertion() throws MarshalException {0}
Explanation	Generation of the SAML assertion failed with MarshalException.
Action	Activate debug logging and check log file for more details.
SINSSE0033	generateAssertion() throws MarshallingException {0}
Explanation	Generation of the SAML assertion failed with MarshallingException.
Action	Activate debug logging and check log file for more details.

23 System Management Hub Messages

ARGAAE0102	SMH Client/Server Layer user 'USER_NAME' failed to log on.
Explanation	User authentication to the Client/Server Layer server failed.
Action	Ensure that the user is valid in the configured environment and that the client version is newer or equal to the server version. If SSX is enabled, then check the SSX configuration of the Client/Server Layer server. Refer to the SSX log file for additional information.
ARGAAE0204	Unknown host: 'HOSTNAME'. Register 'HOSTNAME'.
Explanation	The specified hostname cannot be found.
Action	Use an existing hostname or an IP address of an existing host.
ARGAAE0302	Task task, 'desc' processed with errors.
Explanation	Task was executed with errors.
Action	Action on this error depends on the type of the user-defined task. If you cannot resolve the problem, contact Software AG Global Support. Before you contact the support organization, prepare the following information: system and setup specifics; product error logs with exposed trace.
ARGAAI0106	SSL communication disabled.
Explanation	The System Management Hub client/server infrastructure uses non-secured communication.
Action	none

ARGAAI0405	SSX configuration changed.
Explanation	SSX configuration change
Action	none
ARGCLE2000	ARGCLE2000 Child process has not been created.
Explanation	The agent for the requested action has not been found. The agent program does not have permissions to run. Internal error.
Action	You have enabled an old version of the agent program. For more information on the problem, set to "1" the New_StartAgent key in the CSLayer Server registry settings.
ARGCLE2001	ARGCLE2001 Logging on with user name and password failed.
Explanation	With Security enabled, the user has entered incorrect user name and/or password. The CSLayer server is not running as a service on Windows. The CSLayer server is not running with root rights on UNIX.
Action	Check the security settings on the target machine and type again the user name and password.
ARGCLE2002	The server does not have enough rights to set the user context.
Explanation	CSLayer needs some special rights to execute a scheduled task. All necessary rights and settings are explained in the official documentation.
Action	Refer to the official documentation and set the right user privileges for the CSLayer server.
ARGCLE2003	ARGCLE2003 The server cannot interpret the command in the client's XML request.
Explanation	The server received an unknown command in the client's XML request.
Action	Check the producer of the XML request. Use only the commands that are available for the server.
ARGCLE2004	ARGCLE2004 Command syntax error in the client's XML request.
Explanation	There is a syntax error in the command included in the client's XML request.
Action	Check the syntax of the command that you want to include in the client's XML request.

ARGCLE2005	ARGCLE2005 This type of command is disabled.
Explanation	The client's request includes a disabled command.
Action	Check the server settings on the target machine.
ARGCLE2006	ARGCLE2006 The user is not an administrator for this product.
Explanation	The user's account does not have permissions to perform the requested action.
Action	Check out the product's administrator list for users with administrator's rights.
ARGCLE2007	ARGCLE2007 The user does not have permissions to carry out this command.
Explanation	The user does not have permissions to carry out the command.
Action	Check out your user account for the assigned permissions.
ARGCLE2008	Internal server error.
Explanation	Error occurred on CSLayer server.
Action	Contact Software AG Global Support.
ARGCLE2009	ARGCLE2009 Check out the system configuration. You are running out of memory.
Explanation	This is an internal error produced by the CSLayer server (argsrv).
Action	The operating system has been overloaded. Check out the system configuration.
ARGCLE2010	ARGCLE2010 Failed to pass parameters to the agent program.
Explanation	This is an internal error produced by the CSLayer server (argsrv) in the system call "write".
Action	The write operation to a pipe for passing parameters to an agent failed. Try to continue or restart the server. If the error persists, contact your software supplier.
ARGCLE2011	ARGCLE2011 Failed to create a pipe for running the agent program.
Explanation	Failure to create a pipe for running the agent program is an internal error produced by the CSLayer server (argsrv).
Action	Try to continue or restart the server. If the error persists, contact your software supplier.

ARGCLE2012	ARGCLE2012 Failed to redirect the standard file descriptors to run the agent program.
Explanation	Failure to redirect standard file descriptors is an internal error produced by the CSLayer server (argsrv).
Action	The redirection failed in the 'dup' system call (UNIX). Try to continue or restart the server and if the error persists, contact your software supplier.
ARGCLE2013	ARGCLE2013 Failed to run the agent program.
Explanation	Failure to run the agent program is an internal error produced by the CSLayer server (argsrv).
Action	Try to continue or restart the server and if the error persists, contact your software supplier.
ARGCLE2014	ARGCLE2014: Agent was not found.
Explanation	The agent does not exist in the SMH installation on the target machine or the agent's path is not registered properly.
Action	Check the product installation to see if the agent has been deleted or moved. Next, check the "Path" key of the agent in the SMH registry.
ARGCLE2015	ARGCLE2015 Access denied.
Explanation	The agent program does not have permissions to run. The agent program is being used by another process.
Action	Check the permissions of the agent executable. Check the running processes.
ARGCLE2016	ARGCLE2016 Failed to create child process.
Explanation	Failure to create child process is an internal error produced by the CSLayer server (argsrv) in the system call "fork".
Action	Try to continue or restart the server and if the error persists, contact support.
ARGCLE2017	ARGCLE2017 Failed to run the agent.
Explanation	Failure to run the agent is an internal error produced by the CSLayer server (argsrv) calling to API 'CreateProcess'.
Action	Try to continue or re-start the server and if the error persists, contact support.

ARGCLE2018	ARGCLE2018 The agent program has quit abnormally.
Explanation	The agent program received a signal that it did not catch.
Action	Check the agent. In most cases a patch for the specific agent will solve the problem.
ARGCLE2019	ARGCLE2019 Error duplicating handles
Explanation	Error duplicating handles is an internal error produced by the CSLayer server (argsrv) calling to API "DuplicateHandle".
Action	Try to continue or restart the server. If the error persists, contact support.
ARGCLE2020	ARGCLE2020 Check out the system configuration. You are running out of memory.
Explanation	This is an internal error produced by CSLayer server (argsrv) when attempting to initialize the Java Virtual Machine.
Action	Check out the system settings.
ARGCLE2021	ARGCLE2021 Failed to create the JVM.
Explanation	This is an internal error produced by CSLayer server (argsrv) when attempting to initialize the Java Virtual Machine. The settings used for the JVM - jvm.dll (Windows), libjvm.sl (HP-UX), libjvm.so (other UNIX) - do not match the system configuration.
Action	Check the system settings. Check the path and parameter settings.
ARGCLE2022	ARGCLE2022 Failure to initialize the Java bridge.
Explanation	Failure to initialize the Java bridge is an internal error produced by CSLayer server (argsrv) when attempting to initialize the Java bridge. The settings used for the Java bridge - argjbr.dll (Windows), libargjbr.sl (HP-UX), libargjbr.so (other UNIX) - do not match the system configuration.
Action	Check out the system settings, the path, and the parameter settings.
ARGCLE2023	ARGCLE2023 The Java bridge has been disabled.
Explanation	The support for Java agents has been disabled.
Action	Enable the use of Java agents in the CSLayer server.
ARGCLE2024	ARGCLE2024 Failed to load a class from the Java bridge.
Explanation	The agent class is not found because of incorrect agent's settings.
Action	Check the agent settings including the agent class name and the classpath settings (global or product-specific registry settings).

ARGCLE2025	The agent program failed to find a method from the Java bridge.
Explanation	The Java method is not found because the method's name or signature is incorrect.
Action	Contact Software AG Global Support.
ARGCLE2026	ARGCLE2026 The agent program failed to find a method from the Java bridge.
Explanation	Java bridge error, agent-related problem. Java bridge error, agent-related problem.
Action	Contact your software supplier
ARGCLE2030	ARGCLE2030 The Management Independent Layer cannot manage the selected host.
Explanation	The client you are trying to connect to uses a newer version of the MIL server.
Action	Upgrade the MIL server on your local host machine.
ARGDME0202	MILDOM error.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server. Client/Server Layer communication errors.
Action	This is an internal generic error produced by the XML DOM library. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.
ARGDME0203	MILDOM data mismatch.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML DOM library. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.

ARGDME0204	MILDOM out of memory.
Explanation	Operating system overloaded. The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML DOM library. Check the operating system and/or the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.
ARGDME0205	MILDOM mismatched documents.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML DOM library. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.
ARGDME0206	MILDOM received a document with internal errors.
Explanation	Agent returns an XML document used to signal an error.
Action	The error message provides the error description.
ARGDME0207	MILDOM feature not implemented.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML DOM library. Report the error to Software AG Global Support.
ARGDME0208	MILDOM Unknown node type.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML DOM library. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.

ARGDME0209 **MILDOM Unknown payload.**
Explanation Error in XML parser. Invalid DOM node.
Action Internal error. Contact Software AG Global Support.

ARGDMI0201 **MILDOM OK.**
Explanation OK
Action None.

ARGDPE3010 **Command "%s %s" is deprecated.**
Explanation Information message.
Action Use new command.

ARGDPE3011 **New command was automatically started.**
Explanation Information message.
Action None.

ARGDPE3012 **Command "%s %s" is deprecated on "%s".**
Explanation Command is deprecated.
Action Use new command.

ARGDPE3013 **Command "%s %s" is deprecated with version "%s".**
Explanation Command is deprecated.
Action Use new command.

ARGDPE3014 **Starting command "%s %s".**
Explanation Information message.
Action None.

ARGEVE0005 **Message translation failed.**
Explanation Job message localization failed.
Action Internal error. Contact Software AG Global Support.

ARGEVE0023	No job records found.
Explanation	No job record found for the specified ID.
Action	Ensure that the job ID is correct.
ARGEVE0024	The job 'job' has pending alerts.
Explanation	On executing the job one or more alerts are rised.
Action	Check the event log of the job and confirm the alerts.
ARGEVE0034	Job records for 'job' cannot be deleted because the job is still running.
Explanation	A job can only be deleted if it is finished.
Action	Wait for finalizing the job.
ARGEVE0121	Not enough memory.
Explanation	There is not enough memory for execution an action on argevsrv.
Action	Stop the applications that are not currently needed to free some memory or restart the system.
ARGEVE0803	Could not connect to 'M_ARGEVSRV', service not running.
Explanation	The requested service is not available.
Action	Check that the requested service is available and running.
ARGEVE0807	Job not found; retry with product=product version=version.
Explanation	The specified job was not found.
Action	Check Product and Version.
ARGEVI0029	Some of the jobs specified have unconfirmed warnings, errors or fatal errors.
Explanation	Some of the jobs specified have unconfirmed warnings, errors or fatal errors. These need to be confirmed or ignored before the jobs can be deleted.
Action	Check the jobs, confirm the individual alerts or confirm all alerts.
ARGEVI0034	Job records for 'job' cannot be deleted because the job is still running.
Explanation	A job can only be deleted if the job is finished.
Action	Wait for finalizing the job.

ARGEVI0278	Job record of 'job' cannot be deleted because the job has unconfirmed alerts.
Explanation	A job can only be deleted if the job is finished and all alerts are confirmed.
Action	Confirm all alerts of the job.
ARGEVW0031	One or more jobs could not be deleted from the job log because they have unconfirmed alerts.
Explanation	A job with alert flags can only be deleted if the alerts are confirmed.
Action	Check the job and confirm the alerts.
ARGINE0400	String not found.
Explanation	The request string is not in the product language resource library.
Action	Check that the product is installed properly. If the product has been upgraded, check that the upgrade completed successfully.
ARGINE0401	Cannot find the language library; a language resource is not installed for the product.
Explanation	The language library requested by the product does not exist. The language library requested by the product is incorrectly registered.
Action	Check that the product is properly installed. Check that the product is correctly registered with System Management Hub.
ARGINE0402	Invalid object identifier for the product.
Explanation	A product using System Management Hub has specified an incorrect (or invalid) product name or version.
Action	This is an error generated by System Management Hub. Check the settings used by the product that reports the problem.
ARGINE0403	An error occurred while initializing the registry for reading.
Explanation	An error was detected while attempting to read the registry.
Action	Check the installation. If the problems persist, contact Software AG Global Support.

ARGMLE0302	MIL error
Explanation	Unknown error.
Action	Contact Software AG Global Support.
ARGMLE0303	MIL out of memory
Explanation	Operating system is overloaded.
Action	This is an internal error produced by the MIL server (argmlsrv). Check the system settings.
ARGMLE0304	MIL invalid session
Explanation	Session expired.
Action	Authenticate on the system again.
ARGMLI0301	MIL OK
Explanation	Internal informative message, no error.
Action	None.
ARGTPE0102	Network error.
Explanation	This is an error produced by the transport library. In most cases, this is the TCP/IP driver library. The server is not running or is not using the correct port. Bad target URL or IP address.
Action	Start the specific service and check the URL/IP settings and the port number Check the settings of both Client/Server Layer Server and Management Independent Layer
ARGTPE0103	Timeout in 'receive' or 'accept'.
Explanation	This is an error produced by the TCP/IP driver library. The server is busy.
Action	Retry the operation or log off and reconnect again later.

ARGTPE0104	Reference to an unknown host.
Explanation	This is an error produced by the TCP/IP driver library. The specified server name is unknown or the DNS service is not available.
Action	Check the system settings and the host lists. Check if the DNS server is available.
ARGTPE0105	No sockets available on the TCP/IP stack.
Explanation	This is an internal error produced by the TCP/IP driver library. An internal TCP/IP error that indicates system overload.
Action	Check the system settings Close other applications using TCP/IP communication.
ARGTPE0106	Not enough system resources.
Explanation	This is an internal error produced by the TCP/IP driver library. An internal TCP/IP error that indicates system overload.
Action	Check the system settings Close other applications.
ARGTPE0107	ARGTPE0107 Connecting to the server has failed.
Explanation	The specified server is not running or uses bad port settings.
Action	This is an error produced by the TCP/IP driver library. Check the system settings Check if the specified server is running.
ARGTPE0108	Error in the received message length.
Explanation	This is an internal error produced by the TCP/IP driver library. TCP/IP communication errors.
Action	Check the network settings.

ARGTPE0109	'Bind' failed; a task is already started or attempts to open the privileged socket.
Explanation	On attempt to launch the Management Independent Layer Server or the CS Layer Server (System Management Hub Daemon) they were either already running or other applications are using the required socket.
Action	No action is required if the servers are already running. Otherwise, terminate the application using the socket or configure the relevant System Management Hub server (if applicable).
ARGTPE0110	Overflow during 'receive'.
Explanation	This is an internal error produced by the TCP/IP driver library. TCP/IP communication errors.
Action	Check the network settings.
ARGTPE0111	Message received with zero bytes.
Explanation	This is an internal error produced by the TCP/IP driver library. TCP/IP communication errors.
Action	Check the network settings.
ARGTPE0112	Call aborted or cancelled by a signal.
Explanation	The server was deactivated.
Action	Restart the server and reconnect.
ARGTPE0113	Not enough memory to perform a function.
Explanation	Operating system overloaded.
Action	Close some applications and retry the operation.
ARGTPE0114	Incorrect port number or alias.
Explanation	Incorrect system settings.
Action	Check the system and port settings.
ARGTPE0116	A file operation failure.
Explanation	Operating system error.
Action	Check the operating system settings and the user account rights.

ARGTPE0117	ARGTPE0117 Cannot Initialize TCP/IP Connection
Explanation	Cannot Initialize TCP/IP Connection on Windows
Action	Internal communication error. Contact your system administrator.
ARGTPE0118	TCP/IP send error.
Explanation	Sending data over TCP/IP failed.
Action	Internal communication error. Contact Software AG Global Support. Before you contact the support organization, prepare the following information: system and setup information; error logs with exposed traces.
ARGTPE0119	ARGTPE0119 Error in Client/Server layer response
Explanation	Agent returns badly-formed XML.
Action	Check the producer of the XML document. In most cases a patch for the specific agent or a patch for the XML template file used will solve the problem.
ARGTPE0120	TCP/IP receive error.
Explanation	Receiving data over TCP/IP failed.
Action	Internal communication error. Contact Software AG Global Support. Before you contact the support organization, prepare the following information: system and setup information; error logs with exposed traces.
ARGTPE0121	Incomplete Client/Server Layer response.
Explanation	Incomplete response or invalid protocol detected.
Action	Internal communication error. Contact Software AG Global Support. Before you contact the support organization, prepare the following information: system and setup information; error logs with exposed traces.
ARGTPE0122	Unknown Client/Server Layer response.
Explanation	Unknown error while getting the Client/Server Layer server response.
Action	Internal communication error. Restart MIL and Client/Server Layer servers. If the problem persists, contact Software AG Global Support. Before you contact the support organization, prepare the following information: system and setup information; error logs with exposed traces.

ARGTPE0123	Cannot connect to Client/Server Layer server.
Explanation	Client/Server Layer server is not operating.
Action	Ensure that the Client/Server Layer server is running and listening on the port specified in the connection settings. Ensure that the MIL server uses the right host and port of the running Client/Server Layer server. Check your firewall settings and restart the Client/Server Layer. If the problem persists, contact Software AG Global Support. Before you contact the support organization, prepare the following information: system and setup information; error logs with exposed traces.
ARGTPE0124	Agent invocation results in a broken XML
Explanation	The agent returns incorrect XML format.
Action	Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file in use solves the problem.
ARGTPE0125	Agent invocation results in an empty XML
Explanation	The agent returns an empty XML.
Action	Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file in use solves the problem.
ARGTPE0126	Agent timeout
Explanation	The agent did not finish its task in the given time interval.
Action	Increase the agent timeout interval.
ARGTPE0127	Agent returns large XML content.
Explanation	The agent returned XML that is larger than the maximum allowed size.
Action	Make sure that the agent works properly or increase the maximum XML size that can be read.
ARGTPI0101	Successful call.
Explanation	This is an internal message and does not indicate an error. This message is provided for backward compatibility.
Action	None.

ARGTPI0115	Host closed the connection.
Explanation	The server was deactivated.
Action	Restart the server and reconnect.
ARGXLE0001	Out of memory.
Explanation	Operating system overloaded.
Action	This is an internal error produced by the XML parser. Check the system settings.
ARGXLE0002	Syntax error.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the used XML template file will solve the problem.
ARGXLE0003	No elements to display.
Explanation	Missing or corrupt agent. The agent does not return an XML document. The Client/Server Layer Server cannot start the agent. XML template file not available. Client/Server Layer communication errors.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem. Put the Agent of the correct version for the platform in the correct location.
ARGXLE0004	Incorrect XML file.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.

ARGXLE0005	Unclosed token.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.
ARGXLE0006	Tag mismatch.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.
ARGXLE0007	Duplicated attribute.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.
ARGXLE0008	Additional information after an XML element.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.

ARGXLE0009	Illegal parameter entity reference.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.
ARGXLE0010	Undefined entity.
Explanation	Agent returns badly-formed XML. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases a patch for the specific agent or a patch for the XML template file used will solve the problem.
ARGXLE0011	Recursive entity reference.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.
ARGXLE0012	Asynchronous entity.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.

ARGXLE0013	Reference to an invalid character number.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.
ARGXLE0014	Reference to a binary entity.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.
ARGXLE0015	Reference to an external entity in an attribute.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.
ARGXLE0016	XML processing instruction not available at the beginning of an external entity.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.

ARGXLE0017	Unknown encoding.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem. Only "ISO-8859-1" and "UTF-8" encoding is supported.
ARGXLE0018	Encoding specified in the XML declaration is incorrect.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem. Only "ISO-8859-1" and "UTF-8" encoding is supported.
ARGXLE0019	Unclosed CDATA section.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.
ARGXLE0020	Error in processing external entity reference.
Explanation	The agent returns an incorrect XML format. Incorrect XML template used by the agent. Incorrect XML template used by the Management Independent Layer server.
Action	This is an internal error produced by the XML parser. Check the producer of the XML document. In most cases, a patch for the specific agent or a patch for the XML template file used will solve the problem.

24 Tamino Messages

INMACE0002	Application Server already started
Explanation	The state of the service is not up-to-date.
Action	Use refresh command to update the state.
INMACE0006	Application Server is not started
Explanation	Service cannot be stopped because it is not running.
Action	Command can only be invoked if the service is running.
INMACE0010	Restart of Application Server service failed
Explanation	Something was wrong with the restart of the Application Server service.
Action	Check the state of the service and try to start/stop in the operating system.
INMACE0014	Switch to test mode failed
Explanation	Switch to test mode failed.
Action	none
INMACE0017	Disable failed
Explanation	Switch back failed.
Action	none

INMACE0020 Register failed

Explanation Register failed.

Action none

INMACE0023 Deregister failed

Explanation Deregister failed.

Action none

INMACE0026 Migration failed

Explanation Migration failed.

Action none

INMACE0029 Upgrade failed

Explanation Upgrade failed.

Action none

INMACE0031 Failed to get the authentication configuration - after changing the default configuration it might be required to log out and log in again with a user valid in the new configuration.

Explanation Failed to get the authentication configuration. If this appears after changing the default configuration, the user might have to log out and log in again as a user who is valid in the new configuration.

Action If this appears after changing the default configuration, the user might have to log out and log in again as a user who is valid in the new configuration.

INMACE0032 Failed to update the authentication configuration.

Explanation Failed to update the authentication configuration.

Action none

INMACE0033 No administrator present in new default domain.

Explanation An administrator must always be present in the selected default domain.

Action Ensure that there is an administrator in the selected default domain.

INMACE0034	CentraSite access with given URL failed
Explanation	The URL is not specified correctly.
Action	Correct the URL specification.
INMACE0035	User does not exist or is not authorized to log in for CentraSite registry/repository
Explanation	The user ID or password is specified incorrectly.
Action	Correct the user ID / password or specify another user.
INMACE0036	Adding CentraSite administrator failed
Explanation	The specified user could not be established as a CentraSite administrator.
Action	See additional messages to find the reason.
INMACE0042	Import has failed
Explanation	Import failed
INMACE0045	Failed to read the email settings from CentraSite.
Explanation	Failed to read the email settings from CentraSite.
Action	none
INMACE0046	Failed to read the email settings from CentraSite. The user could not be authenticated.
Explanation	Failed to read the email settings from CentraSite. The current user is not allowed to read data from the CentraSite server.
Action	Switch to a user that is allowed to read from the CentraSite server.
INMACI0001	Do you really want to delete the authentication configuration for domain "domain"?
Explanation	Confirm to delete the selected authentication configuration.
Action	Confirm or cancel the delete operation.
INMACI0003	Application Server successfully stopped
Explanation	Operation completed successfully.
Action	No action required.

INMACI0004	Application Server is starting
Explanation	Service is starting, please wait.
Action	No action required.
INMACI0005	Application Server successfully started
Explanation	Service started successfully.
Action	No action required.
INMACI0007	Application Server is not started
Explanation	Service was not stopped because it has not been started.
Action	No action required.
INMACI0008	Application Server successfully restarted
Explanation	Restart of service completed successfully.
Action	No action required.
INMACI0009	Application Server is stopping
Explanation	Status message shows the service is stopping.
Action	No action required.
INMACI0011	Restart Application Server service
Explanation	This is a status message.
Action	No action required.
INMACI0012	Switch Application Server Tier to test mode
Explanation	Switch Application Server Tier to test mode.
Action	none
INMACI0013	Application Server Tier switched to test mode
Explanation	Application Server Tier switched to test mode.
Action	none

INMACI0015	Disable Application Server Tier version 3.1
Explanation	Switch back Application Server Tier to version 2.2.
Action	none
INMACI0016	Application Server Tier version 3.1 successfully disabled
Explanation	Application Server Tier successfully switched back to version 2.2.
Action	none
INMACI0018	Register Application Server
Explanation	Register Application Server.
Action	none
INMACI0019	Application Server successfully registered
Explanation	Application Server successfully registered.
Action	none
INMACI0021	Deregister Application Server
Explanation	Deregister Application Server.
Action	none
INMACI0022	Successfully deregistered
Explanation	Successfully deregistered.
Action	none
INMACI0024	Migrate Application Server Tier to version 3.1
Explanation	Migrate Application Server Tier to version 3.1.
Action	none
INMACI0025	Application Server Tier successfully migrated
Explanation	Application Server Tier successfully migrated.
Action	none

INMACI0027	Upgrade Registry Repository to version 3.1
Explanation	Upgrade Registry Repository to version 3.1.
Action	none
INMACI0028	Registry Repository successfully upgraded
Explanation	Registry Repository successfully upgraded.
Action	none
INMACI0030	Authentication configuration successfully changed.
Explanation	This is a status message.
Action	No action required.
INMCAE0001	User has not enough permissions to update Registry Repository
Explanation	Specified user has not enough permissions to update the Registry Repository or the specified password was wrong.
Action	Correct the user/password.
INMCAE0003	Internal configuration error error
Explanation	Internal configuration error has occurred.
Action	Please contact your software supplier.
INMCAE0004	Internal server error (server error)
Explanation	Internal server error has occurred.
Action	Please contact your software supplier.
INMCAE0005	Connection to Registry Repository has failed
Explanation	Connection to Registry Repository has failed.
Action	Ensure that Registry Repository is running and that the application port of the Registry Repository is open in the case of a remote access. Then retry.
INMCAE0006	Application Server Tier is in a wrong state (state=state)
Explanation	The triggered action is not permitted to run, because the Application Server Tier is in a wrong state.
Action	Please contact your software supplier.

INMCAE0007	Missing mandatory parameter param
Explanation	The specified parameter is missing.
Action	Set the parameter and retry.
INMCAE0008	Disabling CentraSite version Tomcat has failed
Explanation	CentraSite Tomcat cannot be disabled.
Action	Please contact your software supplier.
INMCAE0009	Disabling CentraSite version Apache has failed
Explanation	CentraSite Apache cannot be disabled.
Action	Please contact your software supplier.
INMCAE0010	Enabling CentraSite version Tomcat has failed
Explanation	CentraSite Tomcat cannot be enabled.
Action	Please contact your software supplier.
INMCAE0011	Enabling CentraSite version Apache has failed
Explanation	CentraSite Apache cannot be enabled.
Action	Please contact your software supplier.
INMCAE0012	Port port already in use
Explanation	The specified port number is already in use.
Action	Specify another port number and retry.
INMCAE0017	Installation of CentraSite Control has failed
Explanation	Installation of CentraSite Control has failed.
Action	Please contact your software supplier.
INMCAE0018	Updating configuration files has failed
Explanation	The configuration files are not modified, because an error has occurred.
Action	Please contact your software supplier.

INMCAE0019	Re-configuration of Software AG Common Tomcat has failed
Explanation	Re-configuration of Software AG Common Tomcat has failed.
Action	Please contact your software supplier.
INMCAE0020	Starting CentraSite version Apache has failed
Explanation	CentraSite Apache cannot be started.
Action	Please contact your software supplier.
INMCAE0022	Application Server Tier version not found. Test mode is not permitted to run.
Explanation	The test mode of the Application Server Tier v3 can only be activated if an Application Server Tier 2.2 exists.
Action	Use the administration function 'migrate' of the System Management Hub to migrate directly to version v3.
INMCAE0025	Application Server Tier version not found
Explanation	Application Server Tier 2.2 is not found. Application Server Tier v3 cannot be disabled.
Action	Please contact your software supplier.
INMCAE0026	Starting Software AG Common Tomcat has failed
Explanation	An error occurred during start of Software AG Common Tomcat.
Action	Please contact your software supplier.
INMCAE0027	Starting CentraSite version Tomcat has failed
Explanation	CentraSite 2.2 Tomcat cannot be started.
Action	Please contact your software supplier.
INMCAE0028	Registration of Application Server Tier version has failed
Explanation	The Application Server Tier 2.2 is activated but could not registered in the Registry Repository.
Action	Please contact your software supplier.

INMCAE0029	Unsupported Registry Repository version version
Explanation	An upgrade of the current Registry Repository version is not supported.
Action	Please contact your software supplier.
INMCAE0030	Starting Registry Repository has failed
Explanation	Starting Registry Repository has failed.
Action	Please contact your software supplier.
INMCAE0031	Stopping Registry Repository has failed
Explanation	Stopping Registry Repository has failed.
Action	Please contact your software supplier.
INMCAI0014	Deactivate Application Server Tier version
Explanation	Deactivates an Application Server Tier. To deactivate an Application Server Tier 2.2, the CentraSite 2.2 Apache and the CentraSite 2.2 Tomcat are stopped and disabled. To deactivate a later version of the Application Server Tier, we only stop and disable the corresponding CentraSite Apache version.
Action	none
INMCAI0015	Activate Application Server Tier version
Explanation	Activates an Application Server Tier. To activate an Application Server Tier 2.2, The CentraSite 2.2 Apache and the CentraSite 2.2 Tomcat are enabled and started. To activate a later version of the Application Server Tier, the corresponding CentraSite Apache version is stopped and disabled and the Software AG Common Tomcat is re-configured.
Action	none
INMCAI0016	Configure Application Server Tier version
Explanation	Configures an Application Server Tier v3 during migration. In that phase, the configuration files are modified and the specified port numbers are checked.
Action	none

INMCAI0021	Register Application Server Tier version
Explanation	The Application Server Tier will be registered by the Registry.
Action	none
INMCAI0023	Configure test mode
Explanation	Configures the test mode of an Application Server Tier v3
Action	none
INMCAI0024	Activate test mode
Explanation	Activates the test mode of an Application Server Tier v3. In that phase, the CentraSite v3 Apacher is enabled and started and the Software AG Common Tomcat is re-configured.
Action	none
INMCAI0035	Upgrade Registry
Explanation	Upgrades the Registry to version 3.
Action	none
INMCAI0036	Upgrade Repository
Explanation	Upgrades the Repository to version 3.
Action	none
INMCAI0037	Convert Registry Repository
Explanation	Converts the Registry Repository to version 3.
Action	none
INMCAI0038	Backup Registry Repository
Explanation	In that phase, a backup of Registry Repository is created.
Action	none
INMCAW0002	Creating backup of Registry Repository has failed. A separate backup of Registry Repository has to be done by the user.
Explanation	Back up Registry Repository as final step of the upgrade has failed. A separate backup has to be triggered by the user.
Action	Backup Registry Repository with the administration function 'backup' of the System Management Hub

INMCAW0013	Application Server Tier could not be registered. A separate registration is necessary.
Explanation	The Application Server Tier could not be registered within the Registry.
Action	Use the administration function 'register' of the System Management Hub to register the Application Server Tier separately.
INOAAE0001	Function not selected : name
Explanation	The server extension function is not selected so that the parameter cannot be modified.
Action	Select the server extension function first.
INOAAE0004	Cannot modify journal space
Explanation	The journal space of the specified database cannot be modified.
Action	Check whether the data space is already in use. Check the database location for remaining disk space.
INOAAE0018	Port number 'port' for 'name' indication
Explanation	The port number cannot be used.
Action	Change the port parameter value.
INOAAE0019	fail - delete database dbname read only parameter is set
Explanation	The database parameter "read only" must be cleared before the database can be deleted.
Action	Remove the read only flag in the database parameters.
INOAAE0020	Modify Email notification properties failed
Explanation	The modification of Email notification properties failed.
Action	Look at the detailed error message and action.
INOAAE0022	mvcount spaces successfully moved from oldloc to newloc, one or more spaces couldn't be moved because of errors/warnings
Explanation	The given number of spaces were moved successfully but one or more spaces could not be moved because an error or a warning occurred during the execution of the command.
Action	Find out why spaces were not moved and try to move them via the 'Move' command of the database spaces entry.

INOAAE0024	Change License file failed
Explanation	Change license file failed.
Action	Check the license file.
INOAAE0026	The parallel option is not supported for incremental backups
Explanation	Options "parallel" and "incremental" are mutually exclusive.
Action	Select only one of the options.
INOAAE0032	Cannot activate dynamic property 'name'
Explanation	The property cannot be updated in the current server session, but will be active after a restart of the database.
Action	Restart the database to activate the property.
INOAAE0038	Cannot open file path, file does not exist or is opened by another one or not enough access rights
Explanation	The file does not exist or is already open.
Action	Check the filename.
INOAAE0039	Unknown database space number
Explanation	The database space number is not valid for this database.
Action	Use a valid database space number.
INOAAE0040	This command is valid for journal space only
Explanation	The database space type is not valid for this command.
Action	Use the journal space.
INOAAE0042	CD database information file not found
Explanation	The error message information file for the CD database not found.
Action	Check the path and filename.
INOAAE0043	CD database information file doesn't contain all necessary data or was created on a different platform
Explanation	The content of the information file is not complete or the file is not the required information file is from a different operating system.
Action	Check the content of the information file.

INOAAE0044	CD database from different operating system cannot be registered
Explanation	Only CD databases from the same operating system can be registered.
Action	Use a CD database that was created on the same operating system.
INOAAE0045	Operation not allowed on CD database or read only database
Explanation	The operation is not allowed on a CD database or read only database.
Action	No action required.
INOAAE0054	The "Add database space" function has failed
Explanation	The attempt to add one or more of the database spaces failed.
Action	Check the database locations for remaining disk space. The server property "read only" may be set to "yes".
INOAAE0055	More than one replication database is not yet supported
Explanation	Only one replication database is allowed.
Action	No action required.
INOAAE0056	Re-invert of database dbName has failed
Explanation	The re-invert operation failed. Possible reasons are that the database is not active or, if active, one or more indices could not be repaired.
Action	Check your database status.
INOAAE0058	Invalid Access Control Element name
Explanation	Function names cannot be part of paths.
Action	Use either a function name or a path but not both.
INOAAE0059	Invalid master database name
Explanation	The master database name specified is invalid.
Action	Specify another database name for the master database.
INOAAE0060	Specification of key parameter is mandatory
Explanation	The parameter must be specified.
Action	Specify the parameter and try again.

INOAAE0065	Server extension 'name' not defined
Explanation	The specified server extension does not exist.
Action	No action required.
INOAAE0066	Internal configuration store key _default not found
Explanation	The default internal configuration store key could not be found.
Action	Please contact your software supplier.
INOAAE0067	File 'path' not found
Explanation	The specified file could not be found.
Action	Specify a valid filename.
INOAAE0068	Different server extension names: name1 is different from name2
Explanation	The server extension names differ.
Action	No action required.
INOAAE0069	File 'path' not extracted
Explanation	The server extension installation file was not extracted.
Action	No action required.
INOAAE0070	File 'path' already installed
Explanation	The server extension installation file was previously installed.
Action	No action required.
INOAAE0072	Document 'path' not installed
Explanation	The server extension installation document was not installed.
Action	The action depends on previous error messages. Please check the previous messages for more information.
INOAAE0073	File 'path' not created
Explanation	The server extension installation file was not created.
Action	Correct the access rights for the directory and retry the operation.

INOAAE0074	Server extension name 'name' not defined
Explanation	The name of the server extension is not defined.
Action	Specify the name of the server extension and retry the operation.
INOAAE0075	Server extension name 'name' already defined
Explanation	The name of the server extension already exists.
Action	Change the name of the server extension and retry the operation.
INOAAE0076	Directory 'path' already exists
Explanation	The server extension installation directory already exists.
Action	Remove the directory and retry the operation.
INOAAE0077	Document 'path' already installed
Explanation	The server extension installation document is already installed.
Action	Remove the server extension installation document.
INOAAE0078	Execution failed: command
Explanation	The specified operating system command failed.
Action	The action depends on previous error messages. Please check the previous messages for more information.
INOAAE0079	Database name not defined
Explanation	The required database name was not specified.
Action	Please contact your software supplier.
INOAAE0080	No functions defined: name
Explanation	There are no functions defined in the server extension.
Action	Add functions to the server extension and retry the installation.
INOAAE0081	The Tamino server returned an invalid server extension response document
Explanation	The server extension response document does not correspond to the agreed protocol with the Tamino server.
Action	Please contact your software supplier.

INOAAE0082	Server extension 'name' does not exist
Explanation	The specified server extension does not exist.
Action	Correct the name of the server extension and retry the operation.
INOAAE0083	File 'path' already open
Explanation	The server extension installation package is already open.
Action	Wait until the package is not being used and retry the operation.
INOAAE0084	File 'path' not open
Explanation	The server extension installation package is not open.
Action	Wait until the package is not being used and retry the operation.
INOAAE0085	File 'path' not previously closed
Explanation	The server extension installation package is not closed.
Action	Wait until the package is not being used and retry the operation.
INOAAE0086	Operation 'type' not implemented
Explanation	The requested operation is not implemented.
Action	No action required.
INOAAE0087	Command 'type' not allowed
Explanation	This command is not allowed for the requested server extension.
Action	Ensure that you use one of the commands allowed for the server extension.
INOAAE0088	message
Explanation	This is a generic container for Tamino error messages.
Action	See the content of the message during online Tamino operation for further information.
INOAAE0089	Not an installation package: path
Explanation	The provided file is not a server extension installation package.
Action	Use a valid installation package.

INOAAE0092	Error during write to inodmn, write interrupted or socket closed by inodmn
Explanation	This is an internal error. It could be caused by not fully compatible versions of Tamino and System Management Hub.
Action	Please contact your software supplier.
INOAAE0093	Error during read from inodmn, read interrupted or socket closed by inodmn
Explanation	This is an internal error. It could be caused by not fully compatible versions of Tamino and System Management Hub.
Action	Please contact your software supplier.
INOAAE0094	Command is an illegal number
Explanation	This is an internal error in the event logging protocol.
Action	Please contact your software supplier.
INOAAE0095	This command requires a different database state
Explanation	An attempt was made to execute a command that either requires an active database, but the database is inactive, or the command can be executed only in inactive mode, but the database is active.
Action	Start or stop the database to bring it into the appropriate mode (active or inactive) and retry the command.
INOAAE0096	The command requested cannot be executed because it is already running
Explanation	The command you wish to execute is already being executed by someone else, but the command cannot be executed in parallel.
Action	Wait until the running command has completed. The argevsrv process keeps track of running commands. If the command is blocked although it is obviously not running, try restarting the argevsrv process.
INOAAE0097	Insufficient resources to complete the command
Explanation	This is an internal error in the event logging protocol. Some resource (usually disk or main storage) is exhausted and the function failed to complete.
Action	Check if there is enough free disk space. Delete temporary and otherwise expandable files, then try again.

INOAAE0098	Path 'path/name' not created
Explanation	The specified path name is too long.
Action	Choose another file structure with shorter path names.
INOAAE0099	Path 'path' not converted
Explanation	The specified path name was not converted to a URL or vice versa. Either the path name or the URL is too long.
Action	Choose another file structure with shorter path names.
INOAAE0110	Internal error with database startup by changing replication database to a normal database
Explanation	An internal error occurred when starting the database.
Action	Please contact your software supplier.
INOAAE0111	No valid destination directory for backup files given.
Explanation	No valid destination directory was given.
Action	Specify at least one valid directory with write access for Tamino and enough space for the backups.
INOAAE0113	Path 'path' not extracted
Explanation	The specified path was not extracted from the internal configuration store. This is an internal error.
Action	Please contact your software supplier.
INOAAE0114	Execution mode 'name' not extracted
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOAAE0115	Execution mode not compatible: mode1 != mode2
Explanation	The specified execution modes are not compatible.
Action	Select a compatible execution mode.

INOAAE0116	GUID not extracted
Explanation	The GUID was not extracted from the internal configuration store. This is an internal error.
Action	Please contact your software supplier.
INOAAE0117	DLL 'path' is not registered
Explanation	The specified DLL cannot be used.
Action	Specify another DLL.
INOAAE0118	DLL 'path' not unregistered
Explanation	The specified DLL cannot be used.
Action	Specify another DLL.
INOAAE0119	Remove of all server extensions failed
Explanation	The server extensions could not be removed.
Action	Check the extensions.
INOAAE0120	XML port not defined for database 'name'
Explanation	The XML port value is missing in the internal configuration store.
Action	Please contact your software supplier.
INOAAE0121	Not enough memory
Explanation	There is not enough memory for an http request.
Action	Close some of your applications.
INOAAE0122	XML template processing failed, template template missing or incorrect
Explanation	This is an internal error of the Tamino Manager browser interface.
Action	Check if the quoted template file exists and if it is intact. If not, either reinstall or contact your software supplier.
INOAAE0123	No package name defined: name
Explanation	For a server extension the Java package name is required.
Action	If you generated the Java package yourself, use a unique name for your Java package. If it is a third-party product, get a new package from your software vendor.

INOAAE0124	Unknown database dbname : rename failed or no information from Software AG XTS Directory Server
Explanation	The database to be renamed could not be found.
Action	Check if the specified database exists and if the Software AG XTS Directory Server is running.
INOAAE0125	Directory 'path' not deleted
Explanation	The directory is in use. Therefore it cannot be deleted.
Action	Wait until the directory is no longer in use and try again.
INOAAE0126	No valid location type found
Explanation	The location type parameter is missing.
Action	Specify the location type parameter.
INOAAE0127	Location type 'type' is unknown
Explanation	An unknown location type is specified.
Action	Specify a valid location type.
INOAAE0128	File 'path' not copied
Explanation	The specified file was not copied to the target file.
Action	Check your permissions or check your disk space.
INOAAE0129	Please specify at least the location path
Explanation	The path parameter is missing.
Action	Specify the path parameter.
INOAAE0130	Path path exceeds the maximum path length of maxpathlen characters
Explanation	The length of the specified path exceeds the allowed maximum length of a directory path.
Action	Specify a shorter directory path.

INOAAE0131	Location path path includes no valid directory
Explanation	The root of the specified directory path is invalid. A possible cause is that the specified directory path could be on a removable drive or RAM disk.
Action	Specify a valid directory path.
INOAAE0132	Location path path is located on a remote drive. Please choose a local drive.
Explanation	A remote drive is not allowed for a location path.
Action	Specify the location path on a local drive.
INOAAE0133	Name name exceeds the maximum name length of maxnamelen characters
Explanation	The length of the specified name exceeds the allowed maximum length.
Action	Specify a shorter name.
INOAAE0134	Name name already exists as database location name
Explanation	The specified location name is the name of an existing database location.
Action	Change the location name.
INOAAE0135	Path path already exists as database location path
Explanation	The specified location path is the path of an existing database location.
Action	Change the location path specification.
INOAAE0136	Database location name not found
Explanation	The specified location name was not found in the internal configuration store.
Action	Specify an existing location name.
INOAAE0137	Location name is the current default location
Explanation	Deleting the current default location is not allowed.
Action	Change the default location.
INOAAE0138	Location name is the current default backup location
Explanation	Deleting the current default backup location is not allowed.
Action	Change the default backup location.

INOAAE0140 **Database dbname uses database location name with location path path as 'category'. If you still want to delete the location, all spaces from that location must be moved to another location before you can delete it.**

Explanation The specified location is defined as a category location for a database, so deleting is not allowed. Move the database spaces on that location to another one.

Action Change the default database location category specification.

INOAAE0141 **No response document received**

Explanation There was no response document received from the server.

Action Check if the network communication is established.

INOAAE0142 **Value for property 'name' too small - minimum is minval**

Explanation The value for the given property is smaller than the minimum allowed.

Action Specify a larger value.

INOAAE0143 **Value for property 'name' too large - maximum is maxval**

Explanation The value is larger than the maximum allowed.

Action Specify a smaller value.

INOAAE0144 **Invalid numeric value for property 'name'**

Explanation The property is a numeric property and the value has the wrong type.

Action Change the property value to numeric.

INOAAE0145 **Property 'name' must be 'yes' or 'no'**

Explanation The property is a boolean property and the value has the wrong type.

Action Change the property value to 'yes' or 'no'.

INOAAE0146 **The sequence of backup spaces is not complete.**

Explanation One or more streams or extents are missing in the selected backup spaces. Only complete backups can be restored. Spaces missing at the end of the sequence will be only detected at runtime when data is loaded into the new database.

Action Check the stream or extent numbers of the selected backup spaces and add missing spaces. Check if the sequence of backup spaces (Extent 1, Extent 2, ..) is correct.

INOAAE0149	Web server wsname already assigned
Explanation	The web server is already assigned to the specified database.
Action	Check the specified web servers and the web server assignments.
INOAAE0153	Web server wsname not assigned
Explanation	The specified web server is not assigned to the specified database, therefore the assignment cannot be deleted.
Action	Check the web server assignments to the specified database.
INOAAE0154	Error retrieving collection/doctype information: the requested document(s) could not be locked
Explanation	The document is already locked or cannot be locked. A possible reason can also be an unclosed session.
Action	Wait for a short time and try this command again.
INOAAE0155	Unknown location location name
Explanation	The given location does not exist.
Action	Choose a valid location.
INOAAE0157	Parameter parameter name missing
Explanation	The parameter with the given name is not specified.
Action	Specify the required parameter.
INOAAE0158	parameter name: invalid path, directory does not exist or is not writable
Explanation	The given path does not exist or is not writeable.
Action	Use a path that exists and is writable.
INOAAE0159	Database dbname already exists
Explanation	The "rename database" command failed because the database name already exists.
Action	Use a different name or remove the database.

INOAAE0162	Cannot delete database space spaceNo
Explanation	The specified database space cannot be deleted from the location.
Action	Check whether the database space is already in use.
INOAAE0165	Cannot expand database space spaceNo
Explanation	The specified database space cannot be expanded.
Action	Check whether the database space is already in use. Check the database location for remaining disk space. If the database is read-only it cannot be expanded.
INOAAE0169	Database database name exists
Explanation	A database with the same name exists either on the local computer, or in the scope of XTS Directory Service (which may know databases on multiple computers).
Action	Choose a different name. On Windows platforms, it is not sufficient to have two names differ only in upper/lowercase.
INOAAE0170	Configuration 'configuration' already exists for external backup method 'method'
Explanation	The configuration name already exists for this external backup method.
Action	Specify a new configuration name which does not exist already.
INOAAE0174	Could not initialize TCP stack
Explanation	This is an internal error in the event logging protocol. The communication between a logging client and the logging server could not be established. Basic functions and commands may be unaffected by this failure but messages will not be stored permanently or displayed in the Tamino Manager browser interface.
Action	This failure is most likely due to extreme shortage of resources, or missing operating system components. Check the disk space. Check the integrity of the installation. Contact you software supplier to check if there is a software update.
INOAAE0175	Error in inodmn conversation: unexpected response buffer
Explanation	This is an internal error of the event logging protocol.
Action	Please contact your software supplier.

INOAAE0177	Error in inodmn conversation: invalid number
Explanation	This is an internal error in the event logging protocol.
Action	Please contact your software supplier.
INOAAE0178	Function not implemented
Explanation	This is an internal error of the event logging protocol, a feature is not implemented in the version installed. Basic functions and commands are probably not affected.
Action	No action necessary. Please contact your software supplier for a possible software update.
INOAAE0179	Error in inodmn conversation: request failed
Explanation	This is an internal error in the event logging protocol. It could be caused by not fully compatible Tamino and System Management Hub versions.
Action	Please contact your software supplier for a possible software update.
INOAAE0180	Too many parameters
Explanation	A parameter has been specified repeatedly, but is only allowed once.
Action	Change the command and retry.
INOAAE0181	Database does not exist
Explanation	There is no database with the given name.
Action	Choose a valid database name.
INOAAE0182	Space space is not a valid backup space
Explanation	The file or tape specified has not been recognized as a valid Tamino backup. The file or tape could be damaged or access to the medium could be denied.
Action	Use a valid backup space.
INOAAE0183	Backup spaces have not been specified in the sequence determined by their extent or stream numbers
Explanation	The spaces are not ordered by their extent or stream number. The first space does not have the extent number 1.
Action	Specify backup spaces in the order of the extent or stream number.

INOAAE0184	Creation of directory path failed
Explanation	The directory at the given path could not be created.
Action	Check the permissions for the given path.
INOAAE0186	Unknown command
Explanation	The command is unknown in this context.
Action	Specify a valid command for this context.
INOAAE0187	Missing parameter
Explanation	A parameter specification is missing.
Action	Specify the needed parameter.
INOAAE0188	Not allowed to set a location of type 'type' as default location
Explanation	The location represents a type which is not allowed to be set as the default location.
Action	Set another location as the default location.
INOAAE0189	No valid location category specified
Explanation	The specified category is not a valid location category.
Action	Specify a valid location category.
INOAAE0190	Memory fault
Explanation	An error has occurred while allocating memory storage.
Action	Reboot the system.
INOAAE0191	database space spaceNo at location oldLoc not found
Explanation	A database space cannot be moved from one location to another, because the space does not exist at the source location.
Action	Search for the space at another location.
INOAAE0192	database space spaceNo at location newLoc already exists
Explanation	The database space cannot be moved to the new location. The space already exists.
Action	Delete the space from the new location.

INOAAE0193	Cannot remove database space spaceNo from location oldLoc
Explanation	A database space cannot be removed from the source location.
Action	Check the permissions for the database space. The database space could be in use by a running database. Do a shutdown of the database and try again.
INOAAE0194	Cannot write internal configuration store
Explanation	The write operation into the internal configuration store failed.
Action	Check the permissions.
INOAAE0195	Unknown database dbname or no information from Software AG XTS Directory Server
Explanation	The database is unknown or there is no information from the Software AG XTS Directory Server.
Action	Check the database name, and check if the Software AG XTS Directory Server is running.
INOAAE0196	Database dbname ID or port not found
Explanation	The database ID or port was not found in the internal configuration store.
Action	Please contact your software supplier.
INOAAE0197	Database dbname already active
Explanation	The database is already active.
Action	Stop the database and re-execute the operation.
INOAAE0198	Database dbname not active
Explanation	The database is not active.
Action	Start the database and re-execute the operation.
INOAAE0203	Function 'name' not found
Explanation	The function was deleted, but the display has not been refreshed.
Action	Refresh your display.

INOAAE0204	Invalid function type 'type'
Explanation	The type of a server extension function was invalid. This is an internal error.
Action	Please contact your software supplier.
INOAAE0205	File 'path' not added
Explanation	The file was not added to the server extension package. This is an internal error.
Action	Please contact your software supplier.
INOAAE0208	Not allowed to specify a recoverydate with recoveryoption=no
Explanation	If a recoverydate is specified, recoveryoption=no is not allowed.
Action	Specify recoveryoption=yes or do not use the recoveryoption parameter.
INOAAE0209	Access Violation - You are not allowed to access the requested database
Explanation	You are not authorized to access the database.
Action	Get authorization from the database administrator.
INOAAE0210	Min Port must be lower than Max Port and Port Ranges cannot overlap
Explanation	An invalid port range was specified. Min Port must be lower than Max Port and Port Ranges cannot overlap.
Action	Change the ports and retry the operation.
INOAAE0212	Error reading database locations
Explanation	An error occurred while reading database locations from the internal configuration store.
Action	Please contact your software supplier.
INOAAE0215	Unknown category
Explanation	The agent was called with an invalid category.
Action	Use a valid category for this agent.
INOAAE0216	Missing database name
Explanation	The database name is missing in the object ID.
Action	Use a valid object ID.

INOAAE0217	Missing Object ID
Explanation	The object ID is missing in the agent call parameter.
Action	Use a valid object ID.
INOAAE0218	Missing database space type
Explanation	The database space type is missing in the agent call parameter.
Action	Use a valid database space type.
INOAAE0219	Unknown database space category
Explanation	The database space category in the agent call parameter is unknown.
Action	Use a valid database space category .
INOAAE0220	The database dbname does not exist
Explanation	One of the following errors may have occurred: - XTS not configured in the "hosts" file - the XTS service not running - the database is not specified in the XTS configuration file xtsurl.cfg.
Action	Choose another database name, check XTS configuration.
INOAAE0222	The database dbname must be offline
Explanation	The database must be stopped for this operation.
Action	Shut down the database.
INOAAE0225	Leave command request on Event Service failed
Explanation	This request is part of the command synchronization scheme. This scheme synchronizes the execution of commands that might interfere otherwise and it prevents parallel execution of commands that should be executed only once per database at a time (like a backup).
Action	Check if the Event Service is running. If it is running, stop and re-start the service to initialize command synchronization
INOAAE0226	Database status request on event demon failed
Explanation	The status of a database could not be received from the event demon.
Action	Check if the event demon is running.

INOAAE0229	Tape path does not exist
Explanation	The tape with the specified path does not exist.
Action	Specify an existing tape path.
INOAAE0230	Device path does not exist
Explanation	The device with the specified path does not exist.
Action	Specify an existing device path.
INOAAE0231	Could not create location name at path
Explanation	Creating the location failed because of an internal configuration store error.
Action	Check access rights (privileges) of the connected user; the user must be a power user (administrator).
INOAAE0232	Could not delete location name
Explanation	Deleting the location failed because of an internal configuration store error.
Action	Please contact your software supplier.
INOAAE0233	Could not rename location name to newname
Explanation	Renaming the location failed because of an internal configuration store error.
Action	Please contact your software supplier.
INOAAE0234	Could not set location name as default database location
Explanation	Setting the location as the default location failed because of an internal configuration store error.
Action	Please contact your software supplier.
INOAAE0235	Could not set location name as default backup database location
Explanation	Setting the location as the default backup location failed because of an internal configuration store error.
Action	Please contact your software supplier.

INOAAE0236	Could not modify default of database location category 'category'
Explanation	Modifying the default database location category failed because of an internal configuration store error.
Action	Please contact your software supplier.
INOAAE0238	Archive path is empty
Explanation	The archive is empty or corrupt. Try with a correct archive.
Action	Correct the archive you want to work with.
INOAAE0242	No database name specified
Explanation	The database name must be specified.
Action	Specify the database name.
INOAAE0243	database registration failed
Explanation	The registration of a read only database failed.
Action	Check the source file/path and database name.
INOAAE0268	Move command for location type 'type' not supported
Explanation	The move command is not supported for some location types, especially tape.
Action	Specify a valid location type as the target of the move command.
INOAAE0272	Backup date 'bckDate' specifies no valid backup set for database dbName
Explanation	The given date was not found as a savepoint entry in the internal configuration store.
Action	Specify a valid date which corresponds to a valid savepoint entry in the internal configuration store.
INOAAE0274	No collection name specified
Explanation	The collection name must be specified for this operation.
Action	Specify the collection name.
INOAAE0284	Unregister is not allowed for normal databases; use "delete" command
Explanation	Use the "delete" command to remove a normal database.
Action	Use the batch command "delete" instead of "unregister".

INOAAE0285	Delete is not allowed for CD databases; use "unregister" command
Explanation	Use the "unregister" command to remove a CD database.
Action	Use the batch command "unregister" instead of "delete".
INOAAE0287	External function name exceeds 80 characters
Explanation	The length of the external function name may not exceed 80 characters.
Action	Specify a shorter function name.
INOAAE0294	No file restored : name
Explanation	No file was restored. Maybe there are no server extensions installed.
Action	If there are server extensions installed check your database.
INOAAE0295	Directory not created : path
Explanation	The specified directory was not created.
Action	Check the permissions of your file system.
INOAAE0296	Directory not found : path
Explanation	The specified directory was not found.
Action	Check the permissions of your file system.
INOAAE0297	Database not running : name
Explanation	The specified database is not running.
Action	Start the database.
INOAAE0298	Server returned error code : type
Explanation	The Tamino server returned an error code.
Action	Please contact your software supplier.
INOAAE0304	Fail - command log switch to mode buffers buffers
Explanation	This is a result message for a batch command.
Action	Check the database.

INOAAE0305	Parameter not defined : name
Explanation	No value given for a mandatory parameter.
Action	Retry the command with the specified parameter value.
INOAAE0306	Invalid object identification : name
Explanation	The given object identification is invalid.
Action	Retry the command with a correct object identification.
INOAAE0307	Update of settings failed : name
Explanation	The update of the given settings parameter failed.
Action	Check the job log for further information.
INOAAE0310	Path exists; please remove it or use another one
Explanation	This is an error message for creating a CD database in batch mode. A specified pathname exists already, so a different pathname must be supplied or the existing path must be removed.
Action	Remove the path or use another one.
INOAAE0311	Invalid character used in the specified location name at position position
Explanation	An invalid character has been specified in the location name. This can be a non-ASCII character or one of the special characters "%&,;! \=#[] \" \< \>".
Action	Change the character.
INOAAE0312	Invalid character used in the specified path at position position
Explanation	An invalid character has been specified in the given path. This can be a non-ASCII character or one of the special characters "\"/::*?\"< > &\"" for Windows or "\":*? \< > ,;&!\" for all other operating systems.
Action	Change the character.
INOAAE0313	Mapped documents exist : name
Explanation	Mapped XML documents exist for the server extension.
Action	Delete the XML documents before uninstalling the server extension.

INOAAE0314	Command not allowed if no function is selected
Explanation	The server extension must contain at least one selected function.
Action	Select some functions from the object being packed.
INOAAE0315	Database name contains invalid character "&" (ampersand)
Explanation	A database name can't contain the "&" character.
Action	Remove the "&" from the database name.
INOAAE0347	Database could not be connected
Explanation	The security manager could not connect to Tamino.
Action	Check if the database has been started.
INOAAE0355	The first and last character of a name should not be a blank
Explanation	Blanks are not allowed at the beginning and end of a name.
Action	Change the first/last character.
INOAAE0356	ACL name contains invalid character:
Explanation	Special characters are not allowed.
Action	Remove special characters from ACL name.
INOAAE0359	Group name contains invalid allowed character:
Explanation	Special characters are not allowed.
Action	Remove special characters from the group name.
INOAAE0361	User ID contains invalid character:
Explanation	Special characters are not allowed.
Action	Remove special characters from the user ID.
INOAAE0362	User created with escaped XML special characters in description
Explanation	XML special characters are not allowed.
Action	Remove special characters from the description.

INOAAE0363	Special characters are not allowed in an ACE name:
Explanation	Special characters are not allowed in an ACE name.
Action	Remove special character from ACE name.
INOAAE0370	TSM@DLL_PARSE_ERR
Explanation	The retrieved XML-document is invalid or the XML parser could not retrieve data.
Action	Shut down the database and restart it.
INOAAE0372	TSM@DLL_UNKNOWN_ACL_OR_ACL_NOT_RETRIEVABLE
Explanation	The mentioned ACL is no longer available. Maybe another concurrent session deleted it.
Action	Refresh the data within the Tamino Manager and try again.
INOAAE0373	TSM@DLL_UNKNOWN_GROUP
Explanation	The mentioned GROUP is no longer available. Maybe another concurrent session deleted it.
Action	Refresh the data within the Tamino Manager and try again
INOAAE0377	Access control element 'name' already exists in access control list
Explanation	The access control element already exists in an access control list.
Action	Change the name of the access control element.
INOAAE0378	Version with compatibility level level of Tamino not found
Explanation	For reading the backup, a Tamino version of the same compatibility level is required.
Action	Install a Tamino version of the required compatibility level.
INOAAE0381	No container size information in backup file filename found
Explanation	The backup file does not contain important information for restoring.
Action	Check the backup file or generate a new one.
INOAAE0382	Not enough free memory
Explanation	Not enough free memory.
Action	try closing other applications to free memory.

INOAAE0386	Access Control List 'name' already exists
Explanation	An access control list with the specified name already exists.
Action	Change the name of the access control list.
INOAAE0387	User 'name' already exists
Explanation	The given user already exists in the ino:user doctype.
Action	Supply a new user ID.
INOAAE0388	User 'name' does not exist
Explanation	The user ID has not been found in the ino:user doctype.
Action	Create the required user ID.
INOAAE0389	Access control list 'name' does not exist
Explanation	The access control list has not been found in the ino:acl doctype.
Action	Create the required access control list.
INOAAE0390	User group 'name' does not exist
Explanation	A user group with the given name has not been found in the ino:group doctype.
Action	Create the required group.
INOAAE0391	Acename has not been defined
Explanation	The command line parameter "acename" has not been provided.
Action	Provide the "acename" parameter.
INOAAE0392	Permission has not been defined
Explanation	The command line parameter "permission" has not been provided.
Action	Provide the parameter "permission".
INOAAE0393	Aclname has not been defined
Explanation	The command line parameter "aclname" has not been provided.
Action	Provide the parameter "aclname".

INOAAE0394	Database is readonly
Explanation	The database is readonly, updates are not possible.
Action	No action required.
INOAAE0395	UserID has not been defined
Explanation	The command line parameter "userid" has not been provided.
Action	Provide the parameter "userid".
INOAAE0396	Groupname has not been defined
Explanation	The command line parameter "groupname" has not been provided.
Action	Provide the parameter "groupname".
INOAAE0397	Ace permission is not defined
Explanation	The permission for the access control element is not defined.
Action	Provide the permission for the access control element.
INOAAE0398	Permission has to be set to an allowed value
Explanation	Permission has not been set to an allowed value.
Action	Set permission to an allowed value.
INOAAE0399	Description has not been defined
Explanation	Description has not been provided.
Action	Provide description.
INOAAE0400	User group 'name' already exists
Explanation	The usr group already exists in the ino:group doctype.
Action	Change the group name to one that does not already exist.
INOAAE0401	Missing compatibility level : type
Explanation	The source or target compatibility level was not specified.
Action	Specify the compatibility level and execute the command again.

INOAAE0402	Set database version failed
Explanation	The "set database" action failed. Read the error messages to get more information.
Action	Check the error messages that are generated before this message at runtime to get the reason.
INOAAE0408	Some databases may be still active at system shutdown
Explanation	An error occurred while all active databases were stopped.
Action	Shut down manually all active databases prior to the system shutdown; get assistance from your software supplier to fix the problems that were reported.
INOAAE0412	This request is in conflict with another request that is currently being executed
Explanation	Some commands that access the same resources are mutually exclusive. This message can also appear if a process has been killed with operating system means or has crashed while the crash held the critical section locked.
Action	Retry later. If no other command is active and no one else is currently executing administrative commands, shut down and restart the System Management Hub Event Layer Service.
INOAAE0413	The request cannot be executed because a condition is missing
Explanation	The request requires another command to be active.
Action	No action possible. Please contact your software supplier.
INOAAE0414	Restore of database dbName failed
Explanation	An error occurred while restoring the specified database.
Action	Try to detect the error, otherwise contact your software supplier.
INOAAE0417	Web server 'wsname' does not exist
Explanation	The IP address and/or port of web server cannot be changed; the specified web server does not exist.
Action	Use an existing web server.
INOAAE0418	IP address of web server 'wsname' is invalid
Explanation	The IP address of the web server is invalid.
Action	Specify the IP address in a valid format.

INOAAE0419	File 'path' already exists
Explanation	The server extension installation file already exists.
Action	Select another path name.
INOAAE0423	Unable to execute command with version 'argbatchversion' for database from version 'version'. Please use 'version=version' parameter for argbatch command, or change your environment : 'argbatch set environment version=version'.
Explanation	A Tamino agent was called from the wrong version.
Action	Use the "version" parameter for the argbatch command or change your environment with: "argbatch set environment version=...".
INOAAE0428	Web server 'wsname' not defined
Explanation	The specified web server is not defined in the web server management.
Action	Add the specified web server in the web server management.
INOAAE0439	Tamino plug-in for argevsrv not installed or not properly initialized
Explanation	The Tamino plug-in was not installed, or the System Management Hub Event Service was unable to load it. Tamino will work without it but some administrative commands will not be be synchronized. This will cause problems only in rare conditions when multiple databases are created at the same time on the same computer.
Action	Avoid creating multiple databases at the same time on the same computer; please contact your software supplier to find out why the Tamino plug-in was not loaded by the System Management Hub Event Service.
INOAAE0441	version of database not found
Explanation	The database was found but not the version of Tamino that it requires.
Action	Check if the correct Tamino version for database is installed or set the version to one installed on the machine.
INOAAE0442	Tamino version not found
Explanation	The specified Tamino version was not found.
Action	Check if the Tamino version is installed on the machine.

INOAAE0443	highest Tamino version not found
Explanation	The highest Tamino version was not found.
Action	Check if Tamino is installed on the machine
INOAAE0444	Max and/or Min port not found or RGS error
Explanation	The Max and/or Min port was not found, or there was an RGS error.
Action	Please contact your software supplier.
INOAAE0456	The "Move database space" function failed
Explanation	An attempt to move a database space failed. Additional information is supplied in error messages that have occurred earlier.
Action	Please follow the actions of the error messages displayed earlier in the same job log.
INOAAE0459	The "Create Database" function failed
Explanation	An attempt to create a database failed. Additional information is supplied in error messages that have occurred earlier.
Action	Please follow the actions of the error messages displayed earlier in the same job log.
INOAAE0462	The "Delete Database" function failed
Explanation	An attempt to delete a database failed. Additional information is supplied in error messages that have occurred earlier.
Action	No action required. Please follow the actions of the error messages displayed earlier in the same job log.
INOAAE0463	The database information is available in ONLINE mode only
Explanation	The information can only determined when the database is started.
Action	Start the database and call the information function again.
INOAAE0472	Backup of database dbName failed
Explanation	Errors occurred while backing up the specified database. A possible reason could be low system memory.
Action	Try to detect the error, otherwise contact your software supplier.

INOAAE0474	Start of database dbName failed
Explanation	Errors occurred while starting the database.
Action	Try to detect the error, otherwise contact your software supplier.
INOAAE0475	Stop of database dbName failed
Explanation	Errors occurred while stopping the specified database.
Action	If you cannot identify the error from a previous error message, please contact your software supplier.
INOAAE0480	Add database space spaceNo to location newLoc failed
Explanation	An attempt to add database spaces to the specified location failed.
Action	No action required.
INOAAE0481	Not enough space on location newLoc
Explanation	The new location to which the database space should be moved is not big enough.
Action	Choose a larger location for moving the database space.
INOAAE0491	Error(s) occurred during modify of database properties
Explanation	An error occurred while attempting to modify database properties. Only the properties with an error message or a warning were not modified. All other properties are changed.
Action	Please contact your software supplier.
INOAAE0509	External function name already used : name
Explanation	The external name of a server extension function is already in use.
Action	Change the external function name and retry the operation.
INOAAE0510	Java classpath not modified : text
Explanation	The Java classpath was not modified according to the modification rules.
Action	Correct the modification parameters and retry the operation.

INOAAE0534	File 'path' not deleted
Explanation	The server extension DLL file could not be deleted.
Action	Delete the DLL manually.
INOAAE0547	Directory path does not exist
Explanation	The directory with the specified path does not exist.
Action	Specify an existing path.
INOAAE0548	No location name specified
Explanation	No location name was specified.
Action	Specify a location name.
INOAAE0549	Character " not allowed as part of location name
Explanation	The character '\" is not allowed as part of the location name, because this name is used as internal configuration store key, and the '\" is the internal configuration store key delimiter.
Action	Replace this character by another one.
INOAAE0567	There is currently only one location defined. Please create at least one more file system location using the Location Management 'Add' command.
Explanation	No second location is defined that can be used as destination location for the move command .
Action	Create a second location and then start this command again.
INOAAE0605	Wrong date or date format. Format 'datepattern' required.
Explanation	An invalid date is specified or an invalid date format is used.
Action	Specify a valid date (use same format as used in 'argbatch show backups').
INOAAE0608	No other Tamino version installed, set version not possible
Explanation	Because there is no other Tamino version installed, it makes no sense to change the version.
Action	No action required.

INOAAE0611	Named pipe path does not exist
Explanation	The named pipe with the specified path does not exist.
Action	Specify an existing named pipe path.
INOAAE0619	Device path is not a named pipe
Explanation	The specified path is not a named pipe.
Action	Specify an existing named pipe path.
INOAAE0637	Directory name 'path' not compatible with object identification 'name'
Explanation	The directory name must consist of the first part of the object identification.
Action	Create a new server extension package with the correct directory name.
INOAAE0638	Server extension function 'name' does not exist
Explanation	The specified server extension function does not exist.
Action	Correct the function name.
INOAAE0639	Server extension function parameter 'name' does not exist
Explanation	The specified server extension function parameter does not exist.
Action	Correct the parameter name.
INOAAE0641	Internal error from DSIF interface name returncode returncode error number errornr
Explanation	This is an internal error message.
Action	Please contact your software supplier.
INOAAE0645	Stop of XML session 'session' failed
Explanation	Errors occurred while stopping the specified XML session.
Action	Try to detect the error, otherwise contact your software supplier.
INOAAE0646	Error reading backup methods for database dbname
Explanation	No backup methods were found in the internal configuration store for the database.
Action	Please contact your software supplier.

INOAAE0648	Error reading parameters of backup method 'method'
Explanation	No parameters were found for the backup method in the internal configuration store.
Action	Please contact your software supplier.
INOAAE0651	Could not set global parameters for external backup method 'method' of database dbname
Explanation	Setting of global parameters failed because of an internal configuration store error.
Action	Please contact your software supplier.
INOAAE0653	Could not set configuration parameters for external backup method 'method' of database dbname
Explanation	Setting of configuration parameters failed because of an internal configuration store error.
Action	Please contact your software supplier.
INOAAE0656	Could not delete configuration 'configuration' of method 'method' of database dbname
Explanation	The deletion of the configuration failed.
Action	Please contact your software supplier.
INOAAE0658	Error reading configurations for database dbname of backup method 'method'
Explanation	An error occurred while reading the configuration data.
Action	Please contact your software supplier.
INOAAE0659	No configuration found for database dbname of backup method 'method'
Explanation	No configuration data was specified for this method and database.
Action	Specify configuration data for this method and database using the 'External Backup Environment' dialog.
INOAAE0660	Replication database name expected
Explanation	The replication database name must be specified for this function.
Action	Specify the replication database name

INOAAE0662	The database replication_db cannot be added into the permission list
Explanation	An error occurred while adding the replication database name to the permission list.
Action	Check the subsequent error messages for more details.
INOAAE0665	Database database cannot be set as replication database
Explanation	An error occurred during the type change. The database cannot be set to a replication database. Possible reason: This database is a master database.
Action	Check for related additional messages.
INOAAE0667	Replication database database cannot be reset to normal type
Explanation	The database cannot be reset to a normal database.
Action	See the subsequent error messages.
INOAAE0668	Database master_database is not active or is not a master database
Explanation	The master database must be in the active state or permit this database to be replicated.
Action	Start up the master database and check the permission list for replication databases.
INOAAE0669	Replication of master database master_database is not permitted
Explanation	Permission to replicate the master database was denied.
Action	Ask the administrator to permit replication access to the master database.
INOAAE0672	Not enough space at location newLoc for additional newsize MB - maximum free is freesize MB
Explanation	The new location to which the database space should be moved or added is not big enough.
Action	Choose a larger location for the database space operation.
INOAAE0680	Backup(s) not found wrongbackups please use one of the following backups
Explanation	Wrong backups were specified.
Action	Use only valid backups of the database. You can see all backups with the command "argbatch show backups database=mydatabase".

INOAAE0681	At least one backup must be given or don't use keepbackups
Explanation	For the option keepbackups, at least one backup must be given/selected.
Action	Give/select at least one backup.
INOAAE0683	Switching log space for database dbName has failed
Explanation	Errors occurred while switching log space for the database.
Action	Try to detect the error, otherwise contact your software supplier.
INOAAE0684	At least one destination directory must be given with parameter "destinationdirectory_0"
Explanation	the option "keep backup files" needs at least one destination directory.
Action	Specify a destination directory with the parameter "destinationdirectory_0".
INOAAE0685	For option "keepbackups=selected" at least one backup date and at least one destination directory must be given with parameter "destinationdirectory_0", "backupdate_0"
Explanation	Give at least one backup date and one destination directory in the parameter list.
Action	Use the parameter "backupdate_0" to specify a backup to be kept and "destinationdirectory_0" for the destination directory.
INOAAE0691	Could not add backup method 'method' for database dbname
Explanation	Adding the backup method failed because of an internal configuration store error.
Action	Please contact your software supplier.
INOAAE0694	Could not delete method 'method' of database dbname
Explanation	Deleting the backup method failed because of an internal configuration store error.
Action	Please contact your software supplier.
INOAAE0696	Internal error errno during modify property 'name' to 'value'
Explanation	An error occurred while setting a new property value.
Action	Please contact your software supplier.

INOAAE0699	Deletion of backup 'bckDate' of database dbName failed
Explanation	An error occurred while deleting the specified backup.
Action	Check the additional messages.
INOAAE0707	No permission to modify the type of the database
Explanation	To change the type of a database to a replication database or to set it back to a normal one, the user needs to have administrator rights. Other possible reason: The database is not allowed to replicate the master database.
Action	Log in as administrator and try the operation again and check whether this database is in the permission list of the master database.
INOAAE0708	Update server sessions exist
Explanation	The database has already update sessions so that it cannot be used to replicate another database.
Action	Use a newly created database and retry this operation.
INOAAE0709	Passwords not matched
Explanation	The passwords entered do not match.
Action	Please ensure the passwords match.
INOAAE0725	Error while changing port ranges
Explanation	An error occurred while changing the port ranges.
Action	Please contact you software supplier.
INOAAE0727	path is not a raw section
Explanation	The specified path must be a raw section.
Action	Ensure that the path specifies a raw section.
INOAAE0728	Unable to load data for CD databases
Explanation	This database is a CD database. Data load not possible.
Action	No action required.

INOAAE0731	Rename web server failed
Explanation	The web server could not be renamed, the operation failed.
Action	The reason why the web server could not be renamed is in the job log. Check it and retry.
INOAAE0733	Add web server failed
Explanation	The web server could not be added, the operation failed.
Action	The reason why the web server could not be added is in the job log. Check it and retry.
INOAAE0737	Delete web server failed
Explanation	The web server could not be deleted, the operation failed.
Action	The reason why the web server could not be deleted is in the job log. Check it and retry.
INOAAE0740	Modify web server failed
Explanation	The web server could not be modified, the operation failed.
Action	The reason why the web server could not be modified is in the job log. Check it and retry.
INOAAE0741	Domain 'name' does not exist
Explanation	Domain has not been defined.
Action	Please check the defined domains list in Tamino and create the domain if necessary.
INOAAE0744	parameter name: must not be a location on a raw section, is only allowed on DATA, INDEX, JOURNAL and RESERVED location
Explanation	A location on raw section is only allowed as DATA, INDEX, JOURNAL and RESERVED location.
Action	Use a location that is not located on a raw section.
INOAAE0745	All reserved locations are located on raw section(s), at least one location must not be located on a raw section
Explanation	At least one reserved location for a database must not be on a raw section.
Action	Use at lease one location not located on a raw section.

INOAAE0746	Location locname is of type type, this type is not allowed for loctype
Explanation	Some location types are only allowed for special locations. For example locations on a tape are only allowed for backup locations.
Action	Use a location which is allowed for the current location type.
INOAAE0747	Not allowed to set a location of type 'type' as default backup location
Explanation	The default backup location cannot be in a location of type "raw".
Action	Use a location of a type that is allowed for a backup location.
INOAAE0749	This command is deprecated. Please use the new command "show acls".
Explanation	The command has been replaced by a new command.
Action	Please use the new command.
INOAAE0750	This command is deprecated. Please use the new command "show groups".
Explanation	The command is deprecated.
Action	Please use the new command.
INOAAE0753	Query internal configuration store key key failed
Explanation	An error occurred when querying the given internal configuration store key.
Action	Please contact your software supplier.
INOAAE0754	This command is deprecated. Please use the new command "show users".
Explanation	The command is deprecated.
Action	Please use the new command.
INOAAE0755	Access to internal configuration store value value key key failed
Explanation	An error occurred when getting the given internal configuration store key value.
Action	Please contact your software supplier.
INOAAE0761	parameter name: must be the logical name of an existing location
Explanation	The parameter must specify the short, "logical" name of a location (not its entire path), and the location must exist.
Action	Display the the "Locations" tree node in the System Management Hub (under the "Tamino" node) to display a list of existing locations or to add a new location.

INOAAE0762	parameter name: must contain only digits 0 to 9
Explanation	The value for this parameter must be an integer number with no fractional parts.
Action	Re-enter the parameter using only digits 0-9.
INOAAE0763	parameter name: must be "yes" or "no"
Explanation	This parameter must have either the value "yes" or "no", all lowercase characters.
Action	Re-enter either "yes" or "no" (without the double quotes).
INOAAE0764	parameter name: must only contain digits 0-9, comma, dot, "E" or "e" for exponentiation
Explanation	The value for this parameter must be a valid floating point number, or a number with an exponent.
Action	Re-enter the parameter value as floating point number, or with an exponent. Depending on the locale settings on the local computer, the decimal sign may be expected either as "," or as a ".".
INOAAE0766	Size for space type extent extend is missing and no default size available
Explanation	No default size could be obtained for this space type.
Action	A size must be specified, and it must be above the minimum value for this space type.
INOAAE0767	The size specified for space type extent extend is under the minimum (minimum size Mb)
Explanation	The given size for the extent is too small.
Action	A size of at least the given minimum must be specified.
INOAAE0768	At least one backup location must be in the filesystem if no tape is supplied as initial backup
Explanation	If no tape is supplied to create the database from (in the "Create From Backup" command) the initial backup is created at creation time as a file and requires a location that is in the file system. Before this message was issued, attempts were made to create it in one of the provided backup locations, in the default backup location and in the default location.
Action	Create a location in the file system using the "Add" command the System Management Hub browser interface, tree node Tamino/DB Locations and make it the default location (by clicking the new location and executing the "Set Default" command).

INOAAE0769	At least one backup location is required for the initial backup of the new database
Explanation	Specify one or more location where backups shall be created later on. This location is already required and used during the creation of the new database.
Action	Specify one or more writable, random accessible backup locations for the database to be created
INOAAE0774	Database version with compatibility level of CD database not installed or found
Explanation	A Tamino of the same compatibility level of CD database must be installed to use the CD database
Action	Install a database of the same compatibility level.
INOAAE0775	Database name contains invalid character "*" (asterisk)
Explanation	A database name cannot contain the "*" character.
Action	Remove the "*" from the database name.
INOAAE0776	This command is deprecated. Please use the new command "show users".
Explanation	This command is not supported as the user descriptions can be seen in the results of the new command.
Action	Please do not use this command and use the new one instead.
INOAAE0778	Database name contains invalid character "/" (slash)
Explanation	A database name cannot contain "/" character.
Action	Remove the "/" from database name.
INOAAE0779	Port address 'buf' is invalid. Valid range is 0 - 65535.
Explanation	The specified port address is not valid.
Action	Specify a valid port address in the range 0 to 65535.
INOAAE0784	Database name contains invalid character "<" (less than)
Explanation	A database name cannot contain the "<" character.
Action	Remove the "<" from database name.

INOAAE0785	Database name contains invalid character ">" (greater than)
Explanation	A database name cannot contain the ">" character.
Action	Remove the ">" from database name
INOAAE0786	This command is deprecated. Please use the new command "show acesofac!".
Explanation	The command is deprecated.
Action	Please use the new command.
INOAAE0787	Domain parameters missing
Explanation	Some or all of the necessary parameters for the domain creation/modification are missing.
Action	Please ensure that all necessary domain parameters are defined.
INOAAE0788	Unrecognized domain parameters
Explanation	The domain parameters defined are not valid for the domain type being created/modified.
Action	Please ensure that the correct domain parameters for the domain type being created/modified are defined.
INOAAE0792	Namespace declarations required. Please check that all namespaces are defined.
Explanation	There are some namespace prefixes for which no namespace declarations have been defined.
Action	Please ensure namespace declarations exist for all namespace prefixes.
INOAAE0794	Internal error occurred
Explanation	Internal error code 41 occurred.
Action	Please contact your software supplier.
INOAAE0797	Domain 'name' already exists
Explanation	A domain with the same name exists.
Action	Please choose another name.

INOAAE0798	Failed to open input file filename for data load
Explanation	The file cannot be opened or does not exist.
Action	Check the input and start the operation again.
INOAAE0799	Parameter 'newname' or 'new_name' missing. The 'new_name' parameter is deprecated, please use the 'newname' parameter for the new name of the database.
Explanation	No parameter with the new name of the database was given.
Action	Provide the database name using the parameter 'newname'.
INOAAE0802	Could not connect to inodmn. Port number not found in internal configuration store, probably not installed.
Explanation	The Software AG EventLayer Service is not installed correctly.
Action	Try re-installing the System Management Hub. Check for a fix or an update from your software supplier.
INOAAE0803	Could not connect to inodmn, service not running
Explanation	The "Software AG EventLayer Service" is not running, database functions and commands are probably unaffected.
Action	Restart the service. If the problem persists, contact your software supplier for an update or fix.
INOAAE0807	Invalid parameter name 'name' specified.
Explanation	The parameter name specified is not valid since it contains one or more space characters.
Action	Specify a parameter name that does not contain space characters.
INOAAE0812	Web server IP address 'ipAddress' is invalid
Explanation	The specified web server IP address is invalid.
Action	Specify a valid IP address. The valid range is 0 - 255.
INOAAE0817	No license for raw section support
Explanation	The use of raw sections requires an appropriate license option.
Action	Contact your software supplier for a license option to support raw sections.

INOAAE0818	No raw section support for the used platform
Explanation	There is no raw section support for the used platform.
Action	Do not use raw sections.
INOAAE0819	Raw section support internal error
Explanation	There was an internal error while processing a raw section.
Action	Please contact your software supplier.
INOAAE0820	Raw section initialization failed
Explanation	An error occurred while initializing a raw section.
Action	Check the raw section.
INOAAE0825	Master database must be restarted before a replication database can be set up
Explanation	A restart of the master database is necessary.
Action	Restart the master database and try to set up the replication database again.
INOAAE0826	Inconsistency detected while setting the database to replication type
Explanation	This database is not suitable to be set as the replication database of the specified master database. Perhaps the versions are not identical or this one was not created from the backup of the master. Also possible is that this database has its own updates after the creation.
Action	Use another database to replicate the master.
INOAAE0831	Only one location specified for parallel backup
Explanation	More than one location is required for parallel backup.
Action	Please specify more than one location for the parallel backup.
INOAAE0832	Renaming a replication database master is not allowed.
Explanation	Renaming a replication database master is not allowed, because the link between the master and replication databases would be lost.
Action	No action required.

INOAAE0834	Database is a replication database master database. Deleting the replication database master is not allowed. No replication databases can be updated from this master database if this database is deleted.
Explanation	Deleting this master database would mean that no replication databases could be updated from this master database. If you really want to delete this replication master database use the "force=yes" parameter for argbatch or check the "Force Delete of Replication Master Database" checkbox in the GUI.
Action	Use the "force=yes" parameter for argbatch or check the "Force Delete of Replication Master Database" checkbox in the GUI.
INOAAE0835	Data load for database dbName failed
Explanation	Load of data failed with error.
Action	Check the other related messages for more information.
INOAAE0836	Unload data from database dbName failed
Explanation	An error occurred while data was being unloaded from the database.
Action	Check for other messages related to this error for possible reasons.
INOAAE0837	Location path path is read only
Explanation	The location path specified is read only.
Action	Specify a location path with write access.
INOAAE0838	Server extension does not contain a function
Explanation	It was detected that no function has been defined for the server extension. Such a server extension is considered as invalid.
Action	Extend your server extension by at least one function.
INOAAE0841	Uninstall of server extension name aborted
Explanation	The uninstall operation for the server extension has not been completed due to functions that are used in some schema.
Action	Restart the uninstall operation with the parameter "force" set to "yes" (batch command).

INOAAE0842	Uninstall of server extension 'name' failed
Explanation	The uninstall operation failed.
Action	Check the job log to find the reason for the failure.
INOAAE0843	Please specify either parameter IP address or node
Explanation	The specification of the IP address or node is invalid.
Action	Please specify either the IP address or the node.
INOAAE0844	Unable to find the replication database name from the permission list
Explanation	The replication database name is not in the permission list.
Action	Check the parameter.
INOAAE0845	Please specify either parameter IP address or node
Explanation	Either the parameter IP address or node must be specified.
Action	Please specify either the parameter IP address or node.
INOAAE0846	Upgrade from this database to Vversion not possible
Explanation	This error occurs because the database cannot be upgraded directly to the target version.
Action	Upgrade to the next higher version and after that try a "set version" to the target version.
INOAAE0847	Named pipe path not allowed for the specified location type
Explanation	A named pipe is not allowed to set for the specified target location. Only the backup location type accepts named pipes.
Action	Specify another location for the target location.
INOAAE0849	Cannot open event log session
Explanation	Open event log session on argevsrv failed.
Action	Check that argevsrv is running.

INOAAE0850	parameter name: must be of type FileSystem or RAW Section
Explanation	Data, Index and Journal location must be of type FileSystem or RAW Section.
Action	Use a location of type FileSystem or RAW Section.
INOAAE0852	This command is deprecated. Please use the new command "inoload".
Explanation	This command is set to deprecated, use the new command instead.
Action	Use inoload to load or unload data in batch mode.
INOAAE0855	Output directory directory does not exist
Explanation	The output directory should exist.
Action	Create the output directory or check the permission if it already exists.
INOAAE0868	Stop request requestid failed :errortext
Explanation	Stop of a request failed.
Action	Check the error text for an explanation of why the operation failed.
INOAAE0870	Query current active requests failed : message
Explanation	A query of the current requests failed.
Action	Check the error message for more information.
INOAAF0002	Version 'version' of Tamino not found. Please use 'set version' command to change the version to the installed version.
Explanation	The specified Tamino version was not found.
Action	Use the "set version" command and change the version of the database.
INOAAF0007	Cannot create database: reason
Explanation	A database cannot be created with the parameters specified.
Action	Alter specified parameter value or provide missing parameter.
INOAAF0253	Error reading savepoints for database dbname
Explanation	An error occurred when reading database savepoint entries in the internal configuration store.
Action	Please contact your software supplier.

INOAAF0254	Could not create XML document
Explanation	An error occurred when creating an XML document.
Action	Reboot and restart the system.
INOAAF0256	Open of event log failed
Explanation	An error occurred when creating an event session.
Action	Check the event demon.
INOAAF0262	Error reading database locations for savepoint 'savepoint'
Explanation	No database locations were found in the internal configuration store for the savepoint.
Action	Please contact your software supplier.
INOAAF0264	Duplicate parameter name parameter
Explanation	The parameter appears more than once in the parameter list, but only a single value is allowed.
Action	Check where the parameter given is repeated and issue the command again without it.
INOAAF0265	Job initialization failed
Explanation	The job log could not be initialized because of insufficient resources. This could be memory or SMP resources like locks or threads.
Action	Free resources and retry.
INOAAF0267	Rename database failed
Explanation	The database could not be renamed.
Action	The reason why the database could not renamed is in the job log. Check it and retry.
INOAAF0369	TSM@DLL *** FATAL ERROR NO ROLLBACK POSSIBLE (SESSION LOST) ***
Explanation	Tamino reported an invalid session ID.
Action	Shut down the database and restart it.

INOAAI0000	Change License file
Explanation	Change license file.
Action	No action required.
INOAAI0003	Modify journal space of database dbname
Explanation	The size of the journal space is being modified.
Action	No action required.
INOAAI0005	Modify journal space successfully finished
Explanation	This message indicates that the "Modify journal space" function completed successfully.
Action	No action required.
INOAAI0006	Modification and reorganization of journal space in location Location from oldsize MB to one journal space of newsize MB
Explanation	The journal space size is being modified at the given location. If more the one journal space exists, the journal space is reorganized to one of the given size.
Action	No action required.
INOAAI0008	Modify properties of Email notification
Explanation	Email notification properties are being modified.
Action	No action required.
INOAAI0009	Add location name at path
Explanation	Start of the "add location" function.
Action	Information message, no action required.
INOAAI0010	Delete location name
Explanation	Start of the "delete location" function.
Action	Information message, no action required.
INOAAI0011	Moving location oldloc to newloc
Explanation	Start of the "move location" function.
Action	Information message, no action required.

INOAAI0012	Rename location name to newname
Explanation	Start of the "rename location" function.
Action	Information message, no action required.
INOAAI0013	Set location name as default database location
Explanation	Start of the "set default location" function.
Action	Information message, no action required.
INOAAI0014	Set location name as default backup database location
Explanation	Start of the "set default backup location" function.
Action	Information message, no action required.
INOAAI0015	Modify default of database location category 'category'
Explanation	Start of the "modify default of database location category" function.
Action	Information message, no action required.
INOAAI0016	Database Version set to version
Explanation	The database was set to the specified version.
Action	Information message, no action required.
INOAAI0017	Modify Email notification properties successfully finished
Explanation	Email notification properties have been modified successfully.
Action	No action required.
INOAAI0021	Unregistering database dbName
Explanation	This is a job log identification message.
Action	No action required.
INOAAI0023	New license file successfully applied.
Explanation	The license file was successfully applied.
Action	No action required.

INOAAI0025	Please log in again to the web application in order to use the new product license!
Explanation	The new functionality is available after you log in again.
Action	Log in again and restart your web applications.
INOAAI0028	Confirmed all pending alerts
Explanation	All warnings, errors and fatal errors of the job records specified have been acknowledged.
Action	No action required.
INOAAI0033	New value of dynamic property 'name' is effective now
Explanation	The property value has been updated and is active from now on.
Action	No action required.
INOAAI0035	Database has been successfully unregistered
Explanation	This message indicates, that the "Unregister Database" function is completed.
Action	No action required.
INOAAI0037	Pending alerts of all jobs have been confirmed
Explanation	All warnings, errors and fatal errors have been confirmed. The job records may be deleted now.
Action	No action required.
INOAAI0048	Server extension command execution
Explanation	This is an informational message.
Action	No action required.
INOAAI0049	Command Name : name
Explanation	This message specifies the command name of a server extension.
Action	No action required.
INOAAI0050	Collection Name : name
Explanation	This message specifies the collection name of an XML document.
Action	No action required.

INOAAI0051	Master database set to masterdb
Explanation	The database named is the master database.
Action	No action required.
INOAAI0063	Tamino will close the current log space extent and open a new one when the current log space block has been filled up
Explanation	Tamino writes log information in blocks. When the currently used block has been filled up completely, Tamino will close the current log space extent and open a new one. As a consequence, you might encounter a minimal growth of the current log space before a new one is created.
Action	No action required.
INOAAI0148	The name 'location_name' is not the name of an existing location; the default location is used instead
Explanation	An invalid location name was specified or extracted from a backup. It could be a valid location on the host where the backup was created.
Action	No action required. The location defined as default in the location management will be used.
INOAAI0152	No item selected for modification
Explanation	No item was selected to be modified.
Action	Select an item and retry.
INOAAI0160	Delete database space of database dbname
Explanation	The database space with the highest extent is being deleted. The deletion will not proceed when the space is in use.
Action	No action required.
INOAAI0161	Delete database space successfully finished
Explanation	This message indicates that the "Delete database spaces" function completed successfully.
Action	No action required.

INOAAI0163	Expand database space of database dbname
Explanation	The last database space is being expanded.
Action	No action required.
INOAAI0164	Expand database space successfully finished
Explanation	This message indicates that the "Expand database spaces" function completed successfully.
Action	No action required.
INOAAI0167	Deleting database space spaceNo from location Location
Explanation	The specified database space is being deleted from the given location.
Action	No action required.
INOAAI0168	Expanding database space spaceNo in location Location from oldsize MB to newsize MB
Explanation	The specified database space is being expanded at the given location.
Action	No action required.
INOAAI0176	Restoring of database dbName without further recovery successfully completed
Explanation	The specified database has been restored successfully. Changes that occurred later than the backup time were not reapplied.
Action	No action required.
INOAAI0211	Data load in collection collectionname
Explanation	Data has been loaded into the named collection.
Action	No action required.
INOAAI0227	Data unload from collection collectionname
Explanation	Data will be unloaded into the named collection.
Action	No action required.

INOAAI0237	mvcount spaces successfully moved from oldloc to newloc
Explanation	The specified number of spaces were moved from one location to another one.
Action	Information message, no action required.
INOAAI0248	Document path : path
Explanation	This message specifies the path name of an XML document.
Action	No action required.
INOAAI0249	Query string : text
Explanation	This message specifies the query string to retrieve XML documents.
Action	No action required.
INOAAI0250	Schema name : name
Explanation	This message specifies the schema name of a XML Document.
Action	No action required.
INOAAI0269	Execution of command 'name' successful
Explanation	A server extension command was successfully executed.
Action	No action required.
INOAAI0273	Location locCount : locName
Explanation	This is an informational message for one default database location of the category.
Action	Information message, no action required.
INOAAI0275	No pending alerts found
Explanation	An attempt was made to confirm all pending alerts, but no job with pending alerts was found. Either there are no alerts in the display, or the alerts in the display have been confirmed meanwhile by someone else.
Action	No action required.
INOAAI0276	When all pending alerts are confirmed, the "Pending Alerts" folder is cleared. Each individual job is still in the "Running Jobs" or in the "Completed Jobs" folder until it is deleted by automatic cleanup; up to that point, the warning, error and alert messages are still visible in the single job view.
Explanation	No job or message is really removed when alerts are confirmed; they are just moved away from the Alerts folder.
Action	No action required

INOAAI0277	When a job record is deleted, it is removed from the job log and its disk file is deleted. Jobs that are not completed (i.e. stopped or still running) and jobs that have unconfirmed alert messages are not deleted and remain in their respective folders.
Explanation	Only finished jobs with no pending alerts are deleted.
Action	No action required
INOAAI0280	Object Identification : text
Explanation	The given text provides the object identification of the server extension.
Action	No action required.
INOAAI0286	Execution type: type
Explanation	The specified type is the selected server extension execution type.
Action	No action required.
INOAAI0288	Backing up all server extensions for database 'name'
Explanation	All server extensions in the specified database are being backed up.
Action	No action required.
INOAAI0289	Backup of all server extensions successful
Explanation	All server extensions have been backed up successfully.
Action	No action required.
INOAAI0290	Restoring server extension for database 'name'
Explanation	A server extension of the specified database is being restored.
Action	No action required.
INOAAI0291	Restore of server extension 'name' successful
Explanation	The specified server extension has been restored successfully.
Action	No action required.

INOAAI0292	Restoring all server extensions for database 'name'
Explanation	All server extensions of the specified database are being restored.
Action	No action required.
INOAAI0293	Restore of all server extensions successful
Explanation	All server extensions have been restored successfully.
Action	No action required.
INOAAI0299	Storing binary file 'path'
Explanation	A binary file is being stored in the database.
Action	No action required.
INOAAI0300	Restoring binary file 'path'
Explanation	A binary file is being restored from the database.
Action	No action required.
INOAAI0301	Removing binary file 'path'
Explanation	A binary file is being removed from the database.
Action	No action required.
INOAAI0303	Command log switched mode buffers buffers
Explanation	This is a result message for a batch command.
Action	No action required.
INOAAI0308	Update of settings successful : name
Explanation	The update of the given settings parameter value was successful.
Action	No action necessary.
INOAAI0316	Backing up server extension for database 'name'
Explanation	A server extension in the specified database is being backed up.
Action	No action required.

INOAAI0317	Backup of server extension 'name' successful
Explanation	The specified server extension has been backed up successfully.
Action	No action required.
INOAAI0318	Deleting document : name
Explanation	The XML document will be deleted.
Action	No action necessary.
INOAAI0319	No mapped document : name
Explanation	No XML document is mapped to the server extension.
Action	No action necessary.
INOAAI0320	Trace server extensions in database 'name'
Explanation	The server extension trace mode is changed in the specified database.
Action	No action required.
INOAAI0321	Trace switched on successfully
Explanation	The server extension trace is switched on.
Action	No action required.
INOAAI0322	Trace switched off successfully
Explanation	The server extension trace is switched off.
Action	No action required.
INOAAI0323	Store server extensions in database 'name'
Explanation	The storing of server extension files is changed to the specified database.
Action	No action required.
INOAAI0324	Store server extension files switched on successfully
Explanation	The storing of server extension files is switched on.
Action	No action required.

INOAAI0325	Store server extension files switched off successfully
Explanation	The storing of server extension files is switched off.
Action	No action required.
INOAAI0326	Analyze object for a new server extension
Explanation	The object for a new server extension will be analyzed.
Action	No action required.
INOAAI0327	Object File : path
Explanation	This specifies the object file for the new server extension.
Action	No action required.
INOAAI0328	Analysis of new server extension object successful
Explanation	The analysis of the object for the new server extension was successful.
Action	No action required.
INOAAI0329	Remove server extension object
Explanation	The object of a new server extension will be removed.
Action	No action required.
INOAAI0330	Select function for a new server extension
Explanation	The function for a new server extension will be selected.
Action	No action required.
INOAAI0331	Select function for a new server extension successful
Explanation	The function for a new server extension was successfully selected.
Action	No action required.
INOAAI0332	Display trace state successful
Explanation	The server extension trace state is displayed successfully.
Action	No action required.

INOAAI0333	Create Database from Backup
Explanation	Button Create Database from Backup
Action	none
INOAAI0357	Access Control List 'name' created
Explanation	A new access control list has been created. Details are generally provided in other messages.
Action	No action required.
INOAAI0358	User group 'name' created
Explanation	A new user group has been created.
Action	No action required.
INOAAI0360	User 'name' created
Explanation	A new user has been created. Details are generally provided in other messages.
Action	No action required.
INOAAI0364	Access control list 'name' modified
Explanation	The current ACL has been modified.
Action	No action required.
INOAAI0365	User group 'name' modified
Explanation	The user group has been modified.
Action	No action required.
INOAAI0366	User 'name' modified
Explanation	The user has been modified.
Action	No action required.
INOAAI0368	Access control element 'name' added to the access control list
Explanation	An ACE has been added successfully to an ACL.
Action	No action required.

INOAAI0374	Access control list 'name' deleted
Explanation	The access control list has been deleted.
Action	No action required.
INOAAI0375	User 'name' deleted
Explanation	The user has been deleted.
Action	No action required.
INOAAI0376	User group 'name' deleted
Explanation	The user group has been deleted.
Action	No action required.
INOAAI0406	Shutdown of all active databases completed
Explanation	All active databases are about to shut down, or they are already inactive.
Action	No action required.
INOAAI0407	All autostart databases checked
Explanation	All databases with autostart parameter set have been started.
Action	No action required.
INOAAI0410	op of operation done
Explanation	This message provides information about operation progress.
Action	No action required
INOAAI0424	New value : text
Explanation	This describes a new value for a Java public or private classpath.
Action	No action required.
INOAAI0425	Starting autostart databases of version version
Explanation	Databases with the autostart parameter set to 'yes' are being started.
Action	No action required.

INOAAI0426	Stopping all active databases of version version
Explanation	Active databases are being stopped
Action	No action required.
INOAAI0429	Confirming all alerts
Explanation	Fatal error, error and warning messages are being confirmed. Once all alerts are confirmed, a job will be scheduled for cleanup (will be removed later), or it can be delete explicitly as a single job or along with all completed jobs.
Action	No action required.
INOAAI0431	Deleting all completed jobs
Explanation	All jobs without unconfirmed alerts are being deleted.
Action	No action required.
INOAAI0432	All job records of completed jobs successfully deleted by user (except jobs with pending alerts)
Explanation	Deleted job records will not appear in the job monitor list any more; the corresponding files have been deleted on disk.
Action	No action required.
INOAAI0445	Setting version for database 'dbName'
Explanation	Set the version of a specific database.
Action	Data must be unloaded and loaded into a new database manually.
INOAAI0446	No property has been modified. All properties already set to the given values.
Explanation	A property will be changed when the new property value is different from the value stored in the internal configuration store.
Action	No action required.
INOAAI0448	'param' has been changed from 'oldValue' to 'newValue'
Explanation	A database property was changed successfully by the "modify property" command.
Action	No action required.

INOAAI0451	Adding database space for database dbName
Explanation	This message indicates the beginning of the execution of the "Add database spaces" function.
Action	No action required.
INOAAI0452	Add database space successfully finished
Explanation	This message indicates that the "Add database spaces" function completed successfully.
Action	No action required.
INOAAI0454	Moving database space for database dbName
Explanation	This message indicates the beginning of the execution of the "Move database spaces" function.
Action	No action required.
INOAAI0455	Move database space successfully finished
Explanation	This message indicates that the "Move database spaces" function completed successfully.
Action	No action required.
INOAAI0457	Creating database dbName
Explanation	This message indicates the beginning of the execution of the "Create Database" function.
Action	No action required.
INOAAI0458	Create database successfully finished
Explanation	This message indicates that the database was created successfully.
Action	No action required.
INOAAI0460	Deleting database dbName
Explanation	This message indicates the beginning of the execution of the "Delete Database" function.
Action	No action required.

INOAAI0461	Database has been successfully deleted
Explanation	This message indicates that the "Delete Database" function completed successfully.
Action	No action required.
INOAAI0465	Start of database dbName successful
Explanation	This message indicates that the specified database has been started successfully.
Action	No action required.
INOAAI0467	Stop of database dbName successful
Explanation	This message indicates that the specified database has been stopped successfully.
Action	No action required.
INOAAI0468	Backup of database dbName
Explanation	This message indicates that a backup of the specified database is being created.
Action	No action required.
INOAAI0469	Restore database dbName using backup 'bckDate' with recovery
Explanation	This message indicates the beginning of the execution of a database restore function with a database recovery based on the log spaces.
Action	No action required.
INOAAI0470	Restore database dbName using backup 'bckDate' without recovery
Explanation	This message indicates the beginning of the execution of a database restore function without a database recovery based on the log spaces.
Action	No action required.
INOAAI0471	Backup of database dbName successfully completed
Explanation	This message indicates that the specified database has been backed up successfully.
Action	No action required.
INOAAI0476	Restoring and recovering of database dbName successfully completed
Explanation	The specified database has been restored and recovered successfully.
Action	No action required.

INOAAI0477	Moving database space spaceNo from location oldLoc to newLoc
Explanation	A database space is being moved from one location to another.
Action	No action required.
INOAAI0479	Adding size MB database space to location newLoc
Explanation	The specified database space is being added to the given location.
Action	No action required.
INOAAI0484	Uninstalling all server extensions in database 'name'
Explanation	All server extensions in a database are being uninstalled from the specified database and the file system. If a restore is being performed the server extensions will be recovered from the backup database.
Action	No action required.
INOAAI0490	Modify database properties successfully finished
Explanation	Database properties have been modified successfully.
Action	No action required.
INOAAI0492	Modify properties for database dbName
Explanation	Database properties are being modified.
Action	No action required.
INOAAI0493	Restore database dbName using backup 'bckDate' with partial recovery
Explanation	A database restore function with partial recovery has been started.
Action	No action required.
INOAAI0494	Checking and repairing database dbName
Explanation	A function to check and repair the database has been started.
Action	No action required.
INOAAI0495	Check and repair of database dbName finished successfully
Explanation	The check and repair function was successfully applied to the specified database, i.e. the recreation of the indices was successful.
Action	No action required.

INOAAI0497	help
Explanation	This is a standard information message to show the server version in space and property commands.
Action	No action required.
INOAAI0501	Uninstall of all server extensions successful
Explanation	All server extensions in a database have been uninstalled successfully. This is an informational message.
Action	No action required.
INOAAI0502	Registering Java class 'path'
Explanation	The installation count for the Java class is added to the internal configuration. This is an informational message.
Action	No action required.
INOAAI0505	Function name: 'name'
Explanation	This is the name of a server extension function. This is an informational message.
Action	No action required.
INOAAI0506	External name: 'name'
Explanation	This is the external name of a server extension function. This is an informational message.
Action	No action required.
INOAAI0511	Parameter 'para' not valid
Explanation	The specified parameter is not valid for the current command.
Action	Check the spelling of the parameter. If the spelling is correct, check whether the parameter is valid in the current context.
INOAAI0514	message
Explanation	This is an informational message about a server extension document that has been returned from the Tamino server.
Action	No action required.

INOAAI0515	Listing server extensions in database 'name'
Explanation	A list of all installed server extensions for the specified database is being generated.
Action	No action required.
INOAAI0516	Installing server extension in database 'name'
Explanation	A new server extension is being installed in the specified database.
Action	No action required.
INOAAI0517	Package file: path
Explanation	The specified path is the pathname of the packed server extension file.
Action	No action required.
INOAAI0518	Execution mode: mode
Explanation	The specified mode is the selected server extension execution mode.
Action	No action required.
INOAAI0519	Installation of server extension 'name' successful
Explanation	The specified server extension was installed successfully.
Action	No action required.
INOAAI0520	Uninstalling server extension from database 'name'
Explanation	A server extension is being uninstalled from the specified database.
Action	No action required.
INOAAI0521	Server extension name: 'name'
Explanation	This message specifies the name of a server extension.
Action	No action required.
INOAAI0522	Uninstall of server extension 'name' successful
Explanation	The specified server extension has been uninstalled successfully.
Action	No action required.

INOAAI0523	Modifying server extension in database 'name'
Explanation	A server extension in the specified database is being modified.
Action	No action required.
INOAAI0524	Modification of server extension 'name' successful
Explanation	The specified server extension has been modified successfully.
Action	No action required.
INOAAI0525	Deleting help URL 'path'
Explanation	The specified help file for a server extension is being deleted.
Action	No action required.
INOAAI0526	Executing command 'call'
Explanation	The specified operating system command is being executed.
Action	No action required.
INOAAI0527	De-registering server extension DLL 'path'
Explanation	The specified server extension DLL file is being de-registered.
Action	No action required.
INOAAI0528	Deleting server extension DLL 'path'
Explanation	The specified server extension DLL file is being deleted.
Action	No action required.
INOAAI0529	Deselect function of a new server extension
Explanation	A selected function for a new server extension is being deselected. This is an informational message.
Action	No action required.
INOAAI0530	Extracting entry 'name'
Explanation	An entry is being extracted from a packed file.
Action	No action required.

INOAAI0531	Inserting document 'path'
Explanation	The URL of a help file for a server extension is being inserted into the server extension's installation document.
Action	No action required.
INOAAI0532	Registering DLL 'path'
Explanation	A server extension DLL file is being registered.
Action	No action required.
INOAAI0533	DLL 'path' already registered
Explanation	The specified server extension DLL file is already registered.
Action	No action required.
INOAAI0535	Deleting file 'name'
Explanation	The specified server extension installation file is being deleted.
Action	No action required.
INOAAI0536	Deleting directory 'path'
Explanation	The specified server extension installation directory is being deleted.
Action	No action required.
INOAAI0537	Showing server extension attributes in database 'name'
Explanation	The attributes of a server extension in the specified database are being listed.
Action	No action required.
INOAAI0538	Setting access rights for server extension in database 'name'
Explanation	The access rights of a server extension are being set in the specified database.
Action	No action required.
INOAAI0543	Stopping database dbName in normal mode
Explanation	This message indicates that the specified database is being stopped in normal mode.
Action	No action required.

INOAAI0544	Stopping database dbName in abort mode
Explanation	This message indicates that the specified database is being stopped in abort mode.
Action	No action required.
INOAAI0545	Stopping database dbName in rollback mode
Explanation	This message indicates that the specified database is being stopped in rollback mode.
Action	No action required.
INOAAI0568	Unexpected messages received
Explanation	This message is the header for subsequent messages.
Action	No action required.
INOAAI0569	Edit details for a new server extension
Explanation	Details for a new server extension will be edited.
Action	No action required.
INOAAI0570	Description: text
Explanation	This is a short description of the new server extension.
Action	No action required.
INOAAI0571	Author name: name
Explanation	This is the name of the new server extension author.
Action	No action required.
INOAAI0572	Help file: name
Explanation	This is the name of a help file for the new server extension.
Action	No action required.
INOAAI0573	Editing of new server extension details successful
Explanation	The editing of the new server extension details was successful.
Action	No action required.

INOAAI0574	Starting database dbName
Explanation	A Tamino database is being started.
Action	No action required.
INOAAI0577	Unloading document 'path'
Explanation	The server extension object information document is being unloaded.
Action	No action required.
INOAAI0578	Edit details for a new server extension function
Explanation	Details for a new server extension function will be edited.
Action	No action required.
INOAAI0579	Function type: text
Explanation	This message displays the type of a server extension function.
Action	No action required.
INOAAI0580	Editing of new server extension function details successful
Explanation	The editing of the new server extension function details was successful.
Action	No action required.
INOAAI0581	Loading document 'path'
Explanation	A server extension analyzer document is being loaded.
Action	No action required.
INOAAI0582	Start Database
Explanation	This is a command for the Tamino agent dbagent.
Action	No action required.
INOAAI0583	Stop Database
Explanation	This is a command for the Tamino agent dbagent.
Action	No action required.

INOAAI0584	Delete Database
Explanation	This is a command for the Tamino agent dbagent.
Action	No action required.
INOAAI0587	Check and Repair
Explanation	This is a command for the Tamino agent dbagent.
Action	No action required.
INOAAI0589	Information
Explanation	This is a command for the Tamino agent dbagent.
Action	No action required.
INOAAI0591	Database Spaces
Explanation	This is a command for the Tamino agent dbagent.
Action	No action required.
INOAAI0592	Properties
Explanation	This is a command for the Tamino agent dbagent.
Action	No action required.
INOAAI0598	Register CD Database
Explanation	This is a command button for the Tamino agent dblist.
Action	No action required.
INOAAI0599	Prepare for CD
Explanation	This is a command for the Tamino agent dblist.
Action	No action required.
INOAAI0600	Unregister CD Database
Explanation	This is a command button for the Tamino agent dbagent.
Action	No action required.

INOAAI0601	Create a new server extension package
Explanation	This is an informational message.
Action	No action required.
INOAAI0602	Package path: path
Explanation	This is the pathname of the server extension package.
Action	No action required.
INOAAI0603	Creation of package 'name' successful
Explanation	A server extension package was created successfully.
Action	No action required.
INOAAI0604	Port range successfully changed
Explanation	The port range was successfully changed.
Action	none
INOAAI0607	inodmp return erg
Explanation	This message shows a return value of inodmp.
Action	No action required.
INOAAI0612	Deselection of function 'name' successful
Explanation	The server extension function was successfully deselected.
Action	No action required.
INOAAI0613	Modify parameter of server extension function
Explanation	The parameter name and XML type of a selected server extension function will be modified.
Action	Insert the corresponding values.
INOAAI0614	Parameter name: name
Explanation	This specifies the name of the parameter being modified.
Action	No action required.

INOAAI0615	Modified name: name
Explanation	This specifies the modified name of the parameter.
Action	No action required.
INOAAI0616	XML type: type
Explanation	This specifies the modified XML type of the parameter.
Action	No action required.
INOAAI0617	Modification of parameter 'name' successful
Explanation	A server extension function parameter was successfully modified.
Action	No action required.
INOAAI0618	Preparation of CD database successful
Explanation	This is an informational message.
Action	No action required.
INOAAI0625	Renaming database dbname to newdbname
Explanation	The database is being renamed.
Action	No action required.
INOAAI0626	Database successfully renamed
Explanation	The database was renamed successfully.
Action	No action required.
INOAAI0627	Server extension class 'name'
Explanation	This message specifies the Java class name of a server extension.
Action	No action required.
INOAAI0629	database successfully registered
Explanation	A database has been successfully registered.
Action	No action required.

INOAAI0630	Registering CD database dbname
Explanation	The CD database is being registered.
Action	No action required.
INOAAI0631	Location name at path successfully added
Explanation	The location was successfully added.
Action	No action required.
INOAAI0632	Location name successfully deleted
Explanation	The location was successfully deleted.
Action	No action required.
INOAAI0633	Location name successfully renamed to newname
Explanation	The location was successfully renamed.
Action	No action required.
INOAAI0634	Location name successfully set as default database location
Explanation	The location was successfully set as the default database location.
Action	No action required.
INOAAI0635	Location name successfully set as default backup database location
Explanation	The location was successfully set as the default backup location.
Action	No action required.
INOAAI0636	Default of database location category 'category' successfully modified
Explanation	The default database location category was successfully modified.
Action	No action required.
INOAAI0642	Stopping XML session
Explanation	The XML session is being stopped.
Action	No action required.

INOAAI0649	Setting global parameters for external backup method 'method' of database dbname
Explanation	Global parameters for external backup method are being set.
Action	No action required, information message.
INOAAI0650	Global parameters for external backup method 'method' of database dbname successfully set
Explanation	The global parameters were successfully set.
Action	No action required, information message.
INOAAI0652	Setting configuration parameters for external backup method 'method' of database dbname
Explanation	The configuration parameters for the external backup method are being set.
Action	No action required, information message.
INOAAI0654	Configuration parameters for external backup method 'method' of database dbname successfully set
Explanation	The configuration parameters were successfully set.
Action	No action required, information message.
INOAAI0655	Deleting configuration 'configuration' of method 'method' of database dbname
Explanation	The "delete configuration" function was started.
Action	No action required, information message.
INOAAI0657	Configuration 'configuration' of method 'method' of database dbname successfully deleted
Explanation	The configuration parameters were successfully deleted.
Action	No action required, information message.
INOAAI0661	Replication database name replication_db added into the permission list
Explanation	This is a status report that the replication database name has been added into the permission list.
Action	No action required.

INOAAI0663 Replication database name replication_db removed from the permission list

Explanation The replication database name has been removed from the permission list.

Action No action required, this is an information message.

INOAAI0664 Database database set to replication type

Explanation The database is set to the type "replication database".

Action No action required, this is an information message.

INOAAI0666 Replication database database has been reset to normal type

Explanation The replication database was reset so that it is a normal database.

Action No action required, this is an information message.

INOAAI0670 Private Classpath: path

Explanation The displayed path is the server extension private Java classpath.

Action No action required.

INOAAI0671 type Classpath: path

Explanation The specified operation type is performed with the server extension private Java classpath.

Action No action required.

INOAAI0673 Keep files from backup datetime

Explanation This indicates that the backup files will be saved.

Action No action required, information message.

INOAAI0674 Move backup space to "destination"

Explanation The backup space is being moved moved to new location.

Action No action required, information message.

INOAAI0682 Switching log space for database dbName

Explanation A switch of the log space is initiated.

Action No action required.

INOAAI0687	Nothing has changed: mode
Explanation	The specified server extension attribute did not change.
Action	No action required.
INOAAI0688	Attribute: mode
Explanation	This specifies a new attribute of the parameter.
Action	No action required.
INOAAI0689	Default value : text
Explanation	This specifies the default value of the parameter.
Action	No action required.
INOAAI0690	Adding backup method 'method' for database dbname
Explanation	An external backup method of the database is being added.
Action	No action required, information message.
INOAAI0692	Backup method 'method' successfully added for database dbname
Explanation	The backup method has been successfully added.
Action	No action required, information message.
INOAAI0693	Deleting method 'method' of database dbname
Explanation	An external backup method of the database is being deleted.
Action	No action required, information message.
INOAAI0695	Method 'method' of database dbname successfully deleted
Explanation	The backup method has been successfully deleted.
Action	No action required, information message.
INOAAI0697	Deleting backup 'bckDate' of database dbName
Explanation	The backup of the database is being deleted.
Action	Information message, no action required.

INOAAI0698	Deletion of backup 'bckDate' of database dbName successfully completed
Explanation	The specified database backup has been deleted successfully.
Action	Information message, no action required.
INOAAI0701	Remove permitted replication database name replicationdb from master database masterdb
Explanation	This is a title for the messages for removing a database name from the permission list.
Action	No action required.
INOAAI0702	Add permitted replication database name
Explanation	This is a title for adding database name into the permission list.
Action	No action required.
INOAAI0704	Set type to normal database
Explanation	This is a title for setting the database type to a normal one.
Action	No action required.
INOAAI0705	Create replication database list
Explanation	This is a title for create replication database list.
Action	No action required.
INOAAI0706	Retrieve replication database information
Explanation	This is a title for retrieving the information of databases.
Action	No action required.
INOAAI0711	Domain 'name' created
Explanation	The domain has been created.
Action	No action required.
INOAAI0713	Domain 'name' modified
Explanation	The domain has been modified.
Action	No action required.

INOAAI0715	Domain 'name' deleted
Explanation	The domain has been deleted.
Action	No action required.
INOAAI0718	Creating database dbName from backup dated timestamp
Explanation	A new database is created with the content of a given backup. The log spaces belonging to the backup are not recovered.
Action	No action required.
INOAAI0721	Web server assignments changed.
Explanation	The web server assignments for this database have changed.
Action	No action required.
INOAAI0722	Setting port ranges for Tamino databases
Explanation	The static and dynamic port ranges are being set.
Action	No action required.
INOAAI0726	Port ranges successfully changed
Explanation	The port ranges were successfully changed.
Action	No action required.
INOAAI0729	Renaming web server 'wbsname' to 'newwbsname'
Explanation	The web server is being renamed.
Action	No action required.
INOAAI0730	Web server successfully renamed
Explanation	The web server was successfully renamed.
Action	No action required.
INOAAI0732	Web server successfully added.
Explanation	The web server was added successfully.
Action	No action required.

INOAAI0734	Adding web server 'newwbsname'
Explanation	The web server is being added.
Action	No action required.
INOAAI0735	Deleting web server 'wbsname'
Explanation	The web server is being deleted.
Action	No action required.
INOAAI0736	Web server successfully deleted
Explanation	The web server was deleted successfully.
Action	No action required.
INOAAI0738	Modifying web server 'wbsname'. New IP address: 'ipaddress', new node: 'node', new port: 'port'.
Explanation	The web server is being modified.
Action	No action required.
INOAAI0739	Web server successfully modified
Explanation	The web server was modified successfully.
Action	No action required.
INOAAI0751	Preparing CD database dbname
Explanation	A CD database is being prepared.
Action	No action required.
INOAAI0770	Could not create database, cleaning up now
Explanation	The "Create Database" or "Create Database From Backup" command has failed. Files, internal configuration store entries and XTS entries made during this process are deleted.
Action	No action required.

INOAAI0771	Location location selected for initial backup
Explanation	The initial backup could not be created in the first backup location specified. It has been created in the location indicated in the message text instead.
Action	No action required.
INOAAI0781	The command requires an active database
Explanation	An attempt was made to execute a command that requires an active database, but the the database is inactive.
Action	The database must be started before the command can be executed.
INOAAI0782	The command requires an inactive database
Explanation	An attempt was made to execute a command but the database is active and the command requires an inactive database.
Action	The database must be stopped before the command can be executed.
INOAAI0789	Web server assignments changed. Please restart all databases which have this web server assigned to make your changes effective.
Explanation	The web server assignments for this database have changed.
Action	Please restart all databases which have this web server assigned to make your changes effective.
INOAAI0795	Set type to replication database with simultaneous query
Explanation	The flag for simultaneous query for replication is set to 'enabled'.
Action	No action required.
INOAAI0796	Set type to replication database without simultaneous query
Explanation	The flag to allow simultaneous query for replication is disabled.
Action	No action required.
INOAAI0821	Initialize raw section
Explanation	This is an event log message while the raw section is being initialized.
Action	No action required.

INOAAI0822	Raw section successfully initialized
Explanation	The raw section has been successfully initialized.
Action	No action required.
INOAAI0827	Set static min port min
Explanation	The static minimum port is being set. All Tamino database static ports must be greater than or equal to this value.
Action	No action required.
INOAAI0828	Set static max port max
Explanation	The static maximum port is being set. All Tamino database static ports must be lower than or equal to this value.
Action	No action required.
INOAAI0829	Set dynamic min port dmin
Explanation	The dynamic minimum port is being set. Tamino databases use the port range for dynamically allocated ports. This port range should not be used by any other software.
Action	No action required.
INOAAI0830	Set dynamic max port dmax
Explanation	The dynamic maximum port is being set. Tamino databases use the port range for dynamically allocated ports. This port range should not be used by any other software.
Action	No action required.
INOAAI0840	Function func is used in collection coll, schema schm, doc type doc
Explanation	The server extension to be uninstalled contains a function that is still used in the given context.
Action	Typically no action is required but be aware that in the case of a forced uninstall the corresponding functions cannot be executed any longer.
INOAAI0848	Restart parameter ignored, because only dynamic properties changed
Explanation	A restart parameter was given, but a restart is only useful if a static property is changed.
Action	No action required.

INOAAI0865	Moving database space spaceNo of database dbname from oldLoc to newLoc
Explanation	The database space of the named database is being moved from one location to another location.
Action	No action required.
INOAAI0866	Stop current request(s)
Explanation	Stop a current running request.
Action	No action required.
INOAAI0867	Request requestid successfully stopped
Explanation	A request has been successfully stopped.
Action	No action required.
INOAAI0869	No current active requests found
Explanation	No requests are running on the XML Server.
Action	No action required.
INOAAW0071	Higher server extension versions exist : name
Explanation	In other databases, higher versions of this server extension exist.
Action	Back up the server extension.
INOAAW0150	Backup spaces are copied because one or more spaces could still be part of an existing backup generation
Explanation	To protect integrity of backup generations, spaces with the Tamino backup filename extension "1B0" are always copied because they could be part of a backup generation on the local host, or another remote host.
Action	Make sure that the selected backup spaces are not used in a backup generation by a local database or elsewhere, and then change their filename extension to something different from "1B0".
INOAAW0166	Parameter 'para' unknown
Explanation	The specified database parameter name is not known by the Tamino server.
Action	Check the spelling of the parameter. If the spelling is correct, check whether the parameter is valid in the current context.

INOAAW0206 **Required spacetype size could not be obtained from the backup, using minimum sizes where not specified otherwise**

Explanation Minimum sizes will be used if not specified otherwise but the new database might refuse to start with these settings.

Action Specify the effective spaces of the saved database if creating with the minimum sizes does not succeed.

INOAAW0271 **Cannot move space of database database, because the database is online**

Explanation The database of the database space to move is in an active state.

Action Stop the database.

INOAAW0411 **Show progress aborted**

Explanation The progress information process is aborted because no more progress is determined, but operation is not finished.

Action No action required.

INOAAW0422 **An error has occurred when user user attempted to remove the records of all completed jobs without pending alerts from the joblog**

Explanation One or more job records may remain in the given job log after the attempt to delete all due records.

Action Check if the service is running. If the problem persists, job records can be deleted "physically" by deleting the files with the extensions "OG0" and "OF0" in the directory where job records are stored (try the "log" directory in the Tamino or System Management Hub root directory) and restarting the service. This however will also delete records with pending alerts and records of active commands and should only be done as a last resort.

INOAAW0433 **File 'path' not deleted**

Explanation The server extension file could not be deleted.

Action No action necessary.

INOAAW0434 **File 'path' not found**

Explanation The specified file could not be found.

Action No action necessary.

INOAAW0435	Directory 'path' not deleted
Explanation	The directory is in use. Therefore it cannot be deleted.
Action	Wait until the directory is not in use, then retry the operation.
INOAAW0436	Directory 'path' not found
Explanation	The specified directory was not found.
Action	Check the permissions of your file system.
INOAAW0440	Automatic assign of ports for the database failed, please assign the ports manually
Explanation	The database is not usable until the ports are assigned manually.
Action	Assign the ports for the database manually.
INOAAW0640	After restarting the Tamino server the server extension will be updated correctly
Explanation	The Tamino server crashed. The server extension will be usable after restart.
Action	Restart the Tamino server to use this server extension .
INOAAW0676	Please store the tape(s) from backup datetime in a safe place!
Explanation	Tapes cannot be saved, the user must store them in a safe place.
Action	Keep the backup in a safe place.
INOAAW0677	Please store the files from external backup datetime in a safe place!
Explanation	External backups cannot be saved, the user must store them in a safe place.
Action	Keep the external backup in a safe place.
INOAAW0700	Updating existing server extension 'name'
Explanation	A previous version of the server extension is already installed in the database and will be updated.
Action	No action required.
INOAAW0800	Disabling autostart for database dbName
Explanation	The parameter "autostart" of the database has been set to "false".
Action	No action required.

INOAAW0804	No property changed, property name and value is missing
Explanation	There is no property name in the command.
Action	Supply the name of the property and the new value (propertyname=value) at the end of the batch command.
INOAAW0815	Parameter 'name' is ignored for server extensions with execution type 'type'
Explanation	The parameter cannot be used for server extensions of the given execution type.
Action	No action required.
INOAAW0833	Force ignore replication database master status is set.
Explanation	Normally it is not allowed to delete a replication database master, so force ignore replication master status is set. The database will be removed.
Action	No action required.
INOAAW0839	Server extension name is used in schema
Explanation	In some node of a schema a function of the server extension name is used.
Action	See the following messages for detailed information.
INOAAW0851	No backups with user data found, please don't use option "Keep Backups"
Explanation	No backups with user data found, please don't use option "Keep Backups".
Action	Do not use the option "Keep Backups".
INOAAW0853	This command is deprecated. Please use the new command "inoload".
Explanation	This command is set to the deprecated state and will be disabled in the next version
Action	Use the new command inoload instead of this command.
INOAAW0854	COM server extension registration/deregistration suppressed
Explanation	When packaging the COM server extension, the option to suppress the registration/deregistration commands has been used.
Action	It is the installer's responsibility to make sure the COM objects are correctly registered/deregistered using the methods provided by the underlying infrastructure.

INOAAW0871	Can't connect to XTS directory server rc = xtsrc
Explanation	Can't connect to XTS directory server. This server is necessary for Tamino databases.
Action	Check the XTS directory server.
INOCVE8065	Collection collection contains non-migrated indexes
Explanation	The upgrade was rejected because there are non-migrated indexes in Tamino 4.1.4.
Action	Please migrate the indexes. Refer to the migration documentation for details.
INOCVE8067	Collection collection contains doctypes that are not namespace clean
Explanation	The upgrade was rejected because at least one doctype in the database is not namespace clean.
Action	Please perform a namespace cleanup. Refer to the migration documentation for details.
INOCVE8069	Conversion of data mapping to version version has failed with response response
Explanation	An error occurred during the conversion of data mapping for standard index and collations.
Action	Please contact your software supplier.
INOCVE8070	number TSD2 user collections exist
Explanation	TSD2 user collections exist and must be migrated to TSD3.
Action	Please use the migration tool to migrate the TSD2 user collections.
INOCVE8071	The count of existing user collections has failed with response response
Explanation	The query to count existing user collections has failed.
Action	Please contact your software supplier.
INOCVE8073	number installed COM server extensions found, conversion not allowed
Explanation	It is not possible to convert a Tamino database to this version as COM server extensions are installed.
Action	Contact your software supplier for help with switching versions.

INOCVE8074	Counting existing COM server extensions has failed with response response
Explanation	The query to count existing COM server extensions has failed.
Action	Contact your software supplier for help with switching versions.
INOCVE8075	Request to create indexes for doctype doctype in collection collection is pending
Explanation	A request to create indexes is pending.
Action	Please correct the current status using the admin-command ino:repairIndex with option CONTINUE or DROP.
INOCVE8077	The schema check for existing user collections has failed
Explanation	The test define of existing user collection during "set version" has failed.
Action	Please contact your software supplier.
INOCVE8078	The check for server extension installation has failed
Explanation	The query to check whether a server extension is installed has failed.
Action	Please contact your software supplier.
INOCVW8066	Schema "schema" in collection "collection" contains unknown attributes
Explanation	The given schema in the given collection contains unknown attributes.
Action	Remove additional attributes before next schema update.
INOCVW8076	The schema check for schema schema in collection collection has failed with response response
Explanation	The test of defining all existing user collections during "set version" has failed.
Action	Please check the schema using the following admin-command ino:CheckSchema(collection-name, schema-name). Correct the schema and update it in Tamino.
INODCE6507	Parameter structure mismatch
Explanation	A parameter structure mismatch was detected.
Action	Please check and correct the given parameters and try again.

INODCE6508	Not enough memory to create communication area
Explanation	There was not enough memory to create the communication area.
Action	Please free some memory and try again.
INODCE6509	Fatal error - unload aborted
Explanation	A fatal error was detected and the unload was aborted.
Action	Please check for other error messages to obtain the cause of the abort.
INODCE6510	Specify either the '-database' or the '-server' parameter, but do not specify both parameters together
Explanation	Please specify either the '-database' or the '-server' parameter, but do not specify both parameters together.
Action	Please do not specify both parameters together.
INODCE6511	Processing failed - cannot get server version
Explanation	The processing failed because it was not possible to get the server version.
Action	Please check that you are using a version of the data loader client which is compatible with the server.
INODCE6512	Path and/or file name too long
Explanation	The path and/or file name is too long.
Action	Please change the file name and try again.
INODCE6514	Cannot open log file 'file'
Explanation	It was not possible to open the log file.
Action	Please make sure the log file can be written and try again.
INODCE6515	Processing failed - corrupted response from server
Explanation	Processing failed because a corrupted response was received from the server.
Action	Please contact your software supplier.

INODCE6517	Server does not support mass loading of data
Explanation	The server does not support mass loading of data.
Action	No action required.
INODCE6518	Cannot retrieve information for input file 'file'
Explanation	It was not possible to retrieve information for the input file.
Action	Please make sure the input file can be read and try again.
INODCE6519	Cannot process an empty input file 'file'
Explanation	It is not possible to process the input file because it is empty.
Action	Please make sure you specify the correct input file and try again.
INODCE6520	Cannot open input file 'file'
Explanation	It was not possible to open the input file.
Action	Please make sure the input file can be read and try again.
INODCE6521	WSAStartup failed
Explanation	WSAStartup failed.
Action	Please check the network configuration.
INODCE6522	Winsock version mismatch
Explanation	A Winsock version mismatch was detected.
Action	Please check the network configuration.
INODCE6523	Not enough memory to create client host name
Explanation	There was not enough memory to create client host name.
Action	Please free some memory and try again.
INODCE6524	Invalid cursor handle delivered
Explanation	An invalid cursor handle was delivered.
Action	Please contact your software supplier.

INODCE6525	No cursor handle delivered
Explanation	No cursor handle was delivered.
Action	Please contact your software supplier.
INODCE6526	Not enough memory to create query object
Explanation	There was not enough memory to create the query object.
Action	Please free some memory and try again.
INODCE6527	Not enough memory to create query name buffer
Explanation	There was not enough memory to create the query name buffer.
Action	Please free some memory and try again.
INODCE6528	Cannot open output file 'file'
Explanation	It was not possible to open the named output file.
Action	Please make sure the output file can be written and try again.
INODCE6529	Invalid output format
Explanation	An invalid output format was detected.
Action	Please contact your software supplier.
INODCE6530	Cannot unload non-XML documents into a single file
Explanation	It is not possible to unload non-XML documents into a single file.
Action	Please make sure you specified a valid output location for non-XML documents and try again.
INODCE6531	Unload to a single file is not allowed
Explanation	An unload to a single file is not allowed.
Action	Please make sure you specified a valid output location and try again.
INODCE6532	Unload to a directory is not allowed
Explanation	An unload to a directory is not allowed.
Action	Please make sure you specified a valid output location and try again.

INODCE6534	Cannot read input file - I/O error code
Explanation	The input file could not be read due to an I/O error.
Action	Please make sure the input file can be read and try again.
INODCE6536	Not enough memory to create save area
Explanation	There was not enough memory to create the save area.
Action	Please free some memory and try again.
INODCE6538	Cannot initialize multi thread context
Explanation	It was not possible to initialize a multi thread context.
Action	Please contact your software supplier.
INODCE6539	Not enough memory to create request
Explanation	The was not enough memory to create a request.
Action	Please free some memory and try again.
INODCE6543	Not enough memory to create file offset area
Explanation	There was not enough memory to create the file offset area.
Action	Please free some memory and try again.
INODCE6544	Processing failed - no response from server
Explanation	The processing failed because there was no response from the server.
Action	Please contact your software supplier.
INODCE6545	Received empty answer from Tamino server
Explanation	An empty reply was received from the Tamino server.
Action	Please contact your software supplier.
INODCE6547	Invalid function code detected
Explanation	An invalid function code was detected.
Action	Please enter either "load", "unload" or "define" for the parameter "-function"

INODCE6548	Parameter 'parm' is only available with function code 'func'
Explanation	The given parameter is only available with the given function code.
Action	Please correct your input and try again.
INODCE6549	Argument for parameter 'arg' missing
Explanation	An argument for the given parameter is missing.
Action	Please correct your input and try again.
INODCE6550	Query filter must be enclosed in brackets: [...]
Explanation	A query filter must be enclosed in brackets: [...].
Action	Please correct your input and try again.
INODCE6551	Please specify the parameter 'parm' only once
Explanation	The given parameter was specified more than once. Please specify the parameter only once.
Action	Please correct your input and try again.
INODCE6552	Doctype is required
Explanation	A doctype is required.
Action	Please correct your input and try again.
INODCE6553	Server name is required
Explanation	The server name is required.
Action	Please correct your input and try again.
INODCE6554	Port number is required
Explanation	A port number is required.
Action	Please correct your input and try again.
INODCE6555	Parameter 'p1' not allowed in conjunction with parameter 'p2'
Explanation	The first parameter cannot be used together with the second parameter.
Action	Please correct your input and try again.

INODCE6556	Memory allocation failed during parsing
Explanation	Memory allocation failed during the parsing phase.
Action	Please free some memory and try again.
INODCE6557	Invalid hexBinary parameter detected
Explanation	An invalid hexBinary parameter was detected.
Action	Please correct your input and try again.
INODCE6558	Invalid parameter detected: 'parm'
Explanation	An invalid parameter was detected.
Action	Please correct your input and try again.
INODCE6559	Invalid argument for parameter -outputformat detected
Explanation	An invalid argument for parameter -outputformat was detected.
Action	Please enter either "singlefile" or "multifiles".
INODCE6560	Invalid argument for parameter -docname detected
Explanation	An invalid argument for parameter -docname was detected.
Action	Please enter either "no", "full", "name" or "nameext".
INODCE6561	Specify both '-sessionid' and '-sessionkey' or neither
Explanation	You must specify either both '-sessionid' and '-sessionkey' or neither.
Action	Please correct your input and try again.
INODCE6562	Mandatory parameter '-server' or '-database' missing
Explanation	The mandatory parameter '-server' or '-database' is missing.
Action	Please correct your input and try again.
INODCE6563	Mandatory parameter '-collection' missing
Explanation	The mandatory parameter '-collection' is missing.
Action	Please correct your input and try again.

INODCE6566	msg
Explanation	This is a general placeholder for a message text.
Action	See the text of the message in the job log for more details.
INODCE6567	Cannot open rejects file 'file'
Explanation	The rejects file could not be opened.
Action	Please make sure the rejects file can be opened and try again.
INODCE6568	Cannot write rejects file 'file'
Explanation	It was not possible to write to the rejects file.
Action	Please make sure the rejects file can be written and try again.
INODCE6570	Access to Tamino Server denied
Explanation	Because of security definitions access to the Tamino server is denied.
Action	Please check your security definitions and try again.
INODCE6575	Cannot write to output file - I/O error code
Explanation	The output file could not be written due to an I/O error.
Action	Please make sure the output file can be written and try again.
INODCE6578	Tamino Data Loader finished with errors
Explanation	The Tamino Data Loader has finished its processing with some error messages.
Action	Check the log output, correct errors and try again.
INODCE6579	libxni provided data buffer of bsize bytes, minimum of nsize bytes needed
Explanation	Internal error in massload utility detected.
Action	Please contact your software supplier.
INODCE6580	Memory allocation failed while loading data
Explanation	An out of memory condition occurred.
Action	Restart the command when virtual memory is available.

INODCE6581	Invalid media type specified for input file 'file'
Explanation	An invalid media type was specified. You can load only documents of media type xml to a xml doctype.
Action	Please specify a legal xml media type and try again.
INODCE6582	Error reading from input file 'file' while writing reject file
Explanation	A file read error occurred while backing up rejected data.
Action	Check the file storage or contact your software supplier.
INODCE6583	Cannot contact Tamino Server - HTTP status code code received
Explanation	Cannot contact Tamino Server - HTTP status code received.
Action	Please contact your system administrator.
INODCE6584	The operation was canceled by the user
Explanation	The operation was canceled by the user.
Action	No action required.
INODCE6585	Invalid argument for parameter -streaming detected
Explanation	An invalid argument for parameter -streaming was detected.
Action	Please enter either "on" or "off".
INODCE6590	Server does not support mass deleting of data
Explanation	The server does not support mass deleting of data.
Action	No action required.
INODCE6592	Disconnect from server failed due to a serious communication error
Explanation	Disconnect from server failed due to a serious communication error.
Action	Please check your network settings.
INODCI6500	Tamino Data Loader vvers - (c) Copyright Software AG 2002-year. All rights reserved.
Explanation	This is the Tamino Data Loader start message.
Action	No action required.

INODCI6501	Loading documents to database 'db', collection 'coll', doctype 'doctype'
Explanation	Documents are being loaded into the database.
Action	No action required.
INODCI6502	Loading documents to database on 'server:port', collection 'coll', doctype 'doctype'
Explanation	Documents are being loaded into the database.
Action	No action required.
INODCI6503	Unloading documents from database 'db', collection 'coll', doctype 'doctype'
Explanation	Documents are being unloaded from database.
Action	No action required.
INODCI6504	Unloading documents from database on 'server:port', collection 'coll', doctype 'doctype'
Explanation	Documents are being unloaded from the database.
Action	No action required.
INODCI6505	Defining schemas to database 'db'
Explanation	Schemas are being defined in the database.
Action	No action required.
INODCI6506	Defining schemas to database on 'server:port'
Explanation	Schemas are being defined in the database.
Action	No action required.
INODCI6513	Unloading file 'file'
Explanation	The given file is being unloaded.
Action	No action required.
INODCI6516	Loading file 'file'
Explanation	The given file is being loaded.
Action	No action required.

INODCI6533	No matching documents found
Explanation	The query you specified returned no results.
Action	Please specify another query and try again.
INODCI6535	start MB of end MB loaded
Explanation	This shows the progress information.
Action	No action required.
INODCI6537	Loading document id
Explanation	The given document is being loaded.
Action	No action required.
INODCI6540	Unloading documents start to end
Explanation	The documents in the range from "start" to "end" are being unloaded.
Action	No action required.
INODCI6541	Data unloading completed, number of documents processed: num
Explanation	The unload of the data has completed.
Action	No action required.
INODCI6542	Committing loaded documents - this may take a while
Explanation	The loaded documents are being committed. This activity can last a while.
Action	No action required.
INODCI6546	Elapsed time: elapse second(s), data processed: amount
Explanation	The elapsed time and the amount of data processed are shown here.
Action	No action required.
INODCI6564	msg
Explanation	This is a general placeholder for a message text.
Action	See the text of the message in the job log for more details.

INODCI6565	Data loading completed, number of documents processed docsproc, loaded docsload, rejected docsrejected
Explanation	The data processing has completed with the given number of loaded and rejected documents.
Action	No action required.
INODCI6569	Process id: id
Explanation	The process has the given ID.
Action	No action required.
INODCI6571	Unloading schemas from database 'db', collection 'coll'
Explanation	Schemas are being unloaded from the database.
Action	No action required.
INODCI6572	Unloading schemas from database on 'server:port', collection 'coll'
Explanation	Schemas are being unloaded from the given collection of the database on the given server and port.
Action	No action required.
INODCI6573	Unloading schemas start to end
Explanation	Schemas in the range from "start" to "end" are being unloaded.
Action	No action required.
INODCI6574	Data unloading completed, number of schema files written: num
Explanation	The unloading of data has completed.
Action	No action required.
INODCI6576	Tamino Data Loader successfully finished
Explanation	The Tamino Data Loader has successfully completed its processing.
Action	No action required.

INODCI6586	Undefining schemas from database 'db'
Explanation	Schemas are being undefined from the database.
Action	No action required.
INODCI6587	Undefining schemas from database on 'server:port'
Explanation	Schemas are being undefined from the database.
Action	No action required.
INODCI6588	Deleting documents from database 'db', collection 'coll', doctype 'doctype'
Explanation	Documents are being deleted from database.
Action	No action required.
INODCI6589	Deleting documents from database on 'server:port', collection 'coll', doctype 'doctype'
Explanation	Documents are being deleted from the database.
Action	No action required.
INODCI6591	Data deleting completed, docsdel documents deleted
Explanation	The data deleting has completed with the given number of deleted documents.
Action	No action required.
INODCW6577	Tamino Data Loader finished with warnings
Explanation	The Tamino Data Loader has finished its processing with some warning messages.
Action	Check the log output, correct errors and try again.
INODSA1000	Starting autorepair after abnormal termination
Explanation	The last server session of the database was terminated abnormally. Before the database can be used, the data consistency will be re-established, changes which had not been written to disk will be redone, and transactions which were open at the time of the abnormal server session termination will be reset.
Action	Wait for the end of the autorepair processing before using your database.

INODSA1001	Start writing crash dump of database, writing to file filename
Explanation	The server has encountered an error situation which causes a crash. In order to enable error analysis, the server writes status information to a file in the reserved location.
Action	Report the crash to your software supplier, together with the dump files in the reserved location.
INODSA1002	name modifierversionmodifier2 on system info
Explanation	This is a generic message that is used for identification of an activity.
Action	No action required.
INODSA1003	Starting recovery
Explanation	The database recovery processing is starting. After restoring a database, the recovery processing re-applies all updates that were done since the database backup was created.
Action	Wait for the end of the recovery processing before using your database.
INODSA1006	Skipping database recovery during restore
Explanation	The database restore is being performed without recovery processing. Log space information will be marked as skipped.
Action	Wait for the end of the recovery skipping before using your database.
INODSA1007	Starting recovery until time
Explanation	The database recovery processing is starting. After restoring a database, the recovery processing re-applies all updates that were done between the database backup creation and the specified time.
Action	Wait for the end of the recovery processing before using your database.
INODSA2278	Tamino name modifierversionmodifier2 on system info
Explanation	This is a generic message that is used for identification of an activity.
Action	No action required.
INODSE1015	Expanding the database has failed, because the licensed database size would have been exceeded
Explanation	The allowed database size is limited by the amount allowed in your license file. The attempted expansion of the database would have exceeded the allowed size.
Action	Please contact your software supplier for an enhanced license which allows a larger database size.

INODSE1025	Source and destination of the copy operation specify the same object (source)
Explanation	Source and destination of a copy operation must not specify the same object.
Action	Please specify another source or destination for the copy operation.
INODSE1026	Copy operation (src to dest) incomplete, copied done of expect bytes
Explanation	The copy operation was incomplete due to a system error.
Action	Please consult your manufacturer's manual.
INODSE1027	System error errno during operation call on file file
Explanation	There was an operating system error while performing the specified operation on the specified file.
Action	Please consult your manufacturer's manual.
INODSE1028	pathname does not specify a valid raw section (returned type error)
Explanation	The given path does not specify a valid raw section.
Action	Specify a valid raw section.
INODSE1029	Size of raw section section was computed as 0
Explanation	The size of the given raw section could not be determined.
Action	Please contact your software supplier.
INODSE1030	Raw section section is not empty and must not be reset
Explanation	The specified raw section is not empty and must not be reset.
Action	Specify another raw section or deallocate all entries from the specified one.
INODSE1031	database space space number of database server in raw section section is in use and must not be changed
Explanation	The specified container is still in use and must not be changed.
Action	Ensure that the container is not in use before trying to change it.
INODSE1032	Incremental backup cannot be used for database creation
Explanation	The backup file selected is an incremental one, but databases can only be created from full backups.
Action	Use a full backup for database creation.

INODSE1036	database space space number of database server in raw section section is in use and must not be deallocated
Explanation	The specified database space is currently in use and must not be deallocated.
Action	No action required.
INODSE1037	database space space number of database server in raw section section is in use and must not be reallocated
Explanation	The specified database space is in use and must not be reallocated.
Action	No action required.
INODSE1042	Incremental backup is not enabled
Explanation	Incremental backup cannot be issued because the feature is not enabled.
Action	Switch on the server parameter for enabling incremental backup.
INODSE1043	Incremental backup is not possible
Explanation	Incremental backup is not possible because there is no valid associated full or incremental backup present, or for some reason the server has deactivated the incremental block collection.
Action	Perform a full backup to resolve this situation.
INODSE1045	Incremental Backup is disabled at the database to be restored
Explanation	The database is not prepared to receive the given incremental backup.
Action	Check the database. Possibly you must restore a full backup first.
INODSE1046	Backup file has invalid or missing incremental backup data
Explanation	The backup file to be restored incrementally has no incremental backup data, or the backup data is corrupted.
Action	Please contact your software supplier.
INODSE1048	Backup numbers do not fit together: database dbnr, backup bcknr
Explanation	The incremental backup file and the database to receive the backup file no not fit together according the backup numbers. The backup number of the backup file must be one higher than the current backup number of the database
Action	Check all your backup files and their numbers.

INODSE1051	Structure level mismatch on log space from session session number
Explanation	The log space was generated by a previous Tamino version.
Action	Use the previous Tamino version for restore/recovery and then switch again to the current version.
INODSE1052	Internal error occurred: error string, location location
Explanation	An internal error has occurred. The database can still be used.
Action	Please contact your software supplier and provide the message text.
INODSE1055	Preparing for an emergency restart
Explanation	The server has terminated due to shortage of journal space. This has caused a situation in which the autorestart processing that will run automatically at the start of the next server session cannot be guaranteed to resolve internal data inconsistencies from the current terminated session. Therefore, the next server session will start with an emergency restart.
Action	Restart the server. If the emergency restart completes without error, the database is in a consistent state and can be used normally. If the emergency start fails, you must recover your data using the latest backup.
INODSE1056	During database restart, an error has occurred in an index on doctype doctype (ID). All indexes on this doctype have been dropped.
Explanation	There was an error in an operation on an index during the database restart processing. All indexes on the affected doctype have been dropped, but the doctype still is available.
Action	After the restart has finished, recreate all indexes by choosing the "Check and Repair" function for the database in the Tamino Manager.
INODSE1057	During database restart, an error has occurred on doctype doctype (ID). The doctype is no longer accessible.
Explanation	There was an error in an operation on the doctype during the database restart processing. The doctype has been destroyed.
Action	After the restart has finished, restore the doctype.
INODSE1058	Incremental Backup does not fit to latest database restore (different database backup ID)
Explanation	The incremental backup to be restored into the database cannot be performed because there the associated full database restore was a different one.
Action	Check whether incremental backup file and its restored master full backup fit together.

INODSE1060	Invalid internal database key found
Explanation	The database's internal database key is corrupt.
Action	Please contact your software supplier.
INODSE1061	No space left in raw section pathname for database space space number of database server
Explanation	The specified raw section does not contain enough contiguous space to allocate the specified database space.
Action	Specify another raw section for this database space or free space in the given raw section.
INODSE1063	database space space number of database server already present in raw section section
Explanation	The required database space is already present.
Action	Remove the database space from the specified raw section.
INODSE1066	Associated full backup not found for incremental backup savepoint
Explanation	A full backup as a base of a selected incremental backup was not found.
Action	There is possibly a corruption of the internal configuration store.
INODSE1068	The raw section section overlaps with a mounted file system
Explanation	Raw sections must not overlap with file systems since this can result in data corruption.
Action	Define the raw section so that it does not overlap with a mounted file system.
INODSE1069	Error accessing the mount table
Explanation	The operating system's mount table could not be processed.
Action	Please contact your software supplier.
INODSE1070	Decreasing the size of the raw section section failed
Explanation	An attempt to decrease the size of the specified raw section failed because the required new size is too small. Only free space at the end of a raw section can be removed.
Action	Specify a raw section partition with a larger size.

INODSE1071	Raw section section is already initialized
Explanation	An attempt was made to initialize a raw section that is already initialized. A raw section can be initialized only once.
Action	No action required.
INODSE1072	No space for database space space number of database server at specified position in raw section pathname
Explanation	At the specified position in the raw section there is not enough contiguous space to allocate the specified database space.
Action	Specify another raw section or another position.
INODSE1073	Overflow on raw section section
Explanation	The raw section contains too many database spaces in the management area.
Action	Choose another raw section or remove obsolete database spaces.
INODSE1074	Error allocating database space space number of database server on raw section section
Explanation	An error occurred while trying to allocate space on the specified raw section.
Action	Please contact your software supplier.
INODSE1076	System error errno during operation call on raw section section
Explanation	There was an operating system error while performing the specified operation on the specified raw section.
Action	Please consult the manufacturer's manual.
INODSE1077	Raw section section is corrupted or not initialized
Explanation	The data on the specified raw section is corrupted.
Action	Please contact your software supplier if the section had been initialized.
INODSE1079	path is a block device and cannot be used for raw sections
Explanation	An attempt was made to define a raw device on a block device. Raw sections must not be block devices.
Action	No action required.

INODSE1080	I/O error on block no in database space space no (operating system error errno)
Explanation	There has been an I/O error during an operation (initialization of a database space). This does not, however, lead to a loss of data.
Action	Check the affected device: is it on-line, are the permissions correct, can operating system tools access the device? If you cannot find the reason for the read error by yourself, please contact your software supplier.
INODSE1081	Journal space must be writable
Explanation	The system could not write the specified database space.
Action	Check the attributes (e.g. permissions) of the database space.
INODSE1082	Error when opening database space space number (at path)
Explanation	The database space could not be opened.
Action	Check the affected device: is it on-line, are the permissions correct, can operating system tools access the device? If you cannot find the reason for the read error by yourself, please contact your software supplier.
INODSE1083	System error errno when opening database space space no (path)
Explanation	The specified operating system error has occurred.
Action	Please consult the manufacturer's manual.
INODSE1084	Invalid block size block size
Explanation	The given block size is not allowed.
Action	Provide a valid block size.
INODSE1085	No space for source left on path
Explanation	There is not enough space on the device.
Action	Specify another device or free some space.
INODSE1086	Tape handling error: blocking factor not supported
Explanation	The specified tape device cannot be written because the blocking factor is not supported.
Action	Change the blocking factor of the tape device. It must be either variable or a multiple of 1024.

INODSE1087	Data error on source
Explanation	The file structure of the specified file does not match the expectations of the system.
Action	Check the file's content and the defined structure.
INODSE1088	A further extent of source cannot be created (reason reason, error err, errtxt)
Explanation	During any given server session, there is a limit on how much the database can grow. This limit has been reached in the current server session.
Action	Stop the current server session and restart the database. In the new server session, the database can be extended.
INODSE1090	Inconsistency detected when checking backup for timestamp savepoint
Explanation	A series of incremental backups cannot be restored completely.
Action	Check if all incremental backups exist. If no backup is missing, please contact your software supplier.
INODSE1091	Incremental Backup does not fit to latest database restore (database modified meanwhile)
Explanation	The incremental backup to be restored into the database cannot be performed because there were some updates to the database in the meantime.
Action	Check if the database has been started between the restore of all involved backups and if there were any updates.
INODSE1092	Incremental Backup does not fit to latest database restore (different backup sequence)
Explanation	The incremental backup to be restored into the database cannot be performed because the latest incremental or full backup restored and the given incremental backup are not in the expected chain.
Action	Check if the incremental backup file and the most recently restored backup file really fit together.
INODSE1093	Options "parallel" and "incremental" are mutually exclusive
Explanation	An incremental parallel backup is not supported.
Action	Select only one of the options.

INODSE1094	Tape device required
Explanation	A tape device is required, but the specified path does not point to a tape device.
Action	Correct the path.
INODSE1095	Incremental backup from timestamp must not be deleted
Explanation	A single incremental backup must not be deleted.
Action	Select only full backups to be deleted. When deleting a full backup, associated incremental backups will be deleted as well.
INODSE1096	Error errno has been signalled in the execution of an asynchronous I/O for id
Explanation	An asynchronous I/O operation has failed due to an operating system error.
Action	Check for problems with the device. Check whether the device is off-line or read-only. In the case of a logical volume, try to access all of its physical devices by using operating system commands. Check the system log file for appropriate error messages.
INODSE1097	An incremental backup must not be used to create a database
Explanation	Only full backups are allowed to be used to create a database.
Action	Select a full backup to create a database.
INODSE1098	Inconsistent backup count count1 found, expected count is count2
Explanation	The existing incremental backups do not represent a valid sequence.
Action	Check if all incremental backups exist. If no backup is missing, please contact your software supplier.
INODSE1099	Ambiguous keyword
Explanation	The input does not uniquely identify a keyword.
Action	Please specify an unambiguous keyword.
INODSE1100	Internal database error error on doctype doctype (ID). No further recovery on this doctype.
Explanation	There was an error in an operation on a doctype. The doctype has been excluded from further recovery processing.
Action	Please contact your software supplier.

INODSE1101	Internal error n f g h r in text index
Explanation	A text index has encountered an error.
Action	Please contact your support center and provide them with the information given in the error message and with a backup copy of your database.
INODSE1102	Internal error n f g h x in text index
Explanation	A text index has encountered an error.
Action	Please contact your support center and provide them with the information given in the error message and with a backup copy of your database.
INODSE1103	Loading of text index failed due to operating system error errno
Explanation	This message indicates an installation error.
Action	Please consult the manufacturer's manual. If you cannot fix the error, contact your software supplier.
INODSE1104	Journal overflow during recovery processing
Explanation	The journal space was insufficient. Recovery processing was terminated.
Action	Provide more journal space. Restart the terminated activity.
INODSE1105	Invalid structure for log space from session session number
Explanation	The log space does not contain correct log information.
Action	Check if files have been moved or copied to the log space location.
INODSE1106	Doctype doctype not found, no further recovery on this doctype
Explanation	A doctype required for recovery processing was not found. The doctype has been excluded from further recovery processing.
Action	If the previous recovery processing aborted, restart the restore and recovery.
INODSE1107	Doctype doctype locked, no further recovery on this doctype
Explanation	A doctype required for recovery processing was locked. The doctype has been excluded from further recovery processing.
Action	The doctype may be locked due to an abort of previous recovery processing. Restart the restore and recovery.

INODSE1108	Internal database error error on index index name of doctype doctype (ID). All indexes on this doctype have been dropped.
Explanation	There was an error in an operation on an index of a doctype. The index of the doctype has been disabled.
Action	After the recovery has finished, recreate the index by choosing the "Check and Repair" function for the database in the Tamino Manager.
INODSE1109	The index of doctype doctype is not accessible, recovery of this doctype will not include index
Explanation	The index remains in a disabled state from a previous abort during recovery processing.
Action	After the recovery has finished, recreate the index by choosing the "Check and Repair" function for the database in the Tamino Manager.
INODSE1111	Utility sub-function has not yet been implemented
Explanation	Although the sub-function is a valid function request, it has not yet been implemented for the utility. This is an internal message.
Action	Please contact your software supplier.
INODSE1112	Utility handling not implemented
Explanation	This is an internal message.
Action	Please contact your software supplier.
INODSE1117	No more memory can be allocated
Explanation	A utility issued a request to allocate temporary memory, but this request failed. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.
Action	No action required. Please contact your system administrator for further information.
INODSE1118	Internal configuration error
Explanation	An internal configuration error has occurred. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.
Action	No action required. Please contact your system administrator for further information.

INODSE1119	Invalid date/time specified. Valid format is YYYY-MM-DD:hh:mm:ss
Explanation	The date and time specified is invalid.
Action	Specify a date and time using format YYYY-MM-DD:hh:mm:ss.
INODSE1120	Sub-function is not valid for utility
Explanation	A sub-function was specified that is not valid for the utility.
Action	Specify a valid sub-function for the utility.
INODSE1121	Open of file path has failed due to operating system error errno
Explanation	The virtual operating system could not open the requested file.
Action	Make sure that the file is available.
INODSE1122	Service name for server servername not found
Explanation	The service name for the server was not found in the configuration store.
Action	Please contact your software supplier.
INODSE1123	SCM open failed with error rsp
Explanation	Service Control Manager open failed.
Action	Please contact your software supplier.
INODSE1124	Utility cannot run because of a pending autorepair on the database
Explanation	An attempt was made to start a utility against a database that had not terminated correctly.
Action	Start the database, and let the autorepair processing complete. Then rerun the utility.
INODSE1125	A syntax error has occurred in a utility
Explanation	A syntax error was detected in the parameters of a utility.
Action	Correct the syntax error and rerun the utility.
INODSE1127	SCM service open failed with error rsp
Explanation	Service Control Manager open service failed.
Action	Please contact your software supplier.

INODSE1128	System error errno occurred during file synchronization
Explanation	A file synchronization operation has failed at the operating system level.
Action	Check the manufacturer's manual.
INODSE1130	System error errno occurred during semaphore operation
Explanation	An error has occurred while an operation on a semaphore was requested from the operating system.
Action	Check the manufacturer's manual.
INODSE1131	Invalid server session number session number found in log space block block number
Explanation	The log space does not contain correct log information.
Action	Check if files have been moved or copied to the log space location.
INODSE1132	Invalid block sequence found in log space - expected block number1, current is block number2
Explanation	The log space does not contain correct log information.
Action	Check if files have been moved or copied to the log space location.
INODSE1133	Error opening log space: error message
Explanation	The log space could not be opened. The recovery function has been stopped.
Action	Check if files have been moved or copied to the log space location.
INODSE1134	SCM service start failed with error rsp
Explanation	Service Control Manager start service failed.
Action	Please contact your software supplier.
INODSE1135	SCM query service status failed with error rsp
Explanation	Service Control Manager query service status failed.
Action	Please contact your software supplier.

INODSE1136	Transaction aborted due to transaction timeout
Explanation	A transaction has been aborted. All changes of this transaction have been undone.
Action	Check whether a higher transaction timeout value would make sense in your environment. Restart the transaction.
INODSE1137	Transaction aborted due to non-active connection
Explanation	A transaction has been aborted. All changes of this transaction have been undone.
Action	Check the reason for the transaction abort. Restart the transaction.
INODSE1138	Transaction aborted because server session had been stopped by administrator
Explanation	A server session was explicitly stopped by the administrator. All changes of this transaction have been undone.
Action	No action required.
INODSE1139	Transaction aborted due to overflow in journal space journal space
Explanation	A transaction has been aborted because there was not enough space to log all the changes of the transaction or because too many transactions were active at the same time. All changes of this transaction have been undone.
Action	Consider enlarging the journal space. Restart the transaction.
INODSE1140	Transaction aborted due to security violation
Explanation	A transaction has been aborted. All changes of this transaction have been undone.
Action	No action required.
INODSE1141	Transaction aborted due to deadlock
Explanation	A transaction has been aborted because its locking requirements caused a deadlock with other transactions. All changes of this transaction have been undone.
Action	Restart the transaction.
INODSE1142	Transaction aborted due to internal error reason
Explanation	A transaction has been aborted. All changes of this transaction have been undone.
Action	Please contact your software supplier.

INODSE1143	Internal database error error has occurred
Explanation	The specified database error has occurred.
Action	Please contact your software supplier.
INODSE1144	The data of doctype doctype is not accessible
Explanation	The doctype may be locked or may have been corrupted by a previous action (e.g. failed server restart).
Action	If the doctype is locked, wait until it is unlocked, then retry. If the doctype was corrupted by a previous action, the system administrator must rebuild the doctype from backups.
INODSE1145	The indexes of doctype doctype are not accessible
Explanation	The indexes may have been corrupted by a previous action (e.g. failed server restart).
Action	Wait for a short while, then retry. If the problem persists, this might indicate that the indexes have to be rebuilt. To rebuild the indexes, choose the "Check and Repair" function for the database in the Tamino Manager.
INODSE1148	I/O error on database space db space number
Explanation	The operating system has signalled an I/O error. This is typically caused by a hardware error.
Action	Check whether any disk devices have gone offline. Check the error log for hardware errors.
INODSE1149	Too many paths specified for a location
Explanation	Only 8 paths are allowed to be specified for a location.
Action	Use less paths for the location to be set up.
INODSE1150	The indexes of doctype doctype are corrupt, reason rsp
Explanation	An internal inconsistency has been found in the indexes.
Action	The indexes have to be rebuilt. To rebuild the indexes, choose the "Check and Repair" function for the database in the Tamino Manager.

INODSE1153	filename is an invalid file name for a database space
Explanation	The specified file name for a database space is not valid.
Action	Specify a valid file name for a database space.
INODSE1154	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INODSE1155	filename is not a database space for server dbname
Explanation	The specified file name is not a database space for the given database name.
Action	Make sure that the file name of the database space is a database space of the specified database.
INODSE1158	I/O subsystem error (e1/e2): error text
Explanation	An error in an I/O related function has occurred.
Action	Please contact your software supplier.
INODSE1167	standard length out of range
Explanation	The specified length value is invalid.
Action	Correct the length specification.
INODSE1171	FI only allowed if standard-length is given
Explanation	The FI option is only allowed if a non-zero standard length is given.
Action	Correct the input line.
INODSE1172	Wrong input file assigned
Explanation	The wrong input file has been used for the utility.
Action	Ensure that the correct input file is being used by the utility.
INODSE1173	Checked and repaired database. Number of corrupted indexes was number. Of these, repairing failed for failed.
Explanation	The database could not be completely repaired.
Action	Please contact your software supplier.

INODSE1175	Invalid load data structure at file (ID id, length length)
Explanation	The structure of the data to be loaded is invalid.
Action	Ensure that the correct input file is being used. Send the load files (extension 1C0/1C1) to your software supplier.
INODSE1176	Unable to attach to shared memory
Explanation	It is not possible to attach the process to the shared memory.
Action	Ensure that there is enough available memory, and contact your software supplier if required.
INODSE1181	An unexpected server response (response) has occurred
Explanation	The specified response has been returned by the server.
Action	Determine the reason for the response, or contact your support center.
INODSE1182	Database server is not accessible
Explanation	It is not possible to access the database server.
Action	Determine the reason why the database server is not accessible and retry the operation.
INODSE1189	Reorganize database is not permitted while database is active
Explanation	To preserve data consistency, the database must not be active while reorganize function is processed.
Action	Shut down the database
INODSE1194	An internal buffer is too large (size)
Explanation	The size of an internal buffer has caused a record to overflow.
Action	Please contact your software supplier.
INODSE1198	Event token not supplied
Explanation	The recovery function was started without supplying an event token.
Action	Check the usage of the administration tool.

INODSE1199	Logging not disabled
Explanation	When the recovery function is started, logging must be disabled. In this case, the recovery function was started with logging enabled.
Action	Check the usage of the administration tool.
INODSE1200	Database name is too long
Explanation	The specified database name is too long. If the database name consists of ASCII characters, it can be up to 16 characters long. If the database name consists of multibyte characters, the total number of bytes required to store the database name must not exceed 16.
Action	Please specify a shorter database name.
INODSE1201	Database name contains invalid character "," (comma)
Explanation	A database name cannot contain a comma.
Action	Please modify the database name.
INODSE1202	Database name contains an invalid character
Explanation	A database name cannot contain certain characters, such as # " . [] .
Action	Please modify the database name.
INODSE1203	Database name contains invalid character "" (backslash)
Explanation	A database name cannot contain a backslash.
Action	Please modify the database name.
INODSE1209	Maximum number of space files reached
Explanation	The maximum allowed number of data/index files has been reached.
Action	Please contact your software supplier.
INODSE1210	Size of space file too large
Explanation	The size of the file to be created exceeds the limits of the operating system or of the underlying storage medium. For example, you want to create a file with a size greater than 2GB, but the operating system does not support this.
Action	Select a smaller file size.

INODSE1212	Internal free space error
Explanation	An unexpected free space management error occurred when adding a new database file.
Action	Please contact your software supplier.
INODSE1213	Error error accessing or modifying information in the internal configuration store
Explanation	The information for a log space or a savepoint entry could not be retrieved or set up.
Action	Check the reasons for errors accessing and updating the internal configuration store (for example permissions or low disk space).
INODSE1214	An error occurred during a create index process on doctype doctype
Explanation	The error is caused by an attempt to create a unique index on data that contains non-unique values.
Action	No action required.
INODSE1215	Database name contains a space
Explanation	A database name cannot contain a space.
Action	Please modify the database name.
INODSE1217	Error when opening database space, compressed state is not permitted (at path)
Explanation	The database file has the compressed attribute, which is not permitted, because write errors should be avoided if the device is getting full.
Action	Remove the compressed attribute from the database file.
INODSE1221	Error error when accessing internal information for savepoint savepoint
Explanation	The information for a savepoint entry could not be retrieved.
Action	Contact your software supplier.
INODSE1222	Error error when trying to move or delete file name
Explanation	A backup file or a file for recovery purpose could not be moved or removed.
Action	Contact your software supplier.

INODSE1223	Log space not found for savepoint savepoint, session number session number
Explanation	A log space entry for the given savepoint and session number could not be found.
Action	Contact your software supplier.
INODSE1224	Backup space not found for savepoint savepoint
Explanation	A backup space for the given savepoint could not be found.
Action	Contact your software supplier.
INODSE1225	Backup file type file type is invalid for savepoint savepoint
Explanation	The internal information for the file type associated with a savepoint is set up incorrectly.
Action	Contact your software supplier.
INODSE1226	Unexpected return code error when executing function function
Explanation	An internal error occurred.
Action	Please contact your software supplier.
INODSE1231	Errors have occurred during autorepair
Explanation	The autorepair from the crash of the previous server session was not completely successfully.
Action	Check the detailed error messages and repair the affected data.
INODSE1232	Database space is too large
Explanation	The database space specified for the current operation is too large.
Action	Retry the operation specifying a smaller database space.
INODSE1233	The limit of extents for container_name has been reached
Explanation	No more extents of the specified space type can be created because the maximum number has been reached.
Action	Retry the operation with a smaller number of extents specified.

INODSE1235	Crash dump file filename could not be created due to operating system error system errno (errtxt)
Explanation	The backup file needed for error analysis could not be created due to the given reason.
Action	Please consult the manufacturer's manual.
INODSE1236	Recovery skipping has terminated with an error
Explanation	An error occurred during recovery skipping. This message indicates an internal inconsistency.
Action	Please contact your software supplier.
INODSE1289	Error when opening database space space no (at path): size mismatch
Explanation	The size of the database space is not equal to the size expected by the server.
Action	Please contact your software supplier.
INODSE1290	I/O error occurred on database space space no. System error errno caused by operation operation on block block number.
Explanation	The operating system has signalled that the specified I/O operation has failed.
Action	Please consult the manufacturer's manual.
INODSE1292	Creation of database space space no (path) has failed
Explanation	The database space could not be created at the specified location.
Action	Look for other error messages to find the reason for the failure.
INODSE1293	Creation of database space space no (path) has failed due to system error errno
Explanation	The database space could not be created at the specified location because of an error signalled by the operating system.
Action	Please consult the manufacturer's manual.
INODSE1295	Creation of journal space 1 (path) has failed
Explanation	The database space could not be created at the specified location.
Action	Look for other error messages to find the reason for the failure.

INODSE1318	Internal server error during database creation, reason: reason
Explanation	The system has tried to allocate a new database space, probably because the existing database spaces did not contain enough free space. The allocation has failed.
Action	Check which database space was affected by checking the free space. Allocate another database space manually.
INODSE1320	Log space structure error error number
Explanation	The log information which is needed to recover the database is corrupt, so the database recovery was stopped when the corruption was detected.
Action	Send the log space to your software supplier for analysis.
INODSE1358	Creation of database space space no (path) has failed because the file already exists
Explanation	The database space could not be created at the specified location because the file is already present.
Action	Remove or move the file to another location before repeating the action.
INODSE1374	No abbreviation allowed for this keyword
Explanation	The specified keyword must not be abbreviated.
Action	Please specify the keyword in full length.
INODSE1375	Invalid keyword
Explanation	The specified keyword is not recognized or invalid.
Action	Please specify a correct keyword.
INODSE1376	Syntax error
Explanation	An internal syntax error occurred.
Action	Please contact your software supplier to analyze the problem.
INODSE1380	Given value not numeric
Explanation	The given value has to be in a numeric format.
Action	Please specify a numeric value.

INODSE1381	Only number value(s) allowed
Explanation	The number of allowed list elements is exceeded.
Action	Please limit the number of list elements to the maximum allowed.
INODSE1382	Value has to be greater than or equal to minvalue
Explanation	The specified value is too low.
Action	Please enter a value greater than or equal to the required minimum.
INODSE1383	Value has to be less than or equal to maxvalue
Explanation	The specified value is too high.
Action	Please specify a value less than or equal to the allowed maximum.
INODSE1385	Invalid range specified
Explanation	The range specified is invalid.
Action	Please specify a range within the allowed limits.
INODSE1386	At least minnum character(s) required
Explanation	The specified number of characters was too low.
Action	Please specify a sufficient number of characters.
INODSE1387	Only maxnum character(s) allowed
Explanation	The maximum allowed number of characters was exceeded.
Action	Please specify no more than the maximum allowed number of characters.
INODSE1390	Missing mandatory parameter param
Explanation	The displayed mandatory parameter could not be found and a default value is not available.
Action	Supply the displayed mandatory parameter.
INODSE1391	Invalid parameter value
Explanation	The specified parameter value is invalid.
Action	Correct the input.

INODSE1413	System error errno when opening database space space no (path)
Explanation	The specified operating system error has occurred.
Action	Please consult the manufacturer's manual.
INODSE1416	architecture mismatch detected, file from platform
Explanation	The crash dump file is from a different platform.
Action	Go to the proper platform.
INODSE1498	unknown option
Explanation	The option specified is unknown.
Action	Correct the input line.
INODSE1506	option not permitted
Explanation	The supplied option is not permitted for this function.
Action	Check the input parameters.
INODSE1512	transition to this level not allowed
Explanation	The specified level number is not allowed in this context.
Action	Correct the input line.
INODSE1523	reserved field name
Explanation	The specified field name is reserved.
Action	Correct the field name.
INODSE1538	Read-only mode is not permitted because the previous session was abnormally terminated
Explanation	The Tamino server cannot be started in read-only mode because the previous session was abnormally terminated.
Action	Start the Tamino server in normal mode to do an autorepair for the abnormal termination. Restart the Tamino server in read-only mode.

INODSE1539	Read-only mode is not permitted because of pending transactions
Explanation	The Tamino server cannot be started in read-only mode because of pending global transactions.
Action	Start the Tamino server in normal mode and close the pending global transactions.
INODSE1603	Error when adding a new type
Explanation	An unexpected error occurred while adding a container.
Action	Check the device and the environment variable relating to the new container.
INODSE1604	Number of additional cont extents currently exhausted
Explanation	The maximum number of created database spaces within one session has been reached.
Action	Shut down and restart the database server and retry the operation.
INODSE1605	No space for extending database space
Explanation	There is no more space on the disk for extending the current database space.
Action	Check the disk size where the latest database space is located. Think about creating a new database space on another disk where space is available.
INODSE1606	Database space to be removed is in use
Explanation	The request to remove a database space failed because the file space at the end of the file is in use.
Action	Ensure that the database space is not in use and retry the operation.
INODSE1633	Recovery terminated with error
Explanation	An error occurred during database recovery.
Action	Check for additional error messages in the event log.
INODSE1769	Invalid database root block header (size blocksize / next block)
Explanation	A database root block linkage is invalid.
Action	Perform a restore/recover of the database.

INODSE1898	The specified doctype is not available.
Explanation	It is not possible to access the specified doctype.
Action	Check that the correct doctype name has been specified, and that it is currently available for use.
INODSE1913	File file not loaded
Explanation	The file with the given number could not be loaded
Action	Check whether the file exists or is not accessible.
INODSE1945	Function not permitted while server is running
Explanation	The given function is invalid with an active server.
Action	Shut down the server.
INODSE1976	Internal database error error during recovery processing
Explanation	While processing a log space, re-applying updates resulted in an error.
Action	Check if the database was in a different state than it was when the original command was executed. This may be caused by using a backup copy and log spaces inconsistently.
INODSE1979	Database space space has reached the upper limit
Explanation	The maximum size of the given database space has been reached. This means the database cannot be extended any more.
Action	A database redesign is necessary. Either delete doctypes from the database or create a second database.
INODSE1984	Allocation of a new data space failed on required index allocation (reason)
Explanation	The database space (data) cannot be enlarged. The new database space requires allocations in the index space, but the index space allocation failed due to the internal reason displayed.
Action	Investigate why the index database space cannot be enlarged.
INODSE1987	Error when extending type
Explanation	A database space extension failed, so the database could not be enlarged.
Action	View the subsequent error message for information about why the database could not be enlarged.

INODSE1992	Invalid container request type
Explanation	An internal error occurred while accessing a database container file.
Action	Contact your software supplier and report the number displayed in the message.
INODSE1995	Access to configuration information for savepoint 'ts' failed: msg
Explanation	The backup with the given representation could not be determined in the database configuration.
Action	Contact your software supplier to analyze the problem.
INODSE1996	Database is inconsistent, restore required
Explanation	The database is in an inconsistent state that cannot be handled by the autorepair process. The database must be restored.
Action	The reason for an inconsistent database can be re-applying a mass load during recovery. If no abort timestamp is shown in the event log of the aborted session, perhaps due to a power failure, restart with restore/recover. For any other reasons that will cause the error to re-occur, set up the restore/recover until a timestamp shortly before the recovery abort shown in the event log of the aborted session.
INODSE1999	Internal database error error during recovery processing on doctype doctype
Explanation	While processing a log space, re-applying the updates resulted in an error.
Action	Check if the database is in a different state than it was when the original command was executed. This may be caused by using a backup copy and log spaces inconsistently.
INODSE2000	Starting replication failed
Explanation	Replication processing could not be started.
Action	Check for for additional related messages in the event log.
INODSE2001	Replication processing cannot be continued due to previous replication error
Explanation	An error during the previous replication processing prevents the continuation of the replication.
Action	If the master database is lost, the Reset Replication function can be used to convert the database for usage as a substitution. In any other case, the replication database has to be recreated using a new backup from the master database.

INODSE2004	Invalid operation detected
Explanation	Replication cannot be continued because a function (e.g. restore without full recover) was executed on the master database which is not yet supported for replication
Action	A backup from the master database after the operation in question should be used to recreate the replication database.
INODSE2013	Database identification already in use
Explanation	The database identification supplied is already in use.
Action	Repeat the process using an unused database identification.
INODSE2014	Failed to enumerate databases
Explanation	An internal call has failed to enumerate the defined database names.
Action	Please contact your software supplier.
INODSE2019	No log space data found for session session number
Explanation	The master database could not find the log space to return the required log space data.
Action	Check the database properties for the number of backup generations and increase the value if set too low.
INODSE2020	Replication database(s) defined, rename not allowed
Explanation	The rename function is not allowed for a database which is to be used as a master database for replication purposes.
Action	Remove replication databases first before renaming the database. New replication databases can be created from a backup created after the rename operation.
INODSE2022	Replication permission denied by master database
Explanation	The name of the replication database was not found in the master database's list of permitted databases.
Action	Add the replication database name to the list of permitted replication databases of the master database.

INODSE2023	Replication database origin mismatch
Explanation	The replication database does not match the contents of the master database.
Action	Check whether the replication database was created using a backup from another database than the one specified as master database or check whether another database was renamed using the same database name as the master database's name.
INODSE2024	An internal utility parameter error (location) has occurred
Explanation	An internal parameter error has caused the utility to fail.
Action	Please contact your software supplier.
INODSE2031	Internal error occurred: DSIF func [mod - line] what parameter param
Explanation	An internal error occurred.
Action	Please contact your software supplier and provide the message text.
INODSE2033	Internal error occurred: OVO func [mod - line] error
Explanation	An internal error occurred.
Action	Please contact your software supplier and provide the message text.
INODSE2034	Internal error occurred: SMP func [mod - line] error
Explanation	An internal error occurred.
Action	Please contact your software supplier and provide the message text.
INODSE2035	Server communication interface [mod - line] error error
Explanation	An unexpected error was returned by the server communication interface.
Action	Please contact your software supplier and provide the message text.
INODSE2036	path is not a valid directory
Explanation	The directory specified does not exist.
Action	Specify a valid directory name.
INODSE2037	Insufficient free disk space on path - available avail MB, needed needed MB
Explanation	There is not enough space in the given directory to complete the operation.
Action	Free some disk space or specify another directory.

INODSE2042	File file already exists in the destination directory dir
Explanation	The file cannot be created in the destination directory because another file with the same name already exists.
Action	Change the destination directory parameter.
INODSE2043	Infofile cannot be created, because otherwise the full path name of the info file would exceed operating system limit
Explanation	The infofile path is too long.
Action	Please specify another directory for the CD database.
INODSE2045	File path does not exist
Explanation	An invalid path was specified.
Action	Specify a valid path.
INODSE2046	Failed to parse infofile , line 'line'
Explanation	The CD database infofile could not be parsed.
Action	Please contact your software supplier.
INODSE2048	Cannot create database, because there are too many databases already
Explanation	A new database cannot be created because there are too many databases already.
Action	Check if you still need all the databases you created and if possible delete some of them.
INODSE2050	Requested operation not permitted in online mode
Explanation	The server must be offline to perform the requested operation.
Action	Shut down the database.
INODSE2061	Work pool too small
Explanation	The work pool used is too small.
Action	Ensure that a sufficiently large work pool is available.

INODSE2064	Invalid infofile format
Explanation	The CD database information file has an invalid format.
Action	This error should not occur unless the file was modified manually. Avoid manual modification in the information file.
INODSE2065	Incompatible operating system (original database was created on operating system)
Explanation	The CD database cannot be created because the database is incompatible with the target platform.
Action	Create the CD database on the same platform as the original database.
INODSE2067	Operation not allowed on read-only or CD databases
Explanation	The required operation cannot be performed on a CD database or read-only database.
Action	Switch the "read only" server parameter to "no". This does not apply to databases on CD.
INODSE2069	Location with the same name already exists
Explanation	A location with the same name already exists.
Action	Choose another location name.
INODSE2070	Cannot delete default location or default backup location
Explanation	There was an attempt to delete the default location or default backup location. Delete operations on these locations are not allowed.
Action	No action required.
INODSE2071	Location with the same path settings already exists
Explanation	A location with the same path settings already exists
Action	Choose another location path.
INODSE2072	Location locname not found
Explanation	The specified location was not found.
Action	Correct the location name parameter and try again.

INODSE2080	Internal error occurred: DSIF func [mod - line] not allowed in this context
Explanation	An internal error occurred.
Action	Please contact your software supplier and provide the message text.
INODSE2081	Internal error occurred: OVO memory what(bytes) [mod - line] error
Explanation	An internal error occurred.
Action	Please contact your software supplier and provide the message text.
INODSE2082	Granting port allocation lock failed with response err - int_err
Explanation	Unexpected response received while trying to lock the port allocation lock.
Action	Please contact your software supplier.
INODSE2084	Invalid port value port detected, valid port values are between portmin and portmax
Explanation	An invalid port value was detected.
Action	Please specify a valid port value.
INODSE2085	Invalid port range r1 - r2 detected, minimum min ports required in range
Explanation	A port range has to contain a minimum number of ports.
Action	Please specify a valid port range.
INODSE2086	Static port range r1 - r2 and dynamic port range r3 - r4 overlap
Explanation	Static and dynamic port range overlap, which is not allowed.
Action	Please specify valid port ranges.
INODSE2087	Port check function could not read static and / or dynamic port range
Explanation	An error occurred while retrieving the static and dynamic port range.
Action	Please contact your software supplier.
INODSE2088	The given dynamic port range r1 - r2 is not free
Explanation	At least one port in the given dynamic port range is already in use by another server.
Action	Please specify a dynamic port range where no ports are used by other servers.

INODSE2092	Internal error occurred: DSIF func [mod - line] invalid combination of parameters
Explanation	An internal error occurred.
Action	Please contact your software supplier and provide the message text.
INODSE2093	Web server webserver not registered
Explanation	The given web server is not registered.
Action	Specify a registered web server.
INODSE2094	Web server webserver not correctly registered
Explanation	The web server is not correctly registered. Either the IP address or the port number is missing.
Action	Correct the web server registration.
INODSE2095	Web server webserver not assigned to database dbname
Explanation	The web server is not assigned to the database.
Action	Check your web server registrations.
INODSE2096	Environment extension envext not registered for Tamino what what1
Explanation	The environment extension is not registered in the Tamino configuration.
Action	No action required.
INODSE2097	No environment extension registered for Tamino what what1
Explanation	No environment extension registered for Tamino version or server.
Action	No action required.
INODSE2099	No extension point definitions found for version version
Explanation	No extension point definitions were found for the specified version.
Action	Check your configuration.
INODSE2103	Invalid port range r1 - r2 detected
Explanation	An invalid port range was detected.
Action	Specify a valid port range.

INODSE2104	Component comp already exists for extension point extp in version vers
Explanation	The component already exists for the extension point in the specified version.
Action	No action required.
INODSE2105	Component comp already exists for extensions in version vers
Explanation	The component already exists in the extension section of the specified version.
Action	No action required.
INODSE2106	Component comp does not exist for extension point extp in version vers
Explanation	The specified component is not defined for the given extension point and version.
Action	No action required.
INODSE2107	Component comp does not exist in extensions for version vers
Explanation	The specified component does not exist in the extensions for the given version.
Action	No action required.
INODSE2108	Could not find function func for extension point extp, version vers, component comp
Explanation	The extension point function was not found in the specified extension point library.
Action	Check library name, path and entry points of the extension point library.
INODSE2109	Extension point extp does not exist in version vers
Explanation	The specified extension point does not exist in the given version.
Action	No action required.
INODSE2110	Could not load library lib for extension point extp, version vers, component comp
Explanation	The extension point library could not be loaded via the specified path.
Action	Check the library name and path of the extension point definitions.
INODSE2111	Could not allocate a port, because the static port range is full
Explanation	No port could be allocated in the static port range, because it is full.
Action	Extend the static port range, use a port from outside the static port range or force reuse of a port from the static range.

INODSE2114	Port allocation function could not read static and / or dynamic port range
Explanation	An error occurred while retrieving the static and dynamic port range.
Action	Please contact your software supplier.
INODSE2117	Granting raw section lock failed with response err - int_err
Explanation	Unexpected response received while trying to lock the raw section lock.
Action	Please contact your software supplier.
INODSE2121	Web server webserver is already registered, rename is not allowed
Explanation	The web server specified is already registered. Therefore the rename is not allowed.
Action	Choose another name for the web server or delete the existing web server.
INODSE2124	Internal error occurred: func [mod - line] what parameter param
Explanation	An internal error occurred.
Action	Please contact your software supplier and provide the message text.
INODSE2125	Web server webserver is already registered
Explanation	The specified web server is already present.
Action	Update the web server.
INODSE2126	database space of database server in raw section section is in use and must not be reallocated
Explanation	The specified database spaces are in use and must not be reallocated.
Action	No action required.
INODSE2127	database space of database server not present in raw section section
Explanation	The specified database space(s) could not be found in the raw section.
Action	Please contact your software supplier.
INODSE2129	pathname does not specify a regular file (returned type error)
Explanation	The given path does not specify a regular file.
Action	Specify a regular file.

INODSE2130 **database space of database server in raw section section is in use and must not be deallocated**

Explanation The specified database spaces are in use and must not be deallocated.

Action No action required.

INODSE2134 **Index recreation not permitted at this item**

Explanation This item has no data records, therefore a reinvert cannot be performed.

Action Use the X-Machine programming command "admin" to recreate the index.

INODSE2135 **database space space number of server server not found**

Explanation The specified database space could not be found.

Action Correct the database space specification and try again.

INODSE2136 **database space of database server in raw section section is in use and must not be changed**

Explanation The specified database space is in use and must not be changed.

Action Ensure that the database space is not in use before changing it.

INODSE2137 **Database server is active, database spaces must not be moved**

Explanation The database is active. Therefore database spaces must not be moved.

Action Stop the database before moving any database spaces.

INODSE2138 **Granting container move lock failed with response err - int_err**

Explanation An unexpected response was received while trying to grant the container move lock.

Action Please contact your software supplier.

INODSE2140 **Error while reading data reference block block into internal pool**

Explanation An unexpected error occurred while reading a data reference block into the internal cache.

Action Please contact your software supplier.

INODSE2141	Load file has unexpected structure level lev (compatibility comp)
Explanation	The input file for a data load operation has a structure level mismatch, or the file is corrupted.
Action	Check if the input file has the wrong structure level or is corrupted.
INODSE2142	Internal error occurred: DSIF func [mod - line] invalid parameter handle (parhdl) supplied
Explanation	An internal error occurred.
Action	Please contact your software supplier and provide the message text.
INODSE2143	Server parameter "param" not available in current context
Explanation	A server parameter was requested in an invalid context.
Action	Please contact your software supplier.
INODSE2144	Invalid server parameter name "param" supplied
Explanation	The given server parameter name is invalid.
Action	Specify a valid server parameter name.
INODSE2145	Static server parameter "param" must not be changed online
Explanation	Static server parameters must not be changed while the server is active.
Action	Stop the server before changing a static parameter.
INODSE2157	Due to license restrictions, raw section access is not allowed
Explanation	The license file does not contain the permission to access raw sections.
Action	Use the file system instead or obtain the required license from your software supplier.
INODSE2160	Upgrade is not allowed for replication database
Explanation	An upgrade is not allowed for a replication database.
Action	If the master database has been upgraded, the replication database must be newly created from the master backup.

INODSE2162	Physical extent count 0 detected at typ
Explanation	The management of physical database spaces has an empty counter.
Action	The database seems to be physically corrupted. Perform a restore/recover.
INODSE2163	First Index blocksize incompatible (bls)
Explanation	The blocksize field of first index space does not match the real blocksize.
Action	No action required.
INODSE2164	Physical extent entry error (typ first - last)
Explanation	The physical management of the database is corrupted.
Action	Perform a restore/recover.
INODSE2167	Check for tape device failed on path. Check that the path is correct and whether tape is in drive.
Explanation	It was no possible to verify that the specified path points to a tape device.
Action	Make sure that the path is correct, that the tape is in the drive, that the tape device is online and the tape device is properly connected to the system.
INODSE2168	Location type mismatch - expected 'type1' , found 'type2'
Explanation	This error can occur during 'Add Location', if the requested location type does not match the actual file type.
Action	Specify the correct location type.
INODSE2169	Received response rsp (intrsp) while starting server
Explanation	Starting the server failed.
Action	Please contact your software supplier.
INODSE2170	Received response rsp (intrsp) while stopping server
Explanation	Stopping the server failed.
Action	Please contact your software supplier.

INODSE2173	Unexpected internal server error: errorstring
Explanation	An internal server call failed with given error string.
Action	Please look into the server job log if there is additional error information. If not, contact your software supplier.
INODSE2175	Unexpected internal server error: errorstring, location location
Explanation	An internal server call failed with given error string.
Action	Please look into the server job log to see if there is additional error information. If not, contact your software supplier.
INODSE2178	Doctype doctype is locked by another user
Explanation	The doctype has a lock conflict with a running action of another user.
Action	Investigate which user is active and what activity is causing the lock.
INODSE2179	Upgrade from version from_version to version to_version not supported
Explanation	The required database conversion between the stated versions is not supported.
Action	Consult the documentation about possible upgrade options.
INODSE2187	Cannot determine file type from path
Explanation	An unexpected error occurred while Tamino tried to determine the file type of the displayed location.
Action	Check if the displayed location is accessible. If the location is accessible please contact your software supplier.
INODSE2192	The maximum number of threads allowed per process (max_threads) is too low to start and manage the Tamino server
Explanation	The current parameter configuration does not allow the creation of all necessary threads to start and manage the Tamino server.
Action	Either the system defined maximum number of threads per process is too low and should be increased, or the Tamino parameter configuration should be changed to decrease the number of threads to be created.

INODSE2193	Insufficient system resources to create thread: thread 'name', error error returned by thread create function
Explanation	There are not enough system resources available to create a new thread.
Action	There are not enough system resources available to create a new thread. The reason for that is either that the system defined maximum number of threads per process is exceeded, or that there is not enough memory available to allocate the necessary thread resources.
INODSE2194	Restore from backup made in version old_version not supported to upgrade to new_version
Explanation	A backup made in the old version cannot be used, e.g. because this old version is not supported any more. This only applies for databases that are already in a higher version than the backup.
Action	Use a more recent backup to restore the database.
INODSE2200	Master database master dbname is not active
Explanation	An attempt was made to execute a replication command that requires the master database to be active.
Action	Start the master database and retry the command.
INODSE2201	Replication database replication dbname is active
Explanation	An attempt was made to execute a replication command that requires the replication database to be offline.
Action	Stop the replication database and retry the command.
INODSE2202	Master database must be restarted before a replication database can be set up
Explanation	A restart of the master database is necessary.
Action	Restart the master database and try to set up the replication database again.
INODSE2203	Update server sessions exist
Explanation	The database already has update sessions so it cannot be used to replicate another database.
Action	Use a newly created database and retry this operation.

INODSE2204	Replicate master database master dbname not permitted
Explanation	Permission to replicate the master database was denied.
Action	Ask the administrator to permit replication access to the master database.
INODSE2205	Inconsistency detected while setting the database to replication type
Explanation	This database is not suitable to be set as the replication database of the specified master database. Perhaps the versions are not identical or this one was not created from the backup of the master. Also possible is that this database has its own updates after the creation.
Action	Use another database to replicate the master.
INODSE2206	No permission to modify the type of the database
Explanation	To change the type of a database to a replication database or to set it back to a normal one, the user needs to have administrator rights. Other possible reason: The database is not allowed to replicate the master database.
Action	Log in as administrator and try the operation again and check whether this database is in the permission list of the master database.
INODSE2208	Internal error occurred: modification not allowed for replication database.
Explanation	An internal error occurred. The server will be stopped.
Action	Please contact your software supplier and provide the message text.
INODSE2211	No valid location provided for backup
Explanation	There can be a number of reasons for this error, for example no free space or the location directory was deleted outside of Tamino. The exact reason for the error is contained in the job log.
Action	Study the job log to find the exact reason for the error. If the job log indicated that there is no space, free some space on the location device. Alternatively, you may provide another location for the backup.
INODSE2212	The names of master and replication databases cannot be identical
Explanation	Identical names have been supplied for the master and a replication database, but this is not allowed.
Action	Supply different names.

INODSE2213	A former replication database cannot be set to replication type
Explanation	After a replication database has been reset by 'Set Type to Normal Database', it cannot become a replication database any more.
Action	Delete the database, recreate it from a non-initial backup of the master and execute 'Set Type to Replication'.
INODSE2214	Data field layout block rabn, invalid periodic group count count for fieldname
Explanation	The data field layout block with the given number is corrupted.
Action	No action required.
INODSE2215	Activity currently not permitted
Explanation	This error may occur when the server is in the starting or stopping phase. During these phases the server is neither online nor offline. The other reason for this error is when the server is offline and there are some activities on the database in parallel, e.g. adding some index space.
Action	Wait until the server is definitely online or offline and than retry.
INODSE2216	Operation is not permitted during a standby server session
Explanation	The operation cannot run in parallel with another operation that requires the server to be running in standby mode.
Action	A standby session is used for the restore/recover operation. Wait until this operation is finished and the server is shut down.
INODSE2217	Operation not allowed for external backup
Explanation	An external backup is an invalid object for this operation.
Action	Some database operations are not allowed for external backups.
INODSE2218	File currently locked
Explanation	A recovery input file must not be moved because it is used by the server.
Action	Try to perform the operation later. A log space will be unlocked after a session switch. Other recovery input files will be unlocked after the termination of a mass load.

INODSE2219	Savepoint not found for internal key key
Explanation	Necessary configuration information was not found.
Action	Please contact your software supplier.
INODSE2220	File filename does not exist
Explanation	A registered backup or recovery file to be moved or deleted does not exist.
Action	Check the locations used for the database whether files have been lost due to unintended removal or restore operations.
INODSE2221	File filename already exists
Explanation	A registered backup or recovery file to be moved already exists.
Action	Check the locations used for the database whether files are present due to restore operations or files remaining from a deleted database.
INODSE2222	File filename could not be moved
Explanation	Moving a backup or recovery file failed.
Action	Check access control settings of the location where the file is to be moved.
INODSE2223	File filename could not be removed
Explanation	Removing a backup or recovery file failed.
Action	Check access control settings of the file to be deleted or of the source file to be moved.
INODSE2229	Backup time has become invalid
Explanation	An earlier backup was used for a restore not using the recover all option. Due to new modifications done on this base, the newer backup must not be used for restore/recover.
Action	Use another backup for restore/recover. The selected backup can only be used to create new database.
INODSE2231	Cannot create initial backup
Explanation	This error can appear during database creation. There are a number of reasons why the creation of the initial backup might fail e.g. a file with the same name already exists in the backup location, a tape is not ready (if the backup medium is tape) or no reading process is attached to a pipe (if backup medium is pipe). The root cause of the error will be given in the job log.
Action	Read the job log to find the root cause of the error. If there is the file with the same name as the initial backup name in the backup location on the file system, remove this file or move it to another place. If the backup medium is tape , ensure that the

tape is ready. If the backup medium is a named pipe, ensure that there is a process reading from this pipe.

INODSE2232 **XML port must not be set to zero if the communication method includes native TCP/IP**
Explanation If native TCP/IP is used as a communication method for the Tamino server the TCP/IP port used must not be set to zero.
Action Use a valid port number for TCP/IP communication.

INODSE2233 **The database dbname must be online**
Explanation The database must be started for this operation.
Action Start the database.

INODSE2236 **Stopping database failed, reason: reason**
Explanation In specific situations it is not possible to shut down the database with rolling back open transactions. This is: 1. a mass load is active 2. an external backup is active 3. there is a LOG file full situation.
Action Wait until a mass load or external backup operation is finished and try again. If the log file is full, supply space for the LOG and try again.

INODSE2237 **No privilege to modify database, concurrent modifying process is currently active**
Explanation There is another modifying job or process active or the server is within startup. Those actions must be serialized.
Action Check your database state and wait until the server is up or check other modifying database actions.

INODSE2241 **Internal error occurred: DSIF func returncode returncode error error**
Explanation This is an internal error message.
Action Please contact your software supplier.

INODSE2242 **Replication database replication dbname not found in the permission list**
Explanation An attempt was made to remove a replication database from the permission list, but the replication database is not present in the permission list.
Action Retry the command with a correct name.

INODSE2243	Replication database replication dbname already present in the permission list
Explanation	An attempt was made to add a replication database to the permission list, but the replication database is already present in the permission list.
Action	Retry the command with a correct name.
INODSE2249	Physical file extent (extent) missing
Explanation	The database file has been divided among more than one physical file extents. Now while processing this file the given extent is not specified.
Action	Specify all physical file extents.
INODSE2250	A further extent of source cannot be created, because current file is incomplete
Explanation	The support of multiple physical file extents requires that the current file is completely written. However with network file systems (e.g. NFS) if getting full, the current file is less in size than expected. Therefore the switch to the next location is impossible in this case. A local file system should not have those problems.
Action	Be sure that you have enough space at your file system because this one can only support one single file extent. Or take locally attached file systems.
INODSE2258	Inconsistent usage or missing filetype file extent during processing extent extent
Explanation	Multiple physical file extents specified by the user are not consistent. Either the extent is missing, unexpected or specified twice or the file does not come from the same database.
Action	Enter all required file extents and verify if they are from the same database.
INODSE2263	(Re)Move of a single file extent is not possible because there is a reference from another database
Explanation	If the backup consists of multiple file extents it is not possible to (re)move single extents when another database has a reference to it.
Action	Check which database references the backup.
INODSE2264	Function not permitted for a replication database
Explanation	An administration function could not be executed because it must not be used for a replication database.
Action	Check whether the function is to be executed for the master database.

INODSE2265	Database is inconsistent and cannot be used
Explanation	During migration or restore/recover, the database is in an undefined state which cannot be solved. The database cannot be started anymore.
Action	Recover from the latest valid backup or if not possible contact your software supplier.
INODSE2268	Database refused startup after conversion
Explanation	During migration the database cannot be started because of an internal error.
Action	View the server's startup text file (inosrv.txt) for more information.
INODSE2274	Server died during startup
Explanation	The server died during the startup phase.
Action	Inspect the server output file and correct the error.
INODSE2275	Property propertyname must not be changed for read only / replication database
Explanation	The operation mode of the database is not suited for changes in this property. Changing it would jeopardize the database consistency.
Action	For a read only database, if you really want to change the parameter, set the "read only" property to "no", modify the parameter, start the database, stop the database, set "read only" property to "yes".
INODSE2279	Invalid version version of the conversion component
Explanation	There is no conversion utility of the most recent version found.
Action	Upgrade the conversion only to the current one.
INODSE2282	Open of source (path) has failed due to operating system error errno (errtxt)
Explanation	The file specified cannot be opened due to an internal operating system error.
Action	Consult the manufacturer's manual.
INODSE2283	io error error (errtxt) on block block no in database space space no
Explanation	An I/O error has occurred on the given database space.
Action	Analyse the internal operating system error.

INODSE2285	Creation of database space space no (path) has failed due to system error errno (errtxt)
Explanation	A database space could not be created because of an operating system error.
Action	Analyse the system error and consult the manufacturer's manual.
INODSE2289	Due to license restrictions, usage of replication management functions is not permitted
Explanation	Your license does not permit usage of replication databases.
Action	Contact your software supplier for an upgrade of your license.
INODSE2290	Due to license restrictions, server startup for replication database database name is not permitted
Explanation	Your license does not permit usage of replication databases.
Action	Contact your software supplier for an upgrade of your license.
INODSE2291	Due to license restrictions, server startup of database name as a master for replication databases is not permitted
Explanation	Your license does not permit usage of replication databases.
Action	Contact your software supplier for an upgrade of your license.
INODSE2293	Due to license restrictions, set version for replication master database dbname is not permitted
Explanation	Your license does not permit usage of replication databases.
Action	Remove all databases from the master database's replication database table or contact your software supplier for an upgrade of your license.
INODSE2298	Cannot establish connection to server
Explanation	The utility cannot connect the server which is assumed to be online. Note that the communication goes over XTS.
Action	Check if the database is reachable over the XTS directory service. If you cannot find the reason switch on the XTS tracing facility.

INODSE2340	Communication error when trying to contact server servername
Explanation	An error was returned from the communication interface when trying to contact the server.
Action	Check whether the communication component is set up correctly and the communication process (e.g. Software AG XTS Directory Server) is running.
INODSE2341	The last backup available must not be deleted
Explanation	The last backup available must not be deleted because in the case of a database crash no restore is possible.
Action	No action required.
INODSE2342	No valid location or directory specified
Explanation	To create a backup, either a valid location or directory must be specified.
Action	Specify a valid location or directory.
INODSE4055	Block size mismatch detected on database_space
Explanation	A block size mismatch has been detected on the specified database space.
Action	Ensure that the block size of the database space to be restored is the same as that in the backup copy.
INODSE4058	Database space storage (container) exhausted
Explanation	The storage for database space is exhausted.
Action	Try to allocate more storage; if this is not possible contact your software supplier.
INODSE4100	Failure accessing file
Explanation	An error has occurred accessing a Tamino file. The file may possibly be corrupt.
Action	Check that it is the correct file and repeat the operation. If the error persists, contact your software supplier.
INODSE4109	Failure calling external backup
Explanation	Tamino could not start external backup processing.
Action	Check that the third party hardware and drivers are installed and working correctly. If the symptoms persist, contact your software supplier.

INODSE4110	Failed to retrieve number of backup generations from internal configuration store
Explanation	There is possibly a corruption of the internal configuration store.
Action	If the symptoms persist, contact your software supplier.
INODSE4111	Failed to remove oldest savepoint information from internal configuration store.
Explanation	There is possibly a corruption of the internal configuration store.
Action	If the symptoms persist, contact your software supplier.
INODSE4113	Failed to retrieve server version
Explanation	There is possibly a corruption of the internal configuration store.
Action	If the symptoms persist, contact your software supplier.
INODSE4114	Failed to enumerate savepoint information
Explanation	There is possibly a corruption of the internal configuration store.
Action	If the symptoms persist, contact your software supplier.
INODSE4118	Failed to downgrade database
Explanation	There is a problem with the database downgrade utility.
Action	If the symptoms persist, contact your software supplier.
INODSE4120	Failed to execute inodmp utility
Explanation	The Create/Backup/Restore utility cannot be executed, possibly due to a corruption in the internal configuration store.
Action	If the symptoms persist, contact your software supplier.
INODSE4121	External Restore failed
Explanation	Tamino could not start external restore processing.
Action	Check that the third party hardware and drivers are installed and working correctly. If the symptoms persist, contact your software supplier.
INODSE4122	Failed to retrieve database identity
Explanation	There is possibly a corruption of the internal configuration store.
Action	If the symptoms persist, contact your software supplier.

INODSE5251	An inodmp client terminated with unexpected error err
Explanation	Within parallel backup a client process of the dump utility terminated unexpectedly.
Action	The error value defines the exit code of the client process. There are generally additional error messages describing the situation in detail. Ask your software supplier for the reason of the given error.
INODSE5261	Invalid or unsupported character set charset
Explanation	The specified character set is not supported by the current software version.
Action	Check for possible typing errors in character set name.
INODSE5267	Software configuration error
Explanation	The Tamino software components that you are using are not compatible.
Action	Please request a new version of Tamino from your software supplier.
INODSE5268	Failed to register server with the Software AG XTS Directory Server: why
Explanation	The database server failed to register with the Software AG XTS Directory Server. The error returned from the XTS layer is displayed as part of the message.
Action	Fix the error situation described by the XTS message or contact your software supplier.
INODSE5271	Failed to create the Software AG XTS Directory Server entries: why
Explanation	The server failed to create the necessary Software AG XTS Directory Server entries and the server startup failed. The reason for the failure is returned by the XTS layer.
Action	Please check that the service "Software AG XTS Directory Server" is running. If not, please start it. On Windows this can be done using the Control Panel. On UNIX please use the scripts provided (which are normally executed at system start). If the service was running when the error occurred, and the XTS message does not specify enough details to fix the problem, please contact your software supplier.
INODSE5272	Parameter setting for the Software AG XTS Directory Server failed: why
Explanation	The server failed to do the necessary parameter setting for the Software AG XTS Directory Server and the server startup failed. The reason for the failure is returned by the XTS layer.
Action	Fix the error situation described by the XTS message or contact your software supplier.

INODSE5283	Invalid parent field format for collation descriptor
Explanation	The format for the parent field of a collation descriptor is invalid. The only allowed parent formats are "wide" and "alphanumeric".
Action	Check the collation descriptor definition.
INODSE5287	Invalid collation locale s
Explanation	The locale name is misspelled or the locale is not supported.
Action	Check the spelling.
INODSE5300	Filename for database space container could not be determined
Explanation	It was not possible to determine the full filename for the specified database space.
Action	This is an internal error. Please contact your software supplier.
INODSE5309	Key id could not be changed, msg
Explanation	An internal error occurred changing a key value in the internal configuration store.
Action	Please contact your software supplier.
INODSE5310	Database name name could not be changed in the internal configuration store, msg
Explanation	Because of an internal error the internal configuration could not be changed.
Action	Please contact your software supplier.
INODSE5320	Database ID could not be determined, msg
Explanation	Internal error, while requesting database ID information.
Action	Contact your software supplier.
INODSE5321	Database name could not be determined, msg
Explanation	Internal error, while requesting database name information.
Action	Please contact your software supplier.
INODSE5334	Unable to get collator version for locale locale
Explanation	This is an internal error.
Action	Please contact your software supplier.

INODSE5335	Collation version does not match
Explanation	Most probably, a newer version of the ICU library has been installed and old data is not available In this case, all collating indexes must be rebuilt.
Action	Rebuild the collating index.
INODSE5336	Internal ICU error (error_text) occurred while producing collation key
Explanation	This is an internal error.
Action	Please contact your software supplier.
INODSE5337	Unable to determine server state
Explanation	This is an internal error.
Action	Please contact your software supplier.
INODSE5341	Database database name already exists
Explanation	This error can occur during database creation, or when trying to rename an existing database and a database with the same name already exists.
Action	Specify another name.
INODSE5343	External backup failed, reason: reason errcode
Explanation	The attempt to perform an external database backup failed due to the reason specified in the message.
Action	Correct the error indicated and retry the operation.
INODSE5344	External restore failed, reason: reason errcode
Explanation	A database restore with a connected external system failed due to the reason specified in the message.
Action	Correct the error indicated and retry the operation.
INODSE5345	External delete failed, reason: reason errcode
Explanation	The call to delete an external backup failed due to the reason given.
Action	Correct the error indicated and retry the operation.

INODSE5346	EMC request failed: text
Explanation	A call of EMC's SYMAPI failed for the given reason.
Action	Correct the error indicated and retry the operation.
INODSE5354	External backup configuration error, reason: reason
Explanation	Configuring the environment for an external backup failed.
Action	Correct the error indicated and retry the operation.
INODSE5358	Set version already running on this database
Explanation	The "Set version" operation is already running on this database.
Action	Wait for the "set version" operation to complete.
INODSE5359	Function is not permitted because of pending transactions
Explanation	The function cannot be processed because of pending global transactions.
Action	Start the Tamino server in normal mode and close the pending global transactions.
INODSE5360	Function is not permitted because the previous session was abnormally terminated
Explanation	The function cannot be processed because the previous session was abnormally terminated.
Action	Start the Tamino server in normal mode to do an autorepair from the abnormal termination.
INODSE5361	Downgrade to version version not supported
Explanation	This message can appear when trying to convert a database to a previous version, but the requested downgrade is not supported.
Action	No action required.
INODSE5402	Maximum number of users exceeded
Explanation	A new user was rejected due to internal reasons.
Action	You can force a memory dump with "inodba database=name trap=9228" for further analysis after reproducing the error.

INODSE5404	Insufficient temporary work space
Explanation	The temporary work space was too small to execute the requested function.
Action	Consider increasing the temporary workspace by adding locations with free space to the temporary working location.
INODSE5405	Insufficient temporary work space
Explanation	The temporary work space was too small to execute the requested function.
Action	Consider increasing the temporary workspace.
INODSE5406	Transaction internally aborted
Explanation	A transaction has been aborted due to internal reasons. All changes of this transaction have been undone.
Action	You can force a memory dump with "inodba database=name trap=9291" for further analysis after reproducing the error.
INODSE5407	Database is corrupt, invalid block block
Explanation	There are structural inconsistencies in the database. The database should not be used any longer.
Action	Restore the database from a backup copy and apply the log files. You can force a memory dump with "inodba database=name trap=9130" for further analysis after reproducing the error.
INODSE5408	buffer pool overflow
Explanation	The current load could not be processed because the buffer pool is too small.
Action	Consider increasing the buffer pool size or force a memory dump with "inodba database=name trap=9138" for further analysis after reproducing the error.
INODSE5410	Database is corrupt, data block damaged
Explanation	There are structural inconsistencies in the database. The database should not be used any longer.
Action	Restore the database from a backup copy and apply the log files. You can force a memory dump with "inodba database=name trap=9127" for further analysis after reproducing the error.

INODSE5411	Database is corrupt
Explanation	There are structural inconsistencies in the database. The database should not be used any longer.
Action	Restore the database from a backup copy and apply the log files. You can force a memory dump with "inodba database=name trap=9123" for further analysis after reproducing the error.
INODSE5416	Database is corrupt, physical structures damaged
Explanation	There are structural inconsistencies in the database. The database should not be used any longer.
Action	Restore the database from a backup copy and apply the log files. You can force a memory dump with "inodba database=name trap=9057" for further analysis after reproducing the error.
INODSE5417	Database is corrupt, allocation error detected
Explanation	There are structural inconsistencies in the database. The database should not be used any longer.
Action	Restore the database from a backup copy and apply the log files. You can force a memory dump with "inodba database=name trap=9058" for further analysis after reproducing the error.
INODSF1008	The location of the license file could not be found
Explanation	The Tamino Server requires a valid license file. The location of the license file could not be determined.
Action	Contact your software supplier.
INODSF1011	The license of Tamino has expired
Explanation	The licensing period of Tamino has expired.
Action	Please contact your software supplier for a renewal of your license.
INODSF1012	The version of Tamino and the version used in the license file do not match
Explanation	The Tamino product version and the version used in the license file must match.
Action	Use the license file that has been shipped with your product version.

INODSF1018	Database creation has failed due to license restrictions. Licensed database size is licsize MB, attempted dataspace container size is datasize MB.
Explanation	The dataspace size of a database is limited by the amount given in your current license.
Action	Create a database with a smaller dataspace size.
INODSF1020	Error error accessing the raw section section via mode
Explanation	Accessing the raw section failed due to an unexpected system response.
Action	Please consult your manufacturer's manual.
INODSF1021	Verification error on raw section section (structure level mismatch)
Explanation	An error occurred while verifying the structure level in the raw section management structure.
Action	Please contact your software supplier.
INODSF1022	Verification error on raw section section (wrong architecture byte)
Explanation	An error occurred while verifying the architecture byte in the raw section management structure.
Action	Please contact your software supplier.
INODSF1023	Verification error on raw section section (section management header)
Explanation	An error occurred while verifying the management header in the raw section management structure.
Action	Please contact your software supplier.
INODSF1024	Raw section section is not initialized
Explanation	The raw section is not initialized.
Action	Please initialize the raw section.
INODSF1062	Replacing the license file after expiration failed
Explanation	Replacing the license file after expiration failed.
Action	Provide a valid license to be able to start the server.

INODSF1180	The operating system is not specified within the license file
Explanation	Check operating systems specification in the license file.
Action	Verify that the license file is valid for the operating system used.
INODSF1250	Open of source (path) has failed due to an incompatible file or a compatibility mismatch
Explanation	The file could not be opened because it either does not have the expected compatibility level or a subsequent file extent does not match the previously opened one.
Action	Check that the correct file has been specified for the operation or if 2 physical file extents belong to each other.
INODSF1251	Internal error error occurred
Explanation	An internal error has caused the server to stop.
Action	Please contact your software supplier. Restart the server.
INODSF1254	Unexpected signal signal received in text index procedure call from thread thread
Explanation	An unexpected exception or signal has occurred.
Action	If the exception or the signal was asynchronous (i.e. no access violation etc.), repeat the operation.
INODSF1255	Index too deep
Explanation	The index structure exceeds the maximum levels of indexing supported.
Action	Please contact your software supplier.
INODSF1256	Internal error on doctype doctype: second error caused by failed recovery due to the following error: first error
Explanation	An error occurred on the specified doctype. While trying to undo the changes on the doctype, another error has occurred. The server must terminate in order to prevent the database from being corrupted.
Action	Restart the server.
INODSF1257	Log space full
Explanation	The server session has been abnormally terminated because there is no space left for logging.
Action	Provide space for logging and restart the server.

INODSF1259	Error closing a log space: error message
Explanation	The log space could not be closed properly. The server session is aborting.
Action	Try to fix the reason for the error. It is recommended to back up the database. Restart the server.
INODSF1260	Error on doctype doctype during rollback transaction: rspmsg
Explanation	An error occurred during the rollback of a transaction. The server must terminate in order to prevent the database from being corrupted.
Action	Restart the server.
INODSF1261	Assertion failed: assertion
Explanation	A coding error has occurred.
Action	Please inform your software supplier. Restart the server.
INODSF1262	Open of source (path) has failed due to an incorrect file type
Explanation	The file could not be opened because it does not have the expected type. It is possible that the file is internally corrupted. For example there is an index space with entirely binary zeroes in it.
Action	Check that the correct file has been specified for the operation.
INODSF1263	Error error number has occurred in SMP initialization.
Explanation	An internal error has occurred. The server has stopped.
Action	Please contact your software supplier.
INODSF1264	Setting the maximum number of resources to value has failed. Server stopped.
Explanation	The requested system resources were not available.
Action	Check your system configuration.
INODSF1265	Server already active
Explanation	There is another server running for the current database.
Action	Please contact your software supplier.

INODSF1266	Error error number during synchronization call in line line (address address)
Explanation	An internal error has occurred. The server has been stopped.
Action	Please contact your software supplier.
INODSF1267	SMP resource allocation failed with response rsp at line line
Explanation	An internal error has occurred. The server has been stopped.
Action	Please contact your software supplier.
INODSF1268	Error error number during synchronization call in line line
Explanation	An internal error has occurred. The server has been stopped.
Action	Please contact your software supplier.
INODSF1269	Increasing the number of resources by value has failed. Server stopped.
Explanation	The requested system resources were not available.
Action	Check your system configuration.
INODSF1270	Invalid value (value) found at location location
Explanation	An internal error has caused the server to stop.
Action	Please contact your software supplier. Restart the server.
INODSF1271	Invalid pointer (value) found at location location
Explanation	An internal error has caused the server to stop.
Action	Please contact your software supplier. Restart the server.
INODSF1272	Internal error error string occurred at location location
Explanation	An internal error has caused the server to stop.
Action	Please contact your software supplier. Restart the server.
INODSF1273	Invalid value (int value) found at location location
Explanation	An internal error has caused the server to stop.
Action	Please contact your software supplier. Restart the server.

INODSF1274	Internal error in block block number occurred at location location
Explanation	An internal error has caused the server to stop.
Action	Please contact your software supplier. Restart the server.
INODSF1275	Invalid value (int value) found on address address at location location
Explanation	An internal error has caused the server to stop.
Action	Please contact your software supplier. Restart the server.
INODSF1276	Invalid values (value 1, value 2) found on address address at location location
Explanation	An internal error has caused the server to stop.
Action	Please contact your software supplier. Restart the server.
INODSF1277	Invalid values (value1, value2) found at location location
Explanation	An internal error has caused the server to stop.
Action	Please contact your software supplier. Restart the server.
INODSF1278	Invalid value (value) found in block block number at location location
Explanation	An internal error has caused the server to stop.
Action	Please contact your software supplier. Restart the server.
INODSF1279	Invalid value (value) found on address address at location location
Explanation	An internal error has caused the server to stop.
Action	Please contact your software supplier. Restart the server.
INODSF1280	Internal error location-c1-c2 occurred
Explanation	An internal error has caused the server to stop.
Action	Please contact your software supplier. Restart the server.
INODSF1282	Received response rsp (intrsp) while loading function(s) for extension point extp
Explanation	Loading a function for an extension point failed.
Action	Please contact your software supplier.

INODSF1283	Internal communication initialization failed
Explanation	The server's internal communication could not be activated.
Action	Please contact your software supplier.
INODSF1284	Internal memory management could not be initialized
Explanation	The initialization of the server's memory management has failed.
Action	Please contact your software supplier.
INODSF1285	Temporary working space could not be allocated
Explanation	The allocation of the working space needed for server operation has failed.
Action	Please contact your software supplier.
INODSF1286	Buffer pool too small. At least minimum value bytes required.
Explanation	The defined buffer pool is too small for the server to start.
Action	Increase the buffer pool parameter and restart the server.
INODSF1287	Buffer pool too small to start the server (internal reason reason)
Explanation	The defined buffer pool is too small for the server to start.
Action	Increase the buffer pool parameter and restart the server.
INODSF1288	Server for this database already active
Explanation	There is already an active server for the same database or at least some resources of the previous server run have not been released yet.
Action	If there is no active server and you cannot determine which resources may cause the conflict, contact your software supplier.
INODSF1291	Not enough memory available to execute process
Explanation	The operating system did not have enough resources to run another process. Possible reasons are too many concurrently active processes or a too small swap/paging space.
Action	Please check the resource usage and the configuration of your computer.

INODSF1296	source (path) is corrupted at offset
Explanation	The data cannot be used.
Action	Please contact your software supplier.
INODSF1297	Creation of source (path) has failed
Explanation	The file could not be created at the specified location.
Action	Look for other error messages to find the reason for the failure.
INODSF1298	source (path) could not be opened: device type not supported
Explanation	An invalid device type was chosen.
Action	Choose a valid device type.
INODSF1299	Open of source (path) has failed due to operating system error errno
Explanation	The file could not be opened.
Action	Please consult the manufacturer's manual.
INODSF1300	Open of source (path) has failed due to an invalid structure
Explanation	The file could not be opened because it does not have the expected structure.
Action	Check if the file origin is the same machine architecture. If you cannot detect the error, please contact your software supplier.
INODSF1301	Open of source (path) has failed. Missing extents or wrong sequence of extents. Please check and retry.
Explanation	The file could not be opened because the sequence in which devices are given (e.g. tapes) is not correct or not all sequences required were specified.
Action	Specify all extents in the correct sequence.
INODSF1302	Open of log space (path) has failed because sequence of log spaces is incorrect
Explanation	The file could not be opened because the sequence in which log spaces are given (e.g. tapes) is not correct.
Action	Use the correct sequence.

INODSF1303	Open of source (path) has failed due to an incorrect file type
Explanation	The file could not be opened because it does not have the expected type.
Action	Check that the correct file has been specified for the operation.
INODSF1305	Open of source has failed due to invalid or missing internal information
Explanation	The file could not be opened because its location was not specified.
Action	Check the database parameters.
INODSF1306	Internal error location occurred: Please report r t h c
Explanation	An internal error has caused the server to stop.
Action	Please contact your software supplier and report the values given with the message. Restart the server.
INODSF1307	Database database name not registered
Explanation	The specified database has not been properly created or the internal entries of this database have been destroyed.
Action	Create the database again.
INODSF1308	Executable name not found
Explanation	The system could not find the executable object specified.
Action	Please check your installation.
INODSF1309	System error errno occurred during the creation of another process
Explanation	The system could not create another process. You might have exceeded the amount of available memory or the maximum number of processes.
Action	Please increase the amount of virtual memory available, or increase the number of possible processes. Please refer to the manual of your operating system for details.
INODSF1310	Invalid value (value) found at location location
Explanation	An internal error has caused the server to stop.
Action	Please contact your software supplier. Restart the server.

INODSF1311 **Error errno has been signalled during the execution of an asynchronous I/O on log space for id**

Explanation An asynchronous I/O has failed due to an operating system error.

Action Check for problems with the device. Check whether the device is off-line or read-only. In the case of a logical volume, try to access all of its physical devices by operating system commands. Check the system log file for appropriate error messages.

INODSF1312 **Error errno has been signalled during the execution of an asynchronous I/O on journal space for id**

Explanation An asynchronous I/O has failed due to an operating system error.

Action Check for problems with the device. Check whether the device is off-line or read-only. In the case of a logical volume, try to access all of its physical devices by operating system commands. Check the system log file for appropriate error messages.

INODSF1313 **Error errno has been signalled during the execution of an asynchronous I/O for id**

Explanation An asynchronous I/O has failed due to an operating system error.

Action Check for problems with the device. Check whether the device is off-line or read-only. In the case of a logical volume, try to access all of its physical devices by operating system commands. Check the system log file for appropriate error messages.

INODSF1317 **Semaphore could not be created because system limit was reached**

Explanation The system limit for semaphores was reached.

Action Increase the number of semaphores supported by the operating system.

INODSF1319 **Unexpected signal signal received**

Explanation An unexpected exception or signal has occurred.

Action If the exception or the signal was asynchronous (i.e. no access violation etc.), repeat the operation.

INODSF1321 **Error opening sequential file: error**

Explanation An error occurred when opening a sequential file.

Action Correct the reason for the sequential file open failure and retry the operation.

INODSF1322	Latest savepoint not found
Explanation	Internal information about the latest savepoint could not be found.
Action	Contact your software supplier.
INODSF1323	Path or type of log location not found
Explanation	The internal information for the log location, path or type could not be found.
Action	Contact your software supplier.
INODSF1324	Processing information for a log space is undefined
Explanation	A previous server session process was killed during restore/recover.
Action	Use a later backup if possible or use a recover until a timestamp that is less than the creation date of the log space in question.
INODSF1325	Signal signal number caught. Termination initiated.
Explanation	An unexpected signal was caught. This leads to an immediate termination.
Action	If the signal cannot be explained by the environment (operator initiated or operating system initiated signal), please contact your software supplier.
INODSF1326	database creation not completed
Explanation	The database creation is not finished, or terminated unexpectedly, leaving the database files on disk.
Action	Check if the creation is still in progress. If so, wait until completed. If not, clean up and restart the database creation.
INODSF1328	Unexpected buffer pool error
Explanation	An unexpected error has occurred when trying to access the buffer pool.
Action	Repeat the action. If it still fails, contact your support center.
INODSF1329	Unexpected error getting a page from the buffer pool
Explanation	An unexpected error has occurred when trying to get a page from the buffer pool. The operation was cancelled.
Action	Contact your software supplier.

INODSF1330	An unexpected I/O error has occurred
Explanation	An unexpected I/O error has occurred. The operation was cancelled.
Action	Contact your software supplier.
INODSF1331	Unable to extend database space. Reason: ret_code.
Explanation	The specified error has occurred while trying to extend a database space.
Action	Determine the reason for the error code, and retry the operation.
INODSF1332	Index chain is corrupt
Explanation	Corruption has been found for an index on a doctype.
Action	The indexes have to be rebuilt. To rebuild the indexes, choose the "Check and Repair" function for the database in the Tamino Manager, then retry the operation.
INODSF1334	No index summary in input file
Explanation	The input file does not have the required index definitions.
Action	Ensure that the correct input file has been specified.
INODSF1335	No streams available
Explanation	Multi-file mode is being used but no streams are available.
Action	Please contact your software supplier.
INODSF1336	Cannot handle given extent type
Explanation	It is not possible to handle the type of extent specified.
Action	This is an internal error. Please contact your software supplier.
INODSF1337	Shared memory segment of server exists
Explanation	At least one shared memory segment of the server already exists.
Action	Check if the server is already active. If not retry the operation. If the error persists remove the existing shared memory segment and retry.
INODSF1341	Error on temporary storage space
Explanation	An error has occurred when trying to write to a temporary storage space.
Action	Ensure that there are no errors on the device where temporary space is to be used and retry the operation.

INODSF1342	No space for index space
Explanation	There are not enough system resources available for the index space.
Action	Allocate sufficient resources to allow the operation to succeed.
INODSF1343	Error opening data space
Explanation	An error has occurred while opening the data space.
Action	Correct the error and retry the operation.
INODSF1344	Error opening journal space
Explanation	An error has occurred while opening the journal space.
Action	Correct the error and retry the operation.
INODSF1345	Internal error: Provided memory not sufficient
Explanation	An area in memory used as working space was defined too small.
Action	Please contact your software supplier.
INODSF1346	No input slot could be allocated
Explanation	An internal error occurred preventing an input slot being allocated for an index.
Action	Please contact your software supplier.
INODSF1347	No space for preserved slot
Explanation	An internal error occurred preventing a preserved slot being allocated for an index.
Action	Please contact your software supplier.
INODSF1348	Invalid database space
Explanation	An internal error occurred.
Action	Please contact your software supplier.
INODSF1349	Error while reading index
Explanation	An internal error occurred while reading the index.
Action	Please contact your software supplier.

INODSF1350	No more temporary space
Explanation	Temporary space has been exhausted.
Action	Ensure that there is enough free space to allocate the required temporary space.
INODSF1351	No slot available
Explanation	An internal error occurred when trying to write to a slot.
Action	Please contact your software supplier.
INODSF1353	More than one block to be written (number)
Explanation	A disk write failed because more than one block was requested to be written. This is an internal error.
Action	Please contact your software supplier.
INODSF1354	Utility not permitted to run
Explanation	This utility is currently not permitted to run.
Action	Wait until the database is available again.
INODSF1355	Internal sort error
Explanation	An internal sort error has occurred.
Action	Please contact your software supplier.
INODSF1356	Internal error occurred: utility entry not found
Explanation	An internal error occurred.
Action	Please contact your software supplier.
INODSF1359	Invalid value (long value) found on address address at location location
Explanation	An internal error has caused the server to stop.
Action	Please contact your software supplier. Restart the server.
INODSF1360	The tape device is not responding, please ensure that a tape is mounted
Explanation	Response EINVAL was returned by the operating system. The most likely cause is that no tape has been mounted.
Action	Ensure that a tape is mounted and the device is switched on.

INODSF1362	Journal space too small (minimum required size is size MBytes)
Explanation	The journal space is not sufficient for the Tamino server.
Action	Create a database with a larger journal space.
INODSF1363	Journal overflow. Server cannot proceed.
Explanation	The journal space was insufficient. The current server session has to be terminated.
Action	Check if more journal space can be provided. Restart the server.
INODSF1364	Log space not found for savepoint savepoint
Explanation	A log space entry for the given savepoint could not be found.
Action	Contact your software supplier.
INODSF1366	License file not found at path
Explanation	Your license is not at the expected place.
Action	Please move the license file to the place indicated.
INODSF1367	License file not valid (error error)
Explanation	Your license is not valid. It is incomplete or has been edited.
Action	Please acquire a correct license file from your software supplier.
INODSF1369	Internal licensing error error
Explanation	There was an internal error in the processing of the licensing information.
Action	Please contact your software supplier.
INODSF1373	Database database name not registered
Explanation	The specified database has not been properly created or the internal entries of this database have been destroyed.
Action	Create the database again.
INODSF1431	Error during autorepair. The database is inconsistent.
Explanation	The last server session terminated abnormally. The database autorepair has failed. The database cannot be used.
Action	Send the journal space and all other error information to your software supplier. Then recover your database from the last backup.

INODSF1432	Start of autorepair information cannot be determined
Explanation	The last server session terminated abnormally. The database autorepair has failed. The database cannot be used.
Action	Send the journal space and all other error information to your software supplier. Then recover your database from the last backup.
INODSF1433	Journal overflow during database autorepair. The database is inconsistent.
Explanation	The last server session terminated abnormally. The database autorepair has failed. The database cannot be used.
Action	Send the journal space and all other error information to your software supplier. Then recover your database from the last backup.
INODSF1436	Terminated with errors
Explanation	A previous error has caused the termination of the process.
Action	Please check the event log for detailed information about previous errors that have caused the process to terminate.
INODSF1454	Internal error occurred: location thread module function. Server stopped.
Explanation	An internal error occurred.
Action	Please contact your software supplier and provide the message text.
INODSF1688	Shared memory of size size MB is not available (internal error errno)
Explanation	The server needs a shared memory of the specified size. However, this shared memory could not be created.
Action	View the previous message which describes the operating system error in detail. Check the manufacturer's manual. Consider increasing the operating system limits on shared memory size or decreasing the needs of the server by decreasing parameters such as buffer pool size.
INODSF2002	Error during replication processing, replication stopped
Explanation	Replication cannot be continued due to a previous error during replication processing
Action	If the master database is lost, the Reset Replication function can be used to convert the database for usage as a substitution. In any other case a new backup from the master database should be used to recreate the replication database.

INODSF2005	Internal replication error error/error info detected when processing data of server session session number - block block number, location record number
Explanation	The data required for replication processing could not be supplied by the master database.
Action	Please check that the log space has not yet been deleted by creating new backups of the master database. If the log space still exists keep the error information and contact your software supplier.
INODSF2075	Failure writing to tape device, please ensure that a tape is loaded
Explanation	The response EFAULT was returned by the operating system. The most likely cause is that no tape is loaded in the device.
Action	Ensure that a tape is loaded and the device is switched on.
INODSF2116	Internal command recovery failure (rsp1) on doctype doctype, caused by: rsp2
Explanation	A internal recovery failed and therefore the server cannot resolve a rollback. The server must terminate in order to prevent the database from being corrupted.
Action	Restart the server.
INODSF2119	Invalid compatibility level: DBMS complev1, backup file complev2 (filename)
Explanation	An invalid compatibility level of DBMS and backup file has been detected.
Action	Please use a DBMS version with the same compatibility level as the backup file, or use a backup file with the compatibility of the DBMS.
INODSF2120	IO [mod-line] error error
Explanation	An unexpected error occurred in an I/O function.
Action	Please contact your software supplier and provide the message text.
INODSF2122	Invalid compatibility level: DBMS complev1, database complev2
Explanation	An invalid compatibility level has been detected.
Action	Please contact your software supplier.
INODSF2123	CF [mod-line] error error
Explanation	An internal configuration error occurred.
Action	Please contact your software supplier and provide the error message text.

INODSF2128	Invalid data block detected at block blknr (doc doc, cont cont)
Explanation	An invalid data block was detected which refused a database backup. At least one collection has a data fault.
Action	Repair the database with restore/recover from the latest good backup.
INODSF2188	Failed to enter the new compatibility level in the internal configuration store
Explanation	The new compatibility level could not be entered in the internal configuration store.
Action	Please contact your software supplier and provide the message text.
INODSF2227	Internal error error during flush operation
Explanation	The write operation of the internal buffer cache to disk failed. A detailed error message precedes this message.
Action	Analyse the error code, maybe check your disks and restart server.
INODSF2234	SMP resource allocation failed at module[line] because of a lack of available memory
Explanation	The allocation of memory failed. The reason for that is either that the pagefile is too small or that the available virtual memory is exhausted.
Action	Increase the size of the pagefile. If that doesn't help contact your software supplier.
INODSF2235	Database key mismatch, required keyreq, present keypres
Explanation	The index space has an unexpected key within the first index space. The database space obviously comes from another database.
Action	Check the index container spaces.
INODSF2266	Cannot start Tamino utility of version due to system error errno
Explanation	Submitting a Tamino utility as a subprocess failed due to an operating system error.
Action	Analyze the system error and check the installed version.
INODSF2280	Unexpected I/O error (io operation) on database_space
Explanation	An I/O failed and the process cannot continue.
Action	View any previous or related system error messages and analyse why the I/O operation on the given database space could have failed.

INODSF2284	Error errno (errtxt) has been signalled during the execution of an asynchronous I/O on database space for id
Explanation	A severe read/write error has occurred.
Action	Analyse the operating system error.
INODSF2286	Internal replication error error/error info detected when processing data of mass load recovery input filename
Explanation	The mass load input required for replication processing could not be supplied by the master database.
Action	Please check that the recovery input file has not yet been deleted by creating new backups of the master database. If the log space still exists, keep the error information and contact your software supplier.
INODSF2287	Internal error error detected when processing mass load recovery input with key key
Explanation	The recovery of a mass load activity failed.
Action	Please contact your software supplier.
INODSF2288	Cannot grant server synchronization semaphore
Explanation	The server synchronization semaphore cannot be granted.
Action	Check if the semaphore already exists and another process has granted it, or if the permission settings of the semaphore do not allow access.
INODSF2294	Filename for database space container could not be determined
Explanation	It was not possible to determine the full filename for the specified database space. It was obviously missing in the internal configuration store.
Action	This is an internal error. Please contact your software supplier.
INODSF2296	Internal error interr on database space (reason)
Explanation	The writing of relevant information to the given database space (Log, Journal) failed due to an internal error.
Action	Check the location where the database space resides and also analyse the previously given operating system error message.

INODSF2299	Internal error number reading dbspace at block blocknumber
Explanation	Reading the given database block resulted in an internal I/O error.
Action	No action required.
INODSF2306	License timer interval too short
Explanation	The license timer detected an unexpected system data and time.
Action	Please contact your software supplier.
INODSF2307	Invalid combination of customer/partner information found in the license file
Explanation	An invalid combination of customer/partner information was found in the license file.
Action	Please contact your software supplier to extend your license.
INODSF2308	Product usage found in the license file is not allowed for an unlimited license
Explanation	The product usage found in the license file is only allowed for a time-limited license.
Action	Please contact your software supplier to correct your license.
INODSF2309	Server abort because of license expiration
Explanation	The grace period after license termination has expired. The server did an abort.
Action	Please contact your software supplier to extend your license.
INODSF2334	The license for name with ID id has expired, server aborts now
Explanation	The license has expired. The server has stopped operation (abort). Operation can be continued upon restart with a renewed license key.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager, then restart the server.
INODSF2335	The license for customername sub-licensed by partnername with ID partnerid has expired, server aborts now
Explanation	The license has expired. The server has stopped operation (abort). Operation can be continued upon restart with a renewed license key.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager, then restart the server.

INODSF2336	The license for customername with ID customerid sub-licensed by partnername has expired, server aborts now
Explanation	The license has expired. The server has stopped operation (abort). Operation can be continued upon restart with a renewed license key.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager, then restart the server.
INODSF2337	The license for customername with ID customerid sub-licensed by partnername with ID partnerid has expired, server aborts now
Explanation	The license has expired. The server has stopped operation (abort). Operation can be continued upon restart with a renewed license key.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager, then restart the server.
INODSF2338	Internal error number writing dbspace at block blocknumber
Explanation	Cannot write database block due to an internal I/O error.
Action	Analyse the error number and check the database.
INODSF2339	XTS refuses database connection, reason reason_code
Explanation	It is not possible to reach the database via XTS.
Action	Switch on XTS_TRACE, repeat the function and check the trace file.
INODSF4256	Structure level mismatch on database
Explanation	The version of the server differs from the version of the utility.
Action	Run the correct version of the utility or server, or convert the database.
INODSF4258	The database type and/or version does not match the backup
Explanation	This operation can only be performed against a database of the same type and/or version as the backup.
Action	Ensure that the utility is being run against the correct type and version of database.
INODSF4262	Database server mismatch: present db_name
Explanation	A mismatch occurred between the database server parameter and the database server name of the assigned index space.
Action	Ensure that the correct database name is supplied.

INODSF5331	Version version is not installed
Explanation	The required software version is not installed.
Action	please contact your software supplier.
INODSF5332	Invalid structure level strlev
Explanation	An invalid structure level has been detected.
Action	Please contact your software supplier.
INODSI1004	Stop of database successfully initiated - server is going down now
Explanation	All database activities are terminated - the server process is about to terminate.
Action	No action required.
INODSI1010	Backup file from older version version
Explanation	Indicates that the input backup file is from a previous version.
Action	No action required.
INODSI1013	Read-only database, word fragment index cannot be created
Explanation	Read-only database, no database update permitted.
Action	Ensure that the database upon which you wish to carry out the operation is write-enabled.
INODSI1016	Initializing journal space
Explanation	When the database first starts, the entire journal space must be formatted with binary zeroes.
Action	Wait until the operation finished: This could take several seconds or even several minutes if the file is very large.
INODSI1019	Database of older version version
Explanation	The database used for restore is from a previous version.
Action	No action required.

INODSI1034	The Tamino Server that is provided with this Tamino Developer Edition may be used for educational purposes only. For production purposes, you must use the Tamino Server that is included in the Tamino Server Edition.
Explanation	This is an informational message
Action	None
INODSI1039	Function function executed
Explanation	The specified function was executed.
Action	Information only, no action required.
INODSI1041	Starting mode database backup
Explanation	Indicates the start of database backup processing.
Action	No action required.
INODSI1044	Starting restore database using type backup from timestamp
Explanation	Indicates the backup that was used to start restore processing.
Action	No action required.
INODSI1049	Starting mode restore of database
Explanation	Indicates that the restore processing has been started.
Action	No action required.
INODSI1059	The time-limited license for the server has expired, switched to an unlimited Community Edition license
Explanation	The time-limited license for the server has expired. The server automatically switched to an unlimited Community Edition license. Some product features may no longer be available.
Action	No action required.
INODSI1110	Waiting time for count users to start a new transaction - min: min seconds, max: max seconds, average: average seconds seconds
Explanation	This message is used to give information about waiting times for users who want to open a new transaction while other users have not yet finished their transaction. This synchronization of all users who do not have an open transaction is required at the end of a backup.
Action	No action required.

INODSI1113	No real modified data for Incremental Backup
Explanation	There is no modification in the database, so an incremental backup will save no new data. Nevertheless a backup with only global data will be created.
Action	No action required.
INODSI1114	Incremental backup from date deleted
Explanation	A full backup to be deleted causes the deletion of dependent incremental backups as well.
Action	No action required.
INODSI1146	Archive Log Location has been reset
Explanation	An Archive Log Location will not be used.
Action	None.
INODSI1147	path set as location name
Explanation	A path or a set of paths has been set for the specified location type.
Action	None.
INODSI1177	Database database name Session session number (name modifier version on system info, process ID pid)
Explanation	This is an informational message.
Action	No action required.
INODSI1178	Database database name Replication Session (name modifier version on system info, processID pid)
Explanation	The server started for a replication database.
Action	No action required.
INODSI1179	Database database name Read-Only Session (name modifier version on system info, process ID pid)
Explanation	This is an informational message.
Action	No action required.

INODSI1183	size MB empty data space found
Explanation	The amount of empty data space assigned to specific doctypes that can be returned to global free space
Action	None.
INODSI1184	No empty data space found
Explanation	Empty data space that can be returned to global free space does not exist
Action	None.
INODSI1188	Creating a temporary backup for free space defragmentation
Explanation	A temporary backup is created to be used for defragmenting free space
Action	Wait until the reorganization is completed.
INODSI1190	size MB empty data space converted to global free space
Explanation	The amount of empty data space that was de-allocated from specific doctypes and returned to global free space.
Action	None.
INODSI1191	Free data space in database is size MB (percent %)
Explanation	Information about the amount of global free data space after reorganization.
Action	None.
INODSI1193	Free space less than percent %, no free space defragmentation and data space shrinking
Explanation	The reorganize function converted empty space to global free space, but the amount of free space is less than a minimum value considered as worthwhile performing a free space defragmentation and data space shrinking.
Action	None, if you are satisfied with the minimum value for free space defragmentation and data space shrinking. In any other case, use the reorganize function with a different minimum value.
INODSI1195	Defragmenting free space
Explanation	A temporary backup is used for restore to defragment free space.
Action	Wait until the reorganization is completed.

INODSI1196	Shrinking data space
Explanation	The size of the data space is reduced by de-allocating free space.
Action	Wait until the reorganization is completed.
INODSI1197	No free data space found
Explanation	Free data space does not exist.
Action	None.
INODSI1246	Read-only database, word fragment index cannot be removed
Explanation	The database is readonly, so no database update is permitted.
Action	Ensure that the database upon which you wish to carry out this operation is write-enabled.
INODSI1327	Database stopped
Explanation	The database has been stopped.
Action	No action required.
INODSI1371	sufficient space in locations, continue
Explanation	Now there is sufficient space on the location where the file was waiting for, the operation now continues
Action	Now there is a subsequent file extent
INODSI1384	Setting of parname=parval
Explanation	no description available
Action	no action required
INODSI1417	database database name at structure level for version version
Explanation	This informational message states the structure level of the database.
Action	No action required.
INODSI1420	Dump file at version: vers, level level
Explanation	This informational message states the version and level of the dump file.
Action	Select the version displayed.

INODSI1451	Creation of word fragment index started
Explanation	The creation of the word fragment index has started.
Action	No action required.
INODSI1452	Server session session number started
Explanation	The server started successfully.
Action	No action required.
INODSI1453	Internal event event has occurred
Explanation	This message indicates a certain event in the server processing. It is not relevant to the user.
Action	No action required.
INODSI1456	The Tamino Server that is provided with the Tamino Developer Edition may be used for test purposes only. For production purposes, you must use the Tamino Server that is included in the Tamino Server Edition.
Explanation	This is an informational message.
Action	Use the correct Tamino Server.
INODSI1457	End of tape tape - rewinding
Explanation	The tape is being rewound.
Action	No action required.
INODSI1458	End of diskette path
Explanation	The diskette is full.
Action	No action required.
INODSI1459	Log space of server session session number from time opened
Explanation	The log space of the specified server session has been opened.
Action	No action required.

INODSI1460	Log space of server session session number completed
Explanation	The log space of the specified server session has been completed.
Action	No action required.
INODSI1463	Database 'database_name' accessed online
Explanation	The specified database has been accessed online.
Action	No action required.
INODSI1464	Database 'database_name' accessed offline
Explanation	The specified database has been accessed offline.
Action	No action required.
INODSI1466	Creation of database space space no (location name) has successfully finished
Explanation	The specified database space has been created.
Action	No action required.
INODSI1467	Tamino name modifierversion on system info
Explanation	This is a generic message used to identify an activity.
Action	No action required.
INODSI1468	No index found
Explanation	No index found.
Action	No action required.
INODSI1469	The database server is active on a remote node
Explanation	This is an informational message.
Action	No action required.
INODSI1470	Database spaces for database db_name have been created
Explanation	The database spaces for a database server have been successfully created. The next step of database creation will be restoring the initial contents of the database.
Action	Restore the initial contents of the database.

INODSI1471	Database db_name has been deleted
Explanation	The database with the given name has been successfully deleted.
Action	No action required.
INODSI1474	Read-only database db_name , startup at startup
Explanation	This message shows the time at which the database was started in read-only mode.
Action	No action required.
INODSI1475	Database db_name, startup at startup
Explanation	This message shows the time at which the database was started.
Action	No action required.
INODSI1480	Log space of server session session number processed until time
Explanation	All information generated before the given end timestamp of the log space of the specified server session was processed.
Action	No action required.
INODSI1481	Log space of server session session number skipped
Explanation	The log space of the specified server session was not processed because it contains only information generated after the given end timestamp.
Action	No action required.
INODSI1484	No log space information found
Explanation	The initial backup was used for restore, and no log space of another session exists.
Action	No action required.
INODSI1485	Checking finished. No inconsistencies found.
Explanation	The check and repair database action has finished.
Action	No action required.
INODSI1486	Log space of server session session number extent extent number archived
Explanation	A log space extent has been copied to the archive location.
Action	No action required.

INODSI1487	The backup tape from time has been unregistered
Explanation	The information about the availability of the given backup tape has been removed.
Action	The tape may be removed from the archive.
INODSI1488	Previous server session aborted when recovering session session number
Explanation	A previously started restore/recovery run did not complete the recovery phase.
Action	See the instructions within subsequent messages.
INODSI1489	Log space data processing end time stamp is time
Explanation	This is a progress message about the aborted recovery run or an abort of replication processing.
Action	In the case of a recovery run, the information can be used to start a recover until.
INODSI1490	Continuing server startup will disable subsequent backups
Explanation	When the server startup is continued, backups done later than the used one will become invalid.
Action	No action required.
INODSI1491	Due to an unexpected problem, Restore and/or Recover was not successful. Please re-execute the Restore and/or Recover now to ensure data integrity.
Explanation	For reasons stated in the job log, the Restore and/or Recover failed to execute properly. Depending on the reason for the abort, either "restore without recover" or "recover until" can be used to recover your data.
Action	If the reason for the initial recovery abort was a missing or corrupted log space, use "restore without recover" or "recover until".
INODSI1492	Subsequent backups disabled
Explanation	Backups older than the one used for the aborted recovery run are invalid now.
Action	No action possible.
INODSI1493	Tamino server successfully started in read-only mode
Explanation	This is an informational message.
Action	No action required.

INODSI1494	Destruction of word fragment index started
Explanation	Destruction of word fragment index started
Action	No action required
INODSI1495	Creation of word fragment index successfully finished
Explanation	Creation of the word fragment index successfully finished.
Action	No action required
INODSI1496	Destruction of word fragment index successfully finished
Explanation	Destruction of the word fragment index successfully finished
Action	No action required
INODSI1532	referential constraint name dropped (primary primary, foreign foreign)
Explanation	The specified referential integrity constraint has been dropped.
Action	None.
INODSI1535	file file refreshed
Explanation	The specified file has been refreshed.
Action	None.
INODSI1550	function not permitted, referential constraint defined
Explanation	The function not permitted because a referential constraint is defined.
Action	None.
INODSI1631	Autorepair completed without errors
Explanation	The autorepair from the crash of the previous server session was successful.
Action	The database can now be used.
INODSI1632	Recovery terminated successfully
Explanation	The recovery has processed all log spaces. All updates have been re-applied.
Action	The server can now be restarted.

INODSI1634	Successful completion
Explanation	The action has completed without errors.
Action	No action required.
INODSI1635	Crash dump of database finished
Explanation	The crash dump is complete.
Action	No action required.
INODSI1636	Tamino server successfully started
Explanation	This is an informational message.
Action	No action required.
INODSI1637	Skipping recovery terminated successfully
Explanation	The operation of skipping the recovery has terminated successfully. The update of the log space information has been completed.
Action	The server can now be restarted.
INODSI1691	Mass load recovery files archived
Explanation	The mass load recovery files have been copied to the archive location.
Action	No action required.
INODSI1732	Calculated RESTART point - BLOCK=block,CHECKPOINT=chkpt
Explanation	Recovery has restarted from the position shown.
Action	No action required.
INODSI1986	no file protection enabled
Explanation	File protection is not enabled
Action	No action required.
INODSI1988	PID pid
Explanation	Process ID.
Action	None.

INODSI2003	Replication of server session session number suspended replication data processed until timestamp
Explanation	Replication processing is suspended due to a server shutdown request of the replication database.
Action	No action required.
INODSI2006	No replication data for server session session number
Explanation	No modifications have been made for a server session on the master database.
Action	No action required.
INODSI2007	Replication of server session session number from timestamp started
Explanation	The replication processing has started to process the log space data of the specified server session of the master database.
Action	No action required.
INODSI2008	Replication of server session session number completed
Explanation	The server completed replication of a master database's server session
Action	No action required.
INODSI2009	Replication of server session session number resumed using replication data from timestamp
Explanation	The server continued replication processing after replication database startup.
Action	No action required.
INODSI2010	Server session session number replicated until time stamp
Explanation	This is the current replication status of the database.
Action	No action required.
INODSI2011	Starting replication using data from database master dbname
Explanation	Replication processing has started. The master database must be active to supply replication data.
Action	No action required.

INODSI2012	Initial server session session number for new replication database
Explanation	A replication database is started for replication the first time.
Action	No action required.
INODSI2017	Updating backup generations
Explanation	Older backups are being removed if the number of backup generations has been exceeded.
Action	No action required.
INODSI2018	Using hostname as host name for the Software AG XTS Directory Server entries
Explanation	The specified hostname has been assigned to the server property "server host name". This name will be registered in the Software AG XTS Directory Server as the host where the database is located.
Action	No action required.
INODSI2021	The following file type file was not deleted: file name
Explanation	In the case of abnormal server terminations, log and dump files will be written. To be able to analyze several problems, these files could be helpful and will not be deleted. Be aware that dump files could be very large.
Action	It might be useful to keep the dump and log files for further examination. If you want to generate a new database in the same location you should move those files to a different location by hand.
INODSI2040	File 'name' copied to directory
Explanation	This is an informational message.
Action	No activity required.
INODSI2044	Infofile 'path' created
Explanation	This is an informational message.
Action	No action required.
INODSI2074	Corrupted block repaired on space
Explanation	Due to a previous crash the latest written block may be corrupted (in the journal or log). In some cases this can be detected and repaired.
Action	Check if the previous session was abnormally aborted. Only in this case should this message appear.

INODSI2091	Process can make use of 3GB virtual address space
Explanation	The process can make use of 3GB virtual address space.
Action	No action required.
INODSI2100	Web server configuration changed, server server notified
Explanation	The web server configuration changed and the server was notified.
Action	No action required.
INODSI2115	Execution continues
Explanation	This message is displayed by debug-enabled executables if they have been selected for debugging.
Action	No action required.
INODSI2146	Replication of server session session number resumed using replication data from timestamp. Simultaneous query permitted.
Explanation	The server continued replication processing after replication database startup.
Action	No action required.
INODSI2148	At least one replication database allows simultaneous query
Explanation	The replication master writes additional locking information to the log space. A replication database with 'Simultaneous Query' enabled may be accessed with queries while it replicates updates.
Action	No action required.
INODSI2149	No replication databases allow simultaneous query
Explanation	The replication master does not write additional locking information to the log space. A replication database with 'Simultaneous Query' enabled cannot process queries while replicating updates of this session.
Action	No action required.
INODSI2150	Database database name set to replication type with simultaneous query
Explanation	If at least one replication database is defined with 'simultaneous query' the master database writes additional locking information to the log space. If this replication database is the first of this kind, the master switches to a new session.
Action	No action required.

INODSI2151	Database database name set to replication type without simultaneous query
Explanation	If no replication database is defined with 'simultaneous query' the master database does not write additional locking information to the log space. If replication database mentioned is the last of that kind, the master switches to a new session
Action	No action required.
INODSI2154	Replication of server session session number from timestamp started. Simultaneous query permitted.
Explanation	The replication processing has started to process the log space data of the specified server session of the master database.
Action	No action required.
INODSI2158	Backup from backup_date deleted
Explanation	After backup, the number of backup generations is updated, i.e older backups are removed. For further information, please refer to the documentation of the server parameter "number of backup generations".
Action	No action required.
INODSI2166	Initial backup removed
Explanation	After backup, the number of backup generations is updated, i.e older backups are removed. For further information, please refer to the documentation of server parameter "number of backup generations".
Action	No action required.
INODSI2190	Doctype doctype has been loaded
Explanation	The specified doctype has been successfully loaded.
Action	No action required.
INODSI2196	Connection to master database master dbname reestablished
Explanation	The replication database obtained new replication data from its master database.
Action	No action required.

INODSI2199	Replication data of session session was generated with different update or hotfix level of Tamino version version: update level update, hotfix number hotfix
Explanation	At the master database node a new update of a Tamino version was installed.
Action	Install the same update of the Tamino version at the replication database node.
INODSI2239	The backup tape from initial savepoint has been unregistered
Explanation	The information about the availability of the initial backup tape has been removed.
Action	The tape may be removed from the archive.
INODSI2259	Creating / deleting database process active, wait for continue
Explanation	Another job which creates or deletes a database is active on the current node. View running jobs for more information.
Action	Wait until this task has been completed. You should not wait longer than a couple of seconds.
INODSI2267	Convert database to version version
Explanation	The database will be converted to the version displayed.
Action	No action required.
INODSI2300	Keep backup file filename
Explanation	The backup file was not deleted because it was selected to be kept by the user.
Action	Keep in mind that there is still a backup file occupying disk space.
INODSI2310	Licensed for name with ID id
Explanation	Display customer/partner information from the license file.
Action	No action required.
INODSI2311	Licensed for customername sub-licensed by partnername with ID partnerid
Explanation	This is a display of customer/partner information from the license file.
Action	No action required.

INODSI2312	Licensed for customername with ID customerid sub-licensed by partnername
Explanation	This is a display of customer/partner information from the license file.
Action	No action required.
INODSI2313	Licensed for customername with ID customerid sub-licensed by partnername with ID partnerid
Explanation	This is a display of customer/partner information from the license file.
Action	No action required.
INODSI2314	Licensed for name with ID id, license expires on date
Explanation	Display customer/partner and expiration information from the license file.
Action	No action required.
INODSI2315	Licensed for customername sub-licensed by partnername with ID partnerid, license expires on date
Explanation	This is a display of customer/partner and expiration information from the license file.
Action	No action required.
INODSI2316	Licensed for customername with ID customerid sub-licensed by partnername, license expires on date
Explanation	This is a display of customer/partner and expiration information from the license file.
Action	No action required.
INODSI2317	Licensed for customername with ID customerid sub-licensed by partnername with ID partnerid, license expires on date
Explanation	This is a display of customer/partner and expiration information from the license file.
Action	No action required.
INODSI2343	Backup created with backup key 'backupkey' (from)
Explanation	The identification of the last created backup is displayed.
Action	No action required.

INODSI2344	backup key 'backupkey' (from)
Explanation	This is a display of backup information.
Action	No action required.
INODSI2345	backup key 'backupkey' (initial backup)
Explanation	This is a display of backup information.
Action	No action required.
INODSI2346	Deleting disabled backup from backup_date
Explanation	A disabled backup file is being deleted.
Action	No action required.
INODSI3469	Dataset dsn created on date
Explanation	The dataset was created on the specified date.
Action	No action required.
INODSI5263	Restoring pending transactions
Explanation	Pending global transactions are being restored during the server startup processing.
Action	No action required.
INODSI5270	Use parameter "param" to force server registration
Explanation	The server could not register with the XTS directory service, because an entry for the server is already present. If this entry is no longer necessary the specified parameter can be used to overwrite the existing entry.
Action	Set the specified parameter to YES to force server registration.
INODSI5282	Overwriting Software AG XTS Directory Server entries
Explanation	The Software AG XTS Directory Server entries already existed. They are overwritten.
Action	No action required.
INODSI5286	New block allocations for database
Explanation	There were container size/blocksize correlations which require new allocations for all files in the database.
Action	No action required.

INODSI5299	Data space container, file file name removed
Explanation	The database space with the qualified type and name has been removed from the file system.
Action	No action required.
INODSI5339	Log space of server session session number from different version - recovery stopped
Explanation	The next log space to be processed was created by another program version.
Action	See the product documentation for further information about migration between program versions.
INODSI5352	Preparing for external backup
Explanation	The database is in synchronized mode, so an external backup can now take place.
Action	No action required.
INODSI5353	Continuing after external backup
Explanation	The synchronized mode of the database has ended. Normal database processing can resume.
Action	No action required
INODSQ1651	The currently inserted tape has been processed
Explanation	The currently inserted tape has been completely filled (backup) or completely read (restore).
Action	Please insert the next tape in the set so that processing may continue.
INODSQ1652	The diskette is full
Explanation	An operation writing to a diskette has completely filled up the diskette.
Action	Provide the information you are prompted for to enable Tamino to switch to a new diskette.
INODSQ1653	Please insert the next sequential tape and verify the selected device name is correct.
Explanation	Another tape is required in the current backup or restore sequence.
Action	Insert the next sequential tape and verify the device name is correct.

INODSQ1654	Please insert diskette diskette number and specify the device name
Explanation	Another diskette is required.
Action	Insert the indicated diskette and specify the device name.
INODSQ1655	First tape required
Explanation	The first tape is required.
Action	Insert the first tape.
INODSQ1656	First diskette required
Explanation	The first diskette is required.
Action	Insert the first diskette.
INODSQ1657	Please insert first tape again and specify the device name
Explanation	The first tape is required.
Action	Insert the first tape and specify the device name.
INODSQ1658	Waiting for space on LOG device
Explanation	The server can no longer perform update operations, because there is no more free space on the LOG device.
Action	Create free space on the LOG device, e.g. by deleting files.
INODSQ1659	Try to get free space on device where LOG is located
Explanation	The server can no longer perform update operations, because there is no more free space on the LOG device.
Action	Create free space on the LOG device, e.g. by deleting files.
INODSQ1660	Continue server startup or re-execute restore/recover
Explanation	When you continue the server startup, autorepair will be used. Database modifications not recovered during the recovery run of the previous aborted server session will be lost.
Action	Decide whether to continue or abort the server startup.

INODSQ1661	Please reply "yes" or "no" to continue server startup
Explanation	At this point in time you can continue or abort the server startup.
Action	Enter "yes" to continue the server startup, enter "no" to abort it.
INODSQ2224	Transfer via pipe stalled
Explanation	The backup activity via named pipe is hanging. One reason could be that the partner pipe process died for some reason, for example if the disk is full.
Action	Find out the reason why the pipe processing is hanging and answer 'OK' to continue or 'Abort' to abort the backup processing.
INODSQ2225	Continue or abort ?
Explanation	Continue or abort the processing. If you answer 'abort' the process immediately terminates with an appropriate message. Answer 'OK' to continue processing if you are sure that the pipe process is still active.
Action	no action
INODSQ2256	File extent extnumber missing
Explanation	A physical file extent of e.g. a backup file was not specified.
Action	Enter the file/device name of the required file extent.
INODSQ2257	Enter file/device name
Explanation	Enter here the full qualified file name of the required extent. Pipe or tape devices may be entered as well.
Action	No action required.
INODSQ2295	No location for database space extent no
Explanation	There is no location given for this database space.
Action	Select a valid location.
INODSR1479	Creating database space extent number of number of extents
Explanation	This is an informational message indicating how many extents of a group of extents have been created for the database space.
Action	No action required.

INODSR1483	Deleting database space extent number of number of extents
Explanation	This is an informational message indicating how many extents of a group of extents for the database space have been deleted.
Action	No action required.
INODSR1682	Analyzing journal information
Explanation	This is an informational message.
Action	No action required.
INODSR1683	Re-applying changes. Processing journal block block number.
Explanation	This is an informational message.
Action	No action required.
INODSR1684	Reconstructing consistent index structures. Processing journal block block number.
Explanation	This is an informational message.
Action	No action required.
INODSR1685	Resetting unfinished transactions. Processing journal block block number.
Explanation	This is an informational message.
Action	No action required.
INODSR1686	Recovered from abnormal termination
Explanation	This is an informational message.
Action	No action required.
INODSR1687	Reading parameters
Explanation	This is an informational message.
Action	No action required.
INODSR2029	Offline conversion phase
Explanation	This is an informational message.
Action	No action required.

INODSR2077	Re-applying updates started
Explanation	The recover process has started.
Action	No action required.
INODSR2078	Re-applying updates of session session
Explanation	The recover process has started re-applying updates of the next session.
Action	No action required.
INODSR2079	Re-applying updates completed
Explanation	The recover process has finished.
Action	No action required.
INODSR5347	Preparing external backup
Explanation	This is an information message.
Action	No action required.
INODSR5348	Synchronizing database
Explanation	This is an information message.
Action	No action required.
INODSR5349	Processing external backup
Explanation	This is an information message.
Action	No action required.
INODSR5350	Performing final cleanup
Explanation	This is an information message.
Action	No action required.
INODSR5351	Processing external restore
Explanation	This is an information message.
Action	No action required.

INODSR5362	Processing backup
Explanation	A backup operation is currently being processed.
Action	No action required.
INODSR5363	Processing restore
Explanation	A restore operation is currently being processed.
Action	No action required.
INODSS1005	Create database space
Explanation	This message indicates that the specified function is in progress.
Action	No action required.
INODSS1009	Delete database space
Explanation	This message indicates that the specified function is in progress.
Action	No action required.
INODSS1089	Creating database with reorganization ...
Explanation	The database will be created from a backup with defragmentation of the database layout.
Action	No action required.
INODSS1711	Recovering from abnormal termination
Explanation	This is an informational message.
Action	No action required.
INODSS1712	Starting database server
Explanation	This is an informational message.
Action	No action required.
INODSS1713	Checking database for index inconsistencies
Explanation	This is an informational message.
Action	No action required.

INODSS1714	Deleting database 'database_name'
Explanation	This is an informational message.
Action	No action required.
INODSS2025	Creating database ...
Explanation	Tamino is creating a new database.
Action	No action required.
INODSS2076	Performing recovery
Explanation	The restore/recover process is in the recover phase.
Action	No action required.
INODSS2159	Converting database
Explanation	The database is being upgraded or downgraded.
Action	No action required.
INODST1751	Start of Tamino name version modifier2 on system info
Explanation	This is an informational message.
Action	No action required.
INODST1752	Database database name Session session number (name modifier2 on system info, process ID pid)
Explanation	This is an informational message.
Action	No action required.
INODST1753	Database database name Read-Only Session (name modifier2 on system info, process ID pid)
Explanation	This is an informational message.
Action	No action required.
INODST1766	Database database name Replication Session (name modifier2 on system info, processID pid)
Explanation	The server started for a replication database.
Action	No action required.

INODSV1053	Database autorepair suppressed
Explanation	The previous server session terminated abnormally. The server attempted to perform an autorepair, but the autorepair has been suppressed by external manipulation. The database might be in an inconsistent state.
Action	Determine what kind of manipulation has occurred and contact your software supplier.
INODSV1129	System error errno occurred
Explanation	A system error has occurred in the context of the current task.
Action	Check the manufacturer's manual.
INODSV1174	No input data available
Explanation	The specified input file is empty.
Action	Ensure that the correct input file is being used.
INODSV1245	Error information: log space of server session session number - block block, location record
Explanation	The information describes the location of the recently processed log space data
Action	Keep this information when log space data analysis is required.
INODSV1258	Journal overflow. Server cannot proceed.
Explanation	The journal space was insufficient. The current server session has to be terminated.
Action	Check if more journal space can be provided. Restart the server.
INODSV1281	Component comp called at extension point extp returned response rsp
Explanation	The Tamino server called an external component which returned an error response.
Action	Please contact your software supplier.
INODSV1473	The database server is active on the local node
Explanation	This is an informational message.
Action	No action required.

INODSV1587	Internal event SCLOST has occurred
Explanation	A sort action has failed due to resource problems. A retry will be started automatically.
Action	No action required.
INODSV1801	Previous server session failed during write operation
Explanation	The previous server session was performing a write operation on modified data when the server session terminated abnormally.
Action	If you can be sure that a single write operation is atomic on your system, you can ignore this warning. You can always assume so if there was no power failure and if the previous server session did not abort due to an I/O error. If you cannot be sure, recover your database from the last backup.
INODSV1806	Aborted by operator
Explanation	The operator has explicitly aborted the operation.
Action	No action required.
INODSV1818	Log space of server session session number is empty
Explanation	An input file to be used for recovery is empty.
Action	Check that the correct log space files are present at the log space location.
INODSV2083	Unlocking port allocation lock failed with response err - int_err
Explanation	An unexpected response was received while trying to unlock the port allocation lock.
Action	Please contact your software supplier.
INODSV2118	Unlocking raw section lock failed with response err - int_err
Explanation	Unexpected response received while trying to unlock the raw section lock.
Action	Please contact your software supplier.
INODSV2139	Unlocking raw section lock failed with response err - int_err
Explanation	Unexpected response received while trying to unlock the container move lock.
Action	Please contact your software supplier.

INODSV2226	System error error (string) occurred
Explanation	An internal system service error occurred.
Action	Analyze the error number and the human readable text.
INODSV2273	The server servername is active
Explanation	The specified server is active.
Action	No action required.
INODSV2276	Aborted by High Availability monitor
Explanation	The High Availability monitor detected that the server did not respond within a specific timeout limit and forced an abnormal crash of this server. There could be two cases: either the server is really hanging or there is something very busy that the check by the High Availability monitor takes a very long time (e.g. a huge buffer flush is in progress).
Action	Check if the HA timeout value is reasonable with the context. One dangerous situation can be a long enduring buffer flush which might block applications for a long time. Maybe it is reasonable to run with small flush limit and/or flush group size parameters.
INODSV2281	System error errno (errtxt) when opening database space space no (path)
Explanation	An internal operating system error has occurred while trying to open a database space.
Action	Analyse the error text and consult the manufacturer's manual.
INODSV5266	Journal overflow. Current activity cancelled.
Explanation	The journal space was insufficient. The current activity has been cancelled. Typically, a transaction has been rolled back internally.
Action	Provide more journal space. Restart the terminated activity.
INODSV5269	Server is already registered with the Software AG XTS Directory Server
Explanation	When the server starts it registers with the Software AG XTS Directory Server. It is possible that entries for the server are already present (server already started somewhere else or previous server session failed). If this message comes as a warning message, the entry found exactly matches the one that should be entered. If this message comes as an error message, the entry found did not match the entry that the server wanted to add.
Action	If this message comes as a warning message no action is required. If this message comes as an error message the Software AG XTS Directory Server entry found for the server should be checked and, if no longer necessary, the next server start should be done with the parameter for overwriting the Software AG XTS Directory Server entry activated.

INODSW1014	Creation of word fragment index failed
Explanation	Creation of word fragment index failed, because corresponding index tree is inaccessible.
Action	Use the function "check and repair database" and restart the server.
INODSW1017	Due to license restrictions, recovery of the database will not be possible
Explanation	Your license file does not allow logging to be enabled. Due to this restriction, recovery of the database will not be possible.
Action	Contact your software supplier for an upgrade of your license.
INODSW1035	Synchronization semaphore lost and recreated
Explanation	The synchronization semaphore was deleted from outside and a new one was created.
Action	No action required.
INODSW1115	Incremental backup disabled due to buffer pool allocation failure
Explanation	An incremental backup is not possible because no space was available for the information of modified blocks.
Action	Create the next backup as a full backup. To avoid the allocation failure increase the buffer pool.
INODSW1116	Incremental backup disabled due to error error
Explanation	An incremental backup is not possible due to an error when maintaining the information of modified blocks.
Action	Create the next backup as a full backup. If the error persists, contact your software supplier.
INODSW1151	Further recovery for doctype doctype will not include index
Explanation	Due to an error during recovery the index of the doctype has been disabled.
Action	Even though the index was disabled, data has been recovered. The index can be rebuilt using the "Check and Repair" function.
INODSW1340	The last available backup could not be deleted
Explanation	It doesn't make much sense to delete all backups. To avoid the situation that someone deletes the last backup by mistake, this deletion is not allowed.
Action	If you want to delete this special last backup, you have to create a new one.

INODSW1372	Waiting for space on space location
Explanation	The location where the file wants to grow has no more free space and the current request will wait until space is available.
Action	Either delete unused files from the location that has insufficient space or define a new location with enough space for that file.
INODSW1409	Error when opening database space space no (at path): size mismatch
Explanation	The size of the database space is not equal to the size expected by the server.
Action	Please contact your software supplier.
INODSW1410	Error when opening database space space number (at path)
Explanation	The database space could not be opened.
Action	Check the affected device: is it on-line, are the permissions correct, can operating system tools access the device? If you cannot find the reason for the read error by yourself, please contact your software supplier.
INODSW1411	Error when opening database space, compressed state is not permitted (at path)
Explanation	The database file has the compressed attribute, which is not permitted, because write errors should be avoided if the device is getting full.
Action	Remove the compressed attribute from the database file.
INODSW1412	System error errno when opening database space space no (path)
Explanation	The specified operating system error has occurred.
Action	Please consult the manufacturer's manual.
INODSW1414	System error errno when opening database space space no (path)
Explanation	The specified operating system error has occurred.
Action	Please consult the manufacturer's manual.
INODSW1455	Database start not allowed because of pending "set version" operation. Please re-execute "set version".
Explanation	A previous "set version" operation aborted. The database may be inconsistent.
Action	Try "set version" again. If it fails also the second time, report the problem to your software supplier.

INODSW1482	Log space of server session session number not to be processed.
Explanation	The log space of the specified server session was not processed because it was skipped by a previous recovery run.
Action	Verify that the skipped log space has also been skipped by the previous recovery run.
INODSW1529	switch internal I/O mode
Explanation	The I/O mode was switched because an internal I/O function is not supported by given platform. This could happen if a platform does not support the call <code>lio_listio()</code> .
Action	No action required.
INODSW1602	Insufficient disk space for journal space, resize to: size MB
Explanation	There is insufficient disk space to create journal space of the required size; a reduced size will be used.
Action	No action required.
INODSW1689	Parallel backup not available on Windows, a sequential backup will be performed.
Explanation	The Windows version of backup does not support 'parallel backup', therefore a sequential backup will be performed.
Action	No action required.
INODSW1784	There is a pending autorepair for the database
Explanation	The database had previously not terminated correctly.
Action	When the database has been restarted, it will perform an autorepair operation.
INODSW1800	This is an emergency restart
Explanation	The server stopped the previous server session due to shortage of journal space. If this restart fails, data may be lost or inconsistent.
Action	If the restart fails, please recover your data from the last backup.
INODSW1802	A transaction has been heuristically rolled back at time
Explanation	The database system has rolled back a transaction for which a decision of the transaction manager was pending.
Action	No action required.

INODSW1803	A transaction has been heuristically committed at time
Explanation	The database system has committed a transaction for which a decision of the transaction manager was pending.
Action	No action required.
INODSW1804	Backup task not responding. Ignoring backup activity.
Explanation	A backup task was running when the server came up. The server synchronization with this backup task has failed. The backup will terminate eventually.
Action	Check if the backup activity is still running. If so, it can be terminated. Redo the backup.
INODSW1805	The server cannot proceed until the backup activity has finished
Explanation	The server will wait for the backup activity to complete. When it has finished, the server will continue.
Action	No action required.
INODSW1807	Switched to read-only mode because a database space is not writable
Explanation	The database will not accept updates.
Action	If this behavior is not intended, make all database spaces write-accessible.
INODSW1808	Read-only database
Explanation	The database is read-only. Some functions are disabled.
Action	No action required.
INODSW1809	Error when opening database space space no (at path): size mismatch, expected bytes bytes
Explanation	The size of the database space is not equal to the size expected by the server.
Action	If the operation does not complete successfully, please contact your software supplier.
INODSW1810	database space space no opened for read-only access
Explanation	The specified database space was opened for read-only access. No updates will be possible on this database space.
Action	No action required.

INODSW1811	Database might be corrupted
Explanation	An inconsistency has been found in the database.
Action	Check the database for consistency.
INODSW1812	Backup process is not responding
Explanation	The synchronization between the backup process and the server has been lost. One possible reason is that the backup process has been killed. The backup will not come to a normal end.
Action	Restart the backup.
INODSW1813	Backup process is not communicating completion
Explanation	The synchronization between the backup process and the server has been lost. One possible reason is that the backup process has been killed. The backup will not come to a normal end.
Action	Restart the backup.
INODSW1814	Backup process is not fetching modified data
Explanation	The synchronization between the backup process and the server has been lost. One possible reason is that the backup process has been killed. The backup will not come to a normal end.
Action	Restart the backup.
INODSW1815	Before image mismatch for number instances on doctype doctype
Explanation	This is an internal error.
Action	Please contact your software supplier.
INODSW1817	Read-only database server accessed
Explanation	A utility is being run against a read-only database server. Certain functions may not be available.
Action	No action required.
INODSW1819	Invalid starting block number block number for log space from session session number
Explanation	The log space does not contain correct log information.
Action	Check if files have been moved or copied to the log space location.

INODSW1823	Unable to remove shared memory
Explanation	It has not been possible to remove a shared memory segment.
Action	Remove any allocated shared memory with available system tools.
INODSW1825	Unexpected database error: resp
Explanation	An internal database error has occurred.
Action	Please contact your software supplier.
INODSW1827	Function is deactivated
Explanation	The requested function is not activated at present.
Action	No action required.
INODSW1828	Doctype deleted but de-allocation failed (reason code reason)
Explanation	A doctype has been deleted from the database but it could not be de-allocated.
Action	Determine the cause of the failure from the supplied reason code.
INODSW1829	Unable to remove utility flag and/or write event
Explanation	The utility was in its final cleanup phase but could not complete all required actions.
Action	The utility has terminated successfully, but the cause of the cleanup failure should be determined.
INODSW1830	Event could not be written due to response response
Explanation	The utility has failed to write a final event due to the response reported.
Action	The utility will end successfully. The response code indicates the reason for the failure to write an event.
INODSW1835	Waiting for debugger to attach
Explanation	This message is displayed by debug-enabled executables if they have been selected for debugging.
Action	Please contact your software supplier.

INODSW1836	Mass load recovery files not archived
Explanation	The mass load recovery files could not be copied to the archive location.
Action	Check for a reason why files could not be created at the archive location. Copy the mass load recovery files manually.
INODSW1837	An error occurred during the create index process on doctype doctype
Explanation	The error is caused by an attempt to create a unique index for non-unique data values.
Action	Contact your software supplier.
INODSW1838	Log space of server session session number processed until time
Explanation	None of the information generated after the given end timestamp of the log space of the specified server session was processed.
Action	Verify that the skipped part of the log space is the same as was skipped with a previous recovery.
INODSW1839	Log space of server session session number extent extent number not archived
Explanation	A log space extent could not be copied to the archive location.
Action	Check the log archive location name and for available space.
INODSW1840	Log space of server session session number extent extent number not closed
Explanation	A log space extent could not be closed.
Action	No action required.
INODSW1841	Database successfully checked and repaired. Number of repaired indexes is number.
Explanation	The database has been repaired.
Action	No action required.
INODSW1842	Update in internal configuration store could not be logged
Explanation	Configuration was successfully updated, however the update could not be logged. Possible reasons may be - update log file is read-only or there is not enough space on device where Tamino is installed.
Action	In most cases this warning can be ignored. Inform your system administrator about the warning.

INODSW1843	No information about previous recovery processing
Explanation	Recovery processing was aborted without being able to write recovery progress information.
Action	See the instructions within subsequent messages.
INODSW1845	Continuing server startup will disable all existing backups
Explanation	A preceding Restore/Recover operation that specified an "until" date that is earlier than the latest backup was performed. This means that any backup that was performed after the "until" date of the Restore/Recover operation is no longer valid.
Action	Create a new database backup as soon as possible.
INODSW1846	All backups disabled, create a new backup copy
Explanation	No information about previous recovery processing was available, all backups have been disabled.
Action	Create a new database backup as soon as possible.
INODSW1848	Container file could not be extended, but attempt to continue
Explanation	The database could not be extended as the backup file signalled. The restore is continued but later I/O errors are possible.
Action	You can ignore this message if the restore terminates successfully. If the restore fails due to an I/O error you must check why the database could not be extended.
INODSW1980	Skipping recovery terminated with warning status
Explanation	While skipping the recovery a situation occurred that requires further investigation.
Action	Check for additional messages in the event log.
INODSW1981	Recovery terminated with warning status
Explanation	During recovery a situation occurred that requires further investigation.
Action	Check for additional messages in the event log.
INODSW1993	keyword combination not allowed
Explanation	The supplied keyword combination is invalid.
Action	Correct the input parameters.

INODSW1997	Due to license restrictions, the database will be started in readonly mode
Explanation	Your license is restricted to readonly mode. Due to this restriction, updates of the database will not be possible.
Action	Contact your software supplier for an upgrade of your license.
INODSW2047	Version cd database version not installed, using compatible version instead
Explanation	The version of the CD database is not installed on the target system. However a compatible version was found and will be used.
Action	No action required.
INODSW2066	Journal size specified is less than the minimum allowed size of numberMB. Increasing to numberMB.
Explanation	The journal size specified is less than the minimum required to allow correct operation of the server. Tamino is adjusting the journal size up to the minimum size.
Action	No action required.
INODSW2073	Previous log file corrupted (reason: reason). Please perform a database backup as soon as possible.
Explanation	During restart after a database crash it was detected that the log file of the previous session is corrupt. A database recovery may fail, therefore a new backup would resolve this situation. Moreover a further database replication would fail, therefore if the database is or will be a replication master the replication must be newly set up with a new database backup.
Action	Perform a new database backup. Revise replication. Reestablish replication with the new database backup.
INODSW2089	Port port already in use as name by server server
Explanation	The port to check is already in use.
Action	Choose another port or be aware that problems with port usage might occur.
INODSW2090	Port port used as name by server server is located in selected dynamic port range
Explanation	An allocated port was found in the dynamic port range.
Action	Specify another dynamic port range or change the allocated port so that it is located outside the dynamic port range.

INODSW2098	Web server webserver assigned to database server
Explanation	The web server is assigned to a database and must not be removed before it is deassigned.
Action	Keep this web server definition or deassign it from all databases.
INODSW2101	Web server configuration changed, notification of server server failed (rc1,rc2,rc3)
Explanation	The web server configuration was changed, but the server notification failed.
Action	The server has to be restarted manually.
INODSW2102	Web server configuration changed for web server webserver, but server notification failed
Explanation	The web server configuration was changed, but the notification of active servers failed.
Action	Restart all active servers which have assigned the web server in question.
INODSW2112	User specified record ID number is not within proposed range
Explanation	The load utility was called with at least one record ID which is within a used range. In the event of a crash the internal doctype may have a corruption.
Action	This is an internal problem. Please contact your software supplier.
INODSW2113	Cleanup of a mass load failed with error
Explanation	The cleanup task, e.g. within a rollback, of a mass load failed for internal reasons.
Action	Please contact your software supplier.
INODSW2133	Nothing to verify, no data available
Explanation	The item only contains index values, therefore no verification is necessary.
Action	No action required.
INODSW2147	Replication of server session session number resumed using replication data from timestamp. Simultaneous query will be enabled when replication database is up-to-date.
Explanation	The server continued replication processing after replication database startup.
Action	No action required. The database server will automatically enable simultaneous read when the locking information becomes available, at the latest when replicating the current master database session.

INODSW2152	Port port is currently active and may not be usable
Explanation	The specified port is currently active and may not be usable by the Tamino server.
Action	Specify another port for the Tamino server or free up the active port before starting the Tamino server.
INODSW2153	Flush limit too high. Value adjusted to new value.
Explanation	The flush limit specified was too high. It has been adjusted to a reasonable value.
Action	To avoid this warning at each startup of the database, configure a lower value.
INODSW2155	Replication of server session session number from timestamp started. Simultaneous query will be enabled when replication database is up-to-date.
Explanation	The replication processing has started to process the log space data of the specified server session of the master database.
Action	No action required. The database server will automatically enable simultaneous read when the locking information becomes available, at the latest when replicating the current master database session.
INODSW2156	Database name1 is fully overlaid with backup from database name2
Explanation	The backup file which was created by a foreign database has been restored into the current database. The previous content of the database has been completely deleted.
Action	No action required.
INODSW2161	corrupted data repaired
Explanation	A detected corruption was repaired immediately by Tamino.
Action	No action required.
INODSW2171	Replication data of session session requires new Tamino version version
Explanation	The replication database is using a different Tamino version than the master database.
Action	Install the required Tamino version at the replication database node. If the required version is already installed and the error still exists, re-create the replication database using a backup created from this Tamino version.

INODSW2172	Master database must be restarted before a replication database can be set up
Explanation	The name of the first replication database has been added to the permission list. The database can be set up as a replication database of this master only after the master has been stopped and restarted.
Action	Stop the master database and start it again.
INODSW2180	Connection to server lost, reason reason
Explanation	The working process must be terminated because the server is stopping or has already stopped. There are 2 possible reasons: 0 means the server has stopped, 1 means the server is stopping and has aborted the process.
Action	Check why the server stopped.
INODSW2186	The configured buffer pool size (lbp MB) exceeds the machine's physical memory size (pms MB)
Explanation	The buffer pool size is configured so that it exceeds the physical memory size of the machine. This does not make sense because the buffer pool replacement strategy will collide with the operating systems memory management.
Action	Choose a buffer pool size that is at least smaller than the machine's physical memory size.
INODSW2191	The maximum number of threads allowed per process (max_threads) may not be sufficient to manage the database server
Explanation	The current parameter configuration may not allow the creation of all necessary threads to manage the database server.
Action	Either the system defined maximum number of threads per process is too low and should be increased, or the database parameter configuration should be changed to decrease the number of threads to be created.
INODSW2195	Connection to master database master dbname interrupted
Explanation	The replication database cannot obtain replication data from its master database.
Action	No action required.
INODSW2197	Replication of server session session number stopped. Replication data processed until timestamp.
Explanation	Replication processing is stopped due to an error as described in previous messages. If simultaneous queries were permitted, then the replication database stays online and may be used for further queries.
Action	Try to solve the problem at the master database's side or recreate the replication database from a new backup of the master.

INODSW2198	Update logging in internal configuration store is not active
Explanation	Updates in the internal configuration store are not logged because update logging is not activated in the current process.
Action	Please contact your software supplier.
INODSW2207	No reading process attached to pipe path
Explanation	Backup location is a named pipe and no process has the pipe open for reading. This situation may occur during database backup or database creation, when initial backup is being made.
Action	Start the process that reads from the pipe and perform the backup again.
INODSW2209	Inconsistent location definition (location) - expected type expected, real type real
Explanation	The location type is unexpected. This is typically the result of user intervention , for example the user deletes a location directory and creates a file with the same name.
Action	Make sure that Tamino locations are not modified outside of Tamino.
INODSW2210	Location location is nearly full
Explanation	Not enough disk space is left on the location.
Action	Free some space or use another location.
INODSW2230	Logging error in internal configuration store occurred at time, future updates may not be logged
Explanation	The internal configuration store showed an update logging error that occurred in the past. There is a chance that future updates will also not be logged, thus preventing a repair of the internal configuration store after a severe error. This message is displayed at each server startup unless you execute the described actions.
Action	To be sure to be able to recreate all configuration data, you can do the following: Copy your registry (all under the key 'Tamino') to a file. Use the 'export' function of your registry editor. Then clean your registry logging file or use another file. The registry logging file is defined with a string value at the registry key 'Tamino'. Combining both files lets you repair your Tamino registry in the case of a corruption. Finally you can remove the 'registry logging error' string value from the registry either with your registry editor or with the Registry functions of your Tamino manager.

INODSW2238	No space to remove
Explanation	The request to remove database space cannot be performed, because trailing space is in use.
Action	No action required.
INODSW2240	File/path path does not exist or is not accessible
Explanation	The given file/pathname does not exist or is not accessible. It will just be skipped.
Action	Check the file/pathname.
INODSW2244	Cannot create initial backup - reference to original one is not possible; perform backup for the database as soon as possible
Explanation	The initial backup for the new database could not be created. It tries to reference this backup, but the backup is already registered with another active database. So the database is left without a valid backup !
Action	Perform a database backup as soon as possible.
INODSW2245	Cannot create initial backup - but referred to original one
Explanation	The creation of the initial backup of the new database failed. Nevertheless a backup entry was set up pointing to the file/device where the creation-backup comes from. This has the same effect as when the nocopyoption has been used.
Action	No action required.
INODSW2246	Reference to original backup is not possible; perform backup for the database as soon as possible
Explanation	The create from backup was used with the nocopy option, which means that the incoming backup file will just be referenced instead of copied. But it is not permitted to reference a backup file which is already registered with an active database. Now there is no valid backup for the created database
Action	Perform a database backup as soon as possible.
INODSW2247	Location skipped (no space)
Explanation	The given location has not enough space for creating a database file. It skips to the next location if any.
Action	Check the space in this location.

INODSW2248	Location skipped, (internal error err)
Explanation	The current location cannot be used and will be skipped. The internal error displayed gives the detailed reason.
Action	Analyse the error and check the path name of the location.
INODSW2260	create / delete database synchronization failed with (error)
Explanation	The semaphore synchronisation failed with an internal error.
Action	Do not start another create / delete database in parallel.
INODSW2261	Removing backup file (filename) failed due to internal error error
Explanation	The given backup file cannot be removed due to displayed error reason, but it will be unregistered.
Action	Delete the backup file by hand if you decide that it would never be needed any more.
INODSW2262	Problem during referencing initial backup file (file), reason: reason
Explanation	A reference operation (insert/delete) to a backup file failed. A reference will be set up at create database from backup to the source backup file. If the setting of a reference failed, then it may happen that the owner of the backup deletes the backup file although a foreign database has it still registered. If this operation failed at the owner side, it may happen that the backup file remains in the file system although it was logically deleted.
Action	Check the databases where this backup file is registered. Maybe perform a new backup of databases which have this backup file registered.
INODSW2269	Failed to load ADABAS interface (library)
Explanation	The Tamino server failed to load the ADABAS interface.
Action	Provide a valid ADABAS interface in one of the locations searched during the library load.
INODSW2277	Buffer pool size set to size MB due to shortage of shared memory
Explanation	The available shared memory was not large enough to allocate the buffer pool with the configured size.
Action	Check whether the configured size of the buffer pool meets the memory resources available within the given environment.

INODSW2297	Perform emergency shutdown, because server is within a space wait situation
Explanation	The server is waiting for space on the log file, therefore a clean shutdown is not possible. It aborts the server with a pending autorepair.
Action	Clean up the log space location and restart the server.
INODSW2318	The license for name with ID id expires in number days
Explanation	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
INODSW2319	The license for customername sub-licensed by partnername with ID partnerid expires in number days
Explanation	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
INODSW2320	The license for customername with ID customerid sub-licensed by partnername expires in number days
Explanation	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
INODSW2321	The license for customername with ID customerid sub-licensed by partnername with ID partnerid expires in number days
Explanation	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
INODSW2322	The license for name with ID id expires in 1 day
Explanation	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2323	The license for customername sub-licensed by partnername with ID partnerid expires in 1 day
Explanation	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
INODSW2324	The license for customername with ID customerid sub-licensed by partnername expires in 1 day
Explanation	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
INODSW2325	The license for customername with ID customerid sub-licensed by partnername with ID partnerid expires in 1 day
Explanation	The license expires soon. After license expiration the server cannot be used any longer. The server will abort and cannot be restarted.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
INODSW2326	The license for name with ID id has expired, server will abort in number days
Explanation	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
INODSW2327	The license for customername sub-licensed by partnername with ID partnerid has expired, server will abort in number days
Explanation	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2328	The license for customername with ID customerid sub-licensed by partnertype has expired, server will abort in number days
Explanation	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
INODSW2329	The license for customername with ID customerid sub-licensed by partnertype with ID partnerid has expired, server will abort in number days
Explanation	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
INODSW2330	The license for name with ID id has expired, server will abort in 1 day
Explanation	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
INODSW2331	The license for customername sub-licensed by partnertype with ID partnerid has expired, server will abort in 1 day
Explanation	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
INODSW2332	The license for customername with ID customerid sub-licensed by partnertype has expired, server will abort in 1 day
Explanation	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.

INODSW2333	The license for customername with ID customerid sub-licensed by partnername with ID partnerid has expired, server will abort in 1 day
Explanation	The license has expired. The server will not restart any more. Final abort after a grace period of 10 days after license expiration.
Action	Please contact your software supplier to extend your license. Activate the new license with the Tamino Manager.
INODSW5255	Internal parameter error (param), using default
Explanation	An invalid internal parameter value was found. The default parameter value is used.
Action	Please contact your software supplier.
INODSW5274	number updates excluded on doctype doctype
Explanation	Due to an error during recovery, not all updates have been re-applied.
Action	Check the previous error messages to find more information about the error.
INODSW5275	Updates performed between server startup and recovery start
Explanation	Updates between server startup and recovery start are not allowed.
Action	Please check subsequent messages for more information.
INODSW5294	waiting for buffer flush end
Explanation	The dump utility must wait until the Tamino server completes the buffer flush action.
Action	No action required.
INODSW5329	Sort request couldn't be specified, reason subc
Explanation	A sort request failed, for the reason specified in the message
Action	Contact your software supplier.
INODSW5340	Collating key truncated to size bytes
Explanation	The collation key was truncated due to the size limit for index values. Only less important information was truncated.
Action	Normally, collation should be defined only for small pieces of data (e.g. words), not for the large texts. Consider reviewing your collation definitions.

INODSW5355	File system UNMOUNT problem, reason reason errtxt
Explanation	Restoring an external backup may require the remounting of the file system. This is necessary to flush the file system cache.
Action	Remount the file system manually and contact your software supplier.
INODSW5356	File system MOUNT problem, reason reason errtxt
Explanation	Restoring an external backup may require the remounting of the file system. This is necessary to flush the file system cache
Action	Remount the file system manually and contact your software supplier.
INODSW5400	Internal sort order lost
Explanation	A sort request could not be satisfied due to internal reasons.
Action	You can force a memory dump with "inodba database=name trap=9299" for further analysis after reproducing the error.
INODSW5401	Function not completely executed
Explanation	A request failed due to internal reasons.
Action	You can force a memory dump with "inodba database=name trap=9298" for further analysis after reproducing the error.
INOINE2051	Resetting the unique status on all indices
Explanation	Duplicate values were detected. Therefore the unique status could not be set for the indices.
Action	Resolve any uniqueness conflicts before trying to set the unique status.
INOINE2053	Index name already in use
Explanation	The specified index name is already in use for this doctype.
Action	Retry the required operation with an unused index name.
INOINF2251	Sort file too small or work pool too large
Explanation	The sort file used is too small or the specified work pool is too large for the given sort file.
Action	Ensure that a sufficiently large sort file is available.

INOINF2252	Sort file too small
Explanation	The sort file used is too small.
Action	Ensure that a sufficiently large sort file is available.
INOINF2253	Corrupt index found
Explanation	Corrupt information has been found in the index.
Action	Please contact your software supplier, and/or reload the data to repair the damage.
INOINI2174	Index processing completed on doctype doctype
Explanation	The requested index operation has ended.
Action	No action required.
INOINI2452	Index modification started
Explanation	The database index modification process has started.
Action	No action required.
INOINI2453	Index modification completed
Explanation	The index modification process has completed.
Action	No action required.
INOINI2454	Index cannot be sorted in main memory
Explanation	The index process cannot perform the sort in main memory. This is an informational message. An external sort will be performed.
Action	No action required.
INOINI2455	Index cannot be sorted
Explanation	It is not possible to sort the index, probably due to a lack of space.
Action	Allow more space to be allocated for a main memory sort of the index, if possible.
INOINI2456	Index cannot be processed in two passes
Explanation	It is not possible to process the index in two passes due to insufficient temporary storage.
Action	Allocate more temporary storage to allow the index to be processed in two passes.

INOINI2457	Index cannot be processed in one pass
Explanation	It is not possible to process the index in one pass due to a lack of temporary storage.
Action	Allocate more temporary storage to allow the index to be processed in one pass.
INOINI2459	Index verification limit has been reached
Explanation	The number of errors found while verifying the index has reached the allowed limit.
Action	Correct the errors in the index, and run the certification process again.
INOINI2460	Data space passes required: count
Explanation	This is the number of passes of the data space required to perform the index operation.
Action	No action required.
INOINI2461	Sort file efficiency: sorteфф %
Explanation	This is the calculated efficiency of the sort file during the index process.
Action	No action required.
INOINI2462	Work pool efficiency: workeфф %
Explanation	This is the calculated efficiency of the work pool during the index process.
Action	No action required.
INOINI2467	Recommended minimum temporary storage size = size KB
Explanation	This is the recommended (minimum) temporary storage size that will be allocated for the process.
Action	No action required.
INOINI2471	Temporary storage size = size KB
Explanation	This is the size of the required temporary storage.
Action	No action required.
INOINI2472	Temporary storage size (1 pass) = size MB
Explanation	This is the temporary storage size required for 1 pass processing.
Action	No action required.

INOINI2473	Temporary storage size (2 passes) = size MB
Explanation	This is the temporary storage size required for 2 pass processing.
Action	No action required.
INOINI2474	Sorting index
Explanation	The index field is being sorted.
Action	No action required.
INOINI2475	No values for index (desc)
Explanation	No values are present for the index field.
Action	No action required.
INOINI2476	Loading index
Explanation	The index field specified is being loaded.
Action	No action required.
INOINI2477	Verifying index (desc)
Explanation	The index field specified is being verified.
Action	No action required.
INOINI2478	Unique status for specified index is being set
Explanation	The unique status for the specified index field is being set.
Action	No action required.
INOINI2479	Unique status for specified index is being reset
Explanation	The unique status for the specified index field is being reset.
Action	No action required.
INOINI2480	Unique status removed for index
Explanation	The unique status of an index field has been removed.
Action	No action required.

INOINI2481	No index fields were found for the specified doctype
Explanation	The index function could not be performed because no index fields were found in the specified doctype.
Action	Check that the correct doctype was specified for the index operation.
INOINI2482	Index processing started on doctype doctype
Explanation	The requested index operation has started.
Action	No action required.
INOINW2800	Errors found for count indices
Explanation	A number of indices were found to be in error during the index process.
Action	Correct the errors and attempt to perform the index process again.
INOINW2801	Number of errors found in index: indexerr
Explanation	This message shows the number of indices found to be in error during index processing.
Action	Correct the indices in error and perform the index operation again.
INOINW2802	Unique conflict detected
Explanation	Duplicate values were detected when trying to create a unique index.
Action	Remove any unique conflicts in the data.
INOLDE3010	Invalid combination of keywords
Explanation	The combination of keywords supplied is not allowed.
Action	Check the keyword combination and retry the operation.
INOLDE3016	FIELDS may be specified only once
Explanation	The parameter FIELDS may be specified only once.
Action	Continue with other parameter settings.
INOLDE3051	Invalid output status returned by user exit
Explanation	A user exit has returned an invalid output status to the load process.
Action	Ensure that the user exit always returns a valid output status.

INOLDE3054	Invalid range of sequence numbers
Explanation	The range of sequence numbers to be deleted is invalid.
Action	Please contact your software supplier.
INOLDE3055	Value must be less than or equal to value
Explanation	A value has exceeded the specified maximum.
Action	Decrease the value specified.
INOLDE3056	Invalid record length
Explanation	The input record length must be a multiple of four for binary data.
Action	Check the input file.
INOLDE3057	Sequence number to be deleted is not present
Explanation	The sequence number to be deleted is either not present or outside the specified doctype's limits.
Action	Ensure that the sequence numbers to be deleted were specified correctly.
INOLDE3058	Dataset dataset, record record, offset offset
Explanation	An error has occurred in the specified dataset at the position indicated.
Action	Correct the input and retry the operation.
INOLDE3059	Index index not defined for doctype doctype
Explanation	The specified index is defined in the load description file but is not present in the doctype to be updated.
Action	Ensure that the load description file contains the correct information and that the correct doctype is specified.
INOLDE3060	Read-only database, function not permitted to run
Explanation	The specified database is read-only and the requested function is not allowed for a read-only database.
Action	Ensure that the database being accessed is not read-only for this type of operation.

INOLDF3018	The requested doctype is locked, load aborted
Explanation	The doctype referenced is locked and the load is unable to proceed.
Action	Wait until the doctype is available. If the lock is due to a previous problem or corrupt doctype, a server restart may clear the lock and return the doctype to a usable state.
INOLDF3251	Load aborted in user exit at record number: record
Explanation	The load process has been aborted by a user exit while processing the specified record number.
Action	Check the user exit for the reason for aborting the load process.
INOLDF3252	Record too big for data storage device
Explanation	The record is too large for the data storage device used.
Action	Decrease the size of the input record, or use a data storage device with a larger block size.
INOLDF3253	Incomplete load definition file
Explanation	The input file containing the load definitions is incomplete.
Action	Check the load definition file and ensure that it contains the correct information.
INOLDF3254	Internal buffer overflow
Explanation	An unexpected overflow of an internal buffer has occurred.
Action	Please contact your software supplier.
INOLDF3255	Sort I/O error
Explanation	An I/O error has occurred on the sort data space.
Action	Check the sort data space for system errors.
INOLDF3256	Selection not yet implemented
Explanation	The selection of sequence numbers to be deleted is not yet implemented.
Action	No action possible.

INOLDF3257	Unexpected error while connecting
Explanation	An unexpected error has occurred while trying to connect to the server.
Action	Please contact your software supplier.
INOLDF3260	Error in user store function
Explanation	An error has occurred in a user-supplied store function.
Action	Check and correct any user-supplied store functions.
INOLDF3261	No free sequence numbers
Explanation	An internal shortage of sequence numbers has occurred.
Action	Please contact your software supplier.
INOLDF3263	No free sequence numbers
Explanation	There are no more free sequence numbers available.
Action	Please contact your software supplier.
INOLDF3264	Cannot allocate user-defined sequence number
Explanation	An error has occurred when trying to allocate a user-defined sequence number.
Action	Check that the user routine that allocates sequence numbers is correct.
INOLDF3265	No index read slots
Explanation	An internal error has occurred because there are no read slots available for the index.
Action	Please contact your software supplier.
INOLDF3266	Error while generating index
Explanation	An internal error has occurred while generating an index.
Action	Please contact your software supplier.
INOLDF3267	Temp stream overflow
Explanation	A stream overflow has occurred while processing the temporary data space.
Action	Please contact your software supplier.

INOLDF3268	Doctype locking failed
Explanation	It was not possible to lock a doctype for access.
Action	Ensure that nothing else is accessing the doctype to be locked.
INOLDF3269	Unexpected error while removing utility entry
Explanation	An unexpected internal error has occurred while removing a utility entry.
Action	Please contact your software supplier.
INOLDF3270	Unexpected error while opening sort space
Explanation	An unexpected internal error has occurred while opening the sort space.
Action	Ensure that there is enough sort space available.
INOLDF3271	Load description does not match
Explanation	The definitions in the load description file do not match those of the current doctype.
Action	Check that the specifications in the load description file are correct.
INOLDI3002	Preparing documents for load
Explanation	Preparing documents for load.
Action	No action required.
INOLDI3019	Loading documents in collection
Explanation	The collection is being modified.
Action	No action required.
INOLDI3451	Termination forced by user exit
Explanation	A user exit has forced the load process to terminate.
Action	If the termination was unexpected, check the user exit for the reason.
INOLDI3452	Number of records read: records
Explanation	This is the number of input records read during the load process.
Action	No action required.

INOLDI3456	Number of documents added to doctype doctype: number
Explanation	The load process has added the given number of documents to the specified doctype.
Action	No action required.
INOLDI3457	Number of documents deleted from doctype doctype: number
Explanation	The load process has deleted the given number of documents from the specified doctype.
Action	No action required.
INOLDI3458	Number of documents unloaded from doctype doctype: number
Explanation	The load process has unloaded the given number of documents from the specified doctype.
Action	No action required.
INOLDI3459	The specified number of records have been loaded
Explanation	The number of records to be loaded has been reached.
Action	No action required.
INOLDI3460	Preparing existing indices for merge
Explanation	Existing indices are being backed up before creating new ones.
Action	No action required.
INOLDI3461	No index modification
Explanation	No modifications have been made to any indices.
Action	No action required.
INOLDI3464	Data space is being modified
Explanation	The data space is being modified.
Action	No action required.
INOLDI3465	Data space prepared for delete
Explanation	The data space will be prepared for deleting records.
Action	No action required.

INOLDI3467	Number of referential integrity violations: number
Explanation	This message indicates the number of referential integrity violations encountered during the load process.
Action	No action required.
INOLDI3468	Erasure from referenced doctype is not supported
Explanation	It is not possible to erase from the referenced doctype.
Action	No action possible.
INOLDI3474	Sorting and loading indices
Explanation	The indices are being sorted and loaded.
Action	No action required.
INORBE4002	Function only permitted if restore database
Explanation	A function was chosen that is not permitted in the current context.
Action	Use the function while restoring the database.
INORBE4005	Backup not currently possible; parts of database are locked
Explanation	It is not currently possible to start a backup because parts of the database are locked by other users or operations.
Action	Retry the backup when there are no longer any users or operations locking any parts of the database.
INORBE4006	This function is not permitted on a system file while Tamino server is active
Explanation	To preserve data consistency, the Tamino server should not be active while restoring the database.
Action	Shut down the Tamino server.
INORBE4007	Restore database is not permitted while Tamino server is active
Explanation	To preserve data consistency, the Tamino server should not be active while restoring the database.
Action	Shut down the Tamino server.

INORBE4053	Terminator of backup copy not found
Explanation	The terminator of the backup copy could not be found. The error can occur if the backup was modified outside of Tamino.
Action	Make sure that the backup copy was not modified outside of Tamino. If the problem persists , contact your software supplier.
INORBE4056	Invalid database space size change
Explanation	The value for changing the database space size is invalid.
Action	Specify a valid value.
INORBE4057	No space for database block allocation at database space (number KB at block)
Explanation	The restore requires more space for the database, but it failed. There are two possible reasons: either the database cannot be extended because there is no more space on the disk, or there are internal structure problems.
Action	Make sure that there is enough space for the database to be enlarged.
INORBE4060	Input file is empty
Explanation	The input file specified for the operation is empty.
Action	Check that the correct input file has been specified.
INORBE4061	Invalid sequence of backup copy files
Explanation	The sequence of the specified backup copy files is incorrect.
Action	Check that the correct backup copy files have been specified.
INORBE4064	Synchronization with database server lost
Explanation	The synchronization with the database server has been lost.
Action	Retry the backup operation. If the problem persists, contact your software supplier.
INORBE4065	Invalid block type type
Explanation	I/O from an unexpected database space is going to be logged so command logging has been deactivated.
Action	This is an unexpected error. Please contact your software supplier.

INORBE4067	Unable to open journal space
Explanation	An error has occurred when trying to open the journal space.
Action	Check that the journal space exists and is correctly defined.
INORBE4068	Reference to missing doctype detected
Explanation	A doctype that does not exist has been referenced.
Action	This is an internal error. Please contact your software supplier.
INORBF4013	Server is in startup phase, backup not possible.
Explanation	The server is still in the startup phase and therefore a backup is not possible. This is probably caused by another (offline) backup running, or the server being started.
Action	Wait until the other backup has finished, or the server has started, and run the backup again.
INORBF4251	Invalid block allocation detected (blocks are shared between different doctypes)
Explanation	The database server is in an inconsistent state.
Action	This is an internal error. Please contact your software supplier.
INORBF4253	Error error number during backup: error message
Explanation	A fatal error occurred during backup.
Action	Try to solve the problem based on the text of the error message. Otherwise, contact your software supplier.
INORBF4255	An error occurred when updating the internal configuration store
Explanation	The operation has been terminated because an error occurred while trying to update the internal configuration store.
Action	Please contact your software supplier and provide the message text of all messages displayed.
INORBF4257	Corrupt structure on backup copy
Explanation	The backup copy does not contain the correct structure.
Action	Check your input file assignments, and ensure that the correct backup copy is being used.

INORBF4259	Error occurred in I/O block blockno
Explanation	An I/O error has occurred on the specified block.
Action	The backup copy is corrupt; back up the database again to create another backup copy.
INORBF4260	Online backup already active
Explanation	Another backup function is active. Only one online backup is possible at one time.
Action	No action required.
INORBF4263	Utility not permitted to run
Explanation	This utility is currently not permitted to run.
Action	Wait until the database is available.
INORBF4265	Internal error found in backup copy
Explanation	An internal structure error has occurred in the backup copy. The backup copy may be corrupt. A possible cause of the error is that the backup copy was modified outside of Tamino.
Action	Check that the backup copy was not modified outside of Tamino. If the problem persists, please contact your software supplier.
INORBF4266	Block size of output file too small
Explanation	The block size of the output file is too small.
Action	Use an output device with a larger block size.
INORBF4267	Invalid record detected, block blockno
Explanation	The backup copy file has a structure error with printed information. This backup copy file cannot be used as input for a restore.
Action	Run the backup function again.
INORBF4268	Internal configuration delete by Tamino utility failed
Explanation	The final stage of saveset processing failed; the internal configuration is incorrect.
Action	Retry the operation.

INORBF4269	Internal configuration update by Tamino utility failed because key could not be moved
Explanation	A utility attempted to create an internal configuration entry, but this call failed for the stated reason. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.
Action	No action required. Please contact your system administrator for further information.
INORBF4270	Internal configuration get by Tamino utility failed because value could not be read
Explanation	A utility attempted to read the values for an internal configuration entry, but this call failed for the stated reason. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.
Action	No action required. Please contact your system administrator for further information.
INORBF4271	Internal configuration set by Tamino utility failed because value could not be set
Explanation	A utility attempted to set the value for an internal configuration entry, but this call failed for the stated reason. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.
Action	No action required. Please contact your system administrator for further information.
INORBF4272	Internal configuration get by Tamino utility failed because values could not be enumerated
Explanation	A utility attempted to count the number of values for an internal configuration entry, but this call failed for the stated reason. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.
Action	No action required. Please contact your system administrator for further information.
INORBF4273	Internal configuration create by Tamino utility failed
Explanation	A utility attempted to create a new internal configuration, but this call failed. The utility will now terminate, and the administration agent will carry out any necessary recovery tasks.
Action	No action required. Please contact your system administrator for further information.
INORBF4276	This operation is not allowed while the Tamino server is active
Explanation	The operation cannot be executed when the database has been started.
Action	Stop the database and retry the operation.

INORBI4063	Access to the Tamino server's shared memory is not possible
Explanation	It is not possible to access shared memory of the Tamino server. Synchronization with the server is lost. A possible cause is that the Tamino server has been shut down in the meantime.
Action	Retry the backup operation. If the problem persists, please contact your software supplier.
INORBI4452	Waiting for autorestart
Explanation	The utility action cannot be performed until the database has completed an autorestart.
Action	No action required.
INORBI4453	Initialization phase
Explanation	This is an informational message indicating that a utility is initializing.
Action	No action required.
INORBI4454	Waiting for transactions to commit
Explanation	The requested operation is waiting for all transactions to commit.
Action	No action required.
INORBI4455	Backup copy successfully checked
Explanation	The backup copy has been successfully checked.
Action	No action required.
INORBI4456	No doctype in backup copy
Explanation	The backup copy used for this operation does not contain any doctypes.
Action	No action required.
INORBI4457	Restore of database completed successfully
Explanation	The database has been successfully restored.
Action	No action required.

INORBI4459	Within allocation
Explanation	This informational message occurs when a utility is allocating space.
Action	No action required.
INORBI4464	Formatting of database_space completed
Explanation	This informational message indicates the completion time of the formatting operation.
Action	No action required.
INORBI4465	Formatting of database_space started
Explanation	This informational message indicates that the formatting operation has started.
Action	No action required.
INORBI4466	Database identification set to 'database_name'
Explanation	The database identification has been set to the specified name.
Action	No action required.
INORBI4468	Backup of database_space completed
Explanation	The indicated database space has been backed up.
Action	No action required
INORBI4469	Terminator block: type
Explanation	This message shows the value of the terminator block.
Action	No action required.
INORBI4475	New block allocations for doctype doctype
Explanation	New blocks have been allocated for the specified doctype.
Action	No action required.
INORBI4478	Doctype doctype contained in saveset
Explanation	The doctype specified is contained in the backup saveset.
Action	No action required.

INORBI4631	Backup of database completed successfully
Explanation	A database copy has been backed up successfully.
Action	No action required.
INORBQ4000	Error accessing database space extent no at location restore location
Explanation	The database space was not found at the specified location. There are many possible causes for this. The container may be corrupt or missing, the defined 'Location' may be missing or corrupt or you may not have sufficient access privileges for the specified location. If you have replaced a location and/or container that was previously missing, this error appears because the database server did not expect the container to re-appear after it detected it was missing.
Action	Verify that the container exists in the correct location. If you have replaced a previously missing container, please move it out of the way to allow the database server to recreate the container and allow the restore process to continue. If the problem persists, please contact your software supplier.
INORBQ4001	Confirm location for recreation of database space extent no
Explanation	Confirm the location for recreation of the database space.
Action	Enter the location name.
INORBR4681	Backing up database_space
Explanation	The specified server space is being backed up.
Action	No action required.
INORBS4009	Restoring database with reorganization ...
Explanation	The database is being restored and a data reorganization will be done..
Action	No action required.
INORBS4458	Restoring database ...
Explanation	The database is being restored.
Action	No action required.

INORBV4012	Doctype loaded = loaded_doctypes; actual number of doctypes = actual_doctypes
Explanation	The number of doctypes loaded differs from the number of doctypes in the backup copy.
Action	Please contact your software supplier with an exact description of the functions that caused the error.
INORBW4010	External backup/restore request failed, detailed info in file filename
Explanation	The specific external backup or restore action failed due to an internal reason. Please view the output file indicated by the error message for the problem.
Action	Analyze the problem in the error file.
INORBW4015	The space size will be increased by size MB
Explanation	The container size specified during create is not sufficient. Tamino is automatically extending the container to accommodate the data.
Action	No action required.
INORBW4803	Database identification could not be changed
Explanation	The database identification could not be changed.
Action	Ensure that the database identification of the new database is correct.
INORBW4805	Waiting for database restart
Explanation	The operation is waiting for the restart of the database (due to its abnormal termination).
Action	Start the database.
INORBW4806	Block block number ignored, run verify and repair function for doctype doctypes
Explanation	During backup a corrupt index block was found which will not be backed up to the backup copy.
Action	Recreate the index of specified doctype and rerun the backup function.
INOSAE7351	Duplicate attribute not allowed in element context
Explanation	The result element will contain multiple attributes of the same name. This is not allowed in XML.
Action	Please verify your query for attribute construction.

INOSAE7352	No serialization for attributes without element context
Explanation	A serialization of attributes without element context was requested but is undefined.
Action	Please verify that the attribute construction belong to an element context.
INOSAE7353	ino:document serialization supports only one document in serialization
Explanation	The ino:document serialization supports only the serialization of a single document.
Action	The query returns more than one document. Correct the query and rerun.
INOSAE7354	ino:serialization supports only the serialization of document nodes
Explanation	The ino:document serialization supports only the serialization of document nodes.
Action	Verify that the query returns only nodes of type document.
INOSAE7356	ino:document serialization has no Query Result
Explanation	The query returned no matching document.
Action	Correct the query so that it delivers one single document node.
INOSAI7355	Internal error
Explanation	During the serialization an internal error occurred.
Action	Please contact your software supplier.
INOSXE6704	Invalid character 'character' in name for compiler settings
Explanation	Names for compiler settings must start with a letter and may be followed by letters or digits.
Action	Use a name that obeys this rule.
INOSXE6705	Settings for default parameter must not be changed
Explanation	The name 'default' is reserved for the compiler settings defined by the Tamino installation.
Action	Use a name other than 'default' to save these compiler settings.
INOSXE6706	No configuration parameters found for compiler 'compiler'
Explanation	The current compiler for Direct X-Tension projects is currently set to the compiler indicated; however, one or all of its configuration parameter files have been deleted.
Action	Use the default compiler as your current compiler; check your Tamino installation.

INOSXE6707	X-Tension: COM initialization failed
Explanation	During X-Tension initialization the initialization of the COM library failed. No COM-based extension functions are available during this server session.
Action	If COM-based server extension functions are required, fix the COM problem and start the Tamino server again.
INOSXE6709	Invalid usage entry: 'value'
Explanation	The Usage entry found in file 'Install.xml' could not be recognized.
Action	Check the documentation for valid values.
INOSXE6710	Function 'function' not usable as 'usage'
Explanation	This function cannot be used as the function type indicated. The function's parameter count or parameter datatypes do not correspond to the specified function type.
Action	Please check the 'Usage' entry in file 'Install.xml' as well as the parameter specification of the current function. See the documentation for the parameters required for the given Usage. It is strongly recommended to use the X-Tension development tools to define new X-Tension functions.
INOSXE6711	Value missing for Init Function 'func'
Explanation	The X-Tension function indicated has been declared as Init Function. However, values are missing for one or more of its parameters.
Action	Use the X-Tension tools to create the X-Tension function and be careful editing the file Install.xml.
INOSXE6712	The server extension crashed or threw an unknown exception
Explanation	Either the server extension has crashed or it threw an exception that could not be caught by the Tamino Server.
Action	Please contact the vendor of the server extension.
INOSXE6713	Extension tried to open message box. Message: 'message'.
Explanation	It is not allowed to display message boxes in a server extension. This terminates the current server extension function.
Action	Please check the server extension code carefully. Maybe the C/C++ runtime system tried to open an assertion box because of programming errors in the server extension.

INOSXE6714	Value is not of the selected data type 'type'
Explanation	The value entered cannot be converted to the data type selected in the 'Add Param' box.
Action	Please check the value entered and the data type selected in the 'Add Param' box. See the documentation of Tamino X-Tension for more details on allowed values.
INOSXE6715	Extension function 'func': Value of parameter 'param' is not of selected data type type
Explanation	The value entered cannot be converted to the data type specified for this parameter.
Action	Please check the value entered and the data type specified for this parameter. See the documentation of Tamino X-Tension for more details on allowed values. Use the Tamino X-Tension tools to specify parameter values!
INOSXE6716	Unexpected error during callback function 'function'
Explanation	An unexpected error occurred during a call of a callback function. Probably it has been called with one or more incorrect parameters.
Action	Check the documentation and your server extension code for the correct use of this callback function.
INOSXE6717	Server extension function not found
Explanation	The desired function name was not found in the SXS repository. Maybe the function name is incorrect, or the function is not installed or was deactivated.
Action	Check and correct the function name or server extension installation.
INOSXE6725	Callback not allowed in init function
Explanation	An Sxs SetProperty callback is not allowed from a server extension init function.
Action	Remove the Sxs SetProperty callback from your server extension init function and retry the operation.
INOSXE7000	Java server extension must have a package name
Explanation	The package name for a Java server extension must not be empty.
Action	Define a package name, e.g. "package com.softwareag.mysxs".

INOSXE7001	File name 'file.sxp' may not be changed
Explanation	Only the directory may be selected; the file name must remain unchanged.
Action	Select a directory.
INOSXE7006	XML callback failed. Transaction was rolled back.
Explanation	No more information.
Action	Try with a modified XML request.
INOSXE7009	Tamino X-Tension not available
Explanation	It is not possible to call a Tamino server extension because either X-Tension is not licensed or the X-Tension feature is not available on this platform.
Action	If possible, buy a license for Tamino X-Tension.
INOSXE7010	Project must be rebuilt before packing. Reason: 'reason'.
Explanation	The project must be rebuilt. See 'reason' for more information.
Action	Call Build / Build <project name> in the Developer Studio before packing.
INOSXE7014	Main class file cannot be removed
Explanation	In the Packaging Dialogue of the X-Tension Builder, the class file is about to be removed that contains the main class of the current server extension.
Action	Do not remove this class file from the list or select a jar file containing this class.
INOSXE7015	Callback not allowed in event function
Explanation	From Tamino server event functions, XML and ODBC callback are not allowed.
Action	Remove the callback call from your server extension code.
INOSXE7016	Illegal database command in callback
Explanation	A database command that is not allowed in callbacks was called in a callback.
Action	Remove the database command from the callback and try again.
INOSXE7017	Tamino server error when calling callback
Explanation	An error occurred in the Tamino server when processing the callback, perhaps an XML or query syntax error.
Action	Method SXJBase.SXSGetInoMsgNo () gives the error code of the Tamino server.

INOSXE7018	Not enough memory for callback
Explanation	The Tamino server could not allocate enough memory to process the callback.
Action	Try to repeat your query when the Tamino server is less loaded.
INOSXE7019	SQL error when calling ODBC callback
Explanation	An SQL error occurred while processing an ODBC callback, perhaps due to an SQL syntax error.
Action	Method SXJBase.SXSGetSQLMsgNo () gives the SQL error code.
INOSXE7020	Illegal handle type for ODBC callback
Explanation	The ODBC callback methods SxsSQLAllocHandle and SxsSQLFreeHandle are only allowed for statement handles of type SQL_HANDLE_STMT.
Action	We recommend that you use the constant SXJBase.SQL_HANDLE_STMT as the parameter handle type.
INOSXE7021	Commit and rollback are not allowed in callbacks
Explanation	You must not use the database commands "commit" or "rollback" in your server extensions.
Action	Remove these commands from the server extension and try again.
INOSXE7022	Result buffer for callback not initialized
Explanation	Result buffers for callbacks must not be null, but should be initialized with an empty string.
Action	Ensure that all result buffers are initialized.
INOSXE7023	Function 'name' failed, because XML callback failed with error 'no'
Explanation	An XML callback failed while trying to perform a write operation. To avoid inconsistencies, the extension function must return with an error.
Action	Check the error caused by the XML callback and fix the problem that caused it to fail.
INOSXE7024	COM error when calling callback
Explanation	A COM error occurred during a callback.
Action	Consult your COM documentation.

INOSXE7025	Another server extension deinstallation is running
Explanation	Only one server extension can be deinstalled at any given time.
Action	Wait until the other deinstallation procedure has finished.
INOSXE7026	Deinstallation timed out. The server extension is in use.
Explanation	A server extension cannot be deinstalled as long as an instance of it is in use. The deinstallation procedure has timed out.
Action	Try it later. If there is a very long running instance of the server extension, try to stop it.
INOSXE7027	The function cannot be executed. The server extension is being deinstalled.
Explanation	This function belongs to a server extension that is just being deinstalled.
Action	The function cannot not be called again. If you need to, contact the database administrator.
INOSXE7032	Cannot create directory 'dir'
Explanation	This directory cannot be created. Maybe the disk drive is unavailable or write protected.
Action	Check the given path and your disk drive.
INOSXE7034	Server extension 'source' threw exception 'errnr', 'errtext'
Explanation	The server extension threw an exception. The number and message of the exception are delivered.
Action	See the documentation of the server extension in question for more information.
INOSXE7040	Extension function name too long: 'name'
Explanation	The complete extension function name, consisting of the extension's name plus the function name plus a dot, must not exceed the length of 80 characters.
Action	Select a shorter name.
INOSXE7041	Wrong character in field: 'char'
Explanation	Some special characters (ampersand, "less than", "greater than") are not allowed in comment fields for a server extension. This affects the "Short description" fields and the "Author" field.
Action	Avoid these characters.

INOSXE7045	X-Tension Trace failed. Transaction was rolled back.
Explanation	An internal server error occurred while X-Tension Trace information was written to the Tamino server.
Action	Deactivate X-Tension Trace
INOSXE7046	XML Callback failed in user session. Transaction must be rolled back.
Explanation	A writing XML call from a server extension failed. The current transaction should be rolled back for consistency reasons.
Action	Perform a rollback request.
INOSXE7047	X-Tension Trace failed in user session. Transaction must be rolled back.
Explanation	An internal server error occurred. The current transaction should be rolled back for consistency reasons.
Action	Deactivate X-Tension Trace
INOSXE7048	Error starting help browser. Reason: 'reason'.
Explanation	The currently configured help browser could not be started. See "reason" for more details.
Action	Use the function "Help/Configure Help Browser" to change your current help browser.
INOSXE7049	'execfile' execution failed: rc = rc
Explanation	The external program 'Program name' was successfully started but it returned with error.
Action	See the context of this error message for more information.
INOSXE7051	COM error 'errno' occurred: 'errtext'
Explanation	A COM error occurred. The COM error number of type HRESULT is delivered.
Action	Consult the COM documentation for more information.
INOSXE7052	COM error 'errno' calling 'dllname': 'errtext'
Explanation	A COM error occurred. The COM error code of type HRESULT and the name of the Tamino server extension DLL which was called is delivered.
Action	Consult the COM documentation for more information.

INOSXE7053	Error 'errno' calling data map: 'errtext'
Explanation	An error occurred when the Tamino server extension part of the data map was accessed. The error number and message received from the Tamino data map is delivered.
Action	Look up the delivered error number and see the action described there.
INOSXE7054	X-Tension system function cannot be deleted
Explanation	An attempt was made to delete a function which is needed for the X-Tension administration.
Action	No action required.
INOSXE7055	The server extension threw exception 'errtext'.
Explanation	The server extension threw an exception. The message and occasionally the number of the exception are delivered.
Action	See the documentation of the server extension in question for more information.
INOSXE7056	X-Tension caller: Not enough memory
Explanation	There was not enough memory for execution of the server extension function.
Action	Close some applications and try again.
INOSXE7057	X-Tension caller: internal error
Explanation	Internal errors occurred within the X-Tension administration structure.
Action	Please contact your software supplier.
INOSXE7058	X-Tension caller: got no spinlock. Reason: 'retval'.
Explanation	An error occurred within the thread synchronization. A server extension could not be locked. The return value received from the thread administration is delivered.
Action	Please contact your software supplier.
INOSXE7059	X-Tension caller: could not get data map information
Explanation	The X-Tension caller was unable to get any data map information.
Action	Please contact your software supplier.

INOSXE7060	Mapping function 'n': Wrong number of parameters implemented. Expected: 'm'.
Explanation	A Tamino server extension mapping function does not support the number of parameters needed for this function type.
Action	Install a correctly implemented server extension.
INOSXE7061	Extension function 'n': Wrong type of parameter 'm' implemented
Explanation	A mapping function does not support the correct parameter types.
Action	Compare the parameter type for this type of extension function as described in the manual with the parameter type supported by the extension function (found using Tamino Manager). Install a correctly implemented extension function.
INOSXE7062	X-Tension caller: initialization failed
Explanation	The X-Tension caller was not initialized when the Tamino server was started. It is impossible to call any extension function, maybe because server extension libraries could not be loaded.
Action	Check your Tamino installation.
INOSXE7063	X-Tension caller: 'No' server event calls failed
Explanation	A server event call to some server extensions failed. The number of failures is delivered.
Action	Please contact your software supplier.
INOSXE7064	Unexpected end of file encountered before end of source
Explanation	During the parsing of the X-Tension installation file, IDL file or one of the server extension source files, an unexpected end of file was found.
Action	Check the syntax of the file(s).
INOSXE7065	Syntax error. Token: 'Token'.
Explanation	An unspecified error was encountered during parsing near or at the place specified by 'Token'.
Action	Check the syntax of the X-Tension installation file.
INOSXE7066	Unbalanced tag / end tag: 'tag1' / ' tag2'
Explanation	In the X-Tension installation file, the names of begin-tag and end-tag are different.
Action	Check the syntax of the X-Tension installation file.

INOSXE7067	Tag 'tagname' not found
Explanation	The specified mandatory tag was not found in the X-Tension installation file.
Action	Check the syntax of the X-Tension installation file.
INOSXE7068	Tag 'tagname' is not a value
Explanation	A simple value was expected for the specified tag, but a node has been found.
Action	Check the syntax of the X-Tension installation file.
INOSXE7069	Tag 'tagname' is not a node
Explanation	A node was expected for the specified tag, but a simple value has been found.
Action	Check the syntax of the X-Tension installation file.
INOSXE7070	Duplicate name: 'name'
Explanation	The specified tag name was found twice in the X-Tension installation file.
Action	Check the syntax of the X-Tension installation file.
INOSXE7071	Error 'character' expected
Explanation	The specified character was expected but not found in the X-Tension installation file or one of the server extension source files.
Action	Check the syntax of the X-Tension installation file and the server extension source files.
INOSXE7072	Error 'character' expected, eof found
Explanation	The specified character was expected, but an end of file was found in the X-Tension installation file or one of the server extension source files.
Action	Check the syntax of the X-Tension installation file and the server extension source files.
INOSXE7073	IDL file 'segment name' is corrupt
Explanation	A syntax error was found in the IDL file for the definition of the server extension interface at or near the specified keyword.
Action	Check the syntax of the IDL file.

INOSXE7074	'SXF' not defined in interface
Explanation	The specified function has been defined in the X-Tension installation file but it had not been entered into the IDL file for the server extension interface.
Action	Remove the function definition from the X-Tension installation file and use the X-Tension Developer Studio add-in to define a new one.
INOSXE7075	Return type must be HRESULT, not 'type'
Explanation	A COM server extension must always return HRESULT.
Action	Use the [retval] attribute for the last parameter as a return value of the server extension function.
INOSXE7076	Method 'method': Different parameter names: 'param1' / 'param2'
Explanation	The parameter name of the indicated server extension function in the X-Tension installation file is different from that defined in the IDL file.
Action	Check the implementation of the server extension function; use the X-Tension Developer Studio add-in to define a server extension function.
INOSXE7077	Too many parameters: 'SXF'
Explanation	The specified server extension function has been implemented with more parameters than are defined in the X-Tension installation file.
Action	Check the implementation of the server extension function; use the X-Tension Developer Studio add-in to define a server extension function.
INOSXE7078	Cannot map parameter type
Explanation	A parameter type is used in the COM interface that cannot be used for server extension function parameters.
Action	Use the X-Tension Developer Studio add-in to define a server extension function.
INOSXE7079	Server extension implementation file could not be found
Explanation	The X-Tension Developer Studio add-in could not find the file with the implementation of the class for the server extension.
Action	Use the X-Tension development tool to create a server extension.

INOSXE7080	Unknown XML data type: 'type'
Explanation	The specification of the XML data type for a server extension function parameter is wrong. See the documentation for allowed data types.
Action	Use the X-Tension Developer Studio add-in to define a new server extension function.
INOSXE7081	Unknown programming language data type: 'type'
Explanation	The function implementation uses a data type for one of its parameters that is not supported when using this function as a server extension function. See the documentation for the allowed data types in this programming language
Action	Use the X-Tension development tools to define a server extension function.
INOSXE7082	Unknown execution mode: 'mode'
Explanation	The specified server extension execution mode is wrong. Allowed modes are: COM-INPROC, COM-LOCAL.
Action	Use the Tamino Manager to change this mode.
INOSXE7083	Wrong numeric value: 'val'
Explanation	The value was expected to be numeric but the given value is not numeric.
Action	Enter a numeric value here.
INOSXE7084	Wrong parameter position
Explanation	The parameter position in the X-Tension installation file must start at 1.
Action	Check the parameter position values. Use X-Tension Developer Studio add-in to define a new server extension function.
INOSXE7085	Cannot open file 'name'
Explanation	The specified file could not be opened.
Action	Check if this file really exists, or if it is locked by another process.
INOSXE7086	Wrong version format: 'string'
Explanation	The server extension version is supposed to be of the form major.minor
Action	Check the server extension version.

INOSXE7087	Event function 'function' not found
Explanation	An event function has been specified in the SXS-EVENT-FUNCTION tag of the X-Tension installation file, but it could not be found in an SXS-FUNCTION tag.
Action	Delete the event function specification tag and use the X-Tension Developer Studio add-in to specify a new one.
INOSXE7088	Wrong document type for X-Tension administration: 'type'
Explanation	The document type (second level tag) of the X-Tension administration file is wrong. Allowed types are: SXS-INSTALL, SXS-DELETE, SXS-SHOW, SXS-RETURN.
Action	For a server extension installation, only SXS-INSTALL is valid.
INOSXE7089	Missing XML attribute 'attribute' for SXS-SHOW
Explanation	No attribute is given for the X-Tension administration type tag SXS-SHOW.
Action	One of the attributes list, object, function, permission, document must be given for the SXS-SHOW tag.
INOSXE7090	Wrong XML attribute: 'attribute'
Explanation	A wrong attribute is given for the X-Tension administration type tag SXS-SHOW.
Action	One of the attributes list, object, function, permission, document must be given for the SXS-SHOW tag.
INOSXE7091	Wrong parameter attribute: 'attribute'
Explanation	A wrong parameter attribute has been specified in the X-Tension installation file. Allowed attributes are: input, output, inout, retval.
Action	Use the X-Tension Developer Studio add-in to define a new server extension function.
INOSXE7092	No current project
Explanation	There is no project open in Developer Studio. The X-Tension add-in will not work.
Action	Open a server extension project first.
INOSXE7093	This is not a C/C++ project
Explanation	The X-Tension add-in will not work for Java or Visual Basic projects.
Action	Open a C/C++ project.

INOSXE7094	This is not an X-Tension project
Explanation	The current project has not been created by an X-Tension development tool.
Action	Use the X-Tension development tool to create a server extension.
INOSXE7095	File 'filename' is read-only
Explanation	The specified file is read-only. Therefore, the X-Tension Developer Studio add-in cannot add the specifications for the new server extension function to it.
Action	Change the ReadOnly parameter of the specified file.
INOSXE7096	System error: 'errtext'
Explanation	An operating system error occurred in the X-Tension Developer Studio add-in.
Action	Check the operating system documentation for further details.
INOSXE7099	Cannot write to file 'filename'
Explanation	The file has been opened, but a write operation failed. Possibly the disk is full.
Action	Check your hard disk space.
INOSXE7100	Wrong package file: 'filename'
Explanation	The file specified is not an output file of the X-Tension Developer Studio add-in package function.
Action	Only use package files created by the X-Tension Developer Studio add-in.
INOSXE7101	Could not get XML session status. Server extension function rolled back at request end.
Explanation	The X-Tension caller could not determine whether there was a regular or an anonymous XML session. So the Tamino server event 'rollback' was sent to all server extensions.
Action	No action required.
INOSXE7102	Initialization of server extensions: server events not activated
Explanation	The Tamino server events could not be activated when the Tamino server was started. Server extensions are not initialized and will not work.
Action	Restart the Tamino server. If this does not give the desired result, please contact your software supplier.

INOSXE7103	Developer Studio automation error 'errno' (errtext)
Explanation	The add-in caused an error when executing a Developer Studio command.
Action	Consult the Developer Studio documentation for further information.
INOSXE7104	Method 'method' could not be found in file 'objfile'
Explanation	The method indicated is not defined in the current server extension object file (Java class file or DLL/Shared Object), or another severe error occurred when accessing the server extension object file.
Action	Check the server extension project for the desired method. Use the X-Tension development tools for developing server extensions!
INOSXE7105	Project must be rebuilt before packing: 'file' is newer
Explanation	One of the project sources is newer than the resulting server extension package.
Action	Call Build / Build <project name> in the Developer Studio before packing.
INOSXE7106	One or more input fields are empty
Explanation	All fields of this form must be set, but at least one field is empty.
Action	Make sure that all fields are correctly set.
INOSXE7107	'name' is not a valid identifier
Explanation	The name entered does not match C/C++ naming conventions.
Action	Check the name for proper syntax.
INOSXE7108	Value for 'valuename' of a server extension not found in data map
Explanation	A value for the specified name of a server extension was expected in the data map but is not present. The problem occurs due to problems at installation or in the repository. Here, the specified name is the name of an expected value.
Action	Re-install the server extension.
INOSXE7109	Memory allocation failed
Explanation	Memory allocation failed.
Action	Please contact your software supplier.

INOSXE7110	Character conversion failed; error code = 'errcode'
Explanation	An internal character conversion failed.
Action	See the Tamino documentation for the given error code. Check if Tamino is properly installed.
INOSXE7113	Cannot find function 'funcname' in library 'libname'
Explanation	The specified function name could not be found in the library. Maybe there is a version problem.
Action	Check your Tamino installation.
INOSXE7114	Java error: Errtext: 'errtext'. Stacktrace: 'trace'.
Explanation	A Java error occurred. See "Errtext" for more specific details. "Stacktrace" is the exception stack trace.
Action	See "Errtext" for more specific details and correct the code accordingly.
INOSXE7115	Cannot create Java virtual machine; error 'errcode'
Explanation	The Java virtual machine could not be started.
Action	Check the Java documentation for the given error code.
INOSXE7116	Function 'sxfname' not found in server extension 'sxsname'
Explanation	The function could not be found in the server extension. Probably the server extension implementation has been changed after installation.
Action	Try to re-install the server extension.
INOSXE7117	Illegal call for Java method 'methodname' in class 'classname'
Explanation	An error occurred during a call for a Java method. Probably the parameter count or the type(s) of at least one parameter is incorrect. For a server extension function, its implementation may have changed since the last installation.
Action	Re-install this server extension.
INOSXE7118	'package' not available on this platform
Explanation	The package specified (COM, Java or Direct) is not available on this platform. Server extensions based on this package cannot be executed.
Action	No action possible. This server extension cannot be run.

INOSXE7119	'package' not installed on this platform
Explanation	The package specified (COM or Java) is not installed on this platform.
Action	To run server extensions based on this package, install the specified package.
INOSXE7120	X-Tension caller: parameter overflow, function 'name' parameter number 'no'
Explanation	The input value was too small or too big.
Action	Change the input value and try again.
INOSXE7121	XQL query function 'n': Wrong number of parameters. Required: 'm'.
Explanation	The user passed a wrong number of parameters to a function called from within an XQL query.
Action	Repeat the call with the correct number of parameters.
INOSXE7122	XQL query function 'n': Wrong type of parameter 'm'
Explanation	The user input is of the wrong data type.
Action	Get information about parameter types of called functions (see the Tamino Manager or the third party manual for the corresponding server extension) and repeat the call with the correct input.
INOSXE7123	Java error during initialization of Java server extension: 'errtext'
Explanation	The error text gives detailed information about the error.
Action	Correct the fault and try again.
INOSXE7124	Java error during call: 'errtext'
Explanation	The error text gives detailed information about the error.
Action	Correct the fault and try again.
INOSXE7125	Java error during server extension function parameter handling: 'errtext'
Explanation	The error text gives detailed information about the error.
Action	Correct the fault and try again.

INOSXE7126	Server extension failed
Explanation	An error occurred when a Tamino server extension was called. The message is followed by another more detailed message.
Action	Analyze the detailed message and act accordingly.
INOSXE7127	X-Tension : Java initialization failed
Explanation	During X-Tension initialization the initialization of the Java virtual machine failed. No Java-based extension functions are available during this server session.
Action	If Java-based server extension functions are required, fix the Java problem (e.g. paths and internal configuration store entries) and start the Tamino server again.
INOSXE7129	'location': Got no spinlock. Reason: 'retval'.
Explanation	There is no lock available for your thread.
Action	Try again later.
INOSXE7130	Internal error when 'location'
Explanation	An unknown internal error occurred.
Action	Please contact your software supplier.
INOSXE7132	'unusedinfrastructur' infrastructure is not available or currently disabled
Explanation	The X-Tension infrastructure specified is either not available in this environment or is currently configured as disabled in the Tamino server parameters.
Action	If the required infrastructure is available in this environment, turn on the appropriate switch of the Tamino server parameters and restart the Tamino server to activate it. If the infrastructure is not available, the relevant server extension code attempting to use it should be modified to utilise a supported infrastructure.
INOSXE7136	Wrong command line for the server extension wrapper tool: 'arg'
Explanation	The command line for the server extension wrapper tool has incorrect syntax.
Action	Please check the documentation for the command line syntax of the server extension wrapper tool or use the server extension development tools to set up a direct server extension project.

INOSXE7137	Duplicate option 'c'
Explanation	The given option may not occur more than once in the command line for the server extension wrapper tool.
Action	Please check the documentation for the command line syntax of the server extension wrapper tool or use the server extension development tools to set up a direct server extension project.
INOSXE7138	Wrong option 'c'
Explanation	The given option is invalid in the command line for the server extension wrapper tool.
Action	Please check the documentation for the command line syntax of the server extension wrapper tool or use the server extension development tools to set up a direct server extension project.
INOSXE7140	No valid JVM, install valid JVM or switch X-Tension Java Usage to 'NO'
Explanation	Error detected when loading a JVM for current Tamino version
Action	Check if JVM is installed, if a valid JVM Version is installed or switch X-Tension Java Usage to 'NO'.
INOSXE7141	Server extension 'name' already locked
Explanation	The server extension is locked by another operation.
Action	Retry the requested operation when the lock has been removed.
INOSXE7142	Server extension 'name' is active
Explanation	The server extension is in use.
Action	Retry the requested operation when the server extension has finished.
INOSXE7143	Server extension 'name' not found
Explanation	The server extension does not exist.
Action	Correct the server extension name and retry the operation.
INOSXE7144	Server extension function 'name' not found
Explanation	The server extension function does not exist.
Action	Correct the function name and retry the operation.

INOSXE7145	Wrong modification operation 'type'
Explanation	The requested modification operation is not implemented.
Action	Correct the modification operation type and retry the operation.
INOSXE7146	Wrong execution mode 'mode'
Explanation	The requested execution mode is not allowed.
Action	Correct the execution mode and retry the operation.
INOSXE7147	Files for server extension 'name' not restored
Explanation	Some files of the server extension have not been restored.
Action	Ensure that the Tamino server has write access to the file system and retry the operation.
INOSXE7148	Files for server extension 'name' not removed
Explanation	Some files of the server extension have not been removed.
Action	Ensure that the files are not locked by another action and retry the operation.
INOSXE7149	Files for server extension 'name' not stored
Explanation	Some files of the server extension have not been stored.
Action	Ensure that the files are not locked by another action and retry the operation.
INOSXE7150	Installation document for server extension 'name' not stored
Explanation	The installation document of the server extension has not been stored.
Action	Ensure that the installation document is not locked by another action and retry the operation.
INOSXE7151	Event Function call failed for server extension: a, Event: b
Explanation	Event functions are for cleaning up server extension data after commit, rollback, session end and so on. See the X-Tension manual (server extension Functions/Server Event Functions), for information about which event failed.
Action	Analyze the cause of failure. If necessary, ask the programmer or vendor of the server extension. Check the data that was written outside the Tamino server by the failed extension for consistency.

INOSXE7152	Attribute 'hidden' cannot be assigned to or removed from this parameter
Explanation	An attempt was made to assign or remove the 'hidden' attribute. This operation is only successful if the parameter has the 'input' direction (for assignment) or the parameter is 'hidden' (for removal).
Action	Check the server extension function and its parameters and read the documentation.
INOSXE7153	This parameter cannot be assigned a default value
Explanation	To assign a default value to a parameter, this parameter must have the 'input' direction.
Action	Check the current server extension function and its parameters.
INOSXE7154	Wrong position for optional / hidden parameter
Explanation	The order for parameters must be: mandatory - optional - hidden - return value.
Action	Please check the order of the server extension function's parameters and their usage.
INOSXE7158	Server extension function parameter 'name' not found
Explanation	The server extension function parameter does not exist.
Action	Correct the parameter name and retry the operation.
INOSXE7160	Duplicate occurrence of 'functiontype'
Explanation	Only one event function or init function may be defined within a server extension.
Action	Check your server extension and delete one of the functions that is superfluous, or use the X-Tension development tools to create and edit the server extension.
INOSXE7161	Invalid input for field: field
Explanation	The user input for the specified field is invalid. Either invalid characters have been used or the format of the characters used is incorrect.
Action	Please correct the specified field.
INOSXE7162	Document not found for specified ino:id/docname
Explanation	A document could not be found using the specified ino:id or docname.
Action	Please specify a valid ino:id or docname.

INOSXE7255	Java Exception
Explanation	Specified Java exception occurred
Action	Resolve the specified Java exception
INOSXF6718	Timeout during execution of server extension function
Explanation	Possible reasons are: 1) There is an endless loop in the server extension function. 2) A server extension function is executed with endless recursion.
Action	Check the server extension carefully. For example, calling the callback SxsXmlProcess will result in an endless recursion if the collection name is the same as the current server extension function is assigned to.
INOSXF6719	Process 'exefile' (for Direct Local) has stopped with rc = rc
Explanation	The external process for X-Tension direct infrastructure (local mode) has aborted. See error for more details.
Action	Check your server extension. Probably it killed the external process for local mode.
INOSXF6720	Stack overflow in server extension function
Explanation	A stack overflow occurred during call of a server extension function.
Action	Check your server extension. Perhaps it has endless recursion.
INOSXF7028	Illegal call of Connect/Disconnect
Explanation	This error may occur in a Visual Basic or Natural implementation of a server extension. Reasons for this error may be: The Connect and Disconnect methods of the InoCallback interface have been called outside ISXSConn_Connect or ISXSConn_Disconnect or have been called there more than once.
Action	Implement ISXSConn_Connect and ISXSConn_Disconnect exactly as shown in the documentation. Do not call the Connect and Disconnect methods of InoCallback outside ISXSConn_Connect and ISXSConn_Disconnect.
INOSXF7030	'tool' does not support server extensions of type 'type'
Explanation	The X-Tension Builder tried to open a COM server extension.
Action	With the X-Tension Builder, open Java or Direct server extensions only.

INOSXF7033	Server extension 'sxsname' not properly installed. Reason: 'reason'.
Explanation	One or more installation steps for this server extension have been skipped or failed. See 'Reason' for more information.
Action	Use the X-Tension Administration of the Tamino Manager to install the server extension.
INOSXF7035	Cannot load library sxcall
Explanation	The library sxcall necessary for Tamino X-Tension cannot be loaded. Therefore no server extensions can be executed in this Tamino installation.
Action	Check your Tamino installation.
INOSXF7036	Cannot load a function in library sxcall
Explanation	Not all functions necessary to run Tamino X-Tension can be found in library sxcall. Therefore no server extensions can be executed in this Tamino installation. Probably there is a version mismatch between the library sxcall and the rest of Tamino.
Action	Check your Tamino installation.
INOSXF7037	Internal configuration store entry not found
Explanation	An internal configuration store entry necessary to initialize Tamino X-Tension or one of the Tamino X-Tension components cannot be found. If this error occurs during Tamino startup, no server extensions can be executed in this Tamino installation.
Action	Check your Tamino installation.
INOSXF7038	Cannot find current version in internal configuration store
Explanation	The 'current version' entry in the internal configuration store that is necessary to initialize Tamino X-Tension or one of the Tamino X-Tension components cannot be found. If this error occurs during Tamino startup, no server extensions can be executed in this Tamino installation.
Action	Check your Tamino installation.
INOSXF7039	Cannot load jvm library
Explanation	The jvm library (libraries) necessary to run Java server extensions cannot be loaded. Therefore no server extensions can be executed in this Tamino installation.
Action	Check your Tamino installation as well as your Java installation. Look if \$LD_LIBRARY_PATH on UNIX (or %PATH% on Windows) includes all required JDK directories.

INOSXF7042	Cannot find executable file 'execfile'
Explanation	The indicated file could not be found in any of the directories listed in PATH.
Action	Check installation(s) on your computer and check your PATH setting.
INOSXF7043	Tamino X-Tension not properly installed. Reason: 'reason'.
Explanation	The X-Tension development tool cannot create a new server extension project because Tamino X-Tension component is not properly installed on your computer.
Action	Use the Install Tool for a correct installation of Tamino X-Tension.
INOSXF7044	Error calling 'execfile'. Reason: 'reason'.
Explanation	An error occurred while trying to start an external process with the indicated file. See the additional text for more details.
Action	Check the given file for correctness.
INOSXF7097	Tamino X-Tension not properly installed
Explanation	The X-Tension development tool cannot create a new server extension project because Tamino X-Tension component is not properly installed on your computer.
Action	Use the Install Tool for a correct installation of Tamino X-Tension.
INOSXF7098	Fatal error
Explanation	An unspecified error occurred.
Action	Please contact your software supplier.
INOSXF7111	Server extension 'xsxname' not properly installed
Explanation	One or more installation steps for this server extension have been skipped or failed.
Action	Use the X-Tension Administration of the Tamino Manager to install a server extension.
INOSXF7112	Cannot load library 'libname': error 'rc'
Explanation	The specified library could not be loaded. Maybe it has been moved from its original location, or environment variables or internal configuration store entries have been changed since the last Tamino installation.
Action	Check your PATH and your Tamino installation.

INOSXF7133	No class has been found that can be used as a direct server extension class.
Explanation	Either there is no class defined in the given header file or none of the classes defined here can be used as a direct server extension.
Action	Please check the documentation about requirements for direct Server Extension classes or use the X-Tension development tools to create a Server Extension.
INOSXF7134	There are at least two classes ('class1', 'class2') that can be used as direct server extensions
Explanation	A header file that should be processed by the direct server extension wrapper tool may define only one class that can be used as a direct server extension.
Action	Please check the documentation on how to mark C++ classes for use as direct server extensions or move all class definitions except the direct server extension class to a different header file.
INOSXF7155	Internal error: 'id'
Explanation	A severe internal error occurred.
Action	Please note the value of the internal error and contact your software supplier.
INOSXF7156	Cannot start process 'exefile' for X-Tension direct infrastructure (local mode)
Explanation	The system cannot start a new process for X-Tension direct infrastructure (local mode).
Action	Check the existence of the file indicated. It should be located in directory Tamino/<version>/bin.
INOSXF7157	Process 'exefile' (for Direct Local) is not running
Explanation	The external process for X-Tension direct infrastructure (local mode) has aborted or is not running for other reason.
Action	Check your server extension. Perhaps it killed the external process for local mode.
INOSXF7251	Thread could not be attached to JVM, return code 'rc'
Explanation	The current XML worker thread could not be attached to the Java virtual machine. Tamino server extensions were not initialized. The return code is the return value of the JNI call "AttachCurrentThread()".
Action	Analyze why the Java call failed and solve the cause of the problem. Then start Tamino server again.

INOSXF7252	Metadata update failed: id
Explanation	Metadata update has failed.
Action	<p>In the case of CentraSite database startup failure indicated by the production of the console message: "INOSXF7252: Metadata update failed" the following information is essential to analyse the problem.</p> <p>The most useful file in these circumstances is the "inosrv.txt" file. This is normally called something like AABinosrv.HH-MM-SS.txt and would normally be present in the same directory as the actual database data files.</p> <pre>inoadmin set CentraSite "request log" "full" norestart</pre> <pre>inoadmin set CentraSite "X-Tension Java Options" "\$-Dlog4j.configuration=file://{full path to log4j.properties}" restart</pre> <pre>log4j.rootLogger=WARN, file</pre> <pre>log4j.logger.com.centrasite.centrasite.onstartup=DEBUG</pre> <pre>log4j.appender.file=org.apache.log4j.FileAppender</pre> <pre>log4j.appender.file.layout=org.apache.log4j.PatternLayout</pre> <pre>log4j.appender.file.layout.ConversionPattern=%d %8r [%t]%-5p %c{3} %x - %m%n</pre> <pre>log4j.appender.file.File={full path to log file}</pre>
INOSXI6708	X-Tension usage is currently disabled
Explanation	All of the X-Tension infrastructures (COM, Java and Direct) are currently disabled.
Action	Turn on the appropriate switch of the Tamino server parameters and restart the Tamino server.
INOSXI6723	JVM started with user options 'jvm_options'
Explanation	The JVM was started with the specified additional user options.
Action	No action required.
INOSXI7029	Finished searching the file
Explanation	The 'Find What' string has not been found after (Direction <i>Down</i>) or before (Direction <i>Up</i>) the current position.
Action	Deselect 'Match case' or select another string.

INOSXI7050	COM for server extension is deactivated
Explanation	COM for server extension is switched off.
Action	Switch on COM for server extension with Tamino Manager.
INOSXI7128	Java for server extension is deactivated
Explanation	Java for server extensions is switched off
Action	Switch on Java for server extension with the Tamino Manager
INOSXI7131	X-Tension 'unusedinfrastructur' usage is currently disabled
Explanation	The specified X-Tension infrastructure (COM, Java or Direct) is currently disabled.
Action	Turn on the appropriate switch of the Tamino server parameters and restart the Tamino server.
INOSXI7253	Metadata update succeeded: id
Explanation	Metadata update has finished successfully.
Action	None
INOSXI7254	Metadata update started.
Explanation	Metadata update has started. This may be a lengthy operation.
Action	None.
INOSXV6726	COM server extensions are deprecated
Explanation	COM server extensions are deprecated and will not be supported in future.
Action	Plan the replacement of your COM server extensions by using a different server extension infrastructure.
INOSXW6700	'function' can no longer be used as 'functype'
Explanation	One of the parameters has been modified or deleted. Therefore this server extension function can no longer be used as the specified function type.
Action	Check the Tamino server extension documentation for the different function types.

INOSXW6701	At least one of the help files does not exist. It will be removed from the list.
Explanation	The Install.xml file for your current X-Tension project has an entry for a help file that no longer exists. It will be removed from your list of help files.
Action	Select a new file.
INOSXW6702	Warning: Settings for compiler 'compiler' already exist and will be overwritten
Explanation	Compiler and linker flags already exist for the compiler specified in this warning. Choosing 'OK' will overwrite these settings.
Action	Choose 'OK' to overwrite these settings or 'Cancel' to stop this action.
INOSXW6703	The path 'path' will be added to the list of executable files of Visual Studio
Explanation	Some libraries residing in Tamino system directories are needed to build a server extension. These directories must be listed in the "Executable files" section of your Visual Studio configuration. If not yet present, sxwizard will add these directories automatically.
Action	Click on OK to accept these changes to your Visual Studio configuration. If you click on Cancel, no changes will be made and sxwizard will be stopped.
INOSXW6721	Project will be moved from platform 'platform1' to 'platform2'
Explanation	This (SXS Direct) project has been created on platform1. It is now opened on a different platform platform2, and a new make file will be created such that it can be compiled on this new platform.
Action	Click OK to generate a new make file, or click cancel if you do not want to have a new make file created. However, this project probably cannot be compiled on this platform.
INOSXW6722	Project will be moved from an older Tamino version to platform 'platform'
Explanation	This (SXS Direct) project has been created by an older version of Tamino. It is now opened by a newer Tamino version on a different platform. A new make file will be created such that it can be compiled in this version and on this new platform.
Action	Click OK to generate a new make file, or click cancel if you do not want to have a new make file created. However, this project probably cannot be compiled in this Tamino version.
INOSXW6724	Unable to start JVM with user options 'jvm_options'. Starting with default options instead.
Explanation	Conflicting or incorrect user options were specified for the JVM, so the JVM could not start. The JVM will be started with the default options.
Action	Correct the user options specified for the JVM and restart the server.

INOSXW6727	The server extension generated a warning.
Explanation	The server extension has invoked the warning XML callback. This will insert a warning into the Tamino response.
Action	The warning message is for informational purposes.
INOSXW6728	Execution failed: command
Explanation	The specified operating system command failed.
Action	Check the SXS installation values for faults.
INOSXW7002	Existing server extension project at 'pathname' will be overwritten
Explanation	A server extension project already exists in the given directory. It will be overwritten if you select "Finish".
Action	Press "OK" to overwrite this project or select another directory.
INOSXW7003	Java initialization failed. Reason: 'errno', 'errtxt'.
Explanation	Tamino was not able to create a Java virtual machine. Java based server extensions will not work.
Action	Make the Java virtual machine available to Tamino and start the Tamino server again or switch the server property X-Tension Java Usage to 'NO'.
INOSXW7004	Java thread initialization failed. Reason: 'errno', 'errtxt'.
Explanation	An XML worker thread could not be attached to the Java virtual machine. Java based server extensions will not work.
Action	Fix the problem of Java initialization and start the Tamino server again.
INOSXW7005	Initialization of COM library failed. Reason: 'errno', 'errtxt'.
Explanation	COM based server extensions will not work.
Action	Make the COM library available to the Tamino server, then start it again.
INOSXW7007	No license for Tamino X-Tension
Explanation	A special license must be bought to use the Tamino X-Tension feature.
Action	Buy a license for Tamino X-Tension.

INOSXW7008	Tamino X-Tension not available
Explanation	On this platform the Tamino X-Tension feature is not available.
Action	No action required.
INOSXW7011	This will remove all previously selected files from your package list
Explanation	For a server extension package, either one or more class files or ONE jar file can be used. This warning shows up in one of the following cases: 1) A jar file was selected and a class file will be added to the class file list: The jar file will be removed from the list. 2) One or more class files or another jar file were selected, and a jar file will be added: All recently selected files will be removed.
Action	Choose "OK" to confirm or "Cancel" to cancel the current selection
INOSXW7012	Main Class File for server extension missing
Explanation	For a server extension package, either one or more class files or ONE jar file can be used. This warning shows up when none of the selected class files contains the main class of the server extension.
Action	Add another class file that contains the main class of the server extension.
INOSXW7013	Server extension might not run without these class(es)
Explanation	In the Packaging Dialogue of the X-Tension Builder, one of the selected class files is about to be removed. Without this class file the installation of this server extension will be incomplete.
Action	Check if this class file is really unnecessary for the current server extension.
INOSXW7031	Directory 'dir' does not exist and will be created
Explanation	This directory does not exist and will be created.
Action	Select "OK" to create this directory, select "Cancel" to cancel project creation.
INOSXW7135	The given class contains no server extension function
Explanation	The given class does not contain any method that can be used as a server extension function.
Action	Enter some methods using the direct server extension development tools.

INOSXW7139	No valid JVM, install valid JVM or switch X-Tension Java Usage to 'NO'
Explanation	Error detected when loading a JVM for current Tamino version
Action	Check if JVM is installed, if a valid JVM Version is installed or switch X-Tension Java Usage to 'NO'.
INOSXW7159	Value will be set to empty string
Explanation	A default value or configuration parameter (Init Function) may be set to empty string if data type is charstring.
Action	Please check if in this special case this effect is intended.
INOX2E8000	Usage of distributed transaction processing is not supported on this platform
Explanation	It is not possible to use distributed transaction processing features on the Tamino server platform.
Action	None - the platform does not support distributed transaction processing.
INOX2E8001	Conversion of the distributed transaction processing transaction identifier was not possible
Explanation	The transaction identifier provided does not have a defined method to convert it to the internal format.
Action	Contract your software supplier - this is a software error.
INOX2E8002	An internal error occurred dealing with the transaction identifier in distributed transaction
Explanation	The transaction identifier caused an internal error when being processed.
Action	Contract your software supplier - this is a software error.
INOX2E8003	Server encountered an error while performing a distributed transaction processing action
Explanation	A distributed transaction processing action resulted in the server not being able to complete the action requested.
Action	Contract your software supplier - this is a software error.

INOX2E8004	The specified distributed transaction processing identifier is unknown by the server
Explanation	A transaction identifier was specified which is unknown to the server. This can happen if a timeout occurred or if the transaction has not been prepared before a server restart.
Action	This message will be given back by the server to the transaction manager.
INOX2E8005	An invalid argument was detected on a distributed transaction processing call
Explanation	An argument supplied by the transaction manager was invalid.
Action	This message will be given back by the server to the transaction manager.
INOX2E8006	Protocol error - an action requested by the transaction manager was invoked in an improper context
Explanation	The specified action cannot be carried out in the current distributed transaction state.
Action	This message will be given back by the server to the transaction manager.
INOX2E8007	An error has occurred which makes server unavailable to process the transaction manager's action
Explanation	The action requested by the transaction manager cannot be fulfilled by Tamino currently.
Action	This message will be given back by the server to the transaction manager.
INOX2E8008	Duplicate distributed transaction identifier encounter while enlisting in a distributed transaction
Explanation	A duplicate transaction identifier was encountered while enlisting in a distributed transaction.
Action	This is an internal error and should be reported to your software supplier.
INOX2E8010	The specified distributed transaction has been rollback
Explanation	The server has decided that this distributed transaction can only be rolled back.
Action	This message is a reply to a transaction manager request.
INOX2E8011	A communications error has occurred
Explanation	A communications error occurred while attempting a distributed transaction processing action sent by the transaction manager.
Action	This message is a reply to a transaction manager request.

INOX2E8012	The server has detected a deadlock involving the specified distributed transaction
Explanation	A deadlock has been detected for the specified distributed transaction. The transaction has been rolled back.
Action	This message is a reply to a transaction manager request.
INOX2E8013	The server has detected an integrity violation for the resources requested by the specified distributed transaction
Explanation	An integrity violation has been detected for the specified distributed transaction. The transaction has been rolled back.
Action	This message is a reply to a transaction manager request
INOX2E8014	The server has detected an unspecified error for the specified distributed transaction
Explanation	An unspecified has been detected for the specified distributed transaction. The transaction has been rolled back.
Action	This message is a reply to a transaction manager request
INOX2E8015	The server has detected an internal protocol error for the specified distributed transaction
Explanation	An internal protocol error has been detected for the specified distributed transaction.
Action	This message is a reply to a transaction manager request.
INOX2E8016	The server has timed out the specified distributed transaction
Explanation	The server timed out the specified distributed transaction.
Action	This message is a reply to a transaction manager request.
INOX2E8017	The server has detected a transient error for the specified distributed transaction
Explanation	The server has detected a transient error for the specified distributed transaction.
Action	This message is a reply to a transaction manager request.
INOX2E8018	The server has heuristically committed the specified distributed transaction
Explanation	The server had to heuristically commit the specified distributed transaction.
Action	This message is reply to a transaction manager request.

INOX2E8019	The server has heuristically rolled back the specified distributed transaction
Explanation	The server had to heuristically roll back the specified distributed transaction.
Action	This is message is reply to a transaction manager request.
INOX2E8020	The server has heuristically completed the distributed transaction. The outcome of the transaction is mixed.
Explanation	The server had to heuristically complete the specified distributed transaction. The outcome is however mixed; this means that part of the transaction was committed and the rest was rolled back.
Action	This message is a reply to a transaction manager request.
INOX2E8021	The specified distributed transaction is read-only
Explanation	There were no modifications made to the server by the specified distributed transaction and therefore the server does not need to receive the commit action from the transaction manager.
Action	This message is a reply to a transaction manager request.
INOX2E8022	An error occurred while issuing a call to the transaction manager
Explanation	The transaction manager rejected a request made by Tamino.
Action	See the extended error messages for the transaction manager's reason for rejecting the call.
INOX2E8023	The command is not allowed while a distributed transaction is active within this session
Explanation	An attempt was made to issue either a <code>_DISCONNECT</code> command before the completion of the distributed transaction or a <code>_COMMIT/_ROLLBACK</code> command in the distributed transaction. These are not allowed.
Action	Complete the two phase commit transaction before issuing the <code>_DISCONNECT</code> command.
INOX2E8024	The current session cannot accept commands while the two phase commit transaction completion protocol is active
Explanation	Issuing Tamino commands to a session that is between phase 1 and phase 2 of a two phase commit transaction completion protocol is not allowed. The two phase commit protocol must complete before the session can be used again.
Action	Do not issue commands while the two phase commit transaction completion protocol is active.

INOX2E8025	The transaction manager specified an invalid recovery action
Explanation	The request action on recovery was invalid.
Action	This is an error sent to the transaction manager. It is internal and if seen should be reported to your software supplier.
INOX2E8027	The outcome of a commit was inconsistent
Explanation	The outcome of a commit was inconsistent: one or more data sources failed to commit.
Action	Check the extended error information for a list of which data sources failed to commit the transaction, then perform appropriate repairs.
INOX2E8028	The outcome of a rollback was inconsistent
Explanation	The outcome of a rollback was inconsistent: one or more data sources failed to roll back.
Action	Check the extended error information for a list of which data sources failed to commit the transaction, then perform appropriate repairs.
INOX2E8030	Invalid transaction token
Explanation	An invalid transaction token was specified.
Action	Provide a valid transaction token with the correct format.
INOX2E8047	Recovery of distributed transactions has found outstanding transactions that are not for the current transaction manager
Explanation	After completion by the transaction manager of recovery for distributed transactions, there are outstanding transactions that do not belong to the transaction manager.
Action	Contact your software supplier for help in resolving the outstanding transactions.
INOX2E8049	An internal error occurred in the distributed transaction processing components of the server.
Explanation	An internal error occurred.
Action	This is an internal error. Please contact your software supplier.
INOX2F8026	Cannot find distributed transaction processing (DTP) library ino2pc
Explanation	The shared library/DLL ino2pc cannot be found.
Action	This is a software installation configuration problem. Contact Software AG support for help

INOX2I8046	Distributed transaction transaction_token with resource manager identifier rmid has been manually resolved to the 'state' state
Explanation	This event is generated when someone manually resolves a distributed transaction.
Action	No action required. This message helps to track the progress of the distributed transaction.
INOX2I8048	Server start-up detected pending or heuristically complete distributed transactions
Explanation	On starting the server, it has been detected that there are outstanding distributed transactions. These transactions should normally be resolved by the transaction manager.
Action	Check the transaction manager log to check that all outstanding distributed transactions are resolved. If the transactions are not resolved, then contact your software supplier to get help in resolving them.
INOXCE8100	Internal error: duplicate root element
Explanation	Invalid migrated data records with duplicate root elements were detected.
Action	Please contact your software supplier.
INOXCE8102	Internal error: document stack corrupted
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXCE8103	Memory allocation failed
Explanation	There was not enough main memory available to perform the request.
Action	Possibly the machine is overloaded. Try again later.
INOXCE8104	Internal error during document composition
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXCE8105	Invalid X-Tension response
Explanation	An X-Tension function returned a string that is not well-formed XML.
Action	Correct the implementation of the X-Tension function

INOXCE8106	Internal error: unknown request
Explanation	An internal error occurred.
Action	Please contact your software supplier.
INOXCE8107	Map to object: illegal document ID encountered.
Explanation	The query attached to a node with map-type=object is of the form "@ino:id=%parent". The document ID found in the parent node is either zero or contains non-digit characters.
Action	The document ID in the parent node is illegal, correct it.
INOXCE8108	Insufficient mapping information, document cannot be composed
Explanation	An XML document could not be created due to insufficient mapping information.
Action	Look at the <ino:messageline> element in the <ino:response> document to find more information about the cause of the problem.
INOXCE8109	Cannot delete externally mapped data
Explanation	Tamino X-Query is not able to delete XML documents that are composed from external data sources like ODBC or Adabas if those documents have not been stored through Tamino. Typically, when displayed, these documents do not have an "ino:id" attribute. Similarly, X-Query cannot delete data from doctypes with "tsd:pure" mapping.
Action	Modify the query that selects the documents to be deleted. In the case of pure mapping, use XQuery update in order to delete documents.
INOXCE8110	Internal error: document data corrupted
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXCE8111	Error in XNode Adabas processing during conversion of Natural date/time value
Explanation	An error occurred while converting a Natural date or time value. The Tamino response contains details about the offending value, as well as an internal error code.
Action	Analyze the error.

INOXCE8114	Document ID unknown, mapping type infofield
Explanation	This error message should never occur.
Action	None
INOXCE8117	Internal error:Document not found
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXCE8118	Mapping type object: number of resulting objects too large
Explanation	This message should never occur
Action	None
INOXCE8119	Internal error: structure description too large
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXDE7500	NOTATION must be restricted by an enumeration
Explanation	NOTATION must be restricted by an enumeration.
Action	Please modify your XML schema accordingly.
INOXDE7501	(a-props-correct.2) default or fixed value is not of declared type
Explanation	If there is a default or fixed value specification, the canonical lexical representation of its value must be valid with respect to the type definition.
Action	Please modify your XML schema accordingly.
INOXDE7502	(a-props-correct.3) If attributes has type ID or a derived type it must not have a value constraint, i.e. a default or fixed value
Explanation	Attributes of type ID or a derived type must not have a value constraint, i.e. a default or fixed value.
Action	Please modify your XML schema accordingly.

INOXDE7503	(e-props-correct.2) default or fixed value is not of declared type
Explanation	If there is a default or fixed value specification, the canonical lexical representation of its value must be valid with respect to the type definition.
Action	Please modify your XML schema accordingly.
INOXDE7504	(e-props-correct.4) Elements of type ID or a derived type must not have a value constraint, i.e. a default or fixed value
Explanation	Elements of type ID or a derived type must not have a value constraint, i.e. a default or fixed value.
Action	Please modify your XML schema accordingly.
INOXDE7505	(ct-props-correct.4) attributes must not have identical names
Explanation	Two distinct attribute declarations in the attribute uses must not have identical names.
Action	Please modify your XML schema accordingly.
INOXDE7506	(ct-props-correct.5) only one attribute may have type ID or a derived type
Explanation	Two distinct attribute declarations in the attribute uses must not have type ID or a derived type.
Action	Please modify your XML schema accordingly.
INOXDE7507	(au-props-correct.2) attribute's fixed value does not match declaration's fixed value
Explanation	If the attribute declaration has a fixed value constraint, then if the attribute use itself has a value constraint, it must also be fixed and its value must match that of the attribute declaration's value constraint.
Action	Please modify your XML schema accordingly.
INOXDE7508	(sch-props-correct.2) name conflict with global declarations
Explanation	Each of the type definitions, element declarations, attribute group definitions, model group definitions and notation declarations must not contain two or more schema components with the same name.
Action	Please modify your XML schema accordingly.

INOXDE7509	invalid type of default value
Explanation	If the type definition is a simple type definition, then the string must be valid with respect to that definition.
Action	Please modify your XML schema accordingly.
INOXDE7510	content type is neither a simple type definition nor mixed
Explanation	If an element declaration specifies a default value and the type definition is a complex type definition, then its content type must be a simple type definition or mixed.
Action	Please modify your XML schema accordingly.
INOXDE7511	element default value does not match type
Explanation	If an element declaration specifies a default value and the type definition is a complex type definition and its content type is a simple type definition, then the default value must be of declared type.
Action	Please modify your XML schema accordingly.
INOXDE7512	content type does not allow for default value
Explanation	If an element declaration specifies a default value and the type definition is a complex type definition and its content type is mixed, then the content type's particle must be emptyable.
Action	Please modify your XML schema accordingly.
INOXDE7513	missing name in type definition
Explanation	If the particles contain, either directly, indirectly or implicitly two or more element declaration particles with the same name, then all their type definitions must be the same top-level definitions.
Action	Please modify your XML schema accordingly.
INOXDE7514	type definitions have different names
Explanation	If the particles contain, either directly, indirectly or implicitly two or more element declaration particles with the same name, then all their type definitions must be the same top-level definitions.
Action	Please modify your XML schema accordingly.

INOXDE7515	type definitions have different namespaces
Explanation	If the particles contain, either directly, indirectly or implicitly two or more element declaration particles with the same name, then all their type definitions must be the same top-level definitions.
Action	Please modify your XML schema accordingly.
INOXDE7516	(no-xmlns) attribute name not allowed
Explanation	The name of an attribute declaration must not match xmlns.
Action	Use the targetNamespace attribute of the schema's root node in order to associate the current schema and objects defined therein with a namespace URI. The import element can be used to compose schemas defining objects for different namespaces.
INOXDE7517	Below Attribute there may be only attributeInfo node but no schemaInfo or elementInfo nodes
Explanation	Below Attribute there may be only attributeInfo node but no schemaInfo or elementInfo nodes.
Action	Please modify your XML schema accordingly.
INOXDE7518	(enumeration-valid-restriction) value of enumeration does not match base type definition
Explanation	The value attribute of an enumeration item must match the definition of the restriction's base type.
Action	Adapt your schema.
INOXDE7519	(notation-defined-restriction) value of enumeration is not defined in a global notation element.
Explanation	An enumeration value being used in a type derived from NOTATION must be defined in a global notation element.
Action	Adapt your schema.
INOXDE7520	invalid index
Explanation	It is not possible to define indices on elements or attributes with type "xs:long", "xs:unsignedLong" or "xs:decimal".
Action	Please modify your XML schema accordingly.

INOXDE7521	invalid text index
Explanation	It is not possible to define text indices on elements or attributes with numeric types.
Action	Please modify your XML schema accordingly.
INOXDE7522	The element pointed to by tsd:refers needs to have a reference index defined for it
Explanation	(mp-valid-refers.5:) The element pointed to by tsd:refers needs to have a reference index defined for it.
Action	Please modify the schema to include a reference index on the element pointed to by tsd:refers and try to define the schema again.
INOXDE7523	Collations can only be defined for string datatypes (derived types of string in W3C XML schema part 2)
Explanation	Collations can only be defined for string datatypes (derived types of string in W3C XML schema part 2).
Action	Please modify your XML schema accordingly.
INOXDE7524	(src-single-facet-value) Facet is only permitted to be defined once
Explanation	A facet has been specified more than once. This facet is only permitted to be defined once.
Action	Please modify the XML Schema accordingly.
INOXDE7525	(cos-element-consistent) Element declarations are not consistent
Explanation	If the particles contain, either directly, indirectly or implicitly two or more element declaration particles with the same name, then all their type definitions must be the same top-level definitions.
Action	Please modify your XML schema accordingly.
INOXDE7526	(maxInclusive-maxExclusive) 'maxInclusive' and 'maxExclusive' facets cannot be used together
Explanation	A simple type restriction, containing both 'maxInclusive' and 'maxExclusive' facets, has been found.
Action	Remove either of the 'maxInclusive' or 'maxExclusive' facets.

INOXDE7527	(minInclusive-minExclusive) 'minInclusive' and 'minExclusive' facets cannot be used together
Explanation	A simple type restriction, containing both 'minInclusive' and 'minExclusive' facets, has been found.
Action	Remove either of the 'minInclusive' or 'minExclusive' facets.
INOXDE7528	Node declarations are not consistent
Explanation	The schema violates a constraint which is a Tamino-specific extension of the (cos-element-consistent) constraint as imposed by XML schema: If there are two attribute or element declarations in the set of complex type definitions being allowed for a given element node due to usage of the xsi:type attribute, then these attributes (or elements) must be consistent. Consistency requirements cover the datatype as well as physical properties (mapping, indexing,...), or logical properties (collation, trigger, ...).
Action	Modify the schema to avoid violation of the constraint. For example it may help to use the 'block' attribute of <xs:element> or <xs:complexType> , or the 'blockDefault' attribute of <xs:schema> in order to control the {prohibited substitutions} with respect to xsi:type. In particular, you may use blockDefault="#all" if you do not need to allow for usage of the xsi:type attribute in your XML documents.
INOXDE7529	(src-resolve.1.1) Global type reference could not be resolved
Explanation	Reference to a global complex or simple type definition could not be resolved.
Action	Check the names of the global type definition and the associated reference.
INOXDE7530	(src-resolve.1.2) The ref attribute of an attribute needs to reference an existing global attribute
Explanation	An attribute defined in the schema uses the 'ref' attribute, however the global attribute with that name cannot be found.
Action	Check that the global attribute is not missing. Also check that the global attribute name and reference have been correctly specified.
INOXDE7531	(minLength-less-than-equal-to-maxLength) 'minLength' facet value must be 'less than or equal to' that of facet 'maxLength'
Explanation	A simple type restriction, where the value of facet 'minLength' is greater than that of 'maxLength', has been found.
Action	Revise the facet values.

INOXDE7532	Invalid pattern facet value found
Explanation	The schema being defined contains a pattern facet which has an invalid value.
Action	Check the schema and consider revising the pattern facet's value.
INOXDE7533	Below Schema there needs to be exactly one appinfo node which defines Tamino mappings
Explanation	Below Schema there needs to be exactly one appinfo node which defines Tamino mappings.
Action	Modify the XML schema accordingly.
INOXDE7534	(src-import.1.1) Invalid import element. If the namespace attribute is present, then its value must not match the value of the enclosing schema's targetNamespace attribute.
Explanation	The schema being defined contains an import element. The namespace attribute is present and its value is the same as the targetNamespace of the enclosing schema. This is not allowed.
Action	Revise either the namespace attribute of the import element or the targetNamespace of the schema.
INOXDE7535	(src-import.1.2) Invalid import element. If the namespace attribute is not present, then the enclosing schema must have a targetNamespace attribute.
Explanation	The schema being defined contains an import element. The namespace attribute is not present and the enclosing schema does not specify a targetNamespace. This is disallowed.
Action	Revise the import element and/or the schema element.
INOXDE7536	(src-import.2) Invalid import element. Schema reference could not be resolved.
Explanation	The schema being defined contains an import element. The schema referenced using either a schemaLocation or namespace attribute could not be located.
Action	If referencing using schemaLocation, check the name of the referenced schema (and optionally the collection name also). If referencing using namespace alone, check the targetNamespace of the referenced schema.
INOXDE7537	(src-import.3.1) Invalid import element. If there is a namespace attribute, then its value must be identical to the value of the targetNamespace attribute of the referenced schema.
Explanation	The schema being defined contains an import element. The namespace attribute is different from the targetNamespace of the referenced schema. This is not allowed.
Action	Revise either the namespace attribute of the import element or the targetNamespace of the referenced schema.

INOXDE7538 (src-import.3.2) **Invalid import element. If there is no namespace attribute, then the referenced schema must have no targetNamespace attribute.**

Explanation The schema being defined contains an import element. The namespace attribute is not present, but the referenced schema specifies a targetNamespace. This is not allowed.

Action Revise the import element and/or the referenced schema element.

INOXDE7539 **The value of schema attribute targetNamespace is not allowed if another schema in the same database already imports the corresponding namespace using only the namespace attribute of the import element**

Explanation The value of the targetNamespace attribute of the schema that you are trying to define is not allowed. This is because another schema in the same database already imports that namespace, using an import element with namespace alone.

Action Revise the schema and/or the other schema importing that namespace. Either change the targetNamespace of the current schema, or change the import element of the referencing schema to also use the schemaLocation attribute.

INOXDE7540 **Found node with a mapped value which is used to construct index entries**

Explanation A node with a mapped value must not be used to construct index entries. This restriction applies for text and standard as well as for the components of a compound index referring to an ancestor of the current node.

Action Remove index definition causing this conflict.

INOXDE7541 **Undefine of schema failed. Schema to be undefined is referenced by other schema(s) in the database.**

Explanation The undefine of a specific schema was performed. Other schema(s) in the database still reference this schema.

Action Before the schema can be undefined, you must first undefine all referencing schemas.

INOXDE7542 **Attribute targetNamespace of element schema, if present, must not be empty.**

Explanation The schema being defined specifies an empty targetNamespace attribute.

Action Revise the schema. Either provide the targetNamespace attribute with a value, or completely remove it.

INOXDE7543	Import using namespace attribute alone is forbidden, if more than one schema with the corresponding targetNamespace is already stored in the current database
Explanation	The schema being defined contains an import element with only a namespace attribute. More than one schema stored in the current database already contains a corresponding targetNamespace attribute.
Action	Revise the schema and/or other schemas stored inside the current database. Consider using the schemaLocation attribute of import to clarify exactly which schema was intended.
INOXDE7544	An import element must have attributes
Explanation	The schema being defined specifies an import element without attributes.
Action	Revise the schema. Add either namespace or schemaLocation attributes to the import element, or remove it and consider using Tamino's content element with value open.
INOXDE7545	Cannot define standard index or unique constraint based on a node whose associated datatype has a variety of 'union'
Explanation	It is not supported to define an index or unique constraint based on a node whose datatype has a variety of 'union' or which is derived via <xs:list> with an item type whose variety is 'union'.
Action	Modify the schema accordingly.
INOXDE7546	An element defined as a primary key cannot be defined as nillable
Explanation	An element which is defined as a primary key value cannot be defined as nillable.
Action	Revise the schema. Either remove the xsi:nillable attribute or set the value to false.
INOXDE7547	Undefine of collection failed. One or more schemas contained inside the collection to be undefined are referenced by other schema(s), from other collection(s) in the current database.
Explanation	The undefine of a specific collection was performed. Other schema(s) from other collection(s) in the database still reference one or more schemas contained inside the collection to be undefined.
Action	Before the collection can be undefined, you must first undefine all referencing schemas.
INOXDE7548	Cannot define standard index or unique constraint based on this element node with complex content if there is a validly derived complex type with simple content which can be used in an xsi:type attribute on that element node
Explanation	It is not allowed to define a standard index or unique constraint based on an element node whose associated datatype is a complex type with complex content if there is another complex type with simple content which can be validly used in an xsi:type attribute on that element node.

Action	Either remove the index definition or modify type definitions to avoid violation of this constraint.
INOXDE7549	Mapping not allowed for datatype of variety
Explanation	Mapping (ADABAS, SQL and SXS) is not allowed for datatypes derived via xs:list or xs:union.
Action	Please change the datatype and try to define the schema again.
INOXDE7550	ElementInfo node is not allowed with a schema reference to a global element definition
Explanation	Below Element an elementInfo node is only allowed if the element node starts an element definition. An elementInfo is not allowed with a reference to a global element definition.
Action	Please modify your XML schema accordingly.
INOXDE7551	AttributeInfo node is not allowed with a schema reference to a global attribute definition
Explanation	Below Attribute an attributeInfo node is only allowed if the attribute node starts an attribute definition. An attributeInfo is not allowed with a reference to a global attribute definition.
Action	Please modify your XML schema accordingly.
INOXDE7552	The path contains invalid expressions
Explanation	The path can only consists of named child steps with abbreviated XPath syntax. In particular, it cannot contain *, .., // operators.
Action	Modify the XML schema accordingly.
INOXDE7553	The index types of elements and attributes having the same multipath index label must be identical
Explanation	The index types of elements and attributes having the same multipath index label must be identical.
Action	Please change the schema so that multipath definitions with the same label are only used when the index types are identical and then try to define the schema again.

INOXDE7554	(src-attribute-group.2) Intentional intersection of namespace constraints is not expressible
Explanation	This may happen e.g. if two attribute wildcards are to be merged due to resolution of a reference to an attributeGroup definition. If those two attribute wildcards both have a namespace constraint ##other, thus referring to different target namespaces, the intentional intersection is not expressible.
Action	Adapt the schema according to XML schema constraint src-attribute-group.2
INOXDE7555	The name attribute of tsd:unique definitions has to be unique within a doctype
Explanation	The name attribute of tsd:unique definitions has to be unique within a doctype.
Action	Please change the duplicate name and try to define the schema again.
INOXDE7556	The elements and attributes pointed to in tsd:unique definitions must have a cardinality of 1
Explanation	The elements and attributes pointed to in tsd:unique definitions must have a cardinality of 1.
Action	Please change the cardinality and try to define the schema again.
INOXDE7557	The path specified the xpath attribute of a field element needs to point to an existing element or attribute
Explanation	The path specified the xpath attribute of a field element needs to point to an existing element or attribute.
Action	Please make sure the specified path is correct and try to define the schema again.
INOXDE7558	multipath index definitions are not allowed in doctypes which have the structureIndex set to none
Explanation	Multipath index definitions are not allowed in doctypes which have the structureIndex set to none.
Action	Please change the structure index to condensed or full and try to define the schema again.
INOXDE7559	The elements and attributes having the same multipath index label must have matching datatypes
Explanation	The elements and attributes having the same multipath index label must have matching datatypes.
Action	Please change the wrong datatype and try to define the schema again.

INOXDE7560	The elements and attributes having the same multipath index label must have matching collations
Explanation	The elements and attributes having the same multipath index label must have matching collations.
Action	Please change the wrong collation and try to define the schema again.
INOXDE7561	The elements and attributes having the same multipath index label must have matching tsd:refers definitions
Explanation	The elements and attributes having the same multipath index label must have matching tsd:refers definitions.
Action	Please change the wrong tsd:refers definition and try to define the schema again.
INOXDE7562	The path defined in tsd:refers has to point to an existing element
Explanation	The path defined in tsd:refers has to point to an existing element.
Action	Please change the path and try to define the schema again.
INOXDE7563	The path defined in tsd:refers has to point to an element which is a predecessor of the element or attribute where it is defined
Explanation	The path defined in tsd:refers has to point to an element which is a predecessor of the element or attribute where it is defined.
Action	Please change the path and try to define the schema again.
INOXDE7564	The path defined in tsd:refers may only point to elements that are locally stored in a Tamino database
Explanation	The path defined in tsd:refers may only point to elements that are locally stored in a Tamino database.
Action	Please change the path and try to define the schema again.
INOXDE7565	The path defined in tsd:refers must point either to the doctype element or to an element for which a tsd:reference is defined
Explanation	The path defined in tsd:refers must point either to the doctype element or to an element for which a tsd:reference is defined.
Action	Please change the path and try to define the schema again.

INOXDE7566	The path specified in the xpath attribute of a field element needs to point to an element or attribute that is locally stored in a Tamino database
Explanation	The path specified in the xpath attribute of a field element needs to point to an element or attribute that is locally stored in a Tamino database.
Action	Please change the path and try to define the schema again.
INOXDE7567	The path specified in the xpath attribute of a field element of a compound index definition needs to point to a leaf node (an attribute or element having no children)
Explanation	The path specified in the xpath attribute of a field element of a compound index definition needs to point to a leaf node (an attribute or element having no children).
Action	Please change the path and try to define the schema again.
INOXDE7568	For a uniqueness constraint a certain path may only be defined once
Explanation	For a uniqueness constraint a certain path may only be defined once.
Action	Please change the path and try to define the schema again.
INOXDE7569	A reference index may not be defined for a doctype element
Explanation	A reference index may not be defined for a doctype element.
Action	Please change the reference index value and try to define the schema again.
INOXDE7570	There may only be one tsd:reference index definition per tsd:physical
Explanation	There may only be one tsd:reference index definition per tsd:physical.
Action	Please make sure there is only one tsd:reference index definition per tsd:physical and try to define the schema again.
INOXDE7571	If an index has been defined as a multipath index, there may not be a tsd:refers defined for that same index
Explanation	If an index has been defined as a multipath index, there may not be a tsd:refers defined for that same index.
Action	Please remove either the multipath definition or the tsd:refers and try to define the schema again.

INOXDE7572	For a compound index a certain path may only be defined once
Explanation	For a compound index a certain path may only be defined once.
Action	Please change the schema and try to define it again.
INOXDE7573	(src-resolve.1.4) Reference to an attribute group definition could not be resolved
Explanation	Reference to an attribute group definition could not be resolved.
Action	Check the qualified names of the attribute group definition and the reference.
INOXDE7574	(src-resolve.1.5) Reference to a model group definition could not be resolved
Explanation	Reference to a model group definition could not be resolved.
Action	Check the qualified names of the model group definition and the reference.
INOXDE7575	(src-attribute-group.3) Circular attribute group reference is disallowed
Explanation	A cycle of attribute group references has been found.
Action	Check the attribute group references and remove the circular reference.
INOXDE7576	(mg-props-correct.2) Circular group reference is disallowed
Explanation	Within the particles of a group there must not be at any depth a reference to the group itself.
Action	Check group definition and remove circular reference inside.
INOXDE7577	(src-include.2.1) Target namespace of the including and the included schema do not match.
Explanation	The values of the targetNamespace attributes of the including and the included schema may not differ if both are present.
Action	Check targetNamespace attributes.
INOXDE7578	(src-include.2.2) Included schema has target namespace whereas including has no target namespace.
Explanation	If the including schema has no targetNamespace attribute, the included schema must not have a targetNamespace attribute as well.
Action	Check and adapt the schema documents.

INOXDE7579	(src-include.2.3) Target namespace of included schema missing. Tamino does not yet support "chameleon include".
Explanation	This is a current limitation of Tamino.
Action	Define the included schema using the same targetNamespace attribute as the including schema's targetNamespace.
INOXDE7580	(src-include.1) Invalid include element. Schema reference could not be resolved.
Explanation	The schema being defined contains an include element. The schema referenced by the schemaLocation attribute could not be located.
Action	Check the name of the referenced schema and, optionally, the collection name as well.
INOXDE7581	invalid collation language
Explanation	The specified language string is not valid.
Action	Please change the wrong collation language string and try to define the schema again.
INOXDE7583	Invalid open content found in pure X-Node mapped doctype
Explanation	For pure X-Node mapping, no open content is allowed for that doctype. This includes wildcards with processContents being "strict" or "lax" and element nodes with type "xs:anyType" or no type at all.
Action	Ensure that the doctype with the pure X-Node mapping is set to closed content, that any of the doctype's wildcards (xs:any and xs:anyAttribute) in scope have processContents set to "strict", and that all elements in scope have a non-absent type specification different from "xs:anyType".
INOXDE7584	Invalid mixed content found in complex type within a pure X-Node mapped doctype
Explanation	Elements in a pure X-Node mapped doctype must not have a mixed content model.
Action	Set the mixed attribute of the corresponding complex type definition to "false".
INOXDE7585	Invalid mapping found in root element of pure X-Node mapped doctype
Explanation	Currently, only Adabas mapping is allowed for the root node of a pure X-Node mapped doctype.
Action	Check the mapping of the root element.

INOXDE7586	Invalid mapping found in non-root node within pure X-Node mapped doctype
Explanation	All leaf nodes must be mapped corresponding to the mapping type of the root element, e.g. to Adabas fields if the root node is mapped to an Adabas file.
Action	Check the mapping of the node.
INOXDE7587	Found invalid recursion in pure X-Node mapped doctype
Explanation	Within a pure X-Node mapped doctype no recursive structures are permitted.
Action	Remove the recursion.
INOXDE7588	Found empty leaf node in pure X-Node mapped doctype
Explanation	A pure X-Node mapped doctype must not contain empty leaf nodes.
Action	Either remove the node or map to an X-Node data item, i.e. either an Adabas field or an SQL column.
INOXDE7589	Reference index definitions are not allowed in doctypes which have the structureIndex set to none
Explanation	Reference index definitions are not allowed in doctypes which have the structureIndex set to none.
Action	Please correct the schema and try to define it again.
INOXDE7590	Unique index constraints may not be defined on elements or attributes on node of given type
Explanation	Unique index constraints may not be defined on elements or attributes of xs:duration or any data type allowing for an optional timezone indicator, e.g. xs:dateTime.
Action	Please correct the schema and try to define it again.
INOXDE7591	Found xs:include or xs:import referencing current schema
Explanation	An xs:include or xs:import must not reference the current schema.
Action	Adapt the schema.
INOXDE7592	Invalid level of structure index for pure X-Node mapped doctype
Explanation	A pure X-Node mapped doctype must not have a full structure index.
Action	Set the structure index to 'condensed' or 'none'.

INOXDE7593	A default function has been defined at an element node with a complex type
Explanation	A default function may only be defined at a node with a simple type.
Action	Modify the schema in an appropriate way.
INOXDE7594	Default function defined for required attribute node
Explanation	If a default function is defined for an attribute, the attribute must be optional.
Action	Check and adapt schema in an appropriate way.
INOXDE7595	Default function defined for a node which has a value constraint
Explanation	An element or attribute node may define either a default function or a value constraint (i.e. a default or fixed value) but not both.
Action	Adapt the schema correspondingly.
INOXDE7596	Too many tsd:elementInfo or tsd:attributeInfo nodes
Explanation	There may be only one tsd:elementInfo or tsd:attributeInfo node per xs:element or xs:attribute node.
Action	Modify the schema accordingly.
INOXDE7597	(src-list-itemType-or-simpleType) Definition of simple type via <xs:list> contains both 'itemType' attribute and <xs:simpleType> child.
Explanation	Either the 'itemType' attribute or the <xs:simpleType> child of the <xs:list> element must be present, but not both.
Action	Remove either the 'itemType' attribute or the <xs:simpleType> child.
INOXDE7598	(src-restriction-base-or-simpleType) Definition of simple type via <xs:restriction> must contain either 'base' attribute or <xs:simpleType> child.
Explanation	Either the 'base' attribute or the <xs:simpleType> child of the <xs:restriction> element must be present, but not both.
Action	Remove either 'base' attribute or the <xs:simpleType> child.
INOXDE7599	(src-union-memberTypes-or-simpleTypes) The 'memberTypes' attribute of the <xs:union> element is empty and there is no <xs:simpleType> child.
Explanation	Either the 'memberTypes' attribute of the <xs:union> element must be non-empty or there must be at least one <xs:simpleType> child.
Action	Add either the 'memberTypes' attribute of the <xs:union> element or at least one <xs:simpleType> child.

INOXDE7614	The noConversion option may only be changed for empty doctypes
Explanation	Changing the noConversion option could make the existing data in the doctype invalid, so this option may only be modified for empty doctypes.
Action	Adapt the schema so that the noConversion option is not changed or make sure there are no documents stored in the doctype for which you are trying to modify the schema.
INOXDE7619	Invalid type of parameter for server extension
Explanation	The type of the parameter is invalid in the current context.
Action	Check and modify the type of parameter to be passed to the server extension function. for example, parameters being passed to a trigger function may only have a simple predefined type.
INOXDE7620	Invalid parameter value
Explanation	The value of the parameter is not valid with respect to the declared type.
Action	Modify the type or value in order to create a consistent parameter definition.
INOXDE7621	(cos-st-restricts.1.1) Invalid base type definition of simple type
Explanation	The base type definition must be an atomic simple type definition or a built-in primitive datatype.
Action	Adapt the type definitions or type hierarchy.
INOXDE7622	(cos-st-restricts.1.2) Invalid base type of simple type definition - the 'final' attribute does not permit derivation of another simple type
Explanation	The {final} of the {base type definition} of a simple type definition must not contain restriction.
Action	Adapt the schema according to the constraint.
INOXDE7623	(cos-st-restricts.2.1) Invalid item type definition of simple type derived via <xs:list>
Explanation	The {item type definition} must have a {variety} of atomic or union (in which case all the {member type definitions} must be atomic).
Action	Adapt the schema according to the constraint.

INOXDE7624	(cos-st-restricts.2.3.1.1) Invalid item type definition of simple type derived via <xs:list>
Explanation	The {final} of the {item type definition} must not contain list.
Action	Adapt the schema according to the constraint.
INOXDE7625	(cos-st-restricts.3.3.2.2) Invalid base type for simple type derived via <xs:restriction>
Explanation	The {final} of the {base type definition} must not contain restriction.
Action	Adapt the schema according to the constraint.
INOXDE7626	(cos-st-restricts.2.3.2.2) Invalid base type for simple type derived via <xs:restriction>
Explanation	The {final} of the {base type definition} must not contain restriction.
Action	Adapt the schema according to the constraint.
INOXDE7627	(cos-st-restricts.2.3.2.4) Invalid facet for simple type derived via <xs:list>
Explanation	Only length, minLength, maxLength, whiteSpace, pattern and enumeration facet components are allowed among the {facets}.
Action	Adapt the schema according to the constraint.
INOXDE7628	(cos-st-restricts.3.1) Invalid member type definition for simple type derived via <xs:union>
Explanation	The {member type definitions} must all have {variety} of atomic or list.
Action	Adapt the schema according to the constraint.
INOXDE7629	(cos-st-restricts.3.3.1.1) Invalid member type definition for simple type derived via <xs:union>
Explanation	All of the {member type definitions} must have a {final} which does not contain union.
Action	Adapt the schema according to the constraint.
INOXDE7630	(cos-st-restricts.3.3.2.4) Invalid facet for simple type derived via <xs:union>
Explanation	Only pattern and enumeration facet components are allowed among the {facets}.
Action	Adapt the schema according to the constraint.

INOXDE7631	(a-props-correct.1) Invalid type of attribute declaration - must be a simple type
Explanation	The type definition of an attribute declaration must be a simple type.
Action	Modify the type definition of the attribute declaration.
INOXDE7632	(st-props-correct.2) Invalid or circular type hierarchy of simple type definition
Explanation	All simple type definitions must be derived ultimately from the simple ur-type definition - circular definitions are disallowed.
Action	Adapt the schema according to the constraint.
INOXDE7633	(ct-props-correct.2) Invalid derivation of complex type with simple base type definition
Explanation	If the {base type definition} is a simple type definition, the {derivation method} must be extension.
Action	Adapt the schema according to the constraint.
INOXDE7634	(ct-props-correct.3) Invalid or circular type hierarchy of complex type definition
Explanation	Circular definitions are disallowed, except for the ur-type definition. That is, it must be possible to reach the ur-type definition by repeatedly following the {base type definition}.
Action	Adapt the schema according to the constraint.
INOXDE7635	(no-xsi) Invalid attribute declaration for targetNamespace
Explanation	The {target namespace} of an attribute declaration, whether local or top-level, must not match http://www.w3.org/2001/XMLSchema-instance , unless it is one of the four built-in declarations for <code>xsi:type</code> , <code>xsi:nil</code> , <code>xsi:schemaLocation</code> , <code>xsi:noNamespaceSchemaLocation</code> .
Action	Adapt the schema according to constraint. See XML Schema Part 1 for a valid declaration of the four built-in declarations.
INOXDE7636	(src-ct.1) Invalid base type definition of complex type with complex content
Explanation	If the <code><complexContent></code> alternative is chosen, the type definition resolved to by the actual value of the 'base' attribute must be a complex type definition.
Action	Adapt the schema according to the constraint.

INOXDE7637	(src-ct.2.1) Invalid base type definition of complex type simple content
Explanation	The type definition resolved to by the actual value of the 'base' attribute must be one of the following: (1) a complex type definition whose {content type} is a simple type definition; (2) only if the <restriction> alternative is also chosen, a complex type definition whose {content type} is mixed and a particle which is emptiable.
Action	Adapt the schema according to the constraint.
INOXDE7638	(src-ct.2.2) Missing <xs:simpleType> below <xs:restriction> for a complex type with simple content which is derived from a complex type via restriction
Explanation	If the <simpleContent>/<restriction> alternative is chosen with the 'base' attribute resolving to a complex type definition whose {content type} is mixed and a particle which is emptiable, there must be a <simpleType> among the [children] of <restriction>.
Action	Adapt the schema according to the constraint.
INOXDE7639	(cos-ct-extends.1.1) Invalid base type of complex type derived via <xs:extension>
Explanation	The {final} of the {base type definition} must not contain extension.
Action	Adapt the schema according to the constraint.
INOXDE7640	(cos-ct-extends.1.4.1) Simple content types of complex type derived via <xs:extension> and the respective base type definition do not match
Explanation	The {content type} of the {base type definition} and the {content type} of the complex type definition itself must be the same simple type definition.
Action	Adapt the schema according to the constraint.
INOXDE7641	(cos-ct-extends.1.4.2) If the content type of a complex type derived via <xs:extension> is empty, the content type of the respective complex base type definition must be empty as well
Explanation	The {content type} of both the {base type definition} and the complex type definition itself must be empty.
Action	Adapt the schema according to the constraint.
INOXDE7642	(cos-ct-extends.1.4.3.1) Invalid content type of a complex type definition derived via <xs:extension> given the content type of the complex base type definition
Explanation	The {content type} of the complex type definition itself must specify a particle.
Action	Adapt the schema according to the constraint.

INOXDE7643	(cos-ct-extends.1.4.3.2.2.1) Invalid content type of complex type definition derived via <xs:extension> from complex type definition
Explanation	Both {content type}s must be mixed or both must be element-only.
Action	Adapt the schema according to the constraint.
INOXDE7644	(cos-ct-extends.2.2) Invalid base type of complex type definition derived via <xs:extension>
Explanation	The {final} of the {base type definition} must not contain extension.
Action	Adapt the schema according to the constraint.
INOXDE7645	(derivation-ok-restriction.1) Invalid base type definition of complex type derived via <xs:restriction>
Explanation	The {base type definition} must be a complex type definition whose {final} does not contain restriction.
Action	Adapt the schema according to the constraint.
INOXDE7646	(derivation-ok-restriction.2.1.1) Invalid value of 'use' attribute of attribute in complex type definition derived via <xs:restriction> compared to value of 'use' attribute for respective attribute in complex base type definition.
Explanation	If there is an attribute use in the {attribute uses} of the {base type definition} (call this B) whose {attribute declaration} has the same {name} and {target namespace}, then one of the following must be true: (1) B's {required} is false. (2) the restricted type's {required} is true.
Action	Adapt the schema according to the constraint.
INOXDE7647	(derivation-ok-restriction.2.1.2) Invalid type of attribute in complex type definition derived via <xs:restriction> compared to type of respective attribute in complex base type definition.
Explanation	If there is an attribute use in the {attribute uses} of the {base type definition} (call this B) whose {attribute declaration} has the same {name} and {target namespace}, then the restricted type's {attribute declaration}'s {type definition} must be validly derived from B's {type definition}.
Action	Adapt the schema according to the constraint.

INOXDE7648	(derivation-ok-restriction.2.1.3) Invalid value constraint of attribute in complex type definition derived via <xs:restriction> compared to value constraint of respective attribute in complex base type definition
Explanation	If there is an attribute use in the {attribute uses} of the {base type definition} (call this B) whose {attribute declaration} has the same {name} and {target namespace}, then one of the following must be true: (1) B's effective value constraint is absent or default. (2) the restricted type's effective value constraint is fixed with the same string as B's.
Action	Adapt the schema according to the constraint.
INOXDE7649	(derivation-ok-restriction.2.2) Invalid attribute use in complex type definition derived via <xs:restriction>, the complex base type definition neither contains a matching attribute use nor an attribute wildcard.
Explanation	If there is no attribute use in the {attribute uses} of the {base type definition} (call this B) whose {attribute declaration} has the same {name} and {target namespace}, the {base type definition} must have an {attribute wildcard} and the {target namespace} of the restricted type's {attribute declaration} must be valid with respect to that wildcard.
Action	Adapt the schema according to the constraint.
INOXDE7650	(derivation-ok-restriction.3) Invalid value of 'use' attribute of attribute in complex type definition derived via <xs:restriction> compared to value of 'use' attribute for respective attribute in complex base type definition
Explanation	For each attribute use in the {attribute uses} of the {base type definition} whose {required} is true, there must be an attribute use with an {attribute declaration} with the same {name} and {target namespace} as its {attribute declaration} in the {attribute uses} of the complex type definition itself whose {required} is true.
Action	Adapt the schema according to the constraint.
INOXDE7651	(derivation-ok-restriction.4.1) Invalid attribute wildcard in complex type definition derived via <xs:restriction>, complex base type definition does not have an attribute wildcard
Explanation	If there is an {attribute wildcard}, the {base type definition} must also have one.
Action	Adapt the schema according to the constraint.
INOXDE7652	(derivation-ok-restriction.4.2) Invalid attribute wildcard in complex type definition derived via <xs:restriction>, its namespace constraint is not a subset of the namespace constraint of the attribute wildcard in the complex base type definition
Explanation	If there is an {attribute wildcard}, the complex type definition's {attribute wildcard}'s {namespace constraint} must be a subset of the {base type definition}'s {attribute wildcard}'s {namespace constraint}.
Action	Adapt the schema according to the constraint.

INOXDE7653	(derivation-ok-restriction.4.3) Invalid 'processContents' of attribute wildcard in complex type definition derived via <xs:restriction> compared to 'processContents' of attribute wildcard in complex base type definition
Explanation	If there is an {attribute wildcard}, and the {base type definition} is not the ur-type definition, the complex type definition's {attribute wildcard}'s {process contents} must be identical to or stronger than the {base type definition}'s {attribute wildcard}'s {process contents}, where strict is stronger than lax is stronger than skip.
Action	Adapt the schema according to the constraint.
INOXDE7654	(derivation-ok-restriction.5.1.2) Invalid base type for complex type with simple content derived via <xs:restriction>
Explanation	If the {content type} of the complex type definition is a simple type definition, one of the following must be true: (1) The {content type} of the {base type definition} must be a simple type definition from which the {content type} is validly derived (2) The {base type definition} must be mixed and have a particle which is emptiable
Action	Adapt the schema according to the constraint.
INOXDE7655	(derivation-ok-restriction.5.2.2) Invalid base type for complex type with empty content derived via <xs:restriction>
Explanation	If the {content type} of the complex type is empty, one of the following must be true: (1) The {content type} of the {base type definition} must also be empty. (2) The {content type} of the {base type definition} must be elementOnly or mixed and have a particle which is emptiable
Action	Adapt the schema according to the constraint.
INOXDE7656	(derivation-ok-restriction.5.3.1) Invalid base type for complex type with neither simple nor empty content derived via <xs:restriction>
Explanation	If the {content type} of the complex type definition is neither a simple type definition nor empty, one of the following must be true: (1) The {content type} of the complex type definition itself must be element-only (2) The {content type} of the complex type definition itself and of the {base type definition} must be mixed.
Action	Adapt the schema according to the constraint.
INOXDE7657	(derivation-ok-restriction.5.3.2) The particle of the complex type derived via restriction does not satisfy the "Particle Valid (Restriction)" constraint with respect to the particle of the complex base type
Explanation	If the {content type} of the complex type definition is neither a simple type definition nor empty, the particle of the complex type definition itself must be a valid restriction of the particle of the {content type} of the {base type definition}.
Action	Adapt the schema according to the constraint.

INOXDE7658	An element's or attribute's shortname definition does not match Adabas field definition
Explanation	A field with the given shortname does not exist in the Adabas file defined for this element.
Action	Adapt the schema to the corresponding Adabas field and file definitions.
INOXDE7659	The element's or attribute's Adabas format definition does not match the Adabas field definition
Explanation	The Adabas format definition cannot be converted to the format defined in the Adabas FDT.
Action	Adapt your schema to the corresponding Adabas field definitions.
INOXDE7660	An element's periodic group definition does not match the Adabas field definition
Explanation	The corresponding Adabas field is not defined as a periodic group in the Adabas FDT.
Action	Adapt your schema corresponding to the Adabas field definition
INOXDE7661	An element's multiple field definition does not match the Adabas field definition
Explanation	The corresponding Adabas field is not defined as multiple field in Adabas.
Action	Adapt your schema definition to the corresponding Adabas definitions.
INOXDE7662	An element nillable definition does not match the Adabas field definition
Explanation	The element defined as xsi:nil is not defined with NC (SQL NULL-Value Representation) -option in the Adabas FDT.
Action	Adapt the schema corresponding to the Adabas field definition.
INOXDE7663	An element's or attribute's format definition xs:date does not match the Adabas field definition
Explanation	An element defined as xs:date must be mapped to an ADABAS field with format P4.
Action	Adapt the schema to the corresponding Adabas definition.
INOXDE7664	An element's or attribute's format definition xs:dateTime does not match the Adabas field definition
Explanation	The element which is defined as xs:dateTime must be mapped to an Adabas field with format P7.
Action	Adapt the schema definition to the corresponding Adabas format.

INOXDE7665	(c-props-correct.1) An <xs:keyref> refers to an unknown <xs:key>
Explanation	The 'refer' attribute of <xs:keyref> must refer to a sibling node of type <xs:key> with a matching value of its 'name' attribute.
Action	Correct the schema document.
INOXDE7666	(c-props-correct.2) Invalid cardinality of <xs:field> child nodes of <xs:keyref>
Explanation	If the {identity-constraint category} is keyref, the cardinality of the {fields} must equal that of the {fields} of the {referenced key}.
Action	Correct the schema document.
INOXDE7667	(e-props-correct.3) The 'substitutionGroup' resolves to an unknown or invalid global element declaration
Explanation	The 'substitutionGroup' attribute of an element declaration, E1, must resolve to a global element, say E2, whose effective 'block' attribute, i.e. the substitution group exclusions do not contain the value "substitution". The {type definition} of E1 must be validly derived from the {type definition} of E2, using a derivation method not given in the effective 'block' attribute.
Action	Adapt the schema to match this constraint.
INOXDE7668	(cos-equiv-derived-ok-rec.1) Invalid relation of types of current element and its substitution group affiliate
Explanation	The derivation method of the type of the current element must be derived from the type of the substitution group affiliate's (i.e. the global element referenced by the 'substitutionGroup' attribute) type. The derivation method must be compatible with the substitution group exclusions defined by the 'block' attribute of the affiliate and the 'blockDefault' attribute of the respective schema node.
Action	Adapt schema to meet this constraint.
INOXDE7669	(e-props-correct.5) Found circular substitution group
Explanation	Circular substitution groups are disallowed. That is, it must not be possible to return to an element declaration by repeatedly following the {substitution group affiliation} property.
Action	Modify the schema to fulfill the constraint.

INOXDE7670	The 'final' attribute of a simple or complex type definition is more restrictive in the new schema compared to the old schema
Explanation	The 'final' attribute must not become more restrictive.
Action	Either adapt the value of the 'final' attribute or use instance validation when updating the schema.
INOXDE7671	A type definition has been set to abstract in the new schema
Explanation	When setting a type definition to abstract, this might cause documents to be invalid with respect to the new schema.
Action	Either make the type definition non-abstract as in the old schema or use instance validation when updating the schema.
INOXDE7672	An element declaration has been set to abstract in the new schema
Explanation	When setting an element declaration to abstract, this might cause documents to be invalid with respect to the new schema.
Action	Either make the element declaration non-abstract as in the old schema or use instance validation when updating the schema.
INOXDE7673	A complex type definition's 'block' attribute has been made more restrictive in the new schema
Explanation	When making a complex type definition's 'block' attribute more restrictive, this might cause documents to be invalid with respect to the new schema.
Action	Either set the complex type definition's 'block' attribute as in the old schema or use instance validation when updating the schema.
INOXDE7674	An element declaration's 'block' attribute has been made more restrictive in the new schema
Explanation	When making an element declaration's 'block' attribute more restrictive, this might cause documents to be invalid with respect to the new schema.
Action	Either set the element declaration's 'block' attribute as in the old schema or use instance validation when updating the schema.
INOXDE7675	An element's 'nillable' attribute was set to false in new schema
Explanation	If an element's 'nillable' attribute is set to false during a schema update, existing documents may become invalid.
Action	Either leave the element declaration's 'nillable' attribute unchanged or use instance validation for schema update.

INOXDE7676	Mismatch of identity constraints found during schema update
Explanation	It is not possible to modify existing or add new identity constraints during a schema update without using instance validation.
Action	Either do not add or modify identity constraints during schema update, or use instance validation.
INOXDE7677	An elements 'substitutionGroup' attribute was omitted or modified during schema update.
Explanation	An element's 'substitutionGroup' attribute may not be omitted or modified during schema update unless instance validation is being used.
Action	Either leave the 'substitutionGroup' attribute as is or use instance validation during schema update.
INOXDE7680	(length valid restriction) the length facet has been changed compared to the length facet of the base type
Explanation	It is an error if length is among the members of {facets} of {base type definition} and {value} is not equal to the {value} of the parent length.
Action	Modify the schema accordingly.
INOXDE7681	(maxLength valid restriction) the maxLength facet has been increased compared to the maxLength facet of the base type
Explanation	It is an error if maxLength is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent maxLength.
Action	Modify the schema accordingly.
INOXDE7682	(minLength valid restriction) the minLength facet has been decreased compared to the minLength facet of the base type
Explanation	It is an error if minLength is among the members of {facets} of {base type definition} and {value} is less than the {value} of the parent minLength.
Action	Modify the schema accordingly.
INOXDE7683	(totalDigits valid restriction) the totalDigits facet has been increased compared to the totalDigits facet of the base type
Explanation	It is an error if totalDigits is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent totalDigits.
Action	Modify the schema accordingly.

INOXDE7684	(fractionDigits valid restriction) the fractionDigits facet has been increased compared to the fractionDigits facet of the base type
Explanation	It is an error if fractionDigits is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent totalDigits
Action	Modify the schema accordingly.
INOXDE7685	(maxExclusive valid restriction) the maxExclusive facet has been increased compared to the maxExclusive facet of the base type
Explanation	It is an error if any of the following conditions is true: 1. maxExclusive is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent maxExclusive 2. maxInclusive is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent maxInclusive 3. minInclusive is among the members of {facets} of {base type definition} and {value} is less than or equal to the {value} of the parent minInclusive 4. minExclusive is among the members of {facets} of {base type definition} and {value} is less than or equal to the {value} of the parent minExclusive
Action	Modify the schema accordingly.
INOXDE7686	(maxInclusive valid restriction) the maxInclusive facet has been increased compared to the maxInclusive facet of the base type
Explanation	It is an error if any of the following conditions is true: 1. maxInclusive is among the members of {facets} of {base type definition} and {value} is greater than the {value} of the parent maxInclusive 2. maxExclusive is among the members of {facets} of {base type definition} and {value} is greater than or equal to the {value} of the parent maxExclusive 3. minInclusive is among the members of {facets} of {base type definition} and {value} is less than the {value} of the parent minInclusive 4. minExclusive is among the members of {facets} of {base type definition} and {value} is less than or equal to the {value} of the parent minExclusive
Action	Modify the schema accordingly.
INOXDE7687	(minExclusive valid restriction) the minExclusive facet has been increased compared to the minExclusive facet of the base type
Explanation	It is an error if any of the following conditions is true: 1. minExclusive is among the members of {facets} of {base type definition} and {value} is less than the {value} of the parent minExclusive 2. maxInclusive is among the members of {facets} of {base type definition} and {value} is greater the {value} of the parent maxInclusive 3. minInclusive is among the members of {facets} of {base type definition} and {value} is less than the {value} of the parent minInclusive 4. maxExclusive is among the members of {facets} of {base type definition} and {value} is greater than or equal to the {value} of the parent maxExclusive
Action	Modify the schema accordingly.

INOXDE7688 (minInclusive valid restriction) the minInclusive facet has been increased compared to the minInclusive facet of the base type

Explanation It is an error if any of the following conditions is true: 1. minInclusive is among the members of {facets} of {base type definition} and {value} is less than the {value} of the parent minInclusive 2. maxInclusive is among the members of {facets} of {base type definition} and {value} is greater the {value} of the parent maxInclusive 3. minExclusive is among the members of {facets} of {base type definition} and {value} is less than or equal to the {value} of the parent minExclusive 4. maxExclusive is among the members of {facets} of {base type definition} and {value} is greater than or equal to the {value} of the parent maxExclusive

Action Modify the schema accordingly.

INOXDE7689 (whiteSpace valid restriction) the whiteSpace facet has been changed to an invalid value compared to the whiteSpace facet of the base type

Explanation It is an error if whiteSpace is among the members of {facets} of {base type definition} and any of the following conditions is true: 1. {value} is replace or preserve and the {value} of the parent whiteSpace is collapse 2. {value} is preserve and the {value} of the parent whiteSpace is replace

Action Modify the schema accordingly.

INOXDE7690 (facet fixed) attempted to specify a different value for a facet which has fixed="true" in the base type definition

Explanation The value of the facet differs from the value of the facet in the base type definition.

Action Omit the facet in the derived value or remove fixed="true" from the base type definition.

INOXDE7696 Invalid change of schema-required property of collection

Explanation A collection must be either schemaless or schemas are required for all documents to be stored. It is not allowed to change the schema-required property.

Action Adapt the collection description correspondingly.

INOXDE7697 Could not create schemaless doctype in collection ino:etc

Explanation It is not possible to have two schemaless doctypes in collection 'ino:etc' with the same lexical QName but different namespace of the root element.

Action A workaround is to change the namespace prefix of the root element of the first instance to be inserted in a new implicit doctype.

INOXDE7698	(c-selector-xpath) Found invalid value of xpath attribute in definition of selector of identity constraint
Explanation	The xpath attribute of the selector of an identity constraint must adhere to the (c-selector-xpath) constraint.
Action	Fix the value of the xpath attribute: all name tests must use valid QNames, all namespace prefixes must be declared, no attribute steps allowed.
INOXDE7699	(c-fields-xpaths) Found invalid value of xpath attribute in definition of selector of identity constraint
Explanation	The xpath attribute of all fields of an identity constraint must adhere to the (c-fields-xpaths) constraint.
Action	Fix the value of the xpath attribute: all name tests must use valid QNames, all namespace prefixes must be declared, an attribute step is only allowed at the last position.
INOXDE7700	successful document validation
Explanation	The document validated without error.
Action	No action required.
INOXDE7701	memory allocation failed
Explanation	Memory allocation failed during document validation.
Action	Please contact your software supplier.
INOXDE7702	internal error
Explanation	An internal processing error occurred during document validation.
Action	Please contact your software supplier.
INOXDE7703	validation has detected an error in document
Explanation	The document validation has discovered some invalid document content.
Action	Modify your document.
INOXDE7704	(Parse error): document not well-formed
Explanation	The document content is not well-formed.
Action	Modify your document

INOXDE7705	(Parse error): junk data
Explanation	The document contains junk data after the document content.
Action	Modify your input stream.
INOXDE7706	(Parse error): close element error
Explanation	The document contains a closing tag that does not match opening tag.
Action	Modify your document
INOXDE7707	(Parse error): multiple attr
Explanation	The document contains multiple occurrences of the same attribute.
Action	Modify your document
INOXDE7708	Invalid root error
Explanation	Tamino allows only insertion of documents with root elements whose names correspond to the name of some doctype in the collection where you tried to insert the current document.
Action	Modify your document or schema.
INOXDE7709	Errors detected during document validation
Explanation	Errors were detected during document validation.
Action	Please either modify your XML schema or fix errors in your document(s).
INOXDE7710	(cvc-complex-type.2.1): empty content error
Explanation	The schema requires empty element content but some content was detected.
Action	Modify your document or schema.
INOXDE7711	(cvc-complex-type.2.3): mixed content error
Explanation	The schema does not allow mixed element content but some mixed content was detected.
Action	Modify your document or schema.

INOXDE7712	(cvc-complex-type.4): required attribute missing
Explanation	The schema requires an attribute that is not present in document.
Action	Modify your document or schema.
INOXDE7713	(cvc-wildcard.2): undeclared wildcard element
Explanation	Schema contains ANY with processContent = strict but element content's name does not match any globally declared element.
Action	Modify your document or schema.
INOXDE7714	(cvc-id.1): undefined IDREF value
Explanation	The document contains an IDREF value which does not exist as an ID value.
Action	Modify your document.
INOXDE7715	(cvc-id.2): duplicate ID value
Explanation	The document contains multiple copies of the same ID value.
Action	Modify your document.
INOXDE7716	(cvc-assess-attr.1): undeclared attribute
Explanation	No matching declaration can be found in the schema for an attribute, neither as an explicitly named attribute nor as attribute wildcard.
Action	Modify your document.
INOXDE7717	(cvc-type.3.1.1): invalid attribute
Explanation	A simple type description in the schema does not allow attributes here.
Action	Modify your document.
INOXDE7718	(cvc-type.3.1.2): invalid element content
Explanation	A simple type description in the schema does not allow element children here.
Action	Modify your document.
INOXDE7719	(cvc-particle): content of element does not match a particle description
Explanation	Element content cannot be successfully validated against a particle description in schema.
Action	Modify your document.

INOXDE7720	(cvc-particle.1.1): element content missing, minOccurs constraint violation in wildcard declaration
Explanation	The length of the element content sequence does not satisfy the minOccurs constraint.
Action	Modify your document.
INOXDE7721	(cvc-particle.1.2): too much element content, maxOccurs constraint violation in wildcard declaration
Explanation	The length of the element content sequence does not satisfy the maxOccurs constraint of the wildcard declaration.
Action	Modify your document.
INOXDE7722	(cvc-particle.2.1): element content missing, minOccurs constraint violation in element declaration
Explanation	The length of the element content sequence does not satisfy the minOccurs constraint.
Action	Modify your document.
INOXDE7723	(cvc-particle.2.2): too much element content, maxOccurs constraint violation in element declaration
Explanation	The length of the element content sequence does not match the maxOccurs constraint for the element declaration.
Action	Modify your document.
INOXDE7724	(cvc-particle.3.1): element content missing, minOccurs constraint violation in all model group declaration
Explanation	The length of the element content sequence does not satisfy the minOccurs constraint.
Action	Modify your document.
INOXDE7725	(cvc-particle.3.1): element content missing, minOccurs constraint violation in choice model group declaration
Explanation	The length of the element content sequence does not satisfy the minOccurs constraint.
Action	Modify your document.

INOXDE7726	(cvc-particle.3.1): element content missing, minOccurs constraint violation in sequence model group declaration
Explanation	The length of the element content sequence does not satisfy the minOccurs constraint.
Action	Modify your document.
INOXDE7727	(cvc-particle.3.2): too much element content, maxOccurs constraint violation in all model group declaration
Explanation	The length of the element content sequence does not satisfy the maxOccurs constraint of the all model group declaration.
Action	Modify your document.
INOXDE7728	(cvc-particle.3.2): too much element content, maxOccurs constraint violation in choice model group declaration
Explanation	The length of the element content sequence does not satisfy the maxOccurs constraint of the choice model group declaration.
Action	Modify your document.
INOXDE7729	(cvc-particle.3.2): too much element content, maxOccurs constraint violation in sequence model group declaration
Explanation	The length of the element content sequence does not satisfy the maxOccurs constraint of the sequence model group declaration.
Action	Modify your document.
INOXDE7730	(cvc-model-group.1):invalid end of sequence
Explanation	A sequence does not contain all required elements. In particular, the sequence ends without containing all required elements.
Action	Modify your document.
INOXDE7731	(cvc-model-group.1):invalid sequence
Explanation	A sequence does not contain all required elements.
Action	Modify your document.

INOXDE7732	(cvc-model-group.2):invalid choice
Explanation	An element's child node does not match any choice in schema.
Action	Modify your document.
INOXDE7733	(cvc-model-group.3):invalid all - missing element
Explanation	An element's child node does not contain all required children of the all model group in the schema.
Action	Modify your document.
INOXDE7734	(cvc-model-group.3):invalid all - undeclared element
Explanation	An element's child node does not match any node declared in the all model group in the schema.
Action	Modify your document.
INOXDE7735	(cvc-model-group.3):invalid all - too many child elements
Explanation	All allowed elements in an all model group already appeared, but there are more illegal child elements.
Action	Modify your document.
INOXDE7736	(cvc-model-group.3):invalid all - repeated occurrence of one element
Explanation	Every child element in an all model group may appear at most once, but here the element appears more often.
Action	Modify your document.
INOXDE7737	(cvc-wildcard-namespace): invalid namespace with respect to namespace constraint of wildcard
Explanation	For namespace="##other" a non-absent namespace is required, which differs from the targetNamespace of the schema. For namespace="##targetNamespace" the namespace must match the current schema's targetNamespace. For namespace="##local" the element or attribute matching vs. the wildcard must not belong to any namespace. If the namespace attribute of the wildcard contains a list of URIs the namespace of the element or attribute matching vs. the wildcard must match one of the URIs in the list.
Action	Modify your document or schema.

INOXDE7738	(cvc-wildcard-namespace.2.3): invalid namespace for wildcard with namespace="##other"
Explanation	The namespace of an element or attribute does not differ from the current schema's targetNamespace as required by namespace='##other' specified in a wildcard (xs:any or xs:anyAttribute).
Action	Modify your document.
INOXDE7739	(cvc-wildcard-namespace.3): invalid namespace for wildcard with namespace="##local"
Explanation	An element or attribute belongs to a namespace in contradiction to the namespace="##local" attribute of a wildcard (xs:any or xs:anyAttribute).
Action	Modify your document.
INOXDE7740	(cvc-complex-type.2.4): element child error
Explanation	The list of child elements could not to be partitioned in a way that it becomes valid with respect to the content type's particle.
Action	Modify your document or schema.
INOXDE7741	A namespace prefix conflict was detected when attempting to insert default or fixed value
Explanation	A namespace prefix used in a value constraint for a node whose datatype is xs:QName, xs:NOTATION or a derived type cannot be associated with the intended URI as the document already contains a namespace declaration for that prefix mapped to a different URI. Note that the default namespace is always assumed to be used.
Action	Adapt the document to be stored or the fragment to be inserted to avoid conflict.
INOXDE7742	(cvc-elt.4.3) The local type definition given by the xsi:type attribute is not validly derived from the type definition as of the underlying schema
Explanation	The local type definition given by the xsi:type attribute must be derived from the type definition as of the underlying schema. Derivation methods listed in the attribute named "block" of the element declaration or the associated complex type definition may not be used.
Action	Either modify the schema by changing or removing the "block" attribute of the element declaration or complex type definition, or modify or remove the xsi:type attribute from the document to be stored.

INOXDE7743	(cvc-elt.2) For an element information item to be locally valid with respect to an element declaration the declaration's abstract must be 'false'
Explanation	Found an element declaration which is abstract when attempting to validate an element.
Action	Change the value of the 'abstract' property of the respective element declaration.
INOXDE7744	(cvc-complex-type.1) For an element information item to be locally valid with respect to a complex type definition the type definition's abstract must be 'false'
Explanation	Attempted to validate an element against a complex type definition which is abstract.
Action	Either make the type definition non-abstract, or use the xsi:type attribute in the XML document referring to a non-abstract derived type.
INOXDE7745	(cvc-identity-constraint.3) An <x:field> of an identity constraint caused multiple matching nodes or the respective node does not have a simple type
Explanation	For each node in the target node set of an identity constraint, all of the {fields} for a selected context node evaluate to either an empty node-set or a node-set with exactly one member, which must have a simple type.
Action	Check the XML document or remove the identity constraint from the schema.
INOXDE7746	(cvc-identity-constraint.4.1) Found multiple occurrence of same key-sequence for <x:unique> identity constraint
Explanation	No two members of the qualified node set of an <x:unique> may have key-sequences whose members are pairwise equal.
Action	Check the XML document or remove the identity constraint from the schema.
INOXDE7747	(cvc-identity-constraint.4.2.1) A field of an <x:key> identity constraint evaluates to an empty node-set
Explanation	For <x:key>, all the {fields} must evaluate to a node-set with exactly one member.
Action	Check the XML document or remove the identity constraint from the schema.
INOXDE7748	(cvc-identity-constraint.4.2.2) Found multiple occurrence of same key-sequence for <x:key> identity constraint
Explanation	No two members of the qualified node set of an <x:key> may have key-sequences whose members are pairwise equal.
Action	Check the XML document or remove the identity constraint from the schema.

INOXDE7749	(cvc-identity-constraint.4.3) Could not locate matching key sequence in node table of <xs:key> identity constraint referenced by <xs:keyref>
Explanation	For each member of the qualified node set of a <xs:keyref> there must be a corresponding entry in the node table of the referenced <xs:key>.
Action	Check the XML document or remove the identity constraint from the schema.
INOXDE7750	(cvc-elt.3.1) Attribute 'xsi:nil' not allowed if the 'nillable' attribute of the element declaration is not set to 'true'
Explanation	The predefined 'xsi:nil' attribute is only allowed on an element information item if the corresponding element declaration in the schema has its 'nillable' attribute to 'true'.
Action	Check the schema or remove the 'xsi:nil' attribute from the document.
INOXDE7751	(cvc-elt.3.2.1) Found character or element content inside element information item with xsi:nil='true'
Explanation	If an element has the xsi:nil='true' attribute, it must not have any character or element content.
Action	Modify the document accordingly.
INOXDE7752	(cvc-elt.3.2.2) Element declaration corresponding to element information item with xsi:nil='true' attribute has a fixed value constraint
Explanation	For an element information item with xsi:nil='true' attribute the corresponding element declaration in the schema must not have a fixed value constraint.
Action	Remove either the 'nillable' or the 'fixed' attribute from the element declaration in the schema.
INOXDE7753	(cos-equiv-derived-ok-rec.2.1) The effective blocking constraint of the element to be substituted contains 'substitution'
Explanation	The blocking constraint of an element to be substituted during validation must not contain 'substitution'.
Action	Adapt the XML document or modify the 'block' or 'blockDefault' attributes in the schema to become consistent with the constraint.
INOXDE7754	(cos-equiv-derived-ok-rec.2.3) Type derivation between type of element to be substituted and type of the substituting element is blocked by the effective 'block' attribute of the element to be substituted
Explanation	The type of the substituting element must be derived from the type of the element to be substituted by means of restriction and/or extension, unless one of those derivation methods is being blocked by the 'block' attribute (if present) of the element to be substituted, or the 'blockDefault' attribute of the parent schema.

Action Adapt the XML document or modify the 'block' or 'blockDefault' attributes in the schema to become consistent with the constraint.

INOXDE7761 (cvc-datatype-valid) Overflow detected during validation

Explanation A value overflow has been detected during validation against the XML schema.

Action Ensure that the values adhere to datatype specific limits.

INOXDE7762 (cvc-datatype-valid) Value out of range detected during validation

Explanation A value smaller than the valid minimum or larger than the allowed maximum has been detected during validation against the XML schema.

Action Ensure that the values adhere to the datatype specific minimum and maximum.

INOXDE7763 (cvc-datatype-valid) An invalid value has been found during validation

Explanation A value outside the lexical space has been detected during validation against the XML schema.

Action Ensure that the value adheres to the datatype specific lexical space.

INOXDE7764 (cvc-enumeration-valid) A value not defined in the respective enumeration has been found during validation.

Explanation A value which is not listed in the respective enumeration has been detected during validation against the XML schema.

Action Ensure that the value matches one of the enumeration values specified in the XML schema.

INOXDE7765 (cvc-length-valid) Facet 'length' was violated by a value during validation.

Explanation A value whose length does not match the 'length' facet has been detected during validation against the XML schema.

Action Ensure that the value's length matches the restriction given by the schema.

INOXDE7766 (cvc-attribute.4): fixed value error

Explanation An attribute declaration in schema requires a fixed value which is different from given value in document.

Action Modify your document.

INOXDE7767	(cvc-elt.5.2.2.1): fixed value error
Explanation	The element declaration in schema requires a fixed value which is different from given value in document.
Action	Modify your document.
INOXDE7768	(cvc-au): fixed value error
Explanation	The attribute use declaration in the schema requires a fixed value which is different from the given value in the document.
Action	Modify your document.
INOXDE7769	(cvc-elt.5.2.2.2.2): fixed value error
Explanation	The element declaration in the schema requires a fixed value which is different from given value in document.
Action	Modify your document.
INOXDE7770	(cvc-minLength-valid) Facet 'minLength' was violated by a value during validation
Explanation	A value whose length is less than the 'minLength' facet has been detected during validation against the XML schema.
Action	Ensure that the value's length matches the restriction given by the schema.
INOXDE7771	(cvc-maxLength-valid) Facet 'maxLength' was violated by a value during validation
Explanation	A value whose length is greater than the 'maxLength' facet has been detected during validation against the XML schema.
Action	Ensure that the value's length matches the restriction given by the schema.
INOXDE7772	(cvc-pattern-valid) Facet 'pattern' was violated by a value during validation
Explanation	A value whose pattern does not match the 'pattern' facet has been detected during validation against the XML schema.
Action	Ensure that the value's pattern matches the restriction given by the schema.
INOXDE7773	(cvc-enumeration-valid) Facet 'enumeration' was violated by a value during validation
Explanation	A value has been found which does not match the valid values specified by the 'enumeration' facet, during validation against the XML schema.
Action	Ensure that the value matches the restriction given by the schema.

INOXDE7774	(cvc-maxInclusive-valid) Facet 'maxInclusive' was violated by a value during validation
Explanation	A value has been found which is greater than the 'maxInclusive' facet, during validation against the XML schema.
Action	Ensure that the value matches the restriction given by the schema.
INOXDE7775	(cvc-maxExclusive-valid) Facet 'maxExclusive' was violated by a value during validation
Explanation	A value has been found which is greater or equal to the 'maxExclusive' facet, during validation against the XML schema.
Action	Ensure that the value matches the restriction given by the schema.
INOXDE7776	(cvc-minInclusive-valid) Facet 'minInclusive' was violated by a value during validation
Explanation	A value has been found which is lower than the 'minInclusive' facet, during validation against the XML schema.
Action	Ensure that the value matches the restriction given by the schema.
INOXDE7777	(cvc-minExclusive-valid) Facet 'minExclusive' was violated by a value during validation
Explanation	A value has been found which is less than or equal to the 'minExclusive' facet, during validation against the XML schema.
Action	Ensure that the value matches the restriction given by the schema.
INOXDE7778	(cvc-totalDigits-valid) Facet 'totalDigits' was violated by a value during validation
Explanation	A numerical value has been found with more digits than specified by the 'totalDigits' facet, during validation against the XML schema.
Action	Ensure that the value matches the restriction given by the schema.
INOXDE7779	(cvc-fractionDigits-valid) Facet 'fractionDigits' was violated by a value during validation
Explanation	A numerical value has been found with more fractional digits (i.e. to the right of the decimal point) than specified by the 'fractionDigits' facet, during validation against the XML schema.
Action	Ensure that the value matches the restriction given by the schema.

INOXDE7780	Divide by zero error
Explanation	An attempt was made to divide by zero. Division by zero is mathematically undefined.
Action	Make sure that no division by zero occurs.
INOXDE7781	Invalid or unsupported attribute found
Explanation	An attribute was found that is not supported by Tamino.
Action	In order to enable xsi:type processing you have to set the server parameter "reject xsi:type" to "no".
INOXDE7782	Namespace prefix is bound to an invalid URI
Explanation	A namespace prefix must be bound to a non-empty URI in a namespace declaration. In addition, some prefixes must be bound to a fixed URI.
Action	Ensure e.g. that the prefix 'xml' is bound to 'http://www.w3.org/XML/1998/namespace', and that 'ino' is bound to 'http://namespaces.softwareag.com/tamino/response2'.
INOXDE7783	The namespace prefix in an element or attribute value is not declared
Explanation	If an element's or attribute's type is xs:QName or xs:NOTATION, the respective prefix must be declared in the schema document.
Action	Add the missing namespace declaration.
INOXDE7784	Invalid namespace prefix
Explanation	A namespace prefix is invalid.
Action	Modify the namespace definition and repeat the request.
INOXDE7785	The datatype referenced by xsi:type is unknown
Explanation	The value of the xsi:type attribute must reference a datatype predefined by XML Schema or a user-defined global datatype.
Action	Check the type reference via xsi:type in XML document.
INOXDE7786	Invalid prefix bound to URI
Explanation	The URI cannot be bound to the given namespace prefix.
Action	Use an appropriate prefix.

INOXDE7787	Invalid value of 'xsi:nil' attribute
Explanation	The value of the 'xsi:nil' attribute must be a valid boolean, i.e. 'true', 'false', '1', or '0'.
Action	Modify the document accordingly.
INOXDE7821	Class not found
Explanation	Tamino schema tree internal error message.
Action	Please contact your system administrator.
INOXDE7822	Duplicated class name
Explanation	Tamino schema tree internal error message.
Action	Please contact your system administrator.
INOXDE7823	Illegal cast
Explanation	Tamino schema tree internal error message.
Action	Please contact your system administrator.
INOXDE7824	Internal API error
Explanation	Tamino schema tree internal error.
Action	Please contact your software supplier.
INOXDE7827	No memory
Explanation	Tamino schema tree internal error message.
Action	Please contact your system administrator.
INOXDE7828	No such element
Explanation	Tamino schema tree internal error message.
Action	Please contact your system administrator.
INOXDE7829	Not implemented
Explanation	Tamino schema tree internal error message.
Action	Please contact your system administrator.

INOXDE7830	Too many classes
Explanation	Tamino schema tree internal error message.
Action	Please contact your system administrator.
INOXDE7831	XML parser error
Explanation	Tamino schema tree internal error message.
Action	Please contact your system administrator.
INOXDE7833	Operation failed
Explanation	An internal error occurred.
Action	Please contact your software supplier.
INOXDE7856	Buffer size exceeded
Explanation	Tamino schema tree error message.
Action	Please contact your system administrator.
INOXDE7860	Internal error: invalid node type
Explanation	This is a Tamino schema tree error message.
Action	Please contact your system administrator.
INOXDE7861	Index out of range
Explanation	Tamino schema tree error message.
Action	Please contact your system administrator.
INOXDE7862	User abort
Explanation	Tamino schema tree internal error message.
Action	Please contact your system administrator.
INOXDE7865	Schema cache: access denied
Explanation	Schema cache: access denied.
Action	Please contact your software supplier.

INOXDE7867	Internal error: schema not in cache
Explanation	Internal error: schema not in cache.
Action	Please contact your software supplier.
INOXDE7868	Internal error: write lock expected
Explanation	Internal error: write lock expected.
Action	Please contact your software supplier.
INOXDE7869	Internal error: schema not locked
Explanation	Internal error: schema not locked.
Action	Please contact your software supplier.
INOXDE7883	(p-props-correct.2.1) If maxOccurs has a numeric value, then minOccurs must not be greater than maxOccurs
Explanation	If maxOccurs has a numeric value, then minOccurs must not be greater than maxOccurs.
Action	Modify the XML schema accordingly.
INOXDE7884	(p-props-correct.2.2) If maxOccurs has a numeric value, then maxOccurs must be greater than or equal to 1
Explanation	If maxOccurs has a numeric value, then maxOccurs must be greater than or equal to 1.
Action	Modify the XML schema accordingly.
INOXDE7885	(src-attribute.2) use must have value optional
Explanation	If the attribute's "default" and "use" attributes are both present, then "use" must have the value "optional".
Action	Modify the XML schema accordingly.
INOXDE7886	(src-attribute.4) For attribute the type and simpleType must not both be present
Explanation	For attribute, the type and simpleType must not both be present.
Action	Modify the XML schema accordingly.

INOXDE7887	(src-element.1) For element the attributes default and fixed must not both be present
Explanation	For element, the attributes "default" and "fixed" must not both be present.
Action	Modify the XML schema accordingly.
INOXDE7888	(src-element.3) For element the attributes type and either simpleType or complex Type are mutually exclusive
Explanation	For element, the attributes "type" and either "simpleType" or "complex Type" are mutually exclusive.
Action	Modify the XML schema accordingly.
INOXDE7889	(src-element.2.1) For element either the attribute ref or name must be present, but not both
Explanation	For element, either the attribute ref or name must be present, but not both.
Action	Modify the XML schema accordingly.
INOXDE7890	(src-element.2.2) For element if parent is not schema and attribute ref is present, only attributes minOccurs, maxOccurs and id are allowed in addition to ref
Explanation	If the parent of the element is not schema and the attribute ref is present, then all of <xs:complexType>, <xs:simpleType>, <xs:key>, <xs:keyref>, <xs:unique>, nillable, default, fixed, form, block and type must be absent.
Action	Modify the XML schema accordingly.
INOXDE7891	(valid-data-types.1) The type of nodes and base attribute of restriction nodes may only be of the supported types
Explanation	The type of nodes and base attribute of restriction nodes may only be of the supported types, namely: date, decimal, double, float, integer, short, SQLNumeric,, SQLVarchar, string, time, timeinstant, ID, IDREF, IDREFS, NMTOKEN, NMTOKENS. No user-defined complexType or simpleType are allowed for type.
Action	Modify the XML schema accordingly.
INOXDE7895	(valid-data-types.2) The facet is not valid for the base datatype
Explanation	A facet has been specified which is not supported for the base datatype of a restriction.
Action	Modify the XML schema accordingly.

INOXDE7900	(length and minLength or maxLength) Conflict between length facet and either minLength or maxLength
Explanation	It is an error for both length and either of minLength or maxLength to be members of {facets}, unless they are specified in different derivation steps in which case the following must be true: the {value} of minLength <= the {value} of length <= the {value} of maxLength.
Action	Modify the XML schema accordingly.
INOXDE7901	(fractionDigits less than or equal to totalDigits) The value of the fractionDigits facet is greater than the value of totalDigits
Explanation	It is an error for fractionDigits to be greater than totalDigits.
Action	Modify the XML schema accordingly.
INOXDE7902	The root node of a doctype has a non-trivial substitution group
Explanation	The root node of a doctype must not have a non-trivial substitution group. The QName of the root element of an XML document stored in a doctype must be identical to the doctype's QName.
Action	Remove the substitutionGroup reference to the root node from the schema.
INOXDE7906	Found illegal logical or physical property for shadowXML doctype
Explanation	It is not allowed to specify certain logical or physical properties, e.g. XNode mapping, for a shadowXML doctype.
Action	Remove the illegal property below <tsd:logical> and <tsd:physical> for the shadowXML doctype.
INOXDE7907	(src-resolve.1.3) The ref attribute of an element needs to reference an existing global element
Explanation	The ref attribute of an element needs to reference an existing global element.
Action	Modify the XML schema accordingly.
INOXDE7908	Found logical or physical properties for nonXML doctype
Explanation	It is not allowed to specify logical or physical properties for a nonXML doctype.
Action	Remove <tsd:logical> and <tsd:physical> for the nonXML doctype.

INOXDE7909	(cos-nonambig.1) Unique Particle Attribution failure
Explanation	A content model must be formed such that during validation of an element information item sequence, the particle contained directly, indirectly or implicitly therein with which to attempt to validate each item in the sequence in turn can be uniquely determined without examining the content or attributes of that item, and without any information about the items in the remainder of the sequence.
Action	Modify the XML schema accordingly.
INOXDE7910	(cos-all-limited.1.2) All group limitation failure
Explanation	The cardinality of an all-model group must be exactly one.
Action	Modify the XML schema accordingly.
INOXDE7911	(cos-all-limited.2) All group limitation failure
Explanation	The maximum cardinality of all elements in all-model group must be 0 or 1.
Action	Modify the XML schema accordingly.
INOXDE7912	(src-attribute.1) For attribute declarations, their attributes default and fixed must not both be present
Explanation	For attribute declarations, the attributes "default" and "fixed" must not both be present.
Action	Modify the XML schema accordingly.
INOXDE7913	(src-attribute.3.1) Either attribute ref or name must be present, but not both
Explanation	Either the attribute "ref" or the attribute "name" must be present, but not both.
Action	Modify the XML schema accordingly.
INOXDE7914	(src-attribute.3.2) If attribute's parent is not schema and ref is present, <simpleType>, form and type are not allowed
Explanation	The form or type attribute as well as a simpleType cannot be specified with attribute declarations if the parent is not the schema node and the ref attribute is present.
Action	Modify the XML schema accordingly.
INOXDE7915	The doctype name needs to be unique within a collection
Explanation	The doctype name needs to be unique within a collection.
Action	Modify the XML schema accordingly.

INOXDE7916	The given path must exist in the current schema
Explanation	The given path must exist in the current schema.
Action	Modify the XML schema accordingly.
INOXDE7917	For each doctype name where the doctype is not of plain non-XML type there must be a matching global element with a matching qualified name
Explanation	For each doctype name where the doctype is not of plain non-XML type there must be a matching global element with a matching qualified name. In particular, for non-XML doctypes with non-XML indexing via a shadow XML document a matching global element must exist.
Action	Modify the XML schema accordingly.
INOXDE7918	For each doctype name where the doctype is of type nonXML there must not be a matching global element with the same name
Explanation	For each doctype name where the doctype is of type non-XML there must not be a matching global element with the same name.
Action	Modify the XML schema accordingly.
INOXDE7919	For accessOptions at least one of read, insert, update or delete needs to be given, but no duplicate entries of these are allowed
Explanation	For accessOptions at least one of read, insert, update or delete needs to be given, but no duplicate entries of these are allowed.
Action	Modify the XML schema accordingly.
INOXDE7920	Invalid node name
Explanation	The name of an element or attribute does not match the repository naming conventions.
Action	Change the name of element or attribute.
INOXDE7921	Attempted to re-use a schema specifying physical properties from a schema belonging to a different collection
Explanation	This constraint has been introduced in order to prevent database inconsistencies. It may vanish in a future version of Tamino.
Action	Change the collection name either of the referenced or the referring schema.

INOXDE7922	The given path must exist in the current Schema and lead to the element or attribute for which it is specified
Explanation	The given path must exist in the current schema and lead to the element or attribute for which it is specified.
Action	Modify the XML schema accordingly.
INOXDE7923	No XPath expression may occur twice for one node to avoid conflicting mappings
Explanation	No XPath expression may occur twice for one node in order to avoid conflicting mappings (not even if it specifies the same mapping).
Action	Modify the XML schema accordingly.
INOXDE7924	At most one elementInfo or attributeInfo may have only empty or a nonexistent which-element, which is taken as the default mapping
Explanation	At most one elementInfo or attributeInfo may have only empty or a non-existent which element, which is taken as the default mapping (Note: empty which elements are ignored, so an elementInfo which has both empty and filled which elements is interpreted as an elementInfo with filled which elements).
Action	Modify the XML schema accordingly.
INOXDE7925	Below Schema there may only be one appinfo node which defines Tamino mappings
Explanation	Below Schema there may only be one appinfo node which defines Tamino mappings.
Action	Modify the XML schema accordingly.
INOXDE7926	Below Schema there must be a schemaInfo node but no elementInfo or attributeInfo nodes
Explanation	Below Schema there must be a schemaInfo node but no elementInfo or attributeInfo nodes.
Action	Modify the XML schema accordingly.
INOXDE7927	Below Element there may only be one appinfo node which defines Tamino mappings
Explanation	Below Element there may only be one appinfo node which defines Tamino mappings.
Action	Modify the XML schema accordingly.

INOXDE7928	Below Element there may be only elementInfo node but no schemaInfo or attributeInfo nodes
Explanation	Below Element there may be only elementInfo node but no schemaInfo or attributeInfo nodes.
Action	Modify the XML schema accordingly.
INOXDE7929	Below Attribute there may only be one appinfo node which defines Tamino mappings
Explanation	Below Attribute there may only be one appinfo node which defines Tamino mappings.
Action	Modify the XML schema accordingly.
INOXDE7930	internal error
Explanation	While processing a schema document an internal error occurred.
Action	Please contact your software supplier.
INOXDE7931	An error occurred while processing a schema document
Explanation	An error occurred during processing of a TSD3 schema document.
Action	Details may be supplied by a secondary error message or can be retrieved using the admin-command <code>ino:CheckSchema(collection-name, schema-name)</code> or <code>ino:CheckSchema()</code> for all schemas in all collections. Correct the schema and update it in the database.
INOXDE7932	Errors occurred when checking constraints for schema document
Explanation	A TSD3 schema document does not adhere to all relevant restrictions.
Action	Check the secondary error message for details.
INOXDE7933	Version mismatch occurred during schema processing
Explanation	An attempt was made to load a TSD3 schema into a TSD2 collection or vice versa.
Action	Ensure that used schema language levels are consistent within a single collection.
INOXDE7934	Invalid schema document
Explanation	The XML document does not contain a valid TSD3 schema.
Action	Ensure that the schema document is consistent with the Tamino schema definition language TSD3.

INOXDE7935	Schema not found
Explanation	The referenced schema does not exist.
Action	Check for the existence of the referenced TSD3 schema.
INOXDE7936	Invalid define of system collection
Explanation	The schema to be defined refers to a collection reserved for system usage.
Action	Choose a different collection name.
INOXDE7938	Internal error: invalid or unknown version information
Explanation	Internal error occurred when retrieving or checking version information.
Action	Please contact your software supplier.
INOXDE7939	Invalid schema document
Explanation	The schema document contains an invalid or outdated format.
Action	Check the schema document. Possibly you are using TSD2. If so, convert to TSD3 using the Tamino Schema Editor.
INOXDE7940	Invalid modification of doctype: cannot switch between storage of XML, nonXML and indexed nonXML documents
Explanation	An error was detected when updating the schema: an attempt was made to modify between storage of XML, nonXML and indexed nonXML documents.
Action	Check the secondary error message for the context where the error was detected.
INOXDE7941	Must not omit doctype during schema update
Explanation	An error was detected when updating the schema: all doctypes defined in the original schema must occur in the new schema.
Action	Check the secondary error message for the context where the error was detected. Either extend the new schema document or undefine the obsolete doctype(s) before the next attempt to update the schema.
INOXDE7942	Cannot switch doctype to closed content via schema update
Explanation	It is not permitted to turn a doctype back to closed content if it had been configured for open content before.
Action	In order to switch a doctype back to closed content mode you have to undefine and re-create the doctype and reload the data.

INOXDE7943	Mismatch of minOccurs attribute during schema update
Explanation	An error was detected when updating the schema: the new value of the minOccurs attribute must be less than or equal to the old one.
Action	Check the secondary error message the for context where the error was detected.
INOXDE7944	Mismatch of maxOccurs attribute during schema update
Explanation	An error was detected when updating the schema: the new value of the the maxOccurs attribute must be greater than or equal to the old one. If it was previously unbounded, it must not be changed at all.
Action	Check the secondary error message for the context where the error was detected.
INOXDE7945	Mismatch of mapping detected during schema update
Explanation	An error was detected when updating the schema: a path containing mapping information which has been added in the new schema was already valid in the old schema.
Action	Check the secondary error message for the context where the error was detected.
INOXDE7946	Mismatch of element or attribute name detected during schema update
Explanation	An error was detected when updating the schema: names of corresponding elements or attributes in old and new schema are different.
Action	Check the secondary error message for the context where the error was detected.
INOXDE7947	Mismatch of element or attribute type detected during schema update
Explanation	An error was detected when updating the schema: types of corresponding elements or attributes in the old and new schema are different.
Action	Check the secondary error message for the context where the error was detected.
INOXDE7948	Mismatch of content model detected during schema update
Explanation	An error was detected when updating the schema: the content models are not equivalent.
Action	Check the secondary error message for the context where the error was detected.

INOXDE7949	Mismatch of content model of sequence detected during schema update
Explanation	An error was detected when updating the schema: the content model inside a sequence of the new schema contains an additional non-optional component.
Action	Check the secondary error message for the context where the error was detected.
INOXDE7950	Mismatch of enumeration detected during schema update
Explanation	An error was detected when updating the schema: it is only possible to add enumeration values in the new schema if there had been at least one enumeration value in the old schema.
Action	Check the secondary error message for the context where the error was detected.
INOXDE7951	Mismatch of fixed attribute detected during schema update
Explanation	An error was detected when updating the schema: the value of the fixed attribute of an element must not be changed.
Action	Check the secondary error message for the context where the error was detected.
INOXDE7952	Mismatch of "default which" detected during schema update
Explanation	An error was detected when updating the schema: no elementInfo or attributeInfo without a which element may be added in the new schema.
Action	Check the secondary error message for the context where the error was detected.
INOXDE7953	Invalid modification of processContents attribute detected during schema update
Explanation	An error was detected when updating the schema: the processContents attribute may only change from "strict" to "lax" to "skip".
Action	Check the secondary error message for the context where the error was detected.
INOXDE7954	Invalid modification of mixed attribute detected during schema update
Explanation	An error was detected when updating the schema: the mixed attribute may only change from "false" to "true".
Action	Check the secondary error message for the context where the error was detected.
INOXDE7955	Invalid modification of components of choice detected during schema update
Explanation	An error was detected when updating the schema: choice in the new schema must contain all components of choice in the old schema in arbitrary order. Additional components may be added for closed content. For open content, components may only be removed from the content model.
Action	Check the secondary error message for the context where the error was detected.

INOXDE7956	Invalid modification of components of sequence detected during schema update
Explanation	An error was detected when updating the schema: sequence in the new schema must contain all components of sequence in the old schema in the same order. Additional optional components with minOccurs=0 may be added in the case of closed content of the doctype. For open content, components may only be removed from the content model.
Action	Check the secondary error message for the context where the error was detected.
INOXDE7957	Invalid modification of element's or attribute's simpleType detected during schema update
Explanation	An error was detected when updating the schema: element or attribute may not be defined with simpleType in the old schema and without simpleType in the new schema or vice versa.
Action	Check the secondary error message for the context where the error was detected.
INOXDE7958	Invalid modification of element's complexType detected during schema update
Explanation	An error was detected when updating the schema: element or attribute may not be defined with complexType in the old schema and without complexType in the new schema or vice versa.
Action	Check the secondary error message for the context where the error was detected.
INOXDE7960	Invalid path in schema definition
Explanation	The specified path inside the which element is invalid for this schema.
Action	Check the path and schema definition.
INOXDE7961	Invalid path in schema definition
Explanation	The specified path inside the which element has an invalid syntax.
Action	Check the path value.
INOXDE7962	Invalid modification of attribute list detected during schema update
Explanation	An error was detected when updating the schema: all attributes defined for an element in the old schema must occur in the new schema in arbitrary order. Optional attributes may be added.
Action	Check the secondary error message for the context where the error was detected.

INOXDE7963	Additional attribute must be optional during schema update
Explanation	An error was detected when updating the schema: all additional attributes must be optional in the case of closed content. For open content, attributes may only be removed.
Action	Check the secondary error message for the context where the error was detected.
INOXDE7964	Mismatch of use attribute detected during schema update.
Explanation	An error was detected when updating the schema: the use attribute of an xsd:attribute may only be changed from "required" to "optional".
Action	Check the secondary error message for the context where the error was detected.
INOXDE7965	Invalid modification of components of all detected during schema update
Explanation	Invalid modification of components of all detected during schema update. Additional optional components may be added in the case of closed content. For open content, components may only be removed from the content model.
Action	Please modify your XML schema.
INOXDE7966	Mismatch of targetNamespace attribute detected during schema update
Explanation	The targetNamespace attribute may not be changed during a schema update.
Action	Please adapt your schema.
INOXDE7967	Mismatch of namespace declaration detected during schema update
Explanation	Namespace declarations may not be changed during a schema update.
Action	Please adapt your schema.
INOXDE7968	New global element detected during schema update
Explanation	Global elements may not be added during a schema update if there is an <code><x:any></code> element by which they may be referred to implicitly.
Action	Please check your schema.
INOXDE7969	New global attribute detected during schema update
Explanation	Global attributes may not be added during a schema update if there is an <code><x:anyAttribute></code> element they may be referred by implicitly.
Action	Please check your schema.

INOXDE7970	Invalid attempt to remove an attribute wildcard (xs:anyAttribute) during a schema update
Explanation	An attribute wildcard may not be removed during a schema update.
Action	Please check your schema.
INOXDE7971	Removed global element during schema update
Explanation	Global elements may not be removed during a schema update if there is an <xs:any> element they may be referred by implicitly.
Action	Please check your schema.
INOXDE7972	Removed global attribute during schema update
Explanation	Global attributes may not be removed during a schema update if there is an <xs:anyAttribute> element they may be referred by implicitly.
Action	Please check your schema.
INOXDE7973	Facet added during schema update
Explanation	The new schema contains a facet which is not present in the existing schema.
Action	Consider removing the facet from the new schema or use instance validation.
INOXDE7974	Attempted to make value of facet more restrictive during schema update
Explanation	The new schema definition contains a facet with a value more restrictive than in the existing schema. This is not allowed by the restricting facet.
Action	Consider changing the value of the facet in the new schema or use instance validation.
INOXDE7975	Restriction facet's value must not change during schema update
Explanation	The new schema definition contains a facet with a value different from that in the existing schema. This is not allowed by the restricting facet.
Action	Consider changing the value of the facet in the new schema or use instance validation.
INOXDE7976	Mismatch of pattern detected during schema update
Explanation	An error was detected when updating the schema: It is only possible to add pattern values in the new schema if there had been at least one pattern value in the old schema. It is only possible to remove pattern values from the new schema if this results in having no pattern values in the new schema.
Action	Check the secondary error message for the context where the error was detected.

INOXDE7978	Mismatch of namespace declarations found during schema update checks
Explanation	An attempt was made to modify the URI associated with a namespace prefix. This is based on namespace declarations in the schema document. Either a namespace declaration was omitted or the URI has been changed. This is not allowed because it would change the semantics of X-Query requests on namespace-clean doctypes.
Action	Modify the schema accordingly.
INOXDE7979	Invalid schema changes found when adding a unique constraint - no other schema changes are permitted
Explanation	When adding a unique constraint no other schema changes are permitted in the same schema update operation. It is also not permitted to add multiple unique constraints in a single schema update.
Action	Either add a single unique constraint or perform other schema changes in separate steps.
INOXDE7980	At least one doctype contains instances with xsi:type attributes. Schema update requires explicit validation.
Explanation	This error may show up e.g. if the set of global types is going to change due to the schema update. Thus, XML instances containing xsi:type attributes require re-validation. Note that this status of the doctype remains set even after the respective XML documents have been deleted.
Action	Perform a schema update with instance validation (<code>_mode=validate</code>).
INOXDE7981	Attempted to remove member of substitution group during schema update for doctype with closed content
Explanation	You cannot remove a member of a substitution group during a schema update for a doctype with closed content without instance validation.
Action	Use instance validation during the schema update.
INOXDE7982	Attempted to add member of substitution group during schema update for doctype with open content
Explanation	You cannot add a member of a substitution group during a schema update for a doctype with open content without using instance validation.
Action	Use instance validation during the schema update.

INOXDE7988	Failed to lock schema document.
Explanation	A schema document could not be locked due to a parallel transaction.
Action	Check for parallel transaction using the same schema with a conflicting type of lock. Typically, commands modifying a schema require a write lock for the schema and will conflict with each other, or with other transactions having a read lock on the schema.
INOXDE7989	Cannot define schema in schemaless collection
Explanation	It is not allowed to define a schema if the collection is defined with schema use 'prohibited'.
Action	Use another collection - or just do not define schema at all. Schemaless collections (like ino:etc) allow documents to be stored without defining a schema. You may also change the collection for optional schema usage.
INOXDE7992	Index migration for doctype 'doctype' in collection 'collection' failed with error code errorCode
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXDE7993	Schema operation failed because the same request has doctype already in use
Explanation	Schemas cannot be modified or deleted from a server extension if the calling command has an affected doctype in use.
Action	Change your application.
INOXDE7996	Doctype requires xsi:type migration - schema update requires instance validation
Explanation	The given doctype contains documents with xsi:type attribute(s) that were stored in previous version of Tamino. As the processing of xsi:type was not complete in previous versions of Tamino up to version 4.2, explicit validation of the documents against the schema is required.
Action	Perform a schema update with instance validation (<code>_MODE=validate</code>). Depending on the type definitions being referenced by the xsi:type attribute, the original schema may need to be adapted, as the type being referenced by xsi:type must be validly derived from the default type of the respective element as given in the schema.

INOXDE7997	Missing 'type' attribute in definition of computed index.
Explanation	The <tsd:computed> elements must have a 'type' attribute if it is not a compound index.
Action	Fix the schema accordingly.
INOXDE7998	Found unexpected 'type' attribute in definition of computed index with multiple components.
Explanation	For a compound computed index, i.e. with multiple components, only the component definitions may have a 'type' attribute.
Action	Fix the schema accordingly.
INOXDE7999	Found component of a computed index which does not have a simple type.
Explanation	The component of a computed index must have a simple type.
Action	Fix the schema accordingly.
INOXDF7601	XML initialization: failed to define collection/doctype, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXDF7613	Unexpected error (rsp,line) occurred during op (parm).
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXDI7582	The path specified in the xpath attribute of a field element may not be empty or start with a slash
Explanation	mp-valid-field.3: The path specified in the xpath attribute of a field element may not be empty or start with a slash.
Action	Please change the schema and try to define it again.
INOXDI7608	Upgrade system collections
Explanation	The system collections need to be upgraded.
Action	No action required.

INOXDI7991	Indexes of doctype 'doctype' in collection 'collection' have been migrated successfully
Explanation	In the given doctype, all indexes marked for migration have been rebuilt successfully.
Action	No action required.
INOXDS7600	Define 'doctype' in collection 'collection'
Explanation	The given system doctype will be defined or upgraded.
Action	No action required.
INOXDS7602	Define collection 'collection'
Explanation	The given system collection will be defined or upgraded.
Action	No action required.
INOXDS7611	Define missing collection objects
Explanation	For all existing collections the respective objects are now being loaded.
Action	No action required.
INOXDW7678	Usage of a non-field element as element or attribute in schema definition
Explanation	Field is defined as phonetic, sub, super or hyper-descriptor in Adabas field definition.
Action	Check your schema definition.
INOXDW7990	Doctype 'doctype' in collection 'collection' requires index migration
Explanation	The referenced doctype contains nodes whose indexes should be newly created.
Action	Refer to the migration related topics in the Tamino documentation.
INOXDW7994	Multipath index 'label' in doctype 'doctype' in collection 'collection' is marked as not available
Explanation	A previous schema update or index repair option could not be finished successfully. The given multipath index is still marked as being not available, and cannot be used for the efficient evaluation of query results.
Action	Update the respective schema in Tamino. This will enforce a rebuild of the respective multipath index.

INOXDW7995	Doctype 'doctype' in collection 'collection' requires xsi:type migration
Explanation	The given doctype contains documents with xsi:type attribute(s) that were stored in a previous version of Tamino. As the processing of xsi:type was not complete in previous Tamino versions up to version 4.2, explicit validation of the documents against the schema is required.
Action	Perform a schema update with instance validation (_MODE=validate). Depending on the type definitions being referenced by the xsi:type attribute, the original schema may need to be adapted, as the type being referenced by xsi:type must be validly derived from the default type of the respective element as given in the schema.
INOXHA8259	Start writing XML dump of database, writing to file filename
Explanation	The server has encountered an error situation which causes a crash. In order to enable error analysis, the server writes XML status information to a file in the reserved location.
Action	Report the crash to your software supplier, together with the dump files in the reserved location.
INOXHE8152	Web server ws: specified node host unknown (DNS rsp: rsp).
Explanation	The given web server on the given node is defined as one of the web servers that are allowed to communicate with this Tamino database. Unfortunately the Tamino database is not able to resolve the specified node name.
Action	Check whether the node name is correct. If it is correct, check whether DNS lookups may fail due to network problems. In this case, use the IP address instead of the node name.
INOXHE8153	Insufficient system resources to create thread: thread 'name', error error returned by thread create function
Explanation	There are not enough system resources available to create a new thread.
Action	There are not enough system resources available to create a new thread. The reason is either that the system defined maximum for the number of threads per process is exceeded, or that there is not enough memory available to allocate the necessary thread resources.
INOXHE8201	Cannot connect to server on host host at port port. TCP error code rsp.
Explanation	The web server interface module was not able to connect to the Tamino server.
Action	Check if the Tamino server is active and accessible (e.g. using Telnet).

INOXHE8202	Tamino database unknown
Explanation	The web server interface module was not able to determine the network address (hostname and port number) of the Tamino database server.
Action	Check if the issued URL really points to the desired Tamino database server. If this is OK, check the configuration data of the web server interface module. If this is OK too, please contact your software supplier.
INOXHE8203	Database server and web server interface module not compatible
Explanation	The versions of the Tamino database server and the Tamino web server interface module are not compatible.
Action	Please use compatible versions of the Tamino database server and the Tamino web server interface module.
INOXHE8220	XML initialization:SXS initialization failed: sxsMsg
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHE8254	Failed to create the Software AG XTS Directory Server entries: why
Explanation	The server failed to create the necessary Software AG XTS Directory Server entries and the server startup failed. The reason for the failure is returned by the XTS layer.
Action	Please check that the service "Software AG XTS Directory Server" is running. If not, please start it. On Windows this can be done using the Control Panel. On UNIX please use the scripts provided (which are normally executed at system start). If the service was running when the error occurred, and the XTS message does not specify enough details to fix the problem, please contact your software supplier.
INOXHE8257	Conversion failed, output encoding enc, error code rsp
Explanation	The conversion into the desired document encoding failed.
Action	Check the desired encoding and correct it.
INOXHE8258	Unable to start request
Explanation	There is a resource shortage on the server.
Action	Increase number of XML work threads. If the problem persists, increase the number of data working threads also.

INOXHE8261	XML crash dump file filename could not be created due to operating system error system errno
Explanation	The XML crash dump file needed for error analysis could not be created due to the given reason.
Action	Please consult the manufacturer's manual.
INOXHE8270	XML internal error num: Session sess, Rsp rsp, time
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHE8278	Internal error
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXHE8282	Internal error
Explanation	Internal error.
Action	Please contact your software supplier.
INOXHE8283	Internal error
Explanation	Internal error.
Action	Please contact your software supplier.
INOXHE8284	Internal error
Explanation	Internal error.
Action	Please contact your software supplier.
INOXHE8285	Invalid Session ID
Explanation	The specified session does not exist or it is currently executing a different request.
Action	Specify a valid Session ID.
INOXHE8286	Internal error
Explanation	Internal error.
Action	Please contact your software supplier.

INOXHE8287 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8288 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8289 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8290 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8291 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8292 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8293 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8294 **Internal error**
Explanation Internal error.
Action Please contact your software supplier.

INOXHE8295	Internal error
Explanation	Internal error.
Action	Please contact your software supplier.
INOXHE8296	Internal error
Explanation	Internal error.
Action	Please contact your software supplier.
INOXHE8297	Error occurred in communication with client
Explanation	A communication problem occurred when receiving a request or sending a response to the client.
Action	Please check the web server log files or network configuration for possible reasons.
INOXHE8298	Internal error
Explanation	Internal error.
Action	Please contact your software supplier.
INOXHE8299	Internal error
Explanation	Internal error.
Action	Please contact your software supplier.
INOXHF8155	Communication method 'SSL' requires a certificate
Explanation	The server property 'communication method' is set to 'SSL', but the server property 'SSL certificate file' is not set. A certificate is mandatory for encrypted communication.
Action	Specify the location of the certificate that the server should use.
INOXHF8158	Set version failed. Reason: reason. Internal response d.
Explanation	An error occurred during migration.
Action	Please contact your software supplier and provide the server startup logfile.
INOXHF8159	Exception d occurred during server startup: msg
Explanation	The server could not be started.
Action	Please contact your software supplier.

INOXHF8160	Communication method 'SSL' requires a private key
Explanation	The server property 'communication method' is set to 'SSL', but the server property 'SSL key file' is not set. A private key is mandatory for encrypted communication.
Action	Specify the location of the private key that the server should use.
INOXHF8200	XML thread initialization failed
Explanation	The initialization of X-Machine failed with the mentioned response code. This is an internal error.
Action	Please contact your software supplier.
INOXHF8205	XML thread initialization: data map initialization failed, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8206	XML thread initialization: define of ino:collection failed, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8207	XML thread initialization: check of ino:collection failed, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8208	XML thread initialization: check of security collection failed, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8209	XML thread initialization: insert security collection failed, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8210	XML thread initialization: insert vocabulary collection failed, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.

INOXHF8211	XML thread initialization: check of vocabulary collection failed, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8212	XML thread initialization: security initialization failed, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8213	XML thread initialization: vocabulary initialization failed, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8214	XML thread initialization: commit failed, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8215	XML thread initialization: rollback failed, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8216	XML thread initialization: Memory allocation failed
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8217	XML work thread thid abended
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8218	XML receive thread thid abended
Explanation	This is an internal error.
Action	Please contact your software supplier.

INOXHF8219	XML listen thread accept failed, rsp: tprsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8221	TCP/IP select failed, rsp: tprsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8223	XML connection initialization failed (error error number)
Explanation	The initialization of the XML communication did not work as expected. The server could not be started.
Action	Repeat the action. If it still fails, contact your software supplier.
INOXHF8224	Unexpected receive count: cnt
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8225	XML initialization: data map initialization failed
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8226	XML initialization:security initialization failed
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8227	XML initialization: internal error
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8228	XML thread initialization: creation of anonymous session failed
Explanation	This is an internal error.
Action	Please contact your software supplier.

INOXHF8229	XML thread initialization: server extension thread initialization failed, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8230	XML initialization:TCP/IP startup failed
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8233	XML initialization: gethostname failed
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8234	XML initialization: gethostbyname failed, host: host, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8235	XML initialization: invalid port number "port" found for web server webserver
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8237	XTS Register Server failed for XML: xtmsg
Explanation	The registration of the Tamino XML server via XTS failed.
Action	Check and correct the XTS configuration and/or directory server.
INOXHF8239	XML initialization: failed to define collection/doctype, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8240	XML thread thread_number has exited due to communication error error_number (text)
Explanation	Either adding the service to the directory server has failed, or registering with the directory server has failed.
Action	Check the XTS configuration.

INOXHF8241	XML thread thread_number has exited due to communication error error_number (text)
Explanation	Either adding the service to the directory has failed, or the registration with the directory server failed.
Action	Check the XTS configuration.
INOXHF8243	XML processing not initialized
Explanation	The initialization of the XML processing did not work as expected. The server could not be started.
Action	Repeat the action. If it still fails, contact your support center.
INOXHF8244	Binding to TCP/IP socket socket number (port type port) has failed
Explanation	The server could not connect to the specified socket. Maybe it is in use.
Action	Check the reason for the error. If the error persists, choose another port number.
INOXHF8255	XML initialization: invalid IP address "ipaddr" found for web server webserver
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8256	XML initialization: Memory allocation failed
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8262	XML thread initialization: initialization of tokenizer failed, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8263	XML initialization: No license for tok tokenizer
Explanation	No valid license found for the default tokenizer.
Action	Please check the setting of database parameter "default tokenizer" and the used license file. If the problem persists, please contact your software supplier.

INOXHF8264	XML thread initialization: Create failed for obj
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8266	Invalid default tokenizer: tok
Explanation	The value of the parameter "default tokenizer" is invalid.
Action	Use a valid value.
INOXHF8269	XML thread initialization: data map initialization for server extensions failed, rsp: rsp
Explanation	Internal error: Data map entries needed by X-Tension could not be initialized.
Action	Please contact your software supplier.
INOXHF8271	XML initialization: invalid/unsupported default encoding 'defEnc'
Explanation	An invalid/unsupported MIME or IANA encoding name is specified for the 'default encoding' database parameter.
Action	Please check the setting of the 'default encoding' database parameter. If the problem persists, please contact your software supplier.
INOXHF8272	XML initialization: Word stemming algorithm initialization failed, rsp: rsp
Explanation	This is an internal error.
Action	Please contact your software supplier.
INOXHF8273	Failed to attach definition of system collections
Explanation	The shared library containing in particular the meta schema could not be loaded.
Action	Check your installation.
INOXHF8279	Necessary allocation of static port failed
Explanation	The allocation of a necessary static port failed.
Action	Please contact your software supplier.

INOXHI8151	Communication method: s
Explanation	The given communication method will be used for the server that is starting. See the user documentation for the server property "Communication Method" for more information.
Action	No action required.
INOXHI8156	TCP/IP send failed, rsp: rsp, time
Explanation	The Tamino server failed to respond to a request. The communication method used was TCP/IP. The reported response code is the error which the Tamino server got from TCP/IP "send".
Action	Please check the state of TCP/IP.
INOXHI8157	XTS send failed, rsp: rsp, time
Explanation	The Tamino server failed to respond to a request. The communication method used was XTS. The reported response code is the error which the Tamino server got from XTS "SendMessageByRT".
Action	Please check the state of XTS.
INOXHI8222	TCP/IP receive failed, rsp: rsp
Explanation	Error in the TCP/IP stack.
Action	Please check the state of TCP/IP.
INOXHI8242	Define doctype in collection collection
Explanation	A system doctype with given name is being created in the given collection.
Action	No action required
INOXHI8247	Dynamic what worker thread created
Explanation	The server increased the number of worker threads to avoid a possible deadlock.
Action	No action required.
INOXHI8251	Overwriting Software AG XTS Directory Server entries
Explanation	The Software AG XTS Directory Server entries already existed. They are overwritten.
Action	No action required.

INOXHI8252	type - 'dsentry'
Explanation	This is an informational message.
Action	No action required.
INOXHI8253	Use switch parameter 'param' to force server registration
Explanation	This is an informational message.
Action	No action required.
INOXHI8260	XML crash dump of database finished
Explanation	The XML crash dump is complete.
Action	No action required.
INOXHI8265	Default tokenizer 'tok'
Explanation	This is an informational message.
Action	No action required.
INOXHI8267	User dictionary 'udict'
Explanation	This is an informational message.
Action	No action required.
INOXHI8274	Word stemming index successfully created
Explanation	The database parameter 'stemming index' is enabled and the stemming index for documents with text indices is created.
Action	No action required.
INOXHI8275	Word stemming index successfully dropped
Explanation	The database parameter 'stemming index' is disabled and the stemming index for documents with text indices is removed.
Action	No action required.
INOXHI8276	Web server configuration updated
Explanation	The web server configuration was changed and is now updated in the server.
Action	No action required.

INOXHI8277	Internal error
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXHR8245	Initializing XML processing
Explanation	This is an informational message.
Action	No action required.
INOXHR8246	Starting XML threads
Explanation	This is an informational message.
Action	No action required.
INOXHV8250	Server is already registered with the Software AG XTS Directory Server
Explanation	When the Tamino server starts it registers with the Software AG XTS Directory Server. It is possible that entries for the server are already present (server already started somewhere else or previous server session failed). If this message comes as a warning message, the entry found exactly matches the one that should be entered. If this message comes as an error message, the entry found did not match the entry that the server wanted to add.
Action	If this message comes as a warning message no action is required. If this message comes as an error message the Software AG XTS Directory Server entry found for the server should be checked and, if no longer necessary, the next server start should be done with the parameter for overwriting the Software AG XTS Directory Server entry activated.
INOXHW8154	TCP connection timed out
Explanation	A violation of Tamino Network Protocol was detected.
Action	Check the client application / network.
INOXHW8161	HTTP connection timed out
Explanation	A violation of Tamino Network Protocol was detected.
Action	Check the client application / network.

INOXHW8204	XML thread initialization: data map initialization for server extension failed, rsp: rsp
Explanation	This is an internal error. Tamino will work as expected unless server extensions are used.
Action	Please contact your software supplier.
INOXHW8231	No license for Tamino XML
Explanation	A special license must be bought to use the Tamino XML feature.
Action	Buy a license for Tamino XML.
INOXHW8232	Only numLic concurrent XML sessions licensed
Explanation	The server parameter "XML maximum sessions" contains a value that is larger than the number of concurrent sessions that is included in the used license.
	Only the number of sessions that is covered by the license used is allowed.
Action	Buy an enhanced license.
INOXHW8236	XML connection refused; current number of connections: totCon
Explanation	Tamino is not able to accept another XML request. The connection attempt is refused.
Action	Increase the number of XML work threads.
INOXHW8238	Unable to free storage.
Explanation	This is an internal error. X-Machine is not able to free all storage during shutdown.
Action	Please contact your software supplier.
INOXHW8248	Maximum number of dynamic what worker threads reached
Explanation	The maximum number of dynamic worker threads is reached. No further threads are created.
Action	The number of worker threads should be increased and the server should be restarted.
INOXHW8249	Creation of dynamic what worker thread failed with response err
Explanation	The server failed to increase the number of worker threads.
Action	No action required.

INOXHW8268	Invalid entry in user dictionary 'tok'
Explanation	The user dictionary contains an invalid entry. It is ignored.
Action	Check the user dictionary contents.
INOXIE8300	No matching document found
Explanation	The specified query did not find any matching documents.
Action	None. This is only an informational error message.
INOXIE8301	Illegal document ID specified
Explanation	The specified document ID is illegal.
Action	Supply a legal document ID.
INOXIE8303	Deleting a document is forbidden
Explanation	A <code>_DELETE</code> operation was issued against a doctype where <code>DELETE</code> is missing in the doctype options as supplied in the schema definition.
Action	Change the doctype options accordingly.
INOXIE8304	Reading a document is forbidden
Explanation	An <code>_XQL</code> operation was issued against a doctype where <code>READ</code> is missing in the doctype options as supplied in the schema definition.
Action	Change the doctype options accordingly.
INOXIE8305	Invalid cursor handle
Explanation	The supplied cursor handle is invalid: either it was never created during the current session, or the corresponding cursor was closed in the meantime.
Action	Supply a correct cursor handle.
INOXIE8306	Invalid cursor position
Explanation	The supplied cursor position is invalid: there is no document in the cursor's result set corresponding to the position. In particular, this error will be returned when positioning beyond the end of the cursor result set.
Action	Supply a correct cursor position.

INOXIE8307	Trying to position backwards in a non-scrollable cursor
Explanation	The position supplied with the "fetch cursor" request would result in a backward positioning which is not possible for a non-scrollable cursor.
Action	Supply a correct cursor position.
INOXIE8309	Duplicate in sort key
Explanation	The system cannot handle sort key values which consist of more than a single node.
Action	Change your query expression so that no multiple node is to be sorted.
INOXIE8310	Invalid parameter detected
Explanation	Either the function is unknown or the number of parameters is invalid or the parameter values are invalid.
Action	Please check the function name, the number of parameters and the parameter values and correct them.
INOXIE8312	Version fromVersion is incompatible with Version toVersion
Explanation	The current version of the database is not compatible with the selected version.
Action	Data must be unloaded and loaded into a new database manually.
INOXIE8313	Internal communication error
Explanation	Database cannot be converted because of an internal error.
Action	Check that the database is running.
INOXIE8314	Database's compatibility level is no longer supported
Explanation	Migration from and to this compatibility level is not possible because this compatibility level is no longer supported.
Action	Data must be unloaded and loaded into a new database manually.
INOXIE8315	Duplicate docnames found in ino:collection = 'collection' ino:doctype='doctype'
Explanation	The upgrade has been rejected because because of duplicate docnames.
Action	Use the administration command ino:AdminDocname("check-unique") to get a list of duplicate docnames. Please delete the duplicate docnames and call the administration command ino:AdminDocname("set-unique").

INOXIE8316	Attempted to delete a partial document
Explanation	With _delete, it is only possible to delete complete XML documents.
Action	Supply a query that selects complete documents.
INOXIE8319	Internal error occurred during query processing: unknown request
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXIE8320	Error parsing the XQL query
Explanation	One or more errors occurred while parsing the XQL query.
Action	Correct query appropriately and re-issue
INOXIE8321	Missing end quotation character
Explanation	The end quotation character of a literal was not found. It could also be that the start and end quotation characters do not match.
Action	Correct query appropriately and re-issue.
INOXIE8322	Named axes are not supported
Explanation	The specification of named axes is not supported in Tamino.
Action	No action possible.
INOXIE8331	Failed to set the server parameter
Explanation	Failed to set the server parameter.
Action	Please contact your software supplier.
INOXIE8332	The old server parameter could not be deleted
Explanation	The old server parameter could not be deleted.
Action	Please contact your software supplier.
INOXIE8333	An old TSD2 collection could not be deleted
Explanation	An old TSD2 collection could not be deleted.
Action	Please contact your software supplier.

INOXIE8334	The database contains data which uses lite mapping
Explanation	The version to which the database should be upgraded does not support lite mapping.
Action	Please delete the data which uses lite mapping and start the upgrade again.
INOXIE8335	Upgrade of metaschema failed with following response code RESPONSE.
Explanation	The upgrade of the metaschema which was performed during upgrade of the database has failed with the specified response code.
Action	Please contact your software supplier.
INOXIE8336	Upgrade is not supported
Explanation	Upgrade is not supported.
Action	Select another version to upgrade the database.
INOXIE8337	Downgrade is not supported
Explanation	Downgrade to an older Tamino version is not supported.
Action	Please contact your software supplier.
INOXIE8338	Data format 'VERSION' found in collection 'COLLECTION' doctype 'DOCTYPE'.
Explanation	The data format found in the user collection is no longer supported.
Action	Please clean up the user collection.
INOXIE8339	Unknown function
Explanation	The provided function name is unknown.
Action	Check if you provided the correct function name and try again.
INOXIE8340	Truncated index detected
Explanation	An index containing truncated entries was detected at query execution time, though the Data Map had no information about truncation available at compile time. This may occur for an index that has been migrated from Tamino version 4.1.4. As a side effect of the failing query, the index has been marked as truncated in the Data Map.
Action	Repeat the query.

INOXIE8341	Internal error
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXIE8342	Memory allocation failed
Explanation	There was not enough main memory available to perform the request.
Action	Possibly the machine is overloaded. Try again later.
INOXIE8343	Postprocessing not supported for non-XML text search
Explanation	A query that contains a text search operator can be executed on a non-XML doctype only if a text index has been defined for that doctype and the query does not require postprocessing.
Action	Modify your schema definition to contain a non-XML text index or change query to avoid postprocessing.
INOXIE8344	Internal error
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXIE8345	Illegal parent operator follows sort operator
Explanation	A query contains a parent operator which might be applied to a node which serves as input for a sort operator. This is not allowed.
Action	Please change your query so that no parent operator can be applied to a sort input node.
INOXIE8346	Malformed proximity expression
Explanation	A subexpression of the query uses either the "adj" or the "near" operator, but there is no corresponding "~=" operator.
Action	Correct the query.
INOXIE8347	Query not supported
Explanation	The specified query is not supported.
Action	Change the query.

INOXIE8348	Wrong arguments for function
Explanation	The function cannot be applied on the current parm settings, i.e. number or type of arguments that a function is called with is not as expected by the function.
Action	Check either the XPath specification for the proper usage of XPath's built in functions or check the documentation for server extension functions.
INOXIE8349	Maximum word length exceeded
Explanation	Text searches are restricted to a maximum word length of 64 characters.
Action	Reduce the length of the search pattern inside the query.
INOXIE8350	No whitespace search is supported with ~=
Explanation	Whitespaces are ignored by a "~=" search, so searching for a whitespace is not possible.
Action	Use the "=" operator to find whitespaces.
INOXIE8351	Wrong direction of result type
Explanation	The result type must be output.
Action	Uninstall the function, change the signature of the external function, install the function again.
INOXIE8352	Operator used outside a document
Explanation	Some operators can only be used inside a document e.g. before/after.
Action	Do not use the operator outside of a document context.
INOXIE8353	Invalid invocation of ino:fullscan
Explanation	The ino:fullscan function can be used only on query level, it cannot be applied to subexpressions.
Action	Correct ino:fullscan invocation.
INOXIE8354	Invalid invocation of ino:explain
Explanation	The ino:explain function can be used only on query level, it can not be applied to subexpressions.
Action	Correct ino:explain invocation.

INOXIE8355	Too many inter-document sort operators
Explanation	The system can process only a single inter-document sort operator. Please note that a "orderby" applied to a root node is also an inter-document sort operator.
Action	Please change your query.
INOXIE8356	Illegal inter-document sort operators
Explanation	Within a query an inter-document sort operator must not follow an intra-document sort operator.
Action	Please change your query.
INOXIE8357	Internal error
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXIE8358	Internal error
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXIE8359	Internal error
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXIE8360	Nodeset is empty
Explanation	The current-node (.) or parent (..) operator was applied upon an empty nodeset during query evaluation.
Action	A subquery executed prior to the current-node or parent operation yielded an empty result.
INOXIE8361	Invalid type occurred when executing query
Explanation	Some query operations can only be applied upon objects of a specific type, e.g. current-node (.) or parent (..) only make sense when working upon nodes. This error may also occur when calling XPath functions upon a set of arguments they cannot be applied upon.
Action	Check whether . (=current node) or .. (= parent) are used in connection with nodes, and that an XPath function's usage corresponds to its type.

INOXIE8362	Internal Error : Invalid Node
Explanation	An invalid XML node was encountered during the evaluation of an XPath function.
Action	Please contact your software supplier.
INOXIE8364	Conversion failed
Explanation	In order to execute a query an invalid conversion was attempted. This happens e.g. if a numerical operation is applied upon data that cannot be converted to a number. This error occurs also if an operator requires two operands of the same type (e.g. between) and the operands are of different types.
Action	Check the operand's types.
INOXIE8366	Wrong arguments for function
Explanation	The function cannot be applied on the current parm settings, i.e. number or type of arguments that a function is called with is not as expected by the function.
Action	Check either the XPath specification for the proper usage of XPath's built in functions or check the documentation for server extension functions.
INOXIE8367	Internal error : Missing root node
Explanation	The query postprocessor encountered a missing node in the XPath parsing tree when evaluating an XPath expression.
Action	Please contact your software supplier.
INOXIE8368	ICU collator definition failed
Explanation	An error was received while opening an ICU collator.
Action	Please contact your software supplier.
INOXIE8369	Right side of ~= must be a single string
Explanation	The match operand requires an operand that evaluates to string on its right side.
Action	Check whether your idea of what match does is correct. It typically looks like list-of-nodes ~= 'pattern' or list-of-nodes ~= 'word' . If the right side of your match is detected dynamically from Tamino data, it does not evaluate to a string as you expected. If the right side of your match is given literally in the query, it might help to add quotes.

INOXIE8371	Invalid comparison operator
Explanation	Within 'adjacent' or 'near' statements, currently only the match comparison operator is allowed.
Action	Replace an equal by a match and a not-equal by a match and the XPath function 'not()'.
INOXIE8372	Too many match tokens
Explanation	The right side of a ~= contains a string that gets tokenized in order to check the expression on the left side for the occurrence of these tokens in the given sequence. The tokenization must not lead to more than ten tokens.
Action	Shorten the pattern to avoid tokenization into more than ten tokens.
INOXIE8374	Invalid Match Pattern
Explanation	The string provided as the right side of a match (~=) must contain at least one character that is not a separation character, i.e. quote or comma. The string may contain wildcards (*), but only in the forms *x, x*, x*x, or *x*.
Action	Correct the pattern.
INOXIE8375	Sortkey too long
Explanation	The internally generated sort key is too long.
Action	Reduce the number of sort criteria.
INOXIE8376	Duplicate in sort key
Explanation	The system cannot handle sort key values which consist of more than a single node.
Action	Please try to fix your data or your query.
INOXIE8378	Server extension returned binary data without setting media type
Explanation	The media type must be defined when a server extension returns binary data.
Action	Use the method SxsSetProperty() with the property of SX_PROPERTY_RSP_MEDIATYPE to define the media type of the binary data.
INOXIE8379	Internal error occurred during query processing: unknown request
Explanation	An internal error has occurred.
Action	Please contact your software supplier.

INOXII8302	Overflow during sorting
Explanation	internal error
Action	Please contact your software supplier.
INOXII8311	Version fromVersion is compatible with Version toVersion
Explanation	The current version of the database is compatible with the selected version.
Action	None
INOXII8317	Internal error during sorting
Explanation	internal error
Action	Please contact your software supplier.
INOXII8318	Locking conflict
Explanation	internal error
Action	Please contact your software supplier.
INOXII8323	Recreation of all indices started in collection COLLECTION, doctype DOCTYPE
Explanation	The administrative command ino:RecreateIndex was issued.
Action	Be aware that the collection is not accessible until index recreation is completed.
INOXII8324	Recreation of all indices in collection COLLECTION, doctype DOCTYPE terminated with code CODE
Explanation	The administrative command ino:RecreateIndex terminated.
Action	Be aware that if the given return code is not 0, the index recreation has been rolled back.
INOXII8325	Recreation of all text indices started in collection COLLECTION, doctype DOCTYPE
Explanation	The administrative command ino:RecreateTextIndex was issued.
Action	Be aware that access to the collection is constricted until the operation is completed.
INOXII8326	Recreation of all text indices in collection COLLECTION, doctype DOCTYPE terminated successfully
Explanation	The administrative command ino:RecreateTextIndex completed.
Action	The collection is fully usable again.

INOXII8327	Recreation of all text indices in collection COLLECTION, doctype DOCTYPE terminated with error CODE
Explanation	The administrative command ino:RecreateTextIndex aborted due to the stated error code.
Action	Repair the indices via the administrative command ino:RepairIndex().
INOXII8328	Repair indices started in collection COLLECTION, doctype DOCTYPE, mode MODE
Explanation	The administrative command ino:RepairIndex was issued.
Action	Be aware that access to the collection is constricted until the operation is completed.
INOXII8329	Repair indices in collection COLLECTION, doctype DOCTYPE, mode MODE terminated successfully
Explanation	The administrative command ino:RepairIndex completed successfully.
Action	Note that if the mode was "drop", the indices have been dropped from the schema.
INOXII8330	Repair indices in collection COLLECTION, doctype DOCTYPE, mode MODE terminated with error CODE
Explanation	The administrative command ino:RepairIndex aborted due to the given error.
Action	Correct the problem if possible and repeat the command.
INOXIW8373	The id() function is not supported
Explanation	XPath describes the result of the id() function as being the node-set containing the elements in the same document as the context node that have a unique ID equal to any of the tokens in the id() function's argument list (see XPath 4.1). As specified in XPath, 5.2.1, a unique ID is the value of the attribute that is declared in the DTD as type ID. Since Tamino currently offers no means to declare attributes as type ID, applying the id() function makes no sense, its result will always be the empty node set.
Action	If some attribute 'att1' has the semantics of an ID, retrieving the node for which this attribute is set to a certain value, e.g. 'val1', is achieved via <code>//*[@att1="val1"]</code> .
INOXIW8399	The required function has not been completely executed
Explanation	See details in the warning line accompanying this message. Possible reasons for this warning are: a sort operation was performed based on an index, and that index contains truncated values. The result is sorted according to the truncated values, and not according to the real values.
Action	No action required, this is a warning only.

INOXME8501	Memory allocation failed
Explanation	Allocation of virtual memory failed.
Action	Either extend the amount of memory resources available for Tamino on your system or reduce resource consumption of Tamino, e.g. by using a smaller buffer pool.
INOXME8502	Internal error: DBMS environment not found
Explanation	The DBMS environment could not be found for X-Node - this is an internal error.
Action	Please contact your software supplier.
INOXME8503	Invalid or unknown encoding found in input document
Explanation	The encoding of the input document could not be recognized.
Action	Check your input document.
INOXME8504	XML maximum request duration exceeded
Explanation	The request was cancelled because the maximum request duration was exceeded.
Action	Either improve the request performance by tuning the database, or increase the value of the "XML maximum request duration" server parameter.
INOXME8505	ODBC error occurred
Explanation	While issuing a command via ODBC to the SQL system an error occurred.
Action	The text of the external error is provided in the extended message.
INOXME8506	Adabas error occurred
Explanation	An error occurred when accessing an Adabas database via X-Node.
Action	Check the Adabas documentation for the reason for the reported error code.
INOXME8507	Maximum parallel databases for session reached
Explanation	The number of parallel databases allowed for one session has been reached.
Action	No action required.
INOXME8508	X-Node licensing error, insufficient rights
Explanation	An attempt was made to access an X-Node datasource or an Adabas version that has not been licensed.
Action	Check that all datasources defined in the schema are correct, or upgrade the X-Node license.

INOXME8509	X-Node datasource mismatch
Explanation	The datasource DBMS name given (implicitly or explicitly) in the schema does not match that of the DBMS vendor to which this datasource has attempted to connect.
Action	The DBMS name must be the same at execution time as it was at schema creation time.
INOXME8510	Request has been cancelled
Explanation	The request has been cancelled by the operator or accessor.
Action	No action required.
INOXME8511	Internal maximum for parallel ODBC access reached
Explanation	Within one transaction, Tamino keeps track of parallel ODBC access. An internal list reached its maximum.
Action	No action required.
INOXME8512	Invalid request ID
Explanation	The given ID is invalid either because the respective request is already terminated or because it is invalid as an accessor-provided unique identifier.
Action	No action required, if the request is already terminated. Otherwise the request ID cannot be used within <code>_admin=ino:Accessor("cancelRequest",...)</code> .
INOXME8513	Cannot create unique text index
Explanation	A unique index cannot be set because duplicate entries are stored in the translated word table.
Action	Please contact your software supplier.
INOXME8514	X-Node SQL column not found or authorization error
Explanation	The specified column was not found in the SQL table or you are not authorized to access the column/table.
Action	Correct the schema.
INOXME8515	X-Node SQL table not found or authorization error
Explanation	The error may occur because: 1. the specified SQL table/schema was not found OR 2. you are not authorized to access the table.
Action	Correct the schema.

INOXME8516	Internal error: cannot lock collection
Explanation	Migration attempted to lock a collection for which it is not possible.
Action	Please contact your software supplier.
INOXME8517	Unlock of collection failed
Explanation	It was not possible to unlock the specified collection.
Action	Please contact your software supplier.
INOXME8518	Unlock of collection failed because the lock is in an incorrect state
Explanation	It was not possible to unlock the specified collection because the lock is in an incorrect state.
Action	Please contact your software supplier.
INOXME8519	Cannot cancel a mass load/unload as a session user
Explanation	Cancelling of a mass load/unload in a session is not possible.
Action	Issue the administration command in an anonymous session.
INOXME8520	Error writing to temporary file during data load
Explanation	An error occurred while writing to a temporary file during a data load request.
Action	Check that temporary directory (\$SAGTMP or \$TMP) is writable and that disk space is available.
INOXME8521	Invalid or unsupported datastore format detected during data load
Explanation	An internal error occurred during data load.
Action	Please contact your software supplier.
INOXME8522	Unsupported datastore descriptor type detected during data load
Explanation	An internal error occurred while data was being loaded.
Action	Please contact your software supplier.
INOXME8523	Unsupported datastore request detected during data load
Explanation	An internal error occurred while data was being loaded.
Action	Please contact your software supplier.

INOXME8524	Value exceeding maximum length detected during data load
Explanation	An internal error occurred while data was being loaded.
Action	Please contact your software supplier.
INOXME8525	Internal error detected in data load module
Explanation	An internal error occurred while data was being loaded.
Action	Please contact your software supplier.
INOXME8527	Data loading/unloading for doctype not supported
Explanation	For data loading: - doctypes of map-type NonXML or Lite are not supported. - doctypes created in Tamino version prior to v2.3 are not supported. For data unloading: - doc-types of map-type NonXML are not supported
Action	Either migrate your doctype to v2.3 or later or use the XML loaders.
INOXME8528	Data loading aborted; cannot create temporary files
Explanation	The data loader was unable to create temporary files.
Action	Using the Tamino Manager or the batch utility "argbatch", check that the settings for the temporary location are correct and that there is space available.
INOXME8529	Data loading into multiple doctypes not supported
Explanation	Data loading is only possible into the collection/doctype given when the data loader is started.
Action	Remove documents from the input file that do not belong to the doctype specified at the start-up of the XML data loader.
INOXME8531	Data load rejected document
Explanation	An error was found while processing the document during a data load operation.
Action	Correct and restart the data loader.
INOXME8536	XML data load recovery of doctype doctype in collection collection was unsuccessful
Explanation	During autorestart, it was detected that a XML data load operation was active in the previous Tamino server session. This message provides information that Tamino could not restore the doctype to the state before the XML data load operation was initiated.
Action	Perform a restore/regenerate of the Tamino database to get it into a consistent state.

INOXME8539	XML data loading failed
Explanation	An XML data load operation was aborted or stopped.
Action	Depending on the reason for the failure, correct and re-process.
INOXME8540	Data loading aborted with rejects
Explanation	Data loading has aborted because a reject was found and the norejects option was chosen.
Action	Either correct the rejected document or load without setting the norejects option.
INOXME8543	Internal error - unexpected response occurred in call to function function, function gave response code(s) codes
Explanation	An internal error has occurred.
Action	Please contact your software supplier with the exact message (the function and codes are important).
INOXME8544	Query using "mapping-type=object" cannot be evaluated
Explanation	The query cannot be evaluated because "mapping-type=object" is involved and the post-processor is needed, or because the "mapping-type=object" node is used within a filter.
Action	Supply a correct query.
INOXME8546	Feature not implemented
Explanation	You attempted to use a feature which is not available in the current environment.
Action	Please contact your software supplier.
INOXME8547	Invalid syntax of _XQL command inside _HTMLREQ
Explanation	An error occurred when converting an _HTMLREQ=_XQL request to an _XQL request.
Action	Check the appropriate documentation.
INOXME8548	Invalid syntax of _PROCESS command inside _HTMLREQ
Explanation	An error occurred when converting an _HTMLREQ=_PROCESS request to a _PROCESS request.
Action	Check the appropriate documentation.

INOXME8549	Doctype not found
Explanation	The doctype indicated in the ino:messageline could not be found during an _UNDEFINE request.
Action	Check the specified name.
INOXME8551	Invalid doctype
Explanation	Storing or deleting documents in the collection "ino:collection" is not permitted.
Action	Check the collection name specified in the request.
INOXME8552	Not a valid request
Explanation	The request has been rejected due to invalid or missing parameters.
Action	Check the request parameters using supplementary error diagnostics in other messages.
INOXME8554	No message received
Explanation	The request did not specify any supported operation or command.
Action	Check the parameters of the request.
INOXME8555	Session error occurred
Explanation	An error occurred when attempting to establish a session context.
Action	Check the supplementary diagnostic message for a detailed explanation.
INOXME8557	Request rejected because a deprecated feature is used
Explanation	The used feature will not be supported in the next version.
Action	Change the server parameter to allow and log deprecated features.
INOXME8558	Error during commit in user transaction
Explanation	A user transaction received an error during commit processing.
Action	The error has to be handled in your application.
INOXME8559	Error during rollback of user transaction
Explanation	A user transaction has been rolled back due to an error. However, the indicated error occurred.
Action	Please contact your system administrator.

INOXME8560	Failed to allocate SMP key
Explanation	An internal error occurred when attempting to allocate a key for thread local storage.
Action	Please contact your system administrator.
INOXME8561	Failed to deallocate SMP key
Explanation	An internal error occurred when attempting to release a key for thread local storage.
Action	Please contact your system administrator.
INOXME8562	Invalid handle
Explanation	Internal error: an invalid handle was passed to an internal interface.
Action	Please contact your system administrator.
INOXME8563	Invalid parameter
Explanation	Internal error: an invalid parameter was passed to an internal interface.
Action	Please contact your system administrator.
INOXME8564	Illegal load factor
Explanation	An internal error occurred when creating a hash map.
Action	Please contact your system administrator.
INOXME8565	Illegal initial capacity
Explanation	An internal error occurred when creating a hash map.
Action	Please contact your system administrator.
INOXME8566	Duplicate key
Explanation	An attempt was made to store the same key twice in a hash map.
Action	Please contact your system administrator.
INOXME8570	Locking failed during data load operation
Explanation	The specified collection or doctype could not be locked.
Action	Check the parameters of the data load request.

INOXME8596	Internal error in locking
Explanation	An unexpected server status caused a lock operation failure.
Action	Please contact your software supplier.
INOXME8598	Access violation
Explanation	The request was rejected due to insufficient access permissions.
Action	Check if the request was as intended and if so, try to get the required access privileges from the system administrator.
INOXME8599	Internal error
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXMF8530	Internal error occurred during data loading
Explanation	An internal error was detected while data was being loaded.
Action	Please contact your software supplier.
INOXMI8532	XML data load recovery initiated
Explanation	During autorestart, it was detected that a XML data load operation was active in the previous Tamino server session. This message defines the start of recovery handling for cleaning up anything that was left over after the data load operation.
Action	No action required.
INOXMI8533	XML data load recovery completed
Explanation	During autorestart, it was detected that a XML data load operation was active in the previous Tamino server session. This message defines the completion of recovery handling for cleaning up anything that was left over after the data load operation.
Action	No action required.
INOXMI8534	XML data load recovery initiated for doctype doctype in collection collection
Explanation	During autorestart, it was detected that a XML data load operation was active in the previous Tamino server session. This message provides information about which doctypes are being recovered.
Action	No action required.

INOXMI8535	XML data load recovery of doctype doctype in collection collection completed successfully
Explanation	During autorestart, it was detected that a XML data load operation was active in the previous Tamino server session. This message provides information that Tamino has successfully restored the doctype to the state before the XML data load operation was initiated.
Action	No action required.
INOXMI8537	XML data loading initiated for doctype doctype of collection collection
Explanation	This is an information message to indicate the start of XML data load operation.
Action	No action required.
INOXMI8538	XML data loading completed, number of documents processed docsproc, loaded docsload, rejected docsrejected
Explanation	This is an information message to indicate the end of an XML data load operation.
Action	Depending on if there were documents rejected, these may need to be investigated and re-processed.
INOXMV8550	Deprecated feature used: feature
Explanation	The request uses a feature which is planned to be removed in the next product version.
Action	Do not use the deprecated feature.
INOXMW8526	Failed to write XML request log to path
Explanation	An error occurred when attempting to write the XML request log to given location.
Action	Check the location for possible reasons such as: a non-existing XML request log folder may have been specified, the directory cannot be accessed, or the disk is full.
INOXMW8545	ino:docname uniqueness is not removed in downgrade
Explanation	The downgrade does not allow the uniqueness of ino:docnames to be removed.
Action	No action required.
INOXMW8571	Request logging was switched off dynamically due to IO errors
Explanation	Probably the disk is full.
Action	Check the disk. Except for request logging, the Tamino server continues operation.

INOXPE8700	Internal error: inconsistent document retrieval
Explanation	The database storage of the retrieved document is inconsistent.
Action	Please contact your software supplier.
INOXPE8701	Memory allocation failed
Explanation	There was not enough main memory available to perform the request.
Action	Possibly the machine is overloaded. Try again later.
INOXPE8702	Invalid document prolog
Explanation	Invalid document prolog found in the file to be loaded.
Action	Please correct the document prolog.
INOXPE8703	Invalid document declaration or more than one declaration found in the file to be loaded
Explanation	Invalid document declaration or more than one declaration found in the file to be loaded.
Action	Correct the document declaration or remove all declarations except for the first.
INOXPE8704	Unknown encoding found
Explanation	Unknown encoding found.
Action	Please correct the document instance.
INOXPE8705	Incompatible encoding found
Explanation	The given encoding isn't supported yet.
Action	Please use another encoding.
INOXPE8706	Entity found twice
Explanation	An entity with same name was found twice.
Action	Please remove one of these entities.
INOXPE8707	Wrong entity definition
Explanation	The definition of an entity isn't correct.
Action	Please correct the entity definition.

INOXPE8708	Document without content
Explanation	An empty document cannot be loaded.
Action	Please provide the document with contents.
INOXPE8709	Encoding not supported
Explanation	The given encoding isn't supported yet.
Action	Please use another encoding.
INOXPE8710	Invalid token found or document incomplete
Explanation	Invalid token found or the document is incomplete.
Action	Please correct the document.
INOXPE8711	Document not well-formed
Explanation	The document to be loaded isn't well-formed.
Action	Please correct the document.
INOXPE8712	Invalid element name
Explanation	The name of the element is either too long or not correct.
Action	Please correct the document.
INOXPE8713	Invalid attribute name
Explanation	The name of the attribute is either too long or not correct.
Action	Please correct the document.
INOXPE8714	Invalid document ID (ino:id) specified
Explanation	The given document ID (ino:id) is either not numeric or not available.
Action	Please correct the document.
INOXPE8715	Inserting or changing a document is forbidden
Explanation	It isn't permitted when using this doctype to insert or to change documents.
Action	Please contact your system administrator.

INOXPE8716	Inserting a document is forbidden
Explanation	It isn't permitted when using this doctype to insert a new document.
Action	Please contact your system administrator.
INOXPE8717	Changing a document is forbidden
Explanation	It isn't permitted while using this doctype to change a document.
Action	Please contact your system administrator.
INOXPE8718	Document incomplete
Explanation	The document to be loaded is incomplete.
Action	Please correct the document.
INOXPE8719	Document contains invalid character reference
Explanation	The document contains an invalid character reference.
Action	Please correct the document.
INOXPE8720	Document contains invalid entity reference
Explanation	The document contains a reference to an entity which wasn't defined before.
Action	Please correct the document.
INOXPE8721	Root element does not match doctype declaration
Explanation	The given root element doesn't correspond to the root element of the used doctype.
Action	Please correct the document.
INOXPE8722	Element with wrong obj-type encountered
Explanation	The given element is defined in the schema as an attribute.
Action	Correct either the document or the accompanying schema.
INOXPE8723	Attribute with wrong obj-type encountered
Explanation	The given attribute is defined in the schema as an element.
Action	Correct either the document or the accompanying schema.

INOXPE8724	Invalid attribute value encountered
Explanation	The value of the attribute contains contents which aren't permitted.
Action	Please correct the document.
INOXPE8725	Attribute was found twice
Explanation	An attribute with same name was found twice.
Action	Please remove one of these attributes.
INOXPE8726	Occurrence count does not match multiplicity option
Explanation	The occurrence count of an element or attribute in an XML instance does not match the multiplicity option specified in the schema.
Action	Please correct the document.
INOXPE8727	Document structure does not match schema definition (choice)
Explanation	The document structure does not match the schema definition for the choice case.
Action	Please correct the document.
INOXPE8728	Internal error: parent object not found
Explanation	Accompanying parent object couldn't be found.
Action	Please contact your system administrator.
INOXPE8729	Unclosed CDATA section detected
Explanation	Unclosed CDATA section detected.
Action	Please correct the document.
INOXPE8730	Required child object not specified
Explanation	An element or an attribute which is defined in the schema as mandatory wasn't specified in the document.
Action	Please correct the document.
INOXPE8731	Internal error: Parse in progress
Explanation	The attempt was made to parse a second document while still parsing the first document.
Action	Please contact your system administrator.

INOXPE8732	Value too long
Explanation	The value of a numeric node or of a node mapped to an external datasource or of a node with search type STANDARD is too long.
Action	Please shorten the corresponding value.
INOXPE8733	Value not numeric
Explanation	The value for an object with an numeric datatype is not numeric.
Action	Please correct the document.
INOXPE8734	Numeric value too large
Explanation	The value of an object with a numeric datatype is too large.
Action	Please shorten the corresponding value.
INOXPE8735	Insufficient space to convert data according to encoding
Explanation	The length of data in an attribute/element that is defined to AdaField exceeds the defined length in the schema.
Action	Correct either the XML input data or modify the schema to increase the defined length.
INOXPE8736	Internal error: buffer exceeded
Explanation	For InfoFile mapping, the size of a document or the size of parts of a document that are mapped to any InfoField construct (like InfoArray) is limited to 64KB at the node level where map type InfoFile is specified. If there is no node with an explicit map type of InfoFile, the limit of 64KB applies to the root node.
Action	Reduce the number of nodes that are mapped to InfoField constructs. Use map type Native instead.
INOXPE8737	Invalid document update attempted
Explanation	The request tried to modify the document such that it would have generated an SQL UPDATE statement without a WHERE clause. This is not allowed.
Action	To accomplish this, delete the document and insert a new document instead of updating the document.

INOXPE8738	Only a single document may be processed.
Explanation	If the document name or the document ID is given, only a single document can be processed.
Action	Please remove additional documents.
INOXPE8740	Internal error in document serialization module detected
Explanation	An internal error occurred in the serialization module.
Action	Please contact your software supplier.
INOXPE8741	Internal error in document serialization module detected
Explanation	An internal error occurred in serialization module.
Action	Please contact your software supplier.
INOXPE8742	Recursion of entities detected
Explanation	During the processing of references to entities a recursion was discovered.
Action	Please check the entity definition and correct the document.
INOXPE8743	Entity stack overflow
Explanation	Entity stack overflow.
Action	Please reduce the nested entity references.
INOXPE8744	Internal error in index processing module detected
Explanation	An internal error occurred in the index processing module.
Action	Please contact your software supplier.
INOXPE8745	Internal error in index processing module detected
Explanation	An internal error occurred in the index processing module.
Action	Please contact your software supplier.
INOXPE8746	Internal error
Explanation	An internal error occurred during document processing.
Action	Please contact your software supplier.

INOXPE8747	Internal error in index processing module detected
Explanation	An internal error occurred in the index processing module.
Action	Please contact your software supplier.
INOXPE8748	Internal error in document processing module detected
Explanation	Processing aborted due to a server internal error.
Action	Please contact your software supplier.
INOXPE8749	Access to XNODEs / trigger functions during massload is not allowed
Explanation	The access to parts of the schema that specify X-Node or trigger function usage is not allowed when loading data with the Tamino Data Loader.
Action	Set "ignore update" for the X-Node or trigger function parts of the schema or use the concurrentWrite option of the Tamino Data Loader.
INOXPE8750	Tag or attribute name is too long
Explanation	The number of characters of a tag or attribute name exceeds the maximum supported value.
Action	Shorten the name of the tag or attribute in question.
INOXPE8751	Storing an object of this mapping type is not permitted
Explanation	Storing an object which is linked to another object is not permitted.
Action	Please correct the document.
INOXPE8752	Document not found in database
Explanation	A document referenced by the current command was not found in the database, because it was deleted by another concurrent access.
Action	Re-issue the command.
INOXPE8753	The element has contents although it is defined with object type "EMPTY"
Explanation	The element has contents although it is defined with object type "EMPTY".
Action	Please correct either the document instance or the schema definition.

INOXPE8754	Comments are not allowed between documents
Explanation	The input file contains a comment between two documents. This is not allowed.
Action	Remove the comment.
INOXPE8755	Invalid document name (ino:docname) specified
Explanation	The document name given in the attribute ino:docname is empty.
Action	Either provide a document name in the attribute ino:docname or remove the ino:docname attribute.
INOXPE8756	Invalid versioning mode
Explanation	The document could not be stored, because the auto-version mode is invalid or the document is not in the correct versioning state.
Action	Make sure that the document is in the checkout-checkin auto-version mode and that the document is not checked out.
INOXQE6250	Feature not implemented
Explanation	The feature you tried to use is not implemented yet.
Action	Try an other method.
INOXQE6251	internal exception
Explanation	An internal exception has occurred.
Action	Please contact your software supplier.
INOXQE6252	Type exception: non-atomic type in element/attribute
Explanation	This error occurs if a non-atomizable type is encountered where a simple type is required, e.g. an element node belonging to a type that allows sub-elements is provided as a parameter for a function that expects a string.
Action	Check the operand's types or adopt the schema definition.
INOXQE6253	Type exception: sequence occurred where atomic value required
Explanation	Some functions and operators do not operate on sequences that contain that more than one entry.
Action	Check the operand types.

INOXQE6254	Type can not be compared / sorted
Explanation	Only totally ordered types such as numeric types, string types, boolean, dateTime, date and time can be compared and sorted.
Action	Try to use a totally ordered type or convert into such a type.
INOXQE6255	Invalid argument to aggregation function
Explanation	The atomic values in a sequence upon which the avg() or sum() function is applied must have a common super-type that is either numeric or a date/time type.
Action	Check the values in the sequence.
INOXQE6256	Conversion detected an invalid value
Explanation	An invalid value could not be converted.
Action	Check the query and the data.
INOXQE6257	Invalid type denotation for atomic type
Explanation	A string provided as an atomic type denotation, for example with a user-defined function, does not denote a type.
Action	Use proper type denotations, for example xs:integer or xdt:anyAtomicType.
INOXQE6261	Duplicate function definition
Explanation	A query or a module definition contains two definitions of the same function, or an imported module defines a function that is already defined.
Action	Remove the extra function definition.
INOXQE6262	Module not found
Explanation	An XQuery module import directive could not be satisfied, because there is no such module.
Action	Correct the import directive, or load an appropriate module definition.
INOXQE6263	Invalid server extension type detected
Explanation	A server extension function is called that returns or consumes a type that is not supported by the XQuery processor.
Action	Check the signature of the called server extension function.

INOXQE6264	Cyclic module import
Explanation	A module M may not import another module that directly or indirectly imports module M.
Action	Remove the cycle from the module import dependencies.
INOXQE6300	Internal error
Explanation	An internal error has occurred in the XQuery execution engine.
Action	Please contact your software supplier.
INOXQE6301	Runtime type exception
Explanation	An invalid type was detected at XQuery execution time.
Action	Correct the query.
INOXQE6302	XQuery feature not implemented
Explanation	The query uses an unimplemented language feature. Please see the documentation and release notes for current product limitations.
Action	Change the query.
INOXQE6303	Invalid position for range
Explanation	The first position parameter for 'range' is negative or zero.
Action	Check the query and data to find the wrong position value.
INOXQE6304	Internal error: buffer overflow
Explanation	An intermediate result is too large.
Action	Please contact your software supplier.
INOXQE6305	Division by zero
Explanation	A division by zero was attempted (not defined mathematically).
Action	Make sure that a divide by zero does not occur.
INOXQE6306	numeric overflow has occurred
Explanation	An arithmetic operation yielded a result which is not representable with the data type.
Action	Make sure that results do not exceed the representable range.

INOXQE6307	duplicate attribute name occurred in element constructor
Explanation	An element constructor contained multiple attributes of the same name.
Action	Make sure that attribute names of constructed elements are unique.
INOXQE6308	sort utility failed
Explanation	An explicit or implicit invocation of the sorting utility failed. This may occur due to insufficient disk space for temporary files.
Action	Check whether sufficient disk space is available for temporary files.
INOXQE6309	namespace prefix conflict between constructed element and attribute
Explanation	A constructed element contained a conflicting namespace declaration while an attribute was added to it.
Action	Use a different namespace prefix in the attribute's target environment.
INOXQE6310	Processing of data with X-Tension or X-Node mapping is not supported by XQuery
Explanation	Currently no data with X-Tension (server extension) or X-Node mapping can be accessed by an XQuery query.
Action	Formulate your query using Tamino X-Query instead of XQuery.
INOXQE6311	temporary file access failed
Explanation	A problem has occurred while accessing a temporary disk file. This may occur due to insufficient disk space for temporary files.
Action	Check whether sufficient disk space is available for temporary files.
INOXQE6312	Document access error
Explanation	A document did not exist though it was part of a query result. This situation can occur when a query is executed with isolation level "uncommitted document", while another transaction has been rolled back after concurrently inserting the document.
Action	Retry the query or use an isolation level different from "uncommitted document".
INOXQE6313	Runtime type exception: non-atomic type in element/attribute
Explanation	This error occurs if a non-atomizable type is encountered where a simple type is required, e.g. an element node belonging to a type that allows sub-elements is provided as a parameter for a function that expects a string.
Action	Check the operand's types or adopt the schema definition.

INOXQE6314	Value cannot be converted
Explanation	The textual representation of the value does not match the type it is being converted to.
Action	Check the query and the data.
INOXQE6315	Runtime type exception: sequence occurred where atomic value required
Explanation	Some functions and operators do not operate on sequences that contain more than one entry.
Action	Check the operand's types.
INOXQE6316	Run-time encountered non-comparable type
Explanation	Only totally ordered types such as numeric types, string types, boolean, dateTime, date and time can be compared and sorted.
Action	Try to use a totally ordered type or convert into such a type.
INOXQE6317	Run-time encountered invalid argument to aggregation function
Explanation	The atomic values in a sequence upon which the avg() or sum() function is applied must have a common super-type that is either numeric or a date/time type.
Action	Check the values in the sequence.
INOXQE6318	Runtime type exception: empty sequence occurred where atomic value required
Explanation	Some functions and operators do not operate on an empty sequence.
Action	Check the operand's types.
INOXQE6319	Invalid simple type detected
Explanation	In an expression, an invalid simple type was used.
Action	Check the actual type and the expected type with your query.
INOXQE6320	Invalid combination of operand types for an arithmetic operation
Explanation	The type of at least one operand is not valid for an arithmetic operation.
Action	Check where the types can occur in your query and correct it.

INOXQE6321	Runtime type exception: invalid node-type
Explanation	Some operations only operate on nodes of certain types.
Action	Check the node's type. Correct the path used to obtain the node.
INOXQE6322	Non-simple type detected
Explanation	A non-simple type was detected where a simple type is required.
Action	Check your query and the data to find a type mismatch.
INOXQE6323	Conversion: facet 'minLength' was violated by a value
Explanation	The value to be converted was too short.
Action	Check the query and the data.
INOXQE6324	Incompatible types for cast operation
Explanation	The source type cannot be cast to the target type.
Action	Check the type of the argument to the cast.
INOXQE6325	Conversion error for comparison
Explanation	During the execution of a comparison, the values must be converted to a common type. This conversion failed, either because of incomparable types or because of invalid data.
Action	Check your query and data to find the mismatch.
INOXQE6326	Comparison undefined
Explanation	Some data types cannot be compared because they are partially ordered.
Action	Check your query and data for undefined comparisons.
INOXQE6327	Invalid last position for range
Explanation	The last position parameter for 'range' is smaller than the first and is not -1.
Action	Check the query and data to find the wrong position value.
INOXQE6328	Value out of range
Explanation	A value could not be converted into the internal representation because it is out of range, for example the allowed range for a month is 1 to 12.
Action	Check your query and/or data.

INOXQE6329	Invalid collation URI exception
Explanation	The specified collation URI is invalid.
Action	Check the collation URI.
INOXQE6330	Invalid collation attributes exception
Explanation	The specified collation attributes are invalid.
Action	Check the collation attributes.
INOXQE6331	Namespace prefix undefined
Explanation	An invalid namespace prefix was detected when casting a string value as a QName at query execution time.
Action	Extend the static namespace context by adding a definition for the missing prefix.
INOXQE6332	Invalid content expression in computed processing instruction
Explanation	The value of the content expression in a computed processing instruction constructor contains the string "?>".
Action	Avoid expressions that may produce strings containing "?>".
INOXQE6333	Invalid name for processing instruction
Explanation	The name of a constructed processing instruction must be different from "XML" (in any combination of upper and lower case).
Action	Avoid expressions that may produce the string "XML".
INOXQE6334	"Treat as" operation has detected two non-matching types during query execution
Explanation	A "Treat as" operation has detected two non-matching types during query execution.
Action	Reformulate your query.
INOXQE6335	Call stack overflow
Explanation	The call stack for user defined functions has exceeded its defined maximum size.
Action	Inspect your XQuery program for potential programming errors, or increase the call stack's maximum size by means of the {?execution?} pragma.

INOXQE6336	Memory allocation limit exceeded
Explanation	The memory limit that has been set by an XQuery execution pragma has been exceeded.
Action	Extend the memory limit, or try to reduce the memory requirements by modifying the query.
INOXQE6337	Invalid content expression in computed comment constructor
Explanation	The result of the content expression of a computed comment constructor contains two adjacent hyphens or ends with a hyphen.
Action	Avoid expressions that produce adjacent hyphens or hyphens at the end.
INOXQE6338	Sort buffer overflow
Explanation	An internal sort buffer has overflowed, because the representation of a single tuple did not fit into it.
Action	Modify the query to reduce the size of tuples to be sorted.
INOXQE6339	Multiple element children in document constructor
Explanation	An XQuery document constructor was supplied with more than one element child. This is not supported by the underlying data model.
Action	Correct the query to avoid constructing multiple element children into a document node.
INOXQE6340	XML parsing error while executing fn:parse()
Explanation	An XQuery invoked fn:parse, but the argument could not be parsed successfully as XML.
Action	Provide well-formed XML.
INOXQE6349	fetching result that is not available
Explanation	A non-sensitive cursor pre-calculates a system defined maximum number of result items. A fetch request has tried to access an item that was not pre-calculated.
Action	Please contact your software supplier.
INOXQE6350	Internal error
Explanation	An internal error has occurred in the XQuery compiler.
Action	Please contact your software supplier.

INOXQE6351	XQuery feature not implemented
Explanation	The query uses an unimplemented language feature. Please see the documentation and release notes for current product limitations.
Action	Change the query.
INOXQE6352	XQuery parsing error
Explanation	One or more errors occurred while parsing the query.
Action	Correct the query appropriately and re-issue.
INOXQE6353	End tag does not match start tag
Explanation	The end tag of an element constructor does not match the start tag.
Action	Correct the query.
INOXQE6354	Namespace prefix undefined
Explanation	The namespace declaration is missing.
Action	Include a namespace declaration in the XQuery prolog.
INOXQE6355	Invalid namespace URI specification
Explanation	URIs must be given as string constants.
Action	Declare the URI literally.
INOXQE6356	Attempted to redefine prefix
Explanation	A prefix may only be defined once.
Action	Rename the prefix in subsequent declarations.
INOXQE6357	The prefix 'xml' must be bound to the namespace 'http://www.w3.org/XML/1998/namespace'
Explanation	The prefix 'xml' can only be declared when bound to the XML namespace URL as defined by the W3C.
Action	If your intent was to include the W3C's XML namespace, correct the URL. Otherwise use a different prefix.

INOXQE6358	Function unknown
Explanation	This function is unknown. The function name is either misspelt or the wrong prefix is used.
Action	Check the spelling and the function namespace.
INOXQE6359	Variable undefined
Explanation	A variable that is used must be declared in a 'for' or 'let' expression.
Action	Check spelling or add a 'for' or 'let' clause.
INOXQE6360	Unbound path not allowed here
Explanation	Currently access to database data is only allowed via the input() function.
Action	Use the input() function.
INOXQE6361	Type exception: invalid operands for operator
Explanation	Static typing detected invalid operand types for the operator.
Action	Please check the static types for the operator.
INOXQE6362	Invalid path: documents have no parent
Explanation	The path tries to apply the parent axis (or '..') to a document node.
Action	Check the path.
INOXQE6363	Unknown collection
Explanation	The URL refers to a collection that does not exist in the chosen database.
Action	Check the URL.
INOXQE6364	XQuery applied on non-XML doctype
Explanation	XQuery is only applicable to XML data.
Action	Use another tool for querying.
INOXQE6365	XQuery applied on non-namespace-clean doctype:
Explanation	XQuery is only applicable on namespace-clean doctypes.
Action	Apply proper namespace migration to doctype or use X-Query.

INOXQE6366	Type exception: invalid input for function
Explanation	The parameters provided as an input to the function do not have the required type.
Action	Check the correct parameter types in the documentation for the function.
INOXQE6367	Compile time type exception
Explanation	An invalid type has been detected at XQuery compile time
Action	Correct the query.
INOXQE6368	Default element namespaces are not allowed
Explanation	The XQuery draft is still uncertain whether default element namespaces defined in the query prolog or in generated elements pertain to element steps in location paths. To avoid migration problems with subsequent versions of Tamino, the use of default element namespaces is prohibited.
Action	Please use a namespace prefix instead.
INOXQE6369	A prefix must not begin with 'xml'
Explanation	This is stated in the Errata Document for the XML Namespaces Recommendation.
Action	Choose a prefix that does not begin with 'xml'.
INOXQE6370	Processing of data with X-Tension or X-Node mapping is not supported by XQuery
Explanation	Currently no data with X-Tension (server extension) or X-Node mapping can be accessed by an XQuery query.
Action	Formulate your query using Tamino X-Query instead of XQuery.
INOXQE6371	The URI 'http://www.w3.org/XML/1998/namespace' can only be bound to the prefix 'xml'
Explanation	According to "Namespaces in XML Errata, 4 November 2002" (http://www.w3.org/XML/xml-names-19990114-errataNE05 substantive), the prefix xml is by definition bound to the namespace name http://www.w3.org/XML/1998/namespace . It may, but need not, be declared, and must not be bound to any other namespace name. No other prefix may be bound to this namespace name.
Action	Use the prefix 'xml' or a different URI.

INOXQE6372	No prefix may be bound to the URI 'http://www.w3.org/2000/xmlns/'
Explanation	This URI is by definition bound to the prefix 'xmlns'. It must not be declared.
Action	Use a different URI.
INOXQE6373	Invalid comparison
Explanation	Items to be compared must be of the same type, or both numeric, or both string or one of the types derived thereof.
Action	Use string comparison via applying the xf:string() function to non-string operands.
INOXQE6374	The prefix xmlns is used only to declare namespace bindings
Explanation	The prefix xmlns cannot be used unless in the form xmlns:prefix="uri" to declare a namespace binding.
Action	Use another prefix.
INOXQE6375	No multiple default collations allowed.
Explanation	Only one default collation can be defined.
Action	To use more than one collation within a single query give the collation's URI explicitly in the comparison function or use the getCollation() function.
INOXQE6376	Collation could not be obtained.
Explanation	The getCollation() function was not applied upon a path that pointed to an appropriate node.
Action	The input to the getCollation() function must be a path that points to an appropriate element or attribute node. A node is appropriate if its corresponding schema definition contains a collation specification.
INOXQE6377	Invalid Collation Identifier
Explanation	This string does not denote a valid collation.
Action	Correct the spelling or make the collection known to the database.
INOXQE6378	Invalid step in path
Explanation	A flat structure, i.e. something that is not a node, cannot be stepped into using any other axis than the self axis.
Action	Either change the object that is stepped into so that it is of type node or node-set, or use only the self axis (or the dot) to refer to the object.

INOXQE6379	Evaluation context undefined
Explanation	Processing of an expression relies on some component of the evaluation context that has not been assigned a value. Many context-sensitive functions like local-name() rely on the context item.
Action	Make sure that expressions relying on the evaluation context are called when an evaluation context is defined as for example within a filter.
INOXQE6382	XQuery cursor request must not specify a serialization method
Explanation	It is not possible to use a serialization method for an XQuery cursor request.
Action	If you want to apply a serialization method to your query result, use a non-cursor query.
INOXQE6383	Type exception: invalid input for internal function
Explanation	The parameters provided as an input to an internal function do not have the required type. Calls to internal functions are, for instance, contained in update queries. This error may thus indicate an invalid update statement.
Action	Reformulate the update statement or check whether the intended update operation is possible at all.
INOXQE6384	Invalid key or value in an optimization pragma.
Explanation	Valid optimization keys are "join" (possible values "default" and "index-only") and "level" (possible values "0" and "1").
Action	Correct the optimization key and/or value.
INOXQE6385	Invalid output handler function detected
Explanation	An invalid output handler has been detected. Please check the signature of the given output handler function.
Action	Please check the signature of the given output handler function.
INOXQE6386	This name must not be local
Explanation	Some names, for example those of user-defined functions, must be in a namespace. They must either be qualified, i.e. consist of a prefix and a local part, or be in a namespace by a default namespace declaration.
Action	Use either a prefix declared in the query or add a default namespace declaration. For user-defined functions the predefined prefix 'local' can be used.

INOXQE6387	The prefix 'local' may only be used when declaring a user-defined function.
Explanation	The 'local' prefix is by definition bound to the URI "http://www.w3.org/2003/11/xquery-local-functions" and is reserved for the definition of user-defined, i.e. local, functions.
Action	Use another prefix.
INOXQE6388	The name of a computed node is neither a string nor a QName.
Explanation	The name of a computed node, such as for example element or attribute node, must either be of type string or derived or of type QName.
Action	Ensure that the expression provided as a computed node's name is of an appropriate type.
INOXQE6389	A user-defined function returns a non-matching type
Explanation	If a user-defined function declares a result type, the type of the function's body must match this declaration.
Action	Correct the function's body or delete the result type declaration.
INOXQE6390	The prefix 'xs' must be bound to the namespace 'http://www.w3.org/2001/XMLSchema'
Explanation	The prefix 'xs' can only be declared when bound to the appropriate namespace URL as defined by the W3C's XML Schema spec.
Action	If your intent was to include the W3C's xs namespace, correct the URL. Otherwise use a different prefix.
INOXQE6391	The name of a computed PI node is not an NCName.
Explanation	The name of a computed PI node must be an NCName.
Action	Ensure that the expression provided as a computed PI node's name is of an appropriate type.
INOXQE6392	The content of a generated PI must be a string.
Explanation	The expression provided as the content of a generated PI node must evaluate to a sequence of strings.
Action	Provide suitable content.

INOXQE6393	Pragma not supported in library module
Explanation	An XQuery library module contains a pragma that is valid only in a main module.
Action	Remove the pragma from the library module.
INOXQE6394	Invalid node comparison
Explanation	A node comparison requires that each operand is either a singleton or an empty sequence.
Action	Check the operands. If an operand is possibly a sequence with more than one entry, use round brackets and a [1] filter.
INOXQE6395	Invalid key or value in an serialization pragma.
Explanation	A valid serialization key is "provide-type-information" (possible values "yes" and "no").
Action	Correct the serialization value.
INOXQE6396	Invalid key or value in an execution pragma.
Explanation	Valid execution keys are "memory" (possible values are integers) and "call-stack-depth" (possible values are also integers).
Action	Correct the execution key/value.
INOXQE6397	Duplicate parameter name in user-defined function
Explanation	Each parameter in a user-defined function's parameter list must have a unique name.
Action	Rename one or more parameters.
INOXQE6398	External variable definition does not conform to restricted XQuery syntax
Explanation	An XQuery expression that is supplied to define an external variable is restricted to sequences of constants, type-specific constructor functions and node constructors.
Action	Reformulate the external variable definition to conform to the restrictions.
INOXQE6399	Duplicate import directive
Explanation	Two 'import module' declarations specify the same module namespace.
Action	Remove the extra import directive or replace it by a namespace declaration.

INOXQE6400	Duplicate main-module pragma
Explanation	More than a single main-module pragma has been found in an XQuery.
Action	Remove the duplicate pragma.
INOXQE6401	Multiple declarations of element/type default namespace not allowed
Explanation	Only one default namespace for elements/types can be defined.
Action	Delete one of the default namespace declarations.
INOXQE6402	Multiple declarations of function default namespace not allowed
Explanation	Only one default namespace for functions can be defined.
Action	Delete one of the default namespace declarations.
INOXQE6403	Function is in a namespace different from the module's target namespace.
Explanation	The name of every function declared in a library module must have a namespace URI that is the same as the target namespace of the module.
Action	Change the function's namespace or move to another module.
INOXQE6404	A user-defined function is in a forbidden namespace
Explanation	The function name in a function declaration (when expanded) must not be in any of the following namespaces (among others): http://www.w3.org/XML/1998/namespace , http://www.w3.org/2001/XMLSchema , http://www.w3.org/2001/XMLSchema-instance , http://www.w3.org/2005/04/xpath-functions , http://www.w3.org/2005/04/xpath-datatypes .
Action	Change the user-defined function's namespace by changing the prefix, or the prefix's binding, or the default function namespace.
INOXQE6406	Invalid context for updating function
Explanation	An updating function was invoked in a context where only a non-updating function is permitted.
Action	Modify the query to provide a proper function or context.
INOXQE6407	Invalid context for non-updating function
Explanation	A non-updating function was invoked in a context where only an updating function is permitted.
Action	Modify the query to provide a proper function or context.

INOXQE6408	Invalid name for external variable
Explanation	A qualified name including a prefix is not supported as the name of an external variable.
Action	Use a non-qualified name.
INOXQE6420	Query not found
Explanation	The given handle does not address any prepared query.
Action	Please correct the given query handle.
INOXQE6421	Invalid query handle
Explanation	The format of the given query handle is wrong. The query handle must be an integer.
Action	Correct the query handle.
INOXQE6424	Missing parameter for query execution
Explanation	The prepared query declares external variables. For at least one of these variables, no suitable input parameter was provided.
Action	Provide input parameter.
INOXQE6450	Update results in non-well-formed document
Explanation	The update statement tries a modification that would result in a non-well-formed document, e.g., insert an element into an attribute, or insert a second root element. The error is accompanied by a message that explains the actual reason in more detail.
Action	Correct the update statement.
INOXQE6451	Conflicting update operations
Explanation	An update statement can consist of several atomic update operations. There may be conflicts between those operations, e.g., a subtree cannot be replaced and deleted at the same time.
Action	Correct the update statement.
INOXQE6452	Attempted to insert or modify one of the meta-attributes ino:id or ino:docname
Explanation	Using XQuery update, it is not allowed to modify the meta-attributes ino:id or ino:docname.
Action	Correct your XQuery update statement.

INOXQE6453	Attempt to modify a nonxml document
Explanation	It is not possible to modify non-XML documents using an XQuery update statement. Only deletion of complete non-XML documents is allowed by XQuery update.
Action	Use the <code>_process</code> command in order to replace and thus modify a non-XML document.
INOXQE6454	Attempt to update the same XNode-mapped field twice with different values
Explanation	An XNode column/field appears at different paths in the schema, and an XQuery update statement tried to modify at least two paths with different values.
Action	Correct the XQuery update statement.
INOXQE6455	Invalid node type passed to updating function
Explanation	A node was passed to an updating function, but the node type was not suitable for the function. <code>tf:setDocname</code> and <code>tdf:setProperty</code> can be applied to document nodes only, while <code>tf:put</code> can be applied to document or element nodes.
Action	Modify the query to provide a node with a proper node type.
INOXQE6456	Invalid invocation of tdf:setProperty for live property
Explanation	<code>tdf:setProperty</code> was used in an XQuery update on a live property. This is not allowed, live properties cannot be updated this way.
Action	Modify the update statement, removing the invalid invocation of <code>tdf:setProperty</code> .
INOXQE6457	Invalid doctype name
Explanation	The URI used in a call to <code>fn:put</code> contained an invalid doctype name. The provided doctype name was either not a valid QName, or it did not match the root element name of the XML document to be stored.
Action	Provide a valid doctype name in the URI used with <code>fn:put</code> , or omit the doctype name from the URI.
INOXQE6458	XML parsing error while converting nonXML document
Explanation	A nonXML document was passed to <code>fn:put()</code> with a URI indicating an XML doctype. The nonXML content however failed to be parsed successfully as XML.
Action	Provide well-formed XML or store the document into an XML doctype.

INOXQE6459	Cannot update transient node
Explanation	A transient node, i.e. a node resulting from a previous constructor, was detected as the subject of an update operation. XQuery update however can only be applied to persistent nodes.
Action	Modify XQuery update statement to avoid applying update operations to transient nodes.
INOXQW6380	A path expression results in an empty node-set
Explanation	An empty node-set as a result of a path expression might indicate an error in referencing the document structure or in a name spelling.
Action	Ensure that the empty result is not due to a wrong path.
INOXQW6405	Invalid entity or character reference
Explanation	The query contains an invalid entity or a character reference that does not map to a valid character. As a corrective action, the ampersand character has been treated as a literal, not as an entity introducer.
Action	To avoid this warning, correct the query appropriately and re-issue.
INOXQW6423	Execution of prepared query requires recompilation
Explanation	Due to schema, security or structure index changes the compiled query yielded by previous preparation is not longer valid. This requires a recompilation of the prepared query.
Action	Recompile the prepared query.
INOXQW6425	querySearchMode=approximate not applicable for this query
Explanation	This query cannot be executed in a streaming mode, thus the specified request parameter querySearchMode=approximate has no effect.
Action	Do not use this request parameter.
INOXRE8802	Internal error: input parameter error
Explanation	Internal error: Data Map was called with missing or invalid parameters.
Action	Please contact your software supplier.

INOXRE8803	Specified name too long
Explanation	The specified name is too long. Length limitations are described in the Tamino documentation.
Action	Modify the schema definition and repeat your request.
INOXRE8805	Invalid collection, element, attribute or server extension name
Explanation	The specified name is not a valid QName. The specified name starts with a colon and/or contains more than one colon.
Action	Correct the schema definition and repeat the request.
INOXRE8806	Collection is currently used by another user
Explanation	The request cannot be executed because at least one of the affected collections is currently held by another user.
Action	Repeat the request.
INOXRE8807	Doctype is currently used by another user
Explanation	There is a persistent lock on a doctype which prevents the current request from continuing.
Action	Repeat the request when the request that has the persistent lock has finished.
INOXRE8808	Index recreation currently not pending on the specified collection
Explanation	There is no index recreation pending to continue or reset. It is not necessary to execute the <code>_admin</code> command.
Action	No action required.
INOXRE8809	Index recreation is pending
Explanation	On the specified doctype an index recreation is pending. The requested action cannot be executed.
Action	Execute the corresponding <code>_admin</code> request to continue or reset the index recreation.
INOXRE8810	Index recreation is running
Explanation	The requested action cannot be executed while an index recreation is running on the specified doctype.
Action	No action required.

INOXRE8811	Collection name not found
Explanation	The specified collection is unknown.
Action	Correct the collection name and repeat the request.
INOXRE8814	Element/attribute name not found
Explanation	The specified element or attribute is unknown.
Action	Correct the element or attribute name and repeat the request.
INOXRE8815	Internal error: mapping already defined
Explanation	Internal error: mapping already defined.
Action	Please contact your software supplier.
INOXRE8816	Internal error while inserting an implicit element or attribute
Explanation	An internal error occurred while inserting an implicit element or attribute.
Action	Please contact your software supplier.
INOXRE8818	Duplicate collection name
Explanation	There is already a collection with the specified name.
Action	Specify another collection name or undefine the existing collection.
INOXRE8819	Duplicate element/attribute name
Explanation	The element or attribute to be inserted is already defined. It is not allowed to specify a schema containing two or more elements or attributes with the same name and the same parent.
Action	Correct the schema definition and repeat the request.
INOXRE8821	Internal error: invalid parent specification
Explanation	Internal error: invalid parent specification.
Action	Please contact your software supplier.
INOXRE8822	Invalid options specification
Explanation	The specified options are incorrect. Either unexpected options are specified or expected options are missing.
Action	Refer to the Tamino documentation, correct your schema definition and repeat the request.

INOXRE8823	Internal error: invalid object ID specification
Explanation	Internal error: an invalid ID was specified.
Action	Retry with an increased transaction timeout value. If that doesn't help restart the Tamino database. If the problem still occurs please contact your software supplier.
INOXRE8824	Internal error: invalid collection ID specification
Explanation	Internal error: an invalid ID was specified.
Action	Please contact your software supplier.
INOXRE8825	Invalid multiplicity specification
Explanation	The specified multiplicity is invalid. Either the multiplicity does not correspond with the mapping type, or a multiplicity of + or * is specified for attributes, or a multiplicity not equal to blank is specified for the root element.
Action	Correct the schema definition and repeat the request.
INOXRE8826	Invalid search type specification
Explanation	The search type is invalid or does not match the specified mapping type. For an external document summary file the specified shortname may be invalid.
Action	Correct the schema definition and repeat the request.
INOXRE8827	Internal error: invalid index ID specification
Explanation	Internal error: an invalid ID was specified.
Action	Please contact your software supplier.
INOXRE8830	Invalid schema structure: missing node definition
Explanation	An attempt was made to specify a node with a mapping type which requires at least one child with a specific other mapping type. This element is missing. (Example: Mapping to an SQL table requires at least one child mapped to an SQL column.)
Action	Correct the schema definition and repeat the request.
INOXRE8831	Deletion rejected because of depending objects
Explanation	The server extension object could not be deleted because at least one node references a server extensions function of the object to be deleted.
Action	Update the schema definitions containing referencing nodes and repeat the request.

INOXRE8833	Internal error: file structure/schema definition mismatch
Explanation	Internal error: file structure/schema definition mismatch.
Action	Please contact your software supplier.
INOXRE8834	Data map record could not be stored
Explanation	A Data Map record could not be stored. The definition of one node is too large.
Action	Modify the schema definition and repeat the request. Please inform your software supplier.
INOXRE8835	Data map record could not be updated
Explanation	A data map record could not be updated. The number of children for one collection or node is too large.
Action	Modify the schema definition and repeat the request. Please inform your software supplier.
INOXRE8836	Modifying or deleting of system collection/doctype rejected
Explanation	Collections and doctypes containing the Tamino namespace may not be modified or deleted.
Action	No action required.
INOXRE8841	Invalid mapping specification: invalid or unexpected primary key definition
Explanation	For a mapped SQL table at least one mapped SQL column must be indicated as the primary key using the keyword ino:sqlprimarykeys.
Action	Correct the schema definition and repeat the request.
INOXRE8842	Invalid mapping specification: invalid or unexpected password specification
Explanation	The specified Adabas password is either too long (maximum length is 8 characters) or unexpected (for nodes not mapped to AdaFile).
Action	Correct the schema definition and repeat the request.
INOXRE8843	Invalid mapping specification: invalid parent - child relation
Explanation	The relation between parent node and child node is not allowed. This is mostly caused by the object type of either parent or child node.
Action	Correct the schema definition and repeat the request.

INOXRE8844	Invalid mapping specification: invalid parent - child relation
Explanation	The relation between parent node and child node is not allowed. This is caused by either an unexpected mapping type of the child node or a node having a multiplicity of + or * between a node mapped to an SQL table or an Adabas file and the corresponding nodes mapped to an SQL column or Adabas field, multiple field or periodic group.
Action	Correct the schema definition and repeat the request.
INOXRE8845	Invalid schema structure: missing elements
Explanation	The mapping of the node is invalid. It requires other mapping in parent nodes. This error is mostly caused by a node mapped to an SQL column without having a corresponding node mapped to an SQL table, or mapped to an Adabas field without having a corresponding node mapped to an Adabas file.
Action	Correct the schema definition and repeat the request.
INOXRE8847	Invalid mapping specification: invalid or unexpected shortname specification
Explanation	The specification of a shortname is not allowed or does not conform to Adabas shortname rules.
Action	Correct the schema definition and repeat the request.
INOXRE8848	Invalid mapping specification: invalid or unexpected Adabas file specification
Explanation	The specification of a database ID and or file number is missing or invalid (Adabas file mapping) or not allowed (other mappings).
Action	Correct the schema definition and repeat the request.
INOXRE8854	Invalid mapping specification: invalid object reference specification
Explanation	The specified object reference was unexpected or refers to an undefined object. An object reference may only be specified for nodes mapped to another node.
Action	Correct the schema definition and repeat the request.
INOXRE8856	Invalid mapping specification: invalid or unexpected SQL specification
Explanation	For an SQL table mapping the table name was missing or a password was specified without userid. For an SQL column mapping the column was not specified. For other mappings SQL specific keywords are unexpected.
Action	Correct the schema definition and repeat the request.

INOXRE8859	Invalid mapping specification: invalid or unexpected format specification
Explanation	A format specification is either invalid (for Adafield mappings) or unexpected (for other mappings). A list of all valid formats is specified in the Tamino documentation.
Action	Correct the schema and repeat the request.
INOXRE8860	Invalid mapping specification: invalid or unexpected length specification
Explanation	A length specification is either invalid (for Adafield mappings) or unexpected (for other mappings). The length specification must conform to the format specification as defined in Adabas.
Action	Correct the schema definition and repeat the request.
INOXRE8861	Invalid mapping specification: invalid or unexpected precision specification
Explanation	A precision was either specified for a non-SQL column mapping, or is unexpected or out of range for the specified datatype. Dependencies between datatype and precision are described in the Tamino documentation.
Action	Correct the schema and repeat the request.
INOXRE8862	Invalid mapping specification: invalid or unexpected scale specification
Explanation	A scale was either specified for a non-SQL column mapping, or is unexpected or out of range for the specified datatype. Dependencies between datatype, precision and scale are described in the Tamino documentation.
Action	Correct the schema definition and repeat the request.
INOXRE8863	Invalid mapping specification: invalid or unexpected data type specification
Explanation	The specification of a data type is not allowed or does not conform to the list of supported datatypes. Please refer to the Tamino documentation for a list of supported data types.
Action	Correct the schema definition and repeat the request.
INOXRE8865	Invalid mapping specification: invalid or unexpected encoding specification
Explanation	The value for an encoding may only be specified for nodes mapped to an Adabas file or mapped to an Adabas field that has an alphanumeric format. The encoding must be a valid encoding string.
Action	Correct the schema and repeat the request.

INOXRE8873	Server extensions: function not found
Explanation	There is no server extension function with the specified function name.
Action	Check the specified function name. Be aware that function names are case sensitive.
INOXRE8887	The request cannot be executed within a session context
Explanation	In a session context it is not possible to recreate indexes for ino:creationDate or ino:lastModified.
Action	Recreate the indexes in a session-less request.
INOXRE8888	Adding a new node definition with the specified attributes is not supported
Explanation	Adding a new node definition with the specified attributes is not supported because of already existing documents.
Action	Remove the affected documents and repeat the request.
INOXRE8889	Modifying an existing node definition with the specified attributes is not supported
Explanation	The requested parameter may not be changed after the schema definition.
Action	Undefine the schema and define the modified schema definition once again.
INOXRE8890	Internal error: unsupported request
Explanation	The internal data map was called for an unsupported request.
Action	Please contact your software supplier.
INOXRE8891	Internal error: Data Map function failed
Explanation	The internal data map encountered an unexpected situation.
Action	Please contact your software supplier.
INOXRE8892	Internal error: Data Map corrupted
Explanation	The internal data map found insufficient data.
Action	Please contact your software supplier.
INOXRE8893	Internal error: conversion services failed
Explanation	An error occurred while the internal data map used conversion services.
Action	Please contact your software supplier.

INOXRE8894	Internal error: invalid file specification
Explanation	An internal error occurred during access to an Infofile.
Action	Please contact your software supplier.
INOXRF8899	Index recreation could not be finished successfully for doctype DOCTYPE in collection COLLECTION
Explanation	An error occurred while finishing the index recreation. The collection is currently not usable.
Action	Restart the server and execute the <code>_admin</code> command to finish the index recreation.
INOXRI8838	Request to create the unique constraint CONSTRAINT for doctype DOCTYPE in collection COLLECTION has failed and will be backed out
Explanation	A request to create a unique constraint was running during server shutdown. The unique constraint is dropped during server start.
Action	Repeat the request to create the unique constraint.
INOXRW8801	Request to create indexes for doctype DOCTYPE in collection COLLECTION is pending
Explanation	A request to create indexes was aborted with an error or was running during server shutdown.
Action	Start the corresponding admin command to continue or reset the index creation.
INOXSE8903	Memory allocation failed
Explanation	There was not enough main memory available to perform the request.
Action	Possibly the machine is overloaded. Try again later.
INOXSE8905	The combination of index-shortname and the search-type and/or map-type is not valid
Explanation	The node with the search-type and/or map-type cannot contain a definition of index-shortname
Action	Check the map-type and the search-type.

INOXSE8906	XML parser failure for schema definition
Explanation	The supplied schema definition is not well-formed XML.
Action	Correct the schema definition.
INOXSE8909	Internal error during schema processing
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXSE8910	Invalid element content in schema definition
Explanation	The schema definition contains elements with mixed content, or the ino:file-format attribute has an illegal value.
Action	Correct the schema definition.
INOXSE8911	The specified mapping parameter(s) (adadsfnr, adadsdbid, adavoc...) can only be specified in a node which has the mapping type AdaFile
Explanation	The specifications such as adadsfnr, adadsdbid, adavoc etc. cannot be used with a mapping type other than AdaFile
Action	Remove the mapping parameters or change the mapping type to AdaFile.
INOXSE8913	Invalid structure of schema definition, hierarchy has to be collection - doctype - node
Explanation	The structure of the schema definition is invalid. It should be defined with the hierarchy collection - doctype - node(s).
Action	Check the schema definition and fix the affected nodes.
INOXSE8914	Internal error: buffer overflow
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXSE8915	The keywords index-shortname, adadsdbid, adadsfnr, adavocdbid and adavocfnr are not supported in the current version
Explanation	These keywords are not supported in the current version.
Action	Remove these keywords from the schema definition.

INOXSE8917	Internal error: doctype without root element
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXSE8918	Internal error: unknown object type
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXSE8920	Internal error: unknown mapping type
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXSE8921	ino:format or ino:length specified with SQL mapping
Explanation	ino:format and ino:length must not be specified with SQL mapping.
Action	Correct the schema definition.
INOXSE8922	Value has to be a number
Explanation	The given value could not be converted to a number.
Action	Correct the schema definition.
INOXSE8923	Specified number larger than allowed maximum
Explanation	The specified number was too large.
Action	Correct the schema definition.
INOXSE8924	Invalid doctype option specified
Explanation	An illegal value was specified for ino:options in the <ino:doctype> element.
Action	Correct the schema definition.
INOXSE8926	Collection name missing or invalid
Explanation	The name supplied in the ino:name attribute of the <ino:collection> element was either illegal or missing.
Action	Check the schema document.

INOXSE8927	Doctype name missing or invalid
Explanation	The name supplied in the ino:name attribute of the <ino:doctype> element was either illegal or missing.
Action	Correct the schema definition.
INOXSE8929	The node name specified does not conform to the XML specification
Explanation	The name specified in the ino:name attribute of an <ino:node> element does not conform to the XML specification.
Action	Correct the schema definition.
INOXSE8930	Doctype specified without any nodes
Explanation	Each doctype must have at least a root node.
Action	Correct the schema definition.
INOXSE8931	Node key missing
Explanation	The required ino:key attribute was missing for a <ino:node> element.
Action	Correct the schema definition.
INOXSE8932	Node object type missing
Explanation	The required ino:obj-type attribute was missing for a <ino:node> element.
Action	Correct the schema definition.
INOXSE8933	Node parent missing
Explanation	The required ino:parent attribute was missing for a <ino:node> element.
Action	Correct the schema definition.
INOXSE8934	Doctype contains multiple root nodes
Explanation	Each doctype must contain exactly one root node.
Action	Correct the schema definition.
INOXSE8935	Doctype contains no root nodes
Explanation	Each doctype must contain exactly one root node.
Action	Correct the schema definition.

INOXSE8937	Invalid parent reference
Explanation	The ino:parent attribute of an <ino:node> element did not point to another node.
Action	Correct the schema definition.
INOXSE8938	Invalid node option specified
Explanation	An illegal value was specified for ino:options in an <ino:node> element.
Action	Correct the schema definition.
INOXSE8939	Adabas dbid value too large
Explanation	The value specified for an Adabas database ID was too large.
Action	Correct the schema definition.
INOXSE8940	Adabas fnr value too large
Explanation	The value specified for an Adabas file number was too large.
Action	Correct the schema definition.
INOXSE8941	Length value too large
Explanation	The length value specified for an Adabas field was too large.
Action	Correct the schema definition.
INOXSE8942	Internal error: invalid ID reference
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXSE8943	Internal error: bad query
Explanation	An internal error has occurred.
Action	Please contact your software supplier.
INOXSE8944	Object definition missing in the new schema definition
Explanation	One or more objects are missing in the schema definition although they are already defined in the data map. The current version does not support object deletion.
Action	Complete the schema definition.

INOXSE8945	Invalid type change
Explanation	Modification of type is not supported if type is CDATA.
Action	Fix the schema definition.
INOXSE8946	Shortname specified for ADAFile without adadsbid/fnr
Explanation	Shortname specified for ADAFile without adadsbid/fnr.
Action	Complete the schema definition.
INOXSE8947	Bad value for structure-index
Explanation	The specified value for structure-index of doctype is not supported.
Action	Fix the schema definition.
INOXSE8948	Attribute already declared
Explanation	An attribute is specified more than once.
Action	Fix the schema definition.
INOXSE8949	Different doctype and root element name
Explanation	The doctype and root element must have the same name.
Action	Fix the schema definition.
INOXSE8950	Too many indexes in schema
Explanation	The schema defines more than the maximum possible number of indexes.
Action	Adapt the schema definition. For example, you may use multipath indexes in order to reduce the number of indexes being created.
INOXSE8951	Too many elements/attributes for "lite" mapping"
Explanation	The schema defines more than the maximum possible number of elements/attributes for "lite" mapping".
Action	Correct the schema definition.
INOXSE8952	No more indexes available
Explanation	Attempted to create too many standard or text indexes in the schema definition.
Action	Remove standard or text indexes or use multi-path indexes where applicable.

INOXSE8953	Invalid node search type specified
Explanation	An illegal value was specified for the ino:search-type attribute.
Action	Correct the schema definition.
INOXSE8954	Scale value too large
Explanation	An illegal value was specified for the ino:scale attribute.
Action	Correct the schema definition.
INOXSE8955	Attribute missing
Explanation	There is a required attribute missing.
Action	Fix a schema definition.
INOXSE8956	Required node attribute missing
Explanation	One of the required attributes for the <ino:node> element is missing.
Action	Correct the schema definition.
INOXSE8957	Required doctype attribute missing
Explanation	One of the required attributes for the <ino:doctype> element is missing.
Action	Correct the schema definition.
INOXSE8958	Required collection attribute missing
Explanation	One of the required attributes for the <ino:collection> element is missing.
Action	Correct the schema definition.
INOXSE8959	Unknown node attribute specified
Explanation	An illegal attribute was specified for an <ino:node> element.
Action	Correct the schema definition.
INOXSE8960	Unknown doctype attribute specified
Explanation	An illegal attribute was specified for the <ino:doctype> element.
Action	Correct the schema definition.

INOXSE8961	Unknown collection attribute specified
Explanation	An illegal attribute was specified for the <ino:collection> element.
Action	Correct the schema definition.
INOXSE8962	Invalid or missing dbid parameter
Explanation	The explanation text in the < ino:messageline> element gives more information about the cause of the error.
Action	Correct the schema definition.
INOXSE8963	Invalid format value
Explanation	An illegal value was supplied in the ino:format attribute.
Action	Correct the schema definition.
INOXSE8964	Invalid object type value
Explanation	An illegal value was specified for the ino:obj-type attribute.
Action	Correct the schema definition.
INOXSE8965	Invalid data type value
Explanation	An illegal value was specified for the ino:data-type attribute.
Action	Correct the schema definition.
INOXSE8966	Invalid multiplicity value
Explanation	An illegal value was specified for the ino:multiplicity attribute.
Action	Correct the schema definition.
INOXSE8967	Invalid mapping type value
Explanation	An illegal value was specified for the ino:map-type attribute.
Action	Correct the schema definition
INOXSE8968	Invalid shortname value
Explanation	An illegal value was specified for the ino:shortname attribute.
Action	Correct the schema definition.

INOXSE8969	Unknown element name in schema definition
Explanation	Only <ino:collection>, <ino:doctype>, and <ino:node> are allowed as elements in a schema definition.
Action	Correct the schema definition.
INOXSE8970	Duplicate key value in schema definition
Explanation	The ino:key values must be unique within a schema definition.
Action	Correct the schema definition.
INOXSE8971	Invalid primary key reference in schema definition
Explanation	Every column reference in a primary definition for SQL table mapping needs to be declared as an SQL column mapping for one node in a subtree of the SQL table mapped node.
Action	Correct the schema definition.
INOXSE8978	Bad value for compression
Explanation	The specified value for compression of the doctype is not supported.
Action	Fix the schema definition.
INOXSE8979	Collection is currently used by another user
Explanation	The request cannot be executed because at least one of the affected collections is currently held by another user.
Action	Repeat the request.
INOXSE8980	Server extensions: external name and module name / function name are mutually exclusive
Explanation	Do not specify both external name and module name/function name for a server extension.
Action	Correct the schema definition.
INOXTE7400	Internal error
Explanation	A text retrieval internal error has occurred.
Action	Please contact your software supplier.

INOXTE7401	Empty search term
Explanation	An empty-valued search term is specified.
Action	Please specify a non-empty search term in the query.
INOXTE7402	Empty search token(s)
Explanation	One or more empty search tokens are specified.
Action	Please specify non-empty search tokens in the query.
INOXTE7403	Empty search term in word function
Explanation	An empty-valued search term is specified in the word function.
Action	Please specify a non-empty search term in the word function.
INOXTE7404	Invalid search term
Explanation	An invalid search term is specified.
Action	Please specify a valid search term in the query.
INOXTE7405	Invalid search token
Explanation	One or more invalid search tokens are specified.
Action	Please specify valid search tokens in the query.
INOXTE7406	Invalid search term in word function
Explanation	An invalid search term is specified in the word function.
Action	Please specify a valid search term in the word function.
INOXTE7407	Maximum number of search tokens exceeded
Explanation	The derived search tokens from the search term or specified search tokens have exceeded the maximum number allowed.
Action	Please correct your search term/tokens in the query.
INOXTE7408	Invalid wildcard usage
Explanation	Invalid wildcards are specified in the query.
Action	Please refer to Tamino documentation for more details.

INOXTE7409	Word function nesting
Explanation	Nesting of word functions is not allowed.
Action	Please correct the query.
INOXTE7410	Invalid highlighting marker
Explanation	Highlighting marker does not conform to an NCName.
Action	Please correct the marker parameter for the highlighting function.
INOXTE7411	Fragmented document reference
Explanation	Highlighting of document fragments is not supported.
Action	Please correct the query for the highlighting function.
INOXTE7412	Invalid node addressing
Explanation	Invalid node addressing of the document has occurred during the highlighting process.
Action	Please correct the query for the highlighting function.
INOXTE7413	No valid document node
Explanation	No valid document node is found for highlighting.
Action	Please correct the query for the highlighting function.
INOXTE7415	Invalid distance for proximity function
Explanation	The distance for a proximity function must be a positive integer.
Action	Correct the distance and try again.
INOXTE7416	index nonXML tsd:onTextInsert shadow X-Tension function not defined
Explanation	A shadow X-Tension function for the insertion of a non-XML text document was expected in the schema.
Action	Define a shadow X-Tension function tsd:onTextInsert in the schema.
INOXTE7417	index nonXML tsd:onBinaryInsert shadow X-Tension function not defined
Explanation	A shadow X-Tension function for the insertion of a non-XML binary object was expected in the schema.
Action	Define a shadow X-Tension function tsd:onBinaryInsert in the schema.

INOXTE7418	illegal phonrule definition
Explanation	The number of replace characters must not be higher than the number of characters to be replaced.
Action	Correct the phonrule(s) in question.
INOXTE7419	illegal stemrule definition
Explanation	The number of replace characters must not be higher than the number of characters to be replaced.
Action	Correct the stemrule(s) in question.
INOXXE8600	The group with name ino:admin may not contain any aclref elements
Explanation	The group with name ino:admin may not contain any aclref elements.
Action	Make sure that the group ino:admin contains no aclref elements and try again.
INOXXE8601	Not enough memory for the requested security operation
Explanation	Not enough memory for the requested security operation.
Action	Free up some memory resources and try executing the operation again.
INOXXE8602	This operation is not allowed for the special 2-Phase-Commit user
Explanation	This operation is not allowed for the special 2-Phase-Commit user.
Action	Make sure you specify a user with the needed privileges for this operation.
INOXXE8603	Namespace prefixes specified in ino:ace paths need to be defined
Explanation	Namespace prefixes specified in ino:ace paths need to be defined.
Action	Please specify a namespace definition for each namespace prefix and try again.
INOXXE8604	The aclref attribute may only reference existing documents
Explanation	The aclref attribute may only reference existing documents.
Action	Please check that only valid references to existing documents are specified in the aclref attribute.

INOXXE8610	Definitions for ino:userid, ino:groupname, and ino:aclname in the collection ino:security need to be unique
Explanation	Definitions for ino:userid, ino:groupname, and ino:aclname in the collection ino:security need to be unique.
Action	First delete the existing entry before loading the new one with the same name into the database.
INOXXE8611	Invalid path specified in an ino:ace element
Explanation	Invalid path specified in an ino:ace element. The path must consist of names that are valid for XML element or attribute names, separated by slashes.
Action	Please correct the path specified in the ino:ace element and try loading the security definitions again.
INOXXE8699	Administration command is not available
Explanation	An administration command is not available.
Action	Please contact your software supplier.
INOXYE9002	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9003	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9004	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9005	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9006 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9007 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9008 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9009 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9010 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9011 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9012 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9013 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9014	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9015	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9016	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9017	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9018	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9019	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9020	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9021	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9022 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9023 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9024 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9025 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9026 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9027 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9028 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9029 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9030	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9031	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9032	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9033	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9034	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9035	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9036	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9037	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9038 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9039 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9040 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9041 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9042 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9043 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9044 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9045 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9046	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9047	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9048	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9049	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9050	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9051	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9052	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9053	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9054 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9055 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9056 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9057 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9058 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9059 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9060 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9061 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9062	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9063	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9064	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9065	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9066	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9067	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9068	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9069	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9070 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9071 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9072 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9073 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9074 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9075 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9076 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9077 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9078	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9079	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9080	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9081	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9082	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9083	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9084	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9085	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9086 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9087 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9088 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9089 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9090 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9091 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9092 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9093 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9094	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9095	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9096	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9097	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9098	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9099	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9100	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9101	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9102 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9103 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9104 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9105 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9106 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9107 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9108 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9109 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9110	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9111	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9112	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9113	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9114	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9115	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9116	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9117	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9118 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9119 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9120 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9121 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9122 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9123 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9124 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9125 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9126	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9127	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9128	Doctype storage limit exceeded
Explanation	The storage limit for a single doctype was exceeded with regard to any of the following: -total number of documents -total collected size of documents -total number of occurrences of elements with reference index.
Action	Please contact your database administrator.
INOXYE9129	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9130	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9131	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9132	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9133	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9134 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9135 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9136 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9137 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9139 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9140 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9141 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9142 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9143	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9144	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9145	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9146	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9147	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9148	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9149	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9150	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9151	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9152	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9153	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9154	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9155	The requested document(s) could not be locked
Explanation	An _XQL request was issued with _LOCKWAIT=no and _ISOLATION=shared/protected. At least one of the requested documents was locked by another user, therefore the lock could not be granted immediately.
Action	Retry the query, or specify _LOCKWAIT=yes.
INOXYE9156	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9157	Locking conflict has occurred
Explanation	The concurrently active transactions have issued conflicting lock requests.
Action	No action required.
INOXYE9158	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9159	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9160	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9161	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9162	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9163	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9164	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9165	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9166	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9167 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9168 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9169 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9170 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9171 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9172 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9173 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9174 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9175	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9176	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9177	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9178	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9179	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9180	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9181	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9182	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9183 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9184 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9185 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9186 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9187 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9188 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9189 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9190 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9191	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9192	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9193	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9194	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9195	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9196	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9197	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9198	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9199	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9200	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9201	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9202	Unique constraint violated
Explanation	Tamino detected either a duplicate ino:docname or a duplicate value for a unique constraint.
Action	Either choose a unique ino:docname or modify the documents.
INOXYE9203	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9204	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9205	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9206	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9207	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9208	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9209	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9210	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9211	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9212	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9213	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9214	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9215 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9216 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9217 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9218 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9219 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9220 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9221 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9222 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9223	Failed to create an additional database container
Explanation	Tamino failed to create an additional database container. This might be caused for example by a full disk or if the auto-expand option is set to "no".
Action	Analyze and remove the cause of the error. Typically, the job log of the database session will provide more information. In the Tamino Manager, select the node "Job Monitor" below "Tamino", and view the job of the database session in the category "Running Jobs" or "Pending Alerts".
INOXYE9224	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9225	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9226	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9227	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9228	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9229	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9230 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9231 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9232 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9233 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9234 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9235 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9236 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9237 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9238	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9239	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9240	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9241	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9242	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9243	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9244	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9245	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9246 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9247 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9248 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9249 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9250 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9251 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9252 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9253 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9254	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9255	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9256	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9257	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9258	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9259	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9260	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9261	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9262 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9263 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9264 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9265 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9266 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9267 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9268 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9269 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9270	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9271	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9272	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9273	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9274	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9275	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9276	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9277	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.

INOXYE9278 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9279 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9280 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9281 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9282 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9283 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9284 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9285 **Internal database error has occurred**
Explanation An internal error occurred. This could result in incorrect data.
Action Please contact your software supplier.

INOXYE9286	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9287	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9288	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9289	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9290	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9291	Transaction aborted because it has taken too long
Explanation	The duration of the transaction has exceeded the maximum transaction duration. This can be caused by several circumstances: 1) The transaction could have done too much work to complete in the given time frame. 2) The number of transactions running in parallel has caused considerable delays in transaction execution. 3) The transaction might have waited for a resource that was held by another transaction for a very long time. In particular, this can happen if the number of XML work threads is too low. In this case, the transactions waiting for a resource block the XML work threads, and no XML work thread is available for the transaction holding the resource. 4) The transaction had to wait for a free XML work thread for a long time
Action	The maximum transaction duration and the number of XML work threads can be configured using the Tamino Manager.

INOXYE9292	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9293	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9294	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9295	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9296	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9297	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9298	Internal database error has occurred
Explanation	An internal error occurred. This could result in incorrect data.
Action	Please contact your software supplier.
INOXYE9484	Marked corrupt index for subsequent repair: collection name = COLL_NAME, node = NODE_PATH
Explanation	A corrupt index has been found and has been marked for index repair. It will not be used for query processing until it has been repaired.
Action	Repair indexes in the corresponding doctype using <code>_admin=ino:RepairIndex()</code> - then retry the operation and recreate the index if necessary.

INOXYE9485	Failed to prepare index marked as corrupt for subsequent repair index: collection name = COLL_NAME, node = NODE_PATH, reason = REASON
Explanation	An error occurred when attempting to prepare a corrupt index for a subsequent index repair.
Action	Please contact your software supplier.
INOXYE9486	Failed to mark index as corrupt due to a pending recreate index operation: collection name = COLL_NAME, node = NODE_PATH
Explanation	A corrupt index cannot be marked as corrupt while a recreate index operation or schema update is pending.
Action	Repair the indexes in the corresponding doctype using <code>_admin=ino:RepairIndex()</code> - then retry the operation and recreate the index if necessary.
INOXYE9487	Failed to mark index as corrupt due to recreate index operation in progress: collection name = COLL_NAME, node = NODE_PATH
Explanation	A corrupt index cannot be marked while a recreate index operation or schema update is in progress.
Action	Wait until recreate index operation or schema update on the corresponding doctype is finished, then retry the operation or recreate the index.
INOXYE9488	Error during index or constraint access
Explanation	An index or constraint is corrupted and must be recreated.
Action	Recreate all indexes and constraints of the doctype via <code>ino:RecreateIndex</code> admin command.
INOXYE9489	Error during index or constraint access
Explanation	An index or constraint is corrupted.
Action	Please contact your software supplier.
INOXYE9490	Error during index or constraint access
Explanation	An index or constraint is corrupted and must be recreated.
Action	Recreate the indexes and constraints via the <code>ino:RecreateIndex</code> admin command or <code>update define</code> .

INOXYE9491	Transaction aborted due to non-activity timeout
Explanation	The transaction has been aborted because there was no activity for a long time.
Action	The time period for non-activity timeout can be configured using the Tamino Manager (Property "non-activity timeout").
INOXYE9492	Transaction aborted due to administrator action
Explanation	The database administrator has cancelled this transaction.
Action	No action required.
INOXYE9493	Transaction aborted because journal space was too small
Explanation	The journal space could not accommodate all the information that was necessary to back out the update command.
Action	Enlarge the journal space.
INOXYE9494	Request terminated because it tried to modify a replication database
Explanation	The request was sent to a replication database. User requests are not allowed to modify a replication database; only the replication process can do this.
Action	Send your request to the master of this replication database.
INOXYE9495	Request terminated because the replication database is currently not up-to-date
Explanation	The database is set to replication type with 'Simultaneous Query', but the currently replicated log space of the server does not contain additional locking information. Therefore the database cannot process queries while it replicates updates of this log space. Simultaneous query will be enabled, however, when the log space of the current session of the master is replicated.
Action	Wait until the log space of a session is replicated that permits simultaneous queries. Alternatively, send your request to the master of this replication database.
INOXYE9496	Transaction aborted due to deadlock
Explanation	The lock requests of concurrent transactions have caused a deadlock.
Action	No action required.

INOXYE9497 **Transaction terminated because of ongoing replication process**
Explanation There is a replication process in progress that does not allow simultaneous queries.

Because the replication process always has top priority on a replication database, any user transactions that had been active were terminated.
Action Wait until the replication process has finished or starts another session that allows simultaneous queries.

Alternatively send your request to the master of this replication database.

INOXYE9498 **Request terminated due to database shutdown**
Explanation The request has been terminated because the database is being shut down.
Action No action required.

INOXYE9499 **Transaction aborted due to non-activity timeout or administration intervention**
Explanation The transaction has been aborted because there was no activity for a long time or because it was stopped by the database administrator.
Action The time period for non-activity timeout can be configured using the Tamino Manager (Property "non-activity timeout").

INOXYW9483 **Found indexes marked as corrupt which cannot be dropped - subsequent index repair with "continue" option required: collection name = COLL_NAME, doctype = DOCTYPE_NAME**
Explanation A Tamino doctype contains indexes which must not be dropped, e.g. because they are used to implement a unique constraint.
Action Issue `_admin=inoRepairIndex()` with the "continue" option for the same doctype in order to fix the corrupt indexes.

L_SSL_certificate_file_desc – This is the file name of the server's certificate.

L_SSL_key_file_desc – This is the file name of the server's key.

L_SSL_password_desc – This is the pass phrase of the server's SSL key.

SSL certificate file – SSL certificate file

SSL key file SSL key file

SSL password SSL password

25 Tamino Adapter Messages

TAI1001	Server not available
Explanation	The specified server is not available or not reachable
Action	Check whether the server is reachable. Make sure the server url points to the database
TAI1004	Internal server error
Explanation	internal server error
Action	contact software vendor with Integration Server error log
TAI1101	Schema name missing
Explanation	Schema name for this service is mandatory
Action	Supply schema name
TAI1102	Collection name missing
Explanation	Collection name for this service is mandatory
Action	Supply collection name
TAI1103	Record name missing
Explanation	When the result type of the select service is set to "IS Record", doctype name is required
Action	Supply the valid IS document type name

TAI1104	Package name missing
Explanation	Package name for this service is mandatory
Action	Supply package name
TAI1105	Folder name missing
Explanation	Folder name for this service is mandatory
Action	Supply folder name
TAI1106	Query missing
Explanation	Query text for this service is mandatory
Action	Supply Query
TAI1107	Doctype name missing
Explanation	Doctype name for this service is mandatory
Action	Supply doctype name
TAI1201	Could not insert,as the document doesn't have compliance with specified schema
Explanation	The document structure should complaince with the specified schema.
Action	Make sure the content of document is compliance with the specified schema.
TAI1204	document(s) cannot be modified with the current lock mode settings
Explanation	Document cannot be modified/deleted with shared lock mode.
Action	set appropriate lock mode which is applicable for this operation. refer Tamino documentation
TAI1205	Invalid query
Explanation	The supplied XQuery is not the valid one
Action	Correct the errors in query. Refer detailed error message for reported errors
TAI1206	Invalid collection
Explanation	The given collection name is not available in the connected Tamino server
Action	Make sure the collection name is valid and available in the connected Tamino Server

TAI1207	Invalid doctype
Explanation	The supplied doctype is not defined.
Action	Make sure the doctype name is valid and available in the connected Tamino server
TAI1212	Invalid schema content
Explanation	The supplied schema is not compliant with the connected Tamino server
Action	Make sure the schema is compliance with the connected Tamino server. Refer Tamino documentation for more details.
TAI1301	Could not run wM built-in services
Explanation	The current ACL setting for the user might not sufficient to execute those reported services
Action	Give appropriate ACL settings for the reported built-in services

26 Tamino Tools Messages

TAJACE0006	Error preparing the XQuery ({0}, {1}, {2}, {3})
Explanation	Error in preparing the XQuery
Action	See the error information in the error
TAJCME0110	keystore {0} does not exist
Explanation	With using SSL connection with keystore and truststore, the properties of the keystore/truststore point to a non existing file
Action	Adjust your SSL properties
TAJCME0111	truststore is not specified
Explanation	At SSL connection the mandatory trustore property (either a custom or a system property) is not specified
Action	Set the required SSL property to a trustore
TAJCME0112	error during loading keystore {0}, type: {1}
Explanation	An error has occurred during opening the keystore for a SSL connection.
Action	Check if there is a valid keystore with given type, maybe check the causing exception in the stack
TAJCNE0207	Invalid userID or password
Action	Please check the supplied user ID and password

TAJIVE0320 **The database you are using is not configured to accept SecurityTokens**

TAJWSE1506 **Access with SecurityToken not supported with WSL Invocation**

Explanation Access with SecurityToken not supported with WSL Invocation

Action use username and password access

XPLHEE0001 **No browser is defined.**

Explanation An HTML browser is not defined in the property file.

Action Check your configuration and set the HTML browser in the property file.

XPLHEE0002 **Help cannot be displayed.**

Explanation The browser for displaying the online documentation could not be started.

Action See the details for more information about the problem.

XPLHEE0003 **Help cannot be displayed.**

Explanation A required help file could not be found or is invalid.

Action See the details for more information about the problem.

XPLXPE0000 **Creation of the collection "{0}" failed.**

Explanation The database is not connected.

Action Close the dialog and connect to the database, then try again.

XPLXPE0001 **Creation of the collection "{0}" failed.**

Explanation An unexpected exception occurred.

Action See the details for more information about the problem.

XPLXPE0005 **Could not write the data to the file {0}.**

Explanation Probably, you do not have write access to the file.

Action Solve the problem and retry.

XPLXPE0006	Deletion of the collection "{0}" failed.
Explanation	An exception occurred.
Action	See the details for more information about the problem.
XPLXPE0007	Deletion of the collection "{0}" failed.
Explanation	An unexpected exception occurred.
Action	See the details for more information about the problem.
XPLXPE0008	File name is not valid.
Explanation	The file does not seem to be a valid file or could not be found.
Action	Enter a correct file name.
XPLXPE0009	Creation of the collection "{0}" failed.
Explanation	An exception occurred.
Action	See the details for more information about the problem.
XPLXPE0010	Unable to save or write object to "{0}".
Explanation	An I/O exception occurred during saving data to a temporary file. Maybe the "Open Location" (see "Tools Options") does not contain a valid directory path.
Action	Check the existence of the directory in the displayed temporary file name. If the directory does not exist try to change it by changing the "Open Location" (see "Tools Options").
XPLXPE0011	Unable to write object to existing file "{0}".
Explanation	The file you have selected already exists but cannot be overwritten due to accessibility reasons. For example, the file may be read-only.
Action	Ensure that you have write access to the selected file or select a different file to write to.
XPLXPE0012	The instance "{0}" cannot be deleted.
Explanation	The underlying service received an exception. See the details for more information about the problem and for recommended actions.
Action	Contact your software supplier support.

XPLXPE0013	The file "{0}" cannot be inserted as an instance.
Explanation	The underlying service received an exception. See the details for more information about the problem and for recommended actions.
Action	Contact your software supplier support.
XPLXPE0014	The schema "{0}" cannot be undefined.
Explanation	The underlying service received an exception. See the details for more information about the problem and for recommended actions.
Action	Contact your software supplier support.
XPLXPE0015	The file "{0}" cannot be defined as a schema.
Explanation	The underlying service received an exception. See the details for more information about the problem and for recommended actions.
Action	Contact your software supplier support.
XPLXPE0016	The system cannot create a new query object.
Explanation	The system could not create a new query object using the internal material service.
Action	Contact your software supplier support.
XPLXPE0017	The specified file "{0}" could not be read into a query object. Make sure that the content of the file has the correct XML structure.
Explanation	A query file must specify the query in a specific XML structure. If the structure of the file is not correct, it cannot be read.
Action	Correct the structure of the file or choose a different file.
XPLXPE0018	The specified file "{0}" could not be closed after reading.
Explanation	An internal exception occurred during closing of the file. See the details for more information about the problem and for recommended actions.
Action	Contact your software supplier support.
XPLXPE0019	The specified file "{0}" could not be closed after reading.
Explanation	An internal exception occurred during closing of the file. See the details for more information about the problem and for recommended actions.
Action	Contact your software supplier support.

XPLXPE0020	Updating the selected instance with the file "{0}" could not be completed successfully.
Explanation	The underlying service received an exception. See the details for more information about the problem and for recommended actions.
Action	Contact your software supplier support.
XPLXPE0021	A runtime exception occurred. See the details for the trace.
Explanation	The X-Plorer received an unexpected exception.
Action	Contact your software supplier support.
XPLXPE0022	The operation could not be completed because the transaction timed out. Try again.
Explanation	The transaction was aborted due to a timeout.
Action	Try again. If the problem persists, contact your software supplier support.
XPLXPE0023	The operation could not be completed because the database connection timed out. Try disconnecting and reconnecting.
Explanation	The database connection was aborted due to a timeout.
Action	Disconnect the database and connect again. If the problem persists, contact your software supplier support.
XPLXPE0024	The operation could not be completed due to a timeout.
Explanation	The operation could not be completed due to a timeout.
Action	Try again or contact your software supplier support.
XPLXPE0025	The schema cannot be defined.
Explanation	The underlying service received an exception. See the details for more information about the problem and for recommended actions.
Action	Contact your software supplier support.
XPLXPE0026	Help cannot be displayed.
Explanation	The browser for displaying the online documentation could not be started.
Action	See the details for more information about the problem.

XPLXPE0027	No browser is defined.
Explanation	An HTML browser is not defined in the property file.
Action	Check your configuration and set the HTML browser in the property file.
XPLXPE0028	Help cannot be displayed.
Explanation	A required help file could not be found or is invalid.
Action	See the details for more information about the problem.
XPLXPE0029	No name has been specified for tool number "{0}".
Explanation	Each tool that you add and customize requires a (non-empty) name.
Action	Enter a (non-empty) name for this tool.
XPLXPE0030	No command has been specified for tool "{0}".
Explanation	Each tool that you add and customize requires a (non-empty) command.
Action	Enter a (non-empty) command for this tool.
XPLXPE0031	The specified tool icon "{0}" for tool "{1}" does not exist.
Explanation	If you specify a tool icon, it must be an existing image file (e.g. .gif).
Action	Enter the path to an existing image file.
XPLXPE0032	The specified command "{0}" for tool "{1}" does not exist.
Explanation	The command must either be an existing application file or command script file.
Action	Enter an existing application file or command script file.
XPLXPE0033	No arguments have been specified for tool "{0}".
Explanation	Arguments must be specified for tools which apply to objects of a certain type.
Action	Enter a list of (non-empty) arguments.
XPLXPE0034	You must define either the argument "{0}", "{1}" or "{2}" for the tool "{3}".
Explanation	For tools which apply to objects of a certain type, you must provide object-specific arguments. This enables each tool to access the object to which it applies.
Action	Enter either one of the given arguments.

XPLXPE0035	No tool has been specified for non-XML instances with media type "{0}" and file extension "{1}".
Explanation	To open the selected object/document, an appropriate tool must be specified and it must be available.
Action	From the Tools menu, choose Customize and specify a tool for the type of object you have selected.
XPLXPE0036	The server URL is missing or invalid.
Explanation	To define a schema from a database, a non-empty and valid server URL is required.
Action	Enter a non-empty and valid server URL.
XPLXPE0037	The database name is missing or invalid.
Explanation	To define a schema from a database, a non-empty and valid database name is required.
Action	Enter a non-empty and valid database name.
XPLXPE0038	The collection name is missing or invalid.
Explanation	To define a schema from a database, a non-empty and valid collection name is required.
Action	Enter a non-empty and valid collection name.
XPLXPE0039	The schema name is missing or invalid.
Explanation	To define a schema from a database, a non-empty and valid schema name is required.
Action	Enter a non-empty and valid schema name.
XPLXPE0041	The schema cannot be updated with the schema from file "{0}".
Explanation	The underlying service received an exception. See the details for more information about the problem and for recommended actions.
Action	Contact your software supplier support.
XPLXPE0042	The schema "{0}" cannot be updated.
Explanation	The underlying service received an exception. See the details for more information about the problem and for recommended actions.
Action	Contact your software supplier support.

XPLXPE0043	The file name is not valid.
Explanation	The file does not seem to be a valid file or could not be found.
Action	Enter a correct file name.
XPLXPE0044	The server URL is missing or invalid.
Explanation	To update a schema from a database, a non-empty and valid server URL is required.
Action	Enter a non-empty and valid server URL.
XPLXPE0045	The database name is missing or invalid.
Explanation	To update a schema from a database, a non-empty and valid database name is required.
Action	Enter a non-empty and valid database name.
XPLXPE0046	The collection name is missing or invalid.
Explanation	To update a schema from a database, a non-empty and valid collection name is required.
Action	Enter a non-empty and valid collection name.
XPLXPE0047	The schema name is missing or invalid.
Explanation	To update a schema from a database, a non-empty and valid schema name is required.
Action	Enter a non-empty and valid schema name.
XPLXPE0048	The collection "{0}" can only contain schemas of type "{1}", but the schema "{2}" has type "{3}".
Explanation	For collection and schema the same schema type is required.
Action	Select collection and schema with the same schema type.
XPLXPE0049	The collection "{0}" can only contain schemas of type "{1}", but the schema "{2}" has type "{3}".
Explanation	The same schema type is required for collection and schema.
Action	Select collection and schema with the same schema type.

XPLXPE0050	You must define the argument "{0}" for the tool "{1}".
Explanation	For tools which apply to objects of a certain type, you must provide object-specific arguments. This enables each tool to access the object to which it applies.
Action	Enter the given argument.
XPLXPE0051	The name of the new schema does not match that of the selected schema. The name of the selected schema is "{0}" and the name of the new schema is "{1}".
Explanation	An update of a selected schema can only be executed if the new schema has the same name and type.
Action	Select the schema with the same name as the new schema.
XPLXPE0052	No tool has been specified for the object type "{0}".
Explanation	To open the selected object/document, an appropriate tool must be specified and it must be available.
Action	From the Tools menu, choose Customize and specify a tool for the type of object you have selected.
XPLXPE0053	Refresh failed due to an exception.
Explanation	An exception occurred. Maybe the object to be refreshed has been deleted by another user meanwhile.
Action	See the details for more information about the problem.
XPLXPE0054	The tool "{0}" is already defined for opening (double-clicking) objects with object type "{1}". Do you want to use the tool "{2}" to open objects of this type?
Explanation	Only one tool can be used to open (double-click) an object of a specific object type.
Action	Select only one tool for opening (double-clicking) an object of a specific object type.
XPLXPE0055	An exception occurred while trying to fetch the instances of doctype {0}.
Explanation	The query used to fetch the instances does not seem to be valid.
Action	Check your filter string.
XPLXPE0056	An exception occurred while fetching the instances of doctype {0}.
Explanation	See the details for more information about the problem.
Action	Try to refresh the group of instances. If this does not help, reconnect to the database.

XPLXPE0057	An exception occurred while fetching the instances of the query result.
Explanation	See the details for more information about the problem.
Action	Try to execute the query once more. If this does not help, reconnect to the database.
XPLXPE0058	An exception occurred while retrieving the content of instance "{0}".
Explanation	See the details for more information about the problem.
Action	Try to refresh the group of instances.
XPLXPE0059	The schema "{0}" has an invalid format: The {1} name in element "{2}" is missing or invalid.
Explanation	See the details for more information about the problem.
Action	Correct or add missing schema element or attribute.
XPLXPE0060	The schema "{0}" has an invalid format: The {1} name in element "{2}" is missing or invalid.
Explanation	See the details for more information about the problem.
Action	Correct or add the missing schema element or attribute.
XPLXPE0061	An exception occurred while retrieving the schemas of collection "{0}".
Explanation	See the details for more information about the problem.
Action	Try to refresh the collection. If this does not help, reconnect to the database.
XPLXPE0063	The customization of the external tools could not be saved.
Explanation	See the details for more information about the problem.
Action	Remove the problem and retry.
XPLXPE0064	The connection to the database is no longer available. The database will be disconnected.
Explanation	The underlying service received an exception. See the details for more information about the problem and for recommended actions.
Action	Check whether server and database are running. Reconnect and try again.

XPLXPE0065	Authentication failed.
Explanation	A connection to the database with the given authentication parameters could not be established.
Action	Specify valid authentication parameters: specify user ID and password and try again. If a domain is required, specify domain and user ID, separated by the special character "/".
XPLXPE0066	Reading the file {0} failed.
Explanation	An initialization file could not be read.
Action	See the details for more information about the problem.
XPLXPE0067	An exception occurred while opening the database "{0}".
Explanation	An exception occurred.
Action	See the details for more information about the problem.
XPLXPE0068	An exception occurred while opening the collection "{0}".
Explanation	An exception occurred.
Action	See the details for more information about the problem.
XPLXPE0069	The connection to the file "{0}" in the file system cannot be closed and associated system resources may not be released.
Explanation	The underlying service received an IOException. The file may be locked in the file system while the X-Plorer is running.
Action	See the details for more information about the problem. After closing the X-Plorer, the file in the file system should be unlocked.
XPLXPE0070	The connection to the database, that was opened for the XQuery tool could not be closed correctly.
Explanation	The underlying service received an exception. See the details for more information about the problem and for recommended actions.
Action	Reconnect and try again.

XPLXPE0071 **The connection to the file "{0}" in the file system cannot be closed and associated system resources may not be released.**

Explanation The underlying service received an IOException. The file may be locked in the file system while the X-Plorer is running.

Action See the details for more information about the problem. After closing the X-Plorer, the file in the file system should be unlocked.

XPLXPE0072 **Modification of Schema Usage for the collection "{0}" failed.**

Explanation Following Schema Usage modifications are permitted for a Collection: \nRequired -> Optional \nProhibited -> Optional

Action See the Explanation and Details for more information.

XPLXPE0073 **Modification of Schema Usage for the collection "{0}" failed.**

Explanation An unexpected exception occurred

Action See the Details for more information.

XPLXPE0074 **Modification of Schema Usage for the collection "{0}" failed.**

Explanation The database is not connected.

Action Close the dialog and connect to the database, then try again.

XPLXPE0083 **The user does not have enough rights to access the contents of this collection.**

XPLXPE0084 **The server URL is missing or invalid.**

XPLXPI0001 **The server name is missing or not a valid URL.**

Explanation To connect to a database, a non-empty and valid server URL is needed.

Action Enter a non-empty and valid server URL.

XPLXPI0002 **The database name is missing.**

Explanation To connect to a database, a non-empty database name is required.

Action Enter a non-empty database name.

XPLXPI0003	The user name is missing.
Explanation	To connect to a database, a non-empty user name is required.
Action	Enter a non-empty user name.
XPLXPI0004	The password is missing.
Explanation	To connect to a database, a non-empty password is required.
Action	Enter a non-empty password.
XPLXPI0005	The collection name is missing or invalid.
Explanation	To create a new collection, a non-empty and valid collection name is required.
Action	Enter a non-empty and valid collection name.
XPLXPI0006	The file path is missing.
Explanation	To save the object, a non-empty file path (such as c:\temp) is required.
Action	Enter a non-empty file path.
XPLXPI0007	The file extension is missing.
Explanation	To save the object, a non-empty file extension (such as .xml) is required.
Action	Enter a non-empty file extension.
XPLXPI0008	The file name is missing.
Explanation	To save the object, a non-empty file name (such as myFileName) is required.
Action	Enter a non-empty file name.
XPLXPI0009	The number of instances per pack is missing or invalid.
Explanation	The field "Number of instances per pack" must contain a valid number from 1 to 999.
Action	Enter a valid number from 1 to 999.
XPLXPI0010	The maximum number of kept instances is missing or invalid.
Explanation	The field "Maximum number of kept instances" must contain a valid number from 1 to 999.
Action	Enter a valid number from 1 to 999.

XPLXPI0011	The collection "{0}" already exists.
Explanation	A collection with the specified name already exists. Collection names must be unique within a database.
Action	Enter a different non-empty and valid collection name.
XPLXPI0012	The number of instances per pack is missing or invalid.
Explanation	The field "Number of instances per pack" must contain a valid number from 1 to 999.
Action	Enter a valid number from 1 to 999.
XPLXPI0013	The maximum number of kept instances is missing or invalid.
Explanation	The field "Maximum number of kept instances" must contain a valid number from 1 to 999.
Action	Enter a valid number from 1 to 999.
XPLXPI0014	The open location is missing or invalid.
Explanation	The field "Open location" must contain a valid location.
Action	Enter a valid location.
XPLXPI0016	The number of instances per pack is missing or invalid.
Explanation	The field "Number of instances per pack" must contain a valid number from 1 to 999.
Action	Enter a valid number from 1 to 999.
XPLXPI0017	The maximum number of kept instances is missing or invalid.
Explanation	The field "Maximum number of kept instances" must contain a valid number from 1 to 999.
Action	Enter a valid number from 1 to 999.
XPLXPI0062	Unable to display contents due to presence of special characters in folder name(s).
Explanation	Folder name contains space or \ character(s).
Action	Remove special character(s) from folder name(s).

XPLXPW0001	The connection to the server could not be established.
Explanation	See the details for more information about the problem and for recommended actions.
Action	Check whether server and database are running.
XPLXPW0002	The connection to the server could not be established.
Explanation	See the details for more information about the problem.
Action	Check whether server and database are running.
XPLXPW0006	File name is not valid.
Explanation	The file does not seem to be valid or could not be found.
Action	Enter a correct file name.
XPLXPW0007	The media type is missing or invalid.
Explanation	To insert a non-XML file, you must enter a valid media type.
Action	Enter a valid media type and try again.
XPLXPW0008	File name is missing.
Explanation	You must enter a file name.
Action	Enter a correct file name.
XPLXPW0009	The database "{0}" of the server "{1}" is not connected. Do you want to connect to this database?
Explanation	You must be connected to the source database of the schema.
Action	Connect to the database.
XPLXPW0010	The specified doctype "{0}" could not be found in the collection.
Explanation	To insert a non-XML instance, you must specify a valid doctype.
Action	Check and correct the name of the doctype or select one from the list of doctypes.
XPLXPW0011	The specified doctype "{0}" is an XML doctype. Non-XML instances can only be inserted in non-XML doctypes.
Explanation	To insert a non-XML instance, you must specify a non-XML doctype.
Action	Specify a non-XML doctype.

XPLXPW0012	Doctype entry is missing. Enter a valid doctype.
Explanation	To insert a non-XML instance, you must specify a (non-XML) doctype.
Action	Specify a (non-XML) doctype.
XPLXPW0013	The URL containing the server name "{0}" is not valid. Correct your entries.
Explanation	The entries server, database and collection must form a valid URL, which is not the case.
Action	Check your entries and correct them.
XPLXPW0014	Database "{0}" could not be found on the server. Check your entry in the database field.
Explanation	The database entry must be a valid database name and the database must be running on the specified server.
Action	Check whether the database entry is valid and whether the database is running.
XPLXPW0015	Could not connect to the selected database "{0}". Check your entry in the database field.
Explanation	The database entry must be a valid database name on the specified server.
Action	Try to connect to this database.
XPLXPW0016	Collection "{0}" could not be found in the specified database on the specified server. Enter a valid collection name.
Explanation	The collection entry must be a valid collection name in the specified database.
Action	Check whether the collection entry is valid.
XPLXPW0017	Server "{0}" could not be found. Enter a valid server name.
Explanation	The server name must be valid.
Action	Check whether the server entry is valid.
XPLXPW0018	The server input field must contain a value. Enter a valid server name.
Explanation	The server field must contain a value.
Action	Enter a value in the server field.

XPLXPW0019	The database input field must contain a value. Enter a valid database name.
Explanation	The database field must contain a value.
Action	Enter a value in the database field.
XPLXPW0020	The collection input field must contain a value. Enter a valid collection name.
Explanation	The collection field must contain a value.
Action	Enter a value in the collection field.
XPLXPW0021	The query editor must contain a value. Enter a query.
Explanation	Before you can execute a query, you must enter a query string.
Action	Enter a query in the query editor.
XPLXPW0022	You must specify a correct file name. The file could not be found.
Explanation	To open a query, you must enter a correct file name.
Action	Enter a valid file name.
XPLXPW0023	File name "{0}" is not valid.
Explanation	The file does not seem to be a valid file or could not be found.
Action	Enter a correct file name.
XPLXPW0024	File name is missing.
Explanation	You must enter a file name.
Action	Enter a correct file name.
XPLXPW0025	File name "{0}" is not valid.
Explanation	The file does not seem to be a valid file or could not be found.
Action	Enter a correct file name.
XPLXPW0026	The database "{0}" is not connected. Do you want to connect to this database?
Explanation	You must be connected to the source database of the schema.
Action	Connect to the database.

XPLXPW0027	The database "{0}" does not support XQuery.
Explanation	This version of the database does not support this kind of query.
Action	Choose another query tool (e.g. X-Query tool) or update the database.
XPLXPW0028	Operation not supported as the user does not have the necessary privileges.
Explanation	User does not have enough privileges to perform the requested operation.
Action	Contact database administrator.
XPLXQE0001	The selected file could not be found.
Explanation	An internal error leads to the problem that the file cannot be opened.
Action	Please try again or contact your software supplier support.
XPLXQE0002	The selected file could not be read.
Explanation	An internal error leads to the problem that the file cannot be read.
Action	Please try again or contact your software supplier support.
XPLXQE0003	The selected file could not be closed.
Explanation	An internal error leads to the problem that the file cannot be closed.
Action	Please try again or contact your software supplier support.
XPLXQE0004	The system cannot create a new query object.
Explanation	The system could not create a new query object using the internal material service.
Action	Contact your software supplier support.
XPLXQE0005	The specified file "{0}" could not be closed after reading.
Explanation	An internal exception occurred during closing of the file. See the details for more information about the problem and for recommended actions.
Action	Contact your software supplier support.
XPLXQE0006	The specified file "{0}" could not be read into a query object. Make sure that the content of the file has the correct XML structure.
Explanation	A query file must specify the query in a specific XML structure. If the structure of the file is not correct, it cannot be read.
Action	Correct the structure of the file or choose a different file.

XPLXQE0007	The specified file "{0}" could not be closed after reading.
Explanation	An internal exception occurred during closing of the file. See the details for more information about the problem and for recommended actions.
Action	Contact your software supplier support.
XPLXQE0008	The specified query could not be processed. Enter a valid query.
Explanation	Either the query does not seem to be valid
Action	Enter a valid query.
XPLXQE0009	The operation could not be completed because the transaction timed out. Try again.
Explanation	The transaction was aborted due to a timeout.
Action	Try again. If the problem persists, contact your software supplier support.
XPLXQE0010	The operation could not be completed because the database connection timed out. Try disconnecting and reconnecting.
Explanation	The database connection was aborted due to a timeout.
Action	Disconnect the database and connect again. If the problem persists, contact your software supplier support.
XPLXQE0011	The operation could not be completed due to a timeout.
Explanation	The operation could not be completed due to a timeout.
Action	Try again or contact your software supplier support.
XPLXQE0012	A runtime exception occurred. See the details for the trace.
Explanation	The X-Plorer received an unexpected exception.
Action	Contact your software supplier support.
XPLXQE0013	The operation could not be completed because an exception occurred.
Explanation	The XQuery Tool received an exception.
Action	Contact your software supplier support.

XPLXQI0007	The maximum number of characters taken from each query row is too high.
Explanation	The maximum number of characters taken from each query history entry must be lower than or equal to the maximum number of characters in each query history entry.
Action	Enter a smaller value for the maximum number of characters taken from each row of the query.
XPLXQW0001	You must specify a correct file name. The file could not be found.
Explanation	To open a query, you must enter a correct file name.
Action	Enter a valid file name.
XPLXQW0002	File name "{0}" is not valid.
Explanation	The file does not seem to be a valid file or could not be found.
Action	Enter a correct file name.
XPLXQW0003	The URL containing the server name "{0}" is not valid. Correct your entries.
Explanation	The entries server, database and collection must form a valid URL, which is not the case.
Action	Check your entries and correct them.
XPLXQW0004	Server "{0}" could not be found. Enter a valid server name.
Explanation	The server name must be valid.
Action	Check whether the server entry is valid.
XPLXQW0005	Database "{0}" could not be found on the server. Check your entry in the database field.
Explanation	The database entry must be a valid database name and the database must be running on the specified server.
Action	Check whether the database entry is valid and whether the database is running.
XPLXQW0006	Could not connect to the selected database "{0}". Check your entry in the database field.
Explanation	The database entry must be a valid database name on the specified server.
Action	Try to connect to this database.

XPLXQW0007	Collection "{0}" could not be found in the specified database on the specified server. Enter a valid collection name.
Explanation	The collection entry must be a valid collection name in the specified database.
Action	Check whether the collection entry is valid.
XPLXQW0008	The server input field must contain a value. Enter a valid server name.
Explanation	The server field must contain a value.
Action	Enter a value in the server field.
XPLXQW0009	The database input field must contain a value. Enter a valid database name.
Explanation	The database field must contain a value.
Action	Enter a value in the database field.
XPLXQW0010	The database "{0}" does not support XQuery.
Explanation	This version of the database does not support this kind of query.
Action	Choose another query tool (e.g. X-Query tool) or update the database.
XPLXQW0011	The collection input field must contain a value. Enter a valid collection name.
Explanation	The collection field must contain a value.
Action	Enter a value in the collection field.
XPLXQW0012	The query editor must contain a value. Enter a query.
Explanation	Before you can execute a query, you must enter a query string.
Action	Enter a query in the query editor.
XSCEDE0057	Cannot convert to All or Choice. Contains duplicate element - "{0}"
Explanation	Neither All nor Choice may contain duplicate element names.
Action	Remove duplicate elements before converting sequence.

27

Trading Network Messages

1003	System property {0} is invalid: {1}. To correct the property, go to the TN Properties page of the WmTN package in the Integration Server Administrator, or edit the "packagesWmTNconfigproperties.cnf" file.
Explanation	The system property provided for Trading Networks is invalid.
Action	Correct the property in the Configure Properties page in My webMethods, or edit the 'IntegrationServer_directory\packages\WmTN\config\properties.cnf' file.
1008	"{0}" is required.
Explanation	Required input value is missing.
Action	Provide value for required input fields and try again.
1027	You have attempted to use a feature that is restricted by your license. To be able to use all product features, please contact webMethods or your webMethods OEM solution provider to upgrade to an unrestricted version of Trading Networks.
Explanation	User not allowed to create doctypes, attempt failed.
Action	To be able to use all product features, please contact Software AG Global Support to upgrade to an unrestricted version of Trading Networks.
1046	Error registering TN's XML content handler.
Explanation	Error while registering content handler for "text/xml".
Action	Contact Software AG Global Support.

1119	Encountered error while creating TN document
1157	New verify certificate set not added.
Explanation	In webMethods Trading Networks, if a verify certificate set is not added to a partner, this error shows up.
Action	Add the very certificate set to the partner and try again.
1158	New verify certificate set not updated.
Explanation	In webMethods Trading Networks, if the new verify certificate set for a partner is not updated, this error shows up.
Action	Ensure that the new verify certficate set for a partner is updated and try again.
1160W	Asset already exists in Trading Networks
Explanation	The asset selected for import already exists in Trading Networks.
Action	To overwrite the existing asset with the one in the imported file, select the "force" option during the import process.
1161E	An error occurred while retrieving package names.
Explanation	My webMethods encountered an error while displaying the names of Integration Server packages.
Action	Take appropriate action to resolve the problem described in the exception and try to perform the action again.
1162W	All processing rules were imported successfully. Processing rules that existed before the import were removed.
Explanation	All the processing rules present in the import file were added to the Trading Networks database. All processing rules that existed before the import process were removed from the database. This happens when the Replace Rule List option is selected during the import of Trading Networks data.
1166	Unable to delete doc type. There are some activity logs associated with this doc type. Either delete the associated activity logs or run this service again with "deleteLogs=true" to have them deleted automatically.
Explanation	Unable to delete doc type because there are some activity logs associated with this doc type.
Action	Either delete the associated activity logs or run this service again with "deleteLogs=true" to have them deleted automatically.

1203E	Error retrieving certificates for keystore alias {0} and key alias {1}. Check the keystore configuration in Integration Server.
Explanation	The keystore was modified or deleted in Integration Server, which caused the keystore mapping in Trading Networks to break.
Action	Check the keystore configuration in Integration Server. If the keystore does not exist in Integration Server, create the keystore. If the keystore mapping in Trading Networks is incorrect, select the correct keystore alias and key name for the certificate.
1204E	Error retrieving keystore aliases.
Explanation	Trading Networks could not retrieve the keystore from Integration Server.
Action	Check the keystore configuration in Integration Server. If the keystore does not exist in Integration Server, ask the Integration Server administrator to create the keystore.
1205E	Error retrieving key aliases for the keystore alias {0}.
Explanation	Trading Networks could not retrieve the keystore from Integration Server.
Action	Check the keystore configuration in Integration Server. If the keystore does not exist in Integration Server, ask the Integration Server administrator to create the keystore.
2017	Could not delete field definition
2020	Error occurred while publishing event messages to NERV.
2023	Error redefining type {0} ({1})
Explanation	Error while updating the document type.
Action	The exception is in the full message. Take appropriate action to resolve the problem described in the exception.
2061	Error initializing type cache.
Explanation	There may have been an SQLException that prevented the initialization of the document type cache.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

2069	Error while defining type {0} ({1}).
Explanation	The error encountered while defining the document type may be due to an SQLException or to a missing mandatory field.
Action	Look at the associated error message or stack trace in the logs and take appropriate action.
2103	MODIFY AND RESUBMIT
2120	Error initializing attribute cache.
Explanation	An SQLException may have prevented the attribute cache from being initialized.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
2174	Unable to import init.xml due to exception message: {0}. Manually import init.xml as described in the Installation Guide.
Explanation	An exception occurred while importing init.xml, as described in the message.
Action	Manually import init.xml as described in the Installation Guide.
2200...0	Error encountered while reading USER status from the database. Exception message: {0}.
Explanation	Encountered SQLException while reading user status from database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
2262	Processing of invitation failed. {0}
2263	User not created for the partner.
2264	Updating the partner status to Invited has failed.
2303	Exception encountered while getting TN assets dependency.
Explanation	In the webMethods Trading Networks Export Import feature using MWS, when webMethods Trading Networks fails to get the dependency of the asset type during export, this exception is thrown.
Action	You need to select the dependent asset and perform the export again.

2304	Exception encountered while exporting TN assets.The exception message is : {0}.
Explanation	In the webMethods Trading Networks Export Import feature using MWS, when webMethods Trading Networks fails to get the asset data during export, this exception is thrown.
Action	Contact your system administrator.
2305	Exception encountered while importing TN assets.The exception message is : {0}.
Explanation	In the webMethods Trading Networks Import feature using MWS, when webMethods Trading Networks fails to import data, this exception is thrown.
Action	Contact your system administrator.
2306	The import data file name is null or empty.
Explanation	In webMethods Trading Networks, when you try to import data and the import data file name is null or empty, this error is thrown.
Action	Import the data again after adding the import data file.
2307	The import data file {0} does not exist.
Explanation	In webMethods Trading Networks, when you try to import a data file but the file does not exist, this error is thrown.
Action	Ensure that the file is available and try again.
2308	The import file does not contain valid data.
Explanation	In webMethods Trading Networks, when you try to import a file and it does not contain valid data according to the type format, this error is thrown.
Action	Add a file that contains valid data according to the type format and try to import it again.
3011	(username={0})already exists.No new account created.Mapping done.
Explanation	While creating a partner account, Trading Networks found an existing user with the same name. No new account was created. Mapping was completed..
Action	Provide a unique name and try again.

3012	Encountered error while enabling the {0} package.
Explanation	This error shows up when trying to enable the WmTN package.
Action	Contact your system administrator.
3013	Encountered error while disabling the {0} package.
Explanation	This error shows up while trying to disable the WmTN package.
Action	Contact your system administrator.
3017	An error occurred while trying to insert document (doc id = {0}, sender id = {1}) into the database.
Explanation	Exception occurred during inserting the document into the database, possibly due to a database or usage error.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
3023	No such documents: {0}.
3024	Could not instantiate documents {0}.
3025E	Error occurred while reinitializing Trading Networks JDBC connection pool in Integration Server.
Explanation	Trading Networks reinitializes the JDBC connection pool when a connection error occurs. This reinitialization disconnects all connections to the Trading Networks database. An error occurred during the reinitialization.
Action	Use the Integration Server Administrator JDBC Pools page to reinitialize the Trading Networks JDBC connection pool.
3068	Error while persisting queue. For details check the full stack trace.
Explanation	In webMethods Trading Networks, while registering a queue, if there is any error in scheduling the queue, this error is thrown.
Action	Check the full stack trace or contact your system administrator.

3243	Cannot process message that is not javax.mail.internet.MimeMessage or javax.mail.internet.MimeBodyPart. Current message is: {0}
Explanation	Cannot parse the message as it is not a javax.mail.internet.MimeMessage or javax.mail.internet.MimeBodyPart.
Action	Check the error message and take action as appropriate.
4024	Invalid Receiver ID
Explanation	In webMethods Trading Networks, while setting the BizDoc envelope attribute, if the receiver ID is not a valid partner ID, this error is thrown.
Action	Enter a valid partner ID (for a receiver ID) and try again.
4168	Exception encountered while listing all the processing rules.
Explanation	Encountered an exception while getting the list of rules from the cache. Either the cache is not updated with data, or there is some exception in the database.
Action	The details of the exception is in the full message. Take appropriate action to resolve the problem described in the exception message.
4169	Access denied, as the User "{0}" does not have the privilege to {1} {2}.
Explanation	You do not have the required permission to take this action on the processing rule.
Action	Request that the Integration Server administrator assign the required permission.
4170	Error while recognizing the document.
Explanation	Error encountered while recognizing the document. The document may be corrupted.
Action	Check if the document is a valid XML document and not a corrupt document.
4177	{0} contacts deleted with ContactID {1}.
Explanation	Encountered data inconsistency issue while contact deletion. Expected exactly one matching contact.
Action	Contact Software AG Global Support.
4178	{0} addresses deleted with AddressID {1}.
Explanation	Encountered data inconsistency issue while address deletion. Expected exactly one matching address.
Action	Contact Software AG Global Support.

4179	{0} connections deleted with ID {1}.
Explanation	Encountered data inconsistency issue while destination deletion. Expected exactly one matching destination.
Action	Contact Software AG Global Support.
4209	Error encountered while getting the host ID
Explanation	The Trading Networks profile cache might be corrupted.
Action	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
4210	Error encountered while getting all the Processing Rule matches for the document.
Explanation	Encountered exception while retrieving rules from cache. The cache might not be updated.
Action	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message. Reload the WmTNWeb package.
4211	Error encountered while getting all the Delivery Services.
Explanation	Encountered exception while retrieving delivery services from the database.
Action	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
4212	Error encountered while getting RuleName with the name - {0}.
Explanation	The rule may have been deleted by someone in a different session.
Action	Refresh the rule cache by executing the search again.
4213	Error encountered while getting Last Change ID.
Explanation	This may be due to an exception while fetching the Last Change ID from the database.
Action	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
4214	Error encountered while getting Processing Rule with ID - {0}.
Explanation	The rule may have been deleted by someone in a different session.
Action	Refresh the rule cache by running the search again.

4215	Error encountered while changing the ordinality of the Processing Rule.
Explanation	Changing the ordering of the processing rules in another session might have caused an error while validating or updating the ordinal numbering in the database.
Action	Refresh the rule cache by executing the search again.
4216	Error encountered while deleting the processing rules.
Explanation	The rule might have been deleted by someone in a different session.
Action	Refresh the rule cache by executing the search again.
4217	Error encountered while updating the processing rule with Rule Name - {0}.
Explanation	The rule might have been deleted by someone in a different session.
Action	Refresh the rule cache by executing the search again.
4218	Error encountered while creating the processing rule with Rule Name - {0}.
Explanation	Error encountered while inserting the rule into the database.
Action	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
4219	Error encountered while querying the processing rules.
Explanation	The query would have failed while picking the rules. Check the database actions.
Action	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
4220	Access denied, as the User "{0}" does not have the permission to {1} processing rule.
Explanation	You do not have the permission to do the necessary action on the processing rule.
Action	Request that the Integration Server administrator assign the required permission.
4221	Access denied, as the User "{0}" does not have the permission to {1} processing rule - "{2}".
Explanation	You do not have the permission to do the necessary action on the processing rule.
Action	Request that the Integration Server administrator assign the required permission.

4228	Exception while changing the processing rule status.
Explanation	The rule might have been deleted by someone in a different session.
Action	Refresh the rule cache by executing the search again.
4237	Error encountered while getting the profiles associated with Profile Group.
Explanation	There might be a database error while retrieving the profile groups.
Action	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
4238	Access denied, as the User "{0}" does not have the permission to {1} processing rule - "{2}".
Explanation	You do not have the permission to do the necessary action on the processing rule.
Action	Request that the Integration Server administrator assign the required permission.
4241E	Processing rule "{0}" change status failed. Processing rule update collision detected. This rule has been modified by another user. Refresh your rule list and retry this operation.
Explanation	In webMethods Trading Networks, while changing the status of a processing rule, if it is modified by another user, this error is thrown.
Action	Refresh your rule list and try again.
4247E	Exception encountered while moving the processing rule. Invalid Ordinal given in Select Location.
Explanation	In webMethods Trading Networks, while moving the processing rule, if an invalid ordinal location is specified, this error is thrown.
Action	Specify a valid ordinal location and try again.
4258E	Error encountered while creating the processing rule with Rule Name - "{0}". Rule name already exists. Change the name and save again.
Explanation	In webMethods Trading Networks, while creating a processing rule, if the rule name already exists, this error is thrown.
Action	Ensure to give a unique processing rule name and try again.

4274E	Error encountered while querying for the delivery queues.
Explanation	In webMethods Trading Networks, if any error occurs while retrieving registered queues, this error is thrown.
Action	Contact your system administrator.
4305E	The following sender(s) and receiver(s) configured in the processing rule do not exist in the system. Sender(s):"{0}" Receiver(s):"{1}"
Explanation	An error occurred while trying to create or update a processing rule with senders and receivers that do not exist in Trading Networks.
Action	Ensure the senders and receivers are valid.
4306E	The following sender(s) configured in the processing rule do not exist in the system: "{0}"
Explanation	An error occurred while trying to create or update a processing rule with senders that do not exist in Trading Networks.
Action	Ensure the senders are valid.
4307E	The following receiver(s) configured in the processing rule do not exist in the system: "{0}"
Explanation	An error occurred while trying to create or update a processing rule with receivers that do not exist in Trading Networks.
Action	Ensure the receivers are valid.
4415	IS DocType signature (ISDocType ={0}) is invalid. Provide a valid IS DocType signature.
Explanation	Exception encountered while loading the corresponding IS docType.
Action	Check whether the namespace of the corresponding IS docType is correct.
4416	Cannot add extended field definition. Extended field with name "{0}" already exists.
Explanation	Extended field with same name already exists.
Action	Supply different name for extended field.

- 4417** **Cannot update extended field definition. Extended field with name "{0}" already exists.**
- Explanation** Extended field with same name already exists.
- Action** Supply a different name for the extended field.
-
- 4422** **A problem was encountered deleting the field definition.**
-
- 4429E** **Importing a profile for {0} (id={1}), which is marked as "My Enterprise", but it has different ID than the existing My Enterprise profile for this Trading Network. Cannot change the identity of the My Enterprise profile.**
- Explanation** You are attempting to import a partner profile marked as "My Enterprise." However, the target Trading Networks server already contains a My Enterprise profile, with a different ID. The existing My Enterprise cannot be overwritten because the IDs are different.
- Action** Import the partner data without selecting the "My Enterprise" profile.
-
- 4430E** **Importing a profile for {0} (id={1}), which is marked as "My Enterprise". A "My Enterprise" profile already exists for this Trading Network. If you want to update it, use the Force option.**
- Explanation** You are attempting to import a partner profile marked as "My Enterprise" without using the "Force import" option; however, the target Trading Networks server already contains a My Enterprise profile.
- Action** Import the partner data using the "Force import" option.
-
- 4431E** **Error encountered while adding DLS artifacts with name {0}. The permissions for role {1} is null or empty.**
- Explanation** You are attempting to import or add a DLS dataset, but the dataset does not contain any permissions.
- Action** If you are adding a DLS dataset, specify the required permissions for the dataset. If you are importing a DLS dataset, make sure that the data is correct.
-
- 4432** **Error encountered while adding DLS artifacts with name {0}. The role name is null or empty.**
- Explanation** You are attempting to import or add a DLS dataset, but the dataset does not contain any roles.
- Action** If you are adding a DLS dataset, specify the required roles for the dataset. If you are importing a DLS dataset, make sure that the data is correct.

4433E	Error encountered while adding DLS artifacts with name {0}. The partner with name {1} is referenced in DLS data, but this partner does not exist on your Trading Networks system.
Explanation	You are attempting to import or add a DLS dataset, but the partner specified in the dataset is not present in the Trading Networks database.
Action	If this happens while importing a DLS dataset, make sure that the dependent partner profile is also imported along with the DLS dataset.
4434E	Error encountered while adding DLS artifacts with name {0}. The document type with name {1} is referenced in DLS data, but this document type does not exist on your Trading Networks system.
Explanation	You are attempting to import or add a DLS dataset, but the document type specified in the dataset is not present in the Trading Networks database.
Action	If this happens while importing a DLS dataset, make sure that the dependent document type is also imported along with the DLS dataset.
4435E	Error encountered while adding DLS artifacts with name {0}. The processing rule with name {1} is referenced in DLS data, but this processing rule does not exist on your Trading Networks system.
Explanation	You are attempting to import or add a DLS dataset, but the processing rule specified in the dataset is not present in the Trading Networks database.
Action	If this happens while importing a DLS dataset, make sure that the dependent processing rule is also imported along with the DLS dataset.
4436W	A deleted profile with the same internal id already exists. Unable to recreate a deleted profile.
Explanation	You are attempting to import a partner. However, the target Trading Networks server already contains a deleted partner with the same ID.
Action	Import the partner using the "Force import" option.
4461	Profile has errors.
Explanation	In webMethods Trading Networks, while adding a profile information, if the profile has any error, this error message is displayed.
Action	Contact your system administrator.

4464 **Attempt to import extended field "{0}" associated with the fieldgroup "{1}" failed. The extended field "{0}" associated with the fieldgroup "{1}" is not defined on your Trading Networks system.**

Explanation This error occurred because the extended field associated with the fieldgroup is not defined on your Trading Networks system.

Action Define the extended field associated with the fieldgroup on your Trading Networks system and try again.

4467 **Administering Partner Onboarding**

4468 **The invitation with id "{0}" does not exist.**

4500 **A database error occurred while deleting a Binary Type.**

Explanation In webMethods Trading Networks, at the time of deleting a binary type, if there is a database error, then this error shows up.

Action Contact your system administrator.

5030 **Exception encountered while adding a new TPA.**

Explanation Encountered an exception while writing the TPA to the database. There might be an SQL Exception while writing to the database or some of the constraints were missed out.

Action The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.

5031 **Exception encountered while updating the TPA.**

Explanation Encountered an exception while writing the TPA to the database. There might be an SQL Exception while writing to the database or some of the constraints were missed out.

Action The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.

5032 **Exception encountered while fetching the TPA.**

Explanation Encountered an exception while fetching the TPA from the database. There might be an SQL Exception while retrieving the TPA from the database or there are TPA caching errors.

Action The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.

5033	Exception encountered while deleting the TPA.
Explanation	Encountered an exception while deleting the TPA from the database. This may be because of SQL Exception during writing to database or may be due to removing the TPA from Cache.
Action	The details of the exception are in the full message. Take appropriate action to resolve the problem described in the exception message.
5034	No initial value created for tpaData.
Explanation	The tpaData parameter was not created. A wrong service output might have caused the issue.
Action	Check if the initService defined in the TPA is correct and generates the correct output. The output of the TPA initService must generate an IData for the "tpaData" parameter.
5036E	An exception occurred while retrieving TPA names.
Explanation	My webMethods encountered an error while displaying the TPA names.
Action	Take appropriate action to resolve the problem described in the exception and try to perform the action again.
5037E	An exception occurred while executing the validation service.
Explanation	My webMethods encountered an error while validating TPA data on the Trading Partner Agreement Details page.
Action	Take appropriate action to resolve the problem described in the exception and try to perform the action again.
5038	No output data was returned by the validation service.
Explanation	The validation service does not conform to the format of the TPA validation service output record "wm.tn.rec:TPAValidateServiceOutput."
Action	Correct the service to pass the output in the format described by the output record "wm.tn.rec:TPAValidateServiceOutput."
5042	Queue
6006	Export file location not specified
Explanation	Trading Networks is not able to find the export directory location.
Action	Specify the export directory location in the tn.deployer.export.dir TN property

6011	Asset deletion failed - roll back to previous state failed.
Explanation	Trading Networks is not able to delete the asset, because of which rollback to the previous state has failed.
Action	Contact your system administrator.
6013	The binary file is either corrupt or not as expected.
Explanation	The binary file provided for deployment is not valid.
Action	Provide a valid binary file.
6014	The artifact ID is not available in the corresponding artifact properties file.
Explanation	Trading Networks needs the artifact ID for installing the artifacts for deployment. This is missing from the artifact properties file.
Action	Provide the artifact ID in the artifact properties file or recreate the artifact ID.
6015	checkpointId is required.
Explanation	Trading Networks needs the checkpoint ID as input for the execution of the checkpoint service. This is missing.
Action	Add the checkpointId in the checkpoint service.
6016	Delete Archive Schedule failed during rollback.
Explanation	Trading Networks may need to delete the archive schedule during deployment roll back. This deletion of archive schedule has failed during rollback.
Action	Contact your system administrator.
6017	Delete Private Queue for Partner failed during rollback.
Explanation	Trading Networks may need to delete the private queue for Partner during deployment roll back. This deletion of private queue has failed during rollback.
Action	Contact your system administrator.
6018	Delete Public Queue failed during rollback.
Explanation	Trading Networks may need to delete the public queue during deployment roll back. The deletion of public has failed during rollback.
Action	Contact your system administrator.

6024	The ProductNamespace "{0}" is not specific to Trading Networks.The expected ProductNamespace is "TN".
Explanation	During deployment, a ProductNamespace, which needs to be passed to the service, is required. The expected ProductNamespace specific to Trading Networks that needs to be passed to the service is "TN".
Action	Specify the ProductNamespace as TN.
6025	The runtime type is not specific to Trading Networks.
Explanation	The Ping service requires type as input. The value of "type" for Trading Networks is TN.
Action	Specify type as TN.
6026	deploymentId is required.
Explanation	The deleteDeliveredArtifacts and activateArtifacts services need the deploymentId. This is not specified.
Action	Specify the deploymentId as the service input.
6030	assetIdentifier(s) is required.
Explanation	The Trading Networks assets that are to be deleted has not been provided.
Action	Provide the Trading Networks assets.
6032	Asset deletion has failed.
Explanation	If the deletion of a Trading Networks asset has failed, this message is displayed.
Action	Based on the additional details in the message, you need to fix the issue and try to delete the Trading Networks asset again.
6034	Trading Networks is not able to retrieve the asset references for the asset: "{0}" of asset type: "{1}". "{2}"
Explanation	Trading Networks is not able to retrieve the asset references for the specified asset due to an unexpected error.
Action	Try to delete the asset again. If it still does not go through, contact your system administrator.

6056	Access denied. User "{0}" does not have the permission to {1} {2}, for Sender "{3}" and Receiver "{4}".
Explanation	User does not have the permission required to perform the necessary action on the TPA.
Action	Ask the B2B Administrator to assign the user the required permission.
6057	Access denied. User "{0}" does not have the permission to view {1}.
Explanation	User does not have the permission required to view the TPA.
Action	Request the B2B Administrator to assign user the required permission.
7010	{0} is not a valid Trading Networks version. Rerun this program by specifying the supported version of your old Trading Networks.
Explanation	The Trading Networks version selected for migration is not valid.
Action	Rerun this program by specifying the correct version number.
7011	Source Server version is not provided. Rerun this program by specifying the source server version of Trading Networks.
Explanation	The Trading Networks version selected for migration is not provided.
Action	Rerun the migration utility by specifying the version number.
7019	The property file {0} does not exist.
Explanation	The properties.cnf file does not exist.
Action	Add the properties.cnf file to the "IntegrationServer > packages > WmTN > config" location.
7020E	Document Type with name "{0}" already exists. Change the name and save again.
Explanation	Document type with the same name already exists.
Action	Change the document type name and save again.
7021E	Error while changing the status of the doctype.
Explanation	Document type status update operation failed.
Action	See the stack trace and take appropriate action.

7022E	Error while changing the status of the doctype {0}.
Explanation	Document type status update operation failed.
Action	See the stack trace and take appropriate action.
7023	List of doctypes for changing status can not be empty.
Explanation	List of doctypes is a mandatory field.
Action	Configure a list of doctypes while changing the status.
7031	The Trading Networks configuration file was successfully migrated.
7033	The Trading Networks data was successfully migrated.
7034	Started migrating onboarding templates data.
7035	Successfully completed migrating onboarding templates data.
7036	Migrating onboarding templates data failed.
7037	Started migrating onboarding idtype.
7038	Successfully completed migrating onboarding idtype.
7039	Migrating onboarding idtype failed.
8001E	new String[]{"Cannot process message that is not javax.mail.internet.MimeMessage or javax.mail.internet.MimeBodyPart. Current message is: {0} ","","0"}
Explanation	Message cannot be parsed because it is neither a MimeMessage, nor a MimeBodyPart.
Action	Check the message type before invoking the service.

8013E **Error encountered while downloading sample csv file. Please see error log for more details, contact your Administrator.**

Explanation In webMethods Trading Networks, in Partner Onboarding, while downloading a sample csv file for uploading a partner, if any error is encountered, this message appears.

Action Contact your system administrator.

8050 **A template field with this name already exists: {0}.**

Explanation In webMethods Trading Networks, while creating a new template field, if the name is not unique, this error shows up.

Action Ensure to have a unique template field name and try again.

8052 **An exception occurred while inserting template field (ID = "{0}", Name = "{1}").**

Explanation In webMethods Trading Networks, while adding a template field, if an exception occurs while adding a new template field, this error is thrown.

Action See the exception stack trace to find out the reason for this error.

8053 **An exception occurred while updating template field (ID = "{0}", Name = "{1}").**

Explanation In webMethods Trading Networks, while updating a template field, if an exception occurs while updating the template field, this error occurs.

Action Check the exception stack trace to find out the reason for the error.

8054 **An exception occurred while inserting template group (ID = "{0}", Name = "{1}").**

Explanation In webMethods Trading Networks, while inserting a template field group, if an exception occurs while updating the template field, this error occurs.

Action Check the exception stack trace to find out the reason for the error.

8055 **A group with this name already exists: {0}.**

Explanation In webMethods Trading Networks, while adding a group to a questionnaire template, if the name already exists, this error shows up.

Action Ensure to use a unique group name and try again.

8056	An exception occurred while fetching template fields for group(ID = "{0}", Name = "{1}").
Explanation	In webMethods Trading Networks, while fetching template fields for a group, if an exception occurs, this error shows up.
Action	Check the exception stack trace to find out the reason for the error.
8057	A template with this name already exists: {0}.
Explanation	In webMethods Trading Networks, while adding a questionnaire template, if the name already exists, this error shows up.
Action	Ensure to use a unique questionnaire template name and try again.
8059	The invitation has expired. Contact your administrator.
8060	The invitation is disabled now. Contact your administrator.
8061	An exception occurred while querying templates.
8146	Sending the new email invitation failed.
9001	Access denied, as the User "{0}" doesnot have the permission to {1} {2}.
Explanation	The corresponding user does not have permissions to perform the associated actions.
Action	Contact a B2B Administrator for granting the corresponding permissions.
9002	Error encountered while fetching search results, page {0} requested is not found for queryId={1}. Contact your administrator to optimize the configuration of the TNQueryResults cache.
Explanation	In webMethods Trading Networks, while getting the query results, if the page request for a query ID is null, this error is thrown.
Action	Contact your administrator to optimize the configuration of the TNQueryResults cache.
9003	Access denied, as the User "{0}" doesnot have the privilege to {1} {2}.
Explanation	The corresponding user does not have permissions to perform the associated action.
Action	Contact a B2B Administrator for granting the corresponding permissions.

9004	Access denied, as the User "{0}" doesnot have the privilege to view {1}.
Explanation	The corresponding user does not have permissions to view the corresponding Trading Networks asset.
Action	Contact a B2B Administrator for granting the corresponding permissions.
9005	Recipient info is not available for the recipientCert
9006E	Primary and secondary certificates already exist for this owner, partner, and usage combination.
Explanation	A maximum of two certificates can be uploaded per unique combination of owner, partner, and usage.
Action	Delete the primary or secondary certificate before uploading an additional certificate.
9007	Error occurred while initializing Ehcache cache manager and accessing cache from it. Error message : {0}.
Explanation	An error occurred while initializing the Ehcache cache manager and accessing cache from it.
Action	Contact your system administrator.
9008	Failed to initialize cache manager for Ehcache. The SoftwareAG_IS_TN.xml file is missing, replaced, or invalid.
Explanation	webMethods Trading Networks failed to initialize the cache manager for Ehcache. The SoftwareAG_IS_TN.xml file is missing, replaced, or invalid.
Action	Add a valid SoftwareAG_IS_TN.xml file in the configurations folder.
9009E	Error occurred while initializing Trading Networks because the following caches are not configured: {0}
Explanation	An error occurred while initializing Trading Networks because one or more caches are not configured.
Action	Check the cache manager SoftwareAG.IS.TN, configure the missing caches, and restart Integration Server.
9012E	Certificate with certificate ID {0} is already the primary certificate.
Explanation	The wm.tn.security:setPrimaryCertificate service was called incorrectly using the certificate ID of a primary certificate.
Action	Specify the certificate ID of the secondary certificate as input to wm.tn.security:setPrimaryCertificate service.

9015	Database error in getting prepared statement or Set proper dequeue strategy map entry
9016	Error encountered in wm.tn.security:setPrimaryCertificate.
TNS.0000.1010E	Error while running archive operation: {0}.
Explanation	Trading Networks encountered an exception while archiving documents.
Action	See the exception in the full message. Take appropriate action to resolve the problem described in the exception.
TNS.0000.1013	{0} could not be completed because another {1} operation was under way or Archive_WorkTable has contents that were not cleaned up. If there is no archive/deletion service running, cleanup the table to complete the operation.
Explanation	Trading Networks cannot complete the archive or delete operation either because another archive or delete operation is in progress or because the Archive_WorkTable has contents that need to be cleaned up.
Action	If no other archive or delete operation is in progress, clean up the Archive_WorkTable contents and restart the incomplete archive or delete operation.
TNS.0000.2004E	Cannot save a {0} without a {1}.
Explanation	Trading Networks cannot save the specified profile component because a required field is missing.
Action	Enter the value for the required field.
TNS.0000.2005E	Error logging database event.
Explanation	Trading Networks encountered an exception while writing an activity log entry to the database.
Action	See the exception written to the server log. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2006E	Error encountered while deleting {0}. {1} rows changed in the database.
Explanation	Instead of deleting exactly one row from a table in the database, Trading Networks deleted the specified number of rows.
Action	See the exception written to the server log. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2008E	Table not recognized: {0}.
Explanation	Trading Networks found a profile field in the database that refers to a nonexistent table.
Action	Ensure that your query is for an existing profile field.
TNS.0000.2009E	Error while inserting document {0}.
Explanation	Trading Networks encountered an exception while writing a document to the database.
Action	See the exception in the full message. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2011E	Error while querying documents: {0}. Original SQL: {1}.
Explanation	Encountered an SQLException while performing a document query.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0000.2012E	Inserting field definition failed.
Explanation	Attempted to add a profile field definition, but the database was unchanged.
Action	Contact webMethods Customer Care.
TNS.0000.2016E	An attempt was made to access the SQL statement {0}, which was not defined in the configuration file.
Explanation	Attempted to execute an SQL statement that is not available in the file of externalized SQL statements (dbops.sql).
Action	If you have modified the dbops.sql file, restore the file to its prior state.
TNS.0000.2026E	An attempt was made to save an extended field with an unsupported data type. Name={0}, Data type={1}.
Explanation	Attempted to save an extended field for a partner, but the field's value is not a supported data type.
Action	Supply a value that is one of the supported data types for an extended field.
TNS.0000.2027D	Could not update type {0} for attribute {1}.
Explanation	Attempted to save a document attribute, but the attribute did not reference a valid document type.
Action	If you are explicitly calling services to save an attribute, ensure that the attribute refers to a valid document type.

TNS.0000.2029E	The database has no version information. Either it has not been initialized, or it has been changed to an invalid state by an external process.
Explanation	The TNModelVersion table is missing. Data from this table was accidentally deleted, the table was dropped, or the database is corrupt.
Action	Restore this table from the most recent backup. If the database is corrupt, work with your DBA to determine the cause. In this case, you will need to restore the entire database to the most recent backup.
TNS.0000.2031S	No model version information was available from the database.
Explanation	The TNModelVersion table is missing. Data from this table was accidentally deleted, the table was dropped, or the database is corrupt.
Action	Restore this table from the most recent backup. If the database is corrupt, work with your DBA to determine the cause. In this case, you will need to restore the entire database to the most recent backup.
TNS.0000.2036E	Unsupported encoding {0} declared in the TN config file (tn.store.encoding).
Explanation	The tn.store.encoding property was set to an invalid value.
Action	Set the tn.store.encoding property to a valid value.
TNS.0000.2037S	The model version specified (tnmv:) seems to be missing from the dbops.sql file in your WmTN package. Check the file and try again.
Explanation	The dbops.sql file must begin with "-- tnmv: x.x", where "x.x" is the current TNModelVersion number. This line has been removed or altered.
Action	Restore the dbops.sql file to the correct state.
TNS.0000.2039S	There was an error while reading the dbops.sql file in your WmTN package. The original error message was: {0}.
Explanation	Encountered an exception while reading the dbops.sql file. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0000.2040E	Error encountered while updating {0}. {1} rows changed in the database.
Explanation	Instead of updating exactly one row in a table in the database, Trading Networks updated the specified number of rows.
Action	Contact webMethods Customer Care.

TNS.0000.2041W	Error while redefining attribute {0} ({1}).
Explanation	Encountered an SQLException while updating a document attribute.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0000.2042E	Error encountered while updating {0}. {1} rows changed in the database for {2}.
Explanation	Instead of updating exactly one row in a table in the database, Trading Networks updated the specified number of rows.
Action	Contact webMethods Customer Care.
TNS.0000.2047E	No extended fields were deleted for group {0} (partnerID={1}).
Explanation	Expected to delete exactly one row in the PartnerProfileField table in the database. Instead, Trading Networks did not delete any rows.
Action	There seems to be an error while deleting. Find out why the row did not get deleted.
TNS.0000.2051E	Unable to insert binary object (partnerID={0}).
Explanation	An INSERT statement was unsuccessful in adding a row to the database.
Action	The exception is in the full message. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2064S	There was an error interpreting the model version specifier (tnmv:) in the dbops.sql file in your WmTN package. The original error message was: {0}.
Explanation	The dbops.sql table must begin with "-- tnmv: x.x", where "x.x" is the current TN Model Version number. This line has been altered.
Action	Restore this line to its correct state.
TNS.0000.2066E	The main connection to the data store has not been initialized. Check the Trading Networks JDBC connection pool.
Explanation	There is no connection to the Trading Networks database.
Action	Use the Integration Server Administrator JDBC Pools page to test the connection to the Trading Networks database. You may need to adjust the connection pool settings or verify that the database is functioning normally.

TNS.0000.2067E	Extended field (fieldID={0}) not deleted (partnerID={1}).
Explanation	A DELETE statement was unsuccessful in removing a row from the database.
Action	Check the database connection or see the logs for more detailed stack trace information and take appropriate action.
TNS.0000.2079E	More than one extended field (fieldID={0}) removed in a single delete operation (partnerID={1}).
Explanation	Instead of deleting exactly one extended field in the database, Trading Networks deleted the specified number of fields.
Action	Check which other extended fields could have been deleted along with the intended one, then recreate the appropriate extended fields and redo the mapping.
TNS.0000.2085E	Cannot change a {0} without a {1}.
Explanation	Attempting to update a profile component, but a required field is missing.
Action	Supply a value for the missing field.
TNS.0000.2089E	Trading Networks could not retrieve data from your database. Go to the JDBC Pools page in the Integration Server Administrator and make sure your database URL, user name, and password are set correctly. Also make sure you created the Trading Networks database tables as described in the webMethods Installation Guide.
Explanation	The TNModelVersion table is missing from the Trading Networks database. The reason can be one of the following: 1) The Trading Networks database tables have not yet been created. 2) Data from TNModelVersion table was accidentally deleted. 3) The TNModelVersion table was dropped. 4) Your database is corrupt.
Action	Check your database. If the Trading Networks tables have not been created, create them. If the TNModelVersion table is missing or not valid, recreate it. If your database is corrupt, work with your database administrator to determine the cause. You might need to restore your entire database from the most recent backup.
TNS.0000.2096E	Document {0} from this sender was not successfully stored in the data store. The original exception message was: {1}.
Explanation	Encountered an exception while writing a document to the database.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0000.2104E **An attempt was made to access the SQL statement {0} before SQL statements were read from the disk.**

Explanation An SQL statement was used before the SQL statement cache was initialized.

Action If your package uses Trading Networks facilities, be sure to declare a dependency on the WmTN package in your package's manifest.v3 file.

TNS.0000.2110E **Error decoding type {0}.**

Explanation Encountered an IOException while decoding binary data from the database into a BizDocType object.

Action See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2112E **Document type not saved. A document type with the name [{0}] already exists. Cannot have two document types with the same name but different IDs.**

Explanation You cannot have two document types with the same name.

Action Change the name of the document type and save it again.

TNS.0000.2114E **The system could not load the JDBC driver {0} for connection to the data store. Check the CLASSPATH setting and try again.**

Explanation The driver specified for the Trading Networks functional alias on the JDBC Pools Configuration page of the Integration Server could not be found.

Action Make sure the driver is in your classpath.

TNS.0000.2119E **Unknown or deleted attribute {0}.**

Explanation The wm.tn.doc:setAttribute service was supplied an invalid attribute ID or name.

Action Supply a valid attribute ID or name.

TNS.0000.2127E **Error encountered while updating Contact. {0} rows changed in database for {1} {2}.**

Explanation Instead of updating exactly one row in the Contact table in the database, Trading Networks updated the specified number of rows.

Action Check the affected details and verify whether the data can be recreated.

TNS.0000.2131E	Could not find doc {0}; no document type {1}.
Explanation	Could not create a bizdoc from binary data in the database. The TN document type it references does not exist.
Action	The document type corresponding to the bizdoc may have been deleted, or the associated data may be corrupted. Contact Customer Care.
TNS.0000.2132E	Could not archive documents.
Explanation	Encountered an SQLException while archiving documents.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2133E	Could not delete archived documents.
Explanation	Encountered an SQLException while deleting archived documents.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2134E	Could not delete documents.
Explanation	Encountered an SQLException while deleting documents.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2135E	Could not queue documents.
Explanation	Encountered an SQLException while queuing a document for polling.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2136E	Could not poll documents.
Explanation	Encountered an SQLException while polling for documents.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2137E	Could not accept document.
Explanation	Encountered an SQLException while accepting a polled document.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2138E	Could not query the event table.
Explanation	Encountered an SQLException while querying activity log entries.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2139E	Could not delete the events.
Explanation	Encountered an SQLException while deleting activity log entries.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2140E	Could not instantiate document {0}.
Explanation	Encountered an SQLException while retrieving a document.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2141E	Could not check uniqueness {0}.
Explanation	Encountered an SQLException while querying the database to determine if a document is unique.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2142E	Could not get the user status.
Explanation	Encountered an SQLException while retrieving the user status of a document.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2143E	Could not insert the new document.
Explanation	Encountered an SQLException while saving a new document.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2144E	Could not change status for {0}.
Explanation	Encountered an SQLException while changing the status of a document.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2145E	One of (fromdoc,todoc) must be persisted.
Explanation	Attempted to relate two documents, but neither of them has been saved to the database.
Action	Save one or both of the documents to be related.
TNS.0000.2146E	Could not relate {0} and {1}.
Explanation	Encountered an SQLException while relating two documents.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2147E	Could not get rels: doc={0}, gr={1}.
Explanation	Encountered an SQLException while retrieving related documents.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2148E	The following exceptions occurred:
Explanation	The following exceptions were encountered while retrieving the full set of TN document types.
Action	See each of the following exceptions for details. Take appropriate action to resolve the problem described in each exception.
TNS.0000.2149E	Database error while fetching all types: {0}.
Explanation	Encountered an SQLException while retrieving the full set of TN document types.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2150E	Database error while adding type {0}: {1}.
Explanation	Encountered an SQLException while saving a new TN document type.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2151E	Encoding error while putting type {0}: {1}.
Explanation	Encountered an IOException while saving a new TN document type.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2152E	Database error while updating type {0}: {1}.
Explanation	Encountered an SQLException while updating a TN document type.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2153E	Encoding error while updating type {0}: {1}.
Explanation	Encountered an IOException while saving a new TN document type.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2154E	Cannot aggregate STRING attributes.
Explanation	Attempted to execute an aggregation operation (SUM, AVG, MIN, MAX) on a String attribute.
Action	Do not specify the aggregation operation.
TNS.0000.2160E	Could not queue document for delivery (id={0}).
Explanation	Encountered an SQLException while changing the status of a document to "QUEUED".
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2162E	Trading Networks database pool is not configured. Please configure a database pool for functional alias "TN" and restart the WmTN package.
Explanation	Data required to configure a connection to the database is missing or invalid.
Action	Use the Integration Server Administrator JDBC Pools page to recreate this data.
TNS.0000.2164E	Error while logging an activity entry to the audit sub system. The exception message is : {0}.
Explanation	Encountered an exception while publishing an activity log entry.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0000.2165E	Error while reading the database configuration. The exception message is : {0}.
Explanation	Trading Networks encountered an exception while reading the database configuration data.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception. You might need to use the JDBC Pools page in the Integration Server Administrator to recreate this data.

TNS.0000.2168E	Trading Networks database pool is not configured properly. Make sure that a valid database pool is assigned for functional alias "TN" and restart the WmTN package.
Explanation	Data required to configure a connection to the database is missing or invalid.
Action	Use the Integration Server Administrator JDBC Pools page to recreate this data.
TNS.0000.2169E	Unable to locate the database configuration information. File {0} does not exist.
Explanation	A file required to configure a connection to the database is missing.
Action	Use the Integration Server Administrator JDBC Pools page to recreate this data.
TNS.0000.2170E	Trading Networks database pool is not configured properly. Make sure that a valid database pool is assigned to functional alias "TN" and try again.
Explanation	Data required to configure a connection to the database is missing or invalid.
Action	Use the Integration Server Administrator JDBC Pools page to recreate this data.
TNS.0000.2175E	The database connection pool associated with TN should allow at least 2 connections. Your TN pool is currently configured with a maximum of {0} connections. Aborting TN startup. Please increase your TN database pool maximum and restart the server.
Explanation	Trading Networks requires at least two connections for its pool. Trading Networks will not initialize with fewer than two connections.
Action	Use the Integration Server Administrator JDBC Pools page to increase the number of connections allowed for the Trading Networks database pool. Then restart your server.
TNS.0000.2180U	Database error while deleting document type {0}: {1}.
Explanation	Encountered an SQLException while deleting a document type.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2181E	A BizDocType with this name already exists: {0}.
Explanation	You cannot have two document types with the same name.
Action	Save the document type with a different name.

TNS.0000.2184E	The profile field definition "{0}" already exists with a different ID. The field definition was not imported.
Explanation	This error can occur when importing extended profile fields. The most likely cause is that the field was already manually created on the target server.
Action	If you do not intend to import extended field values, this error can be ignored. If you do intend to import extended field values, and no partner yet has a value for this field on your target server, you can change the ID of the field definition to match the one on the source server. Carefully update the ProfileFieldID key in the ProfileField table of the database into which you are importing.
TNS.0000.2185E	An IDType with a key of "{0}" already exists with a different ID description. The IDType "{1}" was not imported. You will need to directly edit the IDType table in your database to correct this problem.
Explanation	The error can occur when importing extended ID types. The most likely cause is that the IDType was already manually created on the target server.
Action	Change the Type column of the IDType table on the target database to match that of the source database.
TNS.0000.2186	Could not update comments for document {0}.
Explanation	Encountered SQLException while updating comments for document.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2199	Error encountered while reading routing status from the database. Exception message: {0}.
Explanation	Encountered SQLException while reading routing status from database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2212	A scheduled archival service with this name already exists.
Explanation	A scheduled archival service with the same name already exists.
Action	Change the name of the scheduled archival service and save again.
TNS.0000.2215	Unable to save scheduled archive service "{0}".
Explanation	Error encountered while updating the archive service.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.2221	Interval is not a valid integer.
Explanation	Interval set in the schedule is wrong; it must be a valid integer.
Action	Correct the interval field in the schedule and save the schedule again.
TNS.0000.2222	Interval must be greater than zero.
Explanation	Interval set in the schedule is wrong; it must be greater than zero.
Action	Correct the interval field in the schedule and save the schedule again.
TNS.0000.2223	The scheduled {0} is invalid. Format must be YYYY/MM/DD.
Explanation	Schedule date must be of format YYYY/MM/DD.
Action	Change the schedule according to the format and save it again.
TNS.0000.2224	The scheduled {0} is invalid. Format must be hh:mm:ss.
Explanation	Schedule time must be of format hh:mm:ss.
Action	Change the schedule according to the format and save it again.
TNS.0000.2231	The scheduled delivery date/time is in the past.
Explanation	Schedule delivery date/time set must not be in the past.
Action	Change the delivery schedule with the date/time in the future.
TNS.0000.2232	If an end time is supplied, an end date must also be supplied.
Explanation	End date has to be supplied along with end time.
Action	Set the end date along with the end time, and save the schedule.
TNS.0000.2233	End date/time is in the past.
Explanation	End date/time must not be set in the past.
Action	End date/time should always be later than the start date/time. Correct the end date/time and save the schedule again.
TNS.0000.2234	End date/time is before start date/time.
Explanation	End date/time must not be before the start date/time.
Action	End date/time should always be later than the start date/time. Correct the end date/time and save the schedule again.

TNS.0000.2235	Could not construct a valid timestamp from this schedule. Dates must be in YYYY/MM/DD format and times must be in hh:mm:ss format.
Explanation	Delivery schedule created with an incorrectly formatted date.
Action	Correct the date format and save the delivery schedule.
TNS.0000.2236	Delivery schedule dates must be in the format "YYYY/MM/DD" and times must be in the format "hh:mm:ss".
Explanation	Delivery schedule created with an incorrectly formatted date.
Action	Correct the date format and save the delivery schedule.
TNS.0000.2244	Unable to remove scheduled archival service "{0}".
Explanation	Encountered exception while deleting archival service from database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2246	Unable to update scheduled archival service "{0}".
Explanation	Encountered exception while updating archival service to database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.2301	An exception occurred while listing the document attributes.
Explanation	Encountered exception while getting document attributes from cache or database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.3001E	Persistence Service Failed.
Explanation	Encountered an exception while saving the document to the database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.3002E	An error occurred while trying to insert this document into the database. The original error message was: {0}.
Explanation	Encountered an exception while saving the document to the database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0000.3007E	Non-unique ID(s) detected.
Explanation	This incoming document already exists in the database. This is a duplicate document, based on the unique document criteria.
Action	Notify the document sender that the document sent is a duplicate.
TNS.0000.3008W	This document is not unique. It matched {0} existing documents in the database.
Explanation	This incoming document already exists in the database. This is a duplicate document, based on the unique document criteria.
Action	Notify the document sender that the document sent is a duplicate.
TNS.0000.3015E	Could not get the document bytes.
Explanation	An exception was thrown while adding the document content to the BizDocEnvelope. The document might be corrupt.
Action	Trading Networks wrote the exception to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0000.3016E	No such document: {0}.
Explanation	The wm.tn.doc:view service was passed an invalid internal document ID.
Action	Supply a valid internal document ID to the wm.tn.doc:view service.
TNS.0000.3018E	Invalid duplicate checking service.
Explanation	Custom duplicate check was selected, but either a duplicate check service was not specified or the specified duplicate check service was invalid.
Action	Using My webMethods Server, update the TN document type and/or the processing rule and specify a valid duplicate checking service.
TNS.0000.3019E	The BizDocType refers to a non-existent duplicate checking service: {0}. It may have been renamed, disabled, or deleted.
Explanation	Custom duplicate check was selected, but no duplicate check service was specified or the specified duplicate check service was invalid. This error could also occur when the specified duplicate check service has been renamed, disabled, or deleted.
Action	Using My webMethods Server, update the TN document type and/or the processing rule and specify a valid duplicate checking service.

TNS.0000.3020E	Duplicate document detected.
Explanation	You received a document that failed a custom duplicate document check. The custom duplicate checking service flagged the document as a duplicate.
Action	You can ignore this message, or you can notify the sender of the document that you have received a duplicate.
TNS.0001.1001E	Content Part {0} does not exist in document {1}.
Explanation	The document does not contain the requested content part.
Action	Request a different content part, or request this content part from a different document.
TNS.0001.1002E	Content for Part {0} of document {1} does not exist in TSpace.
Explanation	This is a large document and the requested content part was not found in the temporary storage.
Action	Request a different content part, or request this content part from a different document.
TNS.0001.1003E	Error retrieving content of content part {0} of document {1}. The exception message is : {2}. The stack trace is : {3}
Explanation	An exception was thrown while retrieving the document content.
Action	Take appropriate action to resolve the problem described in the exception message.
TNS.0001.1004E	Unable to find a document type for the given document type name, {0}.
Explanation	Could not find the document type specified for deleting.
Action	Provide a valid TN document type name to the wm.tn.doc:deleteDocuments service.
TNS.0001.1006E	Attempted to update system attributes for the document, but no rows were changed in the database.
Explanation	Trading Networks encountered an error while attempting to update the system attributes of the document.
Action	Retrieve this document from the database and examine it to determine why the error occurred.
TNS.0001.1017	System Attribute update failed.
Explanation	Encountered an exception while updating the system attribute.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.1018E	Error when adding large content part named {0} to this document
Explanation	Encountered an exception while adding a large content part to the document.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0001.1019E	The actual exception is {0}.
Explanation	Encountered an exception while adding a large content part to a document.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0001.1020E	User{0} is not an administrator and attempted to retrieve a document (docID={1}) that does not belong to him.
Explanation	Users without administrative rights can only retrieve documents that they have either sent or received.
Action	None.
TNS.0001.1021E	You do not have the authority to retrieve this document. Only administrators may access documents that they did not send or receive.
Explanation	Users without administrative rights can only retrieve documents that they have either sent or received.
Action	Request a user with administrative rights to access the document.
TNS.0001.2035E	Recognize: unable to get XML DTD for comparison: {0} {1} {2} {3}
Explanation	The DTD statement in the document may be incorrect.
Action	Check the document that is being processed to ensure that it is structured correctly. If it is not, notify the responsible party about this document.
TNS.0001.2036E	BizDocTypeReg: ERROR invoking recognize for {0}
Explanation	See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0001.2040E	{0}: No envelope queries specified
Explanation	The TN document type has no envelope queries defined.
Action	Use My webMethods to edit the TN document type and define envelope queries.

TNS.0001.2041E	Error filling BizDocTypeStore cache
Explanation	Encountered an error while reading the TN document types from the database and caching them in memory.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database.
TNS.0001.2042E	Doctype info not initialized
Explanation	The BizDocType Registry was not initialized.
Action	Try reloading the WmTN package.
TNS.0001.2043E	Unknown type name: {0}
Explanation	The wm.tn.doctype:view service was passed an invalid TN document type name.
Action	Pass a valid TN document type name to the service.
TNS.0001.2044E	Unknown type id: {0}
Explanation	The wm.tn.doctype:view service was passed an invalid TN document type ID.
Action	Pass a valid TN document type ID to this service.
TNS.0001.2045E	Operation not supported for RecordDocType
Explanation	You cannot create an instance of the RecordDocType.
Action	Creating an instance of the RecordDocType is not allowed.
TNS.0001.2054E	IOException encoding pipeline
Explanation	Encountered an exception while binary-encoding the data for an unknown document type. See the nested exception for details.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0001.2056E	Query or Transform Failed
Explanation	Encountered an exception while extracting a document attribute and converting its value.
Action	Verify that the attribute extraction query in the TN document type is valid.

TNS.0001.2057E	Transform Failed
Explanation	An error occurred while converting the attribute value.
Action	Use My webMethods to verify that the attribute details about the TN document type are correct. If they are, gather details about the error and contact Software AG Global Support.
TNS.0001.2058E	Error generating query expression
Explanation	Encountered an exception while generating an XML query to extract a document attribute.
Action	Correct the attribute extraction query on the TN document type.
TNS.0001.2059E	No such BizDocType: {0}
Explanation	The wm.tn.doc:createReply service was passed an invalid replyTypeId.
Action	Pass a valid replyTypeId to the service.
TNS.0001.2060E	Doctype info not initialized. BizDocType registry has not been created.
Explanation	The BizDocType Registry was not initialized.
Action	Try reloading the WmTN package.
TNS.0001.2061E	An error occurred when constructing the XML Document object
Explanation	A document object could not be constructed from the XML. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.
TNS.0001.2062E	Recognition failed.
Explanation	Unable to recognize document. See the next message for details.
Action	Take appropriate action to resolve the problem described in the next message.
TNS.0001.2063E	There is not enough space on TSpace storage system to store the content of this large document
Explanation	The HDD partition used for temporary storage of large documents is full.
Action	Either change the value of the tn.tspace.location property, or increase the size of the partition.

TNS.0001.2065E	Unknown datatype encountered transforming attribute for FFDocType {0}
Explanation	The attribute value supplied in the pipeline for the flat file document is not a String.
Action	Correct the document gateway service that puts this value in the pipeline. The attribute value must be a String.
TNS.0001.2066E	FFDocType {0} encountered an unknown datatype while applying the {1} transformation to the "{2}" attribute.
Explanation	The attribute value supplied in the pipeline for the flat file document is not a String.
Action	Correct the document gateway service that puts this value in the pipeline. The attribute value must be a String.
TNS.0001.2067E	The {0} attribute is required by the {1} doctype. It is missing.
Explanation	The attribute that is required for the flat file TN document type is missing in the pipeline.
Action	Correct the document gateway service that supplies the value for this attribute.
TNS.0001.2068E	FFDocType {0} encountered an error transforming an attribute.
Explanation	The specified flat file document type extracts an attribute. Trading Networks encountered an error while transforming the attribute value.
Action	Use My webMethods to verify that the attribute details for the TN document type are correct. If they are, gather details about the error and contact Software AG Global Support.
TNS.0001.2069E	FFDocType {0} encountered an error while applying the {1} transformation to the "{2}" attribute: {3} : {4}
Explanation	An error occurred while transforming the attribute value.
Action	Use My webMethods to verify that the attribute details for the TN document type are correct. If they are, gather details about the error and contact Software AG Global Support.
TNS.0001.2070E	FFDocType {0} encountered an error reading the document bytes.
Explanation	Encountered a problem while processing the "ffdata" InputStream.
Action	See the entire message for details.

TNS.0001.2071E	FFDocType {0} encountered an error reading the document bytes. {1} : {2}
Explanation	Encountered an exception while reading the "ffdata" InputStream. See the exception message and stack trace for details.
Action	Verify that your document gateway service is not corrupting the "ffdata" InputStream. Resend the document.
TNS.0001.2072E	Cannot unregister a built-in DocType Category: {0}
Explanation	The wm.tn.doctype:unregisterCategory service was passed the name of a built-in TN document type category, such as "XML", or "Flat file".
Action	Do not unregister a built-in category.
TNS.0001.2079E	Could not determine document sender.
Explanation	The TN document type is configured to determine the document sender from the connected user but it could not.
Action	See the entire message for details.
TNS.0001.2080E	Could not determine document sender for doctype "{0}" because there is no connected user.
Explanation	The TN document type is configured to determine the document sender from the connected user but it could not. A possible reason for the error is the lack of a connected user.
Action	Determine why there is not a connected user. Perhaps the document has been submitted by a background thread.
TNS.0001.2081E	Could not get ProfileSummary for sender from connected user "{0}".
Explanation	The TN document type is configured to determine the document sender from the connected user but it could not. There is a connected user, but it does not have a partner profile.
Action	Create a partner profile for the user, or instruct the user to log on the system using a valid partner account.
TNS.0001.2083E	FFDocType {0} encountered an error reading the document bytes. Key "ffdata" is not found in the pipeline
Explanation	The "ffdata" InputStream is missing in the pipeline.
Action	Verify that your document gateway service is not dropping "ffdata" from the pipeline. Resend the document.

TNS.0001.2084E	FFDocType {0} encountered an error reading the content of document {1}.
Explanation	This is a large document and Trading Networks encountered an error while reading the document's InputStream from Tspace (hard disk drive space). See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.
TNS.0001.2085E	Error turning stream into bytes (docid={0})
Explanation	The document has an unsupported encoding. See the server log or open this document in Transaction Analysis to see details about the error.
Action	Request the document to be resend using supported encoding.
TNS.0001.2086E	Attribute transformation '{0}' has no data
Explanation	The attribute referenced by this transformation is null.
Action	Gather details about this error, and contact Software AG Global Support.
TNS.0001.2088E	A corrupted document was encountered in recognition: {0}
Explanation	Trading Networks received an XML document that was not structured well.
Action	Correct the original document and resend it.
TNS.0001.2090E	Unable to load the following TN document types because their classes are not found in the classpath: {0}. Either correct the classpath to include the required classes and restart the Server or, if you no longer use these document types, delete them using the wm.tn.doctype:delete service and then restart the Server.
Explanation	There are TN document types in the database that are not available on the classpath.
Action	Correct the classpath to include the required classes and restart the server; or, if you no longer use these TN document types, delete them using the wm.tn.doctype:delete service, and then restart the server.
TNS.0001.2091	Encountered an unsupported encoding
Explanation	Encoding passed in the document is not supported by Integration Server.
Action	Change the document to a supported encoding.

TNS.0001.2092	Error turning stream into bytes: {0}
Explanation	Error encountered while converting the stream to bytes. This could happen if the stream was closed while still being read.
Action	Examine why the connection dropped while reading the stream.
TNS.0001.2093E	This operation is not supported for MissingDocType.
Explanation	The operation attempted to create a BizDocEnvelope from the MissingDocType class.
Action	If you developed code that creates instances of (No Suggestions) ensure that it does not attempt to create a BizDocEnvelope from the MissingDocType class.
TNS.0001.2094E	ERROR: The Java class for this document type was not found.
Explanation	The JAR file that holds the TN document type editor was not found.
Action	If you are viewing a Trading Networks XML or flat file document type, make sure that the tnclient.jar file is in the webMethods6\IntegrationServer\packages\WmTN\code\jars directory on the Integration Server file system. If you are viewing another category of TN document type, make sure that the JAR file with that TN document type editor is in the IntegrationServer\packages\WmTN\code\jars directory.
TNS.0001.2097	Encountered an error while creating MAPI event to Optimize for EventMap {0} and for Sender with PartnerID {1}.
Explanation	The error may be caused due to Broker being stopped.
Action	Start the associated Broker if it is stopped.
TNS.0001.3000E	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3001	Unable to read mime message data source
Explanation	The MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3002E	Unable to read mime message data source
Explanation	Problem while reading from input data source.
Action	Check input data source for errors.
TNS.0001.3003E	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3004E	Unable to handle data of type: {0}
Explanation	Attempted to add a message of type <msgType> to a multi-part MIME message. This type cannot be part of a multi-part MIME message.
Action	Check the message type that is being added to the multi-part MIME message. It must be either a multi-part MIME or a MIME message.
TNS.0001.3005E	Unable to handle null data source
Explanation	Cannot construct a MIME message from null data source.
Action	Pass valid, non-null data source to the service.
TNS.0001.3006	Unable to read mime message data source
Explanation	Problem while reading from input data source.
Action	Check input data source for errors.
TNS.0001.3007	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3008E	Can not replace existing body part
Explanation	Attempted to add a MIME body part to a MIME message that already contains a body part.
Action	Set the input flag 'replace' on the wm.tn.mime:addBodyPart service to 'yes'. This will replace the existing body part with the new one. Another solution is to set the flag 'multipart' to 'yes'. This will append the new body part to the existing one, making the message a multi-part MIME message.

TNS.0001.3009	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3010	Unable to read mime message data source
Explanation	Problem while reading the input data source.
Action	Check input data source for errors.
TNS.0001.3011E	getBodyPart not supported on non multipart message
Explanation	Attempted to get a MIME body part other than zero from a non-multipart MIME message.
Action	The number '0' (zero) is the only valid value for the input parameter 'index' of the wm.tn.mime:getBodyPartHeader and wm.tn.mime:getBodyPartContent services when the input MIME message is not a multi-part MIME message.
TNS.0001.3012	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3013	Unable to read mime message data source
Explanation	Problem while reading the input data source.
Action	Check input data source for errors.
TNS.0001.3014	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3015	Unable to read mime message data source
Explanation	Problem while reading the input data source.
Action	Check input data source for errors.

TNS.0001.3016	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3017	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3018	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3019	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3020	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3021	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3022	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3023	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3024E	Unable to determine Content type
Explanation	MIME message does not contain content-type information. Message is improperly structured.
Action	Inform the message sender about the error.
TNS.0001.3025E	Unable to get boundary for multipart mime message
Explanation	MIME message does not contain message boundary information. Message is improperly structured.
Action	Inform the message sender about the error.
TNS.0001.3026	Unable to determine content-type
Explanation	MIME message does not contain content-type information. Message is improperly structured.
Action	Inform the message sender about the error.
TNS.0001.3027	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3028	Unable to read mime message data source
Explanation	The MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3029	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3030	Unable to determine content-type
Explanation	MIME message does not contain content-type information. Message is improperly structured.
Action	Inform the message sender about the error.
TNS.0001.3031E	Unable to determine content-type
Explanation	MIME message does not contain content-type information. Message is improperly structured.
Action	Inform the message sender about the error.
TNS.0001.3032E	Unable to read mime message data source
Explanation	The MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3033E	Unable to construct mime message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3034E	Unable to parse Content-Type string
Explanation	MIME message does not contain content-type information. Message is improperly structured.
Action	Inform the message sender about the error.
TNS.0001.3035E	Cannot write message to outputStream, content is null
Explanation	Message does not contain any data.
Action	Construct a MIME message with valid input data.
TNS.0001.3036E	Operation can only be performed on parsed message.
Explanation	The size of a MIME body part can only be determined for MIME messages that are parsed from a complete message. The size of each part cannot be determined when composing a MIME message.
Action	Do not attempt to obtain the size of a MIME body part that is part of a message that is being composed.

TNS.0001.3037E	Unable to parse 'Content-Disposition'
Explanation	MIME message does not contain content-disposition information. Message is improperly structured.
Action	Inform the message sender about the error.
TNS.0001.3039E	Unable to get content.
Explanation	Error occurred while reading the message content.
Action	Check input data source for errors.
TNS.0001.3040E	Message Digest Algorithm '{0}' not supported.
Explanation	User has specified an invalid value for the 'digestAlgorithm' input parameter of the wm.tn.mime:setDigestAlgorithm service.
Action	Specify a valid value of either "MD5" or "SHA-1" for the 'digestAlgorithm' input parameter.
TNS.0001.3041E	Cannot set header for message that is not multipart. Either specify subType or set header using addBodyPart
Explanation	When calling the wm.tn.mime:createMimeData service, header for a non-multipart message cannot be set .
Action	Specify a value for subType, which will create a multi-part MIME message. Alternatively, for a MIME message that is not multi-part, headers can be specified when calling the wm.tn.mime:addBodyPart service.
TNS.0001.3101E	Parameter input must be an InputStream
Explanation	Input parameter 'input' must be an InputStream object.
Action	Pass in an InputStream object.
TNS.0001.3102	Parameter mimeType cannot be null
Explanation	Input parameter 'mimeType' must be sent.
Action	Pass in an mimeType object.
TNS.0001.3103E	content cannot be null when adding a mime body part
Explanation	Content cannot be null when adding a MIME body part
Action	Specify valid content.

TNS.0001.3104E	Unable to handle content of type {0}
Explanation	Input parameter 'content' must be one of the following types: InputStream, byte, array, or MIME message.
Action	Specify the value of the 'content' input parameter using one of the three allowed types.
TNS.0001.3105E	Parameter index must be of type int
Explanation	Specified a non-integer value for the 'index' input parameter when attempting to obtain a MIME body part.
Action	Check the value of the input parameter 'index' to ensure it is a non-negative integer.
TNS.0001.3106E	outputStream required
Explanation	Calls to the wm.tn.mime:writeToStream service require an OutputStream object to be specified for the 'outputStream' parameter.
Action	Pass an OutputStream object to the wm.tn.mime:writeToStream service.
TNS.0001.3107E	Unknown digest algorithm {0}
Explanation	User has specified an invalid value for the 'digestAlgorithm' input parameter.
Action	Specify a valid value of either "MD5" or "SHA-1" for the 'digestAlgorithm' input parameter.
TNS.0001.3108E	Parameter mimeType cannot be null
Explanation	The 'mimeType' input parameter has a null value.
Action	Specify a valid value for the 'mimeType' parameter.
TNS.0001.3109E	Parameter headerName cannot be null
Explanation	The headerName parameter cannot be null.
Action	Specify a valid value for the 'headerName' parameter.
TNS.0001.3112E	A digest algorithm must be specified when creating a message digest.
Explanation	The user has specified an invalid value for the 'digestAlgorithm' input parameter.
Action	Specify a valid value of either "MD5" or "SHA-1" for the 'digestAlgorithm' input parameter.

TNS.0001.3200E	Cannot recognize certificates
Explanation	Cannot recognize certificates.
Action	Certificates must be passed in as byte array objects.
TNS.0001.3201E	Cannot recognize certificate
Explanation	Cannot recognize certificates.
Action	Check the certificate format. The certificates must be a DER encoded ASN.1 format.
TNS.0001.3202E	Cannot recognize certificate at index {0}
Explanation	Cannot recognize certificate in chain at index: <index>.
Action	Check the certificate format. The certificate must be a DER encoded ASN.1 format.
TNS.0001.3203E	Certificate at index {0} is not valid
Explanation	Cannot recognize certificate at index: <index>
Action	Certificate must be passed in as byte array object.
TNS.0001.3204E	Error attempting to parse message contents
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3205E	Error attempting to read from message source
Explanation	An error occurred while reading message content.
Action	Check input data source for errors.
TNS.0001.3206E	Recipient certificate is not valid
Explanation	Cannot recognize certificates.
Action	Check the certificate format. The certificate must be a DER encoded ASN.1 format.
TNS.0001.3207	Cannot recognize recipient certificate at index {0}
Explanation	Cannot recognize certificate in chain at index: <index>
Action	Check certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3208	Cannot recognize recipient certificate at index {0}
Explanation	Cannot recognize certificate in chain at index: <index>
Action	Check certificate format. The certificate must be a DER encoded ASN.1 format.
TNS.0001.3209E	Cannot recognize recipient certificate at index {0}
Explanation	Cannot recognize certificate at index: <index>.
Action	Check the certificate format. The certificate must be a DER encoded ASN.1 format.
TNS.0001.3210E	Certificate format is invalid for recipient certificate at index {0}
Explanation	Cannot recognize certificate in chain at index: <index>.
Action	Check the certificate format. The certificate must be a DER encoded ASN.1 format.
TNS.0001.3211E	Specified keylength {0}, is not allowed
Explanation	Invalid value specified for key length of RC2 encryption algorithm.
Action	Specify one of the allowed key length values: "40", "64", or "128".
TNS.0001.3212E	Specified algorithm '{0}', is not supported
Explanation	Invalid encryption algorithm is specified.
Action	Specify one of the supported encryption algorithms: "TripleDES", "RC2", or "DES".
TNS.0001.3213E	In getEncryptedMimeObject: Cannot handle datasource of type: {0}
Explanation	When trying to create an encrypted message, the 'mimeSrc' object must be a MimeData object.
Action	Pass in a MimeData object. MimeData objects are created using the wm.tn.mime:createMimeData service.
TNS.0001.3214E	In getEncryptedMimeObject: Cannot handle null datasource
Explanation	The 'mimeSrc' input parameter cannot be null.
Action	Specify a valid MimeData object in the 'mimeSrc' parameter.
TNS.0001.3215	Unable to get signer's private key
Explanation	Private key for sender may be missing.
Action	Ensure in My webMethods that the sender's private key is associated.

TNS.0001.3216E	Unable to get signer's private key
Explanation	Cannot recognize the private key.
Action	Check the supplied private key. It should be a DER encoded ASN.1 representation of an RSA private key.
TNS.0001.3217E	Unable to get recipient certificate(s).
Explanation	Cannot recognize the certificates.
Action	Check the certificate format. The certificate must be a DER encoded ASN.1 format.
TNS.0001.3218E	Signer's certificate is not a valid data format
Explanation	Cannot recognize certificates.
Action	Check the certificate format. The certificate must be a DER encoded ASN.1 format.
TNS.0001.3219E	Signer's certificate is not recognized
Explanation	Cannot recognize certificates.
Action	Check the certificate format. The certificate must be a DER encoded ASN.1 format.
TNS.0001.3220E	Input parameter mimeSrc to service createSignedData cannot be of type {0}. It should be of type MimeData.
Explanation	When trying to create a signed message, the 'mimeSrc' object must be a MimeData object.
Action	Pass in a MimeData object. MimeData objects are created using the wm.tn.mime:createMimeData service.
TNS.0001.3221E	Input parameter mimeSrc to service createSignedData cannot be null. It should be of type MimeData.
Explanation	When trying to create a signed message, the 'mimeSrc' object must be a MimeData object.
Action	Pass in a MimeData object. MimeData objects are created using the wm.tn.mime:createMimeData service.
TNS.0001.3222E	Unable to parse message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.

TNS.0001.3223E	Input parameter mimeSrc should be of type MimeData
Explanation	The 'mimeSrc' object must be a MimeData object or an InputStream object.
Action	Pass in a MimeData or InputStream object. MimeData objects are created using the wm.tn.mime:createMimeData service.
TNS.0001.3224E	Could not obtain message content
Explanation	Error occurred while reading the message content.
Action	Check input data source for errors.
TNS.0001.3225E	Content is not of a recognized encryption type
Explanation	Cannot process the encrypted message.
Action	Contact the sender to re-send the message using the correct format.
TNS.0001.3226E	Given certificate does not decrypt message
Explanation	The message was not encrypted for the certificate that was passed to the service.
Action	First, validate that the correct certificate is used to decrypt the message. Then, if the certificate is the correct one, contact the message sender to determine which certificate was actually used to create the encrypted message.
TNS.0001.3229E	Cannot Process this object. Write this MimeData to stream, then process that stream.
Explanation	Cannot process the object.
Action	Write the MimeData to a stream and then process the stream again.
TNS.0001.3230E	Input parameter mimeType must be a MimeData object
Explanation	The 'mimeType' input parameter is not a MimeData object.
Action	Pass in a MimeData object. MimeData objects are created using the wm.tn.mime:createMimeData service.
TNS.0001.3231E	Message content is not certificates only data. Message could not be processed.
Explanation	The message cannot be handled by the wm.tn.mime:processCertsOnlyData service.
Action	Use the wm.tn.mime:createMimeMessage service to determine if the message is signed or encrypted. Then use either wm.tn.mime:processSignedData or wm.tn.mime:processEncryptedData as appropriate.

TNS.0001.3232E	Input parameter mimeSrc must be a MimeData object
Explanation	The 'mimeSrc' object must be a MimeData object.
Action	Pass a MimeData object. MimeData objects are created using the wm.tn.mime:createMimeData service.
TNS.0001.3233E	Message content is not signed data. Message could not be processed
Explanation	The message cannot be handled by the wm.tn.mime:processSignedData service.
Action	Use the wm.tn.mime:createMimeMessage service to determine if the message is signed or encrypted. Then use either wm.tn.mime:processSignedData or wm.tn.mime:processEncryptedData as appropriate.
TNS.0001.3234E	Signing key is not valid
Explanation	The key used to sign the message is invalid.
Action	Check certificate format. The certificate must be a DER encoded ASN.1 format.
TNS.0001.3235E	Unable to sign document
Explanation	The key used to sign the message is invalid.
Action	Check certificate format. The certificate must be a DER encoded ASN.1 format.
TNS.0001.3236E	Invalid signer certificate file information
Explanation	The signer certificate chain is invalid.
Action	The signer certificate chain must be an array of certificates.
TNS.0001.3237E	Certificate at index {0} not in recognizable format
Explanation	Cannot recognize certificate in chain at index: <index>.
Action	Check certificate format. The certificate must be a DER encoded ASN.1 format.
TNS.0001.3238E	Invalid certificate input at index {0}
Explanation	Cannot recognize certificate in chain at index: <index>.
Action	Check certificate format. The certificate must be a DER encoded ASN.1 format.

TNS.0001.3239E	Signature could not be verified
Explanation	The signature is invalid. The signature cannot be validated.
Action	Contact the message creator to determine what message was originally sent.
TNS.0001.3240E	Expired certificate chain
Explanation	A certificate used to sign the message has expired.
Action	Notify the message creator that the certificates used to sign the message are invalid.
TNS.0001.3241E	Error in certificate chain
Explanation	The certificate chain is invalid.
Action	Check certificate format. The certificates must be a DER encoded ASN.1 format. Ensure that the certificates form a chain. If the chain consists of Cert A and Cert B, the issuer of Cert A should be the same as the subject of Cert B.
TNS.0001.3242E	Untrusted certificate
Explanation	The certificate used to sign the message is not signed by a trusted certificate authority. On the other hand, the signature is structured correctly.
Action	The message should not be trusted because the certificate authority is not trusted. Add the certificate authority to the trusted certificate authorities, or the message creator must use a certificate issued by a trusted certificate authority to sign the message.
TNS.0001.3244E	Error using temporary storage space
Explanation	An error occurred when using the temporary storage system.
Action	See the webMethods Integration Server User Guide for more details. Additional details are available in the exception message.
TNS.0001.3245E	Unable to parse Encrypted Content. Invalid encrypted data.
Explanation	The message cannot be decrypted.
Action	Check the server log for additional error information. The stack trace of this error should contain additional information why this message cannot be decrypted.

TNS.0001.3246E	Unable to decrypt data.
Explanation	The message could not be decrypted.
Action	Check the server log for additional error information. The stack trace of this error should contain additional information why this message cannot be decrypted.
TNS.0001.3247E	Unable to parse Encrypted Content. Private key does not decrypt data.
Explanation	The private key used to decrypt the message cannot decrypt the message.
Action	First, validate that the correct private key is used to decrypt the message. Then, if the private key is correct, contact the message sender to determine which certificate was used to create the encrypted message.
TNS.0001.3248E	Unable to determine hash algorithm. Parameter micalg was null
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3249E	Unable to determine hash algorithm. Unknown micalg: {0}
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3250E	Improperly formed multipart/signed message
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3251E	Cannot process body part of type {0}
Explanation	Error occurred while processing the message.
Action	Check the error message and take action as appropriate.
TNS.0001.3252E	Cannot process signed data with content type {0}
Explanation	Message does not seem to be a signed message and thus cannot be processed by the wm.tn.mime:processSignedData service.
Action	Use the wm.tn.mime:createMimeMessage service to determine if the message is signed or encrypted. Then, use either wm.tn.mime:processSignedData or wm.tn.mime:processEncryptedData as appropriate. Otherwise, obtain the message content by using the wm.tn.mime:getBodyPartContent service.

TNS.0001.3253E	Unable to parse Content Type
Explanation	Source data used to construct the MIME message is not a properly structured MIME message.
Action	Check the input data. Fix the message to conform to the MIME standard.
TNS.0001.3254E	Unable to compute message digest using algorithm: {0}
Explanation	The digest algorithm is either invalid or is not a supported algorithm.
Action	Specify a supported algorithm. Valid values for the digest algorithm are: "SHA-1" or "MD5".
TNS.0001.3255E	Either 'profileAlias' or ('privKey','signerCert') are required
Explanation	To execute properly, the service requires either a valid value for 'profileAlias' or a valid value for the 'privKey' and 'signerCert' input parameters.
Action	Specify a value for either 'profileAlias', or 'privKey' and 'signerCert'. See the webMethods Trading Networks Built-In Services Reference for more details about this service.
TNS.0001.3256E	Either 'profileAlias' or ('privKey','recipientCert') are required
Explanation	To execute properly, the service requires either a valid value for 'profileAlias', or a valid value for the 'privKey' and 'recipientCert' input parameters.
Action	Specify a value for either 'profileAlias', or 'privKey' and 'recipientCert'. See the webMethods Trading Networks Built-In Services Reference for more details about this service.
TNS.0001.3257E	Algorithm {0} not supported
Explanation	The message was encrypted using the <algorithmName> algorithm. Cannot decrypt messages encrypted with this algorithm.
Action	Can decrypt messages that are encrypted with RC2, TripleDes, or DES algorithms only.
TNS.0001.3258E	Invalid RC2 parameter version: {0}
Explanation	This version of the RC2 algorithm is unsupported or invalid. The RC2 algorithm is supported with 40, 64, or 128 bit keys.
Action	Contact the message sender to ensure that a supported RC2 key length is being used.

TNS.0001.3259	Supplied certificate cannot decrypt content
Explanation	Decryption failed as the available certificates failed to decrypt content.
Action	Check if the certificates are correctly mapped to the user.
TNS.0001.3300E	No algorithm specified
Explanation	Mandatory 'algorithm' input parameter contained no value.
Action	Specify a valid value for the 'algorithm' input parameter. Valid values are either "SHA-1" or "MD5".
TNS.0001.3301E	Specified algorithm {0}, not supported
Explanation	The 'algorithm' Input parameter contained an invalid value.
Action	Specify a valid value for the 'algorithm' input parameter. Valid values are either "SHA-1" or "MD5".
TNS.0001.3302E	Security provider not found
Explanation	An internal error occurred.
Action	Contact Software AG Global Support.
TNS.0001.3303E	Input to createMessageDigest must be byte[] or InputStream
Explanation	The 'input' parameter must be a byte array or InputStream object.
Action	Specify a byte array or InputStream for the 'input' parameter.
TNS.0001.3304E	Parameter 'data' must be a byte[] or InputStream
Explanation	The 'data' input parameter must be a byte array or InputStream object.
Action	Specify a byte array or InputStream for the 'data' parameter.
TNS.0001.3305E	Parameter 'signerInfo' cannot be null
Explanation	Mandatory 'signerInfo' input parameter must contain a value.
Action	Specify valid information for the 'signerInfo' input parameter.
TNS.0001.3306E	Unable to process 'signerInfo' at index {0}
Explanation	An error occurred attempting to process the signerInfo at index <index>.
Action	The server error log contains a stack trace with additional information about the error.

TNS.0001.3307E	Invalid certificate chain
Explanation	Cannot recognize certificates.
Action	Check certificate format. The certificate must be a DER encoded ASN.1 format.
TNS.0001.3308E	Invalid certificate at index {0}
Explanation	Cannot recognize certificate in chain at index: <index>.
Action	Check certificate format. The certificate must be a DER encoded ASN.1 format.
TNS.0001.3309E	Required parameter 'signatureStream' cannot be null.
Explanation	Required 'signatureStream' parameter cannot be null.
Action	Pass an OutputStream object to the wm.tn.mime:sign service, in the 'signatureStream' parameter.
TNS.0001.3310E	Error occured reading input stream, cannot construct signature.
Explanation	Error occurred while reading the message content.
Action	Check input data source for errors.
TNS.0001.3311E	Hash Algorithm {0} not supported for signer at index {1}
Explanation	Hash Algorithm <algorithmName> not supported for signer at index <index>.
Action	Change the <algorithmName> at <index> to be one of the allowed algorithm names: "MD5" or "SHA-1".
TNS.0001.3312E	Bad certificate. Unable to set signer certificates.
Explanation	Cannot recognize certificate in chain at index: <index>.
Action	Check certificate format. The certificate must be a DER encoded ASN.1 format.
TNS.0001.3313E	Input parameter 'signature' cannot be null.
Explanation	The 'signature' input parameter cannot be null.
Action	Pass the signature to verify into the service in the 'signature' input parameter. The 'signature' object should be either a byte array or an InputStream object.

TNS.0001.3314E	Input parameter 'signature' must be a byte[] or InputStream
Explanation	The 'signature' input parameter must be a byte[] or InputStream.
Action	The 'signature' input parameter must be a byte[] or InputStream.
TNS.0001.3315E	Input parameter 'data' required for verifying detached signature
Explanation	The 'data' input parameter cannot be null.
Action	Pass in the 'data' input parameter of the service, the data that is to be verified. The 'data' object should be either a byte array or an InputStream object.
TNS.0001.3316E	Input parameter 'data' must be a byte[] or InputStream
Explanation	The 'data' input parameter must be a byte[] or InputStream.
Action	The 'data' input parameter must be a byte[] or InputStream.
TNS.0001.3317E	An error occurred while attempting to verify the signature.
Explanation	Problem while reading from input data source.
Action	Check input data source for errors.
TNS.0001.3318E	Signature provided is not PKCS#7 SignedData
Explanation	Signature provided is not PKCS#7 SignedData.
Action	The wm.tn.mime:verify service can verify PKCS#7 SignedData signature only.
TNS.0001.3319E	Input parameter 'outputStream' must be an OutputStream
Explanation	The 'outputStream' input parameter must be an OutputStream.
Action	The 'outputStream' input parameter must be an OutputStream.
TNS.0001.3320E	Input contained no signer information when processed as {0} type signature
Explanation	The message is not properly signed.
Action	This message cannot be verified. Contact the message creator to verify the proper message structure.
TNS.0001.3321E	Parameter 'data' must be null when parameter detachedSignature equals false.
Explanation	The 'data' parameter must be null when 'detachedSignature' parameter equals to false.
Action	If the signature is detached, then set the 'detachedSignature' parameter to "true". Otherwise, do not pass in a value for 'data'. The signed message should be passed in via the 'signature' input parameter.

TNS.0001.3322	Parameter 'data' must not be null
Explanation	The 'data' input parameter cannot be null.
Action	Pass the data into the service in the 'data' input parameter. The 'data' object should be either a byte array or an InputStream object.
TNS.0001.3323E	Certificate chain cannot be null
Explanation	Certificate chain cannot be null.
Action	Specify a certificate chain to use to sign this message.
TNS.0001.3324E	Private key or keyAlias required
Explanation	Private key or keyAlias required.
Action	To sign this message, specify either a private key, or use a keyAlias.
TNS.0001.3325E	Unable to decode signed message. Verify that signature type specified (detached or implicit) matches actual type.
Explanation	Unable to decode the signed message.
Action	Verify that the specified signature type (detached or implicit) matches the actual type.
TNS.0001.3326	Unable to create digest. Input parameter 'data' must be of type com.wm.app.tn.mime.DigestableInputStream or byte[].
Explanation	Error while creating message digest.
Action	Check that the input parameter is passed correctly. Input parameter 'data' must be of type com.wm.app.tn.mime.DigestableInputStream, or byte[].
TNS.0001.3327E	Unable to write message to outputStream.
Explanation	Error occurred while writing the signed message.
Action	The server error log contains a stack trace with additional information about the error.
TNS.0001.3328E	Only one '{0}' can be specified in 'signerInfo'
Explanation	When signing a message using a profile alias, you can only use one alias.
Action	Sign the message with only one profile alias.

TNS.0001.3400E	Values are required for both input parameters type and id
Explanation	Values are required for both 'type' and 'id' input parameters.
Action	Set the 'type' input parameter to "file" and the 'id' parameter to the name of the file that the InputStream will read from.
TNS.0001.3401E	Input parameter type cannot be null
Explanation	Values are required for both 'type' and 'id' input parameters.
Action	Set the 'type' input parameter to "file" and the 'id' parameter to the name of the file that the InputStream will read from.
TNS.0001.3402E	Input parameter id cannot be null
Explanation	Values are required for both 'type' and 'id' input parameters.
Action	Set the 'type' input parameter to "file" and the 'id' parameter to the name of the file that the InputStream will read from.
TNS.0001.3403E	Unable to open SharedInputStream
Explanation	An error occurred while reading from the specified data source.
Action	Check that the specified data source exists. The Integration Server error log should contain additional error information.
TNS.0001.3404E	Value '{0}' for parameter type is not supported. Please select from allowed values.
Explanation	The 'type' input parameter must be set to "file".
Action	Provide an allowed value. The 'type' input parameter must be set to "file".
TNS.0001.3500E	No profile exists for profile alias '{0}'
Explanation	A profile with that name has not been created.
Action	Check that the PKI profile has been created properly. See the webMethods Integration Server Administrator's Guide for more details.
TNS.0001.3501E	Parameter '{0}' must not be null
Explanation	The parameter called <parameterName> must be available but it does not exist in the pipeline .
Action	Specify a valid value for the <parameterName> parameter.

TNS.0001.3502E	Service '{0}' in package WmTNPki not enabled
Explanation	The WmTNPki package is disabled.
Action	Ensure that the WmTNPki package is installed and enabled.
TNS.0001.4001E	No profile store to validate partner ID
Explanation	Unable to retrieve the profile store, probably due to a database error or a validation error.
Action	Check that the data is not corrupted or the database connection is active.
TNS.0001.4002E	Error transforming attribute {0}: {1}
Explanation	An exception was thrown while transforming a document attribute value.
Action	The exception was written to the server log. See the log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0001.4003E	BizDocAttribute: can't connect to profile store
Explanation	Encountered an exception during initialization.
Action	Contact Software AG Global Support. Prepare the following information: server and error logs, a copy of the Support Information page from the Trading Networks Console, and the WmTN/config/properties.cnf file.
TNS.0001.4006E	No profile store to transform attribute {0}
Explanation	Trading Networks was unable to retrieve the profile store.
Action	The exception was written to the server log. See the log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0001.4007E	Unable to transform attribute {0}: attribute type {1} doesn't match function type {2}
Explanation	Trading Networks could not transform the value of the attribute because the selected transformation is inappropriate for the data type of the attribute.
Action	Using My webMethods, update the TN document type that specifies the invalid transformation for the specified attribute. Select a transformation that is appropriate for the data type of the attribute.

TNS.0001.4008E	Error fetching all attributes: {0}
Explanation	An exception was thrown while reading all attributes from the database.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0001.4009E	Error defining attribute {0}: {1}
Explanation	An exception was thrown while saving an attribute to the database.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0001.4010E	Error listing types for {0}: {1}
Explanation	An exception was thrown while retrieving all TN document types that use an attribute.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0001.4011E	Error redefining attribute {0}: {1}
Explanation	An exception was thrown while updating an attribute in the database.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0001.4012E	Supplied value must be a number
Explanation	A processing rule contains extended criteria that uses a custom attribute with a NUMBER data type. However, the value you specified in the condition for this attribute is not a numeric value.
Action	Using My webmethods, update the extended criteria in the processing rule to provide a numeric value for attributes that have a NUMBER data type.
TNS.0001.4013E	Supplied value can not be transformed to a date
Explanation	A processing rule contains extended criteria that uses a custom attribute with a DATETIME data type. However, the value you specified in the condition for this attribute is not a date.
Action	Using My webmethods, update the extended criteria in the processing rule to supply a date value for attributes that have a DATETIME data type.
TNS.0001.4014E	{0} attribute value is a date but there is no transform.
Explanation	A TN document type indicates that a custom attribute with a DATETIME data type should be extracted from a document. However, the TN document type does not specify a date transformation for the custom attribute.
Action	Using My webmethods, update the TN document type to specify an appropriate date transformation for the custom attribute.

TNS.0001.4015E	{0} attribute is configured for custom transformation, but no transformation service is specified.
Explanation	A TN document type indicates that a custom attribute should perform custom attribute transformation. However, the TN document type does not specify a transformation service.
Action	Using My webMethods, update the TN document type to specify a transformation service.
TNS.0001.4016E	Error performing custom transformation on the {0} attribute.
Explanation	Encountered an exception while updating an attribute in the database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0001.4017E	Custom transformation {0} for the {1} attribute returned the wrong type. Should be {2}
Explanation	Custom attribute transformation did not return the data type that matches the data type of the associated attribute.
Action	Modify the custom attribute transformation service to return the correct data type specified in the error message.
TNS.0001.4018E	Custom transformation service {0} for the {1} attribute did not return "newValues" in the pipeline.
Explanation	Custom attribute transformation service did not return the required output parameter 'newValues'.
Action	Modify the custom attribute transformation service to return the 'newValues' output parameter.
TNS.0001.4019E	{0} attribute value is a date list but there is no transform.
Explanation	The TN document type does not specify a transformation for a date list type attribute.
Action	Using My webMethods, update the TN document type to specify a transformation service.
TNS.0001.4020E	Unable to parse the given value. Value {0} could not be converted to date format
Explanation	Unable to convert the value extracted from the document to a date format.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.4021E	Attribute transformation for {0} of doctype {1} generated an exception. The original exception message is: {2}.
Explanation	Encountered an exception while updating an attribute in the database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0001.4022E	Attribute transformation function code {0} is invalid.
Explanation	A TN document type indicates an invalid attribute transformation function.
Action	Using My webMethods, update the TN document type to specify a valid transformation function.
TNS.0001.5006E	Converting the signed body of this document into a string failed. Verification cannot continue. The original signed body was {0}.
Explanation	Conversion failed for a document.
Action	If the signed body of the document is invalid, notify the document sender.
TNS.0001.5008E	This doctype ({0}) has no verification service defined. Verification cannot continue.
Explanation	This TN document type (<doctypeName>) has no verification service defined.
Action	If you are using a built-in TN document type, contact Software AG Global Support. If you are using your own TN document type, specify a verification service for it.
TNS.0001.5009E	No Verification Service
Explanation	The TN document type has no verification service defined. Verification cannot continue.
Action	If you are using a built-in TN document type, contact Software AG Global Support. If you are using your own TN document type, specify a verification service for it.
TNS.0001.5011E	The signature query for doctype {0} ({1}) generated an error. The error was {2}.
Explanation	The signature query (<query>) for the TN document type (<doctypeName>) generated an error. The error was <exceptionMessage>.
Action	If the signed body of the document is invalid, notify the document sender.

TNS.0001.5015E	Query Failed
Explanation	A signature query was defined for the TN document type but it failed to produce a result for this document.
Action	Either adjust the signature query that is defined in the TN document type, or notify the document sender that the structure of the document is incorrect.
TNS.0001.5017E	This document type ({0}) is missing one or both of its signature queries (Signature and SignedBody). Verification cannot proceed.
Explanation	One or both of this document type signature queries (Signature and SignedBody) may be missing.
Action	Using My webMethods, update the TN document type to specify both, a signature query and a signed body query.
TNS.0001.5018E	Missing Signature Query(s)
Explanation	This TN document type is missing one or both of its signature queries (Signature and SignedBody). Trading Networks cannot proceed with the verification of the signature.
Action	Using My webMethods, update the TN document type to specify both, a signature query and a signed body query.
TNS.0001.5019E	The signed body query for doctype {0} ({1}) generated an error. The error was {2}.
Explanation	The signed body query (<query>) for the TN document type (<doctypeName>) generated an error. The error was <exceptionMessage>.
Action	Take appropriate action to resolve the problem described in the exception. If the structure of the document is incorrect, notify the document sender.
TNS.0001.5020E	The signature of this document was invalid; no information was available about the party or parties that signed it.
Explanation	The signature of this document might be invalid.
Action	Notify the document sender.
TNS.0001.5021E	No Signer Info Available
Explanation	The signature of this document was not valid. No information was available about the party or parties that signed it.
Action	Notify the document sender.

TNS.0001.5022E	The PKCS verification service, pub.security.pkcs7:verify, produced an error trying to verify this document. The error was {0}.
Explanation	Encountered an exception while verifying a document signature.
Action	Take appropriate action to resolve the problem described in the exception. If the signature is invalid, notify the document sender.
TNS.0001.5023E	PKCS Service Error
Explanation	The PKCS verification service pub.security.pkcs7:verify, produced an error while trying to verify this document.
Action	Take appropriate action to resolve the problem described in the exception. If the signature is invalid, notify the document sender.
TNS.0001.5024E	The verification service for this document ({0}) generated an error. The original error was {1}.
Explanation	An exception was thrown while verifying a document signature.
Action	Take appropriate action to resolve the problem described in the exception. If the signature is invalid, notify the document sender.
TNS.0001.5025E	Verification Failed
Explanation	An exception was thrown while verifying a document signature.
Action	Take appropriate action to resolve the problem described in the exception. If the signature is invalid, notify the document sender.
TNS.0001.5026E	The signature query for doctype {0} ({1}) failed to produce a value. Without a signature, verification cannot proceed.
Explanation	A signature query was defined for the TN document type but it failed to produce a result for this document.
Action	Either update the TN document type to adjust the signature query, or notify the document sender that the structure of the document is incorrect.
TNS.0001.5028E	The signed body query for doctype {0} ({1}) failed to produce a value. Without a signed body, verification cannot proceed.
Explanation	A signed body query was defined for the TN document type but it failed to produce a result for this document.
Action	Either update the TN document type to adjust the signed body query, or notify the document sender that the structure of the document is incorrect.

TNS.0001.5030E	Base-64 decoding the signature for this document failed to produce a value. The signature (before decoding) was {0,number} bytes.
Explanation	An error occurred while decoding the signature. The signature might be invalid.
Action	Notify the document sender.
TNS.0001.5031E	Decoding Error
Explanation	Trading Networks could not decode the signature. The signature might be invalid.
Action	Notify the document sender.
TNS.0001.5032E	XML {0} failed: does not apply to non-XML documents
Explanation	Trading Networks attempted to perform an operation on a non-XML document. However, the operation can be performed only on XML documents.
Action	Check whether the input document is a valid XML document.
TNS.0001.5033E	XML {0} failed: no document content available
Explanation	Trading Networks attempted to perform an operation that failed because the document has no content.
Action	Notify the document sender.
TNS.0001.5034E	Bad XML content
Explanation	An exception was thrown while retrieving the document.
Action	The document may not be a valid XML document.
TNS.0001.5035E	An error prevented fetching the content of this XML document for {0}. The original error was {2}.
Explanation	An exception was thrown while retrieving the document.
Action	Check the database and make sure that the data is not corrupted.
TNS.0001.5036E	Signature Verification failed : The verification service, {0} aborted processing of this document. The message was {1}.
Explanation	A RoutingAbortedException was thrown by the verification service that caused the document processing to abort.
Action	Take appropriate action to resolve the problem described in the exception. If the document is invalid, notify the sender.

TNS.0001.5037E	The signing service, {0} aborted processing of this document. The message was {1}.
Explanation	A RoutingAbortedException was thrown by the verification service, which caused the document processing to abort.
Action	Take appropriate action to resolve the problem described in the exception. If the document is invalid, notify the sender.
TNS.0001.6001E	Attribute transform for {0} of doctype {1} failed to produce a value. The transform function was {3}, the first original value was {2}.
Explanation	The data type of the attribute might not match the type of the data extracted from the document.
Action	Make sure that the data type of the attribute matches the type of the data extracted from the document. If this is an XML TN document type, make sure that the XQL query that extracts the attribute is correct.
TNS.0001.6002E	Attribute query for {0} of doctype {1} failed to produce a result. The document may not be complete. The query was: {2}
Explanation	The XQL query for the attribute did not return a value.
Action	Change the XQL query accordingly to return correct result.
TNS.0001.6003E	Attribute query for {0} of doctype {1} generated an exception. The original exception message is: {2}.
Explanation	There is either a problem with the document, or with the query.
Action	Examine the document to see if it is well-structured XML. Correct and resubmit if needed. Examine the query to ensure that it is valid. Change the query if needed.
TNS.0001.6004E	Unable to get XML content for corrupted doc {0}. The original exception message is: {1}.
Explanation	The document may be corrupted.
Action	Fix the document and submit it again.
TNS.0001.6005E	Transform for {0} of doctype {1} generated an exception. The transform function was {2}. The original exception message is: {3}.
Explanation	There is either a problem with the document, or with the query.
Action	Examine the document to ensure that it is well-structured XML. Correct and resubmit if needed. Examine the query to ensure that it is valid. Adjust the query if needed.

TNS.0001.6006E	Transform for {0} of doctype {1} failed to produce a value. The transform function was {3}, the first original value was {2}.
Explanation	Perhaps the data type of the attribute does not match the type of the data extracted from the document.
Action	Make sure that the data extracted from the document is the same type as the attribute. If this is an XML TN document type, make sure that the XQL query that extracts the attribute is correct.
TNS.0001.6007E	Envelope query for {0} of doctype {1} failed to produce a result. The document may not be complete. The query was: {2}
Explanation	The XQL query for the attribute did not return a value.
Action	Fix the XQL query, if needed.
TNS.0001.6008E	Envelope query for {0} of doctype {1} generated an exception. The original exception message is: {2}.
Explanation	The document may be corrupted.
Action	Correct the document and submit it again.
TNS.0001.6009E	There was an error in trying to get XML header information (DOCTYPE and DTD). The document ({0}) is probably not valid XML.
Explanation	Probably, the document is not a well-structured XML.
Action	Correct the document and submit it again.
TNS.0001.6010E	There was an error in trying to get XML header information (DOCTYPE and DTD). The document ({0}) is probably not valid XML. The original exception message is: {1}
Explanation	Probably, the document is not a well-structured XML.
Action	Correct the document and submit it again.
TNS.0001.6011E	XQL query {1} failed recognizing document {0}. The document is probably not valid XML. The original exception message is: {2}.
Explanation	Probably, the document is not a well-structured XML. See the exception message for details.
Action	Correct the document and submit it again.

TNS.0001.6013E	No bizdoc supplied to lookup validation schema
Explanation	The wm.tn.doc.xml:getRecordBlueprint service was invoked with no BizDocEnvelope in the pipeline.
Action	Supply a BizDocEnvelope when invoking the wm.tn.doc.xml:getRecordBlueprint service.
TNS.0001.6014E	Non-XML bizdoc supplied to lookup validation schema
Explanation	The BizDocEnvelope passed to the wm.tn.doc.xml:getRecordBlueprint service is not an XML document type.
Action	Supply a BizDocEnvelope that matches an XML TN document type when invoking the wm.tn.doc.xml:getRecordBlueprint service.
TNS.0001.6015E	No bizdoc ID supplied for testing validation
Explanation	The wm.tn.doc.xml:testValidate service was invoked with no internal document ID in the pipeline.
Action	Supply an internal document ID (docID) when invoking the wm.tn.doc.xml:testValidate service.
TNS.0001.6016E	No such bizdoc: {0}
Explanation	The wm.tn.doc.xml:testValidate service was invoked with an invalid internal document ID in the pipeline.
Action	Provide a valid internal document ID when invoking the wm.tn.doc.xml:testValidate service.
TNS.0001.6017E	Required attribute is missing
Explanation	An attribute is defined as required by the document type but the document that matched the document type did not contain this attribute.
Action	Either change the document type so that this attribute is no longer required, or instruct the document sender to supply a value for the attribute.
TNS.0001.6018E	The {0} attribute is required by the {1} doctype. The query {2} did not return any results
Explanation	An attribute is defined as required by the document type but the document that matched the document type did not contain this attribute.
Action	Either change the document type so that this attribute is no longer required, or instruct the document sender to supply a value for the attribute.

TNS.0001.6019E	Attribute transformation for {0} of doctype {1} generated an exception. The query is {2}. The original exception message is: {3}.
Explanation	Encountered an exception.
Action	If the document is corrupted, notify the document sender.
TNS.0001.7003	Error while getting {0}. Find if the EDI package is enabled and running in Integration Server.
Explanation	WmEDI Package may be disabled.
Action	Check if the WmEDI package is enabled and running in Integration Server.
TNS.0001.7004	Error while getting EDI Standards. Input for standard field cannot be null, its is a mandatory field.
Explanation	Input for standard field cannot be null, it is a mandatory field.
Action	Configure the standard field in the input and run the service.
TNS.0001.7005	Error while getting EDI Transactions. Input for standard field cannot be null, its is a mandatory field.
Explanation	Input for standard field cannot be null, it is a mandatory field.
Action	Configure the standard field and run the query again.
TNS.0001.7006	Error while getting EDI Transactions. Input for version field cannot be null, its is a mandatory field.
Explanation	Input for version field cannot be null, it is a mandatory field.
Action	Configure the version field and run the query again.
TNS.0001.7007	Error while getting {0}. Input for {1} field cannot be null, its is a mandatory field.
Explanation	Input field suggested in error message is a mandatory field.
Action	Configure the input field and run the query again.
TNS.0001.7008	Error while querying for document attributes.
Explanation	Encountered an exception while querying document attributes.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.7009	Error while getting the related doctypes for doctype attribute {0}.
Explanation	An error occurred while getting related doctypes for the associated doctype attribute. The error may be because of an SQLException.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0001.7010	Error while changing the status of the doctype attributes.
Explanation	An error occurred while changing the status of the doctype attributes.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0001.7011	Error while getting doctype attribute for doctype attribute ID {0}.
Explanation	An error occurred while getting doctype attribute for the associated attribute ID. This may be because of an SQLException while querying the attribute.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0001.7012	Error while updating doctype attribute for doctype attribute ID {0}.
Explanation	An error occurred while updating the doctype attribute. This may be because of an SQLException while updating the attribute.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0001.7013	Error while changing the status of the doctype attribute ID {0}.
Explanation	An error occurred while updating the doctype attribute. This may be because of an SQLException while updating the attribute.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0001.7014	Error while viewing doctype attribute. Input for docAttrID field cannot be null, its is a mandatory field.
Explanation	An error occurred while viewing the doctype attribute. This may be because of an SQLException while querying for the attribute.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0001.7015	Error while updating doctype attribute. Input for docAttrID field cannot be null, its is a mandatory field.
Explanation	Input for docAttrID field cannot be null, it is a mandatory field.
Action	Configure the docAttrID field while updating the doctype attribute.
TNS.0001.7016	Error while adding doctype attribute. Check whether all input variables have been passed properly.
Explanation	Some mandatory fields may not have been passed before calling the service.
Action	Configure all input variables before calling the service.
TNS.0001.7017E	Attribute name "{0}" already exists. Change the name and save again.
Explanation	Attribute with the same name already exists.
Action	Change the attribute name and save.
TNS.0001.7018	Error while updating doctype attribute. Attribute name with "{0}" already exists. Change the name and save again.
Explanation	Attribute with same name already exists.
Action	Change the name and save.
TNS.0001.7019	Error while querying for document attributes {0}.
Explanation	An error occurred while querying doctype attributes. This may be because of an SQLException while querying the attribute.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0002.1001E	"{0}" is empty. At least one {1} must be supplied. Please supply the required value.
Explanation	You did not supply a value for the specified variable. At least one value is required.
Action	Supply at least one value for the specified field and try again.
TNS.0002.1002E	"{0}" and "{1}" are required ({0}={2}, {1}={3}). Please supply the required values.
Explanation	Both values are required.
Action	Supply both values.

TNS.0002.1009E	The value originally supplied as sender ID for this document was not a valid partner ID. The value was {0}.
Explanation	Partner ID supplied as sender ID is not being recognized as valid partner.
Action	Either create a partner profile for the document sender, add this ID to an existing partner's profile, or tell the document sender to resend the document using a different sender ID value.
TNS.0002.1010E	Error formatting error message {0}: {1}
Explanation	Unable to format the error message.
Action	Contact Software AG Global Support.
TNS.0002.1011E	The value originally supplied as receiver ID for this document was not a valid partner ID. The value was {0}.
Explanation	Partner ID supplied as receiver ID is not being recognized as valid partner.
Action	Either create a partner profile for the document receiver, add this ID to an existing partner's profile, or tell the document sender to resend the document using a different receiver ID value.
TNS.0002.1012E	{0} is null.
Explanation	An internal variable is unexpectedly null.
Action	Contact Software AG Global Support.
TNS.0002.1013E	At least one of "{0}" and "{1}" is required.
Explanation	At least one of the input fields is required, either its null or empty.
Action	Provide non-null value for at least one input parameter and try again.
TNS.0002.1016E	"sourceVersion" is required. Please supply the required value.
Explanation	A required value is missing.
Action	Supply the required value.
TNS.0002.1017E	"feature" is required. Please supply the required value.
Explanation	A required value is missing.
Action	Supply the required value.

TNS.0002.1018E	At least one input is required.
Explanation	All input fields are found to be null, at least one input should not be null.
Action	Provide at least one non-null value for input and try again.
TNS.0002.1019E	Enumeration contains elements that are not Strings.
Explanation	An unexpected value was passed to an internal method.
Action	Contact Software AG Global Support.
TNS.0002.1021E	schema cannot be null.
Explanation	Attempted to create a Trading Networks IData object with an empty set of name/value pairs.
Action	Contact Software AG Global Support.
TNS.0002.1022E	schema rows must be 2 wide
Explanation	Attempted to create a Trading Networks IData object without set of name/value pairs.
Action	Contact Software AG Global Support.
TNS.0002.1023E	keys cannot be null
Explanation	Attempted to create a Trading Networks IData object with keys as null. Keys cannot be null.
Action	Contact Software AG Global Support.
TNS.0002.1024E	index out of bounds: {0}
Explanation	Attempted to seek beyond the end of or before the start of a TNFixedData object.
Action	Supply a valid index to the seek method.
TNS.0002.1025E	TNFixedData does not support setKey
Explanation	Attempted to use an unsupported method.
Action	Do not call the setKey method.
TNS.0002.1027E	TNFixedData does not support delete
Explanation	Attempted to use an unsupported method.
Action	Do not call the delete method.

TNS.0002.1028E	illegal null key
Explanation	Supplied a null key to the keyMatch method on a TNFixedData object.
Action	Supply a valid key value.
TNS.0002.1031E	Must supply props
Explanation	A required value(props) is missing for wm.tn.admin:setProperties().
Action	Supply the required value for field(props) and try again.
TNS.0002.1032E	Must shutdown before starting up again
Explanation	Invoked the wm.tn.admin:startup service while the WmTN package is enabled and loaded.
Action	Use the Integration Server Administrator to stop and start the WmTN package. Do not invoke the wm.tn.admin:start service directly.
TNS.0002.1042E	No such enum: {0}
Explanation	A wm.tn.enumerate service was invoked with an invalid query enumeration identifier.
Action	Supply a valid enumeration identifier.
TNS.0002.1043E	Either {0} or {1} must be supplied. Please supply one of these values.
Explanation	A valid value for either of the required field was not supplied.
Action	Supply one of the valid values which are listed in the error message.
TNS.0002.1044E	{0} is required whenever a value for {1} is supplied. Please supply a value for {0}.
Explanation	A storageRef value was supplied, but no value was supplied for storageType.
Action	Supply a value for the storageType variable. Either supply value for both related fields or keep both fields null and try again.
TNS.0002.1047E	The following TN properties can only take numeric values: {0}
Explanation	Attempted to assign non-numeric values to numeric system properties.
Action	Supply numeric values for numeric system properties.

TNS.0002.1048E	Error setting features on SAX parser. Exception message is: {0}
Explanation	Threw a SAXException while initializing the SAX parser.
Action	Contact Software AG Global Support.
TNS.0002.1056E	The {0} service is for Trading Networks internal use only.
Explanation	The specified service was invoked, but not by Trading Networks. This service is for Trading Networks internal use only.
Action	Do not invoke this service.
TNS.0002.1057E	Error encountered in invoking service wm.tn.samples.helpServices:installTNSamplesACLs
Explanation	Internal error installing ACLs for Trading Networks Sample services.
Action	If you want to protect the WmTNSamples services, invoke the wm.tn.samples:installTNSamplesACLs service.
TNS.0002.1058E	Error encountered in writing TN ACL information to disk
Explanation	An exception was thrown saving the Trading Networks ACLs to the file system.
Action	The exception was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0002.1059E	ThreadQueue: too many jobs waiting
Explanation	Attempted to spawn more threads than the configured limit.
Action	Use the wm.tn.admin:setThreadQueueConfig service to increase the value of the tn.thread.maxWaiting system property.
TNS.0002.1061E	{0} is not an Integer
Explanation	Invalid data type supplied to a service, expected an Integer value
Action	Supply an Integer for the specified field.
TNS.0002.1065	Error encountered while unregistering TN's XML content handler. The exception message is: {0}
Explanation	Error occurred while unregistering TN's content handler and activating default XML content handler.
Action	See the server log for details. Take appropriate action to resolve the problem described in the exception.

TNS.0002.1066	When scheduleType is {0}, a value must be supplied for {1}. Please supply a value for {1}.
Explanation	Attempted to create new queue with schedule values null for a selected scheduleType.
Action	Supply valid values corresponding to selected schedule type.
TNS.0002.1067E	Unable to update password for {0} with handle {1}
Explanation	An exception was thrown when Trading Networks attempted to update the password associated with a profile delivery method.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0002.1068E	Unable to retrieve password for {0} with handle {1}
Explanation	An exception was thrown when Trading Networks attempted to retrieve the password associated with a profile delivery method.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0002.1069E	Unable to insert password for {0} with handle {1}
Explanation	An exception was thrown when Trading Networks attempted to insert the password associated with a profile delivery method.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0002.1070E	Unable to save password for {0} with handle {1}
Explanation	An exception was thrown when Trading Networks attempted to save the password associated with a profile delivery method.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0002.1071E	Unable to delete password for {0} with handle {1}
Explanation	An exception was thrown when Trading Networks attempted to delete the password associated with a profile delivery method.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0002.1072E	Either {0} or {1} must be supplied, but not both. Please supply a value for only one of these.
Explanation	You supplied the specified two values; however, only one value can be specified.
Action	Supply value for either partByets or partStream and try again.

TNS.0002.1073	Unable to import document type {0}. Attribute {1} is used in the document type but, it is not defined.
Explanation	While importing a doctype, related attribute not found, so unable to import the doctype.
Action	Please either import the related attribute or define before importing the doctype.
TNS.0002.1075	Unable to import processing rule {0}. Sender profile {1} is used in the processing rule but, it is not defined.
Explanation	While importing a processing rule, related sender profile not found, so unable to import the processing rule.
Action	Either import the related sender profile or define it before importing the processing rule.
TNS.0002.1076	Unable to import processing rule {0}. Receiver profile {1} is used in the processing rule but, it is not defined.
Explanation	While importing a processing rule, related receiver profile not found, so unable to import the processing rule.
Action	Either import the related receiver profile or define it before importing the processing rule.
TNS.0002.1077	Unable to import processing rule {0}. Document type {1} is used in the processing rule but, it is not defined.
Explanation	While importing a processing rule, related Document Type not found, so unable to import the processing rule.
Action	Either import the related document type or define it before importing the processing rule.
TNS.0002.1081	Error encountered while extracting doctype with doctypeID {0}. Please check whether it is a valid ID.
Explanation	Could not retrieve Document Type from BizDocStore with provided docTypeID, would not be able to enable/update doc type for monitoring.
Action	Please check whether provided docTypeID is a valid ID, as system was not able to retrieve corresponding Document Type from store.

TNS.0002.1083	Error encountered while setting TN BAM Monitoring status to {0}
Explanation	Error encountered while enabling/disabling TN BAM monitoring. This happened while setting monitoring properties invoking service <code>wm.tn.admin:setProperties()</code> .
Action	Please see the error log.
TNS.0002.2005S	Error(s) encountered in WmTN initialization: {0}
Explanation	Encountered an exception while Trading Networks was initializing. This happened during filling the cache of attribute, type, routing rule and profile.
Action	Take appropriate action to resolve the problem described in the exception and try to reload the package.
TNS.0002.2013S	The <code>wm.tn.access:getConsoleRestrictions</code> service has been deleted, renamed or replaced. Aborting Trading Networks initialization.
Explanation	Aborting Trading Networks initialization as the <code>wm.tn.access:getConsoleRestrictions</code> service has been tempered.
Action	Please contact your administrator to restore the original version of this service.
TNS.0002.2014E	Error filling BizDocAttributeStore cache
Explanation	Encountered an error while reading the document attributes from the database during startup.
Action	An exception was written to the server log. Take appropriate action to resolve the problem described in the exception.
TNS.0002.2018W	Unable to register content types with the FlatFile Content Handler. The WmFlatFile package may be disabled. The WmFlatFile package must be enabled in order to use FlatFile capabilities in Trading Networks.
Explanation	The WmFlatFile package is disabled. Unable to register content types with the FlatFile Content Handler.
Action	The WmFlatFile package may be disabled. The WmFlatFile package must be enabled in order to use FlatFile capabilities in Trading Networks.
TNS.0002.3007E	<code>wm.tn.admin:installACLs</code>: Unable to find group, {0}
Explanation	The specified group, <code><group></code> , has not been created.
Action	Run the <code>wm.tn.admin:install</code> service to create the Trading Networks user groups.

TNS.0002.3010S	Can not create IS user group {0}
Explanation	An exception was thrown while creating a user group during server startup.
Action	Contact Software AG Global Support.
TNS.0002.3011E	Can not create IS user {0}
Explanation	An exception was thrown while creating a user during server startup.
Action	Contact Software AG Global Support.
TNS.0002.4011E	Error encountered during TN server starting: {0}
Explanation	An exception was thrown while Trading Networks was starting.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0002.4012E	Error encountered during TN server stopping: {0}
Explanation	An exception was thrown while Trading Networks was stopping.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0002.4013E	Error encountered during TN server restarting: {0}
Explanation	An exception was thrown while Trading Networks was restarting.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0002.4019E	TN database connection pool failed: error initializing Datastore
Explanation	An exception was thrown while initializing the Trading Networks database connection pool.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception. Check TN DB configuration details.
TNS.0002.4020E	TN Server failed starting up: error initializing database connection pool
Explanation	An exception was thrown while initializing the Trading Networks database connection pool.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception. Check TN DB configuration details.

TNS.0002.4021E	TN Server failed starting up: OEM restriction was hacked
Explanation	A user or developer attempted to bypass the OEM restrictions. The server will not start.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0002.4024E	TN task manager encountered error: {0}
Explanation	An exception was thrown that has terminated execution of the task manager.
Action	Take appropriate action to resolve the problem described in the exception. You might need to contact Software AG Global Support.
TNS.0002.4025E	TN temporary storage space initialization failed: {0}
Explanation	An exception was thrown while preparing temporary disk space for large files.
Action	Take appropriate action to resolve the problem described in the exception. You might need to change the tn.tspace.location system property to a disk partition that has more free space.
TNS.0002.4028E	Invalid notification type encountered in pkginit:sendNotif
Explanation	Internal error.
Action	Contact Software AG Global Support.
TNS.0002.4039E	MBean cannot record statistics for document id {0}. Document does not exist.
Explanation	Internal error.
Action	Contact Software AG Global Support.
TNS.0002.4040E	Exception thrown while saving document processing statistics.
Explanation	Error encountered while saving document processing statistics to DB.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.1001E	Invalid datatype. "cert" must be a byte[] or a X509Certificate.
Explanation	You invoked a service and supplied a digital certificate value that is not a recognized data type.
Action	Supply either an X509Certificate or the bytes from an X509Certificate.

TNS.0003.1005E	The user associated with this certificate ({0}) does not have a TN profile.
Explanation	The supplied digital certificate is associated with an Integration Server user, but that user is not a Trading Networks partner.
Action	Either create a partner profile for the user, or supply a certificate that is associated with a Trading Networks partner.
TNS.0003.1007E	An error occurred when the intended receiver tried to accept this document. The original error message was {0}.
Explanation	An exception was thrown while accepting a polled document.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.1008E	Unable to retrieve partner profile associated with supplied certificate.
Explanation	An exception was thrown while retrieving the partner associated with a digital certificate.
Action	Trading Networks wrote the exception to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.1010E	Unable to save partner's certificate.
Explanation	An exception was thrown while saving a partner's certificate.
Action	Trading Networks wrote the exception to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.1015E	Unable to retrieve signing keys to be used for sending documents to specified partner.
Explanation	The wm.tn.access:getSigningKeys service was unable to retrieve the security information needed to sign documents sent to a partner.
Action	Trading Networks wrote the exception to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.1028E	Invalid feature specified.
Explanation	While checking whether a feature was enabled, Trading Networks discovered that an invalid feature was specified.
Action	Contact Software AG Global Support.

TNS.0003.1029E	Error retrieving Console restrictions.
Explanation	An exception was thrown while determining what features are available to My webMethods Server.
Action	Contact Software AG Global Support.
TNS.0003.1030E	No session available
Explanation	Attempted an action that requires an active session, but no active session was found.
Action	Contact Software AG Global Support.
TNS.0003.1031E	No user available from session
Explanation	Unable to determine the connected user as session doesn't have any user defined.
Action	Try defining users and retry or contact your administrator to check database and Integtation Server status.
TNS.0003.1032E	Group TNPartners not defined
Explanation	TNPartners Group was not found
Action	Run the wm.tn.admin:install service to create TNPartners and other required user groups.
TNS.0003.1033	Empty or null username for partner {0}.Also,The username may not have whitespace.
Explanation	Encountered validation error while creating partner account. Iinput field username can't be null and should not contain spaces.
Action	Provide a valid user name and try again.
TNS.0003.2002E	An ID type named {0} already exists.
Explanation	Trading Networks attempted to create an external ID type with the provided name, but an external ID type with that name already exists.
Action	Specify the name of an external ID type that does not already exist when creating an external ID type.
TNS.0003.2003E	A contact type named {0} already exists.
Explanation	Trading Networks attempted to create a contact type with the provided name, but a contact type with that name already exists.
Action	Specify the name of a contact type that does not already exist when creating a contact type.

TNS.0003.2004E	A field group named {0} already exists.
Explanation	Trading Networks attempted to create a field group with the provided name, but a field group with that name already exists.
Action	Specify the name of a field group that does not already exist when creating a field group.
TNS.0003.2005E	Could not get profile dictionary
Explanation	Trading Networks encountered an unexpected error during profile dictionary initialization.
Action	The exception was written to the server log. See the server log for details. Take action appropriate to resolve the problem described in the exception.
TNS.0003.2006E	Could not retrieve field definitions
Explanation	An exception was thrown while retrieving profile field definitions.
Action	The exception was written to the server log. See the server log for details. Take action appropriate to resolve the problem described in the exception.
TNS.0003.2007E	Could not add field definition
Explanation	An exception was thrown while saving a profile field definition.
Action	The exception was written to the server log. See the server log for details. Take action appropriate to resolve the problem described in the exception.
TNS.0003.2008E	Could not update field definition
Explanation	An exception was thrown while updating a profile field definition.
Action	The exception was written to the server log. See the server log for details. Take action appropriate to resolve the problem described in the exception.
TNS.0003.2009E	"definition" is required.
Explanation	A required field value was not supplied.
Action	Supply the required value.
TNS.0003.3010E	Unable to map certificate to user for new partner {0}.
Explanation	The wm.tn.security:setVerifyCertificateSet service was unable to save certificates for a new trading partner.
Action	Save the partner's profile with no certificates and then add the partner's certificates.

TNS.0003.3019E	{0} could not retrieve the ProfileStore.
Explanation	The Profile Store is inaccessible.
Action	Reload the WmTN package or restart the Integration Serve that hosts Trading Networks Server.
TNS.0003.3030E	Unable to retrieve the {0} ID for partner {1}.
Explanation	Could not convert the internal partner ID into an external ID.
Action	Make sure the partner has a value for this type of external ID.
TNS.0003.3034W	An invalid or expired certificate was received from {0} and rejected.
Explanation	An invalid or expired certificate was received and rejected from the Trading Partner specified in the message.
Action	Notify the Trading Partner specified in the message that their certificate is either invalid or expired.
TNS.0003.3037W	Received a certificate issued by {0}, who is not on your list of trusted Certificate Authorities.
Explanation	The Certificate Authority specified in the message is not on your list of trusted sources.
Action	You either can add this Certificate Authority to your list of trusted Certificate Authorities, or you can notify the trading partner that you do not trust their Certificate Authority.
TNS.0003.3038E	Problem creating B2B account for partner (username={0}).
Explanation	An account could not be created on the Integration Server for the partner.
Action	Create the account manually for the partner. The user name must match the partner's required external ID.
TNS.0003.3050E	If {0} is supplied, {1} must also be supplied.
Explanation	You must supply either both values or neither value.
Action	Supply both values or neither value.
TNS.0003.3085W	The Trading Networks user does not have permission to change System properties. The certificate chain verifier is not correctly initialized. All incoming certificate chains will be trusted.
Explanation	The watt.security.cert.wmChainVerifier.trustByDefault property might not be set correctly.
Action	Ask the Administrator to set the watt.security.cert.wmChainVerifier.trustByDefault property appropriately.

TNS.0003.3102E	Either {0} or {1} must be supplied.
Explanation	A value must be supplied for one of the two variables, but no value was supplied for either variable.
Action	Supply a value for one of the variables.
TNS.0003.4001E	Could not delete field group.
Explanation	An exception was thrown while deleting a profile field group.
Action	The exception was written to the error log. See the log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4003E	Could not add partner profile for {0}.
Explanation	An exception was thrown while saving a partner profile.
Action	The exception was written to the error log. See the log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4005E	The partner specified (id={0}) has a {1} ID of {2}, but there is no matching IS user account.
Explanation	Trading Networks could not find an Integration Server user account for this partner.
Action	Verify that the partner has a user account on the Integration Server and that the account name matches the partner's required external ID value.
TNS.0003.4006E	Attempted to save an extended field value with an unknown field ID (id={0}).
Explanation	Field with this ID doesn't exist. Trading Networks could not save the extended field for this ID.
Action	Specify a valid field ID.
TNS.0003.4008E	Got null or empty extended profile fields
Explanation	The "fields" input variable is required.
Action	Pass the extended fields you want to save in the "fields" variable.
TNS.0003.4009E	Attempted to save an external ID that has an unknown type (type code={0}).
Explanation	Trading Networks attempted to save an external ID for a partner, but the external ID is associated with an external ID type that has not been defined.
Action	To save a new type of external ID for a partner, you must first define the external ID type. To do so, use the <code>wm.tn.dictionary:addIDType</code> service.

TNS.0003.4010E	ID Type {0} is not valid. Not found in the Trading Networks database.
Explanation	ID Type provided is not recognized by Trading Networks.
Action	Supply a valid external ID type. Use the wm.tn.dictionary:addIDType service to define a new external ID type.
TNS.0003.4011E	Attempted to save a contact that has an unknown type (type code={0}).
Explanation	Trading Networks attempted to save a contact for a partner, but the contact is associated with a contact type that has not been defined.
Action	To save a new type of contact for a partner, you must first define the contact type. To do so, use the wm.tn.dictionary:addContactType service.
TNS.0003.4012E	Cannot delete a standard field
Explanation	Attempted to delete a standard profile field. You can only delete extended profile fields.
Action	No action required.
TNS.0003.4014E	{0} not a valid Group ID. Must be greater than {1}.
Explanation	Group ID provided is not a positive integer.
Action	Supply a valid group ID value. It should be positive integer.
TNS.0003.4015E	Port must be a positive integer
Explanation	When specifying a partner's host and port, the port value must be greater than zero.
Action	Supply a valid value that is greater than zero for the port number.
TNS.0003.4016E	Could not decode bizdoc
Explanation	Trading Networks created an internal BizDocEnvelope to validate the profile data, but could not decode the BizDocEnvelope.
Action	Contact Software AG Global Support.
TNS.0003.4017E	Could not add {0}. A {0} with an ID of {1} already exists.
Explanation	While adding lookup type (Contact Type/ ID Type/ Binary Type), Trading Networks found that a similar lookup type with same ID already exists. Trading Networks did not add the lookup type.
Action	Save this type with a different ID.

- TNS.0003.4018E** **A profile already exists for the host of this Trading Network. Turn off the SELF setting on the corporate component of the profile and save it again.**
- Explanation** The Enterprise profile already exists.
- Action** If you are programmatically saving profiles, set the Self? variable to false before attempting to save the profile. If you are using My webMethods to save profiles, contact Software AG Global Support.
-
- TNS.0003.4019E** **Could not validate profile: received null bizdoc**
- Explanation** Trading Networks should have created an internal BizDocEnvelope to validate profile data, but the BizDocEnvelope is null.
- Action** Contact Software AG Global Support. Please have the server and error logs and the WmTN/config/properties.cnf file available.
-
- TNS.0003.4020E** **No '{0}' element found in bizdoc**
- Explanation** Trading Networks created an internal BizDocEnvelope to validate profile data, but the BizDocEnvelope did not contain the "errors" element.
- Action** Contact Software AG Global Support. Please have the server and error logs and the WmTN/config/properties.cnf file available.
-
- TNS.0003.4021E** **Cannot set extended fields.**
- Explanation** An exception was thrown while saving extended fields to the database.
- Action** Take appropriate action to resolve the problem described in the exception.
-
- TNS.0003.4024E** **Cannot access profile store.**
- Explanation** An exception was thrown while accessing the Profile store.
- Action** Contact Software AG Global Support.
-
- TNS.0003.4026E** **You are using webMethods Trading Partners. To be able to add more partner profiles, please upgrade to webMethods Trading Networks.**
- Explanation** When using webMethods Trading Partners, you are allowed to create only one profile other than your own.
- Action** If you need to create additional partner profiles, upgrade to webMethods Trading Networks.

TNS.0003.4027E	Could not retrieve {0} using {1}
Explanation	Invalid id is provided. Trading Networks could not retrieve partner details using this ID.
Action	Supply a valid value.
TNS.0003.4028E	An error occurred while retrieving company logos.
Explanation	An exception was thrown while retrieving company logos.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.4029E	Importing a profile for {0} (id={1}), which is marked as "My Enterprise", but it has different ID than the existing My Enterprise profile for this Trading Network. Cannot change the identity of the My Enterprise profile. Process terminated.
Explanation	You attempted to import the Enterprise. However, the target Trading Networks system already has an Enterprise profile, which has a different ID than the one you are attempting to import. Trading Networks cannot import the Enterprise profile.
Action	Import Enterprise profile carefully only to those Trading Networks Servers where it's not already defined.
TNS.0003.4030E	Could not get profile for user (username={0}).
Explanation	An exception was thrown while retrieving a partner profile for a user.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.4032E	Extended fields cannot have a column name.
Explanation	Validation of profile fields failed. The column name on an extended profile field should be null.
Action	If you are programmatically creating extended fields, do not set the Column Name.
TNS.0003.4033E	Extended fields cannot have a table name.
Explanation	Validation of profile fields failed. The table name on an extended profile field should be null.
Action	If you are programmatically creating extended fields, do not set the Table Name.

TNS.0003.4034E	Partner status can only be "Active" or "Inactive" when adding a new profile.
Explanation	Invalid status provided for profile to be added.
Action	Supply a valid value for the Partner Status field.
TNS.0003.4035E	Corporation is invalid: no partnerID.
Explanation	Trading Networks attempted to update a partner profile, but the corporation component has no partner ID.
Action	Set the partnerID field to a valid value.
TNS.0003.4036E	Attempted to save a binary object that has an unknown type (type code={0}).
Explanation	The database does not have binary types defined.
Action	Populate your database with initial values by importing the file <IntegrationServer>/packages/WmTN/bin/init.xml, where <IntegrationServer> is the location where your server is installed.
TNS.0003.4037E	Could not add Field Group {0}.
Explanation	An exception was thrown while adding a profile field group.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.4039E	Could not get {0} for partner (partnerID={1}).
Explanation	An exception was thrown while retrieving protocol information for a partner.
Action	Verify whether the database connection is available. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4041E	Cannot delete the External ID, there has to be at least one external ID
Explanation	Each partner must have a value for the required external ID type. The required external ID value is used for the user name of the partner's Integration Server user account.
Action	Do not attempt to delete the required external ID from a partner's profile.
TNS.0003.4042E	The value for profile field {0} is not one of the valid values.
Explanation	Invalid value provided for profile field.
Action	Supply a valid value.

TNS.0003.4044E	Standard fields must have a column name.
Explanation	Profile field Validation failed. The column name on a standard profile field is null.
Action	Contact Software AG Global Support.
TNS.0003.4045E	Could not update {0}.
Explanation	An exception was thrown while updating a profile component.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.4046E	A profile already exists in the database with the supplied PartnerID ({0}).
Explanation	Trading Networks attempted to save a new profile with the same partnerID as an existing profile.
Action	Do not specify a value for the partnerID when creating a new profile. Trading Networks will generate a unique ID for you.
TNS.0003.4047	{0} cannot be null.
Explanation	Partner ID is required field while fetching the Profile and it should not be null.
Action	Supply Partner ID to fetch profile.
TNS.0003.4048E	Could not get profile for partner (id={0})
Explanation	An exception was thrown while retrieving a partner profile.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.4049E	webMethods Trading Partners is restricted to the creation of one profile in addition to your own.
Explanation	When using webMethods Trading Partners, you can create only one profile other than your own.
Action	If you need to create additional partner profiles, upgrade to webMethods Trading Networks.
TNS.0003.4050E	Could not upgrade your profile. Please contact webMethods Customer Service.
Explanation	An exception was thrown while upgrading your profile from webMethods for Partners to webMethods Trading Networks.
Action	Take appropriate action to resolve the problem described in the exception. If necessary, contact Software AG Global Support.

TNS.0003.4051E	At least 1 field has been defined for this group. Cannot delete.
Explanation	Found at least one field still associated to group. Unable to delete this group.
Action	To delete this field group, you must first delete all extended profile fields in the group, or assign them to other groups.
TNS.0003.4053E	Could not delete {0} ({1}={2}).
Explanation	An exception was thrown while deleting a profile component.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.4054E	Cannot set valid values for a standard field
Explanation	You cannot define a list of valid values for standard fields.
Action	Do not attempt to define a list of valid values for a standard field. Valid values are applicable for extended fields.
TNS.0003.4056E	Errors encountered validating profile/profile fields
Explanation	A list of one or more validation errors follows this message after invoking wm.tn:submit.
Action	Take appropriate action to resolve the errors.
TNS.0003.4058E	Another partner profile with the name "{0}" already exists. Cannot have duplicate partner names. Please enter a different name.
Explanation	You are attempting to create a profile; however, a profile with the Corporation Name and User Name that you specified already exists in Trading Networks.
Action	Supply a different Corporation Name and/or Unit Name.
TNS.0003.4060E	You must add a profile for your enterprise before you can upgrade to webMethods Trading Networks. Please create a profile for your enterprise.
Explanation	You have not defined the Enterprise profile. The Enterprise profile must exist before you can upgrade Trading Networks.
Action	Create the Enterprise profile.
TNS.0003.4062E	Cannot undelete a standard field
Explanation	Standard fields cannot be deleted or undeleted.
Action	Do not attempt to delete or undelete a standard field.

TNS.0003.4064E	{0}, no change made on server
Explanation	Trading Networks encountered an error while saving partner profile information. See the error message for details.
Action	Take appropriate action to resolve the problem described in the error message.
TNS.0003.4065E	An error was encountered deleting a partner's profile (partnerID={0}).
Explanation	An exception was thrown while deleting a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4066E	Could not get host profile.
Explanation	An exception was thrown while retrieving the Enterprise profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4068E	{0} is required.
Explanation	No value was supplied for a required input variable.
Action	Supply the required value.
TNS.0003.4069E	Standard fields must have a table name.
Explanation	Trading Networks encountered an invalid field definition in the Trading Networks database.
Action	Contact Software AG Global Support.
TNS.0003.4072E	Error initializing ProfileStore
Explanation	Encountered error while initializing Profile Store.
Action	Contact Software AG Global Support.
TNS.0003.4073E	Could not set binary object for partner (id={0}).
Explanation	An exception was thrown while saving binary data to the Trading Networks database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4075E	Could not get Extended Field template (group={0}).
Explanation	An exception was thrown while creating a new extended field.
Action	Contact Software AG Global Support.
TNS.0003.4076E	Invalid group specified.
Explanation	The group that was specified is not a valid group.
Action	Use the wm.tn.dictionary:getFieldGroups service to retrieve a list of valid groups.
TNS.0003.4077E	{0} must be specified for partner {1}
Explanation	Profile validation failed! Required data is missing from a partner profile.
Action	Supply a value for the required fields.
TNS.0003.4078E	Datatype cannot be null.
Explanation	Found Datatype parameter null while setting it to profile.
Action	Supply a valid data type.
TNS.0003.4079E	Your webmethods Trading Networks server is restricted to the creation of {0} profiles in addition to your own.
Explanation	Your Trading Networks Server is restricted to the creation of the number of profiles specified in the message.
Action	If you need to add more profiles, contact Software AG Global Support to upgrade your server.
TNS.0003.4080E	Attempted to set the datatype of a field to an unrecognized value: {0}.
Explanation	Provided datatype is not recognized by Trading Networks.
Action	Supply a valid data type.
TNS.0003.4082E	Binary type not found in the Trading Networks database: {0}.
Explanation	Trading Networks attempted to set the value of a binary object, but the type does not exist in the database.
Action	Supply a valid binaryTypeDescription or binaryTypeCode. If you have specified a valid binary type and the problem persists, import the init.xml file from the <IntegrationServer>packages/WmTN/bin directory, where <IntegrationServer> is the location where you installed your server.

TNS.0003.4083E	Could not change {0} Type {1}.
Explanation	An exception was thrown while attempting to update an external ID type or contact type.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4084E	Standard fields cannot have a set of extended valid values
Explanation	Trading Networks encountered an invalid field definition in the Trading Networks database.
Action	Contact Software AG Global Support.
TNS.0003.4085E	The specified delivery data (id={0}) does not exist in the database. Cannot delete.
Explanation	Trading Networks was unable to perform the specified database action because the Destination data does not exist.
Action	Contact Software AG Global Support. Have the server and error logs and the WmTN/config/properties.cnf file available.
TNS.0003.4086E	Standard fields cannot have an extended default value
Explanation	Trading Networks encountered an invalid field definition in the Trading Networks database.
Action	Contact Software AG Global Support.
TNS.0003.4087E	The value for {0} must be a String.
Explanation	Found unexpected non-String value when datatype is String, validation failed.
Action	Supply a String value for the field.
TNS.0003.4088E	A {0} ID of {1} already exists in the database. External IDs must be unique.
Explanation	Cannot have two external IDs of the same external ID type that have the same value.
Action	Supply another value for this external ID.
TNS.0003.4089E	Could not get internal ID for partner (id={0}, typeCode={1}, typeDesc={2}).
Explanation	An exception was thrown while retrieving the internal partnerID.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4090E	Fields must have a datatype
Explanation	Trading Networks encountered an invalid field definition in the Trading Networks database.
Action	Contact Software AG Global Support.
TNS.0003.4091E	Could not get profile summaries.
Explanation	An exception was thrown while retrieving profile summaries.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4092E	{0} cannot be null. {1} not {2}.
Explanation	Trading Networks did not add or update the changes because a required value is missing.
Action	Supply the required value.
TNS.0003.4093E	{0} must be equal or greater than {1}
Explanation	Numeric field validation failed as supplied value found lesser than limit value, should be greater or equal to limit value.
Action	Supply a valid value.
TNS.0003.4094E	You are already using webMethods Trading Networks. No upgrade is necessary.
Explanation	Attempted to upgrade from webMethods for Partners to webMethods Trading Networks, but you are already using webMethods Trading Networks.
Action	No action required.
TNS.0003.4096E	Could not get {0}.
Explanation	An exception was thrown while retrieving a profile component.
Action	An exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4099E	Status was not changed to {0} because the profile has the following errors {1}
Explanation	The profile has issues that must be resolved before the status can be changed.
Action	Take appropriate action to resolve the problem described in the errors.

TNS.0003.4100E	Cannot set Column Name for an extended field
Explanation	It is not valid for an extended profile field to have a value for Column Name.
Action	Do not attempt to set a value for Column Name for an extended profile field.
TNS.0003.4102E	Cannot set Table Name for an extended field
Explanation	It is not valid for an extended profile field to have a value for Table Name.
Action	Do not attempt to set a value for Table Name for an extended profile field.
TNS.0003.4105E	Could not add {0} Type {1}.
Explanation	An exception was thrown while attempting to create an IDType or ContactType.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4106E	Could not get profile summary (partnerID={0}).
Explanation	An exception was thrown while attempting to retrieve a profile summary.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4107E	An error occurred while retrieving polling frequencies.
Explanation	An exception was thrown while retrieving a partner's polling frequency.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4108E	Could not delete External Partner ID (internal PartnerID={0}).
Explanation	An exception was thrown while deleting a partner's external ID.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4109E	Got null profile field metadata for extended field at index {0}
Explanation	Required internal data is missing.
Action	Contact Software AG Global Support.

- TNS.0003.4110E** **Could not undelete profile for partner (id={0}).**
Explanation An exception was thrown while undeleting a partner profile.
Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
- TNS.0003.4113E** **Attempted to save a field definition for an unknown group (group id={0}).**
Explanation The specified field group does not exist and is not valid.
Action Supply a valid field group. If you are using the Trading Networks Console to create an extended field, contact Software AG Global Support.
- TNS.0003.4114E** **Could not get profile summary (username={0}).**
Explanation An exception was thrown while retrieving a profile summary.
Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
- TNS.0003.4115E** **Profile has errors. Saved with a status of {0}.**
Explanation Validation error found for the provided profile, saving with status as inactive.
Action Take appropriate action to resolve the errors listed below this message.
- TNS.0003.4116E** **Could not add external ID data for partner (id={1}).**
Explanation Encountered an Exception while saving a profile component.
Action See the Exception message for details. Take appropriate action to resolve the problem described in the exception.
- TNS.0003.4117E** **webMethods Trading Networks requires a special license key. Please contact webMethods to get a Trading Networks key. Until you do so, you will be limited to the creation of one profile in addition to your own.**
Explanation You currently have a webMethods for Partners license key, which allows you to create only a single partner profile.
Action If you need to create additional partner profiles, upgrade to webMethods Trading Networks.

TNS.0003.4118E	Profile status may only be changed to {0} or {1}.
Explanation	Attempted to change the profile status to an invalid status.
Action	Supply a valid value.
TNS.0003.4120E	Could not change partner's status.
Explanation	An exception was thrown while updating the status of a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4121E	{0} {1} delivery data already exists in the database for this partner.
Explanation	You attempted to add a delivery method for a partner that is already defined for the partner. You cannot have two instances of the same delivery method for a partner.
Action	If the existing delivery method contains the information you want, no action is required. Otherwise, you can update the information for the existing delivery method.
TNS.0003.4122E	Extended fields must have a name.
Explanation	You did not specify a name for the extended profile field.
Action	Supply the required value.
TNS.0003.4123E	Problem initializing Profile services.
Explanation	An exception was thrown during initialization.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4124E	Cannot set default value for a standard field.
Explanation	You cannot define a default value for a standard profile field.
Action	Do not attempt to define a default value for a standard profile field.
TNS.0003.4125E	Could not retrieve extended fields.
Explanation	An exception was thrown while retrieving extended fields for a partner.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4126E	Standard fields cannot be marked as deleted
Explanation	You cannot delete a standard profile field.
Action	Do not attempt to delete a standard profile field.
TNS.0003.4129E	Following errors occurred during updating profile
Explanation	A list of one or more errors follows this message.
Action	Take appropriate action to resolve the problems described in the errors.
TNS.0003.4130E	Cannot delete preferred delivery method
Explanation	The delivery method you tried to delete is the preferred delivery method for the partner.
Action	Before you can delete this delivery method, choose another delivery method to be "preferred."
TNS.0003.4131E	Could not delete {0} Type {1}.
Explanation	An exception was thrown while deleting profile data.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4132E	Could not update corporation.
Explanation	An exception was thrown while updating the Corporate component of a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4133E	Could not update addresses.
Explanation	An exception was thrown while updating one or more addresses on a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4136E	Could not delete connection ({1}={2}).
Explanation	An exception was thrown while deleting a delivery method from a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4138E	Could not update external IDs.
Explanation	An exception was thrown while updating one or more external IDs in a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4141E	Could not get binary object for partner (partnerID={1}).
Explanation	An exception was thrown while retrieving a binary object for a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4142E	"extID" is required.
Explanation	You attempted to invoke a service that requires a value for the extID input variable, but no value was supplied.
Action	Supply the required value.
TNS.0003.4143E	Either idTypeCode or idTypeDesc must be supplied (idTypeCode={0}, idTypeDesc={1}).
Explanation	You invoked a service without providing a required input variable to identify the external ID type.
Action	Supply one of the required values.
TNS.0003.4144E	partnerID is required.
Explanation	You invoked a service without providing a required input variable to identify the partner.
Action	Supply the required value.
TNS.0003.4145E	Could not get external ID for partner (partnerID={0}).
Explanation	An exception was thrown while retrieving an external ID for a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4146E	Error encountered updating binary object in the database (partnerID={0}).
Explanation	An exception was thrown while updating a binary object for a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4147E	{0} must be supplied.
Explanation	You called a Java method without supplying a value for a required field (<fieldName>).
Action	Supply the required value.
TNS.0003.4148E	A status of {0} is not one of the permitted values.
Explanation	Attempted to set the status to an invalid value.
Action	Supply a valid value.
TNS.0003.4149E	Error encountered changing partner status.
Explanation	An exception was thrown while updating the status of a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4151E	A profile is required.
Explanation	While adding profile to the Data store, profile found to be null.
Action	Supply the valid profile data.
TNS.0003.4152E	Error encountered adding profile to the database.
Explanation	An exception was thrown while adding a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4153E	Error encountered adding contacts to the database.
Explanation	An exception was thrown while adding one or more contacts to a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4155E	Error encountered adding destinations to the database.
Explanation	An exception was thrown while adding one or more delivery methods (destinations) to a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4156E	Error encountered adding IDs to the database.
Explanation	An exception was thrown while adding one or more external IDs to a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4157E	Error encountered adding addresses to the database.
Explanation	An exception was thrown while adding one or more addresses to a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4158E	Error encountered adding binary objects to the database.
Explanation	An exception was thrown while adding one or more binary objects to a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4160E	{0} cannot be null.
Explanation	When attempting to delete a profile-related asset from the Profile store, required asset ID was not provided.
Action	Supply the required asset ID.
TNS.0003.4161E	Error encountered deleting profile from the database.
Explanation	An exception was thrown while deleting a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4162E	Error encountered undeleting profile from the database.
Explanation	An exception was thrown while undeleting a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4163E	Error encountered deleting contact (contactID={0}, partnerID={1}).
Explanation	An exception was thrown while deleting a contact from a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4164E	Error encountered deleting address (addressID={0}, partnerID={1}).
Explanation	An exception was thrown while deleting an address from a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4165E	Error encountered deleting destination (destID={0}).
Explanation	An exception was thrown while deleting a delivery method (destination) from a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4166E	Error encountered deleting external id (id={0}).
Explanation	An exception was thrown while deleting an external ID from a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4167E	Error encountered retrieving extended fields.
Explanation	An exception was thrown while retrieving extended fields for a partner.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4168E	Error encountered adding extended field {0} to the database (partnerID={1}).
Explanation	An exception was thrown while adding an extended profile field for a partner.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4170E	Error encountered retrieving contact {0} (partnerID={1}).
Explanation	Encountered an exception while retrieving a contact for a partner.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4171E	Error encountered retrieving binary type {0} (partnerID={1}).
Explanation	An exception was thrown while retrieving a binary object for a partner.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4172E	Invalid binary type: {0}.
Explanation	The supplied binary type is not recognized as a valid binary type. It does not match any existing binary type.
Action	Supply a valid binary type value.
TNS.0003.4173E	A connection was requested for an unknown partner (partnerID={0}).
Explanation	Attempted to establish a connection to a partner's server, but the supplied partnerID was invalid.
Action	Supply a valid partner ID.
TNS.0003.4174E	Delivery method is {0}. Can only create contexts for HTTP or HTTPS destinations.
Explanation	A webMethods context can only be established when using HTTP or HTTPS.
Action	If you want to connect to a partner's server with a different protocol (e.g., FTP or SMTP) use the appropriate service in the WmPublic package or one of the delivery services in the wm.tn.transport folder.
TNS.0003.4175E	Error encountered connecting to partner's server.
Explanation	An exception was thrown while connecting to a partner's server.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4181E	constant must start with FLD_[TBL]_
Explanation	Internal error.
Action	Contact Software AG Global Support.
TNS.0003.4182E	bad constant results in non or multiple fields
Explanation	Internal error.
Action	Contact Software AG Global Support.
TNS.0003.4184E	RetryFactor cannot be zero
Explanation	Supplied RetryFactor is unexpectedly lower than 1, RetryFactor should be greater than or equal to 1.
Action	Supply a valid value for RetryFactor. It should be greater than or equal to 1.

TNS.0003.4187E	External Field: {0} has errors. Error = {1}
Explanation	See the errors listed in the message.
Action	Take appropriate action to resolve the problems described in the errors.
TNS.0003.4188E	Is a required External Field
Explanation	No data was supplied for a required extended profile field.
Action	Supply a value for this field.
TNS.0003.4189E	Field value must be of data type java.lang.String
Explanation	Data type for the extended profile field is String, value must be a String.
Action	Supply a String value.
TNS.0003.4190E	Invalid value selected
Explanation	Supplied value for extended profile field found to be invalid.
Action	Supply a valid value.
TNS.0003.4192E	Could not retrieve ID Types from database
Explanation	An exception was thrown while retrieving external ID types.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4193E	Could not retrieve IDType Descriptions from database
Explanation	An exception was thrown while retrieving external ID type descriptions.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4194E	A database error occurred while adding an ID Type.
Explanation	An exception was thrown while adding an external ID type.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4195E	A database error occurred while changing an ID Type.
Explanation	An exception was thrown while updating an external ID type.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4196E	A database error occurred while deleting an External ID Type.
Explanation	An exception was thrown while deleting an external ID type.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4197E	Could not retrieve Contact Types from database
Explanation	An exception was thrown while retrieving contact types.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4198E	A database error occurred while adding a Contact Type.
Explanation	An exception was thrown while adding a contact type.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4199E	A database error occurred while changing a Contact Type.
Explanation	An exception was thrown while updating a contact type.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4200E	A database error occurred while deleting a Contact Type.
Explanation	An exception was thrown while deleting a contact type.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4201E	Could not retrieve Binary Types from database
Explanation	An exception was thrown while retrieving binary types.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4202E	Could not retrieve Field Groups from database
Explanation	An exception was thrown while retrieving field groups.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4203E	A database error occurred while adding a Field Group.
Explanation	An exception was thrown while adding a field group.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4204E	A database error occurred while changing a Field Group.
Explanation	An exception was thrown while updating a field group.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4205E	A database error occurred while deleting a Field Group.
Explanation	An exception was thrown while deleting a field group.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4206E	Error initializing Profile Dictionary.
Explanation	An exception was thrown during initialization.
Action	Contact Software AG Global Support.
TNS.0003.4207E	pfmd cannot be null.
Explanation	You did not supply a required value.
Action	Supply the required data.
TNS.0003.4208E	A problem was encountered updating the field definition.
Explanation	An exception was thrown while updating a field definition.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4209E	Cannot add a standard field definition. Set Extended to true before saving this definition.
Explanation	Attempted to add a standard profile field. You cannot add standard profile fields.
Action	Add the profile field as an extended profile field.
TNS.0003.4210E	A problem was encountered adding the field definition.
Explanation	An exception was thrown while adding a field definition.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4211E	Error retrieving profile
Explanation	Encountered an exception while retrieving a partner profile.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4212E	Could not retrieve profile from database using external ID
Explanation	An exception was thrown while retrieving a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4213E	Could not retrieve Profile Summaries from database
Explanation	An exception was thrown while retrieving a profile summary.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4216E	Could not retrieve Custom Fields from database
Explanation	An exception was thrown while retrieving extended profile fields.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4218E	Could not retrieve internal ID from database using PartnerIDID ({0}).
Explanation	An exception was thrown while retrieving a partner profile ID.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4219E	Could not retrieve internal ID from database using DestinationID ({0}).
Explanation	An exception was thrown while retrieving a partner profile ID.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4220E	Error retrieving {0} external ID for {1}.
Explanation	An exception was thrown while retrieving the external ID for a partner.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4221E	Could not retrieve IDType from database using PartnerIDID ({0}).
Explanation	An exception was thrown while retrieving an external ID type.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4222E	Could not update profile.
Explanation	An exception was thrown while updating a profile that has been marked deleted.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4223E	Corporation can not be null.
Explanation	Required Corporate information was not supplied.
Action	Supply the required Corporate information.
TNS.0003.4224E	Could not update Corporation.
Explanation	An exception was thrown while updating a partner profile.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4225E	Contacts can not be null.
Explanation	Required Contact information was not supplied.
Action	Supply the required data.

TNS.0003.4226E	At least one Contact is required.
Explanation	The supplied Vector must contain at least one contact.
Action	Supply the required data.
TNS.0003.4227E	Could not update Contacts.
Explanation	An exception was thrown while updating a partner's contact information.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4228E	Address can not be null.
Explanation	Required address information was not supplied.
Action	Supply the required data.
TNS.0003.4229E	At least one Address is required.
Explanation	The supplied vector must contain at least one address.
Action	Supply the required data.
TNS.0003.4230E	Could not update Addresses.
Explanation	An exception was thrown while updating a partner's address information.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4231E	Destinations can not be null.
Explanation	Required delivery method (destination) information was not supplied.
Action	Supply the required data.
TNS.0003.4232E	At least one Destination is required.
Explanation	The supplied vector must contain at least one delivery method (destination).
Action	Supply the required data.
TNS.0003.4233E	Could not update Destinations.
Explanation	An exception was thrown while updating a partner's delivery method (destination) information.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4235E	At least one ID is required.
Explanation	The supplied vector must contain at least one external ID.
Action	Supply the required data.
TNS.0003.4236E	Could not update IDs.
Explanation	An exception was thrown while updating a partner's external ID information.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4237E	A vector of Contacts is required
Explanation	The first argument to ProfileStore.addContacts is null.
Action	Supply the required data.
TNS.0003.4238E	A vector of Destinations is required
Explanation	The first argument to ProfileStore.addDestinations is null.
Action	Supply the required data.
TNS.0003.4239E	A vector of IDs is required
Explanation	The first argument to ProfileStore.addIDs is null.
Action	Supply the required data.
TNS.0003.4240E	A vector of Addresses is required
Explanation	The first argument to ProfileStore.addAddresses is null.
Action	Supply the required data.
TNS.0003.4242E	"addresses" is empty. At least one Address must be supplied.
Explanation	No address was supplied.
Action	Supply the required value.
TNS.0003.4243E	"connections" is empty. At least one Destination must be supplied.
Explanation	No delivery method (destination) was supplied.
Action	Supply the required value.

TNS.0003.4244E	Could not validate profile extended fields: received null bizdoc
Explanation	Internal error occurred during profile validation.
Action	Contact Software AG Global Support.
TNS.0003.4245E	No extended fields found in bizdoc
Explanation	Internal error occurred during profile validation.
Action	This error can be safely ignored. If it persists, contact Software AG Global Support.
TNS.0003.4246E	Could not validate profile standard fields: received null bizdoc
Explanation	Internal error occurred during profile validation.
Action	Contact Software AG Global Support.
TNS.0003.4247E	No standard fields found in bizdoc
Explanation	Internal error occurred during profile validation.
Action	Contact Software AG Global Support.
TNS.0003.4252E	Attempted to import extended field "{0}" for partner ID {1}, but this partner does not exist on your Trading Networks system.
Explanation	Attempted to import extended field for a partner, but this partner does not exist on your Trading Networks.
Action	You must import the partner's profile before you can import extended fields for the partner.
TNS.0003.4253E	Attempted to import extended field "{0}" that has an extended profile field ID of {1}, but this extended field is not defined on your Trading Networks system.
Explanation	Cannot import the value of the extended profile field because there is no definition for the extended field.
Action	You must import the extended field definitions before you can import extended field values.
TNS.0003.4254E	Error encountered invoking wm.tn.profile:addProfile {0}.
Explanation	An exception was thrown while saving a new partner profile.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0003.4257E	Error encountered refreshing ID cache.
Explanation	An exception was thrown while refreshing an internal cache.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4258E	Could not get external IDs for partner (partnerID={0}).
Explanation	An exception was thrown while retrieving external IDs.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4259E	At least one ID must be specified for partner {0}.
Explanation	Because the value of the required external ID type is used as the user name for an Integration Server user account, it must be specified.
Action	Specify the required external ID.
TNS.0003.4260E	Could not retrieve Profile Groups from database.
Explanation	Encountered a SQLException while retrieving profile group information from the database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4262E	profileGroupName can not be null or empty.
Explanation	Trading Networks cannot accept null or an empty string for the profile group name.
Action	Specify a non-null a profile group name.
TNS.0003.4263E	profileGroupName {0} already exists in database.
Explanation	Trading Networks cannot accept a duplicate profile group name.
Action	Specify a unique profile group name.
TNS.0003.4264E	A database error occurred while adding Profile Group {0}.
Explanation	Encountered a SQLException while adding the new profile group.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4265E	A database error occurred while changing Profile Group {0}.
Explanation	Encountered a SQLException while changing the profile group name from its old name to a new name.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4266E	A database error occurred while deleting Profile Group {0}.
Explanation	Encountered a SQLException while deleting the profile group from the database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4267E	A databse error occurred while querying profile information.
Explanation	Encountered a SQLException while executing a profile query.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4275E	Error encountered invoking service {0}
Explanation	Encountered an exception while invoking the specified service.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.4276E	{0} can not be null or a 0-length array.
Explanation	The input signature profileGroupIds should be a non-null array.
Action	Specify non-null values for the profileGroupIds input.
TNS.0003.4281E	Attempted to import security data for partner ID {0}, but this partner does not exist on your Trading Networks system.
Explanation	You attempted to import a trading partner's security data without first importing this trading partner's profile.
Action	Import the trading partner's profile before you attempt to import the security data for this trading partner.
TNS.0003.4282E	No {0} {1} delivery data exists in the database for this partner. Cannot update.
Explanation	The profile update operation cannot be completed because the delivery protocol data is not available.
Action	Provide the delivery protocol details.

TNS.0003.4283E	Could not add contact data for partner (id={1}).
Explanation	Encountered an exception while invoking wm.tn.profile:addContacts. The operation cannot be completed.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4284E	Could not add address data for partner (id={1}).
Explanation	Encountered an exception while invoking wm.tn.profile:addAddresses. The operation cannot be completed.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4285E	Could not add delivery data for partner (id={1}).
Explanation	Encountered an exception while invoking wm.tn.profile:addConnections. The operation cannot be completed.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4287E	Could not delete profile group {0}, it is still in use.
Explanation	The delete operation cannot be completed because the profile group is in use.
Action	Check the trading partner profiles to make sure that no partner belongs to the group you are attempting to delete.
TNS.0003.4289E	Database error in adding partner {0} to profile groups. Import operation aborted.
Explanation	Trading Networks encountered a problem with its database. There is a problem in the database or database driver.
Action	Use the JDBC Pools page on the Integration Server Administrator to ensure that the Integration Server can connect to the Trading Networks database. Correct all connection problems. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0003.4290E	Cannot import partner profile(s) without My Enterprise profile.
Explanation	You are attempting to import one or more partner profiles; however, the target Trading Networks server does not have an Enterprise profile.
Action	Create an Enterprise profile on the target server. Then, import the partner profiles.

TNS.0003.4291E	SQLException encountered in ProfileStore.addPartnerCertificate().
Explanation	Trading Networks encountered a problem with its database. There is a problem in the database or database driver.
Action	Use the JDBC Pools page on the Integration Server Administrator to ensure that the Integration Server can connect to the Trading Networks database. Correct all connection problems. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0003.4292E	EXMLException encountered in ProfileStore.addPartnerCertificate().
Explanation	Trading Networks encountered a problem when attempting to save a certificate for a partner.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.4293E	SQLException encountered in ProfileStore.getPartnerIDForCertificate().
Explanation	Trading Networks encountered a problem with its database. There is a problem in the database or database driver.
Action	Use the JDBC Pools page on the Integration Server Administrator to ensure that the Integration Server can connect to the Trading Networks database. Correct all connection problems. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0003.4294E	EXMLException encountered in ProfileStore.getPartnerIDForCertificate().
Explanation	Trading Networks encountered a problem when attempting to retrieve a certificate for a partner.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.4295E	Cannot deliver to My Enterprise. The supplied partnerID ({0}) is the partnerID of the My Enterprise profile. Please supply a different partnerID.
Explanation	The document receiver is the Enterprise profile, which indicates Trading Networks is to deliver the document to itself. This is not valid; Trading Networks cannot deliver a document to itself.
Action	Either change the receiver to specify a trading partner, or do not attempt to deliver this document.

TNS.0003.4296E **A deleted partner profile with the name "{0}" already exists. Cannot have duplicate partner names. Please enter a different name.**

Explanation You attempted to create a profile. However, the Corporation Name and Unit Name you specify will make the profile a duplicate of a profile that was previously deleted. Although a profile is deleted, Trading Networks continues to maintain information about it in its database. As a result, you cannot create another profile using the same Corporation Name and Unit Name.

Action If you want to reinstate the deleted profile, use the `wm.tn.profile:undeleteProfile` service. Otherwise, enter a different Corporation Name and Unit Name when creating a profile.

TNS.0003.4297E **Importing a profile for {0} (id={1}), which is marked as "My Enterprise". A "My Enterprise" profile already exists for this Trading Network. If you want to update it, use the Force option. Process terminated.**

Explanation You attempted to import an Enterprise profile into a Trading Networks system that already has an Enterprise profile.

Action If you want to replace the existing Enterprise profile with the profile you are trying to import, use the Force option.

TNS.0003.4298E **A deleted profile with the name "{0}" already exists. Unable to recreate a deleted profile.**

Explanation A deleted partner profile with this Corporation Name already exists. Trading Networks maintains information about deleted profiles in its database and does not allow duplicate partner names.

Action You can either use a different Corporation Name, or use the `wm.tn.profile:undeleteProfile` service to reinstate the deleted partner profile.

TNS.0003.4299 **Could not get Users for partner (partnerID={0}).**

Explanation Encountered SQL Exception, not able to fetch users for specified partner.

Action Check database connection

TNS.0003.4300 **Could not get partners for user (username={0}).**

Explanation Encountered SQL Exception, not able to fetch partners for specified user.

Action Check database connection

TNS.0003.4301	Could not add users data for partner (id={1}).
Explanation	An exception was thrown while adding users to a partner.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4302	Could not delete users data for partner (id={1}).
Explanation	An exception was thrown while deleting users for a partner.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4303	Attempted to import a field definition "{0}" that uses a field group {1}, but this field group is not defined on your Trading Networks system.
Explanation	You attempted to import a field definition that uses a field group, but this field group is not defined on your Trading Networks.
Action	Try importing field group before importing the field definition.
TNS.0003.4304	Attempted to import a profile "{0}" that uses a contact type {1}, but this Contact Type is not defined on your Trading Networks system.
Explanation	You attempted to import a profile that uses a contact type, but this contact type is not defined on your Trading Networks system.
Action	Try importing contact type before importing the profile.
TNS.0003.4305	Attempted to import a profile "{0}" that uses an external id type {1}, but this external id type is not defined on your Trading Networks system.
Explanation	You attempted to import a profile that uses an external ID type, but this external ID type is not defined on your Trading Networks system.
Action	Try importing external ID before importing the profile.
TNS.0003.4306	Attempted to import a profile "{0}" that uses a profile group {1}, but this profile group is not defined on your Trading Networks system.
Explanation	You attempted to import a profile that uses a profile group, but this profile group is not defined on your Trading Networks system.
Action	Try importing profile group before importing the profile.

TNS.0003.4309	Could not validate the EXTERNAL ID with (idType={0}) and (externalID={1})
Explanation	An exception was thrown while validating the specified external ID.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4310	Error encountered while getting the External IDs associated with partner with (partnerID={0})
Explanation	Error encountered while getting the External IDs associated with the supplied partnerID.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4311	Following errors occurred during updating externalID
Explanation	Errors occurred during updating external ID.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4312	ID not added as the (externalIDType={0}) given is not a valid one.
Explanation	Validation failed while updating the set of external IDs associated with a profile.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4313	The partner specified (partnerID={0}) doesnot exist in the trading networks. Give a correct one.
Explanation	Supplied partnerID does not exist in the Trading Networks.
Action	Supply valid partner ID.
TNS.0003.4314	ID not added as the (externalIDType={0}) given already exists.
Explanation	ID not added as the externalIDType=0 supplied already exists.
Action	Supply valid ID
TNS.0003.4316	Error encountered while getting registered EDI IDTypes.
Explanation	Error encountered while fetching registered EDI IDTypes.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4317	Error encountered while cleaning up registered EDI IDTypes.
Explanation	Error encountered while deregistering EDI ID Types.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4318	Error encountered while getting the Internal ID of the Enterprise profile.
Explanation	Error encountered while getting the Internal ID of the Enterprise profile.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4319	Error encountered while getting the Internal Identifier for the environment.
Explanation	Error encountered while getting the Internal Identifier for the environment.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4320	"deliveryInfo" is empty. At least one Destination must be supplied.
Explanation	While adding delivery settings, no destination supplied. At least one destination must be supplied.
Action	Supply at least one destination.
TNS.0003.4321	"DestinationID" is empty. At least one DestinationID must be supplied.
Explanation	While removing delivery settings, no destination ID supplied. At least one destination ID must be supplied.
Action	Supply at least one destination ID.
TNS.0003.4322	Error encountered while adding the (externalIDType={0}).
Explanation	Error encountered while adding the External ID type to Trading Networks.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4323	Service Signature given (Service Signature ={0}) is invalid. Give a valid one.
Explanation	Validation failed while retrieving the input or output signature of a specified service.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0003.4324	Error encountered while extracting Registered delivery Services.
Explanation	Error encountered while extracting registered delivery Services.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4325	Cannot set extended field {0} for partnerID {1}.
Explanation	Error encountered while updating extended field for a profile.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4326	Could not add user mapping for partnerID {0} and User {1}.
Explanation	Error encountered while adding user mapping for a profile.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4327	Either one of the inputs of simpleQuery or queryInput is mandatory for querying the profile.
Explanation	Neither input of simpleQuery nor queryInput fields supplied for querying the profile.
Action	Supply either input of simpleQuery or queryInput fields for querying the profile.
TNS.0003.4328	Error encountered while executing Profile Query
Explanation	Error encountered while executing Profile Query
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4329	My Enterprise Profile with specified (partnerID={0}) cannot be deleted.
Explanation	You tried to delete the Enterprise Profile, but the Enterprise profile cannot be deleted.
Action	Don not attempt to delete the Enterprise profile.
TNS.0003.4332	Please specify correct value for routing field. Mandatory values for it are true and false.
Explanation	Supplied value for routing field is neither true nor false.
Action	Supply valid routing field value. It should be either true or false.

TNS.0003.4334	Error encountered while adding DLS artifacts with name ({0}).
Explanation	Error encountered while adding DLS artifacts, found artifact with specified name as null.
Action	Supply valid value for specified artifact name.
TNS.0003.4336	Error encountered while querying on DLS Rules.
Explanation	Error encountered while querying on DLS Rules and roles.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4337	Pipeline for modifying the Rules and RuleRoleInfo shouldn't be null.
Explanation	Input fields found to be null, while modifying the Rules and RuleRoleInfo.
Action	Supply the input fields containing IData/pipeline.
TNS.0003.4338	Either of the Rules or RoleRoleInfo shouldn't be present.
Explanation	Either Rules or RoleRoleInfo should be present while modifying.
Action	Supply either Rules or RoleRoleInfo.
TNS.0003.4339	Error while Rule Addition/Modification, as a Rule already exists with the name ({0}).
Explanation	Error encountered while adding or modifying rule, because a rule with the same name already exists.
Action	Supply rule with a different name.
TNS.0003.4340	Error while Role Addition/Modification, as a Role already exists with the name ({0}).
Explanation	Error encountered while adding or modifying a role, because a role with the same name already exists.
Action	Supply a role with different name.
TNS.0003.4341	Please specify either Permission or ProfileID. Both of them are either null or empty. Either one of them is mandatory.
Explanation	Found that Permission and ProfileID both are either null or empty while checking whether the current user can perform the required action.
Action	Supply either Permission and ProfileID.

TNS.0003.4342	Please specify Permission. Either it is null or empty. Its a mandatory field.
Explanation	During functional permission check, input field Permission found to be null or empty.
Action	Supply mandatory input field Permission.
TNS.0003.4343	Error encountered while during operation on Functional Privileges.
Explanation	Error encountered while checking functional privileges.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4344	Error encountered while querying for Functional Privileges.
Explanation	Error encountered while querying for functional privileges.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4345	Please specify either Add or Remove. Both of them are either null or empty. Either one of them is mandatory.
Explanation	While modifying functional privileges, both of the input field Add/Remove found empty or null.
Action	Supply valid values for the field Add/Remove.
TNS.0003.4346	Access denied, as the User "{0}" does not have the permission to {1} {2}.
Explanation	User is not permitted to perform the specified action.
Action	Contact your administrator.
TNS.0003.4347	Access denied, as the User "{0}" does not have the permission to view {1}.
Explanation	User is not allowed to perform the specified action.
Action	Contact your administrator.
TNS.0003.4348	Access denied, as the User "{0}" does not have the privilege to {1} {2}.
Explanation	User is not allowed to perform the specified action.
Action	Contact your administrator.

TNS.0003.4349	Access denied, as the User "{0}" does not have the privilege to view {1}.
Explanation	User is not allowed to perform the specified action.
Action	Contact your administrator.
TNS.0003.4393	Access Denied. User "{0}" does not have permission to query expired certificates.
Explanation	Specified user does not have permission to query expired certificates.
Action	Contact your administrator.
TNS.0003.4399	Error encountered while getting list of permissions for the user "{0}".
Explanation	Error encountered while getting list of permissions for the specified user.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4401	Error encountered while profile "{0}" disassociation with DataSet "{1}".
Explanation	Error encountered while profile disassociation with DataSet.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0003.4402	Disassociation of profile "{0}" from DataSet "{1}" is disallowed. Dissassociation would have made profile disappear from your profile list.
Explanation	Disassociation of profile from DataSet is disallowed. Dissassociation would have made profile disappear from your profile list.
Action	No action required.
TNS.0003.4404	Could not create delivery service {0}. A delivery service named {0} already exists.
Explanation	Delivery service with the same name already exists in Trading Networks.
Action	Add delivery service with different name.
TNS.0003.4405	The WmTN Property file {0} does not exist
Explanation	Not able to locate Trading Networks properties file at expected location.
Action	Restore the TN Properties file. Contact Software AG Global Support.

TNS.0003.4406	The WmTN Property file {0} is read only
Explanation	Not able to write to the Trading Networks properties file.
Action	Make the Trading Networks properties file writable. Contact Software AG Global Support.
TNS.0003.5001E	This document type ({0}) is missing one or both of its signature queries (Signature and SignedBody). Signing cannot proceed.
Explanation	Trading Networks cannot create a digital signature because the TN document type did not instruct Trading Networks to extract the signature or signed body system attributes.
Action	Add queries to extract the Signature and SignedBody system attributes to the TN document type. For instructions, see the Trading Networks documentation.
TNS.0003.5002E	The signing service for this document ({0}) generated an error. The original error was {1}.
Explanation	Error encountered while signing the specified document.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.5003E	Signing Failed
Explanation	See message TRNSERV.000013.000002 for full details.
Action	Take appropriate action to resolve the problem described in the exception displayed with message TRNSERV.000013.000002.
TNS.0003.5005E	Base-64 encoding the signed body for this document failed to produce a value. The signed body (before encoding) was {0}.
Explanation	The query used to extract the signed body from the document might be invalid. You specify the query that Trading Networks uses in the TN document type used for the document.
Action	If the query used for the signed body returned an empty string, adjust the signed body query for this TN document type. For instructions, see the Trading Networks documentation.
TNS.0003.5006E	Encoding Error
Explanation	See message TRNSERV.000013.000005 for full details.
Action	Take appropriate action to resolve the problem described in the exception displayed with message TRNSERV.000013.000005.

TNS.0003.5007E	An error prevented fetching certificate info for the sender of this document.
Explanation	An exception was thrown while retrieving certificates needed to sign a document.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.5008E	Error fetching cert info
Explanation	See message TRNSERV.000013.000007 for full details.
Action	Take appropriate action to resolve the problem described in the exception displayed with message TRNSERV.000013.000007.
TNS.0003.5010E	No private key information was available for the sender of this document. {0}
Explanation	Trading Networks encountered an error while fetching a private key. See the error message for details.
Action	You might need to import security data for this partner.
TNS.0003.5012E	Applying the {1} query to this document failed. The error: {2}
Explanation	Trading Networks encountered an error while executing the query to extract the signature from a document. See the exception for details.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.5013E	Query Error
Explanation	See message TRNSERV.000013.000012 for full details.
Action	Take appropriate action to resolve the problem described in the exception displayed with message TRNSERV.000013.000012.
TNS.0003.5014E	The signature query for doctype {0} identified the {1} node as the target of the signature, but this node is missing in this document. Signing cannot proceed.
Explanation	The query used to extract the signature from the document identified a node that is not in the document. You specify the query that Trading Networks uses in the TN document type used for the document.
Action	Adjust the signature and/or signed body query for this TN document type. For instructions, see the Trading Networks documentation.

TNS.0003.5015E	Missing Document Node
Explanation	See message TRNSERV.000013.000014 for full details.
Action	Take appropriate action to resolve the problem described in the exception displayed with message TRNSERV.000013.000014.
TNS.0003.5017E	No cert chains are available for the sender of this document. {0}
Explanation	Trading Networks encountered an error while fetching a certificate chain. See the error message for details.
Action	Take appropriate action to resolve the problem described in the error.
TNS.0003.5019E	Cannot sign documents from UNKNOWN sender
Explanation	The sender of the document is unknown to Trading Networks. Reasons that Trading Networks might be unable to determine the sender are: 1) The query that Trading Networks uses to extract the Sender value from the document might be incorrect. The query is defined in the TN document type. 2) The value extracted from the document for the Sender query does not match the external ID of any partner in the Trading Networks database. 3) The structure of the document is incorrect.
Action	Do one of the following: 1) If the query used to extract the Sender value is not valid, adjust the query in the TN document type. For instructions, see the Trading Networks documentation. 2) If the value extracted for the Sender query does not match an external ID in the Trading Networks database, add the external ID to the appropriate partner's profile. For instructions, see the Trading Networks documentation. 3) If the document structure is incorrect, notify the partner that sent the document.
TNS.0003.5021E	This doctype ({0}) has no signing service defined. Signing cannot continue.
Explanation	This TN document type has no signing service defined, so Trading Networks cannot continue with signing.
Action	If this is an XML TN document type, contact Software AG Global Support. If this is not an XML TN document type and the TN document type supports signing services, define a signing service for the TN document type.
TNS.0003.5024E	The signature query for doctype {0} ({1}) failed to identify a node to insert the signature into. Signing cannot proceed.
Explanation	Either the query that Trading Networks uses to extract the signature is incorrect in the TN document type or the structure of the document is incorrect.
Action	If the query is not correct, adjust the signature query for this TN document type. For instructions, see the Trading Networks documentation. If the document structure is incorrect, notify the document sender.

TNS.0003.5025E	The signature query for doctype {0} identified the {1} node as the target of the signature, but this node is not unique in this document. Signing cannot proceed.
Explanation	Either the structure of the document is incorrect or the query that Trading Networks uses to extract the signature is incorrect in the TN document type.
Action	If the document structure is incorrect, notify the document sender. If the query is not correct, adjust the signature query for this TN document type. For instructions, see the Trading Networks documentation. Note that if your XQL query is returning an array of nodes, you can force it to return a single node by adding a subscript. For example, change <code>"/anXMLtag"</code> to <code>"/anXMLtag[0]"</code> .
TNS.0003.5027W	No signing service for doctype {0}
Explanation	This TN document type has no signing service defined, so Trading Networks cannot continue with signing.
Action	If this is an XML TN document type, contact Software AG Global Support. If this is not an XML TN document type and the TN document type supports signing services, define a signing service for the TN document type.
TNS.0003.5030E	Trading Networks will not sign documents originating from the Unknown partner. Signing fails.
Explanation	The sender of the document is unknown to Trading Networks. Reasons that Trading Networks might be unable to determine the sender are: 1) The query that Trading Networks uses to extract the Sender value from the document might be incorrect. The query is defined in the TN document type. 2) The value extracted from the document for the Sender query does not match the external ID of any partner in the Trading Networks database. 3) The structure of the document is incorrect.
Action	Do one of the following: 1) If the query used to extract the Sender value is not valid, adjust the query in the TN document type. For instructions, see the Trading Networks documentation. 2) If the value extracted for the Sender query does not match an external ID in the Trading Networks database, add the external ID to the appropriate partner's profile. For instructions, see the Trading Networks documentation. 3) If the document structure is incorrect, notify the partner that sent the document.
TNS.0003.5031E	The signed body query for this document type ({0}) failed to produce a value. Signing the document fails. The query was {1}.
Explanation	Either the query that Trading Networks uses to extract the signature is incorrect in the TN document type or the structure of the document is incorrect.
Action	If the query is not correct, adjust the signature query for this TN document type. For instructions, see the Trading Networks documentation. If the document structure is incorrect, notify the document sender.

TNS.0003.6001E	Cannot persist a TPA
Explanation	An exception was thrown while saving a TPA to the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.6002E	Cannot retrieve a TPA
Explanation	An exception was thrown while reading a TPA from the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.6006E	Cannot delete a TPA with status="agreed"
Explanation	You cannot delete a TPA with status Agreed.
Action	Change the TPA's status to Proposed and then delete it.
TNS.0003.6007E	Cannot delete a TPA
Explanation	An exception was thrown while deleting a TPA from the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.6008E	Cannot update a TPA that has status="agreed"
Explanation	A TPA in "Agreed" status cannot be revised.
Action	Change the TPA's status to "Proposed" before updating the TPA.
TNS.0003.6009E	Cannot update a TPA
Explanation	An exception was thrown while updating a TPA in the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.6010E	Cannot get a TPA lock
Explanation	An exception was thrown while getting a lock on a TPA in the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TNS.0003.6011E	Cannot update controlNumber for a TPA
Explanation	An exception was thrown while updating the control number of a TPA in the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.6014E	Cannot update tpaData when status="agreed" and dataStatus="immutable"
Explanation	You attempted to update the TPA data that is associated with a TPA. The Agreement Status of the TPA is "Agreed" and the Data Status is "Non-modifiable." You cannot update the TPA data when the Data Status is "Non-modifiable."
Action	To be able to update the TPA data, perform one of the following actions: 1) change the Data Status to "Modifiable," or 2) change the Agreement Status to "Proposed."
TNS.0003.6017E	Cannot update tpaData
Explanation	An exception was thrown while updating the TPA data in a TPA in the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.6018E	Cannot get the next controlNumber for a TPA
Explanation	An exception was thrown while determining the next control number for a TPA in the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.6020E	Cannot change status for a TPA
Explanation	An exception was thrown while changing the status of a TPA in the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.6021E	A TPA that matches senderID, receiverID and agreementID does not exists
Explanation	Internal error
Action	Contact Software AG Global Support.

TNS.0003.6022E	Missing senderID, or receiverID, or agreementID or initService
Explanation	Internal error
Action	Contact Software AG Global Support.
TNS.0003.6023E	Cannot invoke initService
Explanation	Unable to initialize the data in a TPA because the TPA's initialization service could not be invoked.
Action	Make sure the TPA's initialization service is an existing service in an enabled package.
TNS.0003.6025E	Query TPA exception
Explanation	An exception was thrown while executing a TPA database query.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.6026E	Cannot get all TPAs
Explanation	An exception was thrown while retrieving a list of TPAs from the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.6027E	Cannot import TPA
Explanation	An exception was thrown while importing one or more TPAs.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.6028E	Missing data schema
Explanation	No IS document type is defined for the TPA.
Action	Define an IS document type for the TPA.
TNS.0003.6029E	Missing TPA data
Explanation	The TPA Data field in the TPA is empty.
Action	Enter values into the TPA Data field.

TNS.0003.6030E	Cannot invoke validation service
Explanation	An exception was thrown while invoking the pub.schema:validate service while validating the structure of the IS document type in the TPA.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.6031E	Missing {0}
Explanation	A required input variable was not supplied to the wm.tn.tpa:updateTPA service.
Action	Supply a value for the required variable.
TNS.0003.6032E	A TPA that matches senderID, receiverID and agreementID already exists
Explanation	Cannot save this TPA because it would duplicate an existing TPA.
Action	Either add the data in this TPA to the one that already exists, or specify a different agreementID.
TNS.0003.6033E	A TPA that matches senderID, receiverID and agreementID does not exist
Explanation	Cannot update the TPA because Trading Networks cannot locate a TPA in the database that has the supplied senderID, receiverID, and agreementID.
Action	Specify a senderID, receiverID and agreementID that matches an existing TPA.
TNS.0003.6034E	controlNumber cannot not be null
Explanation	Internal error.
Action	Contact Software AG Global Support.
TNS.0003.6035E	tpaData cannot not be null
Explanation	Internal error.
Action	Contact Software AG Global Support.
TNS.0003.6036E	Cannot update tpaData when dataStatus="immutable"
Explanation	You cannot make changes to a TPA's data when the TPA's Data Status is "Non-modifiable."
Action	To make changes to the TPA data, change the TPA's Data Status to "Modifiable."

TNS.0003.6037E	Cannot update controlNumber
Explanation	An exception was thrown while updating the control number of a TPA in the database.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0003.6038E	There are more than one TPA that matches senderID, receiverID and agreementID
Explanation	Internal error.
Action	Contact Software AG Global Support.
TNS.0003.6039E	Cannot serialize tpaData
Explanation	Internal error.
Action	Contact Software AG Global Support.
TNS.0003.6040E	Cannot de-serialize tpaData
Explanation	The supplied control number is not a valid integer.
Action	Supply a valid integer value.
TNS.0003.6041	New controlNumber is not an integer
Explanation	Encountered error while parsing supplied controlNumber because it is not an integer.
Action	Supply an integer value for controlNumber.
TNS.0003.6042E	A TPA with the supplied ID ({0}) does not exist.
Explanation	An invalid value was supplied for the tpaID field.
Action	Supply a valid TPA ID.
TNS.0003.6043E	If "tpaID" is not supplied, then "senderID", "receiverID" and "agreementID" must be supplied.
Explanation	The user did not supply the correct required inputs.
Action	Supply the required inputs.
TNS.0003.6044	Attempted to import a TPA for Sender {0}, but the sender's profile is not defined on your Trading Networks system.
Explanation	Attempted to import a TPA for Sender, but the sender's profile is not defined on your Trading Networks system.
Action	Import Sender's profile first.

TNS.0003.6045	Attempted to import a TPA for Receiver {0}, but the receiver's profile is not defined on your Trading Networks system.
Explanation	Attempted to import a TPA for Receiver, but the receiver's profile is not defined on your Trading Networks system.
Action	Import Receiver's profile first.
TNS.0003.6050	Attempted to import a Archive Scheduled Service for Sender {0}, but the sender's profile is not defined on your Trading Networks system.
Explanation	Attempted to import a Archive Scheduled Service for specified Sender, but the sender's profile is not defined on your Trading Networks system.
Action	Import Sender's profile first.
TNS.0003.6051	Attempted to import a Archive Scheduled Service for Receiver {0}, but the receiver's profile is not defined on your Trading Networks system.
Explanation	Attempted to import a Archive Scheduled Service for Receiver, but the receiver's profile is not defined on your Trading Networks system.
Action	Import Receiver's profile first.
TNS.0003.7002E	Document type {0} has no validation service defined. Validation fails.
Explanation	Supplied document type has no validation service defined.
Action	Contact Software AG Global Support.
TNS.0003.7003E	No Validation Service
Explanation	A TN document type has no validation service defined. Validation fails.
Action	Contact Software AG Global Support.
TNS.0003.7004E	{0}: {1}
Explanation	A document sent to Trading Networks failed validation.
Action	Notify the document sender.
TNS.0003.7005W	Doctype {0}: no validation svc. defined; validation skipped
Explanation	Document type has no validation service defined. Validation fails.
Action	Contact Software AG Global Support.

TNS.0003.7010E	The doctype for this document ({0}) does not have a validation schema defined; validation fails.
Explanation	The document matches a TN document type that indicates the document's structure should be validated, but no schema was defined.
Action	Update the TN document type, and specify the schema to use for document validation.
TNS.0003.7011E	No Validation Schema
Explanation	The document matches a processing rule that indicates the document's structure should be validated, but no schema was defined.
Action	Update the TN document type that the document matches to specify the schema to use for document validation.
TNS.0003.7012E	The validation service for this XML document, {0}, could not be successfully invoked. The original exception message is: {1}
Explanation	The service used to validate the document's structure threw an exception.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.7013E	The validation service used for this document ({0}) failed with the following exception message: {1}
Explanation	The service used to validate the document's structure threw an exception.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.7014E	Validation Service Failed
Explanation	The service used to validate the document's structure threw an exception.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0003.7015E	XML validation failed: does not apply to non-XML documents.
Explanation	Invoked the wm.tn.doc.xml:validate service with a document that is not XML.
Action	Supply an XML document.
TNS.0003.7016E	XML validation failed: no document content available
Explanation	Document is empty.
Action	Supply an XML document that has content.

TNS.0003.7017E	The validation service, {0} aborted processing of this document. The message was {1}.
Explanation	The document is not valid XML.
Action	Notify the document sender.
TNS.0003.7019E	Flat file validation failed. Document type is not "flat file".
Explanation	Attempted to use a flat file validation service to validate a document that is not a flat file.
Action	Supply a flat file document.
TNS.0003.7020E	Flat file validation failed: no document content available
Explanation	Document is empty.
Action	Supply a flat file document that has content.
TNS.0003.7021E	Flat file validation failed. Document type "{0}" has no parsing schema.
Explanation	The document matches a TN document type that indicates the document's structure should be validated, but no schema was defined.
Action	Update the TN document type, and specify the schema to use for document validation.
TNS.0003.7022E	Validation error
Explanation	The flat file document structure is invalid.
Action	Notify the document sender.
TNS.0004.1001E	Invalid or missing page number.
Explanation	This error occurs if a value for the pageNum variable is not specified for the wm.tn.enumerate:nth service or if a value for the pageNumber variable is not specified for the wm.tn.query:getQueryResults service.
Action	Specify a value for the pageNum variable or pageNumber variable.
TNS.0004.1002E	id is required.
Explanation	A value for the id input variable was not specified for either the wm.tn.enumerate:nth service or the wm.tn.enumerate:first service.
Action	Specify a value for the input variable id.

TNS.0004.1004E	Invalid time interval {0} for query.
Explanation	The wm.tn.query:createDocumentQuery service was supplied an invalid value for the input variable timeInterval.
Action	Provide a valid value for the input variable timeInterval.
TNS.0004.1005E	Unknown attribute ID: {0}.
Explanation	The wm.tn.query:createDocumentQuery service was provided an invalid value for the input variable attribId.
Action	Provide a valid value for the input variable attribId.
TNS.0004.1006E	Unknown attribute name: {0}.
Explanation	The wm.tn.query:createDocumentQuery service was provided an invalid value for the input variable attribName.
Action	Provide a valid value for the input variable attribName.
TNS.0004.1007E	Unknown op: {0}.
Explanation	The wm.tn.query:createDocumentQuery service was provided an invalid value for the input variable op.
Action	Provide a valid value for the input variable op. For more information about valid values, refer to the Trading Networks documentation.
TNS.0004.1008E	Invalid entry type {0} for event.
Explanation	The wm.tn.query:createEventQuery service was provided an invalid value for the input variable entryType.
Action	Provide a valid value for the input variable entryType.
TNS.0004.1009E	Invalid time interval {0} for query
Explanation	Either the wm.tn.query:createEventQuery service or the wm.tn.query:createTPAQuery service has an invalid value specified for the input variable timeInterval.
Action	Specify a valid value for the input variable timeInterval.
TNS.0004.1010E	Invalid timeCreated interval {0} for query
Explanation	The wm.tn.query:createTaskQuery service has an invalid value specified for the input variable timeCreated.
Action	Specify a valid value for the input variable timeCreated.

TNS.0004.1012D	Requested page is not available
Explanation	Requested page is not available. This error occurs when Trading Networks attempts to read beyond the end of the query results while invoking the <code>wm.tn.enumerate:nth</code> service. This error can also occur when data corresponding to the <code>pageNumber</code> input variable for the service <code>wm.tn.query:getQueryResults</code> is not available to Trading Networks.
Action	If the error occurs while invoking the <code>wm.tn.enumerate:nth</code> service, ensure the value specified for <code>pageNum</code> is valid. If the error occurs while invoking the <code>wm.tn.query:getQueryResults</code> service, ensure the value specified for <code>pageNumber</code> is valid. If the problem still persists, refresh the query.
TNS.0004.1013D	Unable to retrieve page. Operation timed out.
Explanation	The Integration Server might be busy doing other work.
Action	Attempt to retrieve the page again, or re-execute the query.
TNS.0004.1014E	Query execution failed.
Explanation	An exception occurred while executing a database query.
Action	The exception was written to the log. Take appropriate action to resolve the problem described in the exception.
TNS.0004.1015E	External ID value is required.
Explanation	You created a profile query that specifies an <code>externalIDType</code> , but did not specify an <code>externalIDValue</code> .
Action	Provide a valid value for the <code>externalIDValue</code> input variable to the <code>createProfileQuery</code> service.
TNS.0004.1016E	fieldId[{0}] is null or empty.
Explanation	You created a profile query that specifies an <code>externalIDValue</code> , but you did not specify an <code>externalIDType</code> .
Action	Supply a valid value for the <code>externalIDType</code> input variable to the <code>createProfileQuery</code> service.
TNS.0004.2001E	Illegal query type: {0}.
Explanation	The query type specified as the input to the service is not valid.
Action	Supply a valid value for the query type. For a list of valid values, see the Trading Networks documentation.

TNS.0004.2002E	pageNumber should be a positive integer.
Explanation	The wm.tn.query:getQueryResults service was supplied an invalid value for the input variable pageNumber.
Action	Supply a valid value for the input variable pageNumber. The value must be a positive integer.
TNS.0004.2003E	A valid pageNumber is required.
Explanation	The pageNumber input variable for the wm.tn.query:getQueryResults service is not valid.
Action	Specify a valid value for pageNumber. The value must be a positive integer.
TNS.0004.2005E	Got null query result data for queryId={0}, page={1}.
Explanation	The wm.tn.query:getQueryResults service is not able to find the data corresponding to the specified queryId and pageNumber.
Action	Ensure the queryId and pageNumber are correct. If the issue persists, resubmit the query.
TNS.0004.2006E	Got null row at index {0}.
Explanation	There is no data corresponding to the specified index.
Action	Make sure the specified index is correct.
TNS.0004.2008I	Can not retrieve task {0}.
Explanation	While searching for tasks in My webMethods Server, no data corresponding to the specified taskid was found.
Action	Make sure the taskid is correct. If you update the taskid, then you must resubmit the query.
TNS.0004.2010E	User does not have adequate privilege to obtain requested data.
Explanation	The user's attempt to view the data failed because the user does not have permission to view the requested data.
Action	An administrator can grant permission to the user. For information about assigning permissions, refer to the Trading Networks documentation.

TNS.0004.2011E	Bizdoc with internal id={0} does not exist.
Explanation	The bizdoc with the specified docId cannot be found in the Trading Networks database .
Action	Make sure the docId is correct. If you change the docId, resubmit the query.
TNS.0004.2012E	Null bizdoc retrieved for internal id = {0}.
Explanation	The bizdoc with the specified docID cannot be found in the Trading Networks database.
Action	Make sure the specified docId is correct. If you change the docId, then you must resubmit the query.
TNS.0004.2013E	Can not parse {0}: {1}.
Explanation	The specified input value must be an integer.
Action	Supply a valid integer for the specified input value.
TNS.0004.2017E	Retrieved null content part for document id = {0}, part name = {1}.
Explanation	There are no content parts available for the bizdoc that corresponds to the specified docId.
Action	Make sure that the specified docId is correct and the content parts are recieved. After specifying the correct docId, resubmit the query.
TNS.0004.2019	{0} encountered execution error.
Explanation	An exception occurred while executing the service <code>wm.tn.portal.queries.getContentPartBytes</code> .
Action	The exception is in the full message. Take appropriate action to resolve the problem described in the exception.
TNS.0004.2027	{0} encountered error resubmitting internalDocIDs[{1}] = {2}.
Explanation	In webMethods Trading Networks, when you resubmit the Bizdocs, this exception is thrown if the resubmission fails.
Action	Contact your system administrator.

TNS.0004.2028	{0} encountered error while resubmitting following internalDocIDs: {1}. Access denied, as user {2} doesn't have permission to resubmit these documents.
Explanation	In webMethods Trading Networks, while resubmitting the BizDoc documents, if the user does not have access permission to resubmit these documents, this error is thrown.
Action	The administrator needs to give permission to the user for resubmitting the BizDoc documents.
TNS.0004.2030	{0} encountered null or empty internalDocIDs[{1}], this document was not reprocessed.
Explanation	In webMethods Trading Networks, while reprocessing BizDocs, if null or empty internal DocIDs are passed, this error is thrown.
Action	Ensure that the internal DocIDs are not null or empty.
TNS.0004.2031	{0} encountered error reprocessing internalDocIDs[{1}] {2}.
Explanation	In webMethods Trading Networks, if an error is encountered while reprocessing BizDocs, this error is thrown.
Action	Contact your system administrator.
TNS.0004.2032	{0} encountered error while reprocessing following internalDocIDs: {1}. Access denied, as user {2} doesn't have permission to reprocess these documents.
Explanation	In webMethods Trading Networks, if an error is encountered while reprocessing BizDocs, access is denied as the user does not have permission to reprocess the documents.
Action	Ensure that the administrator gives permission to the user to reprocess BizDocs.
TNS.0004.2034	{0} encountered null or empty taskIDs[{1}] {2}, this task was not stopped.
Explanation	In webMethods Trading Networks, while stopping the tasks, if null or empty taskIDs are passed, this error is thrown.
Action	Ensure that the taskID is not null or empty and try again.
TNS.0004.2035	{0} encountered error stopping taskIDs[{1}] {2}.
Explanation	In webMethods Trading Networks, while stopping the tasks, if the stopping fails for any reason, this error is thrown
Action	Contact your system administrator.

TNS.0004.2036	{0} encountered error while stopping following tasks: {1}. Access denied, as user {2} doesn't have permission to stop these tasks.
Explanation	In webMethods Trading Networks, while stopping the tasks, if the user does not have permission to stop the tasks, this error is thrown.
Action	Ensure that the user has permission to stop the tasks.
TNS.0004.2038	{0} encountered null or empty taskIDs[{1}], this task was not restarted.
Explanation	In webMethods Trading Networks, while restarting tasks, if null or empty taskIDs are passed, this error is thrown.
Action	Ensure that the taskID is not null or empty and try again.
TNS.0004.2039	{0} encountered error restarting taskIDs[{1}] {2}.
Explanation	In webMethods Trading Networks, if restarting tasks fails, this error is thrown.
Action	Contact your system administrator.
TNS.0004.2040	{0} encountered error while restarting following tasks: {1}. Access denied, as user {2} doesn't have permission to restart these tasks.
Explanation	In webMethods Trading Networks, while restarting tasks, if access is denied to the user, this error is thrown.
Action	Ensure that the user has access permission to restart tasks and try again.
TNS.0004.2042	{0} encountered null or empty taskIDs[{1}], this task was not deleted.
Explanation	In webMethods Trading Networks, while deleting tasks, if null or empty taskIDs are passed, this error is thrown.
Action	Ensure that the taskIDs passed are not null or empty, and try again.
TNS.0004.2043	{0} encountered error deleting taskIDs[{1}] {2}.
Explanation	In webMethods Trading Networks, if an error occurs while deleting the tasks, this error is thrown.
Action	Contact your system administrator.
TNS.0004.2044	{0} encountered error while deleting following tasks: {1}. Access denied, as user{2} doesn't have permission to delete these tasks.
Explanation	In webMethods Trading Networks, while deleting tasks, if the user does not have permission, this error is thrown.
Action	Ensure that the user has permission to delete tasks, and try again.

TNS.0004.2048	{0} encountered error while updating User Status for internalDocID {1}. Access denied, as user {2} doesn't have permission to change UserStatus for this document.
Explanation	In webMethods Trading Networks, while updating the user status for XXX, if access is denied because the user does not have permission to change UserStatus for this document, this error is thrown.
Action	Ensure to give permission to the user to change UserStatus for the document, and try again.
TNS.0004.2050	{0} encountered error while updating comments for internalDocID {1}. Access denied, as user {2} doesn't have permission to edit comments for this document.
Explanation	In webMethods Trading Networks, while updating comments for an internal document, if access is denied because the user does not have access permissions, this error is thrown.
Action	Ensure that the user has access permissions and try again.
TNS.0004.2052	{0} encountered error while deleting following ActivityLogIDs: {1}. Access denied, as user {2} doesn't have permission to delete these activity logs.
Explanation	In webMethods Trading Networks, while deleting activity logs, if access is denied because the user does not have access permissions, this error is thrown.
Action	Ensure that the user has access permissions, and try again.
TNS.0004.2054	{0} can not reassign task {1} to {2}.
Explanation	In webMethods Trading Networks, while reassigning the task to another server, if it is unsuccessful, this error is thrown.
Action	Contact your system administrator.
TNS.0004.2055	{0} encountered error while reassigning following tasks. Access denied, as user {2} doesn't have permission to reassign these tasks.
Explanation	In webMethods Trading Networks, while reassigning tasks to another server, if the user does not have access permissions, this error is thrown.
Action	Ensure that the user has access permissions, and try again.
TNS.0004.2057	ws.monitor.process.instance:getList returns null output.
Explanation	In webMethods Trading Networks, while getting process information, if ws.monitor.process.instance:getList service returns null output, this error is thrown.
Action	Ensure that the ws.monitor.process.instance:getList service does not return null output, and try again.

TNS.0004.2058	{0} can not get instance information for conversationId {1}.
Explanation	In webMethods Trading Networks, when the user gets a null value of the process information for the conversation ID, this error is thrown.
Action	Ensure the conversation ID is valid and try again.
TNS.0004.2060	{0} retrieved null instance at index 0 for conversationId {1}.
Explanation	In webMethods Trading Networks, while getting process information for a conversation ID, if the instance at index 0 is null, this error is thrown.
Action	Ensure that the instance at index 0 is not null and try again.
TNS.0004.2065	WmMonitor package is not enabled.
Explanation	In webMethods Trading Networks, while checking process information, the WmMonitor package is not installed or enabled.
Action	Ensure that the WmMonitor package is installed and enabled.
TNS.0004.2066	{0} can not submit document.
Explanation	In webMethods Trading Networks, if resubmission of a modified document fails, this error is thrown.
Action	Contact your system administrator.
TNS.0004.2067	{0} encountered error retrieving submitted document from pipeline.
Explanation	In webMethods Trading Networks, while resubmitting documents with modifications, if the retrieved BizDoc is null, this error is encountered.
Action	Ensure that the resubmitted BizDoc is not null and try again.
TNS.0004.2071	{0} encountered error while modifying & resubmitting following document {1}. Access denied, as user {2} doesn't have permission to modify and resubmit this document.
Explanation	In webMethods Trading Networks, while resubmitting modified BizDoc documents, if the user does not have access permissions, this error is displayed.
Action	Ensure that the user has access permissions to resubmit and modify BizDoc documents, and try again.

TNS.0004.2072	{0} encountered execution error.
Explanation	In webMethods Trading Networks, if the execution of any query related service fails, this error is displayed.
Action	Contact your system administrator.
TNS.0004.2074	can not parse {0} to long number.
Explanation	In webMethods Trading Networks Server portal util, in the getTimestampFromLong utility, if the time is not in numbered format, this error is thrown.
Action	Enter time in a numbered format and try again.
TNS.0004.2075	null or empty field name
Explanation	In webMethods Trading Networks portal util, the checkQueryColumnName utility throws this exception when the column name is null or empty.
Action	Enter a column name that is not null.
TNS.0004.2076	Invalid query column name: {0}.
Explanation	In webMethods Trading Networks portal util, the checkQueryColumnName utility throws an exception if the column name is invalid.
Action	Enter a valid column name and try again.
TNS.0004.2077	Invalid document attribute "{0}".
Explanation	In webMethods Trading Networks portal util, the checkQueryColumnName utility throws an exception if the query type is of doc query and the attribute list of the document does not contain the name passed to the utility.
Action	Ensure that the attribute list of the document contains the name passed to the utility and try again.
TNS.0004.2078	Invalid whichQuery value ({0}) for PortalUtils.checkQueryColumnName().
Explanation	In webMethods Trading Networks portal util, the checkQueryColumnName utility throws an exception if the query type passed to the utility is invalid.
Action	Ensure to enter a valid query type and try again.

TNS.0004.2079	Invalid value for {0}: null or empty.
Explanation	In webMethods Trading Networks portal util, the validateOperator utility throws an exception if the operator passed to the utility is null or empty.
Action	Pass a valid operator to the utility and try again.
TNS.0004.2080	Invalid operator {0} for data type {1}.
Explanation	In webMethods Trading Networks portal util, the validateOpValPair utility throws an exception if the operator passed to the utility is null or empty.
Action	Enter a valid operator and try again.
TNS.0004.2081	Invalid null value for {0}, corresponding operator is {1}.
Explanation	In webMethods Trading Networks portal util, the validateOpValPair utility throws an exception if the value supplied corresponding to an operator is null.
Action	Enter a not null value corresponding to the operator.
TNS.0004.2082	Illegal value for number query, {0}: {1}.
Explanation	In webMethods Trading Networks portal util, the validateOpValPair utility throws this exception if the value passed to this utility corresponding to an operator is not in numeric value.
Action	Pass the value to the utility in numeric value and try again.
TNS.0004.2083	Illegal value for date and time query, {0}: {1}.
Explanation	In webMethods Trading Networks portal util, the validateOpValPair utility throws this exception if the value passed to this utility corresponding to an operator is not parsed to a long value.
Action	Enter a numeric long value for the date and time query and try again.
TNS.0004.2084	Unable to display the error message. An internal error has occurred. Please contact customer support.
Explanation	In webMethods Trading Networks portal util, the decodeErrorMessage2 utility throws an exception and is unable to decode the error message.
Action	Contact your system administrator.

TNS.0004.2085	Can not get related document information for docId={0}: null data returned
Explanation	In webMethods Trading Networks, while getting document information for a document ID, If the data extracted for the document ID is null, it throws an error.
Action	Contact your system administrator.
TNS.0004.2086	Invalid whichQuery value {0}.
Explanation	In webMethod Trading Networks, this error message is shown if the query type (whichQuery) for creating a query is invalid.
Action	Enter a valid query type (whichQuery) in creating a query.
TNS.0004.2088	Invalid non-number value for queryInput/pageSize: {0}.
Explanation	In webMethods Trading Networks, in creating a query, the query input or page size entered is a non-number value.
Action	Enter a valid numeric value for the query input or the page size.
TNS.0004.2089	queryInput/pageSize value is equal or less than 0.
Explanation	In the webMethods Trading Networks, while creating or retrieving a query, the queryInput or pageSize value entered is not valid because it is equal to or less than 0.
Action	Enter a valid queryInput or pageSize value for creating or retrieving a query.
TNS.0004.2090	queryInput/criteria/dateRange/startDate {0} is after queryInput/criteria/dateRange/endDate {1}.
Explanation	In webMethods Trading Networks, while creating a query, if the start time is earlier than the end time, this error is shown.
Action	Ensure to correct the start time.
TNS.0004.2091	Invalid null value for queryInput/sortOrder[{0}].
Explanation	In webMethods Trading Networks, while creating or retrieving a query, if any of the sorting columns is null, this error is shown.
Action	Ensure that the sorting column is not null.

TNS.0004.2092	{0} queryInput/sortOrder[{1}]/columnName ({2}) is not valid, ignored this column for query sorting.
Explanation	In webMethods Trading Networks, while creating a query, if the sorting column specified in the query input is not valid, the column is ignored for query sorting.
Action	Ensure to enter a valid sorting column in the query.
TNS.0004.2093	Invalid null value for queryInput/criteria/fields[{0}].
Explanation	In webMethods Trading Networks, while creating a query, if any of the given fields is null, this error is shown.
Action	Ensure to enter a valid value (not null) for all the fields.
TNS.0004.2094	Invalid null or empty queryInput/criteria/fields[{0}]/fieldName value.
Explanation	In webMethods Trading Networks, while creating a query, if the field name is null or empty, this error is thrown.
Action	Ensure that all field names are valid.
TNS.0004.2095	query criteria for field {0} already exists, additional criteria found at index {1}.
Explanation	In webMethods Trading Networks, while creating a query, if the query criteria for the field already exists, this error is thrown.
Action	Enter a query criteria that is unique.
TNS.0004.2096	Invalid value: {0} for queryInput/criteria/fields/isOrQuery.
Explanation	In webMethods Trading Networks, while creating a query, an invalid value is entered for the IsOrQuery (value of OR is undefined).
Action	Enter a valid value for the IsOrQuery (value of OR).
TNS.0004.2097	queryInput/criteria/fields[{0}]/criteria is null or 0-length.
Explanation	In webMethods Trading Networks, while creating a query object based on filter criteria, the criteria list for query fields is null or empty.
Action	Enter a valid criteria list for query fields in queryInput.
TNS.0004.2100	Invalid value for {0}: null or empty.
Explanation	In webMethods Trading Networks, while creating a query object based on filter criteria, if the criteria does not contain any operator, this error is thrown.
Action	Enter the operator for the criteria.

TNS.0004.2101	{0} criteria can only be a list plus a dynamic profile query.
Explanation	In webMethods Trading Networks, while creating a query object based on filter criteria, if the query type is a doc query, there should be only one list of values and profile query in the sender and receiver criteria.
Action	Enter only one list of values and profile query in the sender and receiver criteria and try again.
TNS.0004.2102	Invalid value for {0}.
Explanation	In webMethods Trading Networks, while creating a query object based on filter criteria, if the query is of jobQuery type, the internal doc ID or the sender ID or the task ID or the server ID or the instance ID cannot be null.
Action	Ensure that the internal doc ID or the sender ID or the task ID or the server ID or the instance ID are not null and try again.
TNS.0004.2103	Can not understand query {0}.
Explanation	In webMethods Trading Networks, while performing a query, if the query type is not a doc, task, event, profile, bizdoc type, attrib, tpa, or invite type of query, this error message is thrown.
Action	Enter the valid query type and try again.
TNS.0005.1003E	Service manager create failed for server {0} - {1}
Explanation	Encountered a problem while communicating with the database. See the text in the SQL exception for details.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1005E	Unable to get profile for {0} - {1}
Explanation	Encountered a problem while communicating with the database. See the text in the SQL exception for details.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1006E	Unable to remove delivery service {0} - {1}
Explanation	Encountered a problem while communicating with the database. See the text in the SQL exception for details.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1014E	Unable to create delivery task {0} - service {1} does not exist
Explanation	Attempted to deliver a document using a non-existent delivery service.
Action	Correct the serviceName parameter sent to wm.tn.delivery:deliver.
TNS.0005.1027E	Unable to create service data for partner {0} - {1}
Explanation	Attempted to deliver a document to a partner that cannot receive the document. Receiver is either INACTIVE or is My Enterprise (the entity hosting this Trading Network).
Action	Deliver the document to a valid trading partner with an ACTIVE status.
TNS.0005.1028E	Unable to set private key and certificate chain - {0}
Explanation	Encountered an exception while setting the certificate chain and private key in preparation to deliver a document. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.1032E	{0} refreshing {1} cache: {2}
Explanation	Encountered an exception while refreshing an internal cache. See the exception message for details.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1038E	Error transporting via {0}: {1}
Explanation	Encountered an exception while delivering a document. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception, if possible. It may be a network error beyond your control.

TNS.0005.1040E	{0} initializing task store: {1}
Explanation	Encountered an exception while initializing internal caches used for document delivery. See the exception message for details.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1041E	{0} deleting delivery service {1}: {2}
Explanation	Encountered an exception while removing a registered delivery service from the database.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1050E	{0} deleting task {1}: {2}
Explanation	Encountered an exception while deleting a delivery or routing task.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1054E	DeliveryUtils init error: Unable to get profile store: {0}
Explanation	Could not access the profile store during server initialization.
Action	Copy the exception details and call Software AG Global Support.
TNS.0005.1055E	Unable to register delivery service {0} - {1}
Explanation	Encountered an exception while registering a delivery service.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1064E	Unable to initialize delivery interface
Explanation	Encountered an exception while initializing the Delivery Service Manager.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1065E	Unable to register delivery defaults
Explanation	Encountered an exception while registering the built-in delivery services.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1066E	Unable to deliver bizdoc by service
Explanation	Encountered an exception when wm.tn.deliver:deliverByService was invoked.
Action	Take appropriate action to resolve the problem described in the exception, if possible. It may be a network error beyond your control.
TNS.0005.1067E	Error delivering bizdoc
Explanation	Encountered an exception while delivering a document.
Action	Take appropriate action to resolve the problem described in the exception, if possible. It may be a network error beyond your control.
TNS.0005.1068E	Error getting delivery job
Explanation	Encountered an exception while retrieving a delivery job.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1069E	Error getting delivery job output
Explanation	Encountered an exception while retrieving the output of a reliable delivery job.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1070E	Error getting delivery job status
Explanation	Encountered an exception while retrieving the status of a delivery job.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1071E	Error removing delivery job
Explanation	Encountered an exception while removing a reliable delivery job.
Action	Use the JDBC Pools page on the Integration Server Administrator to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1072E	Error restarting delivery job
Explanation	Encountered an exception while restarting a reliable delivery job.
Action	Use the JDBC Pools page on the Integration Server Administrator to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1073E	Error getting registered delivery service {0}
Explanation	Encountered an exception while retrieving a registered delivery service.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1074E	Error getting registered delivery services
Explanation	Encountered an exception while retrieving the set of registered delivery services.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1075E	Error determining if delivery service {0} is registered
Explanation	Encountered an exception while retrieving a named registered delivery service.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1076E	Error refreshing service cache
Explanation	Encountered an exception while refreshing the cache of registered delivery services.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1077E	Error registering service {0}
Explanation	Encountered an exception while registering a delivery service.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1078E	Error removing service {0}
Explanation	Encountered an exception while unregistering a delivery service.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1081E	Couldn't query delivery service table
Explanation	Encountered a SQLException while reading delivery services.
Action	Take appropriate action to resolve the problem described in the exception, if possible.
TNS.0005.1082E	Couldn't query delivery job table
Explanation	Encountered a SQLException while reading delivery jobs.
Action	Take appropriate action to resolve the problem described in the exception, if possible.
TNS.0005.1083E	Property watt.server.smtpServer is not set
Explanation	Cannot send e-mail messages because the system property, watt.server.smtpServer, has not been set.
Action	Use the Properties page of the Integration Server Administrator to supply a value for the watt.server.smtpServer property.
TNS.0005.1084E	Receiver of document cannot be self
Explanation	A document is being sent from this Trading Networks server and the receiver of the document is a host of Trading Network. You cannot send a document to yourself.
Action	Ensure that the receiver of the document is not a host of Trading Networks.
TNS.0005.1085E	Receiver of document is not Active
Explanation	Status of the partner profile for the receiver of the document is not in active state. Documents can only be sent to active partners.
Action	Ensure the receiver of the document is an active partner.

TNS.0005.1086E	Unknown protocol: {0}
Explanation	Attempted to send a document via an unknown protocol. Documents must be sent using one of the registered delivery services.
Action	Use a registered delivery service to send the document.
TNS.0005.1087E	Destination info not found
Explanation	Attempting to send a document, but the receiver's destination information cannot be found.
Action	Examine the document to learn the intended receiver. Make sure the receiver's profile has valid delivery method information.
TNS.0005.1090E	Unable to initialize DeliveryStore {0}
Explanation	Encountered an exception during initialization.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.1092E	Service not registered
Explanation	Attempted to remove a delivery service that is not registered.
Action	Check the name of the registered delivery service you want to remove.
TNS.0005.1096E	Delivery queue {0} refers to Delivery service {1} which is not registered.
Explanation	In webMethods Trading Networks, during batch delivery of queued tasks, if the delivery service used is not registered and the delivery queue refers to it, this error is thrown.
Action	Use the webMethods Trading Networks to update the delivery queue so that it uses a valid batch delivery service.
TNS.0005.1097E	Cannot deliver document. Receiver is not active. (DocID={0}, ReceiverD={1})
Explanation	Queued a document for scheduled delivery, but the receiver is inactive and cannot receive documents.
Action	Activate the receiver's trading partner profile, if appropriate.
TNS.0005.1098E	Unable to get document content for delivery. (DocID={0})
Explanation	Queued a document for scheduled delivery and encountered an error while retrieving document content.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.

TNS.0005.1099E	Cannot register a delivery service with the same name as a built-in delivery service ({0}).
Explanation	This name is reserved for a built-in Trading Networks delivery service.
Action	Change the delivery service's name.
TNS.0005.1101E	Cannot get certificate information from security store for partner {0} in getting delivery information: {1}
Explanation	Encountered an exception while retrieving the certificate chain and private key for a trading partner.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.1105E	Unable to get profile for partner {0} - {1}
Explanation	Encountered an exception while retrieving a trading partner profile.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1106E	Unable to get destination info for partner {0} - {1}
Explanation	Encountered an exception while retrieving destination information from a trading partner profile in preparation for document delivery.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. If no connection problem exists, take appropriate action to resolve the problem described in the exception.
TNS.0005.1107E	Encountered error while delivering by context: {0}
Explanation	Encountered an exception while delivering a document using an internal webMethods protocol.
Action	Take appropriate action to resolve the problem described in the exception, if possible. It may be a network error beyond your control.
TNS.0005.1108E	Unable to deliver document {0}. Delivery service [{1}] does not exist
Explanation	Document delivery failed because the associated delivery service does not exist.
Action	Create the missing delivery service or specify a different delivery service.

TNS.0005.1109	The document (id={0}) was not persisted. The "{1}" delivery service will not be invoked. The document will not be delivered.
Explanation	In webMethods Trading Networks, while delivering documents, if the BizDoc is not persisted, the delivery service is not invoked and the document is not delivered.
Action	Contact your system administrator.
TNS.0005.1115	Event found to be null
Explanation	In webMethods Trading Networks, while writing routing events, if the event is found to be null, then this error is thrown.
Action	Contact your system administrator.
TNS.0005.1117	Encountered error while creating TN document from service response: {0}
Explanation	In webMethods Trading Networks, while delivering a document via WebService, if the document cannot be created from response data, this error is thrown.
Action	Contact your system administrator.
TNS.0005.1118	Encountered error while adding service response to bizdoc: {0}
Explanation	In webMethods Trading Networks, while delivering a document via WebService, if the response data cannot be added as content to the BizDoc, this error is thrown.
Action	Contact your system administrator.
TNS.0005.2002E	An error occurred when this partner polled for documents on this server. The original error message was {0}.
Explanation	An exception was thrown while polling for documents.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.2014E	Error polling for documents
Explanation	An exception was thrown while polling for documents.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.2017E	An error occurred when trying to connect to this partner for polling. The original error was: {0}
Explanation	In webMethods Trading Networks, during a remote checking of a partner, if the connection to the partner cannot be made, this error is thrown.
Action	Ensure that the partner connection information is valid and try again.

TNS.0005.2018E	Error connecting for polling
Explanation	An error occurred when trying to connect to this partner for polling.
Action	Take appropriate action to resolve the problem described in the exception. You might need to contact your trading partner about the error.
TNS.0005.2021E	The user account that schedules polling jobs is {0}. The account does not exist on the B2B Server.
Explanation	In webMethods Trading Networks, during scheduling of a polling job, if the user account that starts the polling job does not exist on the B2B server, this error is thrown.
Action	Create a user account for the user and reload the WmTN package or restart the Integration Server.
TNS.0005.2031E	An error occurred in the process of accepting a document polled from this partner. The original document ID was {0}. The original error message was {1}.
Explanation	In webMethods Trading Networks, if any error occurs during the process of submitting a document locally that is polled from a remote partner, this error is thrown.
Action	Contact your system administrator.
TNS.0005.2037E	Error accepting document
Explanation	An exception was thrown while accepting a document polled from a partner.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.2052E	Unable to initialize TN Polling.
Explanation	An exception was thrown during initialization.
Action	The exception was written to the server log. See the log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0005.2053E	User {0} is not an administrator and attempted to accept a document (docID={1}) that does not belong to him.
Explanation	A partner attempted to accept a pollable document; however, the partner is not the specified receiver of the document.
Action	Review the log message. Contact the partner identified in the log message to explain that a partner can only accept pollable documents for which that partner is the specified receiver.

TNS.0005.2054E	You do not have the authority to accept this document. Only administrators may accept documents that they did not receive.
Explanation	A partner attempted to accept a pollable document; however, the partner is not the specified receiver of the document.
Action	Review the log message. Contact the partner identified in the log message to explain that a partner can only accept pollable documents for which that partner is the specified receiver.
TNS.0005.2055E	No document with an ID of {0} exists. No document accepted.
Explanation	A partner is trying to accept a pollable document that does not exist within Trading Networks.
Action	Review the log message. Work with the partner specified in the log message to resolve the issue.
TNS.0005.3001E	{0} is required.
Explanation	A service was invoked, and a required input variable was not supplied.
Action	Supply a value for the specified variable.
TNS.0005.3002E	Unable to save queue "{0}".
Explanation	Attempt to insert queue information into the Trading Networks database failed.
Action	Ask your database administrator (DBA) to examine the database logs to determine the cause of the problem.
TNS.0005.3003E	Cannot reassign tasks to a private queue.
Explanation	Each partner might have its own private queue. Private queues are defined in the profile for a partner. A private queue can contain only tasks for the partner identified by the profile; private queues cannot contain tasks from other partners.
Action	You can reassign these tasks to a public queue.
TNS.0005.3004E	Unable to remove queue "{0}".
Explanation	Attempt to delete queue information from the Trading Networks database failed.
Action	Ask your database administrator (DBA) to examine the database logs to determine the cause of the problem.

TNS.0005.3005E	Unable to update queue "{0}".
Explanation	Attempt to update queue information in the Trading Networks database failed.
Action	Ask your database administrator (DBA) to examine the database logs to determine the cause of the problem.
TNS.0005.3006E	The queue cannot be deleted because there is data that depends on it.
Explanation	The queue cannot be deleted for one or more of the following reasons: 1) There might be tasks currently on the queue. 2) There are partner profiles and/or processing rules that refer to the queue. A list of objects that depend on the queue follow this message.
Action	Take one or more of the following actions: 1) If there are tasks on the queue, place it in a DRAINING state so that the queue will empty. After all tasks in the queue are processed, you can delete the queue. 2) If there are profiles and/or processing rules that refer to the queue, remove those references. After you remove the references, you can delete the queue.
TNS.0005.3007E	There are {0} tasks on the queue.
Explanation	The queue cannot be removed because it has tasks on it.
Action	Place the queue in a DRAINING state so that the queue will empty. After the tasks in the queue have been processed, you can delete it.
TNS.0005.3008E	There are {0} partner profiles that refer to the queue.
Explanation	The queue cannot be removed because one or more partner profiles refers to it.
Action	This message is followed by a list of partners whose profiles refer to the queue. Modify these profiles so they no longer refer to the queue being removed. After you remove the references, you can delete the queue.
TNS.0005.3009E	There are {0} processing rules that refer to the queue.
Explanation	The queue cannot be removed because one or more processing rules refers to it.
Action	This message is followed by a list of processing rules that refer to the queue. Modify these processing rules so they no longer refer to the queue being removed. After you remove the references, you can delete the queue.
TNS.0005.3012E	There is no task with the supplied ID ({0}).
Explanation	The wm.tn.queuing:updateQueuedTask service was supplied an invalid task ID.
Action	Supply a valid task ID.

TNS.0005.3013E **updateQueuedTask may only be invoked for tasks that are currently being processed from a DeliveryQueue. This task ({0}) has a status of {1}.**

Explanation You attempted to run the wm.tn.queuing:updateQueuedTask service for a task; however, you did not first invoke the wm.tn.queuing:getQueuedTask service.

Action Be sure to use the wm.tn.queuing:getQueuedTask service to retrieve a task from a queue.

TNS.0005.3018E **Attempted to update a DeliveryQueue that has not been registered (queue name={0}).**

Explanation The specified queue does not exist.

Action Either supply a valid queue name or use My webMethods to define the delivery queue.

TNS.0005.3019E **status must be "success" or "fail". {0} was supplied.**

Explanation The wm.tn.queuing:updateQueuedTask service was supplied an invalid status.

Action Supply a valid status value.

TNS.0005.3020E **Attempted to remove a DeliveryQueue that has not been registered (queue name={0}).**

Explanation The specified queue does not exist.

Action Supply a valid queue name.

TNS.0005.3021E **Unable to decode TypeData for a DeliveryJob (ID={0}) while dequeuing from {1}**

Explanation Internal error.

Action Contact Software AG Global Support.

TNS.0005.3023E **The scheduled delivery date/time is in the past.**

Explanation Trading Networks cannot schedule delivery to run in the past.

Action Supply a future date and time.

TNS.0005.3024E **The delivery schedule is empty. It has been ignored.**

Explanation The delivery queue does not have a delivery schedule. The operation has failed.

Action If you receive this error while invoking a service, make sure that you are supplying a valid DeliveryQueue object that contains a DeliverySchedule. If you receive this error while using My webMethods, contact Software AG Global Support.

TNS.0005.3025E	Delivery schedule dates must be in the format "YYYY/MM/DD" and times must be in the format "hh:mm:ss"
Explanation	A date and/or time in the delivery schedule is invalid.
Action	All dates and times in the delivery schedule must be in the specified formats.
TNS.0005.3027E	Unable to schedule delivery for queue "{0}". The pipeline for the delivery service does not contain "queue".
Explanation	The variable "queue" was not supplied in the pipeline.
Action	Supply the name of the delivery queue.
TNS.0005.3028E	The delivery schedule has no schedule type. It has been ignored.
Explanation	The delivery schedule must have a type of "repeat", "complex", or "once".
Action	Set the type on the delivery schedule to a valid value.
TNS.0005.3029E	The queue "{0}" does not exist.
Explanation	In webMethods Trading Networks, while updating a queue, if the queue does not exist, this error is thrown.
Action	Ensure that the queue that is to be updated exists, and try again.
TNS.0005.3037E	Scheduled delivery failed. No more retries.
Explanation	The final attempt to delivery a document failed.
Action	See the message TRNSERV.000022.000038 for full details.
TNS.0005.3038E	Scheduled delivery of document {0} failed. No more retries. {1}
Explanation	The final attempt to deliver a document failed.
Action	See the error message for details. You might need to contact your trading partner.
TNS.0005.3039E	The queue "{0}" has a status of "{1}". It is not accepting documents. This document will not be delivered.
Explanation	Attempted to route a document to a delivery queue that is either disabled or draining. Queues in either of these statuses cannot accept documents.
Action	Either change the status of this queue or route the document to a different queue.

TNS.0005.3040E **Unable to validate private queue/partner relationship (id={0}) because the partner could not be retrieved. The queue has been saved with a "disabled" status.**

Explanation You can only create a private queue for a partner that has an active profile. The specified partnerID identifies a partner that does not exist or whose profile is not active.

Action Perform one of the following actions: 1) Specify a different queue. 2) If the profile is not active, change its status to active.

TNS.0005.3041E **Private queue "{0}" has a status of "{1}", but the partner's profile is not active. The queue has been saved with a "disabled" status.**

Explanation Trading Networks attempted to route a document to a private queue that is defined for a profile that is not active. Trading Networks can only route documents to private queues belonging to active partners; it cannot route documents to private queues of inactive partners. Trading Networks has disabled the queue.

Action Enable the partner by changing the profile status to active. Then enable the partner's private queue.

TNS.0005.3042E **Delivery not scheduled from queue.**

Explanation In webMethods Trading Networks, while scheduling delivery of documents from queues, if the queue is private and the partner is either inactive or not found, this error is thrown.

Action Ensure that the partner of the private queue is available and active, and try again.

TNS.0005.3044E **Document was not queued for delivery on queue {0}. The receiver's profile was not found. (receiverID={1}).**

Explanation A processing rule indicated that the document should be delivered to a queue that is associated with a receiver. However, there is no profile for the receiver.

Action Use My webMethods to determine who the intended receiver is. If the receiver is valid but does not have a profile, create a partner profile for the receiver. If the receiver is not valid, notify the document sender that the receiver information in the document is incorrect.

TNS.0005.3045E **Document was not queued for delivery on queue {0}. The receiver is not active (receiverID={1}).**

Explanation A processing rule indicated that the document should be delivered to a queue that is associated with a receiver. However, the receiver's profile is not active. Trading Networks can only route documents to active partners.

Action Enable the partner by changing the profile status to active. Then enable the partner's private queue.

TNS.0005.3046E	The queue "{0}" does not exist.
Explanation	The wm.tn.queuing:deliverBatch service was supplied an invalid queue name.
Action	Supply the name of an existing queue.
TNS.0005.3048E	The scheduled {0} is invalid. Format must be YYYY/MM/DD
Explanation	In webMethods Trading Networks, while validating scheduling of tasks, if the format of the schedule date is invalid, this error is thrown.
Action	Enter the schedule date in the correct format and try again.
TNS.0005.3049E	The scheduled {0} is invalid. Format must be hh:mm:ss
Explanation	In webMethods Trading Networks, while validating the schedule task, if the format of the time is invalid, this error is thrown.
Action	Enter the schedule time in the correct format and try again.
TNS.0005.3056E	Interval is required.
Explanation	An interval must be specified for repeating tasks.
Action	Supply an interval value.
TNS.0005.3057E	Interval is not a valid integer.
Explanation	In webMethods Trading Networks, while validating a scheduling task, if the time interval is not a valid integer, this error is thrown.
Action	Enter the time interval as a valid integer and try again.
TNS.0005.3058E	Interval must be greater than zero.
Explanation	In webMethods Trading Networks, while validating a scheduling task, if the time interval is not greater than zero, this error is thrown.
Action	Enter the time interval as a valid integer greater than zero and try again.
TNS.0005.3059E	End date/time is in the past.
Explanation	In webMethods Trading Networks, while validating a scheduling task, if the end date/time is occurring in the past, this error is thrown.
Action	Enter a valid end date/time and try again.

TNS.0005.3060E	End date/time is before start date/time.
Explanation	In webMethods Trading Networks, while validating a scheduling task, if the end date/time occurs before the start date/time, this error is thrown.
Action	Enter the valid end date/time and try again.
TNS.0005.3061E	Could not construct a valid timestamp from this schedule. Dates must be in YYYY/MM/DD format and times must be in hh:mm:ss format.
Explanation	In webMethods Trading Networks, while validating the scheduling task, if the end date is not in YYYY/MM/DD format and the end time is not in hh:mm:ss format, this error is thrown.
Action	Ensure that the end date and time are in the correct format and try again.
TNS.0005.3062E	A queue with this name already exists.
Explanation	In webMethods Trading Networks, while registering a queue, if a queue with this name already exists, this error is thrown.
Action	Ensure to have a unique queue name and try again.
TNS.0005.3063E	There is a task on the queue (task id={0}).
Explanation	The queue cannot be removed because it has tasks on it.
Action	Place the queue in a DRAINING state so that the queue will empty. After the tasks in the queue have been processed, you can delete it.
TNS.0005.3064E	The profile for {0} refers to the queue (partner id={1}).
Explanation	The queue cannot be removed because one or more partner profiles refers to it.
Action	This message is followed by a list of partners whose profiles refer to the queue. Modify these profiles so they no longer refer to the queue being removed. After you remove the references, you can delete the queue.
TNS.0005.3065E	The {0} processing rule refers to the queue.
Explanation	The queue cannot be removed because one or more processing rules refers to it.
Action	This message is followed by a list of processing rules that refer to the queue. Modify these processing rules so they no longer refer to the queue being removed. After you remove the references, you can delete the queue.

TNS.0005.3066E	If an end time is supplied, an end date must also be supplied.
Explanation	In webMethods Trading Networks, while validating a scheduling task, if the delivery schedule is of complex type, and the end time is supplied but the end date is not supplied, this error is thrown.
Action	Ensure to also supply the end date along with the end time and try again.
TNS.0005.3067	Unable to import partner private queue {0}. Partner profile for {1} does not exist.
Explanation	In webMethods Trading Networks, while importing Trading Networks assets, if the partner profile for which a partner private queue is to be imported does not exist, this error is thrown.
Action	Ensure that the partner profile exists, and try again.
TNS.0005.4002E	Processing recursion was detected: the processing rule {0} invoked itself, most recently with document {1}. Processing fails.
Explanation	A processing rule recursed. Either no recursion is allowed, or recursion is allowed, and the maximum recursion level was exceeded.
Action	If you want a processing rule to recurse (to call itself), set the tn.recursion.max property to an appropriate value. If you do not want the processing rule to recurse, check the service that the processing rule invokes. The service is submitting a document that matches the same routing rule.
TNS.0005.4004E	If alertPartner is not specified, neither alertContact, alertSubject nor alertMessage may be specified.
Explanation	An invalid combination of input values was sent to wm.tn.route:create.
Action	If you are not supplying a value for alertPartner, do not supply a value for alertContact, alertSubject, or alertMessage.
TNS.0005.4008E	Error sending mail: {0}
Explanation	Encountered an exception while sending an email alert.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4011E	An error occurred invoking the processing service ({2}) for this document. The original error was of type {0}; the message was {1} and the service output this pipeline: {3}
Explanation	A processing rule invoked a service, and that service returned an error.
Action	Take appropriate action to resolve the problem described in the error message.

TNS.0005.4012E	Error signaled in processing service
Explanation	A processing rule invoked a service, and that service returned an error.
Action	See the full message (TRNSERV.000014.000012) for details.
TNS.0005.4013E	An internal error prevented processing from finishing normally on this document. The aborted rule was {0}, and the original error message was {1}.
Explanation	See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4014E	Internal processing error
Explanation	See the full message (TRNSERV.000014.000013) for details.
Action	See the full message for details.
TNS.0005.4017E	{0} loading rules
Explanation	Encountered an exception while reading processing rules from the database.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0005.4023S	{0} saving rules
Explanation	Encountered an exception while saving processing rules to the database. Trading Networks wrote the exception to the server log.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4027E	An exception occurred invoking a processing service for document {0}. The processing service was {1}, and the original error message was: {2}.
Explanation	A processing rule invoked a service, and that service threw an exception.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4028E	An error occurred invoking the processing service {0} for this document. The original error was {1}.
Explanation	A processing rule invoked a service, and that service threw an exception.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4029E	Service invoke err: {0}
Explanation	A processing rule invoked a service, and that service threw an exception.
Action	See the full message for details.
TNS.0005.4034E	Error sending via {0}
Explanation	Error encountered.
Action	See the full message for details.
TNS.0005.4035E	Fatal processing error: {0}
Explanation	Encountered an exception while processing a document. See the exception for details.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4038W	Changing the user status on document {0} generated an error. The original error message was: {1}
Explanation	Encountered an exception while changing the status for a document. See the exception for details.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4039E	Error changing status
Explanation	Encountered an exception while changing the status for a document. See the exception for details.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4040E	An error occurred sending via protocol {0}. The original error message was: {1}
Explanation	Encountered an exception while sending a document. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4041E	Error delivering document
Explanation	Encountered an exception while sending a document.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.4052E	Processing Alert Failed
Explanation	Encountered an error while sending an email alert.
Action	See full message for details.
TNS.0005.4053E	The server was unable to send email to {0} during processing. The subject of the email was {1}. The error message was: {2}.
Explanation	Encountered an error while sending an email alert.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4054E	PROCESSING ERROR: partner contact {0}/{1} is not defined
Explanation	Processing is configured to send alerts to a specific contact type, but the partner profile does not have a contact of that type.
Action	Either change the processing rule to send alerts to a different contact type (or use a hard-coded email address), or create a contact of this type for the partner.
TNS.0005.4055E	Partner {1} sent this document posing as {0}.
Explanation	When Trading Networks receives a document, it determines the partner initiating the request based on the user account that sent the document. The partner that sent the request does not match the sender from within the document content.
Action	You might want to notify the partner who sent the document and/or the partner being impersonated.
TNS.0005.4056E	Partner {1} sent document {2} posing as {0}.
Explanation	When Trading Networks receives a document, it determines the partner initiating the request based on the user account that sent the document. The partner that sent the request does not match the sender from within the document content.
Action	You might want to notify the partner who sent the document and/or the partner being impersonated.
TNS.0005.4057E	Partner ID mismatch
Explanation	The partner who sent the document does not match the partner in the document content.
Action	See full message for details.

TNS.0005.4058E	The sender of this document ({0}) has been deleted. Documents from this partner are not permitted at this time.
Explanation	Trading Networks received a document from a partner whose profile was deleted. Although Trading Networks still maintains a copy of the deleted profile in its database, it will not accept documents nor process documents from the partner.
Action	If you do not want to accept documents from the partner, you can either ignore this error or notify the partner to stop sending documents. If you want to receive and process documents from this partner, use the wm.tn.profile:undeleteProfile service to reinstate the partner's profile.
TNS.0005.4059E	The sender of document {2} ({0}) had been deleted. Documents from this partner are not permitted at this time.
Explanation	Trading Networks received a document from a partner whose profile was deleted. Although Trading Networks still maintains a copy of the deleted profile in its database, it will not accept documents nor process documents from the partner.
Action	If you do not want to accept documents from the partner, you can either ignore this error or notify the partner to stop sending documents. If you want to receive and process documents from this partner, use the wm.tn.profile:undeleteProfile service to reinstate the partner's profile.
TNS.0005.4060E	Partner deleted
Explanation	Received a document from a partner whose profile was deleted.
Action	See full message for details.
TNS.0005.4067E	An attempt was made to send email to the {0} contact of the Unknown partner. No email was sent.
Explanation	The processing rule is configured to send an alert to a partner's contact, but Trading Networks could not identify the partner.
Action	Examine the document content and the Sender/Receiver queries on the document type to determine why Trading Networks could not identify the partner.
TNS.0005.4068E	Can't send to UNKNOWN
Explanation	The processing rule is configured to send an alert to a partner, but Trading Networks could not identify the partner.
Action	Examine the document content and the Sender/Receiver queries on the document type to determine why Trading Networks could not identify the partner.

TNS.0005.4070E	Processing aborted
Explanation	Threw a RoutingAbortedException while processing the document.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4071E	The processing service, {0} aborted processing of this document. The message was {1}.
Explanation	Threw a RoutingAbortedException while processing the document.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4074E	The user that posted this document ({0}) could not be associated with a partner to check their identity.
Explanation	Received a document from someone other than a trading partner.
Action	You can either ignore this error or contact the document sender. The sender is using a valid Integration Server account, but not the account associated with their profile.
TNS.0005.4075E	The user that posted document {1} ({0}) could not be associated with a partner to check their identity.
Explanation	Received a document from someone other than a trading partner.
Action	You can either ignore this error or contact the document sender. The sender is using a valid Integration Server account, but not the account associated with their profile.
TNS.0005.4076E	No user ID
Explanation	Received a document from someone other than a trading partner.
Action	You can either ignore this error or contact the document sender. The sender is using a valid Integration Server account, but not the account associated with their profile.
TNS.0005.4078E	No email address
Explanation	Could not determine the address to send an email alert.
Action	Examine the processing rule and the receiver's profile. You must specify an address either in the processing rule or the receiver's profile.
TNS.0005.4079E	No email address was available for sending to {0} ({1}). No email was sent.
Explanation	Could not determine the address to send an email alert.
Action	Examine the processing rule and the receiver's profile. You must specify an address either in the processing rule or the receiver's profile.

TNS.0005.4086E	No SMTP server defined: check property watt.server.smtpServer
Explanation	The processing rule is configured to send an email alert, but no email server is defined.
Action	Set the SMTP Server on the Settings > Logging page of the Integration Server Administrator, or directly set the watt.server.smtpServer property.
TNS.0005.4087E	Cannot specify a Sender of {0} and also supply a specific senderId's.
Explanation	When invoking wm.tn.route:create, you cannot specify that the processing rule matches 'Any' sender or the 'Unknown' sender, and also supply specific senderIDs.
Action	Either remove "Any", "Unknown", or the specific senderIDs.
TNS.0005.4089E	Cannot specify a DocType of {0} and also supply specific docTypeId's.
Explanation	When invoking wm.tn.route:create, you cannot specify that the processing rule matches 'Any' document type or the document type is 'Unknown', and also supply specific document type IDs.
Action	Either remove "Any", "Unknown", or the specific document type IDs.
TNS.0005.4090E	An exception prevented the sender's identity from being completely checked. The original exception was {0}.
Explanation	Threw a ProfileStoreException while checking the identity of the document sender.
Action	Contact Software AG Global Support.
TNS.0005.4094E	The sender of this document ({0}/{1}) is in status {2}. Documents from this partner are not permitted at this time.
Explanation	The document sender is not active. Inactive partners are not allowed to send documents to Trading Networks.
Action	You can ignore this error, activate this partner's profile, or notify the partner to stop sending documents.
TNS.0005.4095E	The sender of document {3} ({0}/{1}) is in status {2}. Documents from this partner are not permitted at this time.
Explanation	The document sender is not active. Inactive partners are not allowed to send documents to Trading Networks.
Action	You can ignore this error, activate this partner's profile, or notify the partner to stop sending documents.

TNS.0005.4096E	Bad status
Explanation	The document sender is not active. Inactive partners are not allowed to send documents to Trading Networks.
Action	You can ignore this error, activate this partner's profile, or notify the partner to stop sending documents.
TNS.0005.4097E	An error occurred trying to send this document via {0} (intended receiver: {1}). The original error message was: {2}.
Explanation	Encountered an exception while sending a document. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4098E	An error occurred trying to send this document via {0} (sender: {1}). The original error message was: {2}.
Explanation	Encountered an exception while sending a document. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4099E	Couldn't send doc {0} via {1}: {2}
Explanation	Encountered an exception while sending a document. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4100E	An error occurred trying to fetch profile information for sending email to the {1} contact of partner {0}. The original error was: {2}
Explanation	Unable to retrieve the partner profile while sending an email alert. See the exception message for details.
Action	Contact Software AG Global Support.
TNS.0005.4101E	Profile error
Explanation	Unable to retrieve the partner profile while sending an email alert. See the exception message for details.
Action	Contact Software AG Global Support.

TNS.0005.4102E	Processing aborted: {0}
Explanation	Threw a RoutingAbortedException while processing the document.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4104E	{0} is not a known document attribute.
Explanation	The wm.tn.route:create service was supplied an invalid attribute name.
Action	Supply only names of existing document attributes.
TNS.0005.4107E	No preferred protocol. Status changed to POLLABLE.
Explanation	The processing rule was configured to send the document using the receiver's preferred protocol, but the receiver does not have a preferred protocol.
Action	Signify one of the receiver's delivery methods as the preferred protocol.
TNS.0005.4111E	No profile summary was available for the sender of this document
Explanation	Could not process the document because Trading Networks could not find a partner profile for the sender.
Action	Modify either the sender identification in the document or the external ID in the profile.
TNS.0005.4112E	No profile summary was available for the sender of document {2}. The sender ID was {0}, and the sender logged in as {1}.
Explanation	Could not process the document because Trading Networks could not find a partner profile for the sender.
Action	Modify either the sender identification in the document or the external ID in the profile.
TNS.0005.4113E	No profile summary available
Explanation	Could not process the document because Trading Networks could not find a partner profile for the sender.
Action	Modify either the sender identification in the document or the external ID in the profile.

TNS.0005.4114E	A supplied attribute condition has an invalid combination of datatype, operator and value ({0} {1} {2}).
Explanation	The wm.tn.route:create service was supplied an invalid attribute condition.
Action	Correct the attribute condition.
TNS.0005.4115E	An invalid value was supplied for the tn.recursion.max property. No recursion of processing rules will be allowed.
Explanation	The value of the tn.recursion.max property is not a valid number.
Action	Supply a valid number for this property.
TNS.0005.4116E	Processing recursion exceeded the allowed recursion depth of {0}. The processing rule {1} invoked itself, most recently with document {2}. Processing fails.
Explanation	One or more processing rules invoked services that resubmitted documents to Trading Networks, exceeding the recursion limit defined by the tn.recursion.max property.
Action	Increase the value of the tn.recursion.max property, or configure your processing rules not to resubmit documents.
TNS.0005.4117E	Couldn't load routing schedule: {0}
Explanation	Encountered an exception while reading the set of processing rules from the database.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4118E	Couldn't save routing schedule: {0}
Explanation	Encountered an exception while saving the set of processing rules to the database.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4119E	Cannot specify a Receiver of Any and also supply a specific receiverId's.
Explanation	When invoking the wm.tn.route:create service, you cannot specify that the processing rule matches 'Any' receiver and also supply specific receivers.
Action	Remove either "Any" or the specific receivers.
TNS.0005.4120E	Cannot specify a Receiver of Unknown and also supply a specific receiverId's.
Explanation	When invoking the wm.tn.route:create service, you cannot specify that the processing rule matches an 'Unknown' receiver and also supply specific receivers.
Action	Remove either "Unknown" or the specific receivers.

TNS.0005.4121E	Cannot specify a DocType of Any and also supply specific docTypeIds.
Explanation	When invoking the wm.tn.route:create service, you cannot specify that the processing rule matches 'Any' TN document type and also supply specific TN document types.
Action	Remove either "Any" or the specific TN document types.
TNS.0005.4122E	Cannot specify a DocType of Unknown and also supply specific docTypeIds.
Explanation	When invoking the wm.tn.route:create service, you cannot specify that the processing rule matches the 'Unknown' TN document type and also supply specific TN document types.
Action	Remove either "Unknown" or the specific TN document types.
TNS.0005.4123E	If deliverUsing is "Queue for delivery", then deliveryQueue cannot be null
Explanation	An invalid combination of input values was sent to the wm.tn.route:create service.
Action	Supply a value for the "deliveryQueue" variable.
TNS.0005.4125E	Cannot queue a bizdoc for deliver that has not been persisted. This bizdoc (id={0}) has not been persisted.
Explanation	The scheduled delivery mechanism requires that the document be saved to the database.
Action	Change the TN document type or processing rule to save documents of this type.
TNS.0005.4130E	qname is required
Explanation	Attempted to enqueue a delivery job without supplying a queue name for the "qname" parameter.
Action	Supply a valid queue name for the "qname" parameter.
TNS.0005.4131E	Invalid queue name ({0}).
Explanation	Attempted to enqueue a delivery job without supplying a queue name for the "qname" parameter.
Action	Supply a valid queue name for the "qname" parameter.
TNS.0005.4132E	Receiver does not have a delivery queue.
Explanation	The processing rule is configured to send the document to the receiver's private delivery queue, but the receiver does not have a delivery queue.
Action	Change the processing rule to deliver the document by a different means, or create a delivery queue for the receiver.

TNS.0005.4133E	Receiver does not have a delivery queue. Document has been made POLLABLE (document id={0})
Explanation	The processing rule is configured to send the document to the receiver's private delivery queue, but the receiver's profile does not contain a definition for a delivery queue.
Action	Change the processing rule to deliver the document by a different means, or update the receiver's profile to specify a delivery queue.
TNS.0005.4134E	Receiver does not have a preferred protocol. Document has been made POLLABLE. (document id={0})
Explanation	The processing rule is configured to send the document by the receiver's preferred delivery method, but the receiver does not have a preferred delivery method.
Action	Change the processing rule to deliver the document by a different means, or signify one of the delivery methods on the receiver's profile as "preferred".
TNS.0005.4135E	Error encountered in RoutingActions.invoke(): can not clone input pipeline.
Explanation	An internal error occurred while invoking a service to process the document.
Action	Contact Software AG Global Support.
TNS.0005.4136E	Unable to save document: {0}.
Explanation	Encountered an exception while saving the document to the database.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.4138E	The processing rule list has been modified by another user. Added this rule to the bottom of the list. Refresh your rule list.
Explanation	The rule list displayed on your Trading Networks Console is not the current list that resides in the database. As a result, the newly added rule is appended to the end of the rule list rather than the specific position required in the list.
Action	Refresh your routing rule list and move the newly added rule to the desired position.
TNS.0005.4139S	Error encountered while inserting processing rule {0}. The exception message is : {1}.
Explanation	Encountered an exception while inserting a processing rule.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0005.4140E	Error encountered while updating processing rule {0}. The rule index cannot be changed during an update operation.
Explanation	You attempted to update both the contents of a processing rule and its location within the list of processing rules (its index) at the same time. You cannot make both these changes at the same time.
Action	Please update the rule first, and then move the rule to a new position in the rule list.
TNS.0005.4141E	Error encountered while updating processing rule {0}. The exception message is : {1}.
Explanation	Encountered an exception while updating a processing rule.
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0005.4142E	Processing rule update failed. Processing rule update collision detected. This rule has been modified by another user. Refresh your rule list and retry this operation.
Explanation	While you were updating this processing rule, another user edited and saved the same processing rule. To prevent your changes from overwriting those made by the other user, Trading Networks did not save your changes.
Action	Refresh the list of processing rules and update the processing rule again.
TNS.0005.4145S	Error encountered while deleting processing rule(s). The exception message is : {0}.
Explanation	Encountered an exception while deleting processing rule(s).
Action	See the exception message for details. Take appropriate action to resolve the problem described in the exception.
TNS.0005.4146E	Processing rule delete operation aborted. The processing rule list has been modified by another user. Refresh your rule list and retry this operation.
Explanation	While you were deleting this processing rule, another user edited and saved the rule. So that your changes do not overwrite those made by the other user, your changes have not been saved.
Action	Refresh your rule list, and then delete the rule again.
TNS.0005.4147E	Processing rule {0} does not exist.
Explanation	The specified routing rule cannot be retrieved because the rule ID does not exist in the database.
Action	Check that the rule ID is correct, modify it if necessary, and then attempt to retrieve it again.

TNS.0005.4148S **Error encountered while reading processing rules from the database. The exception message is : {0}.**

Explanation Encountered an exception while retrieving processing rules from the database.

Action See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0005.4149S **Error encountered while moving processing rules. The exception message is : {0}.**

Explanation Encountered an exception while moving processing rules in the rule list.

Action See the exception message for details. Take appropriate action to resolve the problem described in the exception.

TNS.0005.4150E **Processing rule move operation aborted. The processing rule list has been modified by another user. Refresh your rule list and retry this operation.**

Explanation While you were moving this processing rule, another user edited and saved the rule list. So that your changes do not overwrite those made by the other user, your changes have not been saved.

Action Refresh the rule list, and then move the rule again.

TNS.0005.4151E **Illegal move operation. The insertAt position cannot be within the range of rules to be moved.**

Explanation The insertAt position must be outside the range of rules to be moved.

Action Change the insertAt position to be outside of the range of rules to be moved.

TNS.0005.4152E **Illegal move operation. You cannot move a non-contiguous set of rules.**

Explanation You attempted to change the order of processing rules by moving a non-contiguous set of rules. Trading Networks does not support this type of operation.

Action Define a contiguous set of rules to be moved.

TNS.0005.4156E **Encountered an error retrieving the Profile Summary for partner ID {0}.**

Explanation An error occurred attempting to look up the Profile Summary.

Action Ensure that the partner IDs on the document being processed are valid.

TNS.0005.4157E	Encountered an error while sending MAPI event to Optimize for EventMap {0} and for Sender with PartnerID {1}.
Explanation	In webMethods Trading Networks, while routing a document, if a TN BAM monitoring event cannot be logged in Optimize, this error is thrown.
Action	Contact your system administrator.
TNS.0005.4160E	The content-length ({0}) specified in handleLargeDoc is less than the length of the content ({1}) sent.
Explanation	In webMethods Trading Networks, in a document transaction, while handling large documents, if the content length specified in the handleLargeDoc is less than the length of the BizDoc content, this error is thrown.
Action	Ensure that the content length specified in the handleLargeDoc is equal to the length of the BizDoc content and try again.
TNS.0005.4162E	Routing Aborted as the Receiver is disabled.
Explanation	In webMethods Trading Networks, while routing a document, if the receiver is in an inactive state, this error is thrown.
Action	Ensure to set the receiver to active state and try again.
TNS.0005.4163E	Routing Aborted as the Receiver is deleted.
Explanation	In webMethods Trading Networks, while routing a document, if the receiver is in deleted state, this error is thrown.
Action	Ensure to set the receiver profile is not deleted and try again.
TNS.0005.4164E	Routing Aborted as the Sender is disabled.
Explanation	In webMethods Trading Networks, while routing a document, if the sender is in inactive state, this error is thrown.
Action	Ensure to set the sender to active state and try again.
TNS.0005.4165E	Routing Aborted as the Sender is deleted.
Explanation	In webMethods Trading Networks, while routing a document, if the sender is deleted, this error is thrown.
Action	Ensure to set the sender profile is not deleted and try again.

TNS.0005.4166E	The processing service aborted processing of this document. The message was {0}.
Explanation	In webMethods Trading Networks, while routing a document, if an error occurs in processing the document, this error is thrown.
Action	Contact your system administrator.
TNS.0005.4167E	Posting of BAM events failed because of following errors - {0}.
Explanation	In webMethods Trading Networks, if any error occurs while posting BAM events, this error is thrown.
Action	Contact your system administrator.
TNS.0005.5002E	Delivery service for {0} failed with a status of {1} and status message of {2}
Explanation	Unable to deliver the document, possibly due to a problem with the network or the destination server.
Action	Verify that your server has network connectivity. If a problem exists with the destination server, contact the person responsible for that server.
TNS.0005.5004E	Unable to get output for task {0} - Task has not finished. Status is {1}
Explanation	The task was still executing when the request for output expired.
Action	Request the output again.
TNS.0005.5005E	Unable to refresh {0} cache on server {1} - {2}
Explanation	A cache could not be refreshed, probably due to a database problem.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. Verify that your database is successfully processing requests.
TNS.0005.5007E	Unable to remove task {0} - Does not exist
Explanation	An invalid task ID was supplied.
Action	Supply a valid task ID.
TNS.0005.5011S	Disabling reliable task manager at {0} - Fatal error: {1}
Explanation	Encountered an exception that requires the task manager to shut down.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.5013W	Unable to restart task {0} upon initialization
Explanation	The task status could not be updated to "Pending" in the database.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. Verify that your database is successfully processing requests.
TNS.0005.5015E	Unable to persist task {0}
Explanation	Encountered an exception while saving the task to the database.
Action	See the full message (TRNSERV.000015.000089) for details.
TNS.0005.5019E	Task {0} unable to move to server {1} - {2}
Explanation	Task has already completed. Status is "Done".
Action	No action required.
TNS.0005.5020E	Unable to refresh {0} cache - {1}
Explanation	See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.5025E	Task {0} failed, status changed to {1}
Explanation	The task has failed. No more retries.
Action	See full message (TRNSERV.000015.000036) for details.
TNS.0005.5026E	Unable to init task manager for server {0} - {1}
Explanation	The task manager could not be initialized, probably due to a database problem.
Action	Use the Integration Server Administrator JDBC Pools page to check that the Integration Server can connect to the database. Verify that your database is successfully processing requests.
TNS.0005.5031E	Error invoking service {0} - message: {1} - stacktrace: {2}
Explanation	The task manager invoked a service to process a document, and that service threw an exception.
Action	See the exception message for details. Correct the invoked service to handle the exception condition.

TNS.0005.5036E	Task {0} failed with no more retries available. Reason for failure - {1}
Explanation	See the status message for details.
Action	If the failure is due to an error on another server, contact the person responsible for that server.
TNS.0005.5037E	Unable to restart task {0} - {1}
Explanation	The task status is neither "Failed" nor "Stopped", so the task cannot be restarted.
Action	No action necessary.
TNS.0005.5039E	Unable to shut down the task manager.
Explanation	The wm.tn.task:shutdown service was unable to stop the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.
TNS.0005.5042E	Unable to initialize task manager.
Explanation	The wm.tn.task:init service was unable to start the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.
TNS.0005.5043E	Unable to reset task manager.
Explanation	The wm.tn.task:restart service was unable to restart the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.
TNS.0005.5044E	Unable to retrieve tasks.
Explanation	The wm.tn.task:getTasks service was unable to get tasks from the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.
TNS.0005.5045E	Unable to retrieve task {0}.
Explanation	The wm.tn.task:getTask service was unable to get a task from the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0005.5046E	Unable to get output for task {0}.
Explanation	The wm.tn.task:getTaskOutput service was unable to get output for a task. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.
TNS.0005.5047E	Unable to get status for task {0}.
Explanation	The wm.tn.task:getTaskStatus service was unable to get the status of a task. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.
TNS.0005.5048E	Unable to change server for task {0}.
Explanation	The wm.tn.task:changeServerForTask service was unable to move a task from one server to another. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.
TNS.0005.5049E	Unable to remove task {0}.
Explanation	The wm.tn.task:removeTask service was unable to remove a task from the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.
TNS.0005.5050E	Unable to restart task {0}.
Explanation	The wm.tn.task:restartTask service was unable to restart a task in the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.
TNS.0005.5051E	Unable to stop task {0}.
Explanation	The wm.tn.task:stopTask service was unable to stop a task in the task manager. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.
TNS.0005.5052E	Unable to move task {0} to server {1}. Task does not exist.
Explanation	An invalid task ID was supplied.
Action	Supply a valid task ID.

TNS.0005.5053E	Unable to move task {0} to server {1}. Task has completed.
Explanation	Task status is "Done". Cannot move a completed task.
Action	No action necessary.
TNS.0005.5054E	Unable to move task {0} to server {1}. Could not "ping" server: {2}
Explanation	Invoked the wm.server:ping service on the other server, and it threw an exception.
Action	Take appropriate action to resolve the problem on the other server as described in the exception.
TNS.0005.5055E	Unable to move task {0} to server {1}. Server {2} is up, but the task has not failed.
Explanation	The server that created this task is running. Therefore, the task cannot be moved because the task status is neither "Failed" nor "Stopped".
Action	No action necessary.
TNS.0005.5056E	Unable to move task {0} to server {1}. Server {2} is down, but the task is done.
Explanation	Task status is "Done". Cannot move a completed task.
Action	No action necessary.
TNS.0005.5057E	Unable to stop task {0}. Job has completed.
Explanation	Cannot stop a completed task.
Action	No action necessary.
TNS.0005.5058E	Unable to stop task {0}. Job does not exist.
Explanation	An invalid task ID was supplied.
Action	Supply a valid task ID.
TNS.0005.5060E	Delivery Job Manager error: task {0} is not NEW.
Explanation	Cannot start a task that does not have a "New" status.
Action	No action necessary. Task has already started.
TNS.0005.5061E	Delivery Job Manager error with task {0}. {1}
Explanation	Encountered an exception while writing to the database. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.

TNS.0005.5062E	Task {0} unable to restart. Does not exist.
Explanation	An invalid task ID was supplied.
Action	Supply a valid task ID.
TNS.0005.5064E	Unable to remove task {0}. {1}
Explanation	Encountered an exception while writing to the database. See the exception message for details.
Action	Take appropriate action to resolve the problem described in the exception.
TNS.0005.5065E	Cannot get job output. Job does not exist.
Explanation	An invalid task ID was supplied.
Action	Supply a valid task ID.
TNS.0005.5066E	Unable to initialize task manager. ServerId is null.
Explanation	Unable to determine server ID.
Action	Supply a value for the watt.net.localhost property in the server.cnf file on the Integration Server.
TNS.0005.5068E	Unable to delete tasks. There are {0} active jobs in the list of jobs to be deleted. Stop the active jobs and retry
Explanation	Cannot delete active tasks.
Action	If you want to delete tasks that are active, stop them first.
TNS.0005.5069E	Unable to get task
Explanation	The wm.tn.route:getTask service can only retrieve tasks that are service execution tasks. A taskID of a delivery task was supplied.
Action	Request only service execution tasks from the wm.tn.route:getTask service.
TNS.0005.5070E	Error getting task
Explanation	The wm.tn.route:getTask service encountered an exception while retrieving a task. See the nested exception for details.
Action	Take appropriate action to resolve the problem described in the nested exception.

TNS.0005.5072E **Unable to restart queued task (id={0}). Its delivery queue no longer exists. You can resubmit the document to process it again.**

Explanation The delivery queue for this document has been deleted. Cannot be requeued.

Action Verify that the processing rule that handles this document is configured to use a valid delivery queue. Resubmit the document.

TNS.0005.5081E **Error invoking service, {0} - Service did not return valid output**

Explanation The task manager invoked a service to process a document. The output of the service did not conform to the expected format.

Action If this is a delivery service, make sure the output matches the wm.tn.rec:DeliveryServiceOutput IS document type. If this is a service invoked by a service execution task, make sure the output matches the wm.tn.rec:reliableServiceOutput IS document type.

TNS.0005.5082E **ERROR: Unable to update task {0} due to database error : {1}. Since task update retry is turned off, manual correction is required. Please correct the database errors and manually update the task using the additional task details provided. Additional Details of this task : Task ID={2}; DocID={3}; TaskStatus={4}; Retries={5}; TransportStatus={6}; TransportStatusMessage={7}; TransportTime={8}**

Explanation Could not update the task. See exception message for details.

Action Manually update the task in My webMethods using the details provided in the message.

TNS.0005.5089E **ERROR: Unable to update task {0} due to IOException : {1}. Task update will continue to fail until this exception is rectified. Until this error is rectified, manual correction is required. Manually update the task using the additional task details provided. Additional Details of this task : Task ID={2}; DocID={3}; TaskStatus={4}; Retries={5}; TransportStatus={6}; TransportStatusMessage={7}; TransportTime={8}**

Explanation Could not update the task. See exception message for details.

Action Manually update the task in My webMethods using the details provided in the message.

TNS.0005.5091S **TN Job Manager sweep time property tn.task.sweepTime contains ({0}), which is not a numeric value. Using the default value 300 seconds**

Explanation The tn.task.sweepTime property contains an invalid value.

Action Supply a valid numeric value.

TNS.0005.5094E	Task {0} failed at {1}: Probable reason for failure - {2}. {3} more retries left.
Explanation	In webMethods Trading Networks, if any error occurs while disabling the delivery for a partner, this error is thrown.
Action	Contact your system administrator.
TNS.0006.1001E	Cannot setIData for CertificateData because the supplied data is null.
Explanation	The setIData method on a CertificateData object passed a null IData object.
Action	If your code is calling CertificateData.setIData, supply an IData object that is not null. If it is not your code that is calling this method, contact Software AG Global Support.
TNS.0006.1002E	Cannot setIData for CertificateData.
Explanation	The setIData method on a CertificateData object was not successful.
Action	If Integration Server logging is set to logging level 4 or higher, the exception was written to the server log. See the server log for more information. Take the appropriate action to resolve the problem described in the exception.
TNS.0006.1003S	Certificate provider Entrust/IAIK was not found, so Trading Networks cannot convert byte[] to java.security.cert.X509Certificate. Please ensure that entrust jar files are in the Integration Server's classpath.
Explanation	The Entrust jar files are missing from the Integration Server's classpath.
Action	Place the Entrust jar files in the Integration Server's classpath. If you need assistance, contact Software AG Global support.
TNS.0006.1004E	CertificateException encountered; Trading Networks cannot convert byte[] to java.security.cert.X509Certificat.
Explanation	Trading Networks encountered a certificateException when attempting to convert a byte array to a java.security.cert.X509Certificat.
Action	If Integration Server logging is configured at logging level 4 or higher, the exception was written to the server log. See the server log for details. Take the appropriate action to resolve the problem described in the exception.
TNS.0006.1005E	Cannot convert byte[][] to X509Certificate[], exception encountered at index {0}.
Explanation	Trading Networks could not create a certificate chain from the bytes. Trading Networks encountered the error at <zeroBasedIndexNum> certificate.
Action	Check the byte array to ensure that it is in the correct format.

TNS.0006.1006E	Cannot convert byte[] to java.security.PrivateKey.
Explanation	Trading Networks could not create a private key object from bytes.
Action	Check the byte array to ensure that it is in the correct format.
TNS.0006.1007E	Cannot convert X509Certificate[] to byte[][], CertificateEncodingException encountered at index {0}. Please verify that the certificate is valid.
Explanation	The certificate chain is not valid.
Action	Provide a valid certificate chain.
TNS.0006.1008E	Cannot convert PKCS7 formatted byte[] into .der formatted byte[][].
Explanation	The PKCS7-formatted bytes are not valid.
Action	Check the byte array to ensure that it is in the correct format. Provide a valid byte array.
TNS.0006.1009E	Cannot load certificate from null File. Please supply a valid File.
Explanation	The supplied certificate file is null.
Action	Supply a certificate file that is not null.
TNS.0006.1010S	Certificate provider Entrust/IAIK not found, so Trading Networks cannot load java.security.cert.X509Certificate from file <filename>. Ensure that entrust jar files are in the Integration Server's classpath.
Explanation	The Entrust jar files are missing from the Integration Server's classpath.
Action	Place the Entrust jar files in the Integration Server's classpath. If you need assistance, contact Software AG Global Support.
TNS.0006.1011E	CertificateException encountered getting certificate from file {0}.
Explanation	An error occurred while attempting to load certificates from the specified file.
Action	Check the certificate file to ensure that it is in the correct format.
TNS.0006.1012E	Cannot load private key from null File.
Explanation	Trading Networks attempted to load the private key from a file; however, the file is null.
Action	Supply a private key file that is not null.

TNS.0006.1013E	IOException encountered loading RSA private key from file {0}.
Explanation	An error occurred while the server attempted to load a private key from the specified file.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem described in the exception.
TNS.0006.1014E	InvalidKeyException encountered loading RSA private key from file {0}.
Explanation	An error occurred while the server attempted to load a private key from the specified file.
Action	Check the private key file to ensure that it is in the correct format.
TNS.0006.1015E	Cannot determine whether the certificate is self-signed because the certificate byte[] is null.
Explanation	The supplied certificate byte array is null.
Action	Supply a non-null certificate byte array.
TNS.0006.1016E	Cannot determine whether the certificate is self-signed because both the subject and issuer are null.
Explanation	The supplied certificate is not in a valid format. Both the subject and issuer are null.
Action	Supply a valid certificate.
TNS.0006.1017E	Cannot determine whether the certificate is self-signed because the certificate is null.
Explanation	The supplied certificate is null.
Action	Supply a non-null certificate.
TNS.0006.1018E	Integration Server's certificate file {0} not found.
Explanation	Trading Networks could not find the specified file that contains the Integration Server's client certificate.
Action	Specify a file that contains a client certificate for the Integration Server.

TNS.0006.1019E	Integration Server's CA certificate file {0} not found.
Explanation	Trading Networks could not find the specified file that contains the Integration Server's CA certificate.
Action	Specify a file that contains the Integration Server's CA certificate.
TNS.0006.1020E	IOException encountered when retrieving the Integration Server's private key from {0}.
Explanation	IOException thrown when Trading Networks was attempting to retrieve the Integration Server's private key from the specified file.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem described in the exception.
TNS.0006.1021E	InvalidKeyException encountered when retrieving the Integration Server's private key from {0}.
Explanation	An error occurred when Trading Networks was attempting to retrieve the Integration Server's private key from the specified file.
Action	Specify a file that contains a valid private key for the Integration Server.
TNS.0006.1022E	Certificate chain bytes cannot be null or zero length.
Explanation	The certificate chainBytes parameter is either null or has a length of zero.
Action	Supply a valid certificate chain.
TNS.0006.1023E	Certificate chain contains a single certificate, and that certificate is not self-signed.
Explanation	The certificate chain is not valid. The certificate chain contains only one certificate, and that certificate is not self-signed. When you are not using a self-signed certificate, a certificate chain must include a certificate and its corresponding CA certificate(s).
Action	Supply a valid certificate chain. That is a single self-signed certificate or a certificate and its corresponding CA certificates.
TNS.0006.1024E	Entrust cannot verify the certificate chain: {0}
Explanation	Entrust could not verify the certificate chain.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take appropriate action to resolve the problem.

TNS.0006.1027E	Cannot determine whether to trust the sign/verify certificate because there is no Enterprise profile.
Explanation	Trading Networks cannot determine whether to trust the sign/verify certificate because there is no Enterprise profile.
Action	Create an Enterprise profile. For information about creating profiles, see the Trading Networks documentation.
TNS.0006.1028E	Cannot set sign/verify certificate for receiver, Enterprise, because a CertificateException was encountered when determining whether the Integration Server trusts the certificate chain.
Explanation	Before setting the sign/verify certificates that are specified in the Enterprise profile, Trading Networks ensures that the Integration Server trusts the certificates. A CertificateException was thrown when determining whether the Integration Server trusts the certificates.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take appropriate action to resolve the problem.
TNS.0006.1029W	Cannot set sign/verify certificate for receiver, Enterprise, because the Integration Server is not set up to trust the certificate specified in the Enterprise profile.
Explanation	Before setting the sign/verify certificate that is specified in the Enterprise profile, Trading Networks ensures that the Integration Server trusts the certificate. The certificate supplied in the Enterprise profile is not among the certificates that the Integration Server trusts.
Action	Add this certificate to the Integration Server's directory of trusted certificates.
TNS.0006.1031E	SQLException encountered when setting certificate data for partner {0}; error message is {1}.
Explanation	An error occurred when Trading Networks attempted to set the certificate data for the partner with the specified partner ID.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take appropriate action to resolve the problem described in the exception.
TNS.0006.1032E	SQLException encountered when retrieving certificate data for partner {0}; error message is {1}.
Explanation	An error occurred when Trading Networks attempted to retrieve the certificate data for the partner with the specified partner ID.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem described in the exception.

TNS.0006.1035E	Cannot setIData() for CertData: CertData is null.
Explanation	The setIData method on a CertData object passed a null IData object.
Action	If your code is calling CertData.setIData, supply a non-null IData object. If it is not your code that is calling this method, contact Software AG Global Support.
TNS.0006.1036E	EXMLException encountered in CertData.setIData().
Explanation	com.wm.app.tn.err.EXMLException was thrown in the setIData() method.
Action	If your code is calling CertData.setIData, check the server log for a stack trace. Take the appropriate action to resolve the problem described in the exception. If it is not your code that is calling this method, contact Software AG Global Support.
TNS.0006.1037E	Cannot get expiration date for node certificate.
Explanation	The certificate does not have expiration date information.
Action	Ensure that the certificate is in a valid format.
TNS.0006.1038E	Cannot convert byte array to java.lang.PrivateKey.
Explanation	Trading Networks could not convert the byte array because it is corrupted.
Action	Ensure that the byte array in the private key file is in a valid format.
TNS.0006.1039E	Cannot set illegal usage {0} for CertData.
Explanation	The CertData object contains a certificate usage parameter that is not legal.
Action	Ensure the certificate usage parameter in the CertData object has one of the following values: "sign", "decrypt", or "ssl".
TNS.0006.1040E	Cannot insert CertData into database, CertData is null.
Explanation	The CertData object is null.
Action	Supply a non-null CertData object.
TNS.0006.1041E	Cannot insert CertData into database because data already exists for supplied owner={0}, partner={1} and usage={2}.
Explanation	You attempted to add certificate information for the specified owner/partner/usage combination. However, there is already certificate information for this owner/partner/usage combination in the Trading Networks database.
Action	If you want to update the certificate information for the specified owner/partner/usage combination, use the update operation instead of insert operation. Otherwise, specify a unique owner/partner/usage combination that does not already exist in the Trading Networks database.

TNS.0006.1042E	Error inserting CertData into the database; update row count is not 1.
Explanation	Trading Networks encountered a database error when performing the insert operation.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1043E	Error inserting CertData into the database; IOException encountered encoding data into binary format.
Explanation	Trading Networks encountered an error when performing the insert operation; an IOException was thrown when encoding data into binary format.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1044E	Error inserting CertData into the database; SQLException encountered with the error message {0}.
Explanation	An SQLException occurred while Trading Networks was attempting to perform a database insert operation.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1045E	Cannot update CertData because the supplied CertData object is null.
Explanation	Trading Networks was attempting to perform a database update operation to update certificate information. However, the supplied CertData object that Trading Networks is to use to update the existing certificate information is null. As a result, Trading Networks cannot perform the database update operation.
Action	Supply a non-null CertData object.
TNS.0006.1046E	Cannot update CertData because the supplied CertID is null.
Explanation	Trading Networks is not able to update the certificate information because the supplied unique identifier, CertID, is null.
Action	Supply a non-null CertID.

TNS.0006.1047E **Cannot update CertData because the specified CertID, {0} does not match the CertID that Trading Networks has for the supplied owner/partner/usage.**

Explanation You attempted to update certificate information for the specified owner/partner/usage combination. However, the supplied CertID does not match CertID that Trading Networks has for this owner/partner/usage combination.

Action Retrieve the correct CertID for the owner/partner/usage combination from database, and issue the request again. This time specify the correct CertID for the owner/partner/usage combination.

TNS.0006.1048E **Error updating CertData; the update count from the update operation is not 1.**

Explanation Trading Networks encountered a database error when performing the update operation.

Action If the Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1049E **Error updating CertData in the database; IOException encountered encoding data into binary format.**

Explanation Trading Networks encountered an error when performing the update operation; an IOException was thrown when encoding data into binary format.

Action If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1050E **Error updating CertData in the database; SQLException encountered with the error message {0}.**

Explanation An SQLException occurred when Trading Networks was attempting to perform a database update operation.

Action If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1051E **Cannot delete CertData because the supplied CertID is null.**

Explanation Trading Networks is not able to delete the certificate information because the supplied unique identifier, CertID, is null.

Action Supply a non-null CertID.

TNS.0006.1052E	Error deleting CertData; the delete count from the delete operation is not 1.
Explanation	Trading Networks encountered a database error when performing the delete operation.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1053E	Error deleting CertData from the database; SQLException encountered with the error message {0}.
Explanation	An SQLException was thrown when Trading Networks was attempting to perform a database delete operation.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1054E	Cannot construct new CertData from SecurityOps.getCertificateData().
Explanation	Internal error
Action	Contact Software AG Global Support.
TNS.0006.1055E	Error selecting CertData for ownerId={0}, partnerId={1}, usage={2}; IOException encountered decoding bytes to IData.
Explanation	When Trading Networks was attempting to select CertData for the owner/partner/usage combination, an IOException was thrown when decoding bytes to IData.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1056E	Error selecting CertData for ownerId={0}, partnerId={1}, usage={2}; SQLException encountered with the error message {3}.
Explanation	An SQLException occurred while Trading Networks was attempting select CertData for the owner/partner/usage combination.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1057E	Cannot construct new CertData from SecurityOps.getCertificateDataByCertID().
Explanation	Internal error
Action	Contact Software AG Global Support.
TNS.0006.1058E	Error selecting CertData for CertId=<certID>; IOException encountered decoding bytes to IData.
Explanation	When Trading Networks was attempting to select CertData with the specified CertID, an IOException was thrown when decoding bytes to IData.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1059E	Error selecting CertData for CertId={0}; SQLException encountered with the error message {1}.
Explanation	An SQLException occurred while Trading Networks was attempting select CertData with the specified CertID.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1060E	Cannot construct new CertData from SecurityOps.getCertificateDataForOwner().
Explanation	Internal error
Action	Contact Software AG Global Support.
TNS.0006.1061E	Error selecting CertData for ownerId={0}; IOException encountered decoding bytes to IData.
Explanation	When Trading Networks was attempting to select CertData for the specified owner, an IOException was thrown while decoding bytes to IData.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1062E	Error selecting CertData for ownerId={0}; SQLException encountered with the error message {1}.
Explanation	An SQLException occurred while Trading Networks was attempting to select CertData for the specified owner.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1063E	Cannot search certificate data because the expiration date is null.
Explanation	The certificate expiration date search criterion is null.
Action	Supply a valid certificate expiration date for this search criterion.
TNS.0006.1064E	Cannot construct new CertData from SecurityOps.getCertificateDataForUpdate().
Explanation	Internal error
Action	Contact Software AG Global Support.
TNS.0006.1065E	Error selecting CertData for ownerId={0} and expDate={1}; IOException encountered decoding bytes to IData.
Explanation	While Trading Networks was attempting to select CertData for the specified owner and with the specified expiration date, an IOException was thrown when decoding bytes to IData.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1066E	Error selecting CertData for ownerId={0} and expDate={1}; SQLException encountered with the error message {2}.
Explanation	An SQLException occurred while Trading Networks was attempting to select CertData for the specified owner and with the specified expiration date.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1067E	Cannot construct new CertData from SecurityOps.getCertificateDataForPartnerAndUsage().
Explanation	Internal error
Action	Contact Software AG Global Support.
TNS.0006.1068E	Error selecting CertData for partnerId={0} with usage={1}; IOException encountered decoding bytes to IData.
Explanation	While Trading Networks was attempting to select CertData for the specified partner and with the specified certificate usage, an IOException was thrown when decoding bytes to IData.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1069E **Error selecting CertData for partnerId={0} with usage={1}; SQLException encountered with the error message {2}.**

Explanation An SQLException occurred while Trading Networks was attempting to select CertData for the specified partner and with the specified certificate usage.

Action If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1070E **Cannot get profile store or profile summary list, so Trading Networks cannot migrate certificates.**

Explanation An exception was thrown while retrieving profile data.

Action If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1071W **Cannot get partner's ({0}) profile data; skip migrating this partner's certificate set.**

Explanation Trading Networks was not able to find profile data for the partner with the specified partner ID. As a result, Trading Networks cannot migrate this partners certificate set.

Action Contact Software AG Global Support.

TNS.0006.1074E **Error loading partner's ({0}) certificate; skip migrating this partner's certificate set.**

Explanation An exception occurred while loading certificate data for the partner with the specified partner ID. As a result, Trading Networks cannot migrate this partner's certificate set.

Action If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1075E **Cannot migrate partner's ({0}) certificate set because the certificate is null.**

Explanation While Trading Networks was attempting to migrate the specified partner's certificate set, it encountered a null certificate. As a result, Trading Networks cannot migrate the certificate set.

Action Supply a valid, non-null certificate.

TNS.0006.1077E **Error loading partner's ({0}) CACertificate; skip migrating this partner's certificate set.**

Explanation An exception was thrown while loading certificate data for the partner with the specified partner ID. As a result, Trading Networks cannot migrate this partner's certificate set.

Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1078E	Cannot migrate partner's ({0}) certificate set because a CA certificate is null.
Explanation	While Trading Networks was attempting to migrate the specified partner's certificate set, it encountered a null CA certificate. As a result, Trading Networks cannot migrate the certificate set.
Action	Supply a valid CA certificate.
TNS.0006.1079E	Error loading partner's ({0}) private key; skip migrating this partner's certificate set.
Explanation	An exception occurred while loading the private key for the partner with the specified partner ID. As a result, Trading Networks cannot migrate this partner's certificate set.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1080E	Cannot migrate partner's ({0}) certificate set because the private key is null.
Explanation	The private key is null. When Trading Networks was attempting to migrate the specified partner's certificate set, it encountered a null private key. As a result, Trading Networks cannot migrate the certificate set.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1081E	Error adding partner's verify certificate to Trading Networks database (partner ID={0}, Integration Server user account={1}); skip migrating this partner's verify certificate set.
Explanation	An exception was thrown while attempting to add the verify certificate to the database. As a result, Trading Networks cannot migrate this partner's verify certificate set.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1082E	Found null node certificate for CertId={0} in migration.
Explanation	Trading Networks cannot migrate the certificate with the specified CertID because the node certificate is null.
Action	Supply a valid certificate.

TNS.0006.1083E	IOException encountered in migration, CertID={0}.
Explanation	IOException thrown when Trading Networks attempted to migrate the certificate with the specified CertID.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1084E	Error duplicating sign certificate data to SSL certificate data for owner={0}, partner={1}.
Explanation	Internal error
Action	Contact Software AG Global Support.
TNS.0006.1085E	Cannot migrate certificate information. Cannot get current Trading Networks version from database.
Explanation	Trading Networks cannot migrate certificate information because it cannot determine the Trading Networks version. The database information is not up-to-date or the database is not running.
Action	Ensure that the Trading Networks database is running. Use the JDBC Pools page on the Integration Server Administrator to ensure that the Integration Server can connect to the Trading Networks database.
TNS.0006.1087E	fromVersion is required to run wm.tn.admin.migrate:migrateCerts.
Explanation	The required fromVersion parameter was not supplied.
Action	Supply a valid fromVersion.
TNS.0006.1092E	SQLException encountered in wm.tn.admin.migrate:migrateCerts.
Explanation	An SQLException thrown was when executing the wm.tn.admin.migrate:migrateCerts service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1093E	Error encountered in wm.tn.admin.migrate:migrateCerts.
Explanation	Internal error.
Action	Contact Software AG Global Support.

TNS.0006.1094E	Error encountered invoking service {0}.
Explanation	An error occurred when invoking the specified service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1098E	Cannot get certificate for verification of sender={0}, receiver={1}.
Explanation	The certificates used to verify the Sender-Receiver partner pair are not available.
Action	Specify the certificates that you want to use for the partners in the Trading Networks profiles.
TNS.0006.1099E	Cannot get certificate for verification of sender={0}, receiver={1}, stack trace is {2}.
Explanation	Trading Networks could not retrieve the verify certificate for the specified sender and receiver.
Action	Ensure the verify certificate information is provided for specified sender and receiver.
TNS.0006.1101I	No chain for signer {0} ({1}).
Explanation	Required security data is missing.
Action	If your application code is creating or updating certificates, ensure that you supply all required certificate data to the services you are invoking. If you receive this error while using the Trading Networks Console, contact Software AG Global Support.
TNS.0006.1102E	Cannot find verification cert.
Explanation	Trading Networks could not retrieve a verify certificate.
Action	Contact Software AG Global Support.
TNS.0006.1103E	Cannot find verification cert for sender={0}, receiver={1}.
Explanation	Trading Networks could not retrieve the verify certificate for the specified sender and receiver.
Action	Ensure the verify certificate information is provided for specified sender and receiver.
TNS.0006.1104E	Error encountered verifying XML document.
Explanation	An error was thrown when verifying an XML document.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1109E	Error encountered signing XML document.
Explanation	An error was thrown while signing an XML document.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1110E	Signing certificate for sender={0} receiver={1} not valid.
Explanation	The signing certificate for the specified sender and receiver is not valid.
Action	Provide a valid signing certificate for the sender/receiver pair.
TNS.0006.1111E	Verify certificate for sender={0} receiver={1} not valid.
Explanation	The verify certificate for the specified sender and receiver is not valid.
Action	Provide a valid verify certificate for the sender/receiver pair.
TNS.0006.1115E	Error encountered invoking wm.tn.security:getDecryptCACertificates.
Explanation	An error was encountered while invoking the wm.tn.security:getDecryptCACertificates service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1116E	Error encountered invoking wm.tn.security:getDecryptCertificate.
Explanation	An error was encountered while invoking the wm.tn.security:getDecryptCertificate service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1117E	Error encountered invoking wm.tn.security:getDecryptKey.
Explanation	An error was encountered while invoking the wm.tn.security:getDecryptKey service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1118E	Error encountered invoking <code>wm.tn.security:getEncryptCACertificates</code>.
Explanation	An error was encountered while invoking the <code>wm.tn.security:getEncryptCACertificates</code> service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1119E	Error encountered invoking <code>wm.tn.security:getEncryptCertificate</code>.
Explanation	An error was encountered while invoking the <code>wm.tn.security:getEncryptCertificate</code> service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1120E	Error encountered invoking <code>wm.tn.security:getEncryptKey</code>.
Explanation	An error was encountered while invoking the <code>wm.tn.security:getEncryptKey</code> service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1121E	Error encountered invoking <code>wm.tn.security:getSecurity</code>.
Explanation	An error was encountered while invoking the <code>wm.tn.security:getSecurity</code> service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1122E	Error encountered invoking <code>wm.tn.security:getSignCACertificates</code>.
Explanation	An error was encountered while invoking the <code>wm.tn.security:getSignCACertificates</code> service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1123E	Error encountered invoking <code>wm.tn.security:getSignCertificate</code>.
Explanation	An error was encountered while invoking the <code>wm.tn.security:getSignCertificate</code> service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1124E	Error encountered invoking <code>wm.tn.security:getSignKey</code>.
Explanation	An error was encountered while invoking the <code>wm.tn.security:getSignKey</code> service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1125E	Error encountered invoking <code>wm.tn.security:getVerifyCACertificates</code>.
Explanation	An error was encountered while invoking the <code>wm.tn.security:getVerifyCACertificates</code> service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1126E	Error encountered invoking <code>wm.tn.security:getVerifyCertificate</code>.
Explanation	An error was encountered while invoking the <code>wm.tn.security:getVerifyCertificate</code> service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1132E	Error encountered invoking <code>wm.tn.security:setDecryptCertificateSet</code>.
Explanation	An error was encountered while invoking the <code>wm.tn.security:setDecryptCertificateSet</code> service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1133E	<code>cert is null; however, CACerts is not null.</code>
Explanation	You provided information in <code>CACerts</code> to specify CA certificates; however, you did not specify a certificate for the <code>cert</code> variable.
Action	Provide a valid certificate for the <code>cert</code> variable.
TNS.0006.1134E	<code>CACerts is required when the certificate is not self-signed.</code>
Explanation	You did not specify CA certificates for the <code>CACerts</code> variable. CA certificates are required unless the certificate you specify is self-signed.
Action	Provide valid CA certificates for the <code>CACerts</code> variable.

TNS.0006.1137E	Error encountered invoking <code>wm.tn.security:setEncryptCertificateSet</code>.
Explanation	An error was encountered while invoking the <code>wm.tn.security:setEncryptCertificateSet</code> service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1151E	Error encountered invoking <code>wm.tn.security:setSecurity</code>.
Explanation	An error was encountered while invoking the <code>wm.tn.security:setSecurity</code> service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1152E	<code>privateKey</code> and <code>cert</code> should be both null or neither null.
Explanation	You specified a value for either <code>privateKey</code> or <code>cert</code> , but not for both. The values for <code>privateKey</code> and <code>cert</code> must either both be null or both have non-null values.
Action	Provide valid values for <code>privateKey</code> and <code>cert</code> .
TNS.0006.1153W	<code>CACerts</code> is required for non self signed certificates.
Explanation	A value for <code>CACerts</code> must be specified for non self-signed certificates.
Action	Provide valid value for <code>CACerts</code> .
TNS.0006.1156E	Error encountered invoking <code>wm.tn.security:setSignCertificateSet</code>.
Explanation	An error was encountered while invoking the <code>wm.tn.security:setSignCertificateSet</code> service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1159E	Error encountered invoking <code>wm.tn.security:setVerifyCertificateSet</code>.
Explanation	An error was encountered while invoking the <code>wm.tn.security:setVerifyCertificateSet</code> service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1164E	Error encountered invoking wm.tn.security:updateCertificate.
Explanation	An error was encountered while invoking the wm.tn.security:updateCertificate service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1165E	Error encountered in wm.tn.security:addCertificateData.
Explanation	An error was encountered while executing the wm.tn.security:addCertificateData service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1166E	Cannot get existing Certificate Data from supplied certID={0}.
Explanation	Cannot get existing certificate data for the certificate information with certID=<certID>. The supplied certID might be invalid.
Action	Ensure that the value for certID is valid.
TNS.0006.1167E	Cannot get existing CertID from supplied ownerID={0} partnerID={1} and usage={2}.
Explanation	Cannot get existing CertID for certificate data that is associated with ownerID=<ownerID> partnerID=<partnerID> and usage=<certificateUage>.
Action	Ensure that the values for ownerID, partnerID, and usage are valid.
TNS.0006.1168E	Cannot construct new CertData in wm.tn.security:updateCertificateData.
Explanation	Internal error.
Action	Contact Software AG Global Support.
TNS.0006.1169E	Error encountered in wm.tn.security:updateCertificateData.
Explanation	An error was encountered while executing the wm.tn.security:updateCertificateData service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1170E	Cannot delete non-existing CertData for ownerID={0}, partnerID={1} and usage={2}.
Explanation	Trading Networks could not locate certificate data for the specified ownerID, partnerID, or usage.
Action	Ensure the values for ownerID, partnerID, and usage are valid.
TNS.0006.1171E	Error encountered in wm.tn.security:deleteCertificateData.
Explanation	An error was encountered while executing the wm.tn.security:deleteCertificateData service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1172E	Error encountered in wm.tn.security:getCertificateData.
Explanation	An error was encountered while executing the wm.tn.security:getCertificateData service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1175E	Error encountered in wm.tn.security:getSigningKeyAndChain.
Explanation	An error was encountered while executing the wm.tn.security:getSigningKeyAndChain service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1176E	Error encountered in wm.tn.security:getVerifyingChain.
Explanation	An error was encountered while executing the wm.tn.security:getVerifyingChain service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1178E	Error encountered in wm.tn.security:getDecryptionKeyAndCert.
Explanation	An error was encountered while executing the wm.tn.security:getDecryptionKeyAndCert service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1179E	Error encountered in wm.tn.security:getEncryptionChain.
Explanation	An error was encountered while executing the wm.tn.security:getEncryptionChain service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1182E	{0} private key not defined.
Explanation	The private key for the SSL client certificate set was not defined.
Action	Provide a valid SSL private key for the SSL client certificate set.
TNS.0006.1183E	{0} certificate chain not defined.
Explanation	The certificate chain for the SSL client certificate set was not defined.
Action	Provide a valid SSL certificate chain for the SSL client certificate set.
TNS.0006.1184E	Error encountered in wm.tn.security:getSSLKeyAndChain.
Explanation	Error encountered when executing the wm.tn.security:getSSLKeyAndChain service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.
TNS.0006.1185E	No SSL key and cert defined.
Explanation	The SSL private key and certificate are not defined.
Action	Provide a valid SSL private key and certificates.
TNS.0006.1187E	Error encountered in wm.tn.security:setSSLKeyAndChain.
Explanation	An error was encountered while executing the wm.tn.security:setSSLKeyAndChain service.
Action	If Integration Server logging is configured at logging level 4 or higher, a stack trace was written to the server log. See the server log for details. Take the appropriate action to resolve the problem.

TNS.0006.1190E	Certificate chain bytes cannot be null or zero length.
Explanation	The certificate chainBytes value is either null or a zero length. The certificate chain must contain data.
Action	Provide valid certificate chain byte array.
TNS.0006.1191E	Invalid RSA Private Key file.
Explanation	The RSA private key file is not valid.
Action	Provide a valid RSA private key file.
TNS.0006.1192E	Cannot construct new CertData.
Explanation	Internal Error.
Action	Contact Software AG Global Support.
TNS.0006.1193E	Bad private key for usage {0}: {1}
Explanation	The private key that was provide is not valid.
Action	Provide a valid private key.
TNS.0006.1194	Unable to import security data for owner {0} because the owner is not defined in your Trading Networks system.
Explanation	In webMethods Trading Networks, it is not possible to import the security data for the owner as the owner is not defined.
Action	Define the owner in webMethods Trading Networks and try again.
TNS.0006.1196	Unable to import security data of owner {0} for partner {1} because the partner {1} is not defined in your Trading Networks system.
Explanation	In webMethods Trading Networks, if the partner is not defined as the owner of the certificate, the security data cannot be imported.
Action	Ensure that the partner is the owner of the certificate and try again.
TNS.0006.1198	Error encountered while viewing certificate data for partnerID={0}. The error is {1}
Explanation	In webMethods Trading Networks, an error is encountered while viewing certicate data for the partner.
Action	Contact your system administrator.

TNS.0006.1199 **Error encountered in wm.tn.security:updateCertificateData for partnerID={0}. The error is {1}**

Explanation In webMethods Trading Networks, an error is encountered while updating a certificate.

Action Contact your system administrator.

TNS.0006.1200 **Error encountered while validating chain The error is {0}**

Explanation In webMethods Trading Networks, an error is encountered when the certificate details that are entered is not correct.

Action Ensure to define the certificate details correctly and try again.

TNS.0006.1201 **Unable to import security data for partner {0} because this partner is not defined in your Trading Networks system.**

Explanation webMethods Trading Networks is unable to import security data for the partner because this partner is not defined in your webMethods Trading Networks system.

Action Define the partner in your webMethods Trading Networks system and try again.

TNS.0007.1001E **{0} is required.**

Explanation A value was not supplied for the specified variable.

Action Supply the required value.

TNS.0007.1002E **wm.tnweb.wrapper:xmlEncode: could not encode IData to binary**

Explanation An exception was thrown while encoding an IData.

Action Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1003E **wm.tnweb.wrapper:xmlDecode: could not decode binary to IData**

Explanation An exception was thrown while decoding an IData.

Action Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1004E **wm.tnweb.wrapper:xmlDecode2: could not decode binary to Values**

Explanation An exception was thrown while decoding an IData.

Action Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1005E	wm.tnweb.wrapper:removeNullAlerts: error caught in removing null alerts
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1006E	wm.tnweb.wrapper:compareRights: error caught in comparing rights
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1007E	wm.tnweb.wrapper:getTNRights: error caught in getting Trading Networks partner ACL privilege
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1008E	wm.tnweb.wrapper:getUserGroups: error caught in getting Trading Networks partner ACL group memberships
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1009E	wm.tnweb.wrapper:getUserInfo: error caught in getting Trading Networks partner IS login name
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1010E	wm.tnweb.wrapper:getHashKeys: error caught in getting Hashtable keys
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1011E	{0} cannot be null
Explanation	A value was not supplied for the specified variable.
Action	Supply the required value.

TNS.0007.1012E	wm.tnweb.wrapper:IntegerToStrng: error caught converting Integer datatype to String datatype
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1013E	wm.tnweb.wrapper:ShortToStrng: error caught converting Short datatype to String datatype
Explanation	Trading Networks encountered an internal error
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1014E	wm.tnweb.wrapper:isBIEnabled: error caught in retrieving enabled Integration Server packages
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1015E	wm.tnweb.wrapper:isBIEnabled: could not find if Business Integrator (ProcessMonitor) package is installed and enabled
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1016E	wm.tnweb.wrapper:getStringFromBundle: could not get String from resource bundle wm.tnweb.wrapper_bundle for key = {0}
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1017E	wm.tnweb.querySvc:getQuery: could not get pre-saved query ({0}) for partnerID={1}.
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1018E	{0} cannot be null or empty
Explanation	A value was not supplied for the specified variable.
Action	Supply the required value.

TNS.0007.1019E	partnerID is null or empty in invoking wm.tnweb.querySvc:getSavedQueries
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1020E	wm.tnweb.querySvc:getSavedQueries: could not get pre-saved queries for partnerID={0}
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1021E	wm.tnweb.querySvc:getDocuments: could not get documents
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1022E	wm.tnweb.querySvc:createTaskQuery: could not create task query for document id={0}
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1023E	wm.tnweb.querySvc:getCalendar: invalid input {0}
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1024E	wm.tnweb.querySvc:getCalendar: could not get calender for year={0}, month={1}
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1025E	wm.tnweb.querySvc:getQueryRestriction: could not get document query restriction for document id = {0}
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1026E	Could not get profile store
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1027E	Could not get document attributes for id = {0}
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1028E	Could not get internal document type id for name = {0}
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1029E	wm.tnweb.configSvc:checkDefaultConfigLoaded: could not check if default config is loaded
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1030E	wm.tnweb.configSvc:getHashes: could not construct Hashtables for TNAdministrators and TNPartners
Explanation	Internal error Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1035E	wm.tnweb.configSvc:getUserConfig: could not get membership info for user {0}.
Explanation	The user account for the specified user does not exist in the Integration Server.
Action	If you have deleted the user account for this user, use the Integration Server Administrator to create the user account again. If this is for an external user, ensure that the user account is a member of the TNPartners group.
TNS.0007.1039E	wm.tnweb.configSvc:getUserConfig: could not get partner specific config for {0}
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1040E	wm.tnweb.configSvc:getGroupConfig: could not get group specific config for {0}
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1041E	wm.tnweb.configSvc:getTNPartners: could not get partner information
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1042E	wm.tnweb.configSvc:getTNGroups: could not get IS group information
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1043E	wm.tnweb.configSvc:getTNUsers: could not get Trading Networks IS user information
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1044E	wm.tnweb.configSvc:getUserConfigDisplay: could not get specific user config information
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1045E	wm.tnweb.configSvc:getAvailableStatus: could not get user status from database
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1047E	wm.tnweb.configSvc:saveCustomPages: error encountered in saving new custom pages setting
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1048E	wm.tnweb.configSvc:addToHashes: invalid type value
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1049E	wm.tnweb.configSvc:addToHashes: could not add new config IData to hashtable
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1050E	wm.tnweb.configSvc:changeConfig: could not change config setting
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1051E	wm.tnweb.querySvc:getQueryRestriction: do not have privilege to check query restriction
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1053E	wm.tnweb.wrapper:logBrowserLocale: error encountered in getting browser locale
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1054E	cert is null
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1055E	CACerts is null
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1056E	CACerts[{}] is null
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1057E	privateKey is null
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1058E	Can not get user specific configuration: no such user {0}
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1059E	Error encountered calling wm.tnweb.configSvc:checkAndUpdateConfig
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1061E	Error updating/retrieving configuration info from repo
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1062E	Error encountered in invoking service wm.tnweb.querySvc:getPartnerNameAndID
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1063E	Can not get valid profile summary list: list is null or empty
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1064E	Error encountered in invoking service wm.tnweb.querySvc:runTaskQuery
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1065E	Error encountered in invoking service wm.tnweb.querySvc:taskQueryById
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.

TNS.0007.1066E	Error encountered in invoking service wm.tnweb.querySvc:getDocDetails
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1067E	Got null bizdoc, docId = {0}
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1068E	Got null or 0-length bizdoc content parts, docId = {0}
Explanation	The contents of this document might not have been saved to the Trading Networks database.
Action	Check the corresponding TN document type and processing rule to determine whether Trading Networks has saved the document contents to the database.
TNS.0007.1069E	Invalid startIndex = {0}
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1070E	Can not convert content bytes to String: unsupported encoding
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1071E	NOTE: No privilege to view contents of this document
Explanation	You attempted to view a document of which you are neither the sender nor the receiver.
Action	You can only view a document that you have sent or received.
TNS.0007.1072E	NOTE: No more data to display
Explanation	Either the document has no content or the startIndex is beyond the end of the content.
Action	If you determine that this is an error, gather error information and contact webMethods Customer Care.

TNS.0007.1073E	Got null bizdoc content part, docId={0}, content part name={2}
Explanation	The content of this document might not have been saved to the Trading Networks database.
Action	Check the corresponding TN document type and processing rule to determine whether Trading Networks saved the document content to the database.
TNS.0007.1074E	Error encountered in invoking service <code>wm.tnweb.wrapper:getTNInfo</code>
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1075E	Error encountered in invoking service <code>wm.tnweb.wrapper:registerTNOIntegrationServer</code>
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1076E	Error encountered parsing date {0} or {1}.
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TNS.0007.1077E	Error encountered in invoking service <code>wm.tnweb.wrapper:installTNWebACLs</code>
Explanation	Trading Networks encountered an internal error.
Action	Gather error information from the logs and contact Software AG Global Support.
TRNSERV.000018.000001 – new String[]{"{0} is required", "Please supply the required value", "0"}	
Explanation	A value for the specified input field is not supplied.
Action	Supply a valid value for the specified input field.
TRNSERV.000018.000018 – new String[]{"{0} cannot be null or empty", "", "0"}	
Explanation	The specified input field does not contain a value. A value for this input field is required.
Action	Supply a valid value for the specified input field.

TRNSERV.000018.000025 – new String[]{"wm.tnweb.querySvc:getQueryRestriction: could not get document query restriction for document id = {0}","","0"}

Explanation An error occurred while fetching a document query restriction for specified document.
Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TRNSERV.000018.000051 – new String[]{"wm.tnweb.querySvc:getQueryRestriction: do not have privilege to check query restriction","","0"}

Explanation You are not allowed to check the query restriction.
Action Contact your administrator.

TRNSERV.000018.000066 – new String[]{"Error encountered in invoking service wm.tnweb.querySvc:getDocDetails","","0"}

Explanation An error occurred while retrieving content part bytes.
Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TRNSERV.000018.000067 – new String[]{"Got null bizdoc, docId = {0}","","0"}

Explanation While checking the query restriction, a null bizdoc was found for the specified docID.
Action Supply a valid docId.

TRNSERV.000024.000204 – new String[]{"Error attempting to parse message contents","","0"}

Explanation A MessagingException error occurred while parsing the MIME message.
Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

TRNSERV.000024.000205 – new String[]{"Error attempting to read from message source","","0"}

Explanation An IOException error occurred while reading a MIME message from the message source.
Action The exception was written to the log. Take appropriate action to resolve the problem described in the exception.

bizDocDeletionError – You did not select an item to delete. Select at least one item to delete.

Explanation You did not select an item to delete.

Action Select at least one item to delete.

bizDocSelectionError – You did not select an item to archive. Select at least one item to archive.

Explanation You did not select an item to archive.

Action Select at least one item to archive.

cert.err An error occurred while validating the certificate chain. Take corrective action based on the error details.

Explanation An error occurred while validating the certificate chain.

Action Take corrective action based on the error details.

corp.name.required You did not supply a value for the required Corporation Name field. Provide a value for this field.

Explanation You did not supply a value for the required Corporation Name field.

Action Provide a value for this field.

date.is.required You did not specify a date. Specify a date to proceed.

Explanation You did not specify a date.

Action Specify a date to proceed.

default.connection.error.msg – Trading Networks Server is not configured, or it is not available.

Explanation Trading Networks server is not configured, or it is not available.

Action Contact the Administrator.

dlscheck.dialogMessage – You do not have permission to perform this action. Contact your system administrator for the required privileges.

Explanation You do not have permission to perform this action.

Action Contact your system administrator for the required privileges.

docTypeDetails_NameRequiredError – The document type name is a required field. Provide a document type name.

Explanation The document type name is required.

Action Provide a document type name.

docTypeSearch.fileInput.required.msg – No document was provided for testing. Provide the document.

Explanation No document was provided for testing.

Action Provide the document.

doctype.instantiation.error – The EDI document type could not be instantiated. Make sure that a valid schema standard is specified.

Explanation The EDI document type could not be instantiated.

Action Make sure that a valid schema standard is specified.

editor.detailsid.missing.error – Document Type ID is missing.

Explanation In webMethods Trading Networks, if the Document Type ID is missing, this error shows up.

Action Ensure to log out and log in again to webMethods Trading Networks.

empty.attribute.name.error – The Name field cannot be blank. Provide a valid value for this field.

Explanation The Name field cannot be blank.

Action Provide a valid value for this field.

error.InvalidDefaultValue – You specified a default value of %1\$. This value is not valid. Select a value from the list of valid values.

Explanation The specified default value is not valid.

Action Select a value from the list of valid values.

error.InvalidFieldId – Invalid Field Id Specified: %1\$.

Explanation In webMethods Trading Networks, if the Field Definition ID of the profile is null or invalid, this error shows up.

Action Contact your system administrator.

error.InvalidFieldLength – You specified a field length of %1\$s. This field length is not valid. Specify a positive integer value.

Explanation The specified field length is not valid.

Action Specify a positive integer value.

error.WmEDIPackageNotEnabled – The WmEDI package is not enabled on the Integration Server. Enable the package.

Explanation The WmEDI package is not enabled on the Integration Server.

Action Enable the package.

error.days.greaterthan.zero – You entered a value for Days that is not valid. Enter an integer value greater than zero.

Explanation You entered a value for Days that is not valid.

Action Enter an integer value greater than zero.

error.defValue.exceeds.maxLength – Default Value %1\$s exceeds specified Maximum Length %2\$s

Explanation In webMethods Trading Networks, if the default value of a field definition exceeds the maximum length permissible, this error throws up.

Action Enter a field definition with default value within the permissible maximum length, and try again.

error.delete The activity log(s) could not be deleted. Take corrective action based on the error details.

Explanation The activity log(s) could not be deleted.

Action Take corrective action based on the error details.

error.enter.valid.file.name – Enter a valid file name

Explanation The file name is empty or contains invalid characters such as ", /, \, *, or ?.

Action Specify a valid file name.

error.enter.valid.solution.name – Enter a valid solution name

Explanation The solution name is empty or contains invalid characters such as ", /, \, *, or ?.

Action Specify a valid solution name.

error.extract.file **The file you uploaded is not in a valid format. Provide an XML or a binary file containing valid asset data to import.**

Explanation The file you uploaded is not in a valid format.

Action Provide an XML or a binary file containing valid asset data to import.

error.getComment **An error occurred while retrieving comments from Trading Networks. Take corrective action based on the error details and trace.**

Explanation An error occurred while retrieving comments from Trading Networks.

Action Take corrective action based on the error details and trace.

error.getEDIINTProperties – My webMethods encountered an error while trying to retrieve WmEDIforTN package properties. Take corrective action based on the error details.

Explanation My webMethods Server encountered an error while trying to retrieve WmEDIforTN package properties.

Action Take corrective action based on the error details.

error.getEDIProperties – My webMethods Server encountered an error while trying to retrieve WmEDI package properties. Take corrective action based on the error details.

Explanation My webMethods Server encountered an error while trying to retrieve WmEDI package properties.

Action Take corrective action based on the error details.

error.getTNProperties – My webMethods Server encountered an error while trying to retrieve Trading Networks properties. Make sure the WmTN package is properly installed and loaded.

Explanation My webMethods Server encountered an error while trying to retrieve Trading Networks properties.

Action Make sure the WmTN package is properly installed and loaded.

error.message **Download action failed.**

Explanation An exception occurred while downloading the file.

Action Check the server connection. Contact the system administrator to check your security and locale settings.

error.message.edi.not.installed – This feature requires the WmEDI and WmEDIforTN packages. These packages are either not loaded or are disabled. Enable these packages.

Explanation This feature requires the WmEDI and WmEDIforTN packages. These packages are either not loaded or are disabled.

Action Enable these packages.

error.name.already.exists – The name you have chosen for this field, %1\$s, already exists. Enter a different name.

Explanation The name you have chosen for this field already exists.

Action Enter a different name.

error.noserver **My WebMethods Server could not reassign the task(s) because no target was specified. Specify the target server.**

Explanation My webMethods Server could not reassign the task(s) because no target was specified.

Action Specify the target server.

error.reassign **My WebMethods Server encountered an error while reassigning the task(s). Take corrective action based on the error details.**

Explanation My webMethods Server encountered an error while reassigning the task(s).

Action Take corrective action based on the error details.

error.restart **My WebMethods Server encountered an error while restarting the task(s). Take corrective action based on the error details.**

Explanation My webMethods Server encountered an error while restarting the task(s).

Action Take corrective action based on the error details.

error.saveEDIFormatSettings – My webMethods encountered an error while trying to update EDI Module format settings. Take corrective action based on the error details.

Explanation My webMethods Server encountered an error while trying to update EDI Module format settings.

Action Take corrective action based on the error details.

error.saveEDIINTProperties – My webMethods encountered an error while trying to update EDI Module configuration properties. Take corrective action based on the error details.

Explanation My webMethods Server encountered an error while trying to update EDI Module configuration properties.

Action Take corrective action based on the error details.

error.saveEDIProperties – My webMethods encountered an error while trying to save EDI Module configuration properties. Take corrective action based on the error details.

Explanation My webMethods Server encountered an error while trying to save EDI Module configuration properties.

Action Take corrective action based on the error details.

error.saveTNProperties – My webMethods Server encountered an error while trying to save Trading Networks properties. Make sure the WmTN package is properly installed and loaded.

Explanation My webMethods Server encountered an error while trying to save Trading Networks properties.

Action Make sure the WmTN package is properly installed and loaded.

error.setComment An error occurred while setting comments from Trading Networks. Take corrective action based on the error details and trace.

Explanation An error occurred while setting comments from Trading Networks.

Action Take corrective action based on the error details and trace.

error.stop My WebMethods Server encountered an error while stopping the task(s). Take corrective action based on the error details.

Explanation My webMethods Server encountered an error while stopping the task(s).

Action Take corrective action based on the error details.

error.submitDocument – An error occurred while submitting the document to Trading Networks. Check the file path and resubmit the document.

Explanation An error occurred while submitting the document to Trading Networks.

Action Check the file path and resubmit the document.

g11n.wm_tn_bam_attributes.default.optimize_not_installed – Optimize is not installed. Install webMethods Optimize.

Explanation Optimize is not installed.
Action Install webMethods Optimize.

g11n.wm_tn_bam_doctypes.default.optimize_not_installed – Optimize is not installed. Install webMethods Optimize.

Explanation Optimize is not installed.
Action Install webMethods Optimize.

g11n.wm_tn_dls_viewDataSet.default.at_least_one_permission – Permissions have not yet been granted to this role. Grant at least one permission to this role on the Permissions tab.

Explanation Permissions have not yet been granted to this role.
Action On the Permissions tab, grant at least one permission to this role.

g11n.wm_tn_pf_profile.users.invalid_user_name – You did not specify a user name. Provide a valid user name.

Explanation You did not specify a user name.
Action Provide a valid user name.

g11n.wm_tn_pf_profile.users.no_password – The password is missing. Provide and confirm the password.

Explanation The password is missing.
Action Provide and confirm the password.

g11n.wm_tn_pf_profile.users.passwords_do_not_match – The values for Password and Confirm Password do not match. Enter the same values for these fields.

Explanation The values for Password and Confirm Password do not match.
Action Enter the same values for these fields.

g11n.wm_tn_pf_profile.users.user_already_exists_please – The specified user name already exists. Provide a unique user name.

Explanation The specified user name already exists.
Action Provide a unique user name.

g11n.wm_tn_pf_profile.users.user_name_invalid – The user name provided is not valid because it contains special characters. Specify a user name that contains only alphanumeric characters.

Explanation The user name provided is not valid because it contains special characters.

Action Specify a user name that contains only alphanumeric characters.

id.generate.error Can not generate EDI document type ID. Try again.

Explanation Cannot generate EDI document type ID.

Action Try again.

invalid.integer.value.detail – The value you provided for the Control Number Minimum is not an integer. For the VDA standard, enter an integer value greater than or equal to 0. For other standards, enter an integer value greater than or equal to 1.

Explanation The value you provided for the Control Number Minimum is not an integer.

Action For the VDA standard, enter an integer value greater than or equal to 0. For other standards, enter an integer value greater than or equal to 1.

invalid.message.minimum.value – The value you provided for the Control Number Minimum is not valid. For the VDA standard, enter a value greater than or equal to 0. For other standards, enter a value greater than or equal to 1.

Explanation The value you provided for the Control Number Minimum is not valid.

Action For the VDA standard, enter a value greater than or equal to 0. For other standards, enter a value greater than or equal to 1.

invalid.role You cannot add or remove privileges for Trading Networks or My webMethods administrators. Contact your system administrator.

Explanation Cannot add/remove privileges from TN Administrators or My webMethods Administrators. These roles have all privileges.

Action Contact your system administrator.

invalid.value.inputcontrol – The value you provided for the Control Number Minimum is not valid. Enter an integer value. For the VDA standard, enter a value greater than or equal to 0. For other standards, enter a value greater than or equal to 1.

Explanation The value you provided for the Control Number Minimum is not valid. Enter an integer value.

Action For the VDA standard, enter a value greater than or equal to 0. For other standards, enter a value greater than or equal to 1.

missing.required.extended – The required extended field {1} of group {0} is missing. Provide a value for this extended field.

Explanation The required extended field is missing.

Action Provide a value for this field.

msg.badDateRange The start date is later than the end date. Correct the start date so that it occurs before the end date.

Explanation The start date is later than the end date.

Action Correct the start date so that it occurs before the end date.

msg.badDynamicData You submitted dynamic query criteria that are incomplete. Provide all expected elements for the dynamic query.

Explanation The dynamic query criteria are incomplete.

Action Provide all expected elements for the dynamic query.

msg.errSave The content viewer page size is empty or is not valid. Enter an integer value greater than zero.

Explanation The content viewer page size is empty or is not valid.

Action Enter an integer value greater than zero.

msg.maxReprocessDocuments – You cannot reprocess more than {0} documents. To change this limit, contact your system administrator.

Explanation Reprocessing limit exceeded.

Action To change this limit, contact your system administrator.

msg.maxResubmitDocuments – You cannot resubmit more than {0} documents. To change this limit, contact your system administrator.

Explanation Resubmission limit exceeded.

Action To change this limit, contact your system administrator.

name.is.required You did not specify a queue name. Specify a queue name to proceed.

Explanation You did not specify a queue name.

Action Specify a queue name to proceed.

no.data.set My webMethods was unable to find the dataset for the specified ID. Log in to My webMethods again.

Explanation Unable to find the dataset for the specified ID.

Action Log in to My webMethods again.

no.return.url My webMethods could not navigate to the specified page because of a caching issue. Log in to My webMethods again.

Explanation My webMethods could not navigate to the specified page because of a caching issue.

Action Log in to My webMethods again.

no.root.vailable.error – The sample document used for creating the XML document type does not contain a Root tag. Provide a properly formatted document that contains a Root tag.

Explanation The sample document used for creating XML document type does not contain a Root tag.

Action Provide a properly formatted document that contains a Root tag.

not.valid.document You uploaded a sample document that is not valid. Provide a sample document with a valid root node.

Explanation You uploaded a sample document that is not valid.

Action Provide a sample document with a valid root node.

optionsTab.check.duplicate.doc.error.msg – You selected the "Check for Duplicate Document" option but did not specify a duplication service. Select a service.

Explanation You selected the "Check for Duplicate Document" option but did not specify a duplication service.

Action Select a service.

partnerid.missing.message – The partner ID is missing. Click here to go to the Partner Profiles page, and then specify a valid partner ID.

Explanation The partner ID is missing.

Action Click here to go to the Partner Profiles page, and then specify a valid partner ID.

problem.AccessException – You do not have permission to perform the requested action. Check with your system administrator.

Explanation You do not have permission to perform the requested action.

Action Request that your system administrator assign you the permission.

problem.ConnectException – My webMethods Server could not connect to the Trading Networks Server because that server is not available. Make sure the server is running on the specified host and port "{0}".

Explanation The specified Trading Networks server is not available.

Action Make sure the server is running on the specified host and port.

problem.UnknownHostException – My webMethods Server could not connect to the Trading Networks Server named "{0}" because that server is either not available or its host name is not recognized. Start the Trading Networks Server or specify a different server to connect to.

Explanation The specified Trading Networks server is not available.

Action Verify the host name of the Trading Networks Server.

problem.noSelection – You did not select any items to act on. Select one or more items and retry the action.

Explanation You did not select any items to act on.

Action Select one or more items and then retry the action.

proc.rules.detailsno.server.error – Trading Networks Server is not configured, or it is not available.

Explanation The configured Trading Networks instance may be down, or the system administrator may not have granted you permission to access the Trading Networks Server.

Action Make sure the server is running. If it is, contact the system administrator for permission to access the server.

profile.externalid.required – You did not specify an external ID for this profile. Provide the external ID.

Explanation You did not specify an external ID for this profile.

Action Provide an external ID.

query.not.found.error – You uploaded a sample document that does not contain a valid root node. Provide a sample document with a valid root node.

Explanation You uploaded a sample document that does not contain a valid root node.

Action Provide a sample document with a valid root node.

query.not.match **Your query does not match any of the nodes present in the sample document. Resubmit the query with a valid node.**

Explanation Your query does not match any of the nodes present in the sample document.

Action Resubmit the query with a valid node.

role.is.required **Permissions have not yet been granted to any roles. Grant permission(s) to at least one role on the Permissions tab.**

Explanation Permissions have not yet been granted to any roles.

Action On the Permissions tab, grant permission(s) to at least one role.

rule.name.is.required – **The dataset could not be created or updated because no dataset name was specified. Provide the dataset name.**

Explanation Dataset name not specified while creating or updating the dataset.

Action Enter the dataset name.

std.version.trans.not.sel.error – **You did not specify a standard, version, or transaction while creating the EDI document type. Select a standard, version, and transaction.**

Explanation You did not specify a standard, version, or transaction while creating the EDI document type.

Action Select a standard, version, and transaction.

tn.srvr.displayGroup – **Trading Networks**

tn.srvr.displayName – **Server**

tpa.details.agreementID.required.error – **Agreement ID cannot be empty.**

Explanation Agreement ID is empty.

Action Provide an Agreement ID.

tpa.details.controlnumber.notInteger – **Control Number must be an integer. Provide an integer value.**

Explanation Control Number must be an integer.

Action Provide an integer value.

tpa.details.profiles.required.error – Sender or Receiver fields cannot be empty.

Explanation Sender or Receiver field is empty.

Action Specify Sender and Receiver.

tree.load.error My webMethods encountered an error while loading the XML node tree. Click Upload to try loading the tree again.

Explanation My webMethods Server encountered an error while loading the XML node tree.

Action Click Upload to try loading the tree again.

updateFAStatus.errorMsg – Error in updating EDI FA status.

Explanation Error in updating EDI FA status.

Action Take corrective action according to the error details.

warn.noFileSelected – No document was chosen for submission. Specify the file path to the document to be submitted.

Explanation No document was chosen for submission.

Action Specify the file path to the document to be submitted.

28

Universal Messaging Messages

NUMSPME0001	Unexpected exception encountered.
Explanation	An unexpected exception occurred.
Action	Check the detailed error message. Contact Software AG Global Support for further assistance.
NUMSPME0002	An error occurred while identifying the inventory components of Universal Messaging.
Explanation	Unexpected exception occurred while identifying the inventory components of Universal Messaging.
Action	Please contact webMethods Administrator.
NUMSPME0003	An error occurred while retrieving the interfaces configured for Universal Messaging.
Explanation	Unable to read the adapters.nst file.
Action	Please contact webMethods Administrator.
NUMSPME0005	Invalid configuration instance. {0} entered.
Explanation	Format of the port configuration is wrong.
Action	Contact your webMethods product administrator and re-configure the port settings.

NUMSPME0006	Invalid configuration object. {0} expected.
Explanation	Format of the port configuration is wrong.
Action	Contact your webMethods product administrator and re-configure the port settings.
NUMSPME0007	Invalid input for the port alias.
Explanation	The input for the port alias is not valid.
Action	Input a valid port alias or keep the port alias field empty.
NUMSPME0008	SSL configuration cannot be set for a non-SSL port.
Explanation	SSL configuration can be set only for the SSL ports.
Action	Remove the SSL configuration from the non-SSL port and try again.
NUMSPME0009	The configuration instance ID argument is missing.
Explanation	The configuration instance ID is required to load the port configuration.
Action	Specify the configuration instance ID.
NUMSPME0010	No port matches the provided configuration instance ID.
Explanation	The provided configuration instance ID is incorrect.
Action	Verify the configuration instance ID provided for configuration update.
NUMSPME0011	Protocol entered for the interface is incorrect.
Explanation	The protocol can only be NSP, NHP, NSPS, or NHPS.
Action	Verify the protocol value entered for the port.
NUMSPME0012E	Unable to connect to the UM realm server.
Explanation	Unable to connect to the UM realm server. None of the interfaces can connect to the realm server.
Action	Verify if at least one interface is available for the realm server.
NUMSPME0013	At least one port must be specified.
Explanation	Port configuration is not specified in the port settings input.
Action	Add the port configuration to the port settings input.

NUMSPME0014	Error occurred while saving the port configurations.
Explanation	Unable to save the port configurations.
Action	See the detailed error message and verify the cause of failure.
NUMSPME0015	Only one set of port settings is allowed.
Explanation	More than one set of port settings are passed in the input.
Action	Configure only one set of port setting.
NUMSPME0016	Universal Messaging port number must not be changed.
Explanation	Attempted to change the Universal Messaging port number.
Action	Do not modify the port number.
NUMSPME0017	Universal Messaging Server port type must be STANDARD.
Explanation	Universal Messaging Server port type is not STANDARD.
Action	Set the Universal Messaging Server port type as STANDARD.
NUMSPME0018	Universal Messaging Server protocol must be NSP, NHP, NHPS, or NSPS.
Explanation	Universal Messaging Server protocol is not valid.
Action	Set NSP, NHP, NSPS, or NHPS as the Universal Messaging port protocol.
NUMSPME0019	Do not modify the BindAddress.
Explanation	Attempted to modify the BindAddress.
Action	Do not modify the BindAddress in the input.
NUMSPME0020	ExtendedProperties field is not supported by Universal Messaging.
Explanation	ExtendedProperties field is set.
Action	Do not set the ExtendedProperties field.
NUMSPME0021	IPAccess is not supported by Universal Messaging.
Explanation	IPAccess is set, but Universal Messaging does not support IPAccess.
Action	Do not set the IPAccess.

- NUMSPME0022** **KeepAliveTimeout is not supported by Universal Messaging.**
Explanation KeepAliveTimeout is set, but Universal Messaging does not support KeepAliveTimeout.
Action Do not set the KeepAliveTimeout.
- NUMSPME0023** **ThreadPool is not supported by Universal Messaging.**
Explanation ThreadPool is set, but Universal Messaging does not support ThreadPool.
Action Do not set the ThreadPool.
- NUMSPME0024** **URLAccess is not supported by Universal Messaging.**
Explanation URLAccess is set, but Universal Messaging does not support URLAccess.
Action Do not set the URLAccess.
- NUMSPME0025** **Keystore definition must not be null.**
Explanation Keystore definition for SSL in the port configuration input is set to Null.
Action Set a valid value for the keystore definition.
- NUMSPME0026** **Truststore definition must not be null.**
Explanation Truststore definition for SSL in the port configuration input is set to Null.
Action Set a valid value for the truststore definition.
- NUMSPME0027** **Cannot delete the primary port.**
Explanation Cannot delete the port to which Command Central is connected.
Action Do not delete the port to which Command Central is connected.
- NUMSPME0028** **Unexpected error occurred while fetching the monitoring data.**
Explanation An internal error occurred while fetching the monitoring data.
Action Contact Software AG Global Support for further assistance.
- NUMSPME0029** **The primary port cannot be stopped.**
Explanation The primary port of a ream server cannot be stopped.
Action Do not attempt to stop the primary port of a ream server.

NUMSPME0030	Keystore definition type can only be JKS.
Explanation	Keystore definition type can only be JKS.
Action	Specify JKS in the keystore type.
NUMSPME0031	Truststore definition type can only be JKS.
Explanation	Truststore definition type can only be JKS.
Action	Specify JKS for the Truststore type.
NUMSPME0032	Client Authentication cannot be set to REQUEST_CERTIFICATE.
Explanation	Only values supported for client authentication is REQUIRE_CERTIFICATE or NONE.
Action	Use either REQUIRE_CERTIFICATE or NONE.
NUMSPMW0004	Unable to connect to the Command Central interface of the Universal Messaging realm server.
Explanation	Interface factory could not connect to any interface.
Action	Please contact webMethods Administrator.

29

Web Services Stack Messages

WSSAPE0029	Failed to initialize argus configuration due to the following: {0}.
Explanation	An argus configuration file is invalid or unavailable, or a WS_STACK_HOME variable is not set.
Action	Make sure that the WS_STACK_HOME environment variable is properly set. Check the path to the argus configuration file and make sure that the argus configuration file is valid and not empty.
WSSAPE0030	Unknown user: {0}.
Explanation	The user cannot be authenticated because the supplied username is not correct.
Action	Provide a valid username.
WSSAPE0031	Unknown password callback type: {0}
Explanation	Only UsernameToken authentication is supported. You use a different authentication mechanism.
Action	Provide a valid username and password.
WSSAPE0032	An argus username is not configured in the argus agents properties file.
Explanation	The entries in argus agents properties file must be initialized. The "wsstack.adminservice.user" property does not contain a valid value.
Action	Provide a valid, non-empty value for "wsstack.adminservice.user" property in the argus agents properties file.

WSSARE0000	Login failed.
Explanation	Authentication fails. Invalid or empty credentials provided.
Action	Provide valid, non-empty username and password.
WSSARE0001	The following Web service archive does not comply with the naming standards: {0}. The archive is not deployed.
Explanation	The artifact name and extension contain invalid characters or do not comply with the correct name format.
Action	Edit the current artifact to conform to the AAR standards. Rename the archive using a valid name. The '.aar' extension cannot contain capital letters.
WSSARE0030	A problem occurred while executing a Web service. The Web service name is "{0}" with request payload "{1}".
Explanation	There is a problem while executing the Web service.
Action	Make sure that the requested Web service is operational.
WSSARI0027	Version information.
Explanation	A version information label.
Action	None.
WSSASE0000	Cannot find library jar file "{0}"
Explanation	The message appears when Web Services Stack administration service is trying to locate the axis2-kernel jar but the file does not exist or its location cannot be determined.
Action	Assert that the reported file exists and it is not locked by another process on the system.
WSSASE0009	Cannot find library directory "{0}"
Explanation	The message appears when Web Services stack administration service is trying to locate the library directory with the jar files used by the Web Services Stack runtime.
Action	Assert that the reported path exists and it is a valid directory.
WSSCLE0001	Deployment configuration file cannot be null.
Explanation	A valid deployment configuration file was not specified or an empty value for deployment configuration file was provided.
Action	Specify a valid deployment configuration file.

WSSCLE0002	[[0]] object cannot be null.
Explanation	Deployment configurator is not initialized correctly and returns null.
Action	You must initialize the deployment configurator with a valid, non-empty deployment configuration file or valid deployment configuration properties.
WSSCLE0003	The specified transport protocol [[0]] is not supported.
Explanation	The transport protocol defined in the DeploymentConfigurator is not supported.
Action	Set HTTP or HTTPS transport in the DeploymentConfigurator.
WSSCLE0004	Deployment configuration properties object cannot be null.
Explanation	Valid deployment configuration properties are not specified or empty values for deployment configuration properties are provided.
Action	Specify valid, non-empty deployment configuration properties.
WSSCLE0005	Problems while loading the deployment configuration from the file with the following location path: [[0]].
Explanation	Deployment configuration cannot be loaded from the specified file.
Action	Check whether the provided configuration file is valid and whether its location path is correct.
WSSCLE0006	"Servlet context" configuration is not found. The needed "servlet context" configuration is not set into the deployment configuration file.
Explanation	The deployment configuration property that specifies the servlet context is not set into the deployment configuration file.
Action	Set the servlet deployment configuration property into the deployment configuration file.
WSSCLE0007	"Host name" configuration is not found. The needed "host name" configuration is not set into the deployment configuration file.
Explanation	The deployment configuration property hostname is not set into the deployment configuration file or the given value cannot be resolved.
Action	Set a valid, non-empty value for the hostname property into the deployment configuration file.

WSSCLE0008 **Unknown "host name" configuration found. You can find the needed "host name" configuration into the deployment configuration file.**

Explanation The deployment configuration property hostname is set with a value that cannot be resolved.

Action Set a valid, non-empty value for the hostname property into the deployment configuration file.

WSSCLE0009 **Invalid "port number" configuration found. You can find the needed "port number" configuration into the deployment configuration file.**

Explanation In the deployment configuration property port is set an invalid value.

Action Set a valid port property into the deployment configuration file.

WSSCLE0010 **Service name [{0}] for undeployment is invalid.**

Explanation The Web service added for undeployment does not have a valid service name.

Action Add a valid service name for the Web service that you want to undeploy.

WSSCLE0011 **Archive data unit must not be "null".**

Explanation The archive file added for deployment is null or invalid.

Action Add a valid archive file for deployment.

WSSCLE0012 **Failed to parse the configured [{0}] with value [{1}]. The default value [{2}] will be used.**

Explanation The given value for maxConnectionsPerHost is invalid or cannot be processed. A default value will be used instead.

Action Set a valid positive integer for the value of maxConnectionsPerHost. Otherwise, an alternative default value will be used.

WSSCLE0013 **Failed to parse the configured [{0}] with value [{1}]. The default value [{2}] will be used.**

Explanation The given value for maxTotalConnections is invalid or cannot be processed. A default value will be used instead.

Action Set a valid positive integer for the value of maxTotalConnections. Otherwise, an alternative default value will be used.

WSSCLE0014	There are no archives added for deployment.
Explanation	Web service archives are not added for deployment or undeployment.
Action	Add Web service archives for deployment or undeployment.
WSSCLE0015	An error is thrown during the retrieval of the deployment result.
Explanation	Deployment result cannot be retrieved because of an error while executing the remote operation.
Action	Check the connection to the server and the error log.
WSSCLE0016	An error is thrown during the retrieval of the deployment result. The cause of the error is: {0}
Explanation	Deployment result cannot be retrieved because of an error while executing the remote operation.
Action	Check the connection to the server and the error log.
WSSCLE0017	The URI given for deployment is invalid. The passed value is [{0}].
Explanation	The given URI for deployment is empty or the given value cannot be parsed as a URI reference.
Action	Provide a valid, non-empty URI for deployment.
WSSCLE0018	The org.apache.commons.httpclient.HostConfiguration object passed is "null".
Explanation	The HostConfiguration is empty.
Action	Check that the properties set for the host have valid, non-empty values and check the connection.
WSSCLE0019	An error while deploying Web services occurs due to a problem while invoking the operation on the remote server . Reason: {0}.
Explanation	An error occurs during the deployment. The services cannot be deployed.
Action	Check the error log for details.
WSSCLE0020	An error while undeploying services occurs due to a problem while invoking the operation on the remote server. Reason: {0}.
Explanation	An error occurs during undeployment. The services cannot be undeployed.
Action	Check the error log for details.

WSSCLE0021	An error while listing the Web services occurs due to a problem while invoking the operation on the remote server. Reason: {0}.
Explanation	An error occurs while listing services.
Action	Check the error log for details.
WSSCLE0022	An error while listing properties occurs due to a problem while invoking the operation on the remote server. Reason: {0}.
Explanation	An error occurs while listing properties.
Action	Check the error log for details.
WSSCLE0023	The given keystore file {0} cannot be converted to a URL.
Explanation	The given value for the keystore file cannot be parsed.
Action	Provide a valid, non-empty value for the keystore file and check its location path.
WSSCLE0024	The given truststore file {0} cannot be converted to a URL.
Explanation	The given value for the truststore file cannot be parsed.
Action	Provide a valid, non-empty value for the truststore file and check its location path.
WSSCLE0025	The given proxy port with value [{0}] is invalid.
Explanation	The value provided for a proxy port is not in the correct format.
Action	Provide a valid proxy port. If you do not want to use a proxy port do not set a value to it.
WSSCLE0030	The WSDL definition cannot be null.
Explanation	You have not specified a WSDL definition.
Action	Specify a valid, non-empty WSDL definition.
WSSCLE0031	The WSDL URL cannot be null.
Explanation	You have not specified a WSDL URL or you have provided a null or empty value.
Action	Specify a valid, non-empty WSDL URL.

WSSCLE0032	The constructor is not found.
Explanation	You did not provide a valid constructor for the class.
Action	Check the parameters you used. One or more of them are not suitable for the class. Use one of the available constructors for instantiating the class.
WSSCLE0033	This action is not supported.
Explanation	You are trying to use functionality that is not yet implemented.
Action	This action is not supported. Contact Software AG Global Support.
WSSCLE0034	Service [{0}] is not found.
Explanation	The service with the specified name [{0}] is not available.
Action	Check the service name.
WSSCLE0035	Problem getting the WSDL, HTTP error code: {0}.
Explanation	The operation for getting the WSDL encounters a problem.
Action	Check the causes for the HTTP status error code.
WSSCLE0036	Cannot apply Web service client policy.
Explanation	Policy cannot be applied to the description hierarchy.
Action	Check and validate the configuration and the policy.
WSSCLE0037	Cannot locate the security configuration file "{0}" specified in the axis2 configuration under the key "securityConfigFile".
Explanation	The specified configuration security in the axis2 configuration file cannot be found. The properties cannot be loaded.
Action	If you want to load security properties from a custom security configuration file it must be placed in the proper place. The file is searched as defined in axis2 configuration under the key "securityConfigFile". Check the path and the file name.
WSSCLE0038	Cannot close security configuration file properly.
Explanation	An error occurs during close operation of the security configuration file.
Action	None.

WSSCLE0039	The WSDL file or WSDL definition cannot be found.
Explanation	In order to extract policies, either the WSDL location or the WSDL4J definition object must be valid. They are both missing or empty.
Action	Provide either a WSDL file or a valid WSDL definition.
WSSCLE0040	The class of the supplied callback must extend org.apache.axis2.client.async.Callback.
Explanation	The class of the supplied callback does not extend org.apache.axis2.client.async.Callback. It cannot be used.
Action	Provide a valid callback class.
WSSCLE0041	Failed to create a new client factory instance.
Explanation	Client factory instance cannot be created because the class cannot be found or instantiated.
Action	Check the configuration and the validity of the used constructor.
WSSCLE0042	Failed to create new client factory instance.
Explanation	The supplied factory class name argument does not resolve to a valid com.softwareag.wsstack.client.api.AbstractClientFactory implementation. Client factory instance cannot be created because the class name argument is not a com.softwareag.wsstack.client.api.AbstractClientFactory implementation.
Action	Give a fully qualified name of the factory implementation class that is going to be instantiated.
WSSCLE0043	Output stream cannot be null.
Explanation	The given output stream is not initialized or empty.
Action	Give a valid, non-empty output stream.
WSSCLE0044	Policy input stream cannot be null.
Explanation	The given policy input stream is not initialized or empty.
Action	Give a valid, non-empty policy input stream.

WSSCLE0045	Failed to close the WSDL input stream after reading.
Explanation	The close operation for the used WSDL input stream did not finish successfully.
Action	None.
WSSCLE0046	The provided content is too large to be buffered: {0} bytes.
Explanation	The content exceeds the maximum possible value that can be buffered.
Action	Contact Software AG Global Support.
WSSCLE0047	Cannot create DataObject for type {0}.
Explanation	The requested type {0} cannot be identified.
Action	The used data type is not supported. Use an alternative data type.
WSSCLE0048	Failed to create a wsstack client instance out of the following class: "{0}".
Explanation	A client instance cannot be created because the class cannot be found or instantiated.
Action	Check whether the name of the used class is correct.
WSSCLE0049	Failed to create a wsstack client instance. The class "{0}" is not a valid IWSBasicClient implementation.
Explanation	The defined class exists but its usage is incorrect. The class "{0}" cannot be used for instantiating a wsstack client because it is not a valid IWSBasicClient implementation.
Action	Define a valid implementation class.
WSSCLE0050	The services are not added for undeployment
Explanation	Web service archives are not added for undeployment.
Action	Add service archives for undeployment.
WSSCLE0051	The WS-Stack Java version is older than the Java version of the compiled archive "{0}".
Explanation	You compiled your archive with a newer Java version than the available in WS-Stack. The service cannot be deployed successfully.
Action	Compile the archive with an older Java version. You can check the supported Java version in the validation page of WS-Stack listed as java.version.

WSSCLE0052	There is a corrupted Java class file in the following archive: "{0}".
Explanation	One or more of the class files in the archive is corrupted or it is not a valid Java class file.
Action	Check the classes in your archive. Compile them with a supported Java version in WS-Stack and deploy the archive again.
WSSCLE0053	An error occurred while reading the archive "{0}"; the archive is corrupted or empty.
Explanation	The archive that you want to deploy is not valid. It may be empty or cannot be read.
Action	Check and validate the content of archive "{0}". You may need to repack the content and deploy it again.
WSSCLE0054	An error occurred while manipulating the archive "{0}". The archive is locked or another Input/Output related problem has occurred.
Explanation	Other processes locked the archive and it cannot be processed or an Input/Output related problem has interrupted the execution of the command.
Action	Deploy the archive again.
WSSCLE0056	Cannot configure client factory thread pool.
Explanation	The error occurs when the WSSStack client factory tries to configure a client instance to use a thread pool, and the client already has a thread pool set.
Action	Contact Software AG Global Support.
WSSCLE0057	The specified attachment lifecycle manager instance is not valid.
Explanation	The error occurs when the WSSStack client factory configures a client instance to use an attachment lifecycle manager set by the user, and the specified lifecycle manager property is not a valid instance of <code>org.apache.axiom.attachments.lifecycle.LifecycleManager</code> .
Action	Specify a valid instance of " <code>org.apache.axiom.attachments.lifecycle.LifecycleManager</code> " under the client factory property key " <code>attachmentsLifecycleManager</code> ".
WSSCLE0058	Cannot configure attachment lifecycle manager for a client instance.
Explanation	The error occurs when the Web Services Stack client factory configures a client instance to use a specific attachment lifecycle manager set by the user. Essentially, the error occurs when the attachment lifecycle parameter is locked.
Action	Contact Software AG Global Support.

WSSCLE0059	The supplier object (an instance of {0}) is not a proxy instance.
Explanation	The Web Services Stack client registry API provides a utility for retrieving the internal client configuration from a Web service proxy object. This error indicates that the tool is being used with a wrong proxy implementation (it is not a WSS compliant Web service client proxy).
Action	Modify your client implementation as the utility is used only with proxies created by the Web Services Stack registry API.
WSSCLI0000	Unable to locate the default security configuration file "{0}".
Explanation	The default security configuration file cannot be found and its properties are not loaded.
Action	If you want to load security properties from the default security configuration file, the file must be placed in the proper directory. The default security configuration file name is "wsclientsec.properties" and it must be either in the current working directory, or in "<REPOSITORY_DIRECTORY>/conf".
WSSCLI0026	An XMLStreamException thrown.
Explanation	The close operation for the used XMLStreamWriter did not finish successfully.
Action	None.
WSSCLW0027	Unable to locate the default security configuration file: "{0}".
Explanation	The default security configuration file cannot be found. Its properties are not loaded.
Action	If you want to load security properties from the default security configuration file you must put it in the proper place. The file is searched on the following location: "{0}".
WSSCLW0028	The service policy is not set; cannot write service policy to the given stream.
Explanation	The service policy is not set.
Action	To associate a policy, use one of the setPolicy methods first.
WSSCLW0029	Overwriting an existing policy.
Explanation	This is an existing policy and it is going to be overwritten.
Action	Do not use this method if you expect different behavior.

WSSCLW0055	The parameters for max connections settings passed to configure the connection manager, associated with the HttpClient, caused a problem.
Explanation	The default parameters will be used for the non-standard ones. \n MAX_HOST_CONNECTIONS parameter passed is "{0}". \n MAX_TOTAL_CONNECTIONS parameter passed is "{1}".
Action	None.
WSSCME0001	Key value cannot be null or empty
Explanation	The error appears when you prepare configuration properties parser of a security module. This implementation is used only in private constructors and therefore the error appears only if a severe implementation fault occurs.
Action	The error indicates a severe fault in the Web Services Stack implementation. If the error occurs, report it to the software development team.
WSSCME0002	Rampart configuration element value cannot be null or empty
Explanation	The message appears in an application program interface (API) method and reflects to an error in the implementation. The error appears when you update the security module configuration. It shows that you did not provide configuration to the update process.
Action	When you call a WSClientSecurityProperty#updateRampartConfigElement(OMEElement, String) the implementation ensures that the given OMEElement argument is not null or empty. Specify a valid entry for the OMEElement.
WSSCME0003	Invalid value is configured for time-to-live timestamp: "{0}"
Explanation	The configured time-to-live value for the timestamp used by the security module is invalid. The system expects an integer as a configuration value.
Action	Security module configuration for timestamp time-to-live must be an integer.
WSSCME0004	Invalid value is configured for max skew timestamp: "{0}"
Explanation	The configured max skew value for the timestamp used by the security module is invalid. The system expects an integer as a configuration value.
Action	Security module configuration for timestamp max skew must be an integer.

WSSCME0005	Property name cannot be null or empty
Explanation	You updated the security module configuration and did not specify a property for update.
Action	The error indicates a severe fault in the Web Services Stack implementation. If the error occurs, report it to the software development team.
WSSCME0009	Rampart configuration assertion update error
Explanation	The error occurs when xml serialization of an existing rampart configuration assertion fails. Prior to the update, the configuration assertion is serialized to stax stream and parsed with axiom. An invalid rampart configuration assertion can cause the error.
Action	If you configure the rampart configuration assertion manually, an invalid configuration can cause the error. Use the Web Services Stack configuration properties instead of providing manual configuration.
WSSCME0019	Failed to decode the basic authentication header.
Explanation	Web Services Stack security utility failed to decode the received HTTP Basic authentication header. The header should be encoded with base64 encoding. The error suggests that an illegal character (non-ASCII) was found within the header value.
Action	Make sure the http client sends an HTTP basic authentication header properly encoded in base64 encoding.
WSSCMI0000	Cannot recognize the security configuration key "{0}"; the key is ignored.
Explanation	Rampart configuration updater searches through the client options and dynamic service parameters for keys that refer to the security module configuration. The message is logged when it encounters an unrecognized key. For example, a general purpose key that does not control Rampart specific configuration.
Action	None.
WSSDIE0000	Invalid or unsupported service scope set to AxisService: {0}.
Explanation	The message appears when a service with an invalid scope is created or accessed. The following scopes are supported by Web Services Stack: application; transportsession; soapsession; request.
Action	Recreate your service using one of the following scopes: application; transportsession; soapsession; request.

WSSDIE0001	Cannot create valid policy manager factory implementation.
Explanation	The abstract policy manager factory fails to instantiate the default policy manager factory instance. The default factory implementation class is either not available or the user does not have permissions to access it.
Action	Ensure that the wsstack deployer-impl-[VERSION].jar is available on the classpath and the user who starts the java process has the proper permissions to access it.
WSSDIE0002	Cannot create valid policy repository factory implementation.
Explanation	The abstract policy repository factory fails to instantiate the default policy repository factory instance. The default factory implementation class is either not available or the user does not have permissions to access it.
Action	Ensure that the wsstack deployer-impl-[VERSION].jar is available on the classpath and that the user who starts the java process has the proper permissions to access it.
WSSDIE0003	Cannot close a policy stream after parsing it.
Explanation	Policy supplier cannot close the policy stream after parsing it.
Action	Ensure that the stream source is available and it is not locked by another process.
WSSDIE0004	Cannot initialize the local policy repository; the axis configuration is not available.
Explanation	Axis runtime configuration is not available to the policy repository. This means that the code is not executed in a properly initialized runtime.
Action	Ensure that you access the policy repository inside a properly initialized and started wsstack runtime.
WSSDIE0005	Cannot create an invalid policies directory; the policy repository is null.
Explanation	Invalid policies are automatically moved to a directory inside the policy repository. If the policy repository directory is not available, the invalid policies directory cannot be created.
Action	Ensure that the policy repository is properly initialized.
WSSDIE0006	Duplicate policy ID; the policy file is moved to {0}.
Explanation	The system detects that a policy is deployed with an ID that already exists in the policy repository. The new policy is moved to the invalid policies directory.
Action	When you deploy a policy, ensure that a policy with the same ID does not exist in the repository.

WSSDIE0007	Cannot verify module support for a policy with the following ID: {0}.
Explanation	The policy repository cannot verify whether a policy is supported (all assertions in it are recognized and there are modules deployed in the runtime that handle those assertions). The error occurs when the policy is invalid and/or does not contain any assertions.
Action	Ensure that the verified policy is valid and contains valid policy assertions.
WSSDIE0008	Policy with the following key: {0} exists in the repository.
Explanation	The policy repository contains a policy with the same ID as the policy that is deployed and the "updateIfPresent" flag is set to false.
Action	Ensure that the policy does not contain a policy with the same ID as the deployed one or set the flag "updateIfPresent" to true; that enables the update of the existing policy in the repository.
WSSDIE0009	An error occurred during policy deployment.
Explanation	An unexpected error occurs during policy deployment.
Action	Contact Software AG Global Support
WSSDIE0010	The given policy does not contain any policy alternatives.
Explanation	Cannot verify the policy against modules that support it because it does not contain any policy alternatives.
Action	Ensure that the deployed policy is valid and contains at least one policy alternative.
WSSDIE0011	Cannot find a module to process the following assertion: {0}
Explanation	There is no module deployed in the wsstack runtime that supports the given assertion.
Action	If the assertion requires additional processing by a specific module, ensure that the corresponding module is deployed on the wsstack runtime.
WSSDIE0012	The following module: {0}; cannot process the assertion: {1}.
Explanation	Although the module is registered to handle a certain policy assertion namespace, the module does not support the particular assertion.
Action	Ensure that the policy and all of its assertions are valid and can be processed by the module.

WSSDIE0013	Cannot find a policy with the specified ID: {0}.
Explanation	You are searching for a policy ID that is not available in the policy repository.
Action	Ensure that the policy you use is deployed to the policy repository.
WSSDIE0014	The policy XML does not contain an ID, or a name that can be associated with the ID.
Explanation	When a policy is deployed to the policy repository, the repository attempts to parse it and get its ID, or its name if an ID is not available. The ID or name afterward is used as a key for retrieving the policy from the repository. If there is no ID or a name in the policy XML, the repository cannot deploy it.
Action	Ensure that the policy XML that is deployed in the repository has either a valid (not empty) ID or a valid (not empty) name so that it can be deployed.
WSSDIE0015	Cannot find an element with the following name: {0} and the following namespace: {1} in the policy input stream; the policy document is invalid.
Explanation	When a policy is deployed to the policy repository, the repository attempts to parse it and get its ID, or its name if an ID is not available. The ID or name is used afterward as a key for retrieving the policy from the repository. If there is no ID or a name in the policy XML the repository cannot deploy it.
Action	Ensure that the policy XML includes a name or a wsu:Id attribute declared.
WSSDIE0016	An exception occurs while trying to parse the policy input stream.
Explanation	The policy repository fails to parse the policy XML stream.
Action	Assert that the deployed policy source is a valid XML.
WSSDIE0017	Cannot close policy file input stream.
Explanation	The policy repository cannot close policy stream after reading it.
Action	Ensure that the policy source is available.
WSSDIE0018	Cannot initialize local policy repository; the following repository path is incorrect: "{0}".
Explanation	When the policy repository is initialized it tries to create its directory or use the one that exists. This error occurs when the repository path exists on the file system but it is not a directory.
Action	Ensure that the repository path is a directory on the file system or does not exist (so that the policy repository can create it). Alternatively, you can configure another repository path if the configured one cannot be used.

WSSDIE0019	Cannot move the following invalid policy file: "{0}"; to the invalid policies directory.
Explanation	The policy repository detects that an invalid policy is deployed. The repository cannot move the invalid policy into the invalid policies directory.
Action	Ensure that you deploy a valid XML policy.
WSSDIE0020	Cannot load a policy file during policy repository initialization.
Explanation	The policy repository fails to deploy a problematic policy file.
Action	Ensure that the policy files in the policy repository are valid XML policies.
WSSDIE0021	Cannot initialize local policy repository; the following repository path: "{0}" does not exist and cannot be created.
Explanation	While the policy repository is initialized it checks whether the repository directory exists and if it does not, the repository attempts to create it. This message shows that the creation of the directory fails. The policy repository is not functional.
Action	Ensure that either the repository directory exists or the user who starts the java processes is authorized to create it.
WSSDIE0022	Cannot initialize a local policy repository; the following repository path is incorrect: "{0}".
Explanation	When the policy repository is initialized it tries to determine the repository directory path but it fails. The reason is that the code is not invoked inside an initialized wsstack runtime or the wsstack repository directory is not available (in case if a URL configurator is used, for example).
Action	Ensure that either the wsstack repository directory is available or configure a specific directory to be used as a policy repository directory.
WSSDIE0023	Cannot create a default policy supplier object; the following policy file: "{0}" is not a valid file.
Explanation	The file argument of the policy file that is deployed through a default policy supplier is either null or does not exist.
Action	When you deploy a file through the default policy supplier, ensure that the policy file exists on the file system at the time it is detected by the policy repository.
WSSDIE0024	The following policy file does not exist: "{0}".
Explanation	When a policy stream is retrieved through a default policy supplier instance, the policy file that is used by the supplier is not available.
Action	Ensure that the file with the policy you try to access is available in the policy repository.

WSSDIE0025	Policy repository location must not be null.
Explanation	Policy repository path is not available and therefore the default policy supplier cannot be created since it cannot store the policy in the repository.
Action	Ensure that the policy repository is properly initialized.
WSSDIE0026	Cannot copy a policy to the repository.
Explanation	When a policy stream is deployed through the default policy supplier, the supplier attempts to store the policy in repository directory. However, the copy procedure of the policy file to the repository directory fails.
Action	Ensure that the user who starts the java process is authorized to write to the policy repository directory. Another reason for the error is that the stream is closed before policy file is copied.
WSSDIE0027	An error occurred during policy deployment while trying to close the file output stream.
Explanation	A policy stream is deployed in the policy repository through a default policy supplier instance. While storing the stream to the policy repository directory, the supplier fails to close the original stream. However, the policy XML is successfully stored in the repository and the policy is effectively deployed.
Action	None.
WSSDIE0028	The following policy repository does not exist and cannot be created: {0}.
Explanation	The policy repository directory does not exist and cannot be created.
Action	Ensure that the policy repository is properly initialized. Ensure that the user who starts the java process is authorized to write in the specified repository directory.
WSSDIE0029	Failed to delete a policy file.
Explanation	A policy file deployed through a default policy supplier cannot be deleted.
Action	Ensure that the policy file is not locked by another process.
WSSDIE0138	Cannot assign a policy to a service; a policy with the following ID cannot be found: "{0}".
Explanation	The policy manager is requested to assign a policy to a certain service but the policy denoted by the supplied policy ID cannot be found in the policy repository.
Action	Ensure that the policy you attach exists in the policy repository.

WSSDIE0144	Unsupported IDynamicDescription implementation; the WSPolicyManager implementation works only with dynamic description instances of type {0} but {1} is available.
Explanation	Encountered an unrecognized dynamic description instance. Web Services Stack policy manager is intended to work with a specific implementation of the underlying dynamic description.
Action	If you use the default Web Services Stack policy manager, implement your dynamic assets so that they extend the default implementation of the deployer API.
WSSDIE0158	Service {0} does not use a standard deployment classloader; the resource jar is not appended to the classpath of the classloader.
Explanation	Service resource jar cannot be added to the service classpath. The service class loader is not an instance of org.apache.axis2.deployment.DeploymentClassLoader.
Action	Contact Software AG Global Support.
WSSDIE0162	The method can be called on a deployed unit only.
Explanation	The boolean isEngaged(String, boolean) method is called on an AxisDescription instance that has not been deployed on the Web Services Stack runtime yet. Therefore, it has no AxisConfiguration instance associated with it.
Action	Assert that the isEngaged module check is invoked on the deployed instance.
WSSDIE0164	Web Services Stack policy manager failed to update or remove policy from associated services when handling a "policy file deleted" event fired by the policy repository due to: "{0}".
Explanation	By default, the Web Services Stack policy manager is registered as a policy repository listener so it is notified when the policy repository detects that a policy file has been deleted. When such an event is received the policy manager attempts to remove the deleted policy from any associated attachment points (services, operations, or messages) and in the course of these actions the error occurs.
Action	This is an internal error. Contact Software AG Global Support.
WSSDIE0165	Web Services Stack policy manager fails to update or remove policy from associated services when handling a "policy file updated" event fired by the policy repository due to: "{0}".
Explanation	By default, the Web Services Stack policy manager is registered as a policy repository listener so it is notified when the policy repository detects that a policy file has been updated. When such an event is received the policy manager attempts to remove the policy from any associated attachment points (services, operations, or messages) in case the new policy has a different ID. If the new policy has the same ID as the previously deployed one (true update) it tries to refresh the policy attached to the respective subjects. In the course of these actions the error occurs.
Action	This is an internal error. Contact Software AG Global Support.

WSSDIE0166 **Cannot deploy policy file "{0}" as the policy is invalid. A file with name "{0}" already exists in the invalid policies directory. The existing file is overwritten.**

Explanation You try to deploy more than once an invalid policy. A policy file with the same name already exists in the directory, in which invalid policies are maintained. The existing file is overwritten with the new one (the file is updated).

Action Check the policy you want to deploy.

WSSDIE0167 **The policy ID or name is invalid. The policy is not deployed.**

Explanation The policy ID or name, if available, cannot contain whitespace characters inside. If whitespace characters are found inside, the policy is considered invalid and the policy file is moved to the invalid folder.

Action Check the policy ID or name for whitespace characters and remove them, if any.

WSSDIE0168 **Cannot deploy policy "{0}"; the policy is invalid and cannot be processed.**

Explanation There is a problem while processing the policy. The policy file is corrupted or the XML is invalid.

Action Check and validate the policy XML, check for typographical errors, and so on. Finally, deploy the policy again.

WSSDIE0169 **Failed to roll back disengage of the following module: {0}.**

Explanation An error occurs while disengaging modules, the system attempts to re-engage them but the corresponding module fails.

Action Contact Software AG Global Support.

WSSDIE0170 **Failed to disengage module {0}. Reason: {1}**

Explanation While removing policy components for the current DynamicDescription instance, the system attempts to disengage a referenced module but it fails.

Action Contact Software AG Global Support.

WSSDIE0171 **Exceptions must not be generated when skipping module disengagement.**

Explanation Policy cleanup must not generate any exceptions if module disengagement argument is not set.

Action Contact Software AG Global Support.

WSSDIE0172	Cannot refresh services after the "{0}" policy is updated due to the following: "{1}".
Explanation	Web Services Stack policy manager is automatically updating policy subjects upon a policy update with a certain ID. The update fails when applying the new policy to the subjects.
Action	Contact Software AG Global Support.
WSSDIE0173	Failed to create a dynamic deployer instance.
Explanation	The exception occurs while trying to initialize the default policy manager instance and it fails to initialize the dynamic deployer. This happens when no valid Axis configuration is found.
Action	Ensure that the code is running in properly started and initialized Web Services Stack runtime.
WSSDIE0174	Cannot clean policy of the following Web service: "{0}".
Explanation	The policy manager failed to remove policies for the given Web service. Generally, the exception is generated when the disengageModules flag is set to true. However, this is not what causes the problem in this invocation.
Action	Redeploy your Web service.
WSSDIE0175	Cannot clean policy of the Web service "{0}" operation "{1}".
Explanation	The policy manager failed to clean the policy on the given operation of the given Web service. Generally, the exception is thrown only when the disengageModules flag is set to true. However, this is not what causes the problem in this invocation.
Action	Redeploy your Web service.
WSSDIE0176	Cannot clean message policy for service "{0}" operation "{1}".
Explanation	The policy manager failed to clean the message policy on the given operation of the given service. Generally, the exception is thrown only when the disengageModules flag is set to true. However, this is not what causes the problem in this invocation.
Action	Redeploy your Web service.
WSSDIE0178	Failed to retrieve the following service group after persisting and redeploying it: "{0}".
Explanation	The Dynamic deployer API was used to persist a service group but after redeploying the service group could not be found in Web Services Stack runtime. A possible cause for the error is a problem during the deployment.
Action	Ensure that the service group file or directory is not locked, and the current user has the credentials to write to it. Redeploy your Web service manually.

WSSDIE0179	Exception occurs while trying to obtain policy manager instance and the policy manager cannot be notified about redeployed Web services.
Explanation	When a service is persisted the Web Services Stack runtime undeploys and redeploys it again. That makes any references kept to the previous Web service invalid. Since the policy manager keeps associations between policies and attachment points (such as Web services) it needs to be notified to synchronize its cache.
Action	The system is automatically recovered but the policy manager's cached association for the updated Web services are lost.
WSSDIE0180	Failed to retrieve the following Web service "{0}" after persisting and redeploying it.
Explanation	The Dynamic deployer API was used to persist a Web service but after redeploying the Web service cannot be found in the Web Services Stack runtime. A possible cause for the error is a problem during the deployment.
Action	Ensure that the Web service file or directory is not locked and the current user has permissions to write to it. Redeploy your Web service manually.
WSSDIE0181	Web Services Stack policy engine failed to parse the deployed policy.
Explanation	An exception occurred while the policy engine was processing a freshly deployed policy. Most probably the policy xml is invalid.
Action	Correct the policy xml and redeploy it.
WSSDIW0163	Modules cannot be engaged at the following binding hierarchy - Endpoint (port), Binding, Binding operation, Binding Message.
Explanation	Axis2 does not support engaging modules at the listed subjects and respectfully calling isEngaged on those axis objects throws an UnsupportedOperationException.
Action	Invalid invocation. This method cannot be invoked on IDynamicPort, IDynamicBinding, IDynamicBindingOperation, or IDynamicBindingMessage.
WSSDIW0177	Parent service group is not found for the following Web service: "{0}".
Explanation	The dynamic deployer could not find the parent service group of the given Web service.
Action	Ensure that the Web service is properly deployed or redeploy it.

WSSDSE0000	In order to deploy JAX-WS services you must have a JAX-WS Deployer configured in your axis2.xml.
Explanation	The <deployer extension=".jar" directory="servicejars"class="org.apache.axis2.jaxws.framework.JAXWSDeployer"/> line in your axis2.xml is commented or missing.
Action	Uncomment the <deployer extension=".jar" directory="servicejars"class="org.apache.axis2.jaxws.framework.JAXWSDeployer"/> line in the axis2.xml, or add it if it is missing.
WSSDSE0011	An error occurs while trying to remove the following security provider: "{0}".
Explanation	Before the SAGAdminServlet is destroyed, it checks whether the BouncyCastle and JuiCE are added to the java security providers and whether they are loaded by the current web application classloader. If it is true, the servlet tries to remove them, as they are not available to other web applications. This error occurs when the servlet tries to cleanup the BouncyCastle and JuiCE providers from the list.
Action	Contact Software AG Global Support
WSSDSE0012	DeployServlet requires the following instance in the servlet context but cannot find it: "{0}".
Explanation	An Axis2 "org.apache.axis2.deployment.DeploymentEngine" instance has to be available in Web Services Stack DeployServlet's servlet context under the DEPLOYER servlet context attribute but such an attribute is not found.
Action	The reason for the error is that Web Services Stack Administration servlet fails to initialize. Make sure that the servlet is properly initialized.
WSSJCE0012	Module "{0}" is engaged but configuration for a JAX-WS handler-chain was not found.
Explanation	The module is engaged, but it does not contain any JAX-WS handlers configured into the chain.
Action	Inspect the engaged module if it contains the expected JAX-WS handlers.
WSSJCE0015	The JAX-WS handler chain cannot be loaded.
Explanation	The JAX-WS handler-chain descriptor (XML) file is not correct or the handler instances configured in it cannot be loaded.
Action	Inspect and correct the JAX-WS handler-chain descriptor (XML) file.

WSSJCE0018	An incorrect property value is set for the JAX-WS handler-chain.
Explanation	The JAX-WS handler-chain descriptor (XML) file has an incorrect property value set for a JAX-WS handler.
Action	Check and correct the JAX-WS handler-chain descriptor (XML) file.
WSSJCE0019	An error occurs in the JAX-WS handler-chain execution.
Explanation	At the invocation of JAX-WS in/out flow, an exception is thrown while processing the chain.
Action	For more information about the failure, see the AxisFault response message. Check the JAX-WS chain configuration.
WSSJCW0001	A handler class of the handler chain cannot be found.
Explanation	Classes are missing for some handler instances configured into the handler-chain descriptor (XML) file.
Action	Check that the handler classes configured into the handler-chain descriptor (XML) file are available into the jar library (class-path).
WSSJCW0002	A handler of the handler chain cannot be instantiated.
Explanation	A class of the handler available into the classpath is not a standard one.
Action	Check that the handler class available into the jar library is the original one provided by the product and was not modified improperly.
WSSJCW0004	The configuration of a class from the handler chain is incorrect.
Explanation	A class of the handler available into the classpath is not a standard one.
Action	Check that the handler class available into the jar library is the original one provided by the product and was not modified improperly.
WSSJCW0005	An error occurs while loading the JAX-WS handler chain.
Explanation	A class of the handler available into the classpath is not a standard one.
Action	Check that the handler class available into the jar library is the original one provided by the product and was not modified improperly.

WSSJCW0009	An error occurs while executing PreDestroy methods of the JAX-WS handlers. {0}
Explanation	A JAX-WS handler executed into the chain, throws an exception while destroying it after being used.
Action	Check that the handler class available into the jar library or its XML configuration file were not modified improperly.
WSSJCW0011	An error occurs while executing PostConstruct methods of the JAX-WS handlers. {0}
Explanation	A JAX-WS handler executed into the chain throws an exception during its initialization.
Action	Check that the handler jar archive or its XML configuration file were not modified improperly.
WSSJHE0003	An error occurs during the completion of a JAX-WS handler.
Explanation	An error occurs into the flow when closing a JAX-WS handler.
Action	Check whether the handler class that is available into the jar library or its XML configuration file are not modified improperly.
WSSJHE0004	JAX-WS handler PreDestroy method failed.
Explanation	An error occurs when invoking a JAX-WS handler PreDestroy method.
Action	Check whether the Handler class that is available into the jar library or its XML configuration file are not modified improperly.
WSSJHE0008	A JAX-WS handler failed.
Explanation	An error occurs when invoking a JAX-WS handler.
Action	Check whether the handler class that is available into the jar library or its XML configuration file are not modified improperly.
WSSJHE0010	A JAX-WS handler instantiation failed for the following classname: {0}.
Explanation	An error occurs during JAX-WS handler instantiation.
Action	Check whether the handler class that is available into the jar library or its XML configuration file are not modified improperly.

WSSJHE0011	The JAX-WS handler {1} is not type {0}.
Explanation	An error occurs during JAX-WS handler invocation.
Action	Check whether the handler class that is available into the jar library or its XML configuration file are not modified improperly.
WSSMRE0003	The service does not define adapter class parameter: "{0}".
Explanation	When com.softwareag.wsstack.messagereceivers.AdapterMessageReceiver is invoked, it tries to find a parameter named adapter in the currently invoked service. The adapter parameter denotes a name of a class that implements the com.softwareag.wsstack.adapter.api.Adapter interface. The message receiver attempts to instantiate and execute the configured adapter.
Action	Add an adapter parameter to your service definition (in your services.xml file). As a value to the parameter, set the required adapter implementation class.
WSSMRE0004	The configured adapter class is invalid: "{0}"
Explanation	When com.softwareag.wsstack.messagereceivers.AdapterMessageReceiver is invoked, it tries to find a parameter named adapter in the currently invoked service. The adapter parameter denotes a name of a class that implements the com.softwareag.wsstack.adapter.api.Adapter interface. The message receiver attempts to instantiate and execute the configured adapter.
Action	Specify a valid adapter class name as a value to the adapter parameter in your service definition.
WSSPWE0000	UsernameToken authentication failed.
Explanation	Invalid or empty password provided.
Action	Provide valid credentials.
WSSPWE0001	Unknown password callback type: {0}.
Explanation	Invalid usage of the password callback handler. Valid usage is for signing, decryption, and username password validation.
Action	Provide a valid usage of the callback handler.
WSSPWE0004	The system cannot load the LDAP configuration for the password callback handler: {0}.
Explanation	The password callback handler needs LDAP configuration. If it is not configured, the default LDAP configuration ldap.properties is used. LDAP configuration file cannot be loaded.
Action	Provide valid LDAP configuration.

WSSPWE0008	Invalid LDAP configuration for the password callback handler.
Explanation	One or more of the required LDAP configuration properties are not available in the LDAP configuration.
Action	Provide all required LDAP configuration properties.
WSSPWE0009	UsernameToken authentication failed.
Explanation	Invalid or empty password provided. The user cannot be authenticated.
Action	Provide valid, non-empty values for username and password.
WSSPWE0010	Cannot recognize the following user ID: "{0}".
Explanation	Invalid or empty username, or certificate alias provided.
Action	Check the spelling and provide a valid, non-empty value for username, or certificate alias (depending on the use case).
WSSPWE0012	System cannot load the password callback handler configuration file: {0}.
Explanation	The password callback handler configuration file is not found and cannot be loaded.
Action	Check if the configuration file exists and if the path to the file is correct.
WSSPWE0013	Cannot convert the configuration from a stream to an OMElement: {0}.
Explanation	A problem occurs while converting the configuration file content to an OMElement.
Action	Check and validate the XML format of the configuration file.
WSSTRE0001	Cannot close the input stream of the file; the file absolute path value is [{0}]. The exception message is: {1}.
Explanation	Cannot close a file input stream or cannot release system resources associated with the stream.
Action	Check the file state. For example, it can be locked by another process.
WSSTRE0002	The used key cannot be "null".
Explanation	The key that is used for a property is null.
Action	Contact Software AG Global Support.

WSSTRE0003	Cannot close an input/output stream of type [{0}]; the exception message is: {1}
Explanation	There is an exception during input/output stream closure.
Action	Contact Software AG Global Support.
WSSTRE0004	There is an error while manipulating an input/output stream in use.
Explanation	There is an exception during input/output stream processing.
Action	Contact Software AG Global Support.
WSSTRE0005	The repository listener is not initialized.
Explanation	The repository listener is not initialized.
Action	Contact Software AG Global Support.
WSSTRE0006	The following operation is not supported: [{0}].
Explanation	Non existing operation requested.
Action	Check that an operation with the specified name exists. Contact Software AG Global Support.
WSSTRE0007	Cannot delete the file with the following file path: [{0}].
Explanation	There is a problem deleting the file.
Action	Check that the file exists and it is not locked. Check that you have sufficient permissions to delete the file.
WSSTRE0008	Cannot create a directory in the following location: [{0}].
Explanation	There is a problem while creating a "services" directory.
Action	Contact Software AG Global Support.
WSSTRE0009	The following Web service element cannot be null: {0}.
Explanation	The Web service element is null.
Action	Check the content structure of the Web service that is deployed dynamically.
WSSTRE0010	The name of the Web service client {0} must not be null or empty.
Explanation	The name of the Web service client that is instantiated is null or empty.
Action	Check the Web service client implementation.

WSSTRE0011	Cannot delete the following directory: [{0}].
Explanation	There is a problem while deleting a Web service directory.
Action	Check that the Web service directory is not locked and check that you have sufficient permissions to delete the directory.
WSSXTE0000	{0}: An XML document that is empty, invalid or does not exist.
Explanation	The document is empty or invalid.
Action	Provide a valid, non-empty XML document.
WSSXTE0013	Unexpected element found after the SOAP Body element: "{0}"
Explanation	Web Services Stack is processing an invalid message. The sent message contains an unexpected element in the SOAP Envelope after the SOAP Body element. A SOAP Envelope is expected to contains only an optional SOAP Header element followed by one SOAP Body element.
Action	Inform the web service conversation partner that they are generating invalid web service messages.
WSSXTE0014	Unexpected element found after the SOAP envelope has been consumed: "{0}"
Explanation	Web Services Stack is processing an invalid message. The sent message contains an unexpected element after the already consumed SOAP Envelope. A web service message is expected to contain a single SOAP Envelope element.
Action	Inform the web service conversation partner that they are generating invalid web service messages.

30

webMethods Events Messages

WEPCAE0001	Missing host name.
Explanation	No host name was passed when creating the address of the Event Server to be connected.
Action	Fix the construction of the event server address.
WEPCAE0002	Incomplete credentials provided.
Explanation	Either the user name or the password was null.
Action	Provide non-null values for the user name and password.
WEPCAE0003	The host name is unknown.
Explanation	The host name provided in the address on the Event Server is unknown.
Action	Correct the host name.
WEPCAE0004	There is already a sender connection established to input stream {0} of project {1}.
Explanation	Only one sender connection at a time can be established to an input stream.
Action	Revise your application logic.
WEPCAE0005	The project or the input stream name is null.
Explanation	The project name or the input stream name contains a null name, but non-null names must be provided for the project and the input stream.
Action	Provide non-null names for the project and the input stream.

WEPCAE0006	The callback is null.
Explanation	When connecting to an input stream or query output a callback must be provided.
Action	Fix your application code.
WEPCAE0007	Could not establish connection to input stream {1} in project {0}.
Explanation	Establishing the input connection requires that the underlying direct connection is still active and that the given project containing the specified input stream has been deployed to Event Server.
Action	Check that the direct connection is available and that the given project with the input stream has been deployed to Event Server.
WEPCAE0008	The specified project {0} does not contain query {1}.
Explanation	The query with the given name in the given project is not deployed to Event Server. Thus, it is not possible to connect to that query's output.
Action	Deploy the project with the query or adapt your application.
WEPCAE0009	Cannot establish new input or output connection as primary connection is already closed.
Explanation	The primary connection of type DirectConnection has already been closed. Hence, it is not possible to use derived input or output connections any more.
Action	Check your application logic.
WEPCAE0010	Missing address of Event Server to be connected.
Explanation	One or more Event Server addresses need to be specified.
Action	Provide at least one Event Server address.
WEPCAE0011	Invalid Event Server address: {0}.
Explanation	The address passed to the connect() method is invalid - it must be of type TcpIpEventServerAddress.
Action	Correct your application code correspondingly.
WEPCAE0012	The project or the query name is null.
Explanation	The project name or the query name is null, but non-null names must be provided for the project and query.
Action	Fix the method invocation.

WEPDED0048	... {0}
Explanation	This message is used to list the artifacts that are successfully deployed or undeployed.
Action	No action required.
WEPDED0049	Established output processing for query "{0}".
Explanation	The output processing for the given query has been deployed successfully.
Action	No action required.
WEPDEE0001	Error occurred during deployment.
Explanation	An exception occurred while processing a deployment archive.
Action	Check the detailed error message.
WEPDEE0002	Error occurred when deploying {0}.
Explanation	An exception occurred while processing the given deployment archive.
Action	Check the detailed error message.
WEPDEE0003	Error occurred during rollback.
Explanation	A secondary error occurred while rolling back changes due to a deployment attempt.
Action	Check the detailed error messages.
WEPDEE0005	Error occurred when un-deploying archive {0}.
Explanation	An error occurred when un-deploying the given deployment archive.
Action	Check the detailed error messages.
WEPDEE0007	Error occurred when un-deploying {0}
Explanation	An error occurred when un-deploying a deployment archive.
Action	Check the detailed error messages.
WEPDEE0008	Error occurred when polling the deployment archive directory.
Explanation	An unexpected error occurred when checking the content of the deployment folder for new, modified or removed deployment archives.
Action	Check the detailed error messages.

WEPDEE0009	Details: {0}
Explanation	This message displays the reason why the deployment of an archive has failed.
Action	Check the detail messages to identify potential corrective actions.
WEPDEE0010	Deleting archive {0}.
Explanation	If the deployment of a CAR deployment archive failed and the deployment.xml file could not be written, the deployment archive is deleted immediately.
Action	Check the detailed messages for information about the cause of the deployment failure.
WEPDEE0011	Unexpected error deploying archive file {0}. See deployment data in the directory in {1}
Explanation	An unexpected error occurred while deploying a CAR deployment archive.
Action	Check the server log file and the deployment.xml file for details regarding the deployment failure.
WEPDEE0013	Unable to deploy output processing for query "{0}"
Explanation	The output event schema does not comply with the current restrictions.
Action	Check the associated stack trace for details.
WEPDEE0014	{0}
Explanation	This message is used to pass through detail error messages during deployment.
Action	Check the error messages.
WEPDEE0015	Error when registering project "{0}" in Event Engine.
Explanation	The project name must be a valid identifier as defined in the SQL standard. This constraint is enforced when creating a continuous query project in Designer. However, this error may occur when bypassing the standard procedure.
Action	Fix the project name according to the SQL standard.
WEPDEE0016	Un-deployment of project {0} failed.
Explanation	An exception occurred when attempting to un-deploy the given project.
Action	Check the supplementary messages to find the cause of this error.

WEPDEE0017	Error occurred during deployment of query "{0}".
Explanation	When deploying a continuous query, several steps need to be accomplished internally. One of these steps failed.
Action	Check supplementary error messages for details.
WEPDEE0018	Error creating deployment.xml file for deployment archive {0}.
Explanation	When processing a deployment archive, Event Server creates a file named deployment.xml in a subdirectory of the configured deployment directory. This file is used to record the results from deploying the given deployment archive. This error message occurs when creation of that file failed.
Action	Check the supplementary error messages for the cause of this error.
WEPDEE0019	Requested directory to write deployment file does not exist: {0}.
Explanation	When processing a deployment archive, Event Server creates a file named deployment.xml in a subdirectory of the configured deployment directory. This error message occurs when the subdirectory does not exist as expected.
Action	Check the preceding error messages for additional explanations.
WEPDEE0020	Error creating deployment.xml file {0}.
Explanation	When processing a deployment archive, Event Server creates a file named deployment.xml in a subdirectory of the configured deployment directory. For some reason the creation of that file failed.
Action	Check the preceding error messages and file system where the file should have been written to.
WEPDEE0021	Deployment archive file is missing: {0}.
Explanation	When processing a deployment archive, Event Server creates a file named deployment.xml in a subdirectory of the configured deployment directory. When attempting to create this file, the deployment archive was not available at the given location.
Action	Check the given path of the deployment archive.
WEPDEE0022	Unable to parse deployment.xml file {0}.
Explanation	When processing a deployment archive, Event Server creates a file named deployment.xml in a subdirectory of the configured deployment directory. This file is used to record the results from deploying the given deployment archive. This error message reflects an error when reading that file.
Action	Check the content of the deployment.xml file and the exception details.

WEPDEE0023	Error creating artifact set from deployment archive {0}.
Explanation	An error occurred when trying to determine the set of artifacts contained in the given deployment archive.
Action	Re-create the deployment archive.
WEPDEE0024	Failed to get value of child node "{0}" below "{1}" in deployment file.
Explanation	The deployment.xml file does not have the expected structure.
Action	Re-deploy the continuous query application.
WEPDEE0025	Missing name of deployment archive file.
Explanation	The deployment.xml file does not contain the name of the deployment archive file as expected.
Action	Redeploy the application.
WEPDEE0026	Time stamp given in deployment.xml file is not a valid number
Explanation	The deployment time stamp in the deployment.xml file is invalid.
Action	Re-deploy the continuous query application.
WEPDEE0027	Deployment time stamp not valid.
Explanation	The deployment.xml file logs the original time stamp of the deployment archive. The value is not valid, probably due to manual manipulation.
Action	Change the time stamp to a valid value.
WEPDEE0028	Name of dependent deployment archive file is missing.
Explanation	The structure of the deployment.xml file is not as expected.
Action	Re-deploy the continuous query application.
WEPDEE0029	Dependent deployment archive file {0} does not exist.
Explanation	The deployment.xml file refers to a dependent deployment archive which does not exist.
Action	Check whether a dependent deployment archive had been deleted without taking the dependency into account.

WEPDEE0030	The directory structure of deployment archive {0} is not as expected.
Explanation	Event Server expects a certain directory structure in a deployment archive. In particular, a CAR deployment archive is expected to have a single top-level directory name corresponding to the name of the project.
Action	Check the content of the deployment archive.
WEPDEE0031	Unexpected errors occurred when extracting deployment archive {0}.
Explanation	Event Server could not extract the content of the given deployment archive.
Action	Check and re-create the deployment archive.
WEPDEE0032	Not a valid deployment archive file to extract: {0}.
Explanation	The given deployment archive does not match the expected properties.
Action	Check the name and content of the given deployment archive.
WEPDEE0033	No deployment archive file given.
Explanation	This is an internal error.
Action	Contact your software supplier.
WEPDEE0034	Deployment directory is not valid: {0}.
Explanation	The given path does not exist or does not refer to a directory.
Action	Check the configuration of Event Server.
WEPDEE0035	Error removing the directory {0}.
Explanation	^An error occurred when attempting to delete the given directory.
Action	Check the supplied exception stack trace.
WEPDEE0036	Cannot register source adapter for input stream {0}.
Explanation	An error occurred during deployment of the input processing for the given event input stream.
Action	Check the supplied stack trace for details.

WEPDEE0037	Cannot de-register source adapter for input stream "{0}".
Explanation	An unexpected error occurred when un-deploying input processing for the given event input stream.
Action	Check the supplied stack trace.
WEPDEE0038	Error occurred during deployment.
Explanation	An unexpected error occurred during the deployment processing.
Action	Check the supplied stack trace for details.
WEPDEE0050	Found unexpected file when traversing class files: {0}
Explanation	The given file was not expected among the compiled classes.
Action	Remove the file.
WEPDEE0051	An I/O error occurred during compilation of Java code.
Explanation	During deployment, Java classes used for purposes such as user-defined functions are compiled. An I/O error occurred during the compilation.
Action	Check Event Server's runtime and compile environment.
WEPDEE0052	Failed to create directory "{0}".
Explanation	Could not create the given directory during the deployment processing.
Action	Check the file system privileges.
WEPDEE0055	List of Java compilation error(s): {0}
Explanation	This lists the errors obtained while compiling Java code e.g. for user-defined functions.
Action	Check and fix the error messages.
WEPDEE0056	Failed to retrieve location of runtime bundle.
Explanation	Compilation of Java sources requires additional classpath extensions which could not be determined.
Action	Check the stack trace for further information.

WEPDEE0057	Failed to decrypt secured property.
Explanation	During deployment, some properties like passwords are encrypted and thus must be decrypted by Event Server at deployment time.
Action	Check the stack trace for further information.
WEPDEE0058	File length given in deployment file is not a valid number:
Explanation	The deployment.xml file logs the original length of the deployment archive. This value is not numeric, probably due to manual manipulation.
Action	Change the value of the length field to a valid numerical value.
WEPDEE0059	Invalid deployment archive: {0}.
Explanation	The given file is an invalid deployment archive which cannot be analyzed and/or processed by the Event Server.
Action	Check and remove the invalid archive from the deployment directory.
WEPDEE0062	Error(s) occurred during deployment.
Explanation	Error(s) occurred during processing of the deployment archive and corresponding ACDL file.
Action	Check the supplementary error messages for details.
WEPDEE0066	Location of event type store is unknown.
Explanation	In order to process event type schemas in deployment archives, the Event Server requires the location of the event type store to be configured correctly.
Action	Check the appropriate configuration files.
WEPDEE0068	Event type schema with component path {0} differs from schema in event type store.
Explanation	This error occurs when modification of event type schemas which are already deployed is not permitted.
Action	Consider creating a completely new event type schema in order to preserve backward compatibility.
WEPDEE0069	Error detected in event type schema at {0}.
Explanation	Before an event type schema is deployed to the event type store, the schema is checked by the Event Server. During this step an error has been detected.
Action	Check the stack trace for details.

WEPDEE0072	Failed to resolve reference to event type {0}.
Explanation	A query has a reference to the given output event type which cannot be resolved.
Action	Check the deployment archive and event type store.
WEPDEE0074	Exception occurred during authentication of deployment request.
Explanation	An invalid deployment request has been received which caused an exception during authentication.
Action	Check the associated stack trace for details.
WEPDEE0076	JMS connection alias "{0}" referenced by output binding of query "{1}" does not exist.
Explanation	Deployment of the given query failed because the referenced JMS connection alias does not exist.
Action	Please check whether the name of the JMS connection alias is misspelled. If not, you need to create the JMS connection alias manually.
WEPDEE0078	Deployment folder at "{0}" is not accessible or cannot be written.
Explanation	Event Server continuously monitors the content of the given folder in order to check for assets to be deployed or un-deployed.
Action	Check the existence and access privileges of the given folder. You may also want to change the folder location by adapting the Event Server configuration file and restarting Event Server afterwards.
WEPDEE0080	Mismatch of checksums: {0} does not match {1}.
Explanation	When deploying a project to Event Servers running in a high-availability cluster, the Event Servers compare individually computed checksums with each other in order to ensure that identical deployment archives are deployed to each node. This error indicates that a mismatch has been detected.
Action	Ensure that identical deployment archives are deployed to each node.
WEPDEE0081	Synchronization of deployment of project "{0}" failed.
Explanation	An error was detected when trying to synchronize deployment of a continuous query project to an Event Server configured to run in a cluster.
Action	Check the cluster configuration and ensure consistent deployment to all cluster members.

WEPDEE0082	Failed to synchronize re-deployment at Event Server startup.
Explanation	A problem occurred during cluster synchronization of re-deployment during Event Server startup.
Action	Check the Event Server log files for additional error details.
WEPDEE0083	Error occurred during re-deployment during Event Server startup.
Explanation	An error occurred when the Event Server tried to re-deploy previously deployed projects during startup.
Action	Check the exception stack trace for further details.
WEPDEE0086	Error occurred during deployment processing on high-availability master "{0}".
Explanation	This message may be reported by an Event Server which is running as the slave in high-availability mode. The deployment is controlled by the master which reports details of failures if there are deployment errors. The slave just reports this message as an indicator that there has been an error.
Action	Check the deployment messages reported by high-availability master.
WEPDEE0088	Failed to delete rejected deployment archive "{0}".
Explanation	If the Event Server detects an inconsistency during deployment of a project when running in high-availability mode, it attempts to delete the respective deployment archive from disk. This message occurs when that deletion has failed.
Action	Check the Event Server's access privileges for the archive and delete manually.
WEPDEE0089	Database source "{0}" not configured for caching as required in high-availability mode.
Explanation	When running the Event Server in high-availability mode it is crucial to provide the same input data to all Event Servers in the high-availability cluster. This applies also to data read from a database. Consistency for this data is achieved by using a Terracotta-based shared cache within all Event Servers in the cluster. Hence, the database sources being deployed into a high-availability cluster must be configured to use caching.
Action	Configure the database sources to use the appropriate caching mode.
WEPDEE0091	Failed to determine content of deployment folder "{0}".
Explanation	This error may occur especially during the first startup of Event Server after installation on UNIX and LINUX platforms.
Action	Increase the maximum number of open files permitted per process.

WEPDEE0093	Failed to delete archive file "{0}".
Explanation	During the undeployment of the Continuous Query application, the Event Server tried to delete file "{0}" but was not successful.
Action	Check the server log file for more information.
WEPDEE0095	Failed to delete ACDL file "{0}".
Explanation	During the undeployment of the Continuous Query application, the Event Server tried to delete the ACDL file but was not successful.
Action	Check the server log file for more information.
WEPDEE0096	Invalid artifact name "{0}".
Explanation	The name "{0}" is not valid for an artifact. It does not contain the project name the artifact is stored in.
Action	Check the server log file for more information.
WEPDEE0097	Invalid artifact set. There are artifacts of different projects "{0}" and "{1}".
Explanation	Artifacts within the same set must belong to the same application project. There are resources that belong to project "{0}", others belong to project "{1}". This is not valid.
Action	Check the artifact set used to deploy your Continuous Query application.
WEPDEE0100	User-defined extensions "{0}" must not be removed from a deployed project.
Explanation	Once a project has been deployed successfully, a user-defined extension must not be removed.
Action	Check your deployment set and remove any user-defined extension from it.
WEPDEI0053	Compilation of Java sources ended successfully.
Explanation	Compilation of Java sources ended without any diagnostic messages.
Action	No action required.
WEPDEI0054	There are diagnostic messages from compilation of Java sources:
Explanation	Diagnostic messages occurred during the compilation of Java sources used for purposes such as user-defined functions. The messages will be listed subsequently.
Action	Check for error messages listed subsequently.

WEPDEI0060	Saved deployment archive to {0}.
Explanation	The deployment archive received from webMethods Deployer has been saved to the given location.
Action	No action required.
WEPDEI0061	Project "{0}" has been deployed successfully.
Explanation	The deployment archive, including the corresponding ACDL file, has been processed successfully by the Event Server.
Action	No action required.
WEPDEI0064	Deployment archive {0} has been modified - first un-deploy old one implicitly.
Explanation	If the Event Server detects a modified CAR file in its deployment folder, it undeploys the previous one before processing the new one.
Action	No action required.
WEPDEI0067	Copying event type schemas from "{0}" to "{1}".
Explanation	After the Event Server has successfully processed a deployment archive, it copies event type schemas contained therein to the event type store. This allows them to be shared with other EDA participants.
Action	No action required.
WEPDEI0071	Event type schema with component path {0} is not copied as it is not modified.
Explanation	After successful processing of a deployment archive, the Event Server copies event type schemas to the configured event type store. The given event type schema already exists in the event type store and was not modified. Hence, it is not copied.
Action	No action required.
WEPDEI0077	Re-deploying "{0}".
Explanation	During startup, the Event Server re-deploys all projects which had been deployed before.
Action	No action required.

WEPDEI0084	There are {0} project(s) to be re-deployed.
Explanation	This message gives the number of projects to be re-deployed during the Event Server startup. An explicit list of projects will follow.
Action	No action required.
WEPDEI0085	Project "{0}" using "{1}".
Explanation	This message gives a single project with its associated deployment archive as part of a list.
Action	No action required.
WEPDEI0090	Determine list of projects to be re-deployed
Explanation	When the Event Server is started it checks its deployment folder for projects which had been previously deployed and which are to be re-deployed.
Action	No action required.
WEPDEI0092	Archive file "{0}" deleted successfully.
Explanation	The deletion of file "{0}" was successful.
Action	Check the server log file for more information.
WEPDEI0094	ACDL file "{0}" deleted successfully.
Explanation	During undeployment of the Continuous Query application, the Event Server successfully deleted file "{0}".
Action	Check the server log file for more information.
WEPDEI0098	Request to remove assets can only be processed by HA master - ensure that same request is sent to the other Event Server in HA cluster as well.
Explanation	When running Event Server in high availability mode, all deployment requests must be sent to the HA cluster.
Action	Verify that your deployment request has been sent to the HA cluster but not to only a single Event Server instance.
WEPDEW0012	No subscription for query "{0}" due to given properties
Explanation	Output events for the given query will not be sent to the event bus. This may be intentional, for reasons such as debugging purposes or if the output events are to be consumed by another continuous query.
Action	You may want to consider whether to make the query's output events available on the event bus.

WEPDEW0063	Ignore deployment archive {0} due to previous error during deployment.
Explanation	The Event Server had already attempted to deploy the given deployment archive before but failed. Hence, the deployment archive is ignored when restarting the Event Server.
Action	Check the event server log or deployment.xml file for further details about why the deployment had failed.
WEPDEW0065	Failed to read deployment.xml file in directory {0}.
Explanation	An error occurred when attempting to read the given file.
Action	Check the stack trace for further details.
WEPDEW0070	Modifying existing event type schema with component path {0}.
Explanation	After successful processing of a deployment archive, the Event Server copies event type schemas to the configured event type store. During this step it has detected that a different version of the given schema already exists in the event type store. It will be replaced by the new version.
Action	No action required. However, especially in a production environment, it is considered good practice to use a new event type schema instead of modifying an existing one.
WEPDEW0073	Authentication for user {0} failed.
Explanation	The given user is not authorized to deploy to the Event Server.
Action	Check the specified credentials.
WEPDEW0075	No credentials provided in deployment request.
Explanation	No credentials were passed with the deployment request.
Action	Check the configuration of the deployment client.
WEPDEW0079	Project "{0}" is not known on node "{1}" - discard for re-deployment.
Explanation	During Event Server startup in HA mode, the Event Servers in the cluster compare the list of projects available in their respective deployment folders. Projects not available to all of them are discarded for re-deployment.
Action	Check the content of each Event Server's deployment folder.

WEPDEW0087	Deleted invalid deployment archive "{0}".
Explanation	The deployment archive has been deleted due to an inconsistency detected during deployment to an Event Server cluster.
Action	Check the preceding error messages on all Event Server cluster members.
WEPDEW0099	Deployment archive has been removed: "{0}"
Explanation	During the deployment, Event Server has deleted the previous version of the Continuous Query application.
Action	Check the server log file for more information.
WEPDIE0001	Error registering to listener {0}
WEPDIE0002	Web service not published
WEPDIE0003	Plug-in already registered with name "{0}"
WEPDIE0004	No artifacts stored below the given checkpoint ID "{0}".
Explanation	Event Server cannot activate checkpoint "{0}". There are no artifacts in the persistence manager stored below the given ID.
Action	Check the webMethods Deployer operation reports for more information.
WEPDIE0005	Error parsing ACDL Composite contents.
Explanation	The provided ACDL composite is invalid.
Action	Check the webMethods Deployer operation reports for more information.
WEPDIE0006	The ACDL for archive file "{0}" does not exist. Event Server cannot checkpoint a CAR file based deployment.
Explanation	It is not possible to mix the two methods of deploying a Continuous Query application. Either use the CAR-file based deployment or the repository-based method using webMethods Deployer.
Action	Review your deployment process and ensure that you use just one deployment method for a given Continuous Query application.

WEPDIE0008	Could not fetch the WEP persistence manager service.
Explanation	Event Server could not retrieve a handle of the webMethods Deployer persistence manager.
Action	Check the server log file for more information.
WEPDIE0009	Assets to be stored below a checkpoint ID must not relate to different projects. Some assets relate to project "{0}", other assets to "{1}".
Explanation	Event Server cannot execute the request. Assets to be stored below a checkpoint ID must not relate to different projects. Some assets relate to project "{0}", other assets to "{1}".
Action	Review your deployment composites and ensure that artifacts of one single composite belong to the same project.
WEPDIE0011	Unexpected exception during deployment. {0}.
Explanation	An unexpected error occurred while deploying the Continuous Query application.
Action	Check the server log file for more information.
WEPDII0007	The delivered artifacts for the given identifier "{0}" are ready to be activated.
Explanation	Event Server successfully verified that the artefacts for the given identifier "{0}" can be activated.
Action	Check the webMethods Deployer operation reports for more information.
WEPDII0010	Successfully created checkpoint "{0}".
Explanation	The checkpoint operation for the identifier "{0}" was successful.
Action	Check the webMethods Deployer operation reports for more information.
WEPDII0012	Error retrieving the DatatypeFactory.
Explanation	Event Server was not able to retrieve a handle to the datatype factory.
Action	Check the server log file for more information.
WEPDPE0001	IDispatcher interface already registered
Explanation	An internal error occurred during the startup of the event server.
Action	Contact your software supplier.

WEPDPE0002	Failed to dispatch incoming event for input stream "{0}"; event: {1}
Explanation	An exception occurred when trying to pass an incoming event to the event engine.
Action	Check the supplied primary stack trace.
WEPDPE0003	Failed to dispatch incoming event; no IDispatcher object has been registered
Explanation	This error indicates that an error occurred during the event server startup sequence.
Action	Check the server log.
WEPEBE0004	Failed to create broker "{0}" .
Explanation	An error occurred during the creation of the given Broker instance.
Action	Check the supplied stack trace for further details.
WEPEBE0005	Call failed to Integration Server service "{0}" .
Explanation	An error occurred when calling the given service in the Integration Server.
Action	Check the supplied exception stack trace.
WEPEBE0006	Unable to prepare call to an Integration Server service for user "{0}" .
Explanation	The Event Server failed to prepare a call to an Integration Server service.
Action	Check for an associated exception stack trace and error during the event server startup.
WEPEBE0007	No broker host set for broker "{0}" .
Explanation	The broker host name for the given broker instance is not available.
Action	Check the event server configuration file.
WEPEBE0008	Failed to initialize JMS admin client for broker "{0}" .
Explanation	An error occurred when trying to establish a connection to the given broker instance for administration purposes.
Action	Check the supplied stack trace.
WEPEBE0010	Failed to create client group "{0}"
Explanation	An error occurred when creating the given client group.
Action	Check the supplied stack trace.

WEPEBE0012	Failed to create topic "{0}".
Explanation	The Event Server failed to create the given topic.
Action	Check the supplied stack trace.
WEPEBE0014	Failed to delete topic "{0}".
Explanation	An error occurred when attempting to delete the topic with the given name.
Action	This is an internal error. Please contact your software supplier.
WEPEBE0015	A user name is required to prepare the call to an Integration Server service.
Explanation	The Event Server uses a built-in user name. Hence this error message should not occur.
Action	Contact your software supplier.
WEPEBE0017	Failed to send event to event bus using JMS connection alias "{0}" and topic "{1}".
Explanation	An error occurred when trying to send an output event to the event bus.
Action	Check the supplied stack trace for details.
WEPEBE0018	Error deleting JMS trigger "{0}".
Explanation	An error occurred when trying to delete the given JMS trigger.
Action	Check the supplied stack trace.
WEPEBE0019	Error creating JMS trigger for input stream "{0}".
Explanation	An error occurred when creating the JMS trigger for the given input stream.
Action	Check the supplied stack trace.
WEPEBE0020	Error deleting JMS trigger for input stream "{0}".
Explanation	An error occurred when trying to delete the JMS trigger for the given input stream.
Action	Check the supplied stack trace.
WEPEBE0028	Trigger "{0}" not yet active (current thread count is {1}).
Explanation	A timeout occurred when waiting for activation of the given JMS trigger.
Action	Check the status of the JMS connection alias using Integration Server tooling and the Integration Server log file.

WEPEBE0029	Internal error: unexpected exception occurred.
Explanation	An internal error occurred.
Action	Check the provided stack trace for further details.
WEPEBE0030	Query "{0}" with JMS binding does not have a declared output event type.
Explanation	A query that publishes output events to the Event Bus must declare an output event type.
Action	Check the output settings for the query and verify that the query declares an output event type.
WEPEBE0032	Failed to initialize Nirvana libraries.
Explanation	Event Server is configured to use Nirvana as the JMS provider. However, the corresponding libraries could not be loaded as expected.
Action	Check the path specified in the <EventBusLibraryFolder> element of the EDA configuration file. This configuration file is located at <installRoot>/common/conf/ConfigEDAOrchestrator.xml. The respective folder should contain nJMS.jar, nClient.jar, nP2P.jar, and nAdminAPI.jar.
WEPEBI0025	JMS connection alias "{0}" already exists, will not be updated
Explanation	An attempt was made to create the given JMS connection alias, but it already exists. Hence, it will not be updated or re-created, thus preserving specific settings.
Action	No action required.
WEPEBI0031	Bind JNDI key "{0}" to connection factory for Nirvana Realm Server "{1}".
Explanation	In auto-configuration mode, the Event Server is registering a connection factory for the configured Nirvana realm server instance in the JNDI registry.
Action	No action required.
WEPEBW0026	JMS connection alias "{0}" is not enabled.
Explanation	There may be an issue with the configuration of the JMS connection alias or the access to the underlying JMS provider.
Action	Check the configuration and status of the JMS connection alias using the Integration Server tooling.

WEPEBW0027	Waiting for trigger "{0}" to become active.
Explanation	The JMS trigger with the given name exists but is not yet active.
Action	No action required. The Event Server will poll for some seconds until the JMS trigger becomes active.
WEPESE0003	License check failed using file {0}: {1}
Explanation	An error occurred when checking the supplied license file.
Action	Obtain a correct license file.
WEPESE0007	Unexpected error during Event Server startup.
Explanation	An error occurred during the startup sequence for Event Server.
Action	Check the preceding error message.
WEPESE0008	Error occurred while stopping Event Server.
Explanation	An error occurred while attempting to stop the Event Server.
Action	Check the supplied stack trace.
WEPESE0010	Failed to create directory with name "{0}".
Explanation	The Event Server could not create the specified directory.
Action	Check the event server configuration and file system privileges.
WEPESE0011	Property "{0}" is not set.
Explanation	The given property is not set in the config.ini file.
Action	Check the configuration file. You may need to re-install the Event Server due to preceding installation errors.
WEPESE0012	Bundle context not available - cannot start the Event Server
Explanation	An internal error occurred during the event server startup.
Action	Contact your software supplier.
WEPESE0013	Integration Server failed to start in {0} seconds.
Explanation	As the Event Server depends on services provided by the Integration Server, it needs to wait for the Integration Server to start up. However, the maximum wait time has been exceeded.
Action	Check Integration Server's server.log file for the possible reason.

WEPSE0016	Integration Server not started after {0} seconds.
Explanation	As Event Server depends on services provided by Integration Server, it needs to wait for the Integration Server to start up. This message indicates that a timeout occurred.
Action	Check Integration Server's server.log file.
WEPSE0017	Trigger name "{0}" is not registered.
Explanation	The Event Server received an input event from an unexpected JMS trigger.
Action	Check why the given JMS trigger exists and is not known by the Event Server.
WEPSE0018	Error dispatching event to input stream corresponding to trigger {0} - event: {1}
Explanation	An error occurred while dispatching an input event.
Action	Check the supplied stack trace.
WEPSE0019	The source adapter must not be null.
Explanation	This is an unexpected internal error.
Action	Contact your software supplier.
WEPSE0021	License check failed.
Explanation	An error occurred when attempting to check the license file.
Action	Check the supplied stack trace.
WEPSE0022	No license file configured for Event Server.
Explanation	The license file used by the Event Server is normally located via the config.ini file, but the required entry is not available.
Action	Check the config.ini file.
WEPSE0023	Failed to read license file at {0}.
Explanation	The Event Server failed to read the license file at the given location.
Action	Check the supplied stack trace.
WEPSE0024	Found invalid product code {0}, expected {1}.
Explanation	The product code in the license file does not match the expected value.
Action	Obtain a valid license file.

WEPESE0025	Found invalid product version {0}, expected {1}.
Explanation	The product version in the license file does not match the expected value.
Action	Obtain a valid license file.
WEPESE0027	Server configuration file at "{0}" does not exist.
Explanation	The server configuration file that is required by the Event Server at startup time does not exist.
Action	Check your installation.
WEPESE0028	Required configuration element "{0}" not found in event server configuration file "{1}".
Explanation	The given element that is required within the event server configuration file does not exist.
Action	Check and fix the event server configuration file.
WEPESE0029	Error in event server configuration file "{0}", automatic creation of topics requires either Broker or Nirvana or NERV to be configured.
Explanation	If the event server is configured for automatic creation of topics, the Broker or Nirvana instance to be used must be configured as well. As an alternative, event bus connectivity via NERV may be configured.
Action	Check the event server configuration file.
WEPESE0031	Failed to read file {0} for computation of checksum.
Explanation	An exception occurred when attempting to compute the checksum for the given file.
Action	Check the existence and access privileges for the given file.
WEPESE0032	Error occurred during event processing - cause: "{0}".
Explanation	There are various possible reasons for the occurrence of an exception while processing events inside the Event Server, e.g. events not matching the event type schema, arithmetic exceptions, loss of database connections, etc.
Action	Check the cause (if available) and the supplied exception details.

WEPESE0033	Dropped {1} events from query {0} - size of output queue is {2}.
Explanation	In order to maintain Event Server stability, events from the specified query have been dropped.
Action	Increase the memory of the Event Server or move some of the queries to another Event Server.
WEPESE0035	Decoupling thread for query {0} has been interrupted.
Explanation	The thread that processes events from the specified query has been interrupted.
Action	Check the supplied exception details.
WEPESE0036	Unable to stop event server worker thread.
Explanation	The event server has failed to stop one of its worker threads.
Action	Check the supplied exception details.
WEPESE0037	Invalid or missing configuration of event type store location: "{0}".
Explanation	In order to start successfully, the Event Server must be configured to use a valid location of the event type store.
Action	Check the setting of the event type store location (i.e. the value inside <EventTypeStoreLocation>) in the EDA configuration file. This file is typically located at <installRoot>/common/conf/ConfigEDAOrchestrator.xml.
WEPESE0042	Cluster is still not online after {0} seconds.
Explanation	The Event Server failed to re-establish a connection to the Terracotta server within the given time interval.
Action	Check whether the Terracotta server is up and is available in the network. Furthermore, check that the reconnect time interval has been defined correctly in the configuration.
WEPESE0043	Event server node "{0}" is no longer connected to the cluster.
Explanation	The Event Server failed to preserve the connection to the Terracotta cluster server. This might be due to network issues or because the Terracotta server failed or was mis-configured.
Action	Check the reason why the connection between the Event Server and the Terracotta cluster server was disconnected.

WEPESE0044	Cache provider has been initialized already.
Explanation	This is an internal error.
Action	Contact your software supplier.
WEPESE0047	Unexpected RuntimeException occurred.
Explanation	An unexpected exception occurred within the Event Server.
Action	Check the exception stack trace for further details.
WEPESE0048	Unable to cache database content.
Explanation	An error occurred when trying to cache database content.
Action	Check the stack trace for error details.
WEPESE0049	Could not remove unknown cache "{0}".
Explanation	Internal processing error: an error occurred when trying to remove a cache.
Action	Contact your software supplier.
WEPESE0050	Illegal combination of start={0}, end={1} when trying to register database source cache.
Explanation	This is an internal processing error.
Action	Contact your software supplier.
WEPESE0051	Timeout occurred after {0} seconds when waiting for notification from all cluster members ({1}).
Explanation	An unexpected error caused the synchronization between cluster members to fail.
Action	Check the cluster setup and the state of cluster members.
WEPESE0052	Synchronization of check results failed: obtained "{0}" from node "{1}" and "{2}" from node "{3}".
Explanation	Event Servers within the same cluster obtained different results during synchronization.
Action	Check the details of the provided error message.

WEPESE0053	Element with key "{0}" not found in cache "{1}".
Explanation	This is an internal processing error that occurred during synchronization within cluster.
Action	Contact your software supplier.
WEPESE0054	Error in synchronization across cluster - no entry found for node "{0}" with key "{1}" found in cache "{2}".
Explanation	An internal error during synchronization within the cluster.
Action	Contact your software supplier.
WEPESE0058	Exception occurred when invoking Integration Server service {0}:{1}.
Explanation	An exception occurred when invoking the given Integration Server service.
Action	Check the exception stack trace and the Integration Server log file for error details.
WEPESE0060	Missing Terracotta configuration for Event Server configured to run in high-availability mode.
Explanation	If the Event Server is to run in high-availability mode, it needs to be configured also for usage of the Terracotta server.
Action	Change the configuration of the Event Server as documented.
WEPESE0062	Error occurred when requesting shutdown.
Explanation	An error occurred when trying to shut down the Event Server.
Action	Check the exception stack trace for details.
WEPESE0064	Unsupported approach: {0}.
Explanation	Internal error: the Event Server attempted to use an approach for the representation of event validity which is not supported in this context.
Action	Contact your software supplier.
WEPESE0067	The current memory usage '{0}' exceeds L2-threshold '{1}'.
Explanation	The JVM heap memory consumption of the Event Server has exceeded the given threshold.
Action	Check the product documentation for the configuration of JVM and of Event Server specific memory thresholds.

WEPESE0068	The current memory usage '{0}' exceeds L3-threshold '{1}'.
Explanation	The JVM heap memory consumption of the Event Server has exceeded the given threshold.
Action	Check the product documentation for the configuration of JVM and of Event Server specific memory thresholds.
WEPESE0070	Configuration check: The setting of "{0}" ({1}) on this machine and on the other cluster members does not match.
Explanation	A critical inconsistency of parameter settings for Event Servers in the cluster was detected.
Action	Change the setting of the respective parameter to be consistent.
WEPESE0071	Configuration check: The setting of "{0}" ({1}) does not match the setting of "{2}" ({3}).
Explanation	An inconsistent configuration of the Event Server was detected: the setting for the two given parameters is not allowed.
Action	Adapt the configuration as required.
WEPESE0075	Invalid setting of initial handshake timeout: "{0}" - using default "{1}".
Explanation	The initial handshake timeout must not be negative. The default is unlimited, which corresponds to a setting of 0.
Action	Fix the setting of <initial-handshake-timeout> in the Event Server configuration file EventServerCfg.xml.
WEPESE0076	Invalid setting of master lock acquisition timeout: "{0}" - using default "{1}".
Explanation	The master lock acquisition timeout must not be negative. A default of 30 seconds is used.
Action	Fix the setting of <masterlock-acquisition-timeout> in the Event Server configuration file EventServerCfg.xml.
WEPESE0077	Invalid setting of refresh period for the health check: "{0}" - using default "{1}".
Explanation	The refresh period for the health check must not be negative.
Action	Fix the setting of <health-check-refresh-period> in the Event Server configuration file EventServerCfg.xml.

WEPESE0078	Invalid setting of state logging frequency: "{0}" - state logging is deactivated.
Explanation	The configured state logging frequency must be a non-negative integer.
Action	Fix the setting of <health-check-log-state-frequency> in the Event Server configuration file EventServerCfg.xml.
WEPESE0079	An error has occurred while loading the high-availability configuration.
Explanation	During startup, the Event Server loads the high-availability configuration from the <ha-config> section of the Event Server configuration file.
Action	Fix the Event Server configuration file EventServerCfg.xml according to the error details provided by the stack trace.
WEPESE0080	Internal error when attempting to serialize adapter parameters.
Explanation	This is an internal error which should never occur.
Action	Contact your software supplier.
WEPESE0081	Internal error: the dispatcher proxy has the wrong dispatcher configured: "{0}".
Explanation	This is an unexpected internal product error.
Action	Contact your software supplier.
WEPESE0087	Subscription for "{0}" has failed.
Explanation	During the deployment of the Continuous Query application, the creation of the NERV subscription for "{0}" has failed.
Action	Check the server log file for more information.
WEPESE0089	Unsubscribe for "{0}" has failed.
Explanation	During the undeployment of the Continuous Query application an error occurred while removing the NERV subscription for "{0}".
Action	Check the server log file for more information.
WEPESE0090	Unexpected error while creating the input stream adapter.
Explanation	During the deployment of the Continuous Query application an unexpected error occurred.
Action	Check the server log file for more information.

WEPES0091	During deployment an unexpected error occurred. The OSGi runtime service infrastructure is not available.
Explanation	Event Server makes use of OSGi runtime services to deploy Continuous Query applications. These services are not available.
Action	Check the server log file for more information.
WEPES0092	During the undeployment of "{0}" an unexpected error occurred.
Explanation	An unexpected error occurred while undeploying the Continuous Query application.
Action	Check the server log file for more information.
WEPES0093	An unexpected error occurred while trying to send out the event "{0}".
Explanation	Event Server was not able to publish the event "{0}".
Action	Check the server log file for more information.
WEPES0095	Required services are not available after {0} seconds.
Explanation	Event Server relies on various internal services which are started asynchronously and have not been started after the expected maximum time interval.
Action	Check the Event Server's log file.
WEPESI0026	Event Server has started successfully
Explanation	All components of the Event Server have started successfully.
Action	No action required.
WEPESI0030	Event Server is not configured to create JMS and JNDI aliases.
Explanation	The event server configuration file does not contain the settings required for automatic creation of the JMS connection alias and the JNDI provider alias. This functionality is only available when using the webMethods Broker.
Action	No action required.
WEPESI0038	Register cluster member "{0}".
Explanation	This action is logged when an event server joins a cluster during startup.
Action	No action required.

WEPESI0039	Unregister cluster member "{0}".
Explanation	A cluster member is either unregistered during normal shutdown of the Event Server or when the Event Server gets a notification that another cluster member has left the cluster without removing itself from the cluster member registry e.g. because it aborted abnormally.
Action	No action required.
WEPESI0041	Cluster is online again, successfully reconnected to cluster member registry.
Explanation	The Event Server has successfully reconnected to the Terracotta server and succeeded in locating the cluster member registry.
Action	No action required.
WEPESI0045	Retrieving Terracotta configuration from {0}.
Explanation	When starting up, the Event Server reads the the Terracotta configuration from the given location.
Action	If any issues arise you should check the Terracotta configuration at the given location.
WEPESI0046	Using cache manager with name "{0}".
Explanation	The name of the cache manager determines the set of Event Servers forming a cluster; only Event Servers using the same name belong to the same logical cluster.
Action	You may want to compare the given cache manager name with the one reported for other Event Servers which will belong to the same logical cluster.
WEPESI0055	Memory usage threshold for load shedding set to {0}.
Explanation	There is a threshold for discarding outbound events when heap memory consumption exceeds the given fraction of overall available memory available to the Java virtual machine. This threshold has been set to the given value.
Action	No action required.
WEPESI0056	Maximum output queue size for load shedding has been set to {0}.
Explanation	There is a threshold for discarding outbound events when the size of an output queue due to a single query exceeds the given number of elements. This threshold has been set to the given value.
Action	No action required.

WEPESI0057	Preserve heartbeats set to {0}.
Explanation	When this property is set to false (the default), outgoing heartbeats not yet sent to the output channel are discarded in the output queue if there is a follow-up event or heartbeat on the same channel also indicating progress of time.
Action	No action required.
WEPESI0059	Joining Event Server cluster..
Explanation	The Event Server is about to join the configured cluster.
Action	No action required.
WEPESI0072	The consistency of the configuration has been checked.
Explanation	During startup, the Event Server performs checks of the local configuration.
Action	No action required.
WEPESI0073	The consistency of the configuration with respect to the other HA cluster nodes has been checked.
Explanation	When configured to run in a cluster, the Event Server compares its configuration with all other Event Servers in the cluster which were already started.
Action	No action required.
WEPESI0082	Cache "{0}" has been cleared.
Explanation	All elements of the Terracotta cache "{0}" have been removed.
Action	No action required.
WEPESI0083	The registry is removed from meta-data cache "{0}".
Explanation	The registry has been removed from the meta-data cache "{0}". The new size of the cache is "{1}".
Action	No action required.
WEPESI0084	The cache "{0}" is removed from local cache manager.
Explanation	The cache with name "{0}" has been removed from the local cache manager.
Action	No action required.

WEPESI0085	The meta-data cache has been removed from the local cache manager.
Explanation	The metadata cache has been removed from the local cache manager.
Action	No action required.
WEPESI0086	Registering usage of "{0}" in node "{1}".
Explanation	The usage of cache "{0}" in Event Server node "{1}" has been registered successfully.
Action	No action required.
WEPESI0096	Event type store is located at "{0}".
Explanation	This message reports the location of the event type store.
Action	No action required.
WEPESW0020	Current (logical) processor count {0} exceeds maximum allowed value of {1} (physical) CPUs.
Explanation	A mismatch between the licensed and the actual processor count was detected.
Action	No action required - the Event Server does not strictly enforce this constraint.
WEPESW0034	Dropped {1} heartbeats for query {0} - size of output queue is {2}.
Explanation	In order to maintain Event Server stability, heartbeat events from the specified query have been dropped.
Action	Increase the memory of the Event Server or move some of the queries to another Event Server.
WEPESW0040	Cluster is not online.
Explanation	The Event Server lost its connection to the Terracotta server and will try to reconnect.
Action	Check whether there are stability issues with the network or the Terracotta server.
WEPESW0061	Shutdown of Event Server has been requested - reason: {0}.
Explanation	Due to the given reason a shutdown of the Event Server has been triggered.
Action	Check the reason in order to determine how to proceed.

WEPESW0063	Shutdown requested due to high-availability status.
Explanation	An error condition in the high-availability sub-system has triggered a shutdown of the Event Server.
Action	Check the preceding messages in the Event Server log.
WEPESW0065	Shutdown has been requested via OSGi console.
Explanation	A shutdown of the Event Server has been triggered via the OSGi console. The OSGi console is not enabled by default but has obviously been enabled. This might cause a vulnerability risk.
Action	You might want to disable access to the Event Server via the OSGi console.
WEPESW0066	The current memory usage '{0}' exceeds L1-threshold '{1}'.
Explanation	The JVM heap memory consumption of the Event Server has exceeded the given threshold.
Action	Check the product documentation for configuration of JVM and of Event Server specific memory thresholds.
WEPESW0069	Configuration check: The setting of "{0}" ({1}) on this machine and on the other cluster members does not match.
Explanation	A non-critical inconsistency of parameter settings for Event Servers in the cluster was detected.
Action	Check the parameter settings for the Event Servers in the cluster.
WEPESW0088	Event type "{0}" does not have a target namespace definition. Adding default namespace "{1}".
Explanation	An EDA Event Type must contain a target namespace definition, but Event Type "{0}" does not.
Action	Check "{0}" and add a target namespace.
WEPESW0094	Your Event Server license will expire in {0} days.
Explanation	Your Event Server license has an expiration date which will be reached after the given number of days from now.
Action	You should get a new license key as soon as possible.

WEPSCE0001	Unsupported type: {0}
Explanation	The Event Server does not support the used type {0}. Please refer to the documentation regarding supported types.
Action	Open the event type in the Event Type Editor and change the type of the element. The Event Type Editor provides a list of valid types in the Properties view.
WEPSCE0002	Unsupported builtin base type: {0}
Explanation	The Event Server does not support the used type {0}. Please refer to the documentation regarding supported types.
Action	Open the event type in the Event Type Editor and change the type of the element. The Event Type Editor provides a list of valid types in the Properties view.
WEPSCE0003	Could not find matching field: {0}
Explanation	While converting an Event Type into a relation, the element {0} could not be processed.
Action	Check the Event Type regarding correctness.
WEPSCE0004	Illegal time stamp: "{0}"
Explanation	There was an error while transforming the given XML event into a relational event.
Action	Check the XML event regarding correctness.
WEPSCE0005	invalid digit
Explanation	The provided date is invalid. It contains a character that is not a digit.
Action	Please check the given date and correct the invalid date.
WEPSCE0006	value not available
Explanation	The end date for the given event is not available.
Action	Please provide an end date for the event.
WEPSCE0007	invalid timezone
Explanation	The provided timezone information is not correct.
Action	Please correct the timezone.

WEPSCE0010	File name "{0}" is not consistent with name property "{1}"
Explanation	Continuous Query development artifacts are stored as an XML document on the file system. The name of the file must match the name of the XML root element.
Action	Please change the file name to match the name of the XML root element of the given resource.
WEPSCE0011	Reference to unknown input event type "{0}"
Explanation	The event type "{0}" cannot be resolved.
Action	If the error occurs at design time in the Software AG Designer, you need to establish a project reference to the event type project hosting the referenced type. If the error occurs at run-time, please check if the Event Type Store has been populated. The Event Type Store is located at InstallationDir/common/EventTypeStore.
WEPSCE0012	Reference to unknown output event type "{0}"
Explanation	The event type "{0}" cannot be resolved.
Action	If the error occurs at design time in the Software AG Designer, you need to establish a project reference to the event type project hosting the referenced type. If the error occurs at run-time, please check if the Event Type Store has been populated. The Event Type Store is located at InstallationDir/common/EventTypeStore.
WEPSCE0013	Declared output event type "{0}" does not match query output record format: {1}.
Explanation	The output schema of the query does not match the schema of the declared event type "{0}".
Action	Please review the SELECT clause of the query and align it to the output type "{0}". Alternatively you can select another existing event type as the output event type or you might want to generate a new event type.
WEPSCE0015	Unknown query identifier: {0}
Explanation	The identifier {0} is unknown.
Action	Please check the identifier and correct the value.
WEPSCE0016	Neither JMS connection alias nor channel specified for input/output processing
Explanation	The fields for the JMS connection alias and channel have been left empty, but are required by the system.
Action	Please provide input for the fields JMS connection alias and channel.

WEPSCE0017	No JMS connection alias specified for input/output processing
Explanation	The field JMS connection alias has been left empty, but is required by the system.
Action	Please provide input for the field JMS connection alias.
WEPSCE0018	No channel specified for input/output processing
Explanation	The field channel has been left empty, but is required by the system.
Action	Please provide input for the field channel.
WEPSCE0019	Unable to add {0} to classpath for udf loading.
Explanation	The resource {0} cannot be added to the Java classpath of the project.
Action	Please check the log file for the corresponding exception.
WEPSCE0020	Unable to load udf class {0}.
Explanation	The class hosting the user-defined function {0} cannot be loaded.
Action	Please check if the class is available within the source path of the project.
WEPSCE0021	Invalid type "{0}" of parameter at position {1} of method {2}
Explanation	The type "{0}" is not supported.
Action	Please refer to user documentation regarding supported types when invoking a user-defined function.
WEPSCE0022	Invalid return type "{0}" of method {1}
Explanation	The return type of the user-defined function {1} is not supported.
Action	Please refer to the user documentation to see the supported types.
WEPSCE0023	Exception occurred while invoking user-defined function {0}
Explanation	An exception occurred while invoking the user-defined function {0}.
Action	Please review the code of the user-defined function and handle the exception within the function.
WEPSCE0024	The token "{0}" is unexpected. The first token in a line must be either EVENT, HEARTBEAT or #.
Explanation	The first token indicates the type of the line. There are three different types available: the line represents either an event or a heartbeat or a comment.
Action	Please use either EVENT, HEARTBEAT or # to indicate the line type.

WEPSCE0025	The name of the Input Stream must not be null.
Explanation	The Input Stream name is empty, but is required for an event or heartbeat.
Action	Please specify the name of the Input Stream to which the event or heartbeat refers.
WEPSCE0026	The start timestamp must not be null.
Explanation	The start timestamp is empty, but is required.
Action	Please specify a start timestamp.
WEPSCE0027	Unexpected end of line.
Explanation	An unexpected end of line was found.
Action	Please check the given line.
WEPSCE0028	A heartbeat line must end with the start timestamp.
Explanation	The given heartbeat line is not correct, as additional data is present after the start timestamp.
Action	Please remove any data after the start timestamp.
WEPSCE0029	End timestamp "{0}" is not greater than start timestamp "{1}" for event in Input Stream "{2}".
Explanation	The end timestamp must be greater than the start timestamp.
Action	Fix the creation of timestamps for events. For chronon events you may omit the end timestamp completely.
WEPSCE0030	Error reading timestamp "{0}"; expected format is YYYY-MM-DDThh:mm:ss.sTZD with TZD being either Z (UTC designator) or +hh:mm or -hh:mm (time zone offsets).
Explanation	The provided timestamp "{0}" is invalid as it does not comply with the expected format YYYY-MM-DDThh:mm:ss.sTZD.
Action	Information regarding timezones and outlook of timestamps is given by the W3C at http://www.w3.org/TR/timezone/
WEPSCE0031	Invalid use of double quotes. Check whether the closing double quote is correctly set and double quote pairs are correctly used.
Explanation	The usage of double quotes is not correct.
Action	Please review the usage of double quotes. Any starting quote must be followed by a closing quote.

WEPSCE0032	Only whitespace characters are allowed before and after a quoted sequence.
Explanation	The format of the event sequence line is not correct. When using a quoted sequence there must not be any character before or after the quoted sequence except whitespace.
Action	Please review the event sequence line and remove any character before or after the quoted sequence.
WEPSCE0033	The Input Stream "{0}" is unknown.
Explanation	The event sequence line refers to an Input Stream that does not exist within the project.
Action	Please use a name of one of the existing Input Streams within the project.
WEPSCE0034	The Input Stream "{0}" is referencing an unknown Event Type.
Explanation	The definition of the referred Input Stream "{0}" is not correct. The Input Stream is linked to an unknown Event Type.
Action	Please review the definition of the referred Event Type and specify an existing type.
WEPSCE0035	Illegal order of start timestamps for Input Stream "{2}": current timestamp "{0}" is earlier than preceding timestamp "{1}".
Explanation	The start timestamps of events of the same Input Stream must be in non-descending chronological order.
Action	Please review the start timestamp and change it to a value that is after the start timestamp of the preceding event of the same stream.
WEPSCE0036	Validity ({0} ms) of event in Input Stream "{2}" exceeds maximum configured validity ({1} ms).
Explanation	The provided end timestamp "{0}" is not correct. The difference between it and the start timestamp is greater than the maximum event validity specified for the Input Stream.
Action	Please review the end timestamp and choose a value such that the event validity is less than or equal to the maximum event validity of the Input Stream. You may also revise the configured maximum event validity for the given input stream.
WEPSCE0037	The Event Type is invalid.
Explanation	The Event Type is invalid.
Action	Please review the Event Type and specify a valid type.

WEPSCE0038	The input zip stream cannot be null!
Explanation	During an export of the project an internal exception occurred.
Action	Please check the error log file for details.
WEPSCE0039	Unable to create zip file object {0}
Explanation	During the export of the project an internal exception occurred.
Action	Please check the error log file for details.
WEPSCE0040	The destination directory cannot be null or a file!
Explanation	The destination directory for the export is invalid. It is either null or an existing file.
Action	Please specify an existing directory.
WEPSCE0041	Error closing zip file "{0}"
Explanation	During the export of the project an internal exception occurred.
Action	Please check the error log file for details.
WEPSCE0042	Directory structure for "{0}" was not created
Explanation	During the export of the project an internal exception occurred.
Action	Please check the error log file for details.
WEPSCE0043	Cannot create directory structure for "{0}"
Explanation	During the export of the project an internal exception occurred.
Action	Please check the error log file for details.
WEPSCE0044	Error creating file for "{0}"
Explanation	During the export of the project an internal exception occurred.
Action	Please check the error log file for details.
WEPSCE0045	Error preparing file for file extraction "{0}"
Explanation	During the export of the project an internal exception occurred.
Action	Please check the error log file for details.

WEPSCE0046	Cannot write to file "{0}"
Explanation	During the export of the project an internal exception occurred.
Action	Please check the error log file for details.
WEPSCE0047	Error writing to file
Explanation	During the export of the project an internal exception occurred.
Action	Please check the error log file for details.
WEPSCE0048	File object was not deleted - {0}
Explanation	During the export of the project an internal exception occurred.
Action	Please check the error log file for details.
WEPSCE0049	Directory object not deleted - {0}
Explanation	During the export of the project an internal exception occurred.
Action	Please check the error log file for details.
WEPSCE0050	Unable to convert incoming XML event to tuple.
Explanation	An exception occurred while processing the event; the XML representation does not match the given event type schema.
Action	Please check the XML string of the event for errors or inconsistency with the specified event type schema.
WEPSCE0051	Wrong number of arguments: queryName required.
Explanation	An internal error occurred during the logging of an event.
Action	Please check the error log file for details.
WEPSCE0052	Wrong number of arguments: only queryName and encoding allowed.
Explanation	An error occurred during the logging of an event.
Action	Please check the error log file for details.
WEPSCE0054	Value "{0}" is not a valid channel name.
Explanation	The given value "{0}" is not correct. The name must begin with an alphabetic character, followed by any combination of alphanumeric characters, underscores and colons.
Action	Please remove invalid characters.

WEPSCE0055	Query "{0}" has cyclic dependency on itself
Explanation	A continuous query may get its input from sources like input streams, database sources and other queries. However, it may not refer to itself, neither directly nor indirectly via other continuous queries.
Action	Remove the cyclic dependency.
WEPSCE0056	Exception occurred during creation of archive file.
Explanation	An unexpected exception occurred during the creation of an archive file.
Action	Check the stack trace for details.
WEPSCE0057	Failed to remove folder {0} from archive {1}.
Explanation	An exception occurred when trying to remove the given folder from the deployment archive.
Action	Check the contents and the access privileges for the archive.
WEPSCE0059	Failed to create compilation output directory {0}.
Explanation	Failed to create the given compilation output directory.
Action	Check the path and file system access privileges for the current process.
WEPSCE0060	Failed to retrieve location of bundle {0}.
Explanation	This is an unexpected error during internal processing.
Action	Contact your software supplier.
WEPSCE0061	No secure storage is configured.
Explanation	This is an unexpected internal error.
Action	Contact your software supplier.
WEPSCE0062	Source name "{0}" is not valid. Another source exists with different case.
Explanation	The source name is not valid. Another artifact exists with the same name but with a different combination of uppercase and lowercase letters.
Action	Please use another name for the resource.

WEPSCE0064	Failed to construct valid name for filterable property from "{0}".
Explanation	Filterable property names need to be consistent with the restrictions imposed for properties by the JMS specification.
Action	Check how to modify the given path expression. Note in particular that the property name must not start with JMS.
WEPSCE0065	Error occurred when loading user-defined class "{0}".
Explanation	The Event Engine failed to load the user-defined class with the given name.
Action	Check whether other classes or class libraries are missing and add them to the continuous query project.
WEPSCE0066	Error on input stream {0} occurred when processing heartbeat with timestamp {1}: {2}.
Explanation	An exception occurred while processing an incoming heartbeat.
Action	Check the provided error details.
WEPSCE0067	Error on input stream {0} occurred when processing event ({1}) with validity time interval [{2},{3}]: {4}.
Explanation	An exception occurred while processing an incoming event.
Action	Check the provided error details.
WEPSCE0068	Error on input stream {0} occurred when processing event ({1}) with start timestamp {2}: {3}.
Explanation	An exception occurred while processing an incoming event.
Action	Check the provided error details.
WEPSCE0069	Errors have occurred while cleaning the engine for project "{0}":
Explanation	An internal error occurred while attempting to unregister assets with the Event Engine.
Action	Check the additional details provided in conjunction with this error message.
WEPSCE0070	Class {1} defines a user-defined operator with name "{0}" which is already defined in class {2}.
Explanation	Different classes may only define user-defined operators with different names.
Action	Change the name of one of the user-defined operators to avoid the conflict.

WEPSCE0071	Class "{0}" is not a subclass of "{1}".
Explanation	A valid implementation class for a user-defined operator must be a subclass of the given class.
Action	Fix your implementation of a user-defined operator .
WEPSCE0072	Class "{0}" does not have exactly one public constructor.
Explanation	A valid implementation class for a user-defined operator must have exactly one constructor.
Action	Fix the implementation of the user-defined operator.
WEPSCE0073	Failed to create instance of user-defined operator class "{0}" ({1}).
Explanation	An error occurred when attempting to instantiate a user-defined operator.
Action	Check the error log for additional details.
WEPSCE0074	Data type of parameter number {1} of constructor of user-defined operator class "{0}" is invalid.
Explanation	The constructor of a user-defined operator may only use datatypes supported as literals in SQL.
Action	Check the documentation for valid data types.
WEPSCE0075	Class "{0}" does not have a method: public static StreamMetaData getOutputStreamMetaData(StreamMetaData[], RecordMetaData[], Object[]).
Explanation	A user-defined operator class must provide a static method with the given signature which allows the metadata of the output stream to be computed without creating an instance of the operator.
Action	Add a method public static StreamMetaData getOutputStreamMetaData(StreamMetaData[], RecordMetaData[], Object[]) to the implementation of a user-defined operator.
WEPSCE0076	Unexpected UserDefinedOperatorException occurred when calling {0}.getOutputStreamMetaData() with identical parameters.
Explanation	The exception was unexpected because a preceding call to the method with the same parameters was successful.
Action	Ensure that the behaviour of the public static StreamMetaData getOutputStreamMetaData(StreamMetaData[], RecordMetaData[], Object[]) is identical when called with identical parameters.

WEPSCE0077	Unexpected exception during output stream-metadata computation.
WEPSCE0078	Unable to determine output stream-metadata due to exception.
WEPSCE0079	The class "{0}" does not implement the method "{1}" with the expected signature.
Explanation	The given class should implement the given method in order to provide an appropriate implementation of a user-defined aggregate.
Action	Adapt the implementation as expected.
WEPSCE0080	Invalid method call - PN mode not supported by this user-defined aggregate.
Explanation	This user-defined aggregate does not fully support PN mode. This method should not be called or must be implemented appropriately.
Action	Fix the implementation of the user-defined aggregate.
WEPSCE0081	Failed to instantiate user-defined aggregation function "{0}".
Explanation	A class implementing a user-defined aggregation function must have a public default constructor. Referenced classes must be available within the project.
Action	Ensure that the aggregation function has a public default constructor and all referenced classes are available as a source file or JAR in the current project.
WEPSCE0082	Invalid parameter type "{1}" of user-defined aggregation function "{0}".
Explanation	You have specified an unsupported type for the parameter passed to the user-defined aggregation function.
Action	Change the type of the parameter passed to the user-defined aggregation function.
WEPSCE0083	Invalid result type "{1}" of user-defined aggregation function "{0}".
Explanation	You have specified an unsupported type for the result returned by the user-defined aggregation function.
Action	Change the type of the result returned by the user-defined aggregation function.
WEPSCE0089	Received inconsistent input event: no body has been provided, but not marked as heartbeat as well.
Explanation	An EDA event must either provide an XML body or a heartbeat.
Action	Ensure that either the event publisher provides a body or the header field "Kind" is equal to "Heartbeat".

WEPSCI0008	Start logging {0} - system time: {1}
Explanation	The Event Server starting logging for source {0} at system time {1}.
Action	No action required.
WEPSCI0009	End logging {0} - system time: {1}
Explanation	The Event Server stopped logging for source {0} at system time {1}.
Action	No action required.
WEPSCW0014	No output event type specified
Explanation	The query does not declare an event type describing the schema of the generated events.
Action	Please select an existing event type as the output type for the query. Alternatively you can create a new event type.
WEPSCW0053	The event type name specified in the channel is not consistent with the selected input/output event type.
Explanation	The event type name specified in the JMS channel binding is not consistent with the event type assigned to the resource.
Action	Please provide a consistent event type name in the JMS channel binding.
WEPSCW0058	Found unexpected entry {0} in deployment archive {1}.
Explanation	The given unexpected entry was found while analyzing the content of the CAR deployment archive.
Action	Use the export functionality provided by Continuous Query Development in webMethods Designer in order to create a valid CAR file.
WEPSCW0063	The name "{0}" is an SQL keyword or Java type name. If it is used in a query it must be enclosed in double quotes.
Explanation	The name is an SQL keyword or a Java data type. While using it within a query string it must be enclosed in double quotes.
Action	Consider using a different name.

WEPCW0084	The schema node "{0}" with unsigned base type "{1}" is mapped to the field "{2}" with signed Java type "{3}".
Explanation	The value range of the unsigned XML schema data type and of the signed Java type are different. This may lead to errors during value conversion back and forth between XML and Java.
Action	As Java does not offer unsigned datatypes, you have to ensure that the application only uses values that are in the overlapping value range.