

webMethods EntireX

Installation under z/VSE

Version 9.6

April 2014

This document applies to webMethods EntireX Version 9.6.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 1997-2014 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors..

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA, Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://documentation.softwareag.com/legal/>.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <http://documentation.softwareag.com/legal/> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices and license terms, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". This document is part of the product documentation, located at <http://documentation.softwareag.com/legal/> and/or in the root installation directory of the licensed product(s).

Document ID: EXX-INSTALL-96-20140628VSE

Table of Contents

Installing EntireX under z/VSE	v
1 General Information	1
Contents of Installation Medium	2
Migrating from EntireX Version 7.2.3	2
2 Installing EntireX Broker under z/VSE	5
Prerequisites for EntireX Broker	6
Contents of Sublibrary EXX960	6
Copying the Contents of the Installation Medium to Disk	8
Preparing for Installation	9
Installing EntireX Broker	10
Installation Verification	14
Hints for Setting up Broker JCL in z/VSE	17
3 Installing the z/VSE EntireX RPC Servers	21
Contents of Sublibrary EXP960	22
Installing the CICS RPC Server	23
Installing the Batch RPC Server	28
Installation Verification	33
4 Installing EntireX Security under z/VSE	37
Installing EntireX Security for Broker Kernel	38
Setting up EntireX Security for Broker Stubs	40

Installing EntireX under z/VSE

1 General Information

- Contents of Installation Medium 2
- Migrating from EntireX Version 7.2.3 2

Installation and system prerequisites for z/VSE and other EntireX platforms are described centrally. See *Prerequisites* in the EntireX Release Notes. For communication using Entire Net-Work, Adabas SVC is required (delivered on medium in library WAL826.LIBR). See your Adabas documentation for details.

See also *Administration of Broker Stubs under z/VSE*.

Contents of Installation Medium

The installation medium contains the following base files for z/VSE:

File	Library	Sublibrary	Description
EXB960.INPL			INPL for SYSETB.
EXB960.ERRN			ERRN for SYSETB.
EXP960.LIBR	SAGLIB	EXP960	RPC Server sublibrary.
EXX960.LIBR	SAGLIB	EXX960	EntireX sublibrary.
EXX960.LICS			License file.
EXX960.DC01			Readme file.
WAL826.LIBR	SAGLIB	WAL826	WAL sublibrary.
MLC127.LIBR	SAGLIB	MLC127	MLC sublibrary.

Migrating from EntireX Version 7.2.3

Perform the following steps to migrate from EntireX version 7.2.3:

- [Change the Attribute File](#)
- [Check the License File](#)
- [Replace the EntireX Broker Stubs used by your Applications](#)

Change the Attribute File

New functionality in EntireX version 9.6 led to changes and enhancements of various Broker attributes. This requires the attribute file to be brought up-to-date. A sample attribute file is delivered in `EXX960.LIBR(ETBnnn.ATR)`, which you can use as a basis. If, for example, dynamic memory management is turned on (default and recommended), all `NUM-*` parameters can be omitted. See *Broker-specific Attributes* under *Broker Attributes* in the platform-independent administration documentation.

Check the License File

Ensure the correct license file is referenced in your EntireX Broker startup job control. A sample startup job control is delivered in `EXX960.LIBR(RUNETB.J)`.

Replace the EntireX Broker Stubs used by your Applications

Although existing applications will still run after the migration of EntireX Broker, they should be relinked or replaced, if dynamically loaded, with stubs from version 9.6. See also *Administration of Broker Stubs under z/VSE*.

2 Installing EntireX Broker under z/VSE

■ Prerequisites for EntireX Broker	6
■ Contents of Sublibrary EXX960	6
■ Copying the Contents of the Installation Medium to Disk	8
■ Preparing for Installation	9
■ Installing EntireX Broker	10
■ Installation Verification	14
■ Hints for Setting up Broker JCL in z/VSE	17

Prerequisites for EntireX Broker

Prerequisites for EntireX components are described centrally. See *z/VSE Prerequisites*.

For customers who do not have Adabas installed at their site, the Adabas modules delivered with EntireX in the library WAL826 for the Broker kernel must be installed.

For information on how to install Adabas SVC and configure Adabas cross memory services in batch and CICS, refer to your Adabas documentation.

Contents of Sublibrary EXX960

EntireX Broker, Configuration, Startup JCL and Executables

File	Description
RUNETB.J	EntireX Broker startup JCL.
PSFADA.J	Adabas COMPRESS and ADALOD sample JCL for persistent store creation.
ETB nnn .ATR	EntireX Broker Attribute File.
USRTCHA.A	Sample user translation routine.
ETBSTART.PHASE ETBNUC.PHASE ETBCEE.PHASE	EntireX Broker kernel.
EXXICU.PHASE	International components for Unicode.
USERSEC.PHASE SECUEXIO.PHASE ETBENC.OBJ ETBTB.OBJ ETBUEVA.OBJ ETBUPRE.OBJ ETBVEVA.OBJ ETBVPRE.OBJ	Security exit modules.
BKIMB.OBJ BKIMB.PHASE BROKERB.PHASE BKIMC.OBJ BKIMC.PHASE BROKERC.PHASE	EntireX Broker stubs.

Samples, Utilities and Sources

File	Description
RUNBCOC . J	Client sample JCL.
BCOC . PHASE	Client sample executable.
RUNBCOS . J	Server sample JCL.
BCOS . PHASE	Server sample executable.
RUNCMD . J	Command Services JCL.
ETBCMD . PHASE	Command Services executable.
RUNINFO . J	Information Services JCL.
ETBINFO . PHASE	Information Services executable.
BROKER . PRO CLIENT . PRO CLOGFLT . PRO CONV . PRO NET . PRO POOL . PRO PSF . PRO PSFADA . PRO PSFFILE . PRO PUBLIC . PRO PUBSHR . PRO RESOURCE . PRO SECURITY . PRO SERVER . PRO SERVICE . PRO STATIS . PRO SUBSCBR . PRO TCP . PRO TOPIC . PRO USER . PRO WKRUSAGE . PRO WORKER . PRO	Information Services Profiles.
RUNPUB . J	Publisher sample JCL.
PUB . PHASE	Publisher sample executable.
RUNSUB . J	Subscriber sample JCL.
SUB . PHASE	Subscriber sample executable.
COBDEF . C	COBOL ACI control block definitions.
COBINF . C	COBOL CIS definitions
ETBCDEF . H	C language ACI control block definitions.
ETBCINF . H	C language Command and Information Services API definitions.
ASMDEF . A	Assembler control block definitions.

File	Description
ASMINF.A	Assembler CIS definitions.

EntireX Broker Stubs, Sample JCL, Objects and Executables

See *Administration of Broker Stubs under z/VSE*.

File	Description
BKIMB.J	Sample JCL for linking the batch stub for use with external security
BKIMC.J	Sample JCL for linking the CICS stub for use with external security

Copying the Contents of the Installation Medium to Disk



Note: If you are using SMA, please refer to the System Maintenance Aid Manual, chapter Installing Software AG Products with SMA. If you are *not* using SMA, please follow the instructions below.

This section explains how to:

- Copy data set COPYTAPE.JOB from the installation medium to library.
- Modify this member to conform with your local naming conventions.

The JCL in this member is then used to copy all data sets from installation medium to disk.

If the data sets for more than one product are delivered on the installation medium, the member COPYTAPE.JOB contains the JCL to unload the data sets for all delivered products from the installation medium to your disk, except the data sets that you can directly install from the installation medium, for example, Natural INPL objects.

After that, you will have to perform the individual install procedure for each component.

Step 1: Copy Data Set COPYTAPE.JOB from Installation Medium to Disk

The data set COPYTAPE.JOB (file 5) contains the JCL to unload all other existing data sets from installation medium to disk. To unload COPYTAPE.JOB, use the following sample JCL:

```

* $$ JOB JNM=LIBRCAT,CLASS=0, +
* $$ DISP=D,LDEST=(*,UID),SYSID=1
* $$ LST CLASS=A,DISP=D
// JOB LIBRCAT
* *****
* CATALOG COPYTAPE.JOB TO LIBRARY
* *****
// ASSGN SYS004,NNN <----- tape address
// MTC REW,SYS004
// MTC FSF,SYS004,4
ASSGN SYSIPT,SYS004
// TLBL IJSYSIN,'COPYTAPE.JOB'
// EXEC LIBR,PARM='MSHP; ACC S=lib.sublib' <----- for catalog
/*
// MTC REW,SYS004
ASSGN SYSIPT,FEC
/*
/&
* $$ EOJ

```

where *NNN* is the installation medium address and
lib.sublib is the library and sublibrary of the catalog

Step 2: Modify COPYTAPE.JOB

Modify `COPYTAPE.JOB` to conform with your local naming conventions and set the disk space parameters before submitting this job.

Step 3: Submit COPYTAPE.JOB

Submit `COPYTAPE.JOB` to unload all other data sets from the installation medium to your disk.

Preparing for Installation

Before the following steps can be performed, the EntireX installation medium must be copied to disk. If this has not yet been done, go to [Step 1: Copy Data Set COPYTAPE.JOB from Installation Medium to Disk](#) and follow the instructions there.

To use Software AG's System Maintenance Aid (SMA), you must modify SMA parameter values to suit your environment. Refer to the System Maintenance Aid Readme file (P060).

This installation procedure contains the following SMA jobs and steps:

Install Step	Activity	SMA Job	Job Step
1	<i>Adapt the SMA Parameters</i>	(P060)	
2	<i>Install the EntireX License File</i>	I070	7610
3	<i>Customize the Broker Attribute File</i>	I070	7604
4	<i>Customize the Broker Startup Job Control</i>	I070	7606
5	<i>Define an Adabas Persistent Store</i>	I050	7600 / 7610
6	<i>Load the INPL and ERRN Files (Broker Tutorial)</i>	I061	7600 / 7602
7	<i>Install the Stubs</i>	-	-

Installing EntireX Broker

- Step 1: Adapt the SMA Parameters
- Step 2: Install the EntireX License File
- Step 3: Customize the EntireX Broker Attribute File (ETBnnn.ATR)
- Step 4: Customize the EntireX Broker Startup Job Control (RUNETB.J)
- Step 5: Define an Adabas Persistent Store (Optional)
- Step 6: Load the INPL and ERRN Files: Install the Natural-based EntireX Broker Tutorial Job JSYSETB (Optional)
- Step 7: Install the Stubs

Step 1: Adapt the SMA Parameters

When using Software AG's System Maintenance Aid (SMA), you must modify SMA parameter values to suit your environment. Refer to the System Maintenance Aid readme file (P060).

Step 2: Install the EntireX License File

(SMA Job I070 / Step 7610)

The EntireX license file `EXX960.LICS` is delivered on the installation medium and/or CD.

The license file may reside in a sublibrary. The following FTP command sequence can be used to upload the file to z/VSE and place it into a sublibrary. Please note that the file needs to be uploaded in binary format and requires the record format "stream" on the target system.


```
ftp>
bin
quote site RECFM S
cd SAGLIB.EXX960
put <license_file> EXX960.LICS
```

The license file can then be referenced in the EntireX Broker startup procedure (RUNETB.J) by using a SETPARM JCL control statement.

```
// SETPARM ETBLIC=SAGLIB.EXX960(EXX960.LICS)
```

Alternatively, the JCL provided in file EXX960.LIBJ on the installation medium can be used to copy the license file to a sequential disk file. Make sure the sequential disk file is referenced in the EntireX Broker startup procedure (RUNETB.J).

```
// ASSGN  SYS002,DISK,VOL= VSEnnn,SHR
// DLBL   ETBLIC,'SAG.ETBLIC',0
// EXTENT SYS002 ,VSEnnn,.,,xxxxx,yy
```

Step 3: Customize the EntireX Broker Attribute File (ETBnnn.ATR)

(SMA Job I070 / Step 7604)

Customize the delivered EntireX Broker attribute file (ETBnnn.ATR) to suit your environment. Specify at least the following four parameters:

```
BROKER-ID = ETBnnn
PORT      = port_number
ADASVC    = svc_number
NODE      = node_number
```

Parameters ADASVC and NODE can be omitted with transport method TCP/IP (TRANSPORT=TCP). See *Broker Attributes* in the platform-independent administration documentation.

Please ensure the partition size is adequate for running EntireX Broker, taking into consideration the resource specified in the particular attribute file you are using. See also *Broker Resource Allocation* in the general administration documentation.

Step 4: Customize the EntireX Broker Startup Job Control (RUNETB.J)**(SMA Job I070 / Step 7606)**

Customize the delivered EntireX Broker startup job control (RUNETB.J) to suit your environment. Ensure that license and attribute file are referenced correctly.

RUNETB.J

```
* $$ JOB JNM=RUNETB,CLASS=0,DISP=D
* $$ LST CLASS=A,DISP=H
// JOB RUNETB
*
* BROKER START UP JOB CONTROL
*
// LIBDEF *,SEARCH=(SAGLIB.EXX960,SAGLIB.MLC127,SAGLIB.WAL826)
/*
/* ATTRIBUTE FILE
/*
// SETPARM ETBATTR='DD:SAGLIB.EXX960(ETBnnn.ATR)'
/* / ASSGN SYS000,DISK,VOL=VSEnnn,SHR
/* / DLBL ETBATTR,'SAG.ETBATTR',0
/* / EXTENT SYS000,VSEnnn,,xxxxx,yy
/*
/* TRACE DESTINATION
/*
// SETPARM ETBLOG='DD:SYSLST'
/* / ASSGN SYS001,DISK,VOL=VSEnnn,SHR
/* / DLBL ETBLOG,'SAG.ETBLOG',0
/* / EXTENT SYS001,VSEnnn,,xxxxx,yy
/*
/* LICENSE FILE
/*
// SETPARM ETBLIC='DD:SAGLIB.EXX960(EXX960.LICS)'
/* / ASSGN SYS002,DISK,VOL= VSEnnn,SHR
/* / DLBL ETBLIC,'SAG.ETBLIC',0
/* / EXTENT SYS002 ,VSEnnn,,xxxxx,yy
/*
/* TURN OFF CONSOLE PROMPT
/*
/* / UPSI 00000001
/*
// EXEC ETBSTART
// EXEC LISTLOG
/&
* $$ EOJ
```

If the subsequent optional installation steps are not required, you may now run job RUNETB.J to start the EntireX Broker.

To test your installation, see [Installation Verification](#).

Step 5: Define an Adabas Persistent Store (Optional)

(SMA Job I050 / Step 7600 / 7610)

To create an Adabas Persistent Store, adapt and run job `PSFADA.J` in sublibrary `EXX960`. Running this job will load an empty Adabas persistent store file into your Adabas database. To activate the Adabas persistent store, set up at least following parameters in the broker attribute file. See *Broker Attributes* in the platform-independent administration documentation.

```

DEFAULTS=BROKER
STORE           = BROKER
PSTORE         = HOT/COLD
PSTORE-TYPE    = ADABAS
DEFAULTS=ADABAS
DBID           = dbid
FNR           = pstore_file_number
DEFAULTS=NET
ADASVC        = svc_number

```

See *Managing the Broker Persistent Store* for more information.

Step 6: Load the INPL and ERRN Files: Install the Natural-based EntireX Broker Tutorial Job JSYSETB (Optional)

(SMA Job I061 / Step 7600, 7602)



Note: Perform this step only if you want to install the sample Natural programs.

1. Use the Natural system command `INPL` and `ERRLODUS` (see *Natural User's Guide*) to load the EntireX Broker system objects (`EXB960.INPL` and `EXB960.ERRN`).

This loads the following library:

Library	File	Contents
SYSETB	FNAT	Sample Natural programs.

2. Set the Natural profile parameter `ESIZE=40`.
3. Invoke Natural, logon to library `SYSETB` and edit the member `PARM` on library `SYSETB` to set parameters as required at your site, especially the `BROKER-ID`.

Parameter members can also be made user-dependent. Copy the `PARM` member and save it in a member with a user ID as name (Natural variable `*USER`). If a user logs on with this user ID, these parameters take effect instead of the `PARM` member.

Step 7: Install the Stubs

If you will be using the EntireX Broker stubs on z/VSE, see *Administration of Broker Stubs under z/VSE*. The EntireX Broker stubs are installed as part of the Developer's Kit under UNIX and Windows (these are delivered with the EntireX Developer's Kit).

Installation Verification

You can use the sample client and server programs `BCOC` and `BCOS` to test the EntireX Broker installation. First start the server program, then the client program.

Customize the delivered job control samples `RUNBCOS.J` and `RUNBCOC.J`. Choose the desired transport method and replace all placeholder values (in *italic* font).

- [Specifying the Broker ID](#)
- [RUNBCOS.J](#)
- [RUNBCOC.J](#)
- [Verification Steps](#)
- [RUNBCOS Sample Server Output](#)
- [RUNBCOC Sample Client Output](#)

Specifying the Broker ID

Depending on the transport method, the Broker ID can be specified in two formats:

■ TCP Transport Method

```
ip:port:TCP
```

where *ip* is the address or DNS host name,
port is the port number that EntireX Broker is listening on, and
TCP is the protocol name

■ NET Transport Method

```
ETBnnn:SVCmmm:NET
```

where *nnn* is the ID under which EntireX Broker is connected to the Adabas ID table,
mmm is the SVC number under which the Adabas ID table can be accessed, and
NET is the protocol name

RUNBCOS.J

```

* $$ JOB JNM=RUNBCOS,CLASS=0,DISP=D
* $$ LST CLASS=A,DISP=H
// JOB RUNBCOS
*
* BCOS (SERVER) SAMPLE JCL
*
// LIBDEF *,SEARCH=(SAGLIB.EXX960,SAGLIB.WAL826)
/*
/* / EXEC BCOS,PARM='-b<ip>:<port>:TCP -i50 -p2000'
// EXEC BCOS,PARM='-bETB<nnn>:SVC<mmm>:NET -i50 -p2000'
/*
// EXEC LISTLOG
/&
* $$ EOJ

```

RUNBCOC.J

```

* $$ JOB JNM=RUNBCOC,CLASS=0,DISP=D
* $$ LST CLASS=A,DISP=H
// JOB RUNBCOC
*
* BCOC (CLIENT) SAMPLE JCL
*
// LIBDEF *,SEARCH=(SAGLIB.EXX960,SAGLIB.WAL826)
/*
/* / EXEC BCOC,PARM='-b<ip>:<port>:TCP -i50 -p2000'
// EXEC BCOC,PARM='-bETB<nnn>:SVC<mmm>:NET -i50 -p2000'
/*
// EXEC LISTLOG
/&
* $$ EOJ

```

Verification Steps

Run job RUNBCOS.J. It will register as ASERVER, ASERVICE, ACLASS at EntireX Broker. Run job RUNBCOC.J in a different z/VSE partition. This client sample program will exchange some test data with the previously registered server ASERVER.

RUNBCOS Sample Server Output

```

CLIENT: Message size 2000
CLIENT: Number of messages (10)
CLIENT: Broker ID localhost:1971:TCP
CLIENT: Using default class ACLASS
CLIENT: Using default server ASERVER
CLIENT: Using default service ASERVICE
CLIENT: Using default ACI version 10
CLIENT: Maximum stub ACI version: 10
CLIENT: Max kernel ACI version: 10
CLIENT: Kernel Version 9.6.0.00 Platform z/VSE 5.1.2
CLIENT: Using ACI version: 10
Request returns (900000000,838610000000000000000000000000000000)
Request returns (800000000,838610000000000000000000000000000000)
Request returns (700000000,838610000000000000000000000000000000)
Request returns (600000000,838610000000000000000000000000000000)
Request returns (500000000,838610000000000000000000000000000000)
Request returns (400000000,838610000000000000000000000000000000)
Request returns (300000000,838610000000000000000000000000000000)
Request returns (200000000,838610000000000000000000000000000000)
Request returns (100000000,838610000000000000000000000000000000)
Request returns (000000000,838610000000000000000000000000000000)
CLIENT: Test successfully performed
  
```

RUNBCOC Sample Client Output

```

SERVER: Userid EXXUSER
SERVER: Message size 2000
SERVER: Number of messages (10)
SERVER: Broker ID localhost:1971:NET
SERVER: Using default class ACLASS
SERVER: Using default server ASERVER
SERVER: Using default service ASERVICE
SERVER: Using default ACI version 10
SERVER: Maximum stub ACI version: 10
SERVER: Max kernel ACI version: 10
SERVER: Kernel Version 9.6.0.00 Platform z/VSE 5.1.2
SERVER: Using ACI version: 10
Incoming data (000000000000000000000000000016838,000000009)
Incoming data (000000000000000000000000000016838,000000008)
Incoming data (000000000000000000000000000016838,000000007)
Incoming data (000000000000000000000000000016838,000000006)
Incoming data (000000000000000000000000000016838,000000005)
Incoming data (000000000000000000000000000016838,000000004)
Incoming data (000000000000000000000000000016838,000000003)
Incoming data (000000000000000000000000000016838,000000002)
Incoming data (000000000000000000000000000016838,000000001)
Incoming data (000000000000000000000000000016838,000000000)
SERVER: Test successfully performed
  
```

Hints for Setting up Broker JCL in z/VSE

- [Where the Files Reside](#)
- [Informing Broker where the Files Reside](#)
- [Using the BSI TCP/IP Stack](#)

Where the Files Reside

- ETBLIC and ETBATTR can reside in z/VSE libraries as members (recommended) or they can reside as sequential disk files (SD files).
- ETBLOG, including possible traces, can go to SYSLST (recommended) or to an SD file.

Informing Broker where the Files Reside

- Supply the information with SETPARAM JCL control statements

```
// SETPARAM ETB(LIC|ATTR|LOG)='DD:d1bl_name'
```

for SD files, and for library members:

```
'DD:lib.sublib(member.type)'
```

- Supply the information as PARM in the EXEC card:

```
// EXEC ETBSTART,          +
PARM='ENVAR("ETB_ATTR=DD:lib.sublib(member.type)")/'
```

If files reside in SD files, the necessary z/VSE JCL statements DLBL, EXTENT and ASSGN must be provided for each file too.

The shortest way

See also [Step 4: Customize the EntireX Broker Startup Job Control \(RUNETB.J\)](#).

```
01 * $$ JOB JNM=RUNETB,CLASS=0,DISP=D
02 * $$ LST CLASS=A,DISP=H
03 // JOB RUNETB
04 // LIBDEF *,SEARCH=(SAGLIB.EXX960,SAGLIB.MLC127,SAGLIB.WAL826)
05 // UPSI 00000001
06 // SETPARAM ETBLOG='DD:SYSLST'
07 // SETPARAM ETBATTR='DD:SAGLIB.EXX960(ETBnnn.ATR)'
08 // SETPARAM ETBLIC='DD:SAGLIB.EXX960(EXX960.LICS)'
09 // EXEC ETBSTART
10 // EXEC LISTLOG
```

```
11 /&
12 * $$ E0J
```

To line 6:

This avoids message "4881I NO LABEL INFORMATION FOUND" during Broker startup.

To lines 7 and 8:

If z/VSE JCL parameters ETBATTR and ETBLIC are defined, the Broker retrieves the values of these parameters and derives the location of the attribute and license files from there.

► **To define ETBLIC, ETBATTR and ETBLOG as SD files**

```
■ // ASSGN SYS000,DISK,VOL=VSEnnn,SHR
// DLBL ETBATTR,'SAG.ETBATTR',0
// EXTENT SYS000 ,VSEnnn,,xxxxx,yy
/*
// ASSGN SYS001,DISK,VOL= VSEnnn,SHR
// DLBL ETBLOG,'SAG.ETBLOG',0
// EXTENT SYS001,VSEnnn,,xxxxx,yy
/*
// ASSGN SYS002,DISK,VOL= VSEnnn,SHR
// DLBL ETBLIC,'SAG.ETBLIC',0
// EXTENT SYS002 ,VSEnnn,,xxxxx,yy
/*
```

The following table describes the file assignment names:

File Assignment	DLBL Name	Description	See also Step
SYS000	ETBATTR	EntireX Broker attribute file.	Step 3: Customize the EntireX Broker Attribute File (ETBnnn.ATR)
SYS001	ETBLOG	Log file to which EntireX Broker writes trace output. Omitting this file assignment will route a trace output to SYSLST.	
SYS002	ETBLIC	EntireX License Certificate File.	

Using the BSI TCP/IP Stack

In addition to CSI's TCP/IP stack, EntireX Broker also supports the BSI TCP/IP stack. For this, the BSI library must be included in the LIBDEF search chain.

If multiple stacks are installed (for example, both CSI and the BSI stack are installed in parallel) specify the corresponding stack ID. See the sample job control for Broker startup below:

```
* $$ JOB JNM=RUNETB,CLASS=0,DISP=D
* $$ LST CLASS=A,DISP=H
// JOB RUNETB
*
* BROKER START UP JOB CONTROL
*
// LIBDEF *,SEARCH=(SAGLIB.EXX960,SAGLIB.MLC127,SAGLIB.WAL826,BSILIB.BSIvrs)
/*
/* ATTRIBUTE FILE
/*
// SETPARM ETBATTR='DD:SAGLIB.EXX960(ETBnnn.ATR)'
/* / ASSGN SYS000,DISK,VOL=VSEnnn,SHR
/* / DLBL ETBATTR,'SAG.ETBATTR',0
/* / EXTENT SYS000,VSEnnn,,xxxxx,yy
/*
/* TRACE DESTINATION
/*
// SETPARM ETBLOG='DD:SYSLST'
/* / ASSGN SYS001,DISK,VOL=VSEnnn,SHR
/* / DLBL ETBLOG,'SAG.ETBLOG',0
/* / EXTENT SYS001,VSEnnn,,xxxxx,yy
/*
/* LICENSE FILE
/*
// SETPARM ETBLIC='DD:SAGLIB.EXX960(EXX960.LICS)'
/* / ASSGN SYS002,DISK,VOL= VSEnnn,SHR
/* / DLBL ETBLIC,'SAG.ETBLIC',0
/* / EXTENT SYS002 ,VSEnnn,,xxxxx,yy
/*
/* TURN OFF CONSOLE PROMPT
/*
/* / UPSI 00000001
/*
/*
/* SET STACK ID
/*
// OPTION SYSPARM='BSI_stack_id'
/*
// EXEC ETBSTART
// EXEC LISTLOG
/&
* $$ EOJ
```


3 Installing the z/VSE EntireX RPC Servers

- Contents of Sublibrary EXP960 22
- Installing the CICS RPC Server 23
- Installing the Batch RPC Server 28
- Installation Verification 33

This chapter covers the following topics:

Contents of Sublibrary EXP960

Configuration, Startup JCL and Server Executables

File	Description
RUNRPC . J	Batch RPC Server startup JCL.
RPCPARM . CFG	Batch RPC Server configuration file.
CICSDEF . J	CICS CSD definitions JCL.
VSAMDEF . J	Server mapping file VSAM definition JCL.
SVMPRIME . PHASE	Server mapping file VSAM prime utility.
RPCSRVB . PHASE RPCCONS . PHASE RPCLEST . PHASE	Batch RPC Server.
RPCSRVC . PHASE	CICS RPC Server.
COBUEX02 . C COBUEX02 . CPY	CICS RPC Server user exit.

CICS RPC Server ERXMAIN Control Block and Online Maintenance Tool

File	Description
ERXMAIN . J	Assemble and LNKEDT JCL.
EMAINGEN . A	ERXMAIN control block macro.
ERXMAIN . A	Assembler source to generate the ERXMAIN control block containing the CICS RPC Server default configuration.
ERXMAIN . PHASE	default ERXMAIN control block executable.
ERXMAINT . PHASE	CICS RPC Server online maintenance tool.
ERXMAPS . PHASE	CICS RPC Server online maintenance tool map.

Batch COBOL Client Server Example (CALC)

File	Description
CALCRUN.J	Batch CALC client startup JCL.
CALCCLT.PHASE	Batch CALC client executable.
CALC.PHASE	Batch CALC server program.

CICS COBOL Client Server Example (SQUARE)

File	Description
SQRECLT.PHASE	CICS SQUARE client executable.
SQREMAP.PHASE	CICS SQUARE client map.
SQUARE.PHASE	CICS SQUARE server program.

Installing the CICS RPC Server

- [Step 1: Define an RPC Server Mapping File - VSAMDEF.J \(Optional\)](#)
- [Step 2: Build the ERXMAIN Control Block \(Optional\)](#)
- [Step 3: Modify CICS Startup JCL](#)
- [Step 4: Update the CICS Tables](#)
- [Step 4: Start CICS RPC Server](#)
- [Installing Multiple EntireX RPC Servers in the same CICS \(Optional\)](#)

Step 1: Define an RPC Server Mapping File - VSAMDEF.J (Optional)

(SMA Job I008 / Step 7570 and Job I025 / Step 7570)



Note: Perform this step for Batch RPC Server and CICS RPC Server with different file names.

The SVM file is used at runtime to marshal and unmarshal the RPC data stream. This enables the RPC Server to support special COBOL syntax. See *Handling SVM Files*. This server-related information is held in a VSAM cluster, which needs to be defined and primed. Each RPC server requires its own SVM file.

If this step is omitted, the RPC server will start without the SVM file. This means that server programs cannot make use of special COBOL syntax.

Customize and run job VSAMDEF.J. Specify the desired VSAM KSDS cluster name, catalog and Catalog ID. These are marked by the placeholders "<...>" in VSAMDEF.J.

SVM File Definition Job Control

```

* $$ JOB JNM=VSAMDEF,CLASS=H,DISP=D
* $$ LST CLASS=0,DISP=D
// JOB VSAMDEF
*
* DEFINE AND INITIALIZE THE RPC SVM File VSAM CLUSTER
*
// EXEC IDCAMS,SIZE=AUTO
/* ----- */
/* DELETE SERVER MAPPING VSAM CLUSTER */
/* ----- */
DELETE (<vsam_ksds_cluster_name>) CL NOERASE PURGE -
CATALOG(<catalog_name>)
SET MAXCC = 0
SET LASTCC = 0
/* ----- */
/* DEFINE SERVER MAPPING VSAM CLUSTER */
/* ----- */
DEFINE CLUSTER -
( NAME(<vsam_ksds_cluster_name>) -
RECORDSIZE(1024 16384) -
RECORDS(1000 1000) -
KEYS(255 0) -
INDEXED -
SHR(2,3) -
VOL(<volume>) -
) -
DATA(NAME(<vsam_ksds_cluster_name>.DATA)) -
INDEX(NAME(<vsam_ksds_cluster_name>.INDEX)) -
CATALOG(<catalog_name>)
/*
/* ----- */
/* INITIALIZE SERVER MAPPING VSAM CLUSTER */
/* ----- */
// DLBL ERXSVM,'<vsam_ksds_cluster_name>',0,VSAM,CAT=<catalog>
// LIBDEF *,SEARCH=(SAGLIB.EXP960),TEMP
// EXEC SVMPRIME,SIZE=AUTO
/*
/ &
* $$ EOJ

```

Step 2: Build the ERXMAIN Control Block (Optional)

(SMA Job I070 / Step 7572, 7573)

The ERXMAIN control block holds the EntireX CICS RPC Server parameter settings. This configuration can be manually maintained by using the EntireX CICS Online Utility. A preconfigured ERXMAIN phase is delivered in sublibrary EXP960. To alter this configuration, perform the following steps.

1. Adapt source `EMAINGEN.A` to fit the environment (see also *RPC Servers*)
2. Adapt job `ERXMAIN.J` to fit your environment.
3. Run job `ERXMAIN.J`.

Running job `ERXMAIN.J` assembles macro `ERXMAIN` and links a new `ERXMAIN` phase with the preferred default settings.

The name of the phase may be altered within job `ERXMAIN.J`. This allows you to run multiple EntireX CICS RPC Server instances. To do so, a new control block needs to be loaded. The EntireX CICS Online Utility provides the necessary functionality. Note that the new control block requires a PPT entry in CICS according to the delivered ERXMAIN control block phase.

Step 3: Modify CICS Startup JCL

To enable CICS to find the various programs defined to the PPT (installation step 4), the CICS startup JCL needs to be modified to include the sublibraries EXP960 and EXX960 into the DFHRPL chain.

Additionally, if installation Step 1 was performed, a DLBL statement, as shown below, needs to be added for the VSAM KSDS cluster of the SVM file.

```
// DLBL ERXSVM, '<vsam_ksds_cluster_name>',0,VSAM,CAT=<catalog>
```

Each RPC Server instance running in same CICS partition requires its own SVM file, that is, its own DLBL entry. You can choose any DLBL name. ERXSVM is the default. It can be altered manually in the EntireX CICS Online Utility or set up permanently in the ERXMAIN control block (installation Step 2).

Step 4: Update the CICS Tables

(SMA Job I005 / Step 7570)

Add the definitions listed below to your CICS system, either manually or with job CICSDEF.J in sublibrary EXP960.

- File Definitions
- Program Definitions
- Mapset Definition
- Transaction Definitions

File Definitions

If installation Step 1 was performed, the SVM file VSAM KSDS cluster needs to be defined. Replace the `<vsam_ksds_cluster_name>` in the DEFINE statement.

```
DEFINE FILE(ERXSVM) GROUP(EXX)
  DSNAME(<vsam_ksds_cluster_name>)
  DESCRIPTION(ENTIREX RPC SVM File)
  LSRPOOLID(NONE) ADD(YES) BROWSE(YES) DELETE(YES) READ(YES)
  UPDATE(YES) RECORDSIZE(16384) KEYLENGTH(255) STRINGS(2)
  DATABUFFERS(201) INDEXBUFFERS(200)
```

Program Definitions

```
DEFINE PROGRAM(BKIMC) GROUP(ERX) LANGUAGE(ASSEMBLER)
DEFINE PROGRAM(BROKERC) GROUP(ERX) LANGUAGE(C)
DEFINE PROGRAM(ERXMAIN) GROUP(ERX) LANGUAGE(ASSEMBLER)
DEFINE PROGRAM(ERXMAINT) GROUP(ERX) LANGUAGE(C)
DEFINE PROGRAM(RPCSRVC) GROUP(ERX) LANGUAGE(C)
DEFINE PROGRAM(SQRECLT) GROUP(ERX) LANGUAGE(COBOL)
DEFINE PROGRAM(SQUARE) GROUP(ERX) LANGUAGE(COBOL)
```

The programs in the definitions above are used for following purposes:

Program	Purpose
BKIMC	CICS Broker stub interface.
BROKERC	CICS Broker stub.
ERXMAIN	Control block.
ERXMAINT	EntireX CICS Online Utility.
RPCSRVC	CICS RPC Server.
SQRECLT	COBOL CICS SQUARE example client.
SQUARE	COBOL CICS SQUARE example server.

Mapset Definition

```
DEFINE MAPSET(ERXMAPS) GROUP(EXP)
DEFINE MAPSET(SQREMAP) GROUP(EXP)
```

This mapset is used by the EntireX CICS Online Utility.

Transaction Definitions

```
DEFINE TRANSACTION(ERXM) GROUP(EXXERX) PROGRAM(ERXMAINT) TWASIZE(128)
DEFINE TRANSACTION(ESRV) GROUP(EXXERX) PROGRAM(RPCSRVC) TWASIZE(128)
DEFINE TRANSACTION(EC01) GROUP(ERX) PROGRAM(SQRECLT) TWASIZE(28)
```

Transaction `ERXM` is used to start the EntireX CICS Online Utility. The transaction `ESRV` is used internally to run EntireX CICS RPC Server.

Step 4: Start CICS RPC Server

To start the CICS RPC Server, use the EntireX CICS Online Utility by entering transaction `ERXM`. The EntireX CICS Online Utility is command line oriented. If the default `ERXMAIN` control block is used, adapt the parameter settings to fit the environment, especially the Broker ID by entering:

```
BROKER=<Broker ID>
```

Depending on the communication method, the Broker ID can be specified in two formats:

■ TCP Transport Method

```
ip:port:TCP
```

where *ip* is the address or DNS host name,
port is the port number that EntireX Broker is listening on, and
TCP is the protocol name

■ NET Transport Method

```
ETBnnn:SVCmmm:NET
```

where *nnn* is the ID under which EntireX Broker is connected to the Adabas ID table,
mmm is the SVC number under which the Adabas ID table can be accessed, and
NET is the protocol name

To start CICS RPC Server, press PF8.

To stop CICS RPC Server, press PF10.

Installing Multiple EntireX RPC Servers in the same CICS (Optional)

▶ To install a second RPC server in the same CICS

- 1 Copy the default CICS RPC Server transaction definition `ESRV` and give it a unique name, e.g. `ESR2`.

```
CEDA COPY TRANSACTION(ESRV) GROUP(ERX) TO(ERX2) AS(ESR2)
```

- 2 Copy the default CICS RPC Server `ERXMAIN Control Block` and give it a unique name, e.g. `ERXMAIN2`.

```
CEDA COPY PROGRAM(ERXMAIN) GROUP(ERX) TO(ERX2) AS(ERXMAIN2)
```

- 3 Add the new group `ERX2` to the CICS autoinstall list.

```
CEDA ADD GROUP(ERX2) LIST(listname) AFTER(groupname)
```

- 4 Build a new `ERXMAIN Control Block` and give it the name created above, e.g. `ERXMAIN2`.

As a minimum, set the `ERXMAIN Macro` parameter `REPL` in the `ERXMAIN Control Block` to the new RPC server transaction ID created above, e.g. `REPL=ESR2`.

The second CICS RPC server can now be started. See *Starting the RPC Server* under *RPC Online Maintenance Facility* in the CICS RPC Server documentation.

Installing the Batch RPC Server

Step 1: Define an RPC Server mapping file (SVM File) - VSAMDEF.J (Optional)

(SMA Job I008 / Step 7570)



Note: Perform this step for Batch RPC Server and CICS RPC Server with different file names.

The SVM file is used at runtime to marshal and unmarshal the RPC data stream. This enables the RPC Server to support special COBOL syntax. See *Handling SVM Files*. This server-related information is held in a VSAM cluster, which needs to be defined and primed. Each RPC server requires its own SVM file.

If this step is omitted the RPC server will start without the SVM file. This means that server programs cannot make use of special COBOL syntax.

Customize and run job VSAMDEF .J. Specify the desired VSAM KSDS cluster name, catalog, catalog ID and volume. These are marked by the placeholders "<...>" in VSAMDEF .J.

SVM File Definition Job Control

```
* $$ JOB JNM=VSAMDEF,CLASS=H,DISP=D
* $$ LST CLASS=0,DISP=D
// JOB VSAMDEF
*
* DEFINE AND INITIALIZE THE RPC Server mapping file VSAM CLUSTER
*
// EXEC IDCAMS,SIZE=AUTO
/* ----- */
/* DELETE SERVER MAPPING VSAM CLUSTER */
/* ----- */
DELETE (<vsam_ksds_cluster_name>) CL NOERASE PURGE -
CATALOG(<catalog_name>)
SET MAXCC = 0
SET LASTCC = 0
/* ----- */
/* DEFINE SERVER MAPPING VSAM CLUSTER */
/* ----- */
DEFINE CLUSTER -
( NAME(<vsam_ksds_cluster_name>) -
RECORDSIZE(1024 16384) -
RECORDS(1000 1000) -
KEYS(255 0) -
INDEXED -
SHR(2,3) -
VOL(<volume>) -
) -
DATA(NAME(<vsam_ksds_cluster_name>.DATA)) -
INDEX(NAME(<vsam_ksds_cluster_name>.INDEX)) -
CATALOG(<catalog_name>)
/*
/* ----- */
/* INITIALIZE SERVER MAPPING VSAM CLUSTER */
/* ----- */
// DLBL ERXSVM, '<vsam_ksds_cluster_name>',0,VSAM,CAT=<catalog>
// LIBDEF *,SEARCH=(SAGLIB.EXP960),TEMP
// EXEC SVMPRIME,SIZE=AUTO
/*
/&
* $$ EOJ
```

Step 2: Adapt the RPC Parameter File

(SMA Job I200 / Step 7570)

RPCPARM.CFG in sublibrary EXP960 contains the RPC server parameters. If the default settings are used, only the `BROKERID` parameter needs to be set up according to your environment. The Batch RPC Server will then run in a default configuration with two permanent worker tasks (up to 16 replicates are possible) and the deployment service turned off. See *Server Mapping Deployment*. It will register at EntireX Broker as service SRV1, class RPC and service CALLNAT, which corresponds to the settings in the delivered Broker attribute file. System Management Hub support and security are turned off. See also *Configuring the RPC Server* under *Administering the Batch RPC Server*.

Depending on the communication method, the Broker ID can be specified in two formats:

■ TCP Transport Method

```
ip:port:TCP
```

where `ip` is the address or DNS host name,
`port` is the port number that EntireX Broker is listening on, and
`TCP` is the protocol name

■ NET Transport Method

```
ETBnnn:SVCmmm:NET
```

where `nnn` is the ID under which EntireX Broker is connected to the Adabas ID table,
`mmm` is the SVC number under which the Adabas ID table can be accessed, and
`NET` is the protocol name

To turn on the Deployment Service, a built-in service of the RPC server, (see *Deployment Service* under *Administering the Batch RPC Server*) uncomment the line shown below. This will allow deploying information from the *EntireX Workbench* into the SVM file. Additionally, the SVM file needs to be installed; See [Step 1: Define an RPC Server mapping file \(SVM File\) - VSAMDEF.J \(Optional\)](#).

```
* DEPLOYMENT=YES register Deployment Service
```

The default configuration file RPCPARM.CFG:

```

* * * * *
*
*           EntireX RPC Server configuration file
*
* * * * *
* * * * * * * * * * EntireX Broker Parameters * * * * *
*
BROKERID=<ip>:<port>:TCP           Broker Id if TCP/IP is used
* BROKERID=ETB<nnn>:SVC<ccc>:NET   Broker Id if XCOM is used
*
SERVERNAME=SRV1
SERVICE=CALLNAT
CLASS=RPC
*
TIMEOUT=30
*
* USERID=ERXUSER
* PASSWORD=PASSWORD
* LOGON=YES
*
* * * * * * * * * * EntireX RPC Server Parameter * * * * *
*
RESTARTCYCLES=3                   try three times (1 minute
*                                   interval) when EntireX
*                                   Broker is unavailable
*
* DEPLOYMENT=YES                   register Deployment Service
*
* TRACELEVEL=ADVANCED              NONE, STANDARD or ADVANCED
*
* SMHPOPT=<smhport>                port number for System
*                                   Management Hub connection
*
* ETBLNK=BROKER                    required if Relay Manager
*                                   communication is desired
*
* Start up a fixed number of workers (up to 16 workers possible)
* -----
MINWORKERS=2                       number of parallel server
*                                   replicates started
*                                   MAXWORKERS will be ignored
ENDWORKERS=NEVER                   stop never
*
*
* Balance the load of available workers
* -----
* MINWORKERS=0                     keep alive at least one
*                                   replicate
*
* MAXWORKERS=<n>                    n .. maximum of parallel
*                                   server replicates
*
* ENDWORKERS=IMMEDIATLY            stop immediately after

```

```

*                                     request worked off
*
* Balance the load of available workers
* -----
* MINWORKERS=1                       keep alive at least one
*                                     replicate
* MAXWORKERS=<n>                      n..maximum of parallel
*                                     server replicates
* ENDWORKERS=TIMEOUT                 stop after timeout received
*
*
* * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *

```

Step 3: Customize the Batch RPC Server Startup JCL - RUNRPC.J

Adapt the Batch RPC Server startup JCL RUNRPC.J to fit your environment.

If installation Step 1 was performed, include the VSAM KSDS Cluster name of the SVM file and uncomment following line:

```
/* / DLBL ERXSVM,'<vsam_ksds_cluster_name>',0,VSAM,CAT=<catalog>
```

Insert the sublibraries containing your own server programs into the LIBDEF search chain.

If you wish to suppress the console prompt, uncomment the UPSI statement.

```
/* / UPSI 00000001
```



Note: In the current RPC Server version, the UPSI setting suppresses the startup of the RPC Server Console task. In that case an MSG *partition_id* command will not have any effect as there is no AR routine present. Stopping the RPC Server is then only possible through System Management Hub.

Batch RPC Server Job Control:

```

* $$ JOB JNM=RUNRPC,CLASS=0,DISP=D
* $$ LST CLASS=A,DISP=H
// JOB RUNRPC
*
* BATCH RPC SERVER START UP JOB CONTROL
*
// OPTION DUMP,NOSYSDUMP
/*
/* TURN OFF RPC SERVER CONSOLE PROMPT
/*
/* / UPSI 00000001
/*
/* SERVER MAPPING FILE
/*

```

```

/* / DLBL ERXSVM, '<vsam_ksds_cluster_name>', 0, VSAM, CAT=<catalog>
/*
// LIBDEF PHASE, SEARCH=(SAGLIB.EXP960,           +
                        SAGLIB.EXX960,           +
                        SAGLIB.WAL826), TEMP
/*
// EXEC RPCSRVB, SIZE=AUTO, PARM='CFG=DD:SAGLIB.EXP960(RPCPARAM.CFG)'
/*
/&
* $$ E0J

```

Step 4: Start Batch RPC Server

▶ To start the batch RPC Server

- Run job RUNRPC.J.

▶ To stop the batch RPC Server

- Use the console command STOP.

```
task_id STOP
```

or use System Management Hub functionality.

Installation Verification

There are two COBOL client/server examples delivered as executables with the RPC servers, one for use in Batch (CALC), the other for CICS (SQUARE). These examples are useful for verifying the RPC Server installation. They are a subset of the z/VSE COBOL examples provided with EntireX Developer's Kit on Windows. See *Client and Server Examples for z/VSE CICS* and *Client and Server Examples for z/VSE Batch* for more information.

You can also download the full set of z/VSE COBOL examples from the Software AG's customer service site [Empower](#). In Empower, choose **Products > Download Components**. The examples are provided as AWS tape EXAMPLE.AWS. The tape contains several example sources, JCL and detailed descriptions, and also ready-to-run load modules.

This section covers the following topics:

- [CICS COBOL SQUARE Client Server Example \(Optional\)](#)

- [Batch COBOL CALC Client Server Example \(Optional\)](#)

CICS COBOL SQUARE Client Server Example (Optional)

This COBOL client server example is delivered as executable and ready to run. Its purpose is to verify the CICS RPC Server installation.

Ensure following CICS transaction and programs are defined:

```
DEFINE TRANSACTION(EC01) GROUP(ERX) PROGRAM(SQRECLT) TWASIZE(28)
DEFINE PROGRAM(SQRECLT) GROUP(ERX) LANGUAGE(COBOL)
DEFINE PROGRAM(SQUARE) GROUP(ERX) LANGUAGE(COBOL)
```

Executing the transaction EC01 will display following CICS map:

```
16:06:11      ---- RPC  SQRECLT  example for  COBOL  ----          31/01/14
BROKER-ID  localhost:1971
CLASS      RPC
SERVER     SRV1
SERVICE   CALLNAT
USER-ID    COBUSER
PASSWORD
Operand    000000012
-----
F3 Exit   F5 Exec
```

Enter the Broker ID, depending on the transport method used:

■ TCP Transport Method

```
ip:port:TCP
```

where *ip* is the address or DNS host name,
port is the port number that EntireX Broker is listening on, and
TCP is the protocol name

■ NET Transport Method


```
ETBnnn:SVCmmm:NET
```

where *nnn* is the ID under which EntireX Broker is connected to the Adabas ID table,
mmm is the SVC number under which the Adabas ID table can be accessed, and
 NET is the protocol name

Enter the BROKER-ID and press **PF5** to execute the client.

Batch COBOL CALC Client Server Example (Optional)

This COBOL client server example is delivered as executable and ready to run. Its purpose is to verify the Batch RPC Server installation.

Customize `CALCRUN.J` to fit the environment. Set up `BROKERID` as described under [CICS COBOL SQUARE Client Server Example \(Optional\)](#).

Run job `CALCRUN.J`.

```
* $$ JOB JNM=CALCRUN,CLASS=0,DISP=D
* $$ LST CLASS=A,DISP=H
// JOB CALCRUN
*
* CALC EXAMPLE CLIENT START UP JOB CONTROL
*
// LIBDEF PHASE,SEARCH=(SAGLIB.EXP960,
                        SAGLIB.EXX960,
                        SAGLIB.WAL826),TEMP
// EXEC  CALCLT,SIZE=AUTO
* * * * *
* Input Parameter
* * * * *
BROKERID <ipaddr>:<port>:TCP
* BROKERID ETB<nnnnn>::NET
* USERID  <userid>
* PASSWORD <password>
CLASS    RPC
SERVER   SRV1
SERVICE CALLNAT
LOGON
CALC     + 00012345 00067890
CALC     - 00067890 00012345
CALC     * 00001234 00005678
CALC     / 00005678 00001234
CALC     % 00005678 00001234
END
/*
/&
* $$ EOJ
```

4 Installing EntireX Security under z/VSE

- Installing EntireX Security for Broker Kernel 38
- Setting up EntireX Security for Broker Stubs 40

Installing EntireX Security for Broker Kernel

This section describes the steps for installing EntireX Security for Broker kernel under z/VSE.

- [Step 1: Modify Broker Attribute File](#)
- [Step 2: Configure IBM Basic Security Manager](#)
- [Step 3: Define User Profiles for Basic Security Manager](#)
- [Step 4: Start / Restart Broker Kernel](#)

Step 1: Modify Broker Attribute File

1. Insert the following parameter in the section `DEFAULTS=BROKER` of the Broker attribute file:

```
SECURITY=YES
```

2. Modify the `SECURITY-PARMS` parameter according to your requirements: see *Security Solutions in EntireX*.



Note: Setting `SECURITY=YES` will load the provided `PHASE` module `USRSEC` from the `EXX960` product sublibrary. This module will issue the `IBM PRODID` macro in order to obtain authorization to perform privileged operations, such as execute the `RACROUTE`.

Step 2: Configure IBM Basic Security Manager

The IBM Basic Security Manager must be installed and configured on your system in order to use EntireX Security. This allows EntireX Broker to perform authentication based on a user ID and password stored in BSM for all connected application components. See IBM documentation *z/VSE Installation*, *z/VSE Administration* and *z/VSE Planning* for complete details of IBM Basic Security Manager (BSM).



Note: It is not necessary to activate the Basic Security Manager in batch.

Step 3: Define User Profiles for Basic Security Manager

See your IBM documentation for detailed instructions for defining user IDs for Basic Security Manager (BSM). The section *Resource Definition* with subsection *Tailoring the Interactive Environment/Maintaining User Profiles* provides a description of both online (ICCF) and batch utilities for adding user IDs. The online ICCF transaction for adding user IDs is shown below.

Required fields are shown in **bold**. If `DAYS=0`, the password will never expire.

Alternatively, you can use the batch program `IESUPDCF`. See your *z/VSE* documentation for details.

```

↵
|
| IESADMUPBA          ADD OR CHANGE USER PROFILE
|
| Base    II        CICS    ResClass ICCF
|
|
| To CHANGE, alter any of the entries except the userid.
|
|
| USERID..... ENDU      4 - 8 characters (4 characters for ICCF
users) |
|
| INITIAL PASSWORD... _____ 3 - 8 characters
|
|
| DAYS..... 000        0-365 Number of days before password expires
|
| REVOKE DATE..... _____ Date when Userid will be revoked (mm/dd/yy)
|
|
| USER TYPE..... 1      1=Administrator, 2=Programmer, 3=General
|
| INITIAL NAME..... IESEADM Initial function performed at signon
|
| NAME TYPE..... 2      1=Application, 2=Selection Panel
|
| SYNONYM MODEL..... _____ Userid to be used as model for synonyms
|
|
|
|
| PF1=HELP          3=END          5=UPDATE
|
|                   8=FORWARD
|
|
|

```



Step 4: Start / Restart Broker Kernel

This is needed to pick up changes to the Broker attribute file and to initialize Broker kernel under z/VSE as an authorized subsystem able to perform security checks.

Installation of EntireX Security for Broker kernel is now complete.

Setting up EntireX Security for Broker Stubs

This section describes the steps for installing EntireX Security for Broker stubs under z/VSE.

- [Step 1: Relink the Stub Modules or your Application for Use with External Security](#)
- [Step 2: Rename SECUEXI0](#)

The delivered phases `BKIMB.PHASE` and `BKIMC.PHASE` are linked for use with internal security, which requires an application to use ACI version 8 or above. If you are running your application at ACI version 7 or below, the steps above are required to install EntireX Security for the Broker stubs in all environments where applications execute either in client/server or in publish/subscribe mode. These steps are *not* required if you are running your application at ACI version 8 or above.

Step 1: Relink the Stub Modules or your Application for Use with External Security

To enable external security, relink the stub modules `BKIMB.PHASE`, and `BKIMC.PHASE` (and your application if it does not dynamically load the stub).

Additionally include the following objects:

- `ETBUEVA`
- `ETBUPRE`
- `ETBVPRE`
- `ETBVEVA`
- `ETBENC`
- `ETBTP`

The following job control is delivered and may be used for relinking the various stub modules:

- `BKIMB.J`
- `BKIMC.J`

Additionally, a detailed description of how to link the stubs and your application can be found under *Administration of Broker Stubs under z/VSE*.

Step 2: Rename SECUEXIO

Rename the phase SECUEXIO.PHASE in library EXX960 to SECUEXIT.PHASE.

