

Message Class 0020 - EntireX ACI - User Error in the API

This message class is returned when invalid arguments are specified in the API (ACI) or invalid EntireX Broker function sequences are issued. It is usually an error made by the application programmer. The situation can be examined using the error number returned. The messages have the format:

0020nnnn

where 0020 is the message class, and

nnnn is the message number in the range 0000 - 9999

Overview of Messages

00200004	00200006	00200031	00200044	00200047	00200048
00200052	00200094	00200098	00200134	00200149	00200164
00200166	00200180	00200181	00200182	00200183	00200184
00200185	00200186	00200187	00200188	00200189	00200190
00200191	00200192	00200193	00200194	00200195	00200199
00200200	00200203	00200208	00200210	00200211	00200212
00200216	00200218	00200226	00200228	00200229	00200246
00200251	00200252	00200267	00200268	00200302	00200311
00200312	00200314	00200335	00200336	00200362	00200371
00200372	00200377	00200379	00200380	00200393	00200400
00200401	00200404	00200419	00200420	00200421	00200422
00200424	00200449	00200450	00200451	00200452	00200453
00200454	00200472	00200478	00200482	00200485	00200494
00200505	00200532	00200533	00200538	00200539	00200540
00200563	00200566	00200569	00200613	00200614	00200639
00200801	00200901	00209400	00209401	00209402	00209403
00209404	00209405	00209406	00209407	00209410	00209413
00209416	00209417	00209418	00209419	00209420	00209421
00209422	00209423	00209424	00209450	00209451	00209452
00209453	00209454	00209455	00209456	00209457	

00200004 API: No Function Possible After EOC

Explanation The user has tried to access a conversation after finishing it with a previous EOC call.

Action This is a user error. Perhaps an invalid conversation ID was specified. Check the program and correct the error.

00200006 API: Last Message Not Found

Explanation This response is given to a RECEIVE call with OPTION=LAST when no data/messages have yet been received. It is not possible to look at the last message if you have not read the first one.

Action This is a user error. Check the program and correct the error.

00200031 API: Invalid value for :1:

Explanation This response is given when invalid values for the WAIT or UWTIME or UWSTATP-ADDER fields of the API are specified (for example, non-digits are given or the last character is not one of the valid time units S,M,H).

Action This is a user error. Check the value for the field in the API of your program.

00200044 API: Invalid error buffer ptr or length

Explanation The user has set the errtext_length in the Broker control block but has not provided an error buffer.

Action This is a user error. The user should either provide an error buffer or set the errtext_length to 0.

00200047 API: QUIESCE invalid for Attach Manager

Explanation Because a service registered with the option ATTACH does not run normal conversations, the Deregister cannot wait for them to finish. In fact, the attachable service is no longer attachable after the Deregister

Action Do not use the Deregister option QUIESCE for services that are registered as attach manager (option ATTACH)

00200048 API: Already registered with ATTACH

Explanation An application can register a service either with the option ATTACH or as a normal server (without option ATTACH). The error occurs when an application attempts to do both.

Action Do not try to register a single server as an attach manager and as a normal server simultaneously

00200052 API: Already registered without ATTACH

Explanation An application can register a service either with the option ATTACH, or as a normal server (without option ATTACH). The error occurs when an application attempts to do both.

Action Do not try to register a single server as a normal service and as an attach manager simultaneously.

00200094 API: MSG Truncated To Fit Receive-Buffer

Explanation The data/message retrieved is larger than the supplied receive buffer. The data/message has been truncated to the actual length given in RECEIVE-LENGTH field of the API if API version 2 or above is used.

Action See *Error Cases* under *Using Send and Receive Buffers* for information on how to respond to this error code.

00200098 API: Function not possible if LOGON only

Explanation The performed function is not valid if only a LOGON call has been performed. This applies to a RECEIVE, DEREGISTER or EOC function. They are not allowed right after a LOGON call.

Action Do not perform the listed function right after a LOGON. Perform a REGISTER before running the DEREGISTER, perform a SEND or a RECEIVE before running an EOC and accept or establish a conversation before running a RECEIVE.

00200134 LOGON required

Explanation If AUTOLOGON=NO is defined in the attribute file, all participant applications must perform a LOGON call as the very first Broker call and a LOGOFF call when they have finished communicating with the Broker. If the user is using UOW, clients and servers must do a LOGON. If AUTOLOGON=YES and a LOGON is not done, this error will occur when a SEND with OPTION=SYNC is done. See AUTOLOGON under *Broker Attributes*.

Action Make LOGON the very first call and LOGOFF the last call. If necessary, define the attribute AUTOLOGON=YES in order to support automatic LOGON. However, the recommended definition is to force an explicit LOGON call.

00200149 No Error Text

Explanation The broker stub was unable to initialize the environment.

- Under z/OS, the EXX load library was not concatenated to the STEPLIB chain.
- Under BS2000/OSD, the EXX load library was not assigned to LINK-NAME ETBLIB.

Action Depends on the operating system:

- z/OS: Make sure the EXX load library is concatenated to the STEPLIB chain. See *Step 4: Authorize the Broker STEPLIB Data Sets*.
- BS2000/OSD: Make sure the EXX load library is assigned to LINK-NAME ETBLIB. See *Linking the Stubs*.

00200164 API: USER-ID and TOKEN required

Explanation USER-ID and TOKEN should be provided for durable subscription.

Action Supply USER-ID and TOKEN in the Broker control block.

00200166 Invalid OPTION/PUBLID combination

Explanation The OPTION / PUBLID combination in the API is invalid. For example, a CONTROL_PUBLICATION was issued with OPTION=SETUSTATUS, and no specific publication ID was given.

Action This is a user error. Check the program and correct the error.

00200180 API: Invalid TOPIC

Explanation A request was issued and no topic name was specified.

Action Specify a topic name.

00200181 API: Invalid User-ID

Explanation The value for the USER-ID field of the API is missing. The USER-ID is a mandatory parameter.

Action This is a user error. Check the value for the USER-ID field in the API of your program.

00200182 API: Invalid Function

Explanation The value for the FUNCTION field of the API is invalid.

Action This is a user error. Check the value for the FUNCTION field in the API of your program.

00200183 API: Invalid CLASS/NAME/SERVICE

Explanation The service is missing or invalid in a Broker call that requires a service, that is, a REGISTER/DEREGISTER or a SEND/RECEIVE/EOC call with no CONV-ID specified.

Action This is a user error. Make sure that at least one of the following fields has been provided: SERVER-CLASS, SERVER-NAME or SERVICE. Together, these fields define the service.

00200184 API: Invalid SEND-LENGTH

Explanation The value for the SEND-LENGTH field of the API is missing.

Action This is a user error. A SEND call always requires a send-length. Check the program and correct the error.

00200185 API: Invalid FUNCTION/CONVID Combination

Explanation The value for the CONV-ID field of the API is invalid, missing, or invalid in combination with the desired function.

Action This is a user error. A SEND/RECEIVE/EOC/UNDO call requires a valid value for the CONV-ID (CID) field. Check the program and correct the error.

00200186 API: Char '.', or ',' not allowed in ACI CB

Explanation The character fields within the EntireX Broker ACI must not contain the metacharacter '.', or ','. These characters are used as special characters in the communication protocol between the Broker stub and the Broker.

Action Correct the wrong character in the EntireX Broker ACI.

00200187 API: Invalid FUNCTION/OPTION Combination

Explanation The FUNCTION / OPTION combination is invalid.

Action This is a user error. Check the value for the OPTION field in conjunction with the FUNCTION field in the API of your program and correct the error.

00200188 API: Invalid Option

Explanation The OPTION field of the API contains an unknown value.

Action This is a user error. Check the value for the OPTION field in the API of your program and correct the error.

00200189 API: Invalid RECEIVE-LENGTH

Explanation The value for the RECEIVE-LENGTH field of the API is missing. RECEIVE calls and blocked SEND calls always require a valid RECEIVE-LENGTH.

Action This is a user error. Check the program and correct the error.

00200190 API: Invalid Cmd/Info Services Version

Explanation The EntireX Broker kernel does not recognize the Command and Information Services API version requested.

Action This is a user error. Please check the following:

- If you are using ETBINFO, ETBCMD or any other Software AG-provided Command and Information Services application: Check that the version of ETBINFO or ETBCMD is the same or earlier than the version of the Broker kernel.
- If you are using your own Command and Information Services application: verify that the Command and Information Services API version will work with the version of EntireX. The following table shows the maximum CIS API version for the respective version of EntireX:

Broker/EntireX Version	Max. CIS API Version
ETB 1 or ETB 2	1
EXX 3,4,5,6	2
EXX 7.1	3
EXX 7.2	4
EXX 7.3	5
EXX 8.0 or 8.1	6
EXX 8.2	7
EXX 9.0	8

- A possible cause for this error is a SEND-LENGTH that is too short. Increase this value if necessary.

00200191 API: Invalid OPTION/CONV-ID Combination

Explanation The OPTION / CONV-ID combination in the API is invalid. For example, a SEND was issued with OPTION=EOC and CONV-ID=NONE or a RECEIVE with OPTION=LAST and no specific conversation ID (CONV-ID) was given.

Action This is a user error. Check the program and correct the error.

00200192 API: Invalid parameter count

Explanation More than four pointers have been supplied in the parameter list used to call the Broker stub.

Action Correct the program. A maximum of four pointers can be supplied.

00200193 API: Invalid FUNCTION/WAIT Combination

Explanation The FUNCTION / WAIT combination in the API is invalid. A WAIT value in the API can be specified for the SEND, RECEIVE and RECEIVE_PUBLICATION functions only.

Action This is a user error. Check the program and correct the error.

00200194 API: Invalid OPTION/WAIT Combination

Explanation The OPTION / WAIT combination in the API is invalid, that is, a SEND with OPTION=EOC, HOLD or SYNC, or a RECEIVE with OPTION=LAST was issued.

Action This is a user error. Check the program and correct the error.

00200195 API: Deregister not allowed from clients

Explanation This response is given when a client tries to issue a deregister call to EntireX Broker.

Action Do not issue a DEREGISTER call for clients. Check the program and correct the error.

00200199 API: Receive/CID=ANY Invalid For Clients

Explanation A client issued a RECEIVE call for new conversations.

Action This is a user error. Clients cannot issue a RECEIVE with CONV-ID=ANY because a RECEIVE with CONV-ID=ANY must be preceded by a REGISTER call. Check the program and correct the error.

00200200 API: RECEIVE/CID=NEW Invalid For Clients

Explanation A client has issued a RECEIVE call for new conversations.

Action This is a user error. Clients cannot issue a RECEIVE with CONV-ID=NEW because a RECEIVE with CONV-ID=NEW must be preceded by a REGISTER call. Check the program and correct the error.

00200203 API: No RECEIVE -BUFFER Address

Explanation The address of the receive buffer is missing for the Broker call. That is, a RECEIVE or a blocked SEND was issued without the receive buffer address.

Action This is a user error. Check the program and correct the error.

00200208 API: Invalid version number

Explanation One of the following errors occurred: Invalid `API-TYPE` or `API-VERSION` supplied by user when calling Broker stub. Invalid version supplied by user in internal control blocks when calling Broker stub. Broker detected an invalid or unsupported prefix version specified by stub. Broker does not support the `API-VERSION` supplied by user.

Action This is a user error. Check version of Broker stubs and Broker kernel. Determine the stub version by using function `FCT_VERSION`. Determine the kernel version by using function `FCT_KERNELVERS`. Correct `API-TYPE` or `API-VERSION` in the Broker control block.

00200210 API: No Send Buffer Address

Explanation A `SEND` was issued without the send buffer address. Therefore, no address is given to the Broker stub as the second parameter.

Action This is a user error. Check the program and correct the error.

00200211 API: No API Control Block Address

Explanation The ACI control block is missing for the call. No address is given to the Broker stub as the first parameter.

Action This is a user error. Check the program and correct the error.

00200212 API: (*) In SN/SC/SV Invalid For Function

Explanation The `FUNCTION / SERVICE` combination provided by the `SERVER-CLASS`, `SERVER-NAME`, and `SERVICE` fields of the API is invalid. That is, a `SEND` function is used with an asterisk (*) in any of the `SERVICE` fields.

Action This is a user error. Check the program and correct the error.

00200216 API: Invalid BROKER-ID

Explanation The `BROKER-ID` field in the API does not contain a valid numeric node ID.

Action The `BROKER-ID` in the API should be the same as the `BROKER-ID` in the Broker attribute file.

00200218 API: Send Or Receive Length Exceed Max

Explanation The maximum length possible for the send buffer/receive buffer depends on the Broker API version and the transport method (TCP/IP or Entire Net-Work) used, and on the configuration of the EntireX Broker.

Action Check the API version and the transport method (TCP/IP or Entire Net-Work) used, and the possible maximum length of send buffer/receive buffer for the transport method. See the field SEND-LENGTH of the Broker ACI control block. See SEND-LENGTH under *Broker ACI Fields*.

Check the Broker attribute MAX-MESSAGE-LENGTH. See MAX-MESSAGE-LENGTH under *Broker Attributes*.

A shortage of the attached buffers or the intermediate user buffers may also lead to this error, especially when attribute EXTENDED-ACB-SUPPORT is set to "YES" to allow buffers greater than 32 KB to be transmitted using transport method NET. Check the Broker attributes NABS and IUBL under *Adabas SVC/Entire Net-Work-specific Attributes* under *Broker Attributes*.

00200226 API Invalid STATUS

Explanation The Broker has returned an invalid status.

Action Contact Software AG support.

00200228 API Invalid CONV-STAT

Explanation The Broker has returned an invalid conversation status.

Action Contact Software AG support.

00200229 API Invalid value for STORE

Explanation There are two possible error sources:

1. The application has supplied an invalid value for STORE in the Broker ACI control block. See STORE under *Broker ACI Fields*.
2. The Broker has returned an invalid value for STORE from the kernel.

Action In situation 1, ensure that the application assigns only a valid value to the field.
In situation 2, contact Software AG support.

00200246 API: Cannot subscribe durable/non-durable

Explanation A SUBSCRIBE request can be made with option DURABLE. If the user is already subscribed to the topic, the same durability scope must be specified as option. A durable subscriber resubscribes with option DURABLE; a non-durable subscriber resubscribes without option DURABLE. A change of the durability scope requires an UNSUBSCRIBE request.

Action Apply the correct option.

00200251 API: Invalid FUNCTION/PUBLID combination

Explanation No publication ID was specified for this CONTROL_PUBLICATION request.

Action Specify the publication ID.

00200252 CID=NONE required for this service

Explanation The application tried to start a conversation when issuing an EntireX Broker command operation. The internal service should be used in non-conversational mode only (CID=NONE).

Action Change your code.

00200267 API: CID=NEW required for this service

Explanation An INFO service request has been started with CID not equal NEW. Because INFO services are conversational, a new conversation must be started with every initial SEND command. The returning information can be spread across several messages which must be received separately.

Action Always send INFO requests with CID=NEW.

00200268 API: REGISTER internal service rejected

Explanation The service that you specified is already registered as an internal service. All service definitions with the class SAG are reserved.

Action Choose another service name

00200302 EOC error: must back out unit of work

Explanation EOC commands are not allowed while a UOW is being built.

Action Do not issue an EOC command before a UOW is committed. This message is for diagnostic purposes only.

00200311 API: Invalid Numeric Field

Explanation The API field must be numeric.

Action Correct the field value.

00200312 API: Out of Range

Explanation The value of a field is incorrect.

Action Correct the field value.

00200314 API: UOW status invalid

Explanation Returned status of UOW is not valid.

Action Check the CONVID and UOWID in the Broker control block.

00200335 No Mixed Message with UOW on the Same CONVID

Explanation You cannot have UOW and non-UOW messages in the same conversation, that is, the same CONVID.

Action Check the application and correct the error.

00200336 No Mixed UOW with MSG on the Same CONVID

Explanation You cannot have UOW and non-UOW messages in the same conversation, that is, the same CONVID.

Action Check the application and correct the error.

00200362 API: Broker Stub De-Initialized

Explanation The Broker stub was initialized but had to be de-initialized because none of the shared library pointers (TCP, XTI or ADALNK) was available.

Action Check for any serious errors that may have caused library cleanup.

00200371 API: Cannot Specify arch w/o codepage

Explanation You cannot specify a DATA-ARCH to which a codepage applies without also specifying the codepage itself, using LOCALE-STRING.

Action Check the application and correct the error.

00200372 API: Error converting locale to codepage

Explanation The locale string sent by a client/server or publish-and-subscribe component could not be mapped to a codepage by the broker's built-in locale string mapping. See *Broker's Built-in Locale String Mapping*.

Action Identify the locale string that could not be mapped to a codepage. The value of the LS keyword (`LS=locale-string`) in the broker trace may be helpful in identifying the erroneous locale string. Please use a valid locale string or define a new mapping in the broker attribute file. See the relevant attribute under `locale-string` for information on how to customize the mapping of locale strings to codepages.

00200377 API: Character Conversion Overflow

Explanation The data/message retrieved after character conversion is larger than the supplied receive buffer. Conversion can increase the amount of your data. No data is provided in the receive buffer. The minimum buffer length required to receive the converted data is returned in the RETURN-LENGTH field of the API if API version 2 or above is used. The client or server should reread the message using a larger buffer with the required length.

Action For RPC components, the error can be ignored because the reread of the message is handled inside the RPC layer. Exception: for older Natural RPC versions it may be necessary to increase the MAX-BUFF parameter.

For ACI programming, see *Error Cases* under *Using Send and Receive Buffers* for information on how to respond to this error code.

00200379 API: Inconsistent security installation

Explanation The setting for security in the Broker kernel is different from the settings in one or more of the Broker stubs. Either the Broker kernel and all stubs must be configured to operate with security, or the kernel and all stubs must be configured to operate without security.

For ACI version 8 and above, this error can be caused by an application not setting the correct value of `KERNELSECURITY` in the EntireX Broker control block field; see `KERNELSECURITY` under *Broker ACI Fields*. The correct value is set automatically by the `KERNELVERS` command and this value must be maintained in the EntireX Broker control block field. If the application is unable or unwilling to perform the `KERNELVERS` command, configure the stub so that the security setting is consistent with the Broker kernel. See `KERNELVERS` under *Broker ACI Functions* and also *Which EntireX Security Solution*.

Action Ensure the security settings are consistent for Broker kernel and all the stubs.

00200380 Some Characters Could not Be Converted

Explanation When receiving a message, the Broker's `CONVERSION` exit determined that at least one character in the incoming message had no equivalent in the receiver's character set. The possibilities for this incomplete conversion:

- The sender's message contained a data value with no corresponding character in the sender's character set.
- All the sender's characters are valid, but at least one of them has no corresponding character in the receiver's character set.

If this condition occurs, the application should consider the received data to be potentially incomplete or missing.

Action Ensure that both sender and receiver are using the correct locale string and that all character values being sent have a corresponding character in the receiver's character set.

00200393 API: (*) in TOPIC invalid for FUNCTION

Explanation Wildcard `ANY` is currently not supported as valid topic name.

Action Use specific topic name.

00200400 Invalid SSL parameter specified

Explanation The Broker ACI call `FCT_SETSSLPARMS` failed due to invalid specifications.

Action Check the 2nd parameter of this broker call and the length specified in the Broker ACI control block.

00200401 Invalid value specified for EL

Explanation Only values of 0, 1 or 2 are valid encryption levels.

Action Correct the setting in the Broker ACI control block.

00200404 CSLNK is not defined, NET disabled

Explanation Entire Net-Work transport layer could not be initialized because the cslnk.so shared library could not be loaded.

Action Set the environment variable CSLNK to point to the cslnk.so library.

00200419 Mismatch of EL and current encryption

Explanation An inconsistency has been detected. The actual security setting to encrypt the payload buffer does not match the specification of the EL parameter in the current broker call.

Action Verify the EL parameter in the Broker ACI control block and/or verify the correct installation of the security exit.

00200420 Mismatch of client encryption and ATTR

Explanation The encryption settings of the EntireX client program do not match the settings in the Broker attribute file.

Action Check the ENCRYPTION-LEVEL specification in the Broker attribute file and adapt the settings to your client program (with respect to the security setting and/or the EL parameter).

00200421 Mismatch of server encryption and ATTR

Explanation For servers with API version below 6, a mismatch was found between the current security settings and the ENCRYPTION-LEVEL specification in the Broker attribute file.

Action Change the security settings:

- Activate / deactivate the security exit on the server side, or
- Amend the ENCRYPTION-LEVEL specification for this service in the Broker attribute file.

00200422 Server EL and ATTR not identical

Explanation For servers with API version 6 or above, the setting of EL and the specification for ENCRYPTION-LEVEL in the Broker attribute file is not identical.

Action Either

- Correct the EL parameter (and security setting) in the server program, or
- Change the ENCRYPTION-LEVEL for this service in the Broker attribute file.

00200424 SETSSLPARMS only valid for transport=SSL

Explanation ACI function FCT_SETSSLPARMS was set for a non-SSL Broker connection.

Action Either change the BROKER-ID to use SSL or do not issue the ACI function FCT_SETSSLPARMS.

00200449 API: Invalid Compress option

Explanation Compression is supported, but invalid option was specified.

Action Correct the compress option.

00200450 Error during data compression

Explanation Compression of the data was attempted, but resulting size was equal to or greater than original data.

Action The compress option is turned OFF for this transmission of data; data will not be compressed.

00200451 Error during data decompression

Explanation During a decompress operation, failure occurred; it is most likely the result of insufficient memory for the process.

Action Increase available memory for process, if possible.

00200452 Unexpected error during comp/decomp

Explanation Error resulted from a compress or decompress operation, and is not accounted for by errors 0450 or 0451.

Action Save trace information. Contact Software AG support.

00200453 Decompressed data corrupt

Explanation When decompressing a compressed data stream, the integrity of the data was compromised.

Action Save trace and data. Contact Software AG support.

00200454 API: Compression is not available

Explanation Compression was requested but is not available

Action Retry the operation without compression.

00200472 API: No PSTORE but durable subscriber

Explanation A durable SUBSCRIBE request requires an available PSTORE, but the PSTORE is not available.

Action Option DURABLE is currently not permitted. Please consult your Broker Administrator.

00200478 EOC Error: Still Unread Unit of Work

Explanation Participant issues the function EOC, but unprocessed UOWs exist for the conversation. The EOC request is rejected.

Action Read the unprocessed UOWs first and issue function EOC afterwards.

00200482 API: CONV-ID NONE not supported

Explanation Value NONE is not supported for the requested EntireX Broker function.

Action Correct application.

00200485 API: User [UN]SUBSCRIBE not allowed

Explanation ALLOW-USER-SUBSCRIBE=NO was specified and therefore subscribe/unsubscribe must be performed by an administrator.

Action No action is required.

00200494 Publish and Subscribe not enabled

Explanation The publish and subscribe subsystem is not enabled due to missing definitions or license issues. Requested EntireX Broker function is rejected.

Action Contact your Broker Administrator.

00200505 Illegal operation due to wrong UOW type

Explanation The specified UOWID does not contain a unit of work

Action Please correct the UOWID.

00200532 API: Error code missing in REPLY-ERROR

Explanation Stub application did not provide a numeric value in the ERROR-CODE field in Broker control block while making a REPLY_ERROR function call.

Action Send a valid numeric value in the ERROR-CODE field of the Broker control block.

00200533 API: Invalid error code in REPLY-ERROR

Explanation Stub application provided an invalid error code in the Broker control block, while making REPLY_ERROR function call. User-defined error codes should not begin with number 8, and should contain only numeric values.

Action Make sure that error code in the Broker control block does not start with '8' and contains only numerals.

00200538 API:Must specify locale to do CONVERSION

Explanation Receiving application did not provide its codepage information in LOCALE-STRING field of the Broker control block.

Action Supply codepage information in the LOCALE-STRING field of the Broker control block. If you want the broker to supply default codepage information, specify MAP=YES in CONVERSION attribute under DEFAULTS=SERVICE section.

00200539 API: Sender did not specify locale info

Explanation Sender application did not provide codepage information in LOCALE-STRING field of the Broker control block.

Action Supply codepage information in the LOCALE-STRING field of the Broker control block. If you want the broker to supply default codepage information, specify MAP=YES in CONVERSION attribute under DEFAULTS=SERVICE section.

00200540 API: :1: value truncated

Explanation The value for RETURN-LENGTH was truncated. This occurs if the value is greater than 99,999,999 and ACI version 8 or below is used.

Action Upgrade to ACI version 9 or above.

00200563 DEREGISTER not completed due to UOWs

Explanation There are still open units of work that have not been committed, cancelled, or backed out yet. The ACI function DEREGISTER was not completed successfully.

Action Finish the open units of work first before calling DEREGISTER.

00200566 API: Invalid value for COMPRESSION TYPE

Explanation The supplied value is invalid. Broker supports compression types GZIP and ZLIB.

Action Correct the program to supply a valid value.

00200569 API: Extension data truncated to fit

Explanation The amount of message extension data to be returned is greater than the value specified under EXTENSION-RECEIVE-LENGTH. Field EXTENSION-RETURN-LENGTH is set to amount of extension data still to be returned.

Action Set EXTENSION-RECEIVE-LENGTH to value of EXTENSION-RETURN-LENGTH and receive the message again (OPTION=LAST) to receive the remaining associated extension data.

00200613 API: Filter already active

Explanation Command and Information Services were unable to add a command log filter as the specified filter was already active.

Action Specify a filter that is not already active.

00200614 API: Filter not found

Explanation Command and Information Services were unable to delete a command log filter as the specified filter did not exist.

Action Specify a filter that does exist.

00200639 API: Protected UOWID has been specified

Explanation An application has specified a protected unit of work ID in an API request. Protected unit of work IDs are 0000000000000000 and 0000000000000001.

Action Specify a non-protected unit of work ID.

00200801 Unsecure shutdown broker not allowed

Explanation The user is not authorized to shut down EntireX Broker.

Action A security violation has occurred. This message and the related user ID are written to the Broker log.

00200901 User did not request SINGLE-CONV-MODE

Explanation A mismatch was detected between settings of service and user regarding the mode chosen to send or receive ARF data. The single conversation mode (one conversation per service) has to be requested by the user before sending or receiving ARF data. It is not possible to change the mode if there are still conversations active that have been created with the old mode.

Action ARF can be configured to use or not to use the ETBSCONV feature (single conversation mode). We strongly recommend using this feature, but it requires a service without any conversations created with the old mode. If the ETBSCONV feature was specified and conversations still exist, these conversations have to be consumed before you change to single conversation mode.

00209400 FUNCTION NOT SUPPORTED

Explanation An unsupported function (UNDO or DELETE) has been issued.

Action Check the program and correct the error.

00209401 CONV-ID VALUE NOT SUPPORTED

Explanation An unsupported value has been specified for the CONV-ID field.

Action This is a user error. Check the program and correct the error.

00209402 WAIT VALUE NOT SUPPORTED

Explanation An unsupported value has been specified for the WAIT operand.

Action This is a user error. Check the program and correct the error.

00209403 OPTION NOT SUPPORTED

Explanation An unsupported value has been specified for the OPTION field.

Action This is a user error. Check the program and correct the error.

00209404 xxxxxxxx - ADAPTER ERROR

Explanation An error has occurred in the EntireX Broker Services protocol adapter. Depending on the protocol in use, it may be an SNA sense code or an MQM reason code.

Action Obtain the error code from the first 8 bytes of the error message (xxxxxxx) or the ADAPTER-ERROR field. Then refer to the appropriate SNA or MQM documentation to determine the actual error.

00209405 INVALID BROKER API REQUEST

Explanation An unsupported value has been specified for CLASS or SERVICE, e.g., APPC is not specified for CLASS.

Action This is a user error. Check the program and correct the error.

Action No action is required.

00209406 CONV-ID REQUIRED FOR DEREGISTER

Explanation No CONV-ID, or an incorrect CONV-ID, was specified for the DEREGISTER function.

Action This is a user error. Check the program and correct the error.

00209407 INVALID REMOTE ATTACH FUNCTION

Explanation OPTION=ATTACH was specified for a function that is not a REGISTER, DEREGISTER, or RECEIVE function.

Action Check the program and correct the error.

00209410 NO ATTACH REQUESTS AVAILABLE

Explanation A Remote Attach Manager program has issued a non-blocked RECEIVE request with WAIT=NO, but there are no pending attach requests.

Action This is an informational message.

00209413 CONV-ID REQUIRED FOR RECEIVE

Explanation An ACI RECEIVE request has been issued without a valid CONV-ID value. All ACI RECEIVE requests must specify a CONV-ID value.

Action Check the program and correct the error.

00209416 MODELQ REQUIRES SPECIFIC CONV-ID=

Explanation An ACI RECEIVE request has been issued by a client program that specified CONVID=OLD or ANY while an MQI MODEL queue was in use.

Action Change the program to use a specific, existing CONVID, or remove the REPLYTOQ specification from the directory entry.

00209417 INVALID MSGTYPE=, WAIT= COMBINATION

Explanation A SEND request has been issued with an invalid combination of MSGTYPE=, WAIT= and CONFIRMATION operands. For example, specifying WAIT=YES when sending a DATAGRAM or a REPLY type message is invalid.

Action Correct the program logic.

00209418 SERVER CANNOT ISSUE SEND CONVID=NONE

Explanation A server program attempted to issue a SEND request with CONVID=NONE, which is not allowed. Server programs must use a specific CONVID when issuing a SEND.

Action Correct the program logic.

00209419 INVALID MESSAGE TYPE FOR SERVER SEND

Explanation A server program attempted to issue a SEND request with MSGTYPE=DATAGRAM or REQUEST, which is not allowed. Server programs are allowed to issue SEND MSGTYPE=REPLY only.

Action Correct the program logic.

00209420 INVALID MESSAGE TYPE FOR CLIENT SEND

Explanation A client program attempted to issue a SEND request with MSGTYPE=REPLY, which is not allowed. Client programs are allowed to issue SEND MSGTYPE=REQUEST or DATAGRAM only.

Action Correct the program logic.

00209421 OPT=SYNC INVALID WITH SEND WAIT=

Explanation A request was issued with OPTION=SYNC and WAIT=YES. It is not possible to issue a "blocking" request (WAIT=YES) within a unit of work.

Action Correct the program logic.

00209422 SYNCPOINT REQUIRES OPTION=COMMIT/BACKOUT

Explanation A SYNCPOINT request was issued without a valid OPTION= specification. Either OPTION=COMMIT or OPTION=BACKOUT must be specified with the SYNCPOINT function.

Action Correct the program logic.

00209423 MSGID REQUIRED WITH CONVID=ANY/NEW/NONE

Explanation A client program must use a specific MSGID when issuing a RECEIVE request with CONVID=ANY, NEW, or NONE.

Action Correct the program logic.

00209424 UNIT FIELD OF WORK NOT SUPPORTED

Explanation An ACI request was received that has specified a value for one of the unit of work fields.

Action Programmer: Ensure no unit of work fields have been specified in the ACI request. If API Version=3 has been specified in the Broker control block (ETBCDEF .H), ensure that the unit of work fields have all been cleared.

00209450 INTERNAL ERROR - GETMAIN FAILED

Explanation An internal buffer shortage has occurred that prevents the function from executing.

Action Review the JES JOBLLOG and external trace for error messages that might give additional information on the problem.

00209451 RECEIVE FAILED - tpname NOT REGISTERED

Explanation A Remote Attach Manager has issued a RECEIVE request for a TP that is not currently REGISTERED to its SERVICE-ID.

Action Modify the Remote Attach Manager program to REGISTER this *tpname*.

00209452 REGISTER REJECTED - function ACTIVE

Explanation A Remote Attach Manager has issued a REGISTER request for a TPNAME that already issued a REGISTER.

Action A TPNAME must be unique and can be registered under one and only one SERVICE-ID.

00209453 UNKNOWN FUNCTION REQUESTED function

Explanation A request was received using the ATTACH-MANAGER DDM, but the request was not a REGISTER, RECEIVE, or DEREGISTER.

Action Correct the Remote Attach Manager program and retry. The external trace may contain additional information for debugging.

00209454 ENTIREX BROKER SERVICES TERMINATED BY OPERATOR

Explanation EntireX Broker Services have been shut down by the computer operator.

Action No action required; normal processing continues.

00209455 function REJECTED, MISSING value

Explanation A Remote Attach Manager has issued a verb that is invalid.

Action The message text will contain the function and missing value. Correct the request and retry.

00209456 tpname NOT DEFINED VIA CONTROL OPERATOR

Explanation A REGISTER request from a Remote Attach Manager is being rejected because of conflicts with Control Operator Interface definitions (RESTRICT-PARTNERS=PROFILE has been specified).

Action Add the TPNAME in the message to the appropriate local LU definitions and retry the Remote Attach Manager program.

00209457 servername STOPPED BY OPERATOR COMMAND

Explanation An Attach Manager RECEIVE was issued, but the specified servername has been stopped by an operator command. The message contains the actual server name.

Action The Remote Attach Manager Dispatcher program may be restarted after using the RESUME, D6 *servername* operator command to reactivate the *servername*.