

webMethods EntireX

EntireX z/OS Batch RPC Server

Version 9.7

October 2014

This document applies to webMethods EntireX Version 9.7.

Specifications contained herein are subject to change and these changes will be reported in subsequent release notes or new editions.

Copyright © 1997-2014 Software AG, Darmstadt, Germany and/or Software AG USA, Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA, Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

Use of this software is subject to adherence to Software AG's licensing conditions and terms. These terms are part of the product documentation, located at <http://softwareag.com/licenses/> and/or in the root installation directory of the licensed product(s).

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third-Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

Use, reproduction, transfer, publication or disclosure is prohibited except as specifically provided for in your License Agreement with Software AG.

Document ID: EXX-BATCHRPC-97-20160805

Table of Contents


1 Inside the RPC Server	1
Worker Models	2
Inbuilt Services	3
Impersonation	6
Usage of Server Mapping Files	7
2 Administering the Batch RPC Server	9
Customizing the RPC Server	10
Configuring the RPC Server	12
Locating and Calling the Target Server	23
Using SSL or TLS with the RPC Server	26
Starting the RPC Server	29
Stopping the RPC Server	29
Activating Tracing for the RPC Server	30
3 Extractor Service	31
Introduction	32
Scope	33
CA Librarian Support	33
Enabling the Extractor Service	34
Disabling the Extractor Service	34
Restrictions	35
4 Deployment Service	37
Introduction	38
Scope	39
Enabling the Deployment Service	39
Disabling the Deployment Service	40
5 Server-side Mapping Files	41
Server-side Mapping Files in the RPC Server	42
Deploying Server-side Mapping Files to the RPC Server	43
Undeploying Server-side Mapping Files to the RPC Server	44
Change Management of Server-side Mapping Files	45
List Deployed Server-side Mapping Files	45
Check if a Server-side Mapping File Revision has been Deployed	46
Access Control: Secure Server Mapping File Deployment	46
Ensure that Deployed Server-side Mapping Files are not Overwritten	46
Is There a Way to Smoothly Introduce Server-side Mapping Files?	46
6 Scenarios and Programmer Information	47
COBOL Scenarios	48
PL/I Scenarios	49
C Scenarios	50
Assembler Scenarios	50
Aborting RPC Server Customer Code and Returning Error to RPC Client	51

1 Inside the RPC Server

▪ Worker Models	2
▪ Inbuilt Services	3
▪ Impersonation	6
▪ Usage of Server Mapping Files	7

The EntireX z/OS Batch RPC Server allows standard RPC clients to communicate with RPC servers on the operating system z/OS running in batch mode. It supports the programming languages COBOL, PL/I and C.

Worker Models



RPC requests are worked off inside the RPC server in worker threads, which are controlled by a main thread. Every RPC request occupies during its processing a worker thread. If you are using RPC conversations, each RPC conversation requires its own thread during the lifetime of the conversation. The Batch RPC Server provides two worker models:

- **FIXED**

The *fixed* model creates a fixed number of worker threads. The number of worker threads does not increase or decrease during the lifetime of an RPC server instance.

- **SCALE**

The *scale* model creates worker threads depending on the incoming load of RPC requests.

A maximum number (thru value of the `workermodel` parameter) of worker threads created can be set to restrict the system load. The minimum number (from value of the `workermodel` parameter), allows you to define a certain number of threads - not used by the currently executing RPC request - to wait for new RPC client requests to process. In this way the RPC server is ready to handle many RPC client requests arriving at the same time.

See parameter `workermodel` under *Configuring the RPC Server*.


Inbuilt Services

Batch RPC Server provides several services for ease-of-use:

- Extractor Service
- Deployment Service
- SMH Listener Service


Extractor Service

The Extractor Service is a prerequisite for remote extractions with the *IDL Extractor for COBOL* and *IDL Extractor for PL/I*. See *Extractor Service* for more information.



Deployment Service


The Deployment Service allows you to deploy server-side mapping files (EntireX Workbench files with extension .svm) interactively using the *Server Mapping Deployment Wizard*. On the RPC server side, the server-side mapping files are stored in a server-side mapping container (VSAM file). See [Server-side Mapping Files in the RPC Server](#) and [Deployment Service](#) for configuration information.




SMH Listener Service

With the SMH Listener Service you use the System Management Hub to monitor the RPC server. See *Administering the EntireX RPC Servers using System Management Hub* in the UNIX and Windows administration documentation.

The SMH Service is switched on if the parameter `smhport` is set. See parameter `smhport` under *Configuring the RPC Server*.



Impersonation



The Batch RPC Server can be configured to execute the RPC request impersonated under the RPC client user ID. This means that for the request execution, the worker thread gets the identity of the RPC client. This is necessary when accessing (security) protected data sets, for example with the [Extractor Service](#). The way authentication is carried out can be controlled by the RPC parameter [impersonation](#).

- For `impersonation` value `AUTO`, the Batch RPC Server does not validate RPC passwords, so you have to make sure the RPC client is correctly authenticated, either by using a secure EntireX Broker (validation must be against the correct mainframe security repository where z/OS user IDs are defined) or with your own security implementation.

- For `impersonation` value YES, the Batch RPC Server uses the RPC user ID and password supplied by the RPC client for authentication and impersonation of the client. This means that the RPC server validates the password.


The picture above shows the configuration `impersonation=yes`.

The lifetime of an impersonated task starts when an open request for an RPC conversation or a non-conversational RPC request is received. It ends when the RPC conversation stops (after a commit operation or timeout) or when the non-conversational RPC request has been performed.

Usage of Server Mapping Files

There are many situations where the Batch RPC Server requires a server mapping file to correctly support special COBOL syntax such as `REDEFINES`, `SIGN LEADING` and `OCCURS DEPENDING ON` clauses, `LEVEL-88` fields, etc.

Server mapping files contain COBOL-specific mapping information that is not included in the IDL file, but is needed to successfully call the COBOL server program.



The RPC server marshals the data in a two-step process: the RPC request coming from the RPC client (Step 1) is completed with COBOL-specific mapping information taken from the server mapping file (Step 2). In this way the COBOL server can be called as expected.

The server mapping files are retrieved as a result of the *IDL Extractor for COBOL* extraction process and the *COBOL Wrapper* if a COBOL server is generated. See *When is a Server Mapping File Required?*.

There are *server-side* mapping files (*EntireX Workbench* files with extension `.svm`) and *client-side* mapping files (*Workbench* files with extension `.cvm`). See *Server Mapping Files for COBOL* and *How to Set the Type of Server Mapping Files*.

If you are using server-side mapping files, you need to customize the server-side mapping container with parameter `svm`. See *Configuring the RPC Server*.



Note: Server mapping files are used for COBOL only.

2 Administering the Batch RPC Server

■ Customizing the RPC Server	10
■ Configuring the RPC Server	12
■ Locating and Calling the Target Server	23
■ Using SSL or TLS with the RPC Server	26
■ Starting the RPC Server	29
■ Stopping the RPC Server	29
■ Activating Tracing for the RPC Server	30

The EntireX z/OS Batch RPC Server allows standard RPC clients to communicate with RPC servers on the operating system z/OS running in batch mode. It supports the programming languages COBOL, PL/I and C.

Customizing the RPC Server

The following elements are used for setting up the Batch RPC Server:

- [Configuration File](#)
- [IBM LE Runtime Options](#)
- [Started Task JCL](#)

Configuration File

The name of the delivered example configuration file is `CONFIG` (see source library `EXP970.SRCE`). The configuration file is specified as a DD definition with a user-defined DD name in the [Started Task JCL](#). The configuration file contains the configuration for the Batch RPC Server. The following settings are important:

- connection information such as broker ID, server address (class, name, service)
- location and usage of server-side mapping container, see [Usage of Server Mapping Files](#)
- scalability parameters
- trace settings
- etc.

For more information see [Configuring the RPC Server](#).

IBM LE Runtime Options

Depending on the feature the Batch RPC Server needs to support (see table below) additional runtime options for IBM's Language Environment need to be set. For a full description of LE runtime options, see [z/OS V1R4.0 Lang Env Prog Guide](#).

Feature	LE Runtime Options	Description
Trap abends of called RPC server programs	ABTERMENC (RETCODE) ⁽¹⁾	Required to also trap the LE abends within a server program.
Level of information if called RPC server program terminates by unhandled condition	TERMTHDACT (UADUMP) ⁽¹⁾	Forces a U4039 system dump for abends not trapped by the server.
SSL/TLS connections	POSIX (ON)	If not specified, TCP or NET connections are supported.

Feature	LE Runtime Options	Description
Call RPC server programs with AMODE 24 as well	ALL31(OFF),STACK(,,BELOW)	If not specified, AMODE 31 is supported.



Note: ⁽¹⁾ Set internally by the Batch RPC Server and cannot be changed.

There are various ways to specify LE runtime options, for example during installation; using JCL; using CSECT CEEUOPT (for application-specific LE runtime options) linked to the RPC Server; etc. We recommend you use the IBM standard approach with CEEOPTS DD statement in the started task JCL. See [Started Task JCL](#) for this purpose. Add the following lines to your started task JCL:

```
//...
//CEEOPTS DD *
ALL31(OFF),STACK(,,BELOW)
/*
//..
```

The example above uses an in-stream data set to configure ALL31(OFF),STACK(,,BELOW) to allow calling of 24-bit and 31-bit programs and configure RPTOPTS(ON) to list all used LE runtime options to SYSOUT.

Started Task JCL

The name of the started task is EXPSRVB (see EntireX job library EXX970.JOBS). The started task contains the following:

- the target server libraries of the called COBOL or PL/I server
- the configuration file used; see [Configuration File](#); specified as a DD definition with a user-defined DD name as RPC server startup argument CFG:

```
CFG=DD:ddname
```

Example using the DD name CONFIG:

```
CFG=DD:CONFIG
```

- LE runtime options used; see [IBM LE Runtime Options](#)
- etc.

Configuring the RPC Server

The following rules apply:

- In the configuration file:
 - Comments must be on a separate line.
 - Comment lines can begin with '*', '/' and ';'.
 - Empty lines are ignored.
 - Headings in square brackets [<topic>] are ignored.
 - Keywords are not case-sensitive.
- Underscored letters in a parameter indicate the minimum number of letters that can be used for an abbreviated command.

For example, in `brokerid=localhost`, `brok` is the minimum number of letters that can be used as an abbreviation, i.e. the commands/parameters `broker=localhost` and `brok=localhost` are equivalents.

Parameter	Default	Values	Req/Opt
<code>brokerid</code>	<code>localhost</code>	Broker ID used by the server. See <i>Using the Broker ID in Applications</i> in the RPC Programming documentation. Example: <code>brokerid=myhost.com:1971</code>	R
<code>ceeoptions</code>		Allows you to change IBM's LE runtime options. This parameter is deprecated. See IBM LE Runtime Options for how to set the LE runtime options.	O
<code>class</code>	<code>RPC</code>	Server class part of the server address used by the server. The server address must be defined as a service in the broker attribute file (see <i>Service-specific Attributes</i> (DEFAULTS=SERVICE) under <i>Broker Attributes</i> in the platform-independent administration documentation). Case-sensitive, up to 32 characters. Corresponds to <code>CLASS</code> . Example: <code>class=MyRPC</code>	R
<code>codepage</code>	<code>no codepage transferred</code>	Depending on the internationalization approach, the codepage (locale string) where incoming data is provided to the COBOL server. Conversely, the COBOL server must provide outgoing data in the	O

Parameter	Default	Values	Req/ Opt
		<p>given codepage, otherwise unpredictable results occur. See <i>What is the Best Internationalization Approach to use?</i> under <i>Internationalization with EntireX</i> for information on which internationalization approach requires a codepage (locale string).</p> <p>By default, no codepage is transferred to the broker. For the most popular internationalization approach, <i>ICU Conversion</i> under <i>Introduction to Internationalization</i>, the correct codepage (locale string) must be provided. This means it must:</p> <ul style="list-style-type: none"> ■ follow the rules described under <i>Locale String Mapping</i> in the internationalization documentation ■ be a codepage supported by the broker ■ be the codepage used in your environment for file and terminal IO, otherwise unpredictable results may occur. <p>Example: codepage=ibm-273</p>	
<code>compresslevel</code>	N	<p>Enforce compression when data is transferred between broker and server. See <i>Data Compression in EntireX Broker</i> in the general administration documentation.</p> <p><code>compresslevel= 0 1 2 3 4 5 6 7 8 9 Y N</code></p> <p>0-9 0=no compression 9=max. compression</p> <p>N No compression. Y Compression level 6.</p> <p>Example: <code>compresslevel=6</code></p>	O
<code>deployment</code>	NO	<p>Activates the deployment service, see Deployment Service. Required to use the Server Mapping Deployment Wizard. See <i>Server Mapping Deployment Wizard</i> in the EntireX Workbench documentation.</p> <p>YES Activates the deployment service. The RPC server registers the deployment service in the broker.</p>	O

Parameter	Default	Values	Req/ Opt		
		<p>NO The deployment service is deactivated. The RPC server does not register the deployment service in the broker.</p> <p>Example: deployment=yes</p>			
<u>encryptionlevel</u>	0	<p>Enforce encryption when data is transferred between client and server. Requires EntireX Security. See ENCRYPTION-LEVEL under <i>Broker ACI Fields</i>.</p> <p>0 Encryption is enforced.</p> <p>1 Encryption is enforced between server and broker kernel.</p> <p>2 Encryption is enforced between server and broker kernel, and also between client and broker.</p> <p>Example: encryptionlevel=2</p>	O		
<u>etblnk</u>	BROKER	<p>Define the broker stub to be used. See <i>Administering Broker Stubs</i> in the z/OS administration documentation for available stubs.</p> <p>Example: etblnk=broker</p>	O		
<u>extractor</u>	NO	<p>The extractor service is a prerequisite for remote extractions. See <i>Extractor Service</i>.</p> <p>extractor=YES <u>NO</u></p> <p>Example: extractor=yes</p>	O		
<u>impersonation</u>	NO	<p>Defines if RPC requests are executed under the user ID of the RPC client. Depending on settings, different levels of checks are done prior to RPC server execution. See also <i>Impersonation</i>.</p> <p>impersonation= <u>NO</u> YES AUTO [, <u>sameuser</u> , anyuser]</p> <table><tr><td>NO</td><td>The RPC request is executed anonymously, which means the user ID of the RPC client is not used. RPC requests are executed under the user ID of the RPC server.</td></tr></table>	NO	The RPC request is executed anonymously, which means the user ID of the RPC client is not used. RPC requests are executed under the user ID of the RPC server.	O
NO	The RPC request is executed anonymously, which means the user ID of the RPC client is not used. RPC requests are executed under the user ID of the RPC server.				

Parameter	Default	Values		Req/ Opt	
		YES	The RPC request runs impersonated under the supplied <i>RPC client user ID</i> . The Batch RPC Server validates the <i>RPC client user ID/password</i> pair against the mainframe security repository.		
		AUTO	Same as option YES above, except that no password validation is performed, that is, the client is treated as already authenticated. For this setting, make sure the RPC client is correctly authenticated; use either <ul style="list-style-type: none">■ a secure broker (validation must be against the correct mainframe security repository where the user IDs are defined) and option <code>sameuser</code> or■ your own security implementation (option <code>anyuser</code> is supported for compatibility reasons if you need different broker and server user IDs - the customer-written security implementation must validate the RPC client using the <i>RPC client user ID</i>)		
			<code>sameuser</code>	The Batch RPC Server checks whether the <i>broker client user ID</i> matches the <i>RPC client user ID</i> . This is the default if AUTO is used.	
			<code>anyuser</code>	The <i>RPC client user ID</i> is used for impersonation. The <i>broker client user ID</i> is ignored.	
		Note: 1. EntireX supports two user ID/password pairs: a <i>broker client user ID/password</i> pair and an			

Parameter	Default	Values	Req/ Opt
		<p>(optional) <i>RPC user ID/password</i> pair sent from RPC clients to the RPC server.</p> <ol style="list-style-type: none"> With EntireX Security, the <i>broker client user ID/password</i> pair is checked. The <i>RPC user ID/password</i> pair is designed to be checked by the target RPC server. Thus it is possible to use different user IDs in the broker and target RPC server. RPC clients send the (optional) <i>RPC user ID/password</i> pair in the same way as specifying the Natural user ID/password pair for a Natural RPC Server. See for example <i>Using Natural Security</i> in the respective section of the documentation. If the RPC client does not specify the optional <i>RPC user ID/password pair</i>, the <i>broker client user ID</i> is inherited to the <i>RPC user ID</i> and thus used for impersonation by the Batch RPC Server. <p>Example: <code>impersonation=auto,anyuser</code></p> <p>Using impersonation requires additional installation steps. See <i>Using z/OS Privileged Services</i> in the z/OS installation documentation.</p>	
<code>library</code>	no default	<p><code>library = search-logic [- library]</code> where <i>search-logic</i> is one of <code>FIX(dllname) PREFIX(prefix) PREFIX()</code></p> <p>This parameter applies to programming language C only. Do not set if other programming languages for RPC server are used.</p> <p><code>FIX(dllname)</code> The IDL library name coming from the RPC client is ignored, thus long IDL library names can be used. You have to define the DLL names for all client interface objects and RPC servers.</p> <p><code>PREFIX(prefix)</code> The IDL library name coming from the RPC client is used to form the DLL name. As <i>prefix</i> you can define any character. If an RPC client sends, for example, "SYSTEM" as the IDL</p>	O

Parameter	Default	Values	Req/ Opt				
		<div><div>library name and "D" is defined as <i>prefix</i>, the DLL name derived is "DSYSTEM". This configuration restricts the IDL library names to max. 7 characters.</div><div>PREFIX()<div>The IDL library name coming from the RPC client is used as DLL name. This configuration restricts the IDL library names to max. 8 characters.</div></div></div> <div>Example PREFIX configuration (this configuration matches the standard names produced by the C Wrapper): library=PREFIX(D)-PREFIX()</div> <div>Example FIX configuration: library=FIX(MYSTUBS)-FIX(MYRPCS)</div>					
<u>logon</u>	YES	<div>Execute broker functions LOGON/LOGOFF in worker threads. Must match the setting of the broker attribute AUTOLOGON. Reliable RPC requires logon set to YES. See <i>Reliable RPC</i>.</div> <div>NO No logon/logoff functions are executed.</div> <div><u>YES</u> Logon/logoff functions are executed.</div> <div>Example: logon=no</div>	O				
<u>marshalling</u>	COBOL	<div>The Batch RPC Server can be configured to support either COBOL, PL/I or C. See also <i>Locating and Calling the Target Server</i>.</div> <div>marshalling=(LANGUAGE=<u>COBOL</u> <u>PLI</u> <u>flavor=ENTERPRISE</u> <u>MVS</u> <u>C</u>)</div> <table><tr><td>COBOL</td><td>Server supports COBOL. The COBOL servers are called directly without a server interface object. So-called server mapping files are used to call the COBOL server correctly if one is available. See <i>Usage of Server Mapping Files</i>.</td></tr><tr><td>PLI</td><td>Server supports PL/I Server compiled with IBM's PL/I. In z/OS load modules</td></tr></table>	COBOL	Server supports COBOL. The COBOL servers are called directly without a server interface object. So-called server mapping files are used to call the COBOL server correctly if one is available. See <i>Usage of Server Mapping Files</i> .	PLI	Server supports PL/I Server compiled with IBM's PL/I. In z/OS load modules	O
COBOL	Server supports COBOL. The COBOL servers are called directly without a server interface object. So-called server mapping files are used to call the COBOL server correctly if one is available. See <i>Usage of Server Mapping Files</i> .						
PLI	Server supports PL/I Server compiled with IBM's PL/I. In z/OS load modules						

Parameter	Default	Values	Req/ Opt
		<div>produced by newer IBM PL/I compilers and linkers, the flavor can be detected automatically, thus <code>flavor</code> can be omitted.</div> <div>ENTERPRISE Enterprise compiler z/OS. This is the default if PL/I is used. See prerequisites for z/OS.</div> <div>MVS Server supports PL/I Server compiled with older IBM compiler PL/I MVS & VM V1R1 and above. See prerequisites for z/OS.</div> <div>C Server supports C. The modules are called using a server interface object built with the <i>C Wrapper</i>.</div>	
<code>password</code>	no default	<p>Password for broker logon. Case-sensitive, up to 32 characters. For more information see broker ACI control block field <code>PASSWORD</code>.</p> <p>Example: <code>password=MyPwd</code></p>	O
<code>restartcycles</code>	15	<p>Number of restart attempts if the broker is not available. This can be used to keep the Batch RPC Server running while the broker is down for a short time. A restart cycle will be repeated at an interval which is calculated as follows:</p> <p><code>timeout + ETB_TIMEOUT + 60 seconds</code></p> <p>where <code>timeout</code> is the RPC server parameter (see this table), and <code>ETB_TIMEOUT</code> is the environment variable (see <i>Environment Variables in EntireX</i> in the general administration documentation)</p>	O

Parameter	Default	Values	Req/ Opt
		<p>When the number of cycles is reached and a connection to the broker is not possible, the RPC server stops.</p> <p>Example: restartcycles=30</p>	
<u>return_code</u>	NO	<p>Enable application-specific errors. return_code=(<u>NO</u> YES)</p> <p>NO No tests of COBOL special register RETURN-CODE for application-provided error.</p> <p>YES After execution of the RPC server, tests COBOL special register RETURN_CODE for application provided error. See Aborting RPC Server Customer Code and Returning Error to RPC Client.</p> <p>Example: return_code=yes</p>	O
<u>runoption</u>	no default	<p>This parameter is for special purposes. It provides the Batch RPC Server with additional information. The runoptions are normally set to meet the platform's requirements. Set this parameter only if a support representative provides you with an option and asks you to do so. The parameter can be defined multiple times.</p> <p>Example: runoption=<option> runoption=<option></p>	O
<u>servername</u>	SRV1	<p>Server name part of the server address used by the server. The server address must be defined as a service in the broker attribute file. See <i>Service-specific Attributes</i> (DEFAULTS=SERVICE) under <i>Broker Attributes</i> in the platform-independent administration documentation. Case-sensitive, up to 32 characters. Corresponds to SERVER of the broker attribute file.</p> <p>Example: servername=mySrv</p>	R
<u>service</u>	CALLNAT	<p>Service part of the server address used by the server. The server address must be defined as a service in the broker attribute file. See <i>Service-specific Attributes</i> (DEFAULTS=SERVICE) under <i>Broker Attributes</i> in the platform-independent administration documentation.</p>	R

Parameter	Default	Values	Req/ Opt
		Case-sensitive, up to 32 characters. Corresponds to SERVICE attribute of the broker attribute file. Example: service=MYSERVICE	
<code>smhport</code>	0	The port where the server listens for commands from the System Management Hub (SMH). If this port is 0 (default), no port is used and management by the SMH is disabled. Example: smhport=3001	O
<code>ssl_file</code>	no default	Set the SSL parameters. See Using SSL or TLS with the RPC Server for examples and more information.	O
<code>svm</code>	ERXSVM	Usage and location of server-side mapping files; see Server-side Mapping Files in the RPC Server . If no <code>svm</code> parameter is given, the RPC server tries to open the server-side mapping container using DD name ERXSVM. If this DD name is not available, no server-side mapping files are used. If you use server-side mapping files, the server-side mapping container must be installed and configured; see <i>Install the Server-side Mapping Container for a Batch RPC Server (Optional)</i> under <i>Installing the EntireX RPC Servers under z/OS</i> . There are also client-side mapping files that do not require configuration here; see <i>Server Mapping Files in the EntireX Workbench</i> in the EntireX Workbench documentation. <code>svm = no ddname</code> <code>no</code> No server-side mapping files are used. <code>ddname</code> DD name of the server-side mapping container in the started task JCL of the Batch RPC Server. Example: svm=MY SVM For the example above, define the DD name MY SVM in the started task JCL of the Batch RPC Server (see Started Task JCL) as	O

Parameter	Default	Values	Req/ Opt
		//MYSVM DD DISP=SHR,DSN=<svm.cluster> See also Usage of Server Mapping Files .	
<code>timeout</code>	60	Timeout in seconds, used by the server to wait for broker requests. See broker ACI control block field WAIT for more information. Also influences restartcycles . Example: timeout=300	O
<code>tracedestination</code>	DD:ERXTRACE	The name of the destination file for trace output. tracedestination=DD:ddname, where ddname is the name of the trace file. Example: tracedestination=DD:MYTRACE The DD name MYTRACE must be defined in the started task of the Batch RPC Server (see Started Task JCL): //MYTRACE DD DISP=SHR,DSN=<rpctrace-file>	O
<code>tracelevel</code>	None	Trace level for the server. See also Activating Tracing for the RPC Server . tracelevel = <u>None</u> Standard Advanced ↔ Support None No trace output. Standard For minimal trace output. Advanced For detailed trace output. Support This trace level is for support diagnostics and should only be switched on when requested by Software AG support. Example: tracelevel=standard	O
<code>traceoption</code>	None	Additional trace option if trace is active. None No additional trace options. STUBLOG If tracelevel is Advanced or Support, the trace additionally activates the broker stub log.	O

Parameter	Default	Values	Req/ Opt								
		<p>NOTRUNC Normally if a data buffer larger than 8 KB is traced, the buffer trace is truncated. Set this option to write the full amount of data without truncation.</p> <p>Note: This can increase the amount of trace output data dramatically if you transfer large data buffers.</p> <p>Example: traceoption=(STUBLOG,NOTRUNC)</p>									
<u>userid</u>	ERX-SRV	<p>Used to identify the server to the broker. See broker ACI control block field USER- ID. Case-sensitive, up to 32 characters.</p> <p>Example: userid=MyUid</p>	R								
<u>workermodel</u>	SCALE,1,3,slowshrink	<p>The Batch RPC Server can be configured to</p> <ul style="list-style-type: none">■ adjust the number of worker threads to the current number of client requests: <pre>workermodel=(SCALE,from,thru [,slowshrink ↵ fastshrink])</pre> <ul style="list-style-type: none">■ use a fixed number of worker threads: <pre>workermodel=(FIXED,number)</pre> <table><tr><td>FIXED</td><td>A fixed <i>number</i> of worker threads is used by the Batch RPC Server.</td></tr><tr><td>SCALE</td><td>The number of worker threads is adjusted to the current number of client requests. With the <i>from</i> value, the minimum number of active worker threads can be set. The <i>thru</i> value restricts the maximum number of worker threads.</td></tr><tr><td></td><td><table><tr><td>slowshrink</td><td>The RPC server stops all worker threads not used in the time specified by the</td></tr></table></td></tr></table>	FIXED	A fixed <i>number</i> of worker threads is used by the Batch RPC Server.	SCALE	The number of worker threads is adjusted to the current number of client requests. With the <i>from</i> value, the minimum number of active worker threads can be set. The <i>thru</i> value restricts the maximum number of worker threads.		<table><tr><td>slowshrink</td><td>The RPC server stops all worker threads not used in the time specified by the</td></tr></table>	slowshrink	The RPC server stops all worker threads not used in the time specified by the	O
FIXED	A fixed <i>number</i> of worker threads is used by the Batch RPC Server.										
SCALE	The number of worker threads is adjusted to the current number of client requests. With the <i>from</i> value, the minimum number of active worker threads can be set. The <i>thru</i> value restricts the maximum number of worker threads.										
	<table><tr><td>slowshrink</td><td>The RPC server stops all worker threads not used in the time specified by the</td></tr></table>	slowshrink	The RPC server stops all worker threads not used in the time specified by the								
slowshrink	The RPC server stops all worker threads not used in the time specified by the										

Parameter	Default	Values		Req/ Opt
				<code>timeout</code> parameter, except for the number of workers specified as minimum value. This is the default if <code>SCALE</code> is used.
			<code>fastshrink</code>	The RPC server stops worker threads immediately as soon as it has finished its conversation, except for the number of workers specified as minimum value.
		Example: <code>workermodel=(SCALE,2,5)</code>		

Locating and Calling the Target Server

The IDL library and IDL program names that come from RPC client are used to locate the RPC server. See `library-definition` and `program-definition` under *Software AG IDL Grammar* in the *IDL Editor* documentation. This two-level concept (library and program) has to be mapped to the Batch RPC Server environment. Different mechanisms are used depending on the language:

- `COBOL`
- `PL/I`
- `C`
- `Assembler (IBM 370)`

COBOL

The approach used to derive the z/OS module name for the RPC server depends on whether server mapping is used or not. See [Usage of Server Mapping Files](#) for an introduction.

1. If the RPC client sends a client-side type of server mapping with the RPC request, this server mapping is used first.
2. If no server mapping is available from step 1 above, and if server-side type of server mapping is used, the IDL library and IDL program names are used to form a key to locate the server mapping in the server-side mapping container. If a server mapping is found, this is then used.
3. If a server mapping is available from step 1 or 2 above, the z/OS module name of the RPC server is derived from this mapping. In this case the IDL program name can be different to the

z/OS module name if it is renamed during wrapping process (see *Customize Automatically Generated Server Names*) or during the extraction process in the *COBOL Mapping Editor*.

4. If no server mapping is used at all, the IDL program name is used as the z/OS module name of the RPC server (the IDL library name is ignored).

➤ To use the Batch RPC Server with COBOL

- 1 Make sure that all z/OS modules called as RPC servers
 - are compiled with IBM's Language Environment (see [z/OS V1R4.0 Lang Env Prog Guide](#) for more information)
 - use COBOL calling conventions
 - can be called dynamically ("fetched") from any Language Environment program
 - are accessible through the Batch RPC Server started task JCL STEPLIB concatenation. See [Started Task JCL](#).
- 2 Configure the parameter `marshalling` for COBOL, for example:

```
marshalling=COBOL
```

- 3 Configure the parameter `svm` depending on whether server-side mapping files are used or not. See [Usage of Server Mapping Files](#).

See also [Scenario I: Calling an Existing COBOL Server](#) or [Scenario II: Writing a New COBOL Server](#).

PL/I

There is a simple mechanism to derive the RPC server z/OS module name:

- The IDL program name is used as the z/OS module name.
- The IDL library name is not used.

➤ To use the Batch RPC Server with PL/I

- 1 Make sure that all z/OS modules called as RPC servers
 - are compiled with IBM's Language Environment (see [z/OS V1R4.0 Lang Env Prog Guide](#) for more information)
 - use PL/I calling conventions
 - can be called dynamically ("fetched") from any Language Environment program

- are accessible through the Batch RPC Server started task JCL STEPLIB concatenation. See [Started Task JCL](#).

2 Configure the parameter `marshalling` for PL/I, for example `marshalling=PLI`.

See also [Scenario III: Calling an Existing PL/I Server](#) or [Scenario IV: Writing a New PL/I Server](#).

C

The approaches needed to derive the dynamic-link library (DLL) names for the RPC server are more complex for C, for the following reasons:

- the limitation of 8 characters per (physical) member (DLL name in PDSE)
- the maximum length of 128 characters per IDL library name (see *Rules for Coding Library, Library Alias, Program, Program Alias and Structure Names* under *Software AG IDL File* in the IDL Editor documentation).

Either you restrict yourself in short IDL library names (up to 8 characters) and use the flexible `PREFIX` configuration, or, if you need independence from the IDL library length and names, use the `FIX` configuration. The parameter `library` is used for this purpose.

➤ To use the Batch RPC Server with C

- 1 Make sure all dynamic-link libraries (DLLs) called as RPC servers and client interface objects are accessible through the Batch RPC Server started task JCL STEPLIB concatenation. See *Started Task JCL* under *Administering the Batch RPC Server*.
- 2 Configure the parameter `marshalling` for C, for example `marshalling=C`.
- 3 Configure the parameter `library` either with the `FIX` configuration or `PREFIX` configuration, depending on how you have built your DLLs. See *Using the C Wrapper for the Server Side (z/OS, UNIX, Windows, BS2000/OSD, IBM i)*.

See also [Scenario V: Writing a New C Server](#).

Assembler (IBM 370)

There is a simple mechanism to derive the RPC server z/OS module name:

- The IDL program name is used as the z/OS module name
- The IDL library name is not used.

➤ To use the Batch RPC Server with Assembler

- Make sure all z/OS modules called as RPC Servers

- are accessible through the Batch RPC Server started task JCL STEPLIB concatenation. See *Started Task JCL* under *Administering the Batch RPC Server*.
- Use PL/I or COBOL calling conventions. Configure the parameter `marshalling` for PL/I or COBOL.

See also [Scenario VI: Writing a New Assembler Server](#).

Using SSL or TLS with the RPC Server

The Batch RPC Server supports certificates stored in RACF as keyrings. There are two ways of specifying the RACF keyring and other SSL or TLS parameters, depending on the complexity of the parameters:

- as part of the Broker ID for short parameters, the simplest way
- using the SSL file, a text file containing more complex parameters.

As an alternative, you can use for this purpose IBM's Application Transparent Transport Layer Security (AT-TLS), where the establishment of the SSL or TLS connection is pushed down the stack into the TCP layer.

This section covers the following topics:

- [Specifying the SSL or TLS Parameters as Part of the Broker ID](#)
- [Specifying the SSL or TLS Parameters in a Separate File](#)
- [Using IBM's Application Transparent Transport Layer Security \(AT-TLS\)](#)

For more information, see *SSL or TLS and Certificates with EntireX*.

Specifying the SSL or TLS Parameters as Part of the Broker ID

» To specify the SSL or TLS parameters as part of the Broker ID

- 1 In the [Started Task JCL](#) set the LE runtime option `POSI(ON)`, see [IBM LE Runtime Options](#).
- 2 Add the RACF keyring `<user-id>/<ring-name>` and other SSL or TLS parameters to the server parameter `brokerid` in the [Configuration File](#). SSL or TLS parameters are separated by ampersand (&).

Example with *Transport-method-style* Broker ID:

```
ETB024:1609:SSL?TRUST_STORE=<user-id>/<ring-name>&VERIFY_SERVER=N
```

Example with *URL-style Broker ID*:

```
ssl://localhost:2010?TRUST_STORE=<user-id>/<ring-name>&VERIFY_SERVER=N
```

- 3 Make sure the target the Batch RPC Server connects to is prepared for SSL/TLS connections as well. See the following sections:
 - *Running Broker with SSL or TLS Transport* in the respective section of the administration documentation
 - *Setting up and Administering the Broker SSL Agent* in the UNIX and Windows administration documentation
 - Direct RPC in the EntireX Adapter documentation under [http://documentation.software-ag.com > webMethods Product Line](http://documentation.software-ag.com/webMethods/ProductLine)

Specifying the SSL or TLS Parameters in a Separate File

» To specify the SSL or TLS parameters in the SSL file

- 1 In the *Started Task JCL* set the LE runtime option `POSI(ON)`, see *IBM LE Runtime Options*.
- 2 Define a so-called SSL file in text format (for example as a PDS member) with the RACF keyring `<user-id>/<ring-name>` and other SSL or TLS parameters.

Example:

```
TRUST_STORE=<user-id>/<ring-name>
VERIFY_SERVER=N
```



Note: Each line in the SSL file must be terminated with hexadecimal zero.

- 3 In the *Configuration File*, define a DDNAME to be used in the *Started Task JCL* to enable the Batch RPC Server to access the SSL file defined in Step 2 above.

Example:

```
...
SS_FILE=DD:MYSSL
...
```

- 4 Add a DD statement to the *Started Task JCL* using the DDNAME defined in Step 3 above to point to the SSL file defined in Step 2 above.

Example:

```
//...  
//MYSSL DD DISP=SHR,DSN=<high-level-qualifier>.MYPDS(SSLFILE)  
//...
```

- 5 In the *Configuration File* define the server parameter `brokerid` for SSL or TLS connections.

Example with *Transport-method-style Broker ID*:

```
ETB024:1609:SSL
```

Example with *URL-style Broker ID*:

```
ssl://localhost:2010
```

- 6 Make sure the target the Batch RPC Server connects to is prepared for SSL/TLS connections as well. See the following sections:
- *Running Broker with SSL or TLS Transport* in the respective section of the administration documentation
 - *Setting up and Administering the Broker SSL Agent* in the UNIX and Windows administration documentation
 - Direct RPC in the EntireX Adapter documentation under <http://documentation.software-ag.com> > *webMethods Product Line*

Using IBM's Application Transparent Transport Layer Security (AT-TLS)

» To set up SSL or TLS with AT-TLS

- 1 Set up the Batch RPC Server for a TCP/IP connection.
- 2 Configure the rules for the AT-TLS policy agent the Batch RPC Server matches, for example by using the job name and remote port number the Batch RPC Server connects to. Used certificates are also defined with those rules. Refer to your IBM documentation for further information.
- 3 Make sure the target the Batch RPC Server connects to is prepared for SSL/TLS connections as well. See the following sections:
 - *Running Broker with SSL or TLS Transport* in the respective section of the administration documentation
 - *Setting up and Administering the Broker SSL Agent* in the UNIX and Windows administration documentation
 - Direct RPC in the EntireX Adapter documentation under <http://documentation.software-ag.com> > *webMethods Product Line*

Starting the RPC Server

➤ To start the Batch RPC Server

- 1 Modify the member EXPSRVB (see EntireX job library EXX970.JOBS) according to your system requirements and copy the started task JCL to your system PROCLIB concatenation. See [Started Task JCL](#).
- 2 Modify the server parameters [Configuration File](#) according to your system requirement. For details, see [Configuring the RPC Server](#).
- 3 Start the task manually with

```
/s EXPSRVB
```

Or:

Add the task to your system automation tool(s)

Stopping the RPC Server

➤ To stop the Batch RPC Server

- Use the operator command STOP. Examples:

```
/p EXPSRVB  
/f EXPSRVB,STOP
```

Or:

Add the STOP command to your system automation tool(s).

Or:

Use the System Management Hub; this method ensures that the deregistration from the Broker is correct. See *Broker Administration using System Management Hub* in the UNIX and Windows administration documentation.

Activating Tracing for the RPC Server

➤ To switch on tracing for Batch RPC Server

- 1 Set the parameters `tracelevel` and `tracedestination`.
- 2 Dynamically change the trace level with the operator command

```
F EXPSRVB,TRACELEVEL=tracelevel,
```

for valid *tracelevel* values, see `tracelevel`.

The `TRACELEVEL` command without any value will report the currently active trace options, for example:

```
F EXPSRVB,TRACELEVEL
```

might reply with the operator message

```
Tracelevel=0 TraceFile=DD:ERXTRACE
```

To evaluate the return codes, see *Component Return Codes in EntireX* under *Error Messages and Codes*.

3


Extractor Service

■ Introduction	32
■ Scope	33
■ CA Librarian Support	33
■ Enabling the Extractor Service	34
■ Disabling the Extractor Service	34
■ Restrictions	35

Introduction

The extractor service

- provides access to PDS data sets and CA Librarian DA master files defined within the z/OS catalog
- provides access to security-protected data sets (protected e.g. by RACF, CA ACF2, CA Top Secret)
- is a built-in service of the RPC server, which can be enabled/disabled by RPC server configuration settings
- depending on the platform where the broker is running, usage can be restricted to certain users or group of users, using EntireX Security; see *Authorization of Client and Server* under *Overview of EntireX Security* in the EntireX Security documentation.



Scope

The extractor service is a prerequisite for the

- **IDL Extractor for COBOL**

used together with a remote extractor environment, see *Step 2: Select a COBOL Extractor Environment or Create a New One* in the IDL Extractor for COBOL documentation.

- **IDL Extractor for PL/I**

used together with an RPC environment, see *RPC Environment Manager* in the IDL Extractor for PL/I documentation

The extractor service uses the same class and server names as defined for the RPC server, and "EXTRACTOR" as the service name, resulting in `class/server/EXTRACTOR` as the broker service. Please note "EXTRACTOR" is a service name reserved by Software AG. See `SERVICE` under *Broker Attributes*.

CA Librarian Support

- Supported Features:

- Traditional CA Librarian DA master files are supported.
- Extraction from multiple CA Librarian data sets is possible.
- CA Librarian archive levels (history) are supported for the COBOL (main) source where the extraction starts.
- Security RACROUTE is supported.
- PDS data sets and CA Librarian data sets can be mixed, that is:
 - the COBOL source can reside in a PDS, and some copybooks in CA Librarian, and others in PDS
 - the COBOL source can reside in CA Librarian, and some copybooks in PDS and others in CA Librarian
 - -INC and COBOL COPY statements can be mixed in one source

Enabling the Extractor Service

➤ To enable the extractor service

- 1 Set the Batch RPC Server parameter `extractor=yes`. See `extractor` under *Configuring the RPC Server*.
- 2 Define in the broker attribute file, under the RPC service, an additional broker service with "EXTRACTOR" as the service name and values for class and server identical to those used for the RPC service. For example, if your RPC service is named

```
CLASS = RPC      SERVER = SRV1      SERVICE = CALLNAT
```

the extractor service requires the following additional service definition in the Broker attribute file:

```
CLASS = RPC      SERVER = SRV1      SERVICE = EXTRACTOR
```

- 3 Optional. If you need to restrict the use of the extractor service to a selected group of users, use EntireX Security and define security rules for the `class/server/EXTRACTOR` broker service. The service name `EXTRACTOR` is a constant.
 - For a z/OS broker, see *Resource Profiles in EntireX Security* in the EntireX Security documentation.
 - For a UNIX or Windows broker, see *Administering Authorization Rules using System Management Hub* in the UNIX and Windows administration documentation.
 - Not applicable to a BS2000/OSD broker.
- 4 Optional. Use the `impersonation` feature of the Batch RPC Server to enable access to security-protected data sets (protected e.g. by RACF, CA ACF2, CA Top Secret). See `impersonation` under *Configuring the RPC Server*.

Disabling the Extractor Service

➤ To disable the extractor service

- Set the Batch RPC Server parameter `extractor=no`. See `extractor` under *Configuring the RPC Server*. The Batch RPC Server will not register the extractor service in the broker.

Restrictions

The following restrictions apply to CA Librarian:

- Filtering with programmer and type, as is done by the CA Librarian ELIPS (Extended Librarian Interactive Productivity Services) application, is not supported.
- CA Librarian Wide Record Master Files (PDS/E - PO) are not supported.
- CA Librarian MCD Security is not supported
- CA Librarian member passwords (NOBYPP installations) are not supported
- The optional syntax elements `seq1`, `seq2` and `ARC` of the CA Librarian `-INC` `module-name[,seq1[,seq2][,ARC={date | Lx | -y}]` statement are not supported. Therefore CA Librarian archive levels (history) are not supported for COBOL copybooks. It is always the most recent member (last update) that is delivered by the extractor service.

No access is provided to other data sets (e.g. CA Panvalet) or to data sets not defined in the z/OS catalog (e.g. defined in VTOC only).

4

Deployment Service


■ Introduction	38
■ Scope	39
■ Enabling the Deployment Service	39
■ Disabling the Deployment Service	40

Introduction

The deployment service is the (server-side) counterpart to the deployment wizard; see *Server Mapping Deployment Wizard*. It is a built-in service of the EntireX RPC server, which can be enabled/disabled by EntireX RPC server configuration settings.

Usage can be restricted to certain users or group of users, using EntireX Security; see *Authorization of Client and Server* under *Overview of EntireX Security* in the EntireX Security documentation.

You need to configure the deployment service only when server-side mapping files are used. There are also client-side server mapping files that do not need configuration here; see *Server Mapping Files for COBOL* in the EntireX Workbench documentation.



Scope

The deployment service is used in conjunction with the

- IDL Extractor for COBOL to deploy server-side mapping files with the deployment wizard;
- COBOL Wrapper for RPC server generation to deploy server-side mapping files with the deployment wizard.

See also [Deploying Server-side Mapping Files to the RPC Server](#).

The deployment service uses the same class and server names as defined for the EntireX RPC server, and `DEPLOYMENT` as the service name, resulting in `class/server/DEPLOYMENT` as the broker service. Please note `DEPLOYMENT` is a service name reserved by Software AG. See broker attribute `SERVICE`.

Enabling the Deployment Service

» To enable the deployment service

- 1 For a Batch RPC Server, the server-side mapping container (VSAM file) must be installed and configured. See *Install the Server-side Mapping Container for a Batch RPC Server (Optional)* under *Installing the EntireX RPC Servers under z/OS*.
- 2 Set the RPC server parameter `deployment=yes`. See `deployment` under [Configuring the RPC Server](#).
- 3 Define in the broker attribute file, under the RPC service, an additional broker service with `DEPLOYMENT` as the service name and values for class and server identical to those used for the RPC service. For example, if your RPC service is named

```
CLASS = RPC      SERVER = SRV1      SERVICE = CALLNAT
```

the deployment service requires the following additional service definition in the broker attribute file:

```
CLASS = RPC      SERVER = SRV1      SERVICE = DEPLOYMENT
```

- 4 Optional. If you need to restrict the use of the deployment service to a selected group of users, use EntireX Security and define security rules for the `class/server/DEPLOYMENT` broker service. The service name `DEPLOYMENT` is a constant.
 - For a z/OS broker, see *Resource Profiles in EntireX Security* in the EntireX Security documentation.

- For a UNIX or Windows broker, see *Administering Authorization Rules using System Management Hub* in the UNIX and Windows administration documentation.
- Not applicable to a BS2000/OSD or z/VSE broker.

Disabling the Deployment Service

➤ To disable the deployment service

- Set the Batch RPC Server parameter `deployment=no`. See `deployment` under *Configuring the RPC Server*.

The Batch RPC Server will not register the deployment service in the broker.

5

Server-side Mapping Files

▪ Server-side Mapping Files in the RPC Server	42
▪ Deploying Server-side Mapping Files to the RPC Server	43
▪ Undeploying Server-side Mapping Files to the RPC Server	44
▪ Change Management of Server-side Mapping Files	45
▪ List Deployed Server-side Mapping Files	45
▪ Check if a Server-side Mapping File Revision has been Deployed	46
▪ Access Control: Secure Server Mapping File Deployment	46
▪ Ensure that Deployed Server-side Mapping Files are not Overwritten	46
▪ Is There a Way to Smoothly Introduce Server-side Mapping Files?	46

Server mapping enables the RPC server to correctly support special COBOL syntax such as `REDEFINES`, `SIGN LEADING` and `OCCURS DEPENDING ON` clauses, `LEVEL-88` fields, etc. If one of these elements is used, the IDL Extractor for COBOL automatically extracts a server mapping file in addition to the IDL file (interface definition language). Also, the COBOL Wrapper may generate a server mapping file for RPC server generation. The server mapping is used at runtime to marshal and unmarshal the RPC data stream. There are client-side mapping files (EntireX Workbench files with extension `.cvm`) and server-side mapping files (Workbench files with extension `.svm`). If you have not used server-side mapping, we recommend you use client-side mapping. See *Server Mapping Files for COBOL* in the EntireX Workbench documentation.

See also *Source Control of Server Mapping Files* | *Comparing Server Mapping Files* | *When is a Server Mapping File Required?* | *Migrating Server Mapping Files* in the EntireX Workbench documentation.

Server-side Mapping Files in the RPC Server

Under z/OS, server-side mapping corresponds to lines of EntireX Workbench files with extension `.svm`. See *Server Mapping Files for COBOL*. The mapping information is stored as records within one VSAM file, the server-side mapping container. This container contains all server-side mapping entries from all EntireX Workbench files with extension `.svm`. The unique key of the VSAM file consists of the first 255 bytes of the record: for the type (1 byte), for the IDL library (127 bytes) and for the IDL program (127 bytes).

If *one* server requires a server-side mapping file, you need to provide this to the RPC server:

- Development environments: to deploy new server-side mapping files, see [Deploying Server-side Mapping Files to the RPC Server](#).
- Production environments: provide a server-side mapping container (VSAM file) containing all required server-side mapping files to the RPC server. See configuration parameter `svm`.

If *no* server requires server-side mapping, you can execute the RPC server without server mapping files:

- Development environments: you can disable the deployment service. See [Disabling the Deployment Service](#).
- Production environments: there is no need to provide a server-side mapping container (VSAM file) to the RPC server. See configuration parameter `svm`.

Deploying Server-side Mapping Files to the RPC Server


The following approaches are available to deploy a server-side mapping file (EntireX Workbench file with extension .svm; see *Server Mapping Files for COBOL*):

- Server Mapping Deployment Wizard
- FTP and IDCAMS

➤ To deploy a server-side mapping file with the Server Mapping Deployment Wizard

- 1 Make sure your RPC server is active and that the Deployment Service of the RPC server is properly configured. See [Deployment Service](#).
- 2 From the context-menu of your IDL file, choose **COBOL > Deploy/Synchronize Server Mapping** and call the Server Mapping Deployment Wizard. See *Server Mapping Deployment Wizard* in the EntireX Workbench documentation.

➤ To deploy a server-side mapping file using FTP and IDCAMS



- 1 Make sure the server-side mapping container (VSAM file) is installed. See *Install the Server-side Mapping Container for a Batch RPC Server (Optional)* under *Installing the EntireX RPC Servers under z/OS*.
- 2 Allocate a target sequential file on your mainframe.
- 3 Allow write access to the VSAM file mentioned above and usage of IDCAMS tools.
- 4 Transfer the server-side mapping file to the target host, using FTP. You have to switch to text mode and the codepage of the FTP service must be the same as the codepage (locale string) of the RPC server used.
- 5 Install the server mapping contained in the server-side mapping file into the server-side mapping container (VSAM file) with an appropriate IDCAMS job.

```
//EXPSVMR JOB (,,,999),ENTIREX,NOTIFY=&SYSUID,MSGLEVEL=(1,1),
//          CLASS=K,MSGCLASS=X,REGION=0M,COND=(0,LT)
//*-----*
//* FILL THE SVM VSAM CLUSTER                               *
//*-----*
//IMPORT   EXEC PGM=IDCAMS
//RECORDS  DD DISP=SHR,DSN=EXP.SVM.TARGET.SEQ.RECORDS
//SVM      DD DISP=SHR,DSN=EXP.SVM.KSDS
//SYSPRINT DD SYSOUT=*
//SYSIN    DD *
    REPRO -
    REPLACE -
    INFILE(RECORDS) -
    OUTFILE(SVM)
```



Note: If you omit the keyword `REPLACE` or define `NOREPLACE` in the `SYSIN` data stream of IDCAMS instead, existing server mapping information is not overwritten. This protects server-side mapping records from being overwritten by duplicates.

Undeploying Server-side Mapping Files to the RPC Server

Use the Server Mapping Deployment Wizard to undeploy a server-side mapping file (Workbench file with extension `.svm`). See *Server Mapping Files for COBOL*.

» To undeploy a server-side mapping file with the Server Mapping Deployment Wizard

- 1 Make sure your RPC server is active and that the Deployment Service of the RPC server is properly configured. See [Deployment Service](#).
- 2 Make sure your IDL file is within an EntireX Workbench directory (folder) without the related server-side mapping file (`.svm`).
- 3 From the context-menu of your IDL file, choose **COBOL > Deploy/Synchronize Server Mapping** and call the Server Mapping Deployment Wizard. See *Server Mapping Deployment Wizard* in the EntireX Workbench documentation. Because there is no related server-side mapping file in the Workbench, all server mapping information related to the IDL file in the RPC server will be removed.

Change Management of Server-side Mapping Files

Under z/OS, change management for a VSAM file (server-side mapping container, see [Server-side Mapping Files in the RPC Server](#)) is similar to change management for a database. The complete VSAM file can be backed up at any time, for example by using IDCAMS. All updates to the VSAM file done after a backup must be kept.

All EntireX Workbench server-side mapping files (.svm) added since the last backup should be available. See *Server Mapping Files for COBOL* in the EntireX Workbench documentation.

List Deployed Server-side Mapping Files

Use IDCAMS to list the contents of the server-side mapping container. See [Server-side Mapping Files in the RPC Server](#).

```
//EXXPRINT JOB (,,,999),ENTIREX,NOTIFY=&SYSUID,MSGLEVEL=(1,1),
//              CLASS=K,MSGCLASS=X,REGION=0M
//*-----*
/* PRINT CONTENTS OF AN SVM VSAM CLUSTER                      *
/*-----*
//SVMPRINT EXEC PGM=IDCAMS
//SYSPRINT DD SYSOUT=*
//IN      DD DISP=SHR,DSN=ETS.SVM.KSDS
//OUT     DD SYSOUT=*
//SYSIN   DD *
PRINT -
  INFILE(IN) -
  DUMP | HEX | CHAR -
  OUTFILE(OUT)
/*
//
```

Use **DUMP** or **CHAR** format to print the server-side mapping records of the VSAM file.

Check if a Server-side Mapping File Revision has been Deployed

Server-side mapping records in the server-side mapping container correspond to lines of EntireX Workbench files with extension .svm. See *Server Mapping Files for COBOL* in the EntireX Workbench documentation. The records contain a creation timestamp at offset 276 (decimal) in the format *YYYYMMDDHHIISS*. Precision is 1/10 of a second. The creation timestamp can be checked.

The timestamp can be found on the same offset in the records in the server-side mapping container (VSAM file). See [Server-side Mapping Files in the RPC Server](#).

Access Control: Secure Server Mapping File Deployment

For deployment with the *Server Mapping Deployment Wizard*, use EntireX Security if the broker is running on platforms z/OS, UNIX, Windows or z/VSE. See [Enabling the Deployment Service](#).

For IBM deployment tool IDCAMS, use RACF to secure deployment.

Ensure that Deployed Server-side Mapping Files are not Overwritten

For IDCAMS, use the `NOREPLACE` option to disallow overwriting of duplicate server-side mapping records in the server-side mapping container (VSAM file); see [Server-side Mapping Files in the RPC Server](#). See also [Deploying Server-side Mapping Files to the RPC Server](#).

Is There a Way to Smoothly Introduce Server-side Mapping Files?

All EntireX RPC servers can be executed without server-side mapping files. See [Server-side Mapping Files in the RPC Server](#). There is no need to install the server-side mapping container if the following conditions are met:

- You do not use features that require server mapping; see *When is a Server Mapping File Required?*
- Server-side type of COBOL mapping is switched on in the EntireX Workbench. If you have not used server-side mapping, we recommend you use client-side mapping. See *Server Mapping Files for COBOL*.

You can also call COBOL servers generated or extracted with previous versions of EntireX mixed with a COBOL server that requires server-side mapping. All EntireX RPC servers are backward compatible.

6

Scenarios and Programmer Information

■ COBOL Scenarios	48
■ PL/I Scenarios	49
■ C Scenarios	50
■ Assembler Scenarios	50
■ Aborting RPC Server Customer Code and Returning Error to RPC Client	51

COBOL Scenarios

Scenario I: Calling an Existing COBOL Server

➤ To call an existing COBOL server

- 1 Use the *IDL Extractor for COBOL* to extract the Software AG IDL and, depending on the complexity, also a server mapping file. See *When is a Server Mapping File Required?* in the EntireX Workbench documentation.
- 2 Build an EntireX RPC client using any EntireX wrapper. For a quick test you can:
 - use the IDL Tester; see *EntireX IDL Tester* in the EntireX Workbench documentation
 - generate an XML mapping file (XMM) and use the XML Tester for verification; see *EntireX XML Tester* in the XML/SOAP Wrapper documentation

See *Client and Server Examples for z/OS Batch* in the COBOL Wrapper documentation for COBOL RPC Server examples.

Scenario II: Writing a New COBOL Server

➤ To write a new COBOL server

- 1 Use the *COBOL Wrapper* to generate a COBOL server skeleton and, depending on the complexity, also a server mapping file. See *When is a Server Mapping File Required?* in the EntireX Workbench documentation. Write your COBOL server and proceed as described under *Using the COBOL Wrapper for the Server Side*.
- 2 Build an EntireX RPC client using any EntireX wrapper. For a quick test you can:
 - use the IDL Tester; see *EntireX IDL Tester* in the EntireX Workbench documentation
 - generate an XML mapping file (XMM) and use the XML Tester for verification; see *EntireX XML Tester* in the XML/SOAP Wrapper documentation

See *Client and Server Examples for z/OS Batch* in the COBOL Wrapper documentation for COBOL RPC Server examples.

PL/I Scenarios

Scenario III: Calling an Existing PL/I Server

➤ To call an existing PL/I server

- 1 Use the *IDL Extractor for PL/I* to extract the Software AG IDL.
- 2 Build an EntireX RPC client using any EntireX wrapper. For a quick test you can:
 - use the IDL Tester; see *EntireX IDL Tester* in the EntireX Workbench documentation
 - generate an XML mapping file (XMM) and use the XML Tester for verification; see *EntireX XML Tester* in the XML/SOAP Wrapper documentation

See *Client and Server Examples for z/OS Batch* for PL/I RPC Server examples.

Scenario IV: Writing a New PL/I Server

➤ To write a new PL/I server

- 1 Use the *PL/I Wrapper* to generate a PL/I server skeleton. Write your PL/I server and proceed as described under *Using the PL/I Wrapper for the Server Side*.
- 2 Build an EntireX RPC client using any EntireX wrapper. For a quick test you can:
 - use the IDL Tester; see *EntireX IDL Tester* in the EntireX Workbench documentation
 - generate an XML mapping file (XMM) and use the XML Tester for verification; see *EntireX XML Tester* in the XML/SOAP Wrapper documentation

See *Client and Server Examples for z/OS Batch* in the PL/I Wrapper documentation for PL/I RPC Server examples.

C Scenarios

Scenario V: Writing a New C Server

➤ To write a new C server

- 1 Use the *C Wrapper* to generate a C server skeleton and a C server interface object. Write your C server and proceed as described under *Using the C Wrapper for the Server Side (z/OS, UNIX, Windows, BS2000/OSD, IBM i)*.
- 2 Build an EntireX RPC client using any EntireX wrapper. For a quick test you can:
 - use the IDL Tester; see *EntireX IDL Tester* in the EntireX Workbench documentation
 - generate an XML mapping file (XMM) and use the XML Tester for verification; see *EntireX XML Tester* in the XML/SOAP Wrapper documentation

Assembler Scenarios

Scenario VI: Writing a New Assembler Server

➤ To write a new Assembler (IBM 370) server

- 1 Build an RPC server in Assembler. Here are some hints:
 - The RPC server is dynamically callable (no pre-initialization required).
 - The parameter interface is either compatible with the COBOL or PL/I calling convention (IDL level parameter will be passed in the address list). Configure the parameter [marshalling](#) accordingly for COBOL or PL/I.
 - The alignment of integer or float data types is considered. The HASM Assembler aligns integer or float data types to appropriate boundaries. For example:

```
...
MyLabel    DSECT
MyField1   DS    H                I2
MyField2   DS    F                I4
MyField3   DS    E                F4
MyField4   DS    L                F8
```

- The Batch RPC Server will not align these data types by default.

- To force alignment by definition in your IDL file (see the aligned attribute within the `attribute-list`) before generating your RPC client. For information on whether your client supports the aligned attribute, see *Mapping the aligned Attribute* in the respective Wrapper documentation.
- 2 Build an EntireX RPC client using any EntireX wrapper. For a quick test you can:
 - use the IDL Tester; see *EntireX IDL Tester* in the EntireX Workbench documentation
 - generate an XML mapping file (XMM) and use the XML Tester for verification; see *EntireX XML Tester* in the XML/SOAP Wrapper documentation

Aborting RPC Server Customer Code and Returning Error to RPC Client

Using RETURN-CODE Special Register (COBOL only)

The `RETURN-CODE` special register (an IBM extension to the COBOL programming language) is used by your RPC server to report an error.

Upon return, the value contained in the `RETURN-CODE` special register is detected by the Batch RPC Server and sent back to the RPC client instead of the application's data.

For IBM compilers the `RETURN-CODE` special register has the implicit definition:

```
RETURN-CODE GLOBAL PICTURE S9(4) USAGE BINARY VALUE ZERO
```

Special registers are reserved words that name storage areas generated by the compiler. Their primary use is to store information produced through specific COBOL features. Each such storage area has a fixed name, and must not be defined within the program. See your compiler documentation for more information.

The following rules apply to application error codes:

- The value range for application errors is 1-9999. No other values are allowed.
- On the RPC client side, the error is prefixed with the error class 1002 "Application User Error" and presented as error 1002nnnn.
- No application data is sent back to the RPC client in case of an error.
- It is not possible to return an error text to the RPC client.

Example

```
. . .  
    IF error occurred THEN  
        MOVE <error-number> TO RETURN-CODE  
        GO TO MAIN-EXIT  
    END-IF.  
    . . .  
  
    MAIN-EXIT.  
    EXIT PROGRAM.  
END PROGRAM RETCODE.
```



Note: To enable this feature, configure the Batch RPC Server with `return_code=yes`.