

# webMethods Universal Messaging 9.9 Readme

## October 2015

This file contains important information you must read before using webMethods Universal Messaging 9.9. You can find user documentation on the [Documentation website](#) or the [TECHcommunity website](#). At those locations, you can also find the suite-related information listed below.

*webMethods Product Suite Release Notes*

*webMethods and Intelligent Business Operations System Requirements*

*webMethods System Cache Specifications*

*Using the Software AG Installer*

*Installing webMethods and Intelligent Business Operations Products*

*Using the Software AG Update Manager (fixes)*

*Upgrading webMethods and Intelligent Business Operations Products*

*Security and globalization information*

<b>1.0</b>	<b>Critical Information.....</b>	<b>2</b>
<b>2.0</b>	<b>Known Issues.....</b>	<b>2</b>
<b>3.0</b>	<b>Usage Notes.....</b>	<b>2</b>
<b>4.0</b>	<b>Fixes Included in Each Release.....</b>	<b>3</b>
<b>5.0</b>	<b>Other Resolved Issues.....</b>	<b>5</b>
<b>6.0</b>	<b>Documentation Changes .....</b>	<b>6</b>
<b>7.0</b>	<b>Terminology Changes .....</b>	<b>6</b>
<b>8.0</b>	<b>Added, Removed, Deprecated, or Changed Items.....</b>	<b>7</b>
<b>9.0</b>	<b>Added, Removed, Deprecated, or Changed APIs .....</b>	<b>12</b>
<b>10.0</b>	<b>Copyright Information.....</b>	<b>14</b>
<b>11.0</b>	<b>Support.....</b>	<b>15</b>

## 1.0 Critical Information

This section lists any critical issues for the current release that were known when this readme was published. For critical information found later, go to the Knowledge Center on the [Empower website](#).

## 2.0 Known Issues

This section lists any issues for the current release that were known when this readme was published. For known issues found later, go to the Knowledge Center on the [Empower website](#).

- Shared memory drivers are currently not supported on HP-UX systems  
On HP-UX systems, shared memory drivers are currently not supported.  
There is currently no workaround for this issue.
- NUM-2211  
Paged Store type is unsupported in Solaris / SPARC with JDK 1.8.  
Currently, the Paged Storage feature is not supported in a Solaris/SPARC environment with JDK 1.8.  
Workaround: Consider using JDK 1.7 instead.
- PIF-12248  
Cannot deploy JNDI assets from a source Universal Messaging server to a target Universal Messaging server using webMethods Deployer.  
To resolve this issue, install the latest Universal Messaging fixes.

## 3.0 Usage Notes

This section provides any additional information you need to work with the current release of this product.

## 4.0 Fixes Included in Each Release

This section lists the latest fix level that has been included in each release for each product component. A release is listed in this section only if changes occurred in that release. Go to the Knowledge Center on the [Empower website](#) for detailed information about fixes.

### **Release 9.9**

- NUM\_9.8\_Client\_Fix3
- NUM\_9.8\_RealmServer\_Fix3
- NUM\_9.8\_EnterpriseManager\_Fix3
- NUM\_9.8\_TemplateApplications\_Fix2
- NUM\_9.8\_PlatformManagerPlugins\_Fix2

### **Release 9.8**

- NUM\_9.7\_Client\_Fix7
- NUM\_9.7\_RealmServer\_Fix7
- NUM\_9.7\_EnterpriseManager\_Fix7
- NUM\_9.7\_TemplateApplications\_Fix3

### **Release 9.7**

- NUM\_9.6\_Client\_Fix11
- NUM\_9.6\_RealmServer\_Fix11
- NUM\_9.6\_EnterpriseManager\_Fix9
- NUM\_9.6\_TemplateApplications\_Fix10

### **Release 9.6**

- NUM\_9.5.2\_Client\_Fix11
- NUM\_9.5.2\_RealmServer\_Fix11
- NUM\_9.5.2\_EnterpriseManager\_Fix11
- NUM\_9.5.2\_TemplateApplications\_Fix10

## Release 9.5 SP2

- NUM\_9.0.1\_Client\_Fix10
- NUM\_9.0.1\_RealmServer\_Fix11
- NUM\_9.0.1\_EnterpriseManager\_Fix11

### Enhancements:

- **Off Heap Stores**

Universal Messaging 9.5 SP2 introduces a new store type for channels and queues – Off Heap. Off Heap Store is a new Topic or Queue store mechanism that uses memory which is not within the Java Heap space, but rather, is allocated directly from the host's memory.

Any memory allocated within the JVM is subject to Garbage Collection inspection. This inspection allows the JVM to release unused memory and move memory that has been used for a while into different memory partitions. It also adds a level of jitter to the JVM, as it needs to pause while it does this inspection and potential move. The use of Off Heap memory stops the Garbage Collection from inspecting and moving these regions since they are outside of the JVM's memory domain. This has the effect of reducing such jitter within the Universal Messaging Server.

Since the events are stored in memory, you still get fast memory access, with no impact from GC within the Server. This is extremely useful when using stores that can potentially contain data that will exist for a prolonged period of time, since pauses that might otherwise be caused by GC inspections will not occur.

By default, the server will be allowed to use a maximum of 1GB of memory for off heap store use (in addition to the current default of 1GB maximum available to the Java heap). However, these amounts are not pre-located. Typically, a system will start off consuming approximately 128-256MB of RAM, and will consume more memory only if it needs to.
- **RDMA**

Remote Direct Memory Access is direct access from the memory of one computer into that of another without involving either one's operating system. This permits high-throughput low-latency communication, which is especially useful in massively parallel computer clusters.

With Shared Memory drivers built into Universal Messaging and supported in C#, C++ and Java we can achieve very fast, high throughput messaging on the same machine. With conventional networking standards like TCP/IP, all messages are pushed through the kernel's network stack and back again. There are some off-loaded drivers allowing application code direct access to the Network card, but these still require a layer of TCP above to interpret and manage. RDMA removes this restriction and allows an area of application memory to be mapped and then written to from a remote computer with no Operating System involvement at all; instead, the Interface card and driver alone marshal the incoming event and put the data directly in the application's memory. This results in performance close to that of same-machine Shared Memory, but between 2 separate computers.
- **Changes to Default Configurations**

The default value for *Config / Event Storage / CacheAge* has been reduced from 1 day to 1 minute.

The default value for: *Config / Global Values / DisableExplicitGC* has been changed from *true* to *false*.

A new configuration parameter: *Config / Fanout Values / DelayPublishOnCapacity* has been added, with a default value of *true*. It causes the publisher to be throttled once any optionally set capacities are reached on a channel or queue.

The default heap size has been changed from 512MB to 1GB.

## 5.0 Other Resolved Issues

This section lists the issues that were resolved in each release but were not part of the fixes listed in the previous section. A release is listed in this section only if changes occurred in that release.

### **Release 9.9**

- NUM-2769  
UM / JMS Temp Queue / Topics must be destroyed on disconnect  
Temporary queues are a JMS feature. When a client is closed, the temporary queues should be deleted. In some cases, for example if a client connection dropped due to a network problem, this was not happening correctly. Now the temporary queues will always be deleted correctly.  
The issue is resolved.

### **Release 9.8**

- NUM-2614  
Universal Messaging Client with semicolon-separated RNAME list always connects to the first entry when there are two nodes in the list.  
The issue is resolved.
- NUM-2427  
Join information not working correctly with .net admin API.  
nChannel.getJoinInformation is returning blank results instead of the correct list of joins fetched from the server.  
The issue is resolved.

### **Release 9.7**

- NUM-1396  
UM does not provide transparent failover in cluster  
Example: there is a cluster with two nodes (two sites, second site with isPrime=true). If we switch the node which is not in the isPrime-site off, we would expect a transparent failover. Instead we see the following behavior in a standalone Java client and in a Message-Driven Bean running in JBoss 4.2.3 (using the UM 9.5 client libs): Standalone client: for about 10 seconds sends fail with a "nSessionNotConnectedException". If these are caught and the sends are retried, the client can recover. JBoss MDB: stops receiving messages and never does a failover. Even if the node is brought up again, the MDB does not recover.  
This issue is now resolved. The value of the nirvana.conxExceptionOnRetryFailure property of a JMS connection factory determines whether the Universal Messaging cluster fails over

transparently when the prime site fails or throws an exception to the JMS client. For transparent cluster failover, set this property to true. By default, the value of the `nirvana.conxExceptionOnRetryFailure` property is false.

## 6.0 Documentation Changes

This section describes significant changes to the documentation, such as the addition, relocation, or removal of product guides, online help, chapters, or other major content. A release is listed in this section only if changes occurred in that release.

### ***Release 9.7***

The documentation is provided in a new format, with a navigation frame and content frame. The navigation presents the documentation under the following main categories:

- Concepts
- Administration
- Developer's Guide
- Reference Guide
- Installation Guide

The API documentation is available as a topic in the Reference Guide. The code examples for each of the supported languages are available within the appropriate language-specific part of the Developer's Guide.

## 7.0 Terminology Changes

A release is listed in this section only if changes occurred in that release.

### ***Release 9.7***

Old Term	New Term
Brokerless API	umTransport API

## 8.0 Added, Removed, Deprecated, or Changed Items

This section lists features, functionality, controls, portlets, properties, or other items that have been added, removed, deprecated, or changed. A release is listed in this section only if changes occurred in that release.

### **Release 9.9**

Added Item	Description
AMQP 1.0 Support	<p data-bbox="810 506 1471 892">Universal Messaging 9.9 introduces support for AMQP 1.0. AMQP is an open standard binary application layer protocol whose main topics of concern are orientation, queuing, routing (both point-to-point and publish-and-subscribe), reliability and security. It defines a number of mechanisms such as flow control, message-delivery guarantee strategies (at-most-once, at-least-once and exactly-once), authentication based on SASL or TLS, etc.</p> <p data-bbox="810 919 1471 1150">The Universal Messaging AMQP implementation provides support for a subset of the components of the protocol specification (for more information on AMQP, please refer to <a href="http://www.amqp.org/">http://www.amqp.org/</a>). Here is the complete list of features that we support:</p> <ul data-bbox="810 1171 1471 1728" style="list-style-type: none"><li data-bbox="810 1171 1292 1201">•AMQP PLAIN &amp; AMQP over SASL</li><li data-bbox="810 1228 1256 1262">•Publishing to Topics and Queues</li><li data-bbox="810 1289 1081 1323">•Temporary Queues</li><li data-bbox="810 1350 987 1383">•Keep Alive</li><li data-bbox="810 1411 1446 1478">•Synchronous and Asynchronous consuming on topics and queues</li><li data-bbox="810 1505 995 1539">•Flow control</li><li data-bbox="810 1566 1089 1600">•Durable subscribers</li><li data-bbox="810 1627 1458 1728">•Interoperability with existing AMQP JMS clients (SwiftMQ, Apache QPID and Apache Legacy QPID)</li></ul>

Added Item	Description
New ordering policy for rolled back messages on queues	When a transactional queue consumer rolls back a message, it needs to be put back onto the queue. Prior to 9.9 this message would be simply republished to the end of the queue. In 9.9 we have changed the default behavior so that the message is re-added to the front of the queue.
Per-session SSL settings	It is now possible to specify custom SSL settings per nSession rather than per JVM, e.g. key store, trust store.
JMS resource adapter support	As part of the install we now ship a resource adapter for JMS. Users with existing JMS applications that run on an application server such as JBoss can now seamlessly switch to Universal Messaging as a JMS provider.
Support for dynamically updating Google Protocol Buffer schema	Universal Messaging allows you to attach a Google Protocol Buffer schema to a channel/queue but until 9.9, changing the schema would require deleting and recreating the channel. A channel edit that only changes the schema is now supported without recreating the channel.
Usability improvements for shared named objects	It is now possible to monitor the number of messages outstanding for a shared named object. Due to the architecture of shared named objects it was not previously clear how many events were being stored waiting to be consumed. This information is now available in the API and also visible in the Enterprise Manager.
Enterprise Manager JNDI panel improvements	The JNDI panel has been reworked to make it more user friendly. It now automatically shows the contents for the server you are connected to and does not require entry of a server URL. It is also clearer how to enable shared durables on creation of a connection factory.

## **Release 9.8**

<b>Added Item</b>	<b>Description</b>
WAN interest propagation (Realm Zones)	Zones provide a logical grouping of one or more Realms which maintain active connections to each other. Using zones, Universal Messaging can deliver messages between realms and clusters when interest from one realm or cluster has been registered on another realm or cluster in the same zone. Interest between zones is propagated by manually creating static joins.
MQTT 3.1.1 Support	Support for the standardized MQTT protocol version 3.1.1 has been added in addition to the legacy 3.1 version. Additional features now include automatic topic creation, authentication support as well as retained messages and session persistence.
JNDI assets: Connection Factories, Topic Connection Factories, Queue Connection Factories, XA Connection Factories, JNDI Topics, JNDI Queues.	JNDI assets from a source Universal Messaging server can be deployed to a target Universal Messaging server using webMethods Deployer.

<b>Removed Item</b>	<b>Replacement, if any</b>
MQTT Virtual Payload types	Virtual payload type support has now been removed for reasons of compliance to the specification. All MQTT messages are now being handled as JMS bytes messages.

## **Release 9.7**

<b>Added Item</b>	<b>Description</b>
Interest Propagation	Interest Propagation expands upon the functionality provided by joins to provide the ability to forward information only when there are subscribers present on the remote realm or cluster. By forwarding only events which have an active subscription present reduces the number of events and bandwidth used on these links.

Added Item	Description
umTransport API (formerly Brokerless API) support for C++	The umTransport API was already available for Java, and now this API is available for C++ also, with some restrictions in functionality compared to the Java-based API.

## **Release 9.6**

Added Item	Description
Java Transport API	To provide a broker-less style of messaging, Universal Messaging now contains a new API, <code>com.softwareag.um.io</code> , which exposes the underlying communication drivers used within the UM client and server, and enables direct synchronous and asynchronous communication between client applications using TCP/SSL sockets, SHM (shared memory), or RDMA protocols.
SASL Support	Universal Messaging now provides new security authentication features offering password authentication (Plain and Cram-MD5) via SASL. The UM server now accepts username and password credentials from the client, and enables administrators to lock down servers in accordance with specific pluggable providers configured on the UM server. These pluggable directory providers include User File (similar to <code>.htaccess</code> files) and LDAP.
MQTT Virtual Payload Types	Universal Messaging now provides MQTT users with the ability to define namespace roots where advanced namespace semantics can be applied. Specifically, the last part of the full topic namespace address can be used to publish / subscribe, indicating your preferred virtual payload type.

## **Release 9.5 SP1**

Added Item	Description
------------	-------------

**Added Item**

Multicast for Channel/Topic Delivery

**Description**

Channels/topics now support delivery of events via multicast. Previously, multicast support was limited to Data Group and inter-cluster communication. As multicast is a broadcast mechanism, the consumers can receive events through Multicast only when they do not use selectors in their subscriptions to channels.

Individual Message Acknowledgement

With both topic and queue delivery in JMS, the acknowledge model means that if you consume messages 1 through 10, but acknowledge message 5 only, then messages 1 to 4 are also automatically acknowledged. While this is fine in most cases, there is sometimes the requirement for applications to distribute the consumed messages across different threads or other components, which makes this model a difficult fit.

We have therefore provided support for acknowledging individual messages, which ensures that only the specified message will be acknowledged.

***Release 9.5 SP2*****Added Item**

Multicast for Channel/Topic Delivery

**Description**

Channels/topics now support delivery of events via multicast. Previously, multicast support was limited to Data Group and inter-cluster communication. As multicast is a broadcast mechanism, the consumers can receive events through Multicast only when they do not use selectors in their subscriptions to channels.

## Added Item

Individual Message Acknowledgement

## Description

With both topic and queue delivery in JMS, the acknowledge model means that if you consume messages 1 through 10, but acknowledge message 5 only, then messages 1 to 4 are also automatically acknowledged. While this is fine in most cases, there is sometimes the requirement for applications to distribute the consumed messages across different threads or other components, which makes this model a difficult fit.

We have therefore provided support for acknowledging individual messages, which ensures that only the specified message will be acknowledged.

## 9.0 Added, Removed, Deprecated, or Changed APIs

A release is listed in this section only if changes occurred in that release.

### ***Release 9.9***

#### Added API

Storage API

#### Description

The Universal Messaging server has a highly optimized I/O subsystem for efficient serialization of data to and from disk. The umStorage API (Java only) abstracts this layer from the server so it can be used directly by applications. This simple API allows the user to construct any of the standard Universal Messaging storage types (Mixed, Off Heap, Reliable etc.) and easily serialize/deserialize data.

## Release 9.8

### Added API

com.pcbsys.nirvana.nAdminAPI.nRealmNode

- public Zone createZone(String zoneName)
- public void joinZone(Zone zone)
- public void leaveZone(Zone zone)
- public Zone getZone()

### Description

Provides Zone management functionality through the Universal Messaging Administration API, allowing users to create a zone, join a realm to a zone, remove a realm from a zone, and obtain realm zone information.

## Release 9.6

### Added API

com.softwareag.um.io

### Description

Provides direct, broker-less synchronous and asynchronous communication between client applications, using Universal Messaging TCP/SSL sockets, SHM (shared memory), or RDMA protocols.

## Release 9.5 SP1

### Added API

**nConsumeEvent** class has new method:

*ack(boolean isSynchronous, boolean ackPrevious)*

Sends an ack for a specific event to the server.

**nConsumeEvent** class has new method:

*rollback(boolean isSynchronous)*

Sends a rollback for this event to the server.

**nQueueTransactionReader** class has new method:

*commit(long eventId)*

Commits all events up to the event ID specified. This means you can partially commit received events.

**nQueueTransactionReader** class has new method:

*rollback(long eventId, boolean isIndividual)*

If *isIndividual* is true, then just the event with the specified event ID is rolled back. This event is then pushed back onto the queue for redelivery. If *isIndividual* is false, then all events consumed after the specified event ID are rolled back.

**nStoreProperties** class has new method:

*enableMulticast(boolean flag)*

If *flag* is true, then the channel/topic will be multicast-enabled. If false, it won't (default).

## Release 9.5 SP2

Added API	Description
<b>nConsumeEvent</b> class has new method: <i>ack(boolean isSynchronous, boolean ackPrevious)</i>	Sends an ack for a specific event to the server.
<b>nConsumeEvent</b> class has new method: <i>rollback(boolean isSynchronous)</i>	Sends a rollback for this event to the server.
<b>nQueueTransactionReader</b> class has new method: <i>commit(long eventId)</i>	Commits all events up to the event ID specified. This means you can partially commit received events.
<b>nQueueTransactionReader</b> class has new method: <i>rollback(long eventId, boolean isIndividual)</i>	If <i>isIndividual</i> is true, then just the event with the specified event ID is rolled back. This event is then pushed back onto the queue for redelivery. If <i>isIndividual</i> is false, then all events consumed after the specified event ID are rolled back.
<b>nStoreProperties</b> class has new method: <i>enableMulticast(boolean flag)</i>	If <i>flag</i> is true, then the channel/topic will be multicast-enabled. If false, it won't (default).

## 10.0 Copyright Information

Copyright © 2015 Software AG, Darmstadt, Germany and/or Software AG USA Inc., Reston, VA, USA, and/or its subsidiaries and/or its affiliates and/or their licensors.

The name Software AG and all Software AG product names are either trademarks or registered trademarks of Software AG and/or Software AG USA Inc. and/or its subsidiaries and/or its affiliates and/or their licensors. Other company and product names mentioned herein may be trademarks of their respective owners.

Detailed information on trademarks and patents owned by Software AG and/or its subsidiaries is located at <http://softwareag.com/licenses>.

This software may include portions of third-party products. For third-party copyright notices, license terms, additional rights or restrictions, please refer to "License Texts, Copyright Notices and Disclaimers of Third Party Products". For certain specific third-party license restrictions, please refer to section E of the Legal Notices available under "License Terms and Conditions for Use of Software AG Products / Copyright and Trademark Notices of Software AG Products". These documents are part of the product documentation, located at <http://softwareag.com/licenses> and/or in the root installation directory of the licensed product(s).

## 11.0 Support

Visit the [Empower website](#) to learn about support policies and critical alerts, read technical articles and papers, download products and fixes, submit feature/enhancement requests, and more.

Visit the [TECHcommunity website](#) to access additional articles, demos, and tutorials, technical information, samples, useful resources, online discussion forums, and more.

UM-RM-99-20151015